



US006631778B2

(12) **United States Patent**  
**Mallette**

(10) **Patent No.:** **US 6,631,778 B2**  
(45) **Date of Patent:** **Oct. 14, 2003**

(54) **SHOCK LINKAGE ASSEMBLY FOR A SNOWMOBILE SUSPENSION SYSTEM**

(75) Inventor: **Bertrand Mallette, Rock-Forest (CA)**

(73) Assignee: **Bombardier Inc., Valcourt (CA)**

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 60 days.

5,860,486 A	*	1/1999	Boivin et al. ....	180/193
5,904,216 A	*	5/1999	Furusawa .....	180/193
5,947,217 A	*	9/1999	Snare et al. ....	180/9.56
6,234,264 B1	*	5/2001	Boivin et al. ....	180/193
6,237,706 B1	*	5/2001	Karpik et al. ....	180/9.52
6,253,867 B1	*	7/2001	Lillbacka .....	180/193
6,263,991 B1	*	7/2001	Savage et al. ....	180/190
6,283,241 B1	*	9/2001	Kubota .....	180/193
6,302,232 B1	*	10/2001	Forbes .....	180/193

\* cited by examiner

(21) Appl. No.: **09/778,801**

(22) Filed: **Feb. 8, 2001**

(65) **Prior Publication Data**

US 2001/0023787 A1 Sep. 27, 2001

**Related U.S. Application Data**

(60) Provisional application No. 60/181,231, filed on Feb. 9, 2000.

(51) **Int. Cl.<sup>7</sup>** ..... **B62M 27/02**

(52) **U.S. Cl.** ..... **180/193; 180/9.25; 180/9.28; 180/182; 180/186**

(58) **Field of Search** ..... **180/9.25, 9.28, 180/182, 184, 186, 190, 193**

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,265,692 A	11/1993	Mallette .....	180/193
5,664,649 A	9/1997	Thompson et al. ....	188/314
5,692,579 A	12/1997	Peppel et al. ....	180/190
5,727,643 A	* 3/1998	Kawano et al. ....	180/193
5,791,429 A	* 8/1998	Bergman .....	180/193

*Primary Examiner*—Lesley D. Morris


*Assistant Examiner*—L. Lum

(74) *Attorney, Agent, or Firm*—Pillsbury Winthrop LLP

(57) **ABSTRACT**

The present invention provides a snowmobile suspension system comprising a slide frame for engagement with an endless track, a suspension arm, a bracket arm, and a rocker arm. The suspension arm has an upper portion adapted to be pivotally mounted relative to a chassis on a snowmobile and a lower portion adapted to be pivotally mounted relative to the slide frame. The bracket arm has an end fixedly connected to the lower portion of the suspension arm. The rocker arm has an upper end pivotally connected to the other end of the bracket arm and a lower end supporting a lower end of a shock absorber, the lower end of said shock absorber being pivotally attached thereto. The upper end of the shock absorber is pivotally interconnected to the chassis. The rocker arm is constructed and arranged such that a lower end thereof is disposed beneath the lower portion of the suspension arm.

**16 Claims, 5 Drawing Sheets**







FIG. 2

**FIG. 1**  
**PRIOR ART**



**FIG. 2**  
**PRIOR ART**




FIG. 3




FIG. 4




FIG. 5

1

## SHOCK LINKAGE ASSEMBLY FOR A SNOWMOBILE SUSPENSION SYSTEM

The present application claims priority to U.S. Provisional Application of Mallette, filed Feb. 9, 2000, Ser. No. 60/181,231, the entirety of which is hereby incorporated into the present application by reference.

### FIELD OF THE INVENTION

This invention relates to a rear shock linkage system for a suspension system of a snowmobile.

### BACKGROUND OF THE INVENTION

Tracked vehicles such as snowmobiles have rear suspensions generally consisting of front and rear suspension arms pivotally mounted on shafts, which are rotatably connected to a slide frame. The slide frame comprises a pair of laterally spaced apart slide rails or longitudinal skids interconnected transversely on opposing lateral sides of the snowmobile. The slide rails are in sliding contact with an endless track which contacts the snow surface and drives the snowmobile. The front and rear suspension arms pivotally interconnect the chassis of the snowmobile to the slide frame.

In many current arrangements, front and rear suspension arms pivotally interconnect the chassis to the slide frame. In one typical arrangement, the rear suspension system includes a pair of shock absorbers pivotally interconnected to the chassis, extending downward to a transverse tube that is pivotally mounted relative to the slide frame by connecting parts. Also, to attach the rear shock absorber to the transverse tube, the conventional approach is to pivotally mount the shock absorber to a bracket arm that, in turn, is fixedly attached to the transverse tube. Such a system is shown in U.S. Pat. No. 5,664,649 to Thompson et al., with the above-mentioned bracket arm designated as element 90.

In the above arrangement, it is preferable to make the bracket arm as short as possible so that the shock absorber is attached at the lowest possible point to thereby provide greater suspension travel within the confines defined by the endless track. However, a short bracket arm length creates the possibility that the shock absorber will become jammed with other suspension components and/or belt during large angular displacements of the pivoting shaft, and, correspondingly, the bracket arm. Therefore, a short bracket arm length limits flexibility in the design of the suspension linkage system.

One way to alleviate the concerns over the restriction on the design options and also provide for sufficient shock absorber travel is to attach the shock absorber to an end of an additional component that permits a higher or lower pivoting point for the additional component. Such a prior art system is shown in FIG. 1. Here, shock absorber 1 is attached to a rocker arm 2, which is pivotally attached via a bolt 3 to an additional component designated as plate bracket 4. Plate bracket 4 is in turn fixed to transverse tube 5, which is fixed to the slide frame. Thus, rocker arm 2 pivots about plate bracket 4 via bolt 3. Because of the large forces experienced by the system, plate bracket 4 and rocker arm 2 require additional support. To provide such support, plate bracket 4 includes a C-shaped portion 6, which is more clearly shown in the exploded view in FIG. 2. This C-shaped portion 6 is in sliding contact with transverse portion 8 of front suspension arm 7. Thus, plate bracket 4 is supported at both ends for additional strength. As can be seen from FIG. 1, shock absorber 1 is thus attached to a low position that allows for sufficient suspension travel. Because rocker arm 2 is long and can pivot freely about pivot 3, the concerns about the restrictions in the suspension linkage system are reduced.

2

However, the prior art apparatus shown in FIG. 1 has three problems. First, the added components of the plate bracket 4 and support tube 5 add weight. Second, the forces involved combined with the friction between the C-shaped portion 6 and transverse portion 8 create significant wear of both the transverse portion 8 and the C-shaped portion 6. Third, because of the forces between the C-shaped portion 6 and the transverse portion 8, "stiction" occurs between the two components, preventing free movement of the front suspension arm and thereby reducing the overall performance of the suspension system.

### SUMMARY OF THE INVENTION

It is an object of the present invention, therefore, to overcome the problems associated with the prior art noted above. In achieving this object, the present invention provides a snowmobile suspension system comprising a slide frame for engagement an endless track, a suspension arm, a bracket arm, and a rocker arm. The suspension arm has an upper portion adapted to be pivotally mounted relative to a chassis on a snowmobile and a lower portion adapted to be pivotally mounted relative to the slide frame. The bracket arm has an end fixedly connected to the lower portion of said suspension arm. The rocker arm has an upper end pivotally connected to the other end of the bracket arm and a lower end supporting a lower end of a shock absorber, the lower end of the shock absorber being pivotally attached thereto. The upper end of the shock absorber is pivotally interconnected to the chassis.

### BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is further described in the detailed description which follows, by reference to the noted drawings by way of non-limiting exemplary embodiments, in which like reference numerals represent similar parts throughout the several views of the drawings, and wherein:

FIG. 1 shows a prior art suspension system which utilizes a rocker arm, a plate bracket, and a C-shaped support portion for additional support;

FIG. 2 illustrates an expanded view of a portion of the prior art system shown in FIG. 1;

FIG. 3 shows an overall view of a snowmobile with its major components, including the preferred embodiment of the snowmobile suspension system of the present invention;

FIG. 4 shows a perspective view of the preferred embodiment of the snowmobile suspension system of the present invention; and

FIG. 5 shows a two dimensional view of FIG. 4.

### DETAILED DESCRIPTION

While the present invention will hereinafter be described in connection with at least one exemplary embodiment thereof, it should be understood that it is not intended to limit the invention to that embodiment. On the contrary, it is intended to cover all alternatives, modifications and equivalents as may be included within the spirit and scope of the invention as defined by the appended claims.

Referring to FIG. 3, a snowmobile 10 is generally shown having a forward end 13 and a rearward end 15 (that are defined consistently with the travel direction of the vehicle). Snowmobile 10 includes a body 17 (i.e., the exterior upper portions) and a chassis 12. While not shown in FIG. 3, an engine is carried by chassis 12 at its forward end. In addition, two skis 11 are attached to the forward end of chassis 12 through a front suspension 19. An endless, drive track 16 of the rear suspension 18 is disposed under chassis 12 and is connected operatively to the engine for propulsion of the vehicle. As is shown more clearly in FIG. 4, rear track

support wheels **24** are supported on the slide rails **28** of a slide frame **20** by an axle shaft **32**.

At the front of chassis **12**, snowmobile **10** includes fairings **25** that enclose the engine to protect it and to provide a external shell that can be decorated so that the snowmobile is aesthetically pleasing. Typically fairings **25** comprise a hood and a bottom pad (neither of which have been individually identified in the Figures). A windshield **26** may be connected to fairings **25** near the forward end **13** of snowmobile **10**. Windshield **26** acts as a windscreen to lessen the force of the air on a rider when snowmobile **10** is moving.

A seat **14** extends from rearward end **15** of snowmobile **10** to the fairings **25**. A steering device **27**, such as a handlebar, is positioned forward of the rider and behind the engine. Two footrests (not shown) are positioned on either side of seat **14** to accommodate the rider's feet.

Referring to FIGS. 4 and 5, the rear suspension system of the snowmobile **10** comprises a slide frame **20** that is connected to the chassis **12** through the front and rear suspension assemblies generally indicated as **29** and **49**, respectively. Each of the front and rear suspension assemblies **29**, **49** comprises, among other things, front and rear suspension arms **30** and **50**, respectively, and front and rear shock absorbers **60** and **70**, respectively. In the embodiment shown in FIG. 4, the rear shock absorber **70** is preferably of the piston-damper type, while the front shock absorber **60** of the coil-over piston-damper type. The slide frame **20** comprises two longitudinally extending transversely spaced apart slide rails **28** that are transversely interconnected by suitable cross structures to form a generally rigid structure. The lower surfaces of the slide rails **28** are coated in a known manner with a suitable low friction material such as nylon, Teflon®, and preferably UHMW (ultra high molecular weight polyethylene), for sliding contact with the drive track **16**.

As shown in FIG. 4, front and rear suspension arms **30** and **50**, respectively, interconnect the slide rails **28** with the chassis **12**. The front suspension arm **30** is a trapezoidally-shaped structure that includes an upper tube portion **34** and a lower tube portion **38** that are connected by two tubes **30a** and **30b**. In the preferred embodiment, the components are all welded together to form an integral structure. The upper portion **34** of front suspension arm **30** is pivotally mounted on a first transverse shaft (not shown) that is fixedly attached to the chassis **12** by means of bolts **34a**. Likewise, the lower tube portion **38** of front suspension arm **30** is pivotally mounted on a second transverse shaft (not shown) that is fixedly attached to the respective slide rails **28**. Therefore, as the slide frame **20** displaces vertically, front suspension arm **30** is able to pivot about the first transverse shaft relative to the chassis **12** and simultaneously pivot about the second transverse shaft relative to the slide frame **20**.

A front shock absorber **60** extends from the upper tube portion **34** of the front suspension arm **30** downwardly and rearwardly to fixedly connect to a lower transverse shaft **22**, which is fixedly attached to slide rails **28** by bolts **60b**, as shown in FIG. 5. The front shock absorber **60** is pivotally attached to a bracket arm **42** of the upper tube portion **34** by a bolt **60a**. Bracket arm **42** is in turn fixedly attached to the upper tube portion **34** of front suspension arm **30**.

The rear suspension assembly **49** comprises, among other things, a rear suspension arm **50**, a rear shock absorber **70**, and a location rod **90**. The rear suspension arm **50** comprises a transverse rear upper tube that is pivotally mounted on a third transverse shaft (not shown), which is connected to the chassis **12** in known manner by a bolt **54**, as shown in FIG. 4. Rear suspension arm **50** is a rectangularly-shaped structure that includes a transverse rear upper tube **52** and a transverse rear lower tube **56** that are connected at interme-

diated locations thereon by a metal plate **51**. Although shown being connected by a metal plate **51**, the transverse rear upper and lower tubes **52** and **56** can also be connected with at least one bar or tube, in which case the components of the rear suspension arm **50** would all be welded together to form a single unit.

The rear suspension arm **50** extends from the upper tube **52** downwardly and rearwardly to the lower tube **56**. The transverse rear lower tube **56** is connected to a lower arm **55** which is in turn pivotally connected to the slide frame **20**. The axial ends of the rear lower tube **56** have blocks **59a** and **59b** which are movable within the block stoppers **57a** and **57b** located on each slide rail **28**.

A rear shock absorber **70** extends from the transverse rear upper tube downwardly and forwardly to pivotally attach to a rocker arm **80**, which will be discussed below. The other end of the rear shock absorber **70** is pivotally interconnected to the chassis **12**. That is, the upper end of rear shock absorber **70** is pivotally attached by a bolt **70a** to a bracket arm **40**, which in turn is fixedly attached to the transverse rear upper tube **52**. Additionally, the rear suspension assembly **49** further comprises a location rod **90** that at one end (lower end) is pivotally attached to the lower end of rocker arm **80** by a bolt **90b**. The location rod **90** runs adjacent the rear shock absorber **70** and is pivotally interconnected to the chassis **12**. That is, the other end (upper end) of the location rod **90** is pivotally connected by a bolt **90a** to bracket arm **92**, which in turn is fixedly attached to the transverse rear upper tube **52**. Therefore, as the slide frame **20** displaces vertically, rear suspension arm **50** is able to pivot about the third transverse shaft relative to the chassis **12**.

Biasing elements are provided in both front and rear suspension assemblies **29** and **49**, respectively, for urging the slide rails **28** away from the chassis **12**. The biasing elements on the rear suspension assembly **49** preferably include a pair of torsion springs **72** around the transverse upper tube **52** of the rear suspension arm **50**. One end **74** of each torsion spring **72** is connected to its corresponding slide rail **28** and the other end **76** of each is engaged with the rear suspension arm **50**. The biasing element on the front suspension assembly **29** includes a helical spring **63** that is incorporated into the shock absorber **60**. A pair of extension limiters, such as straps **64** shown in FIG. 4, is used to prevent over-extension of the slide rails **28** by the springs **63** and **72**.

As mentioned earlier, the rear shock absorber **70** extends downwardly and forwardly to pivotally attach to rocker arm **80**. Rocker arm **80** and its attachment to the front suspension arm **30** represents a major aspect of the preferred embodiment. Rocker arm **80** is made of two spaced apart flat plates which, when connected, together form one rocker arm **80**. Of course, an integral cast, forged or manufactured rocker arm **80** can also be used. One end of rocker arm **80** is pivotally attached to bracket arm **84** by a bolt **82**, and bracket arm **84** is in turn fixedly attached to the transverse lower tube portion **38** of the front suspension arm **30**. Rocker arm **80** curls around and extends rearwardly beneath tube portion **38**. Pivotally attached to the other end of rocker arm **80** are the lower end of the rear shock absorber **70** by a bolt **70b** and the lower end of the location rod **90** by a bolt **90b**. Bushings can be provided at one or more of the rocker arm/bracket arm, rocker arm/shock absorber and rocker arm/location rod pivot joints, as is known, to reduce friction between the components during operation. The positioning of bracket arm **84** is designed so that when the displacement of the slide frame **20** has reached its maximum compression point, i.e., bottomed out, the top of bracket arm **84** is close to or touches the underside of the snowmobile track **16**. It can be appreciated that the orientation angle between the bracket arm **84** and the front suspension arm **30** remains fixed, and as the front suspension arm **30** moves up vertically due to a

5

displacement of slide frame **20**, bracket arm **84** likewise moves upward and also pivotally rotates about bolt **32**.

With this structure, fewer parts are required to ensure sufficient suspension travel, thereby reducing the complexity and weight of the system, while providing greater flexibility in designing the suspension linkage systems. Additionally, the rocker arm **80** linkage arrangement of the illustrated embodiment eliminates the wear and stiction problems associated with the prior art.

While the invention has been described in connection with what is presently considered to be the most practical and preferred embodiments, it is to be understood that the invention is not to be limited to the disclosed embodiments and elements, but, on the contrary, is intended to cover various modifications, equivalent arrangements, and equivalent elements included within the spirit and scope of the appended claims.

What is claimed is:

1. A snowmobile suspension system comprising:
  - a slide frame for engagement with an endless track;
  - a first suspension arm having an upper portion adapted to be pivotally mounted relative to a chassis on a snowmobile and a lower portion adapted to be pivotally mounted relative to said slide frame;
  - a bracket arm having an end fixedly connected to said lower portion of said first suspension arm; and
  - a rocker arm having an upper end pivotally connected to an other end of said bracket arm and a lower end supporting a lower end of a first shock absorber, said lower end of said first shock absorber being pivotally attached thereto, an upper end of said first shock absorber being pivotally interconnected to the chassis.
2. A snowmobile suspension system according to claim 1, wherein said rocker arm is constructed and arranged such that a lower end of said rocker arm is disposed beneath said lower portion of said first suspension arm.
3. A snowmobile suspension system according to claim 2, further comprising:
  - at least one location rod having an upper end adapted to be pivotally interconnected to the chassis and a lower end adapted to be pivotally attached to said lower end of said rocker arm.
4. A snowmobile suspension system according to claim 3, further comprising:
  - a second suspension arm adjacent said first suspension arm, said second suspension arm having an upper portion adapted to be pivotally mounted relative to said chassis and a lower portion adapted to be pivotally mounted relative to said slide frame.
5. A snowmobile suspension system according to claim 4, wherein said upper end of said at least one location rod is adapted to be pivotally connected to an end of a second bracket arm, an other end of said second bracket arm being fixedly attached to said upper portion of said second suspension arm.
6. A snowmobile suspension system according to claim 4, wherein said first shock absorber is to be downwardly and forwardly angled, and said upper end of said first shock absorber is to be pivotally connected to said upper portion of said second suspension arm.
7. A snowmobile suspension system according to claim 1, further comprising a second shock absorber having an upper end for pivotal connection to said upper portion of said first suspension arm and a lower end to be pivotally mounted relative to said slide frame.

6

8. A snowmobile suspension system according to claim 1, wherein said rocker arm comprises two spaced apart, substantially parallel flat plates.

9. A snowmobile, comprising:

- a chassis;
- an engine disposed on the chassis;
- an endless track disposed below the chassis and connected operatively to the engine for propulsion of the snowmobile;
- at least one ski disposed on the chassis;
- a seat disposed on the chassis, suitable for a rider;
- a steering device disposed on the chassis forward of the seat, the steering device being operatively connected to the at least one ski for steering the snowmobile;
- a slide frame for engagement with the endless track;
- a first suspension arm having an upper portion pivotally mounted relative to the chassis and a lower portion pivotally mounted relative to said slide frame;
- a bracket arm having an end fixedly connected to said lower portion of said first suspension arm; and
- a rocker arm having an upper end pivotally connected to an other end of said bracket arm and a lower end supporting a lower end of a first shock absorber, said lower end of said first shock absorber being pivotally attached thereto, an upper end of said first shock absorber being pivotally interconnected to the chassis.

10. A snowmobile according to claim 9, wherein said rocker arm is constructed and arranged such that a lower end of said rocker arm is disposed beneath said lower portion of said first suspension arm.

11. A snowmobile according to claim 10, further comprising:

- at least one location rod having an upper end pivotally interconnected to the chassis and a lower end pivotally connected to said lower end of said rocker arm.

12. A snowmobile according to claim 11, further comprising:

- a second suspension arm adjacent said first suspension arm, said second suspension arm having an upper portion pivotally mounted relative to said chassis and a lower portion pivotally mounted relative to said slide frame.

13. A snowmobile according to claim 12, wherein said upper end of said at least one location rod is pivotally mounted to an end of a second bracket arm, an other end of said second bracket arm being fixedly attached to said upper portion of said second suspension arm.

14. A snowmobile according to claim 12, wherein said first shock absorber is downwardly and forwardly angled, and said upper end of said first shock absorber is pivotally connected to said upper portion of said second suspension arm.

15. A snowmobile according to claim 9, further comprising a second shock absorber having an upper end pivotally connected to said upper portion of said first suspension arm and a lower end pivotally mounted relative to said slide frame.

16. A snowmobile according to claim 9, wherein said rocker arm comprises two spaced apart, substantially parallel flat plates.