



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ :

H02H 3/00

A1

(11) International Publication Number:

WO 96/10856

(43) International Publication Date:

11 April 1996 (11.04.96)

(21) International Application Number: PCT/US95/10079

(22) International Filing Date: 25 July 1995 (25.07.95)

(30) Priority Data:

08/315,522

30 September 1994 (30.09.94) US

(71) Applicant: SIEMENS ENERGY & AUTOMATION, INC.
[US/US]; 3333 State Bridge Road, Alpharetta, GA 30202 (US).

(72) Inventors: KING, William, A.; 5845 Shadow Rock Drive, Lithonia, GA 30058 (US). ALEXANDER, James, Oliver; 1907 Ridgewood Drive N.E., Atlanta, GA 30307 (US). JENKINS, Jeffrey, Alan; 2012 Newcastle Court, Fort Collins, CO 80526 (US).

(74) Agents: BOLES, Donald, M. et al.; Siemens Corporation, Intellectual Property Dept., 186 Wood Avenue South, Iselin, NJ 08830 (US).

(81) Designated States: CA, MX, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).


Published

With international search report.

(54) Title: GRAPHICAL DISPLAY FOR AN ENERGY MANAGEMENT DEVICE

(57) Abstract

A graphics based display for use with an electronic circuit protection device is taught. Briefly stated, a utility-type electric meter or an electronic circuit protection device has incorporated therewith an LCD display which allows for the graphical display of information. Upon system start-up or key activation, a menu appears which allows for user selection of the information or parameters to be sampled and displayed.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

GRAPHICAL DISPLAY FOR AN ENERGY MANAGEMENT DEVICE**FIELD OF THE INVENTION**

5 This invention relates, generally, to graphical displays and more particularly to a graphical display for use in conjunction with utility-type electric meters or electronic circuit protection devices having integral metering functions in order to display power consumption
10 factors, in graphical format.

BACKGROUND OF THE INVENTION

15 It is becoming increasingly important that the consumption of electrical power by a load be monitored. The reason for such importance relates to cost of operation, maintenance and keeping equipment on-line for purposes such as production, environmental controls and the like. As such, equipment manufacturers are now
20 routinely supplying or incorporating electronic circuit protection devices thereby forming circuit breaker electronic trip units. These electronic circuit protection devices typically incorporate or have the ability to sample waveforms representative of current,
25 voltage, power factor, harmonics, kilowatt hours, var-hours, va-hours, instantaneous power, phase balance/imbalance, phase loading in relation to historical numbers as well as a percentage of maximum level. Moreover, these values can be stored in order to
30 form an historical database which may also include fault data, etc.

35 Unfortunately, such information is generally only available in alpha-numeric displays which are viewed at the power meter or electronic trip unit. Any other form of display may only be accomplished by down loading the

relevant data to another computer either directly or in a network configuration.

Accordingly, it is difficult for an operator to
5 quickly evaluate system performance. It is for this
reason that electronic automotive dash boards typically
use display graphics information in an analog gauge type
format rather than an alphanumeric display. It is known
and appreciated that it is quicker and easier to gauge
10 values, performance and the like in a graphics format.

Accordingly, it is an object of the present
invention to produce a display for use with energy
measurement equipment which will provide information in a
15 graphical rather than alphanumeric format.

It is yet another object of the present invention to
produce a display which does not require a central
computer for subsequent processing and display.
20

It is still another object of the present invention
to produce a display which may scroll through a variety
of values and functions automatically or manually.

25 Still a further object of the present invention is
to produce graphically displayed data which allows the
user to select which information or information set will
be displayed automatically as well as the order in which
it is displayed.

30

Finally, it is another object of the present
invention to produce a graphical display for an AC load
control device, comprising a device for monitoring AC
electrical load usage of a load and a graphical display
35 device connected to the device for monitoring AC
electrical load usage adapted so as to graphically

display at least one parameter of said AC electrical load usage of the load.

5

DETAILED DESCRIPTION OF THE FIGURES

Reference may be now had to the accompanying figures, in which:

10 Fig. 1 is a front view of the display and keypad input as well as the graphical display of the present invention;

Figs. 2a, 2b, 2c, 2d are representative of graphs shown on the display of the present invention; and

15

Fig. 3 is an overview of a circuit breaker display inter-connect scheme of the preferred embodiment of the present invention.

20

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to Figure 1 there is shown the front panel 10 of the present invention indicating exemplary information or indicia. As can be seen, the front panel
25 10 has disposed thereon a liquid crystal diode (LCD) display 12, a key-pad input area 14, status indicators 16, 18, 20, 22, and 24 indicating system status, alarm tripping, system check, protective metering, and communications check respectively. Also evident is a
30 communication port 26 as well as a test connector 28.

Shown on LCD display 12 are phase A display area 13, phase B display area 15, phase C display area 17 and phase N display area 19. It is to be understood that
35 although in the preferred embodiment of the present invention the front panel 10 has numerous functions in a particular order, different indicators or layout may be

utilized without departing from the spirit and scope of the present invention. In this regard, although LCD Display 12 shows four separate display areas 13, 15, 17 and 19, the number of display areas may be increased or
5 decreased as appropriate as well as the use or elimination of numerical indicia thereunder.

In the preferred embodiment of the present invention, LCD Display 12 is at least a 128 by 128 pixel
10 display although other sizes may be utilized as well as the use of color and the like. Further, the LCD display 12 could be electrofluorescent or any other type of suitable display without departing from the spirit and scope of the present invention.

15

It is to be understood that the front panel 10 of the present invention and hence the graphic display taught by the preferred embodiment of the present invention cooperates with an electronic trip unit
20 typically utilized with and part of a circuit breaker. Such trip units, frequently referred to as metering trip units, are readily known and available to one skilled in the art and utilize current transformers and electronic circuitry to measure and if necessary calculate a
25 multitude of parameters relating to power being consumed by the load to which they are attached. Accordingly, a more detailed description will not be given. However, it is to be remembered that the present invention may be utilized with any device which monitors or controls power
30 or a load such as, for example, a utility-type electric meter.

As described more fully below, keypad input 14 is utilized to program and/or command the information to be
35 presented by LCD Display 12. Moreover, communication port 26, which in the preferred embodiment of the present invention presents an RS-232 protocol scheme, may be

utilized to perform bi-directional communications to accomplish this and other functions as described below. However, it is to be understood that other types of ports may be utilized without departing from the spirit and
5 scope of the present inventions.

Similarly, while test connector 28 is utilized to perform interrogation and testing of panel 10 as well as the breaker (not shown) to which it is attached, the
10 connector may be eliminated or modified as appropriate without departing from the spirit and scope of the present invention.

Referring now to Figure 3 it can be seen how the
15 display of the present invention is interconnected with the metering and protective boards of the present invention. As is readily known and available to one skilled in the art, a protective board such as 30, which may be functionally part of a metering trip unit, is used
20 to cooperate directly with a circuit breaker, protective relay and the like (not shown). In the preferred embodiment of the present invention protective board 30 cooperates with a circuit breaker (not shown) and performs housekeeping and monitoring functions such as
25 tripping of the breaker, measuring load values and the like. Further, in the preferred embodiment of the present invention a typical circuit breaker is an 'SB' type circuit breaker manufactured and produced by Siemens Energy & Automation of Atlanta, Georgia although other
30 manufacturers equipment could and may be utilized without departing from the spirit and scope of the present invention.

The metering board 32 which is interconnected
35 through wire interconnects 34, 36 with protective board 30 is utilized to process, accumulate and otherwise monitor the power being consumed by the load (not shown),

for eventual display by LCD display 12. As can be seen, the metering board 32 has interconnected therewith a plurality of components necessary to operate the control panel 10 and hence the display 12 of the present invention. Accordingly, Jack M-J1 at designated numeral 38 functions as the communication port jack which is ultimately connected to communication port 26 as shown in Figure 1. Jack M-J4 which is designated numeral 40 cooperates with and is connected to test connector 28 as also shown in Figure 1. Similarly, terminal M-J2, designated numeral 42 functions as a keypad input jack and cooperates with the keypad 14 as shown in Figure 1 while Jack M-J3, designated numeral 44 cooperates directly with the actual LCD Display 12 as shown in Figure 1.

A typical protective board for the mentioned 'SB' circuit breaker utilizes a microprocessor such as, for example, a 68HC11 which has an integral 8 bit A to D converter and which is suitable for the monitoring, housekeeping and protective functions previously mentioned. However, it has been found that when trying to display information in graphical form, the resolution offered by an 8 bit A to D converter is somewhat lacking. Accordingly, in the preferred embodiment of the present invention, the metering board 32 has an external 12 bit A to D converter which thereafter is interconnected with preferably a 68HC16 microprocessor which is a 16 bit microprocessor.

30

Therefore, with the use of an external 12 bit A to D converter and a 16 bit microprocessor (not shown) the information presented by graphic LCD display 12 may be sufficiently detailed so as to provide accurate, smooth and useful graphics based graphical and alphanumeric information on display 12.

35

Reference may be now had to Figures 2a, 2b, 2c and 2d which indicate exemplary graphical information which may be displayed by LCD Display 12. Accordingly such types of information may include but are not limited to harmonics amongst any of the conductors, phase balance between the three phases, voltage on any of the three phases as well as current among the three phases and of course the neutral conductor parameters may also be viewed.

10

Operation and implementation of LCD Display 12 is relatively simple and will now be described. Although, other types of keypads such as, for example, alphanumeric may be utilized, in the preferred embodiment of the present invention a simple six button keypad input such as 14 having Up, Down, Left, Right, Escape and Enter keys is sufficient. In this regard, keypad input 14 cooperates with the mentioned 68HC16 microprocessor (not shown) contained on metering board 32 and functions in conjunction with software so as to provide a menu style operation for LCD display 12.

Although the LCD display 12 is capable of operating in a "pure" graphics mode thereby allowing access to each individual pixel, in the preferred embodiment of the present invention, rather than having a microprocessor update each pixel during a write command thereby creating a "clunky" or "jagged" screen update, a separate RAM is used. By using a RAM in conjunction with a microprocessor and hence as a buffer area for the LCD display, individual bit manipulations are allowed and done in RAM rather than individual LCD pixel manipulations at the display. This has the advantage of allowing the RAM to be periodically "dumped" to the LCD in a block and thereby making the screen update appear much more smooth. This is found to be much more desirable and convenient from the users standpoint when

the user "toggles" between menus or information on the display.

By use of the term "graphical" display in the present invention, it is specifically meant to mean and include graphics as is presently used and understood in the industry, that is the ability to display information in an 'analog' fashion, and not merely the use of a 'graphics' display capable of only showing alphanumeric characters.

Further, although software is utilized to interact with protective board 30, metering board 32 and hence display 12, it is to be understood that the writing of such software is within the purview of one skilled in the art and therefore a description of the actual code is not included herein. Moreover, the actual code would of course change depending upon the microprocessors and other hardware elements utilized.

As previously recited, the types of information and the format in which it is displayed is selectable by menus which may be created, maintained or prestored. Menus, in the preferred embodiment of the present invention also include housekeeping items such as contrast adjustment for the LCD display. This is accomplished simply by having the appropriate menu appear on the screen and using the Up or Down keys to adjust the contrast. It has been found that adjustable contrast is a necessary and important feature due to the great variety of lighting environments in which equipment of the present invention is installed.

Upon system start-up, in the preferred embodiment of the present invention, a Sign-On screen will display housekeeping items such as the version number of the software, copyright notices, logos and the like.

Thereafter, when any key is pressed the highest level menu choices available will be displayed. These choices are from a category standpoint, Protective, Metering, Communications and logs. The Protective menu has
5 selections for the long time, instantaneous, short-time and ground fault settings. The Metering menu has selections for metered data, alarms, protective relays, and demand period. The Communications menu has
10 selections for EIA-485 settings as well as EIA-232 settings. The log menu has selections for the min-max metering log, the trip log, as well as clearing the min-max log and clearing the trip log.

Further, the metering/metered data menu has
15 selections for the meter screen and graphs while the metering/alarms menu has selections for all the metering alarm settings. Similarly, the metering/protective relay menu has selections for all the metering protective relay settings.

20

The metering/metered data/meter screen will display all the metered data on a single screen in text form while the metering/metered data/graphs menu will have selections to display graphs for items such as total
25 harmonics, phase current loading and balance, phase A, B and C voltage waveforms and phase A, B and C current waveforms (see e.g. Figures 2A-2D).

The log/trip log screen displays the most recent
30 trip event as well as at least two trip events prior to the most recent event also recalled. Additionally, the log/min-max metering log displays a menu of all metered values. Therefore, when a value is selected, LCD Display 12 will produce a screen showing the values min-max with
35 time stamps adjacent thereto. By pressing the up or down keys as appropriate sequential values will be displayed on the screen.

Accordingly, a number of menu items may therefore be produced and simply by pressing the Enter key certain groups contained in the menu may be selected as well as use of the appropriate directional keys to toggle through the various menus displayed. Therefore, other than during start-up as described above, the arrow keys will highlight the category/graph/menu which may be selected. Thereafter, by pressing the Enter key, a particular menu selection will show the sub-menu items or display of an actual graph or data. In this regard, in the preferred embodiment of the present invention, the menu outline is provided in a heirarchichal format as shown below, although this may be changed as required.

Menu Outline

Sign-on Screen

Protective

- Long Time Settings
- Instantaneous Settings
- Short Time Settings
- Ground Fault Settings

Metering

Metered Data

- Meter Screen

Graphs

- Total Harmonics
- Phase Current Loading & Balance
- Phase A Voltage Waveform
- Phase B Voltage Waveform
- Phase C Voltage Waveform
- Phase A Current Waveform
- Phase B Current Waveform
- Phase C Current Waveform

Alarms

- Over Current Settings
- Ground Over Current Settings
- Over Amp Demand Settings
- Total Harmonics Settings
- Over KW Settings
- Over KW Demand Settings
- Over KVAR Settings
- Over KVA Settings
- Under Power Factor Lagging Settings

11

	Over Power Factor Leading Settings
	Protective Relays
5	Neutral Over Current Settings
	Current Unbalance Settings
	Under Voltage Settings
	Voltage Unbalance Settings
	Over Voltage Settings
10	Over Reverse KW Settings
	Under Frequency Settings
	Over Frequency Settings
	Demand Period
15	<u>Communications</u>
	EIA-485 settings
	EIA-232 settings
20	<u>Logs</u>
	Min-Max Metering Log
	Over Current Min-Max
	Ground Over Current Min-Max
25	Over Amp Demand Min-Max
	Total Harmonics Min-Max
	Over KW Min-Max
	Over KW Demand Min-Max
	Over KVAR Min-Max
30	Over KVA Min-Max
	Under Power Factor Lagging Min-Max
	Over Power Factor Leading Min-Max
35	Neutral Over Current Min-Max
	Current Unbalance Min-Max
	Under Voltage Min-Max
	Voltage Unbalance Min-Max
	Over Voltage Min-Max
40	Over Reverse KW Min-Max
	Under Frequency Min-Max
	Over Frequency Min-Max
	Trip Log
	Clear Min-Max Log
45	Clear Trip Log

Further, by utilization of port 26, communications may be accomplished directly so that information indicating fault readings and the like may be downloaded while the menus available to the user may be modified as appropriate.

Accordingly, the present invention produces a
electronic circuit protection device having an integral
graphical function which provides readily accessible and
useful graphical information along with a convenient
5 mechanism to view or alter that which is seen.

It is to be understood that many variations from the
present invention may be practiced without departing from
the spirit and scope of the present invention. Such
10 variations may include, for example, a different set of
microprocessors, memory devices and the like or the way
in which the display is interconnected with a circuit
protection device. Further, a cursor arrangement
available on the screen may be utilized or a touch
15 operated screen may be utilized. Additionally, screens
having higher or lower resolution may be utilized as well
as larger or smaller screens without departing from the
spirit and scope of the present invention. Further, the
menu choices may be expanded or minimized to reflect user
20 requirements.

Accordingly, the present invention is not to be
limited by the specification but rather by the claims
appended hereto.

WHAT IS CLAIMED IS:

1. A graphical display for an AC load control device, comprising:

5

an device for monitoring AC electrical load usage of a load; and

a graphical display device connected to said
10 device for monitoring AC electrical load usage, said graphical display device adapted so as to graphically display at least one parameter of the AC electrical load usage of the load.

15 2. A device according to claim 1, further comprising a circuit protective device for interrupting electrical power to the load.

3. A device according to claim 2 wherein said
20 circuit protective device is a circuit breaker.

4. A device according to claim 2, wherein said device for monitoring AC electrical load usage is comprised of a first means for controlling said circuit
25 protective device and a second means for producing a plurality of signals representative of at least one of the current, voltage and power related characteristics of the load.

30 5. A device according to claim 4, wherein said graphical display device is comprised of a metering means connected to said second means for receiving and processing and storing said plurality of signals and for producing graphics related output image signals, and a
35 display means connected to said metering means and adapted to receive said graphics related output image

signals for producing graphic images which are viewable by a user.

6. A device according to claim 5, wherein said
5 display means is comprised of an LCD display.

7. A device according to claim 6 wherein said LCD display is at least 128 pixels square.

10 8. A device according to claim 5 wherein said metering means is comprised of:

an Analog to Digital converter, adapted to receive and digitize said plurality of signals; and

15

a microprocessor connected to said Analog to Digital Converter for processing the digitized plurality of signals.

20 9. A device according to claim 8, further comprising a Random Access Memory (RAM) device connected to said microprocessor for storing the processed digitized plurality of signals.

25 10. A device according to claim 5 wherein said display means is comprised of an Electrofluorescent display.

30 11. A graphical display for an AC load control device, comprising:

a circuit protective device for interrupting electrical power to a load;

35 means for monitoring AC electrical load usage of a load comprised of a first means for controlling said circuit protective device and a second means for

producing a plurality of signals representative of at least one of the current, voltage and power related characteristics of the load; and

5 a graphical display device connected to said device for monitoring AC electrical load usage and adapted so as to graphically display at least one parameter of the AC electrical load usage of the load, said graphical display device comprised of a metering
10 means connected to said second means for receiving and processing and storing said plurality of signals and for producing graphics related output image signals, and a display means connected to said metering means and adapted to receive said graphics related output image
15 signals for producing graphic images which are viewable by a user, wherein said metering means is comprised of:

 an Analog to Digital converter, adapted to receive and digitize said plurality of signals; and
20

 a microprocessor connected to said Analog to Digital Converter for processing the digitized plurality of signals

25 12. A device according to claim 11 wherein said circuit protective device is a circuit breaker.

 13. A device according to claim 11, wherein said display means is comprised of an LCD display.
30

 14. A device according to claim 13 wherein said LCD display is at least 128 pixels square.

 15. A device according to claim 11, further
35 comprising a Random Access Memory (RAM) device connected to said microprocessor for storing the processed digitized plurality of signals.

16. A device according to claim 11 wherein said display means is comprised of an Electrofluorescent display.

5 17. A method for graphically displaying load related parameters comprising the steps of:

 A. Sampling at least one of the voltage, current and power components of a load and producing an
10 analog signal representative thereof;

 B. Digitizing said analog signal into a representative Digital signal;

15 C. Processing said digital signal into a form which is usable by a graphic image display device; and

 D. Displaying the processed digital signal on a display in a graphics based analog format.
20

18. A method according to claim 17 further comprising the additional step (C-1) between steps C and D of:

25 C-1. storing said processed digital signal in RAM until all pixels on a display device may be updated substantially simultaneously.




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 95/10079

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H02H3/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H02H G01R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	FARAHAT ET AL. 'conference record of 1990 annual pulp and paper industry technical conference' 18 June 1990, IEEE INDUSTRY APPLICATIONS SOCIETY, PROCESS INDUSTRIES DEPARTMENT, PULP AND PAPER INDUSTRY COMMITTEE XP 000166444 see page 158 - page 163 ---	1-5, 11, 17
X	ETZ ELEKTROTECHNISCHE ZEITSCHRIFT, vol. 113, no. 17, August 1992 BERLIN, DE, pages 1070-1075, XP 000311688 OFFHAUS 'Entwicklungstendenzen beim digitalen Leitungsschutz' see figures 4, 6 ---	1, 17
P, X	US, A, 5 369 356 (KINNEY) 29 November 1994 see figure 1A ---	1-18
-/--		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *&* document member of the same patent family

Date of the actual completion of the international search

27 November 1995

Date of mailing of the international search report

24.01.96

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+ 31-70) 340-3016

Authorized officer

Hoornaert, W

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 95/10079

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US,A,4 672 555 (HART) 9 June 1987 see claim 1 -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 95/10079

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-5369356	29-11-94	NONE	
US-A-4672555	09-06-87	NONE	