

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
28 June 2001 (28.06.2001)

PCT

(10) International Publication Number  
**WO 01/46102 A1**

(51) International Patent Classification<sup>7</sup>: C07C 39/04, (74) Agents: LOO, Blossom, E.; ExxonMobil Chemical Company, P.O. Box 2149, Baytown, TX 77522-2149 et al. (US).  
49/08, 37/08, 45/53

(21) International Application Number: PCT/US00/34843

(81) Designated States (national): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(22) International Filing Date: 20 December 2000 (20.12.2000)

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(25) Filing Language: English

Published:

— With international search report.

(26) Publication Language: English

(30) Priority Data:  
09/468,465 21 December 1999 (21.12.1999) US

(71) Applicant: MOBIL OIL CORPORATION [US/US];  
5200 Bayway Dr., Baytown, TX 77520-5200 (US).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(72) Inventors: LEVIN, Doron; Apt. D2, 125 Montgomery Avenue, Bala Cynwyd, PA 19004 (US). SANTIESTEBAN, Jose, G.; 191 Applegate Drive, West Chester, PA 19382 (US).



A1

(54) Title: PRODUCTION OF PHENOL USING REACTIVE DISTILLATION

(57) **Abstract:** A process for producing phenol and acetone from cumene hydroperoxide comprises: i) introducing a cumene hydroperoxide feed into a reactive distillation column comprising at its upper portion a distillation column and at its lower portion a catalyst bed, at a point above said catalyst bed; ii) mixing a diluting portion of acetone with said cumene hydroperoxide to provide a diluted cumene hydroperoxide; iii) directing said diluted cumene hydroperoxide through said catalyst bed under conditions sufficient to effect the exothermic decomposition of said cumene hydroperoxide to a product comprising a heavy fraction comprising phenol and a vaporized light fraction comprising acetone; iv) withdrawing said heavy fraction as bottoms from said column; v) flowing said vaporized light fraction upwards through the catalyst bed and at least a portion of the reactive distillation column; vi) condensing said light fraction to provide at least a portion of said diluting portion of acetone for subsequent mixing with said cumene hydroperoxide feed; vii) optionally withdrawing a portion of said light fraction as overhead from said column; and viii) repeating steps i) through vii). An apparatus for carrying out the process is also provided.

**WO 01/46102**

## PRODUCTION OF PHENOL USING REACTIVE DISTILLATION


### BACKGROUND OF THE INVENTION

5    Field of the Invention

This invention relates to the production of phenol and more particularly to a process for producing phenol and acetone from cumene hydroperoxide (CHP) using reactive distillation.

10    Description of the Prior Art

Phenol is an important organic chemical with a wide variety of industrial uses. It is used, for example, in the production of phenolic resins, bisphenol-A and caprolactam. A number of processes are currently in use for the production of phenol but the single process providing the largest proportion of the total production capacity is the cumene process which now accounts for over three quarters of the total U.S. production. The basic reaction involved in this process is the cleavage of cumene hydroperoxide into phenol and acetone:



20

The reaction takes place under acid conditions with the yield of both phenol and acetone generally being 40 percent or more.

On an industrial scale, the cumene hydroperoxide is usually treated with dilute sulphuric acid (0.5 to 25 percent concentration) at a temperature of about 25 50° to 70°C. After the cleavage is complete, the reaction mixture is separated and the oil layer distilled to obtain the phenol and acetone together with cumene, alpha-methylstyrene, acetophenone and tars. The cumene may be recycled for conversion to the hydroperoxide and subsequent cleavage. The phenol produced in this way is suitable for use in resins although further purification is 30 required for a pharmaceutical grade product.

The heterogeneous cleavage of cumene hydroperoxide (CHP) over

various solid acid catalysts has already been reported. For example, U.S. Patent No. 4,490,565 discloses the use of zeolite beta in the cleavage of cumene hydroperoxide, whereas U.S. Patent No. 4,490,566 discloses the use of a Constraint Index 1-12 zeolite, such as ZSM-5, and EP-A-492807 discloses the 5 use of faujasite in the same process. The use of smectite clays in the acid-catalyzed decomposition of cumene hydroperoxide is described in U.S. Patent No. 4,870,217.

U.S. Patent No. 4,898,995 discloses a process for the coproduction of phenol and acetone by reacting cumene hydroperoxide over a heterogeneous 10 catalyst consisting of either an ion exchange resin having sulfonic acid functionality or a heteropoly acid, such as 12-tungstophosphoric acid, on an inert support, such as silica, alumina, titania and zirconia. Such heteropoly acid catalysts are generally used as their hydrates, and as such are inherently unstable at temperatures in excess of 350°C.

15 Catalytic distillation has been used to produce cumene by alkylating propylene with benzene. See, J. Shoemaker, et al., Cumene by Catalytic Distillation, Hydrocarbon Processing, p. 57, (June, 1987).

U.S. Patent No. 4,935,577 to Huss, Jr., et al. discloses the use of Lewis 20 acid promoted inorganic oxide catalyst systems for alkylation and oligomerization processes using catalytic distillation.

U.S. Patent No. 5,055,627 to Smith, Jr., et al. discloses an alkylation process for preparing cumene from benzene and propylene in a zeolitic catalyst bed disposed in a distillation column reactor. The alkylated benzene is withdrawn from the distillation column reactor at a point below the fixed bed and 25 unreacted organic aromatic compound may be taken off as an overhead.

U.S. Patent No. 5,905,178 to Hildreth discloses a process for removing *alpha*-methyl styrene from admixtures with cumene by hydrogenation using catalytic distillation to selectively hydrogenate the side chains and produce cumene. The *alpha*-methyl styrene is produced as a byproduct in the cumene-30 phenol peroxidation process.

It is an object of the present invention to provide a process for the

production of phenol and acetone using catalytic distillation. This process would provide a method of reacting cumene hydroperoxide which would avoid excessive heat buildup and utilize cumene hydroperoxide's high heat of reaction (60.6 kcal/mol) to separate out low boiling point decomposition products, such as 5 acetone.

#### SUMMARY OF THE INVENTION

The present invention relates to a process for producing phenol and acetone from cumene hydroperoxide, wherein the process comprises the 10 steps of:

- i) introducing a cumene hydroperoxide feed into a reactive distillation column comprising at its upper portion a distillation column and at its lower portion a catalyst bed, at a point above or at an upper portion of said catalyst bed;
- 15 ii) mixing a diluting portion of acetone with said cumene hydroperoxide to provide a diluted cumene hydroperoxide;
- iii) directing said diluted cumene hydroperoxide through said catalyst bed under conditions sufficient to effect the exothermic decomposition of said cumene hydroperoxide to a product comprising a heavy fraction comprising and 20 a vaporized light fraction comprising acetone;
- iv) withdrawing said heavy fraction as bottoms from said column;
- v) flowing said vaporized light fraction upwards through the catalyst bed and at least a portion of the reactive distillation column;
- vi) condensing said light fraction to provide at least a portion of said 25 diluting portion of acetone for subsequent mixing with said cumene hydroperoxide feed;
- vii) optionally withdrawing a portion of said light fraction as overhead from said column; and
- viii) repeating steps i) through vii).

30

Steps v) and vi) can be used to control dilution of the cumene

hydroperoxide feed, e.g., by setting the reflux rate of acetone through said column. The liquid flow of the diluted cumene hydroperoxide through the reactor is preferably maintained at a rate sufficient to keep the catalyst bed wetted, thereby maintaining catalyst temperature at or near the boiling point of the liquid 5 to provide isothermal operation of the process. Given that step vii) is optional, the presently claimed process includes operation under conditions of total reflux with all overhead product being returned to the column.

The diluting portion of acetone can be added to at least one of: 1) the upper portion of the distillation column, 2) the lower portion of the distillation 10 column, upstream of said catalyst bed, e.g., at the CHP feed tray, and 3) the cumene hydroperoxide feed prior to its introduction to said distillation column. Recovered overhead which contains acetone can also be added directly at one or more locations to the catalyst bed in amounts sufficient to reduce formation of heavy compounds, i.e., compounds with normal boiling points greater than 15 182°C, e.g., dimers of  $\alpha$ -methylstyrene (AMS). Such interstage injection of acetone diluent can be used to assist in maintaining the catalyst bed at a temperature at or near the boiling point of the reactant liquid to provide preferred isothermal operation, while eliminating reactor "hot spots."

In another aspect, the present invention relates to an apparatus for 20 preparing phenol from cumene hydroperoxide which comprises:

- a) a reactive distillation column comprising at its upper portion a distillation column and its lower portion a catalyst bed;
- b) a lower outlet downstream of the catalyst bed for removing high boiling bottom products comprising phenol;
- c) an inlet at or near the bottom of said distillation column for introducing cumene hydroperoxide feed at a point upstream of said catalyst bed;
- d) an upper outlet for removing low boiling overhead products comprising acetone;
- e) a heat exchanger upstream of said upper outlet for cooling said 25 overhead products;
- f) an overhead products receiver upstream of said heat exchanger having

an outlet from which said overhead products are collected and/or returned to said distillation column; and

g) overhead products inlet at an upper portion of said distillation column for introducing overhead products reflux from said receiver.

5

The apparatus can further comprise an element selected from the group consisting of

h) an overhead products inlet at a lower portion of said distillation column for introducing overhead products from said receiver to said distillation column at 10 or near said inlet for introducing cumene hydroperoxide;

i) an overhead products line which recycles overhead products to the cumene hydroperoxide feed upstream of said inlet for introducing cumene hydroperoxide; and

j) an overhead products line which recycles overhead products to one or 15 more portions of the catalyst bed.

The process and apparatus of the invention can achieve at or near 100% conversion of cumene hydroperoxide at long on-stream times with high selectivity to phenol and acetone and with extremely low coproduction of high boiling 20 impurities such as 4-cumylphenol, and 2,4-diphenyl-4-methyl-1-pentene. Moreover, the present invention allows efficient use of the heat of reaction evolved from decomposition of cumene hydroperoxide to effect separation of lower boiling products, e.g., acetone, from the reaction product mixture. Such an arrangement minimizes reboiler use, reducing energy costs, while providing 25 higher yields, good product purity and lower capital investment.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIGURE 1 depicts a flow diagram for an embodiment of the present 30 invention wherein reflux acetone is introduced at the top of the distillation column.

FIGURE 2 depicts a flow diagram for an embodiment of the present invention wherein acetone is introduced at the top of the distillation column, directly above the catalyst bed, and/or recycled into the cumene hydroperoxide feed.

5 FIGURE 3 depicts a flow diagram for an embodiment of the present invention wherein acetone is introduced at the top of the distillation column, directly above the catalyst bed, and/or into the catalyst bed.

#### DESCRIPTION OF SPECIFIC EMBODIMENTS

10 In catalytic distillation, a reaction zone containing catalyst is fitted into a fractionation tower equipped with an overhead condenser, reflux pump, reboiler, overhead receiver and control instrumentation. Feed components are introduced above the catalyst bed. Products are continuously removed from the reaction zone by the distillation process.

15 Catalytic distillation is suitable only for chemical reactions where the distillation of reaction components occurs in the same temperature range as the reaction. Thus, operation above the critical point can be a limitation, and the presence of azeotropes or close boiling components may cause difficulties.

20 Inasmuch as distillation columns are typically operated at higher liquid and vapor flow rates than conventional reactors, the reduced residence time in the reactive section of the column of the present invention will minimize the formation of byproducts. This is especially advantageous in the case of CHP decomposition as the dehydration of 2-phenyl-2-propanol leads to the formation of  $\alpha$ -methylstyrene (AMS), a reactive intermediate that could undergo further 25 reactions such as dimerization, oligomerization, and coke formation. Minimizing the formation of heavy compounds will extend catalyst life if a heterogeneous catalyst is employed for the reactive section of the column.

20 The preferred conditions for the decomposition reaction include temperature and pressure ranges that are suitable for use in a distillation column. 30 Due to the high heat of reaction, decomposition preferably takes place under dilute CHP concentrations, of the order of less than 50 wt.%, preferably 0.1 to 25

wt.%, and most preferably 0.5 to 5 wt.%, e.g., about 3 wt.% CHP. The feed to the tower can range from 25 to 95 wt.%, preferably 75 to 85 wt.%, e.g., 80 wt.% CHP, and needs to be further diluted, preferably by acetone, to the above-noted levels. Control of the dilution level can be achieved by setting the reflux rate

5 through the tower, or directly adding the recycled overhead containing acetone to the cumene hydroperoxide feed.

Table 1 lists the normal boiling points for the major components involved in the decomposition of cumene hydroperoxide. Acetone has a significantly

10 lower boiling point than all the other major components, thereby facilitating its separation in a reactive distillation column. Other low boiling components may also be present in the column, e.g., methanol, acetaldehyde, and benzene.

TABLE 1

Component	Normal Boiling Point (°C)
Acetone	56.3
Cumene	152.4
$\alpha$ -Methylstyrene	165.5
Phenol	181.8
2-Phenyl-2-Propanol	192.6
Acetophenone	202.0

15 The catalyst employed can be either a homogeneous or heterogeneous catalyst. Suitable homogeneous catalyst systems can employ a suitable catalyst such as dilute (0.01 to 5 percent concentration) sulfuric acid. Other acids such as perchloric acid, phosphoric acid, p-toluenesulfonic acid, and sulfur dioxide are also effective homogeneous catalysts.

20 Suitable heterogeneous catalysts for use in the cleavage of cumene hydroperoxide include solid acid catalysts such as zeolite beta, disclosed in U.S. Patent No. 4,490,565; a Constraint Index 1-12 zeolite, such as ZSM-5, disclosed in U.S. Patent No. 4,490,566; faujasite, disclosed in EP-A-492807; smectite clays, described in U.S. Patent No. 4,870,217; ion exchange resins having

25 sulfonic acid functionality or heteropoly acids, such as 12-tungstophosphoric

acid, on an inert support, such as silica, alumina, titania and zirconia, disclosed in U.S. Patent No. 4,898,995. Additional solid-acid catalysts suited for use in the present invention include those comprising a sulfated transition metal oxide such as sulfated zirconia together with an oxide of iron or oxides of iron and 5 manganese as described in U.S. Patent Application Serial No. 09/296,852, filed 4/22/1999 (Attorney's Docket No. 10144-1), as well as those comprising a mixed oxide of cerium and a Group IVB metal, e.g., zirconium, described in U.S. Patent Application Serial No. 09/366,249, filed 8/3/1999 (Attorney's Docket No. 10173-1.)

The process of the invention can also use a solid acid catalyst comprising 10 an oxide of a Group IVB metal modified with an oxyanion or oxide of a Group VIB metal by calcination of the oxide species at a temperature of at least 400°C, as disclosed in U.S. Patent Application Serial No. 09/275,749, filed 3/25/1999 (Attorney Docket No. 10135-1). The modification of the Group IVB metal oxide with the oxyanion of the Group VIB metal imparts acid functionality to the 15 material. The modification of a Group IVB metal oxide, particularly, zirconia, with a Group VIB metal oxyanion, particularly tungstate, is described in U.S. Patent No. 5,113,034; and in an article by K. Arata and M. Hino in Proceedings 9th International Congress on Catalysis, Volume 4, pages 1727-1735 (1988).

The large pore crystalline molecular sieves which can be used in the 20 present invention include those which have pores sufficiently large to physically absorb 2,2,4-trimethylpentane. Representative large pore crystalline molecular sieves include, for example the following zeolites: ZSM-3, ZSM-4, ZSM-12, ZSM-18, ZSM-20, zeolite Beta, zeolite L, mordenite, faujasite, zeolite Y, and the rare earth metal-containing forms of the above. For the purposes of this invention, 25 zeolite Y includes zeolite Y in its as synthesized form, as well as its variant forms including framework dealuminated zeolite, e.g., ultrastable Y (USY) described in U.S. Pat. No. 3,293,192 and LZ-210 described in U.S. Pat. No. 4,503,023, hereby incorporated by reference.

The large pore zeolite selected for use in the process of this invention generally 30 can possess an alpha value over a wide range of from less than 1 to over 1000. "Alpha value", or "alpha number", is a measure of zeolite acidic functionality and

is more fully described together with details of its measurement in U.S. Pat. No. 4,016,218, J. Catalysis, 6, pp. 278-287 (1966) and J. Catalysis, 61, pp. 390-396 (1980). Zeolites of low acidity (alpha values of less than about 200) can be achieved by a variety of techniques including (a) synthesizing a zeolite with a

5 high silica/alumina ratio, (b) steaming, (c) steaming followed by dealuminization and (d) substituting framework aluminum with other species. For example, in the case of steaming, the zeolite can be exposed to steam at elevated temperatures ranging from about 500° to about 1200° F and preferably from about 750° to about 1000° F. This treatment can be accomplished in an atmosphere of 100%

10 steam or an atmosphere consisting of steam and a gas which is substantially inert to the zeolite. A similar treatment can be accomplished at lower temperatures using elevated pressure, e.g., at from about 350° to about 700°F. with from about 10 to about 200 atmospheres. Specific details of several steaming procedures may be gained from the disclosures of U.S. Pat. Nos.

15 4,325,994; 4,374,296 and 4,418,235, the contents of which are incorporated by reference herein. Aside from, or in addition to any of the foregoing procedures, the surface acidity of the zeolite can be eliminated or reduced by treatment with bulky reagents as described in U.S. Pat. No. 4,520,221, the contents of which are incorporated by reference herein.

20 Other large pore crystalline molecular sieves which can be used in the present invention include pillared silicates and/or clays; aluminophosphates, e.g., ALPO-5, VPI-5; silicoaluminophosphates, e.g., SAPO-5, SAPO-37, SAPO-31, SAPO-40, SAPO-41; and other metal aluminophosphates. These are variously described in U.S. Pat. Nos. 4,440,871; 4,554,143; 4,567,029; 4,666,875 and

25 4,742,033, incorporated herein by reference.

The particular class of macroreticular acid cation exchange resins useful as catalysts in the present invention are characterized by substantial porosity, high surface area and a low surface acid concentration, generally less than about 0.5 milliequivalents of hydrogen ion per square meter surface area. The cation exchange resin can contain a small amount of water, generally between 0.5 and 30 20 percent by weight. The macroreticular resins utilized in the process of this

invention are characterized by the presence of acid functional groups and a structure having a high degree of true porosity while possessing rigidity and being subject to minimum volume change when immersed or removed from solvents or solutions.

5        The macroreticular acid ion exchange resin used is typified by the presence of sulfonic acid groups, e.g., the sulfonated styrene-divinylbenzene copolymer exchange resins such as those commercially available as Amberlyst-15, Amberlyst XN-1005, Amberlyst XN-1010, Amberlyst XN-1011, Amberlyst XN-1008 and Amberlite 200.

10      Perfluorinated ion-exchange polymers, or porous microcomposites comprising perfluorinated ion-exchange polymer containing sulfonic acid and/or carboxylic acid groups dispersed within a network of a metal oxide such as silica, e.g. Nafion®, are also useful as catalysts in the present invention.

15      The solid catalyst can be shaped into a wide variety of particle sizes. The particles can be in the form of a powder, a granule, or a molded product, such as an extrudate. In cases where the catalyst is molded, such as by extrusion, the catalyst can be extruded before drying, or partially dried and then extruded. The present catalyst may be extruded by itself, or it may be composited with a matrix material to form the finished form of the catalyst and for this purpose

20      conventional matrix materials such as alumina, silica-alumina and silica are suitable with preference given to silica as a non-acidic binder. Other binder materials may be used, for example, titania, zirconia and other metal oxides or clays. The active catalyst may be composited with the matrix in amounts from 80:20 to 20:80 by weight, e.g., from 80:20 to 50:50 active catalyst:matrix.

25      Compositing may be done by conventional means including mulling the materials together followed by extrusion or pelletizing into the desired finished catalyst particles.

30      The cleavage reaction of the invention is effected by contacting the cumene hydroperoxide with the solid oxide catalyst described above in the liquid phase at a temperature of 20 to 150°C, preferably 40 to 120°C, and a pressure of -10 to 1000 psig, preferably atmospheric to 400 psig. To effect the contacting

of the cumene hydroperoxide, the catalyst may be contained in a stationary bed, and the contacting operation takes place continuously. The liquid hourly space velocity (LHSV) based on cumene hydroperoxide is within the range of 0.1 to 100 hr<sup>-1</sup>, preferably 1 to 50 hr<sup>-1</sup>. The cumene hydroperoxide is preferably diluted in an 5 organic solvent inert to the cleavage reaction, such as benzene, toluene, cumene and most preferably acetone. Control of the dilution level can be achieved by setting the reflux rate through the tower, or directly adding the recycled overhead containing the solvent to the cumene hydroperoxide feed. The use of a solvent is preferred so as to assist in dissipating the heat of reaction (about 60 kcal/mol).

10 The packing which may be used in the distillation column employed in the present invention is selected as a function of the efficiency necessary for the distillation operation. The packing can be selected from packings which are well known to the skilled person, such as solids in the form of rings, poly-lobed extrudates or saddle packing. Non-limiting examples of packing are Raschig 15 rings, Pall rings, Intos rings, Berl saddle packing, Novalox saddle packing and Intalox saddle packing. The packing can also be selected from structured packings, for example, FLEXIPAC (registered trademark) sold by Koch, or SULZER CHEMTECH or SULZER (registered trademarks) sold by Sulzer.

20 A distributing tray which may be used in the process of the present invention is a simple tray which allows the upward passage of vapor and collection, then overflow, of liquid, as in any distributing tray which is known to the skilled person, in particular if the major portion of the distillation zone to which it belongs is composed of packing. When a distillation tray is used in accordance with the present invention, the tray can be selected from distillation trays which 25 are known to the skilled person, in particular perforated trays, bubble cap trays, or valve trays.

20 The operation of a catalytic distillation column according to the present invention leads to a distribution of components throughout the column and catalyst bed. The concentration of various components may affect the optimal 30 performance of the catalyst by retarding desired reactions and promoting undesired ones. To achieve optimal operation of the catalyst bed, the -bed can

be located at a position within the column where the component concentrations are optimal. This may lead to the presence of a separate distillation section acting as a stripper positioned below the catalyst bed.

The invention will now be more particularly described with reference to 5 the following Examples.

### Example 1

In the process configuration of FIGURE 1, phenol and acetone are produced from cumene hydroperoxide in a reactive distillation column 100. A 10 cumene hydroperoxide-containing feed line 110 containing about 80 wt.% CHP introduces feed through inlet 120 at a point above catalyst bed 130 where it is mixed with a diluting portion of acetone derived from column overhead to provide a dilute cumene hydroperoxide mixture which passes through the catalyst bed 130 under cumene hydroperoxide decomposition conditions including a 15 temperature of about 50 to 90°C, a pressure of 0 to 10 psig, and an LHSV of 0.3 to 5 hr<sup>-1</sup> to provide a product comprising phenol and acetone. The catalyst bed is an unstructured packed bed of solid catalyst. The catalyst is in the form of pellets, typically greater than 1/24" diameter, such that the catalyst bed void volume allows for liquid flow down the bed, and vapor flow up the bed. 20 The catalyst is prepared as follows: five hundred parts of ZrOCl<sub>2</sub>.8H<sub>2</sub>O are dissolved with stirring in 3.0 liters of distilled water. To this solution is added 7.6 parts of FeSO<sub>4</sub>·7H<sub>2</sub>O. Another solution containing 260 parts of concentrated NH<sub>4</sub>OH, 54 parts of (NH<sub>4</sub>)<sub>6</sub>H<sub>2</sub>W<sub>12</sub>O<sub>40</sub>·xH<sub>2</sub>O and 2940 parts of distilled water was prepared. Both solutions were heated to 60°C and the heated solutions were 25 combined at a rate of 50 parts/min using nozzle mixing. The pH of the final composite was adjusted to approximately 9 by the addition of concentrated ammonium hydroxide. This slurry was then put in polypropylene bottles and placed in a steambox (100°C) for 72 hours. The product formed was recovered by filtration, washed with excess water, and dried overnight at 85°C. The dried 30 product was calcined to 800°C in flowing air for 3 hours, and then formed into

pellets. The catalyst pellets were thereafter added to the catalyst bed.

Phenol and other heavies formed pass downwardly through the catalyst bed and are withdrawn from the reactive distillation column through lower outlet **140** and are sent for recovery in the distillation section of the plant (not shown).

5      Overheads containing acetone pass upwardly through the column and through upper outlet **150** and thence to a heat exchanger such as condenser **160** and thereafter to overheads receiver **170**. The acetone-containing overhead can be withdrawn from the receiver through line **180** or recycled as reflux to an upper portion of the distillation column **190**. Dilution of cumene hydroperoxide feed with 10 acetone is controlled by varying the amount of acetone recycled to the distillation column, i.e., setting the reflux rate through the tower. The compositions of the proposed feed and estimated product compositions are provided below in TABLE 2.

15

**TABLE 2**

	Feed	Overhead Product	Bottoms Product
Acetone	0.00	99.57	8.43
Mesityl Oxide	0.00	0.00	0.00
Cumene	7.70	0.00	10.26
Phenol	0.17	0.00	67.67
$\alpha$ -Methyl Styrene	0.27	0.00	9.47
Acetophenone	2.19	0.00	2.92
2-Phenyl-2-Propanol	7.87	0.00	0.00
Cumene Hydroperoxide	81.80	0.00	0.00
Water	0.00	0.43	1.25

**Example 2**

In the process configuration of FIGURE 2, phenol and acetone are 20 produced from cumene hydroperoxide in a reactive distillation column **200**. A cumene hydroperoxide-containing feed line **210** containing about 80 wt.% CHP introduces feed through inlet **220** at a point above catalyst bed **230** where it is

mixed with a diluting portion of acetone derived from column overhead to provide a dilute cumene hydroperoxide mixture which passes through the catalyst bed 230 under cumene hydroperoxide decomposition conditions including a temperature of about 50 to 90°C, a pressure of 0 to 10 psig, and an LHSV of 0.3 5 to 5 hr<sup>-1</sup> to provide a product comprising phenol and acetone. The catalyst bed is an unstructured packed bed of solid catalyst as described in Example 1. Phenol and other heavies formed pass downwardly through the catalyst bed and are withdrawn from the reactive distillation column through lower outlet 240 and are sent for recovery in the distillation section of the plant (not shown). Overheads 10 containing acetone pass upwardly through the column and through upper outlet 250 and thence to a heat exchanger such as condenser 260 and thereafter to overheads receiver 270. The acetone-containing overhead can be withdrawn from the receiver through line 280 or recycled as reflux to an upper portion of the distillation column through line 290 or through line 292 to a lower portion of the 15 distillation column (at the CHP feed tray level). Alternatively, or in addition, the recycled overhead is directed through line 294 to the cumene hydroperoxide feed 210 as a way to effect dilution as required. Thus, dilution of cumene hydroperoxide feed with acetone is controlled by varying the amount of acetone recycled to the distillation column, i.e., setting the reflux rate through the tower, at 20 upper and/or lower portions of the distillation column, or added directly to the CHP feed. The compositions of the proposed feed and estimated product compositions are provided below in TABLE 3.

TABLE 3

	Feed	Overhead Product	Bottoms Product
Acetone	0.00	99.68	27.61
Mesityl Oxide	0.00	0.00	0.00
Cumene	7.70	0.00	8.11
Phenol	0.17	0.00	53.42
α-Methyl Styrene	0.27	0.00	7.47
Acetophenone	2.19	0.00	2.31
2-Phenyl-2-Propanol	7.87	0.00	0.00

Cumene Hydroperoxide	81.80	0.00	0.00
Water	0.00	0.32	1.08

### Example 3

In the process configuration of FIGURE 3, phenol and acetone are produced from cumene hydroperoxide in a reactive distillation column 300. A 5 cumene hydroperoxide-containing feed line 310 containing about 80 wt.% CHP introduces feed through inlet 320 at a point above catalyst bed 330 where it is mixed with a diluting portion of acetone derived from column overhead to provide a dilute 3 wt.% cumene hydroperoxide mixture which passes through the catalyst bed 330 under cumene hydroperoxide decomposition conditions including a 10 temperature of about 50 to 90°C, a pressure of 0 to 10 psig, and an LHSV of 0.3 to 5 hr<sup>-1</sup> to provide a product comprising phenol and acetone. The catalyst bed is an unstructured packed bed of solid catalyst as described in Example 1. Phenol and other heavies formed pass downwardly through the catalyst bed and are withdrawn from the reactive distillation column through lower outlet 340 and are 15 sent for recovery in the distillation section of the plant (not shown). Overheads containing acetone pass upwardly through the column and through upper outlet 350 and thence to a heat exchanger such as condenser 360 and thereafter to overheads receiver 370. The acetone-containing overhead can be withdrawn from the receiver through line 380 or recycled as reflux to an upper portion of the 20 distillation column through line 390 or through line 392 to a lower portion of the distillation column (at the CHP feed tray level). Alternatively, or in addition, the recycled overhead can be directed through line 396 directly to the catalyst bed 340. This interstage injection of the acetone-containing overhead may be used to control concentration levels in the lower portion of the catalyst bed to minimize 25 formation of heavy compounds. Thus, dilution of cumene hydroperoxide feed with acetone is controlled by varying the amount of acetone recycled to the distillation column, i.e., setting the reflux rate through the tower, at upper and/or lower portions of the distillation column, or added directly to the catalyst bed. The compositions of the proposed feed and estimated product compositions are

provided below in TABLE 4.

**TABLE 4**

	Feed	Overhead Product	Bottoms Product
Acetone	0.00	99.63	19.14
Mesityl Oxide	0.00	0.00	0.00
Cumene	7.70	0.00	9.06
Phenol	0.17	0.00	59.71
$\alpha$ -Methyl Styrene	0.27	0.00	8.35
Acetophenone	2.19	0.00	2.58
2-Phenyl-2-Propanol	7.87	0.00	0.00
Cumene Hydroperoxide	81.80	0.00	0.00
Water	0.00	0.37	1.16

What is claimed is:

1. A process for producing phenol and acetone from cumene hydroperoxide, which comprises:
  - 5 i) introducing a cumene hydroperoxide feed into a reactive distillation column comprising at its upper portion a distillation column and at its lower portion a catalyst bed, at a point above or at an upper portion of said catalyst bed;
  - ii) mixing a diluting portion of acetone with said cumene hydroperoxide to 10 provide a diluted cumene hydroperoxide;
  - iii) directing said diluted cumene hydroperoxide through said catalyst bed under conditions sufficient to effect the exothermic decomposition of said cumene hydroperoxide to a product comprising a heavy fraction comprising phenol and a vaporized light fraction comprising acetone;
  - 15 iv) withdrawing said heavy fraction as bottoms from said column;
  - v) flowing said vaporized light fraction upwards through the catalyst bed and at least a portion of the reactive distillation column;
  - vi) condensing said light fraction to provide at least a portion of said diluting portion of acetone for subsequent mixing with said cumene 20 hydroperoxide feed;
  - vii) optionally withdrawing a portion of said light fraction as overhead from said column; and
  - viii) repeating steps i) through vii).
- 25 2. The process of claim 1 wherein steps v) and vi) are used to control dilution of the cumene hydroperoxide with acetone.
- 30 3. The process of claim 2 which comprises setting a reflux rate of acetone through said column to control dilution of cumene hydroperoxide feed.
4. The process of claim 1 wherein a flow of diluted cumene hydroperoxide

through the reactor is maintained at a rate sufficient to keep the catalyst bed wetted, thereby maintaining catalyst temperature at or near the boiling point of the liquid.

5 5. The process of claim 1 wherein said diluting portion of acetone is added to at least one of: 1) the upper portion of the distillation column, 2) the lower portion of the distillation column, upstream of said catalyst bed, and 3) the cumene hydroperoxide feed prior to its introduction to said distillation column.

10 6. The process of claim 1 wherein said diluting portion of acetone is added to the upper portion of the distillation column.

7. The process of claim 1 wherein said diluting portion of acetone is added to the lower portion of the distillation column.

15 8. The process of claim 1 wherein said diluting portion of acetone is added to the cumene hydroperoxide feed prior to its introduction to said distillation column.

20 9. The process of claim 1 wherein said diluting portion of acetone is added directly at one or more locations to the catalyst bed in an amount sufficient to reduce formation of heavy compounds having a normal boiling point greater than 182°C.

25 10. The process of claim 9 wherein said diluting portion of acetone is added to said catalyst bed in amounts sufficient to maintain the catalyst bed at a temperature at or near the boiling point of the reactant liquid to provide isothermal operation.

30 11. The process of claim 1 wherein said catalyst bed comprises a solid acid heterogeneous catalyst.

12. The process of claim 1 wherein said conditions sufficient to effect the exothermic decomposition of said cumene hydroperoxide comprise a temperature of 20 to 5 150°C and a pressure of atmospheric to 1000 psig.
13. The process of claim 1 wherein said conditions sufficient to effect the exothermic decomposition of said cumene hydroperoxide comprise a temperature of 40 to 10 120°C and a pressure of atmospheric to 400 psig.
14. An apparatus for preparing phenol from cumene hydroperoxide which 15 comprises
  - a) a reactive distillation column comprising at its upper portion a distillation column and its lower portion a catalyst bed;
  - b) a lower outlet downstream of the catalyst bed for removing high boiling bottom products comprising phenol;
  - c) an inlet at or near the bottom of said distillation column for introducing cumene hydroperoxide feed at a point upstream of said catalyst bed;
  - d) an upper outlet for removing low boiling overhead products comprising acetone;
  - e) a heat exchanger for cooling said overhead products;
  - f) an overhead products receiver for receiving cooled overhead products from said heat exchanger, having an outlet from which said overhead products are collected and/or returned to said distillation column; and
  - g) overhead products inlet at an upper portion of said distillation column for introducing overhead products reflux from said receiver.
15. The apparatus of claim 14 which further comprises an element selected 30

from the group consisting of

- h) an overhead products inlet at a lower portion of said distillation column for introducing overhead products from said receiver to said distillation column at or near said inlet for introducing cumene hydroperoxide;
- 5 i) an overhead products line which recycles overhead products to the cumene hydroperoxide feed upstream of said inlet for introducing cumene hydroperoxide; and
- j) an overhead products line which recycles overhead products to one or more portions of the catalyst bed.

10

16. The apparatus of claim 14 which further comprises an overhead products inlet at a lower portion of said distillation column for introducing overhead products from said receiver to said distillation column at or near said inlet for introducing cumene hydroperoxide.

15



17. The apparatus of claim 14 which further comprises an overhead products line which recycles overhead products to the cumene hydroperoxide feed upstream of said inlet for introducing cumene hydroperoxide.

20

18. The apparatus of claim 14 which further comprises an overhead products line which recycles overhead products to one or more portions of the catalyst bed.

25

19. The apparatus of claim 14 which further comprises a stripping section located beneath said catalyst bed.



2 / 2




FIG. 3

# INTERNATIONAL SEARCH REPORT

Int'l. Application No  
PCT/US 00/34843

<b>A. CLASSIFICATION OF SUBJECT MATTER</b>				
IPC 7 C07C39/04 C07C49/08 C07C37/08 C07C45/53				
According to International Patent Classification (IPC) or to both national classification and IPC				
<b>B. FIELDS SEARCHED</b>				
Minimum documentation searched (classification system followed by classification symbols)				
IPC 7 C07C				
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched				
Electronic data base consulted during the international search (name of data base and, where practical, search terms used)				
EPO-Internal				
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>				
Category °	Citation of document, with indication, where appropriate, of the relevant passages			Relevant to claim No.
A	EP 0 018 159 A (ICI) 29 October 1980 (1980-10-29) -----			
A	US 5 463 136 A (BLACKBOURN ROBERT L ET AL) 31 October 1995 (1995-10-31) -----			
<input type="checkbox"/> Further documents are listed in the continuation of box C.		<input checked="" type="checkbox"/> Patent family members are listed in annex.		
<p>° Special categories of cited documents :</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&amp;" document member of the same patent family</p>				
Date of the actual completion of the international search		Date of mailing of the international search report		
6 March 2001		13/03/2001		
Name and mailing address of the ISA		Authorized officer		
European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Van Geyt, J		

# INTERNATIONAL SEARCH REPORT

## Information on patent family members

International Application No

PCT/US 00/34843

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
EP 0018159	A 29-10-1980	BR 8002437 A		02-12-1980
		DE 3063046 D		16-06-1983
		ES 490709 D		16-02-1981
		ES 8103005 A		16-05-1981
		GB 2048260 A		10-12-1980
		JP 55153730 A		29-11-1980
		PL 223582 A		13-02-1981
		US 4310712 A		12-01-1982
US 5463136	A 31-10-1995	NONE		