



(51) International Patent Classification:

C10G 65/12 (2006.01) ***C10G 69/06*** (2006.01)

(21) International Application Number:

PCT/US2020/055892

(22) International Filing Date:

16 October 2020 (16.10.2020)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

16/668,566	30 October 2019 (30.10.2019)	US
------------	------------------------------	----

(71) Applicant: SAUDI ARABIAN OIL COMPANY
[SA/SA]; Box 5000, Dhahran, 31311 (SA).

(72) Inventors: and

(71) Applicants (for US only): XU, Qi [US/SA]; P. O. Box 6081, Saudi Aramco, Dhahran, 31311 (SA). **ABUDAWOUD, Raed** [SA/SA]; P. O. Box 6970, Saudi Aramco, Dhahran, 31311 (SA).

(74) **Agent: CRISPINO, Ralph, J.;** Abelman, Frayne & Schwab, 666 Third Avenue, New York, NY 10017 (US).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, IT, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW,

(54) Title: SYSTEM AND PROCESS FOR STEAM CRACKING AND PYROLYSIS FUEL OIL TREATMENT INTEGRATING SELECTIVE HYDROGENATION AND SELECTIVE HYDROCRACKING




FIG. 1

(57) Abstract: A process for treatment of PFO from a steam cracking zone includes selectively hydrogenating PFO or a portion thereof for conversion of polyaromatics compounds contained in the PFO into aromatic compounds with one benzene ring to produce a selectively hydrogenated stream. The selectively hydrogenated stream is selectively hydrocracked for selective ring opening and dealkylation to produce a selectively hydrocracked BTX+ stream. The selectively hydrocracked BTX+ stream is separated into BTX compounds. Optionally the PFO is separated into a first stream containing C9+ aromatics compounds with one benzene ring, and a second stream containing C10+ aromatic compounds, whereby the first stream containing C9+ aromatics compounds with one benzene ring is passed to the selective hydrocracking step, and the feed to the selective hydrogenation step comprises all or a portion of the



SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(84) Designated States *(unless otherwise indicated, for every kind of regional protection available):* ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:
— *with international search report (Art. 21(3))*

SYSTEM AND PROCESS FOR STEAM CRACKING AND PYROLYSIS FUEL OIL TREATMENT INTEGRATING SELECTIVE HYDROGENATION AND SELECTIVE HYDROCRACKING

BACKGROUND OF THE INVENTION

Field of the Invention

[01] The present disclosure concerns integrated processes and systems to maximize recovery of products including benzene, toluene and xylenes (BTX) from pyrolysis fuel oil (PFO) obtained from a steam cracking unit.

Description of Related Art

[02] Petrochemical refiners are facing issues with utilization of PFO streams obtained from steam cracking. Such steam cracking processes are well known and employ very high temperature, high flow rates and production of large amounts of flammable gases. The overall process conditions are set to maximize useful and valuable chemicals in the steam cracking effluent, the most desirable of which are typically light olefins. Useful and valuable products are also typically obtained from LPG and pyrolysis gasoline, commonly referred to as pygas or py-gas.

[03] The heaviest portion of the steam cracking effluents is commonly referred to as pyrolysis oil, pyrolysis fuel oil (PFO) stream, py-oil or pyoil, which is a C₉⁺ stream that contains C₉⁺ paraffins, monoaromatics, naphtho-monoaromatics, diaromatics, naphtho-diaromatics, and poly-aromatics.

[04] In steam cracking operations in which ethane or propane are used as the feedstock, the product is mainly ethene, with other products including methane, propene, butadiene, and py-gas, with relatively small quantity of PFO being produced. In steam cracking

operations in which naphtha is used as feedstock, in addition to the light olefin products, the yields of both py-gas and PFO are relatively higher as compared to ethane or propane cracking. The PFO from naphtha cracking contains C₉+ paraffins, monoaromatics including BTX components, naphtho-monoaromatics, diaromatics, naphtho-diaromatics, and to some extent poly-aromatics with more than three aromatic rings. A typical PFO from steam cracking of naphtha can be further processed conventionally, for example for naphthalene extraction or for production of carbon black (see Ristic et al., *Compositional Characterization of Pyrolysis Fuel Oil from Naphtha and Vacuum Gas Oil*, *Energy Fuels*, 2018, 32 (2), pp 1276–1286). Table 1 below shows an example of the chemical compositions of PFO streams obtained from the steam cracking of naphtha and the steam cracking of VGO, according to the data disclosed in Ristic et al., *Compositional Characterization of Pyrolysis Fuel Oil from Naphtha and Vacuum Gas Oil*, *Energy & Fuels* 32(2) · January 2018 (1276 – 1286), Table 6.

Table 1

<u>Compound name</u>	<u>PFO from naphtha cracking</u> <u>(wt %)</u>	<u>PFO from VGO cracking</u> <u>(wt %)</u>
naphthalene	12.5	3.8
1-methylnaphthalene	2.1	2.2
2-methylnaphthalene	3.7	3.3
acenaphthene	0.4	0.2
acenaphthylene	1.7	1.0
fluorene	1.1	1.0
phenanthrene	1.6	1.4
anthracene	0.3	0.4
fluoranthene	0.1	0.2
pyrene	0.4	0.3
chrysene	0.1	0.1

[05] In contrast, with steam cracking of heavier feedstocks, the PFO that is produced contains a much higher quantity of poly-aromatics having three or more aromatic rings.

For instance, in certain embodiments, PFO from steam cracking of heavy feedstocks contains at least about 20, 30, 40, 50, or 60 wt% of poly-aromatics having three or more aromatic rings. The below Table 2 shows an example of the chemical composition of a PFO stream obtained from hydroprocessing of Arab light crude oil and steam cracking of a fraction having heavy components separated, for instance cut at 540°C, from the hydroprocessed crude oil, for example, according to the process described in US Patent 9,255,230. This PFO, referred to herein as a “refractory” PFO from the steam cracking of treated crude oil or other treated heavy oil feeds, includes over 40 wt% of poly-aromatics having three or more aromatic rings, which include triaromatics, naphtheno-triaromatics, tetraaromatics, penta-aromatics and heavier poly-aromatics including asphaltenes and coke. These excessive quantities of heavier poly-aromatics are uncommon in PFO from naphtha steam cracking. In addition to the di-aromatics and tri-aromatics, the PFO also contains tetra-aromatics, penta-aromatics and heavier poly-aromatics in concentrations that exceed those from naphtha steam cracking.

Table 2

<u>Compounds</u>	<u>wt%</u>
Paraffin (C9+)	0.64
Monoaromatics	1.81
Naphtheno-monoaromatics	3.2
Diaromatics	20.26
Naphtheno-diaromatics	9.83
Triaromatics	9.59
Naphtheno-triaromatics	7.26
Tetraaromatics	5.14
Penta-aromatics	2.04
Other heavier polyaromatics	40.23
<u>Total</u>	<u>100</u>

[06] Typically, the PFO stream is a rejected stream at the bottom of the steam cracking effluent separator. The PFO stream contains various poly-aromatics including styrene,

naphthene, anthracene, bi-phenyl, and also having poly-aromatics with three or more aromatic in higher concentrations in refractory PFO compared to PFO obtained from naphtha cracking. Conventionally, PFO streams from naphtha cracking and also from cracking of heavier feeds are used and/or valued as fuel oil blending components. For instance, in economic evaluations, PFO is valued as a low sulfur fuel oil stream, which is a considerable discount compared to aromatic hydrocarbons including benzene, toluene and mixed xylenes (BTX), or benzene, toluene, ethylbenzene and mixed xylenes (BTEX).

[07] Therefore, a need exists for improved processes and systems for treatment of PFO streams to maximize recovery of BTX or BTEX compounds.

SUMMARY OF THE INVENTION

[08] The above objects and further advantages are provided by the system and process for treatment of refractory PFO from steam cracking of treated crude oil or other treated heavy oil feeds, which comprises at least 40 wt% of polyaromatics having three or more aromatic rings including triaromatics, naphtheno-triaromatics, tetraaromatics, penta-aromatics and heavier poly-aromatics including asphaltenes and coke.

[09] In certain embodiments, a process for treatment of PFO from a steam cracking zone comprises optionally separating the PFO into at least a first stream containing C₉+ aromatics compounds with one benzene ring, and a second stream containing C₁₀+ aromatic compounds. All or a portion of the PFO, or all or a portion of the second stream containing C₁₀+ aromatics compounds, is selectively hydrogenated using catalysts and conditions, including hydrogen, that are effective for conversion of polyaromatics compounds contained in the PFO into aromatic compounds with one benzene ring to produce a selectively hydrogenated stream. All or a portion of the selectively hydrogenated

stream, and optionally all or a portion of the first stream containing C₉+ aromatics compounds with one benzene ring, is selectively hydrocracked using catalysts and conditions, including hydrogen, effective for selective ring opening and dealkylation to produce a selectively hydrocracked BTX+ stream. At least a portion of the selectively hydrocracked BTX+ stream is separated into BTX compounds.

[10] In certain embodiments, a system for treatment of PFO from a steam cracking zone comprises an optional PFO separation zone having one or more inlets in fluid communication with the steam cracking zone, one or more outlets for discharging a fraction of the PFO including C₉+ aromatics compounds with one benzene ring, and one or more outlets for discharging a fraction of the PFO including containing C₁₀+ aromatic compounds. A selective hydrogenation zone includes one or more inlets in fluid communication with the steam cracking zone to receive PFO or the second outlet of the PFO separation zone to receive C₁₀+ aromatic compounds from the PFO, and hydrogen, and one or more outlets discharging reaction effluent including selectively hydrogenated aromatic compounds. A selective hydrocracking zone includes one or more inlets in fluid communication with the one or more outlets of the selective hydrogenation zone, and hydrogen, and one or more outlets for discharging reaction effluent including selectively hydrocracked BTX+ compounds. A BTX splitting zone includes one or more inlets in fluid communication with the one or more outlets of the selective hydrocracking zone for discharging reaction effluent including selectively hydrocracked BTX+ compounds, and one or more outlets for discharging BTX compounds.

[11] Still other aspects, embodiments, and advantages of these exemplary aspects and embodiments, are discussed in detail below. Moreover, it is to be understood that both the

foregoing information and the following detailed description are merely illustrative examples of various aspects and embodiments, and are intended to provide an overview or framework for understanding the nature and character of the claimed aspects and embodiments. The accompanying drawings are included to provide illustration and a further understanding of the various aspects and embodiments, and are incorporated in and constitute a part of this specification. The drawings, together with the remainder of the specification, serve to explain principles and operations of the described and claimed aspects and embodiments.

BRIEF DESCRIPTION OF THE DRAWINGS

[12] The invention will be described in further detail below and with reference to the attached drawings, and where:

FIG. 1 is a process flow diagram of an embodiment of an integrated system including steam cracking and treatment of light PFO by selective hydrogenation and selective hydrocracking to produce BTX;

FIG. 2 is a process flow diagram of an embodiment of an integrated system including steam cracking and treatment of PFO by selective hydrogenation and selective hydrocracking to produce BTX; and

FIGs. 3, 4, 5 and 6 schematically depict operations of steam cracking units integrated with feed pretreatment.

DETAILED DESCRIPTION OF THE INVENTION

[13] The phrase “a major portion” with respect to a particular stream or plural streams means at least about 50 wt% and up to 100 wt%, or the same values of another specified unit.

[14] The phrase “a significant portion” with respect to a particular stream or plural streams means at least about 75 wt% and up to 100 wt%, or the same values of another specified unit.

[15] The phrase “a substantial portion” with respect to a particular stream or plural streams means at least about 90, 95, 98 or 99 wt% and up to 100 wt%, or the same values of another specified unit.

[16] The phrase “a minor portion” with respect to a particular stream or plural streams means from about 1, 2, 4 or 10 wt%, up to about 20, 30, 40 or 50 wt%, or the same values of another specified unit.

[17] The term “crude oil” as used herein refers to petroleum extracted from geologic formations in its unrefined form. Crude oil suitable as the source material for the processes herein include any crude oil produced worldwide. Examples are Arabian Heavy, Arabian Light, Arabian Extra Light, other Gulf crudes, Brent, North Sea crudes, North and West African crudes, Indonesian, Chinese crudes, or mixtures thereof. The crude petroleum mixtures can be whole range crude oil or topped crude oil. As used herein, “crude oil” also refers to such mixtures that have undergone some pre-treatment such as water-oil separation; and/or gas-oil separation; and/or desalting; and/or stabilization. In certain embodiments, crude oil refers to any of such mixtures having an API gravity (ASTM D287 standard), of greater than or equal to about 10°, 20°, 30°, 32°, 34°, 36°, 38°, 40°, 42° or 44°.

[18] The term “C# hydrocarbons” or “C#”, is used herein having its well-known meaning, that is, wherein “#” is an integer value, and means hydrocarbons having that value of carbon atoms. The term “C#+ hydrocarbons” or “C#+” refers to hydrocarbons

having that value or more carbon atoms. The term “C#- hydrocarbons” or “C#-” refers to hydrocarbons having that value or less carbon atoms. Similarly, ranges are also set forth, for instance, C1-C3 means a mixture comprising C1, C2 and C3. When “C#”, “C#+” or “C#-” are used in conjunction with “aromatics” they represent one-ring aromatics, diaromatics and/or other polyaromatics having that value of carbon atoms, that value or more carbon atoms, or that value or less carbon atoms. As used herein in describing mixed hydrocarbon streams, “C#” is not intended to represent a sharp cut-off but rather are used for convenience to describe the carbon number of a major portion of said stream. For example, a “C5” stream generally contains a major portion of C5 components and a minor portion of C4 and C6 components.

[19] The term “petrochemicals” or “petrochemical products” refers to chemical products derived from crude oil that are not used as fuels. Petrochemical products include olefins and aromatics that are used as a basic feedstock for producing chemicals and polymers. Typical olefinic petrochemical products include, but are not limited to, ethylene, propylene, butadiene, butylene-1, isobutylene, isoprene, cyclopentadiene and styrene. Typical aromatic petrochemical products include, but are not limited to, benzene, toluene, xylene, and ethyl benzene.

[20] The term “olefin” is used herein having its well-known meaning, that is, unsaturated hydrocarbons containing at least one carbon-carbon double bond. In plural, the term “olefins” means a mixture comprising two or more unsaturated hydrocarbons containing at least one carbon-carbon double bond. In certain embodiments, the term “olefins” relates to a mixture comprising two or more of ethylene, propylene, butadiene, butylene-1, isobutylene, isoprene and cyclopentadiene.

[21] The term “BTX” as used herein refers to the well-known acronym for benzene, toluene and xylenes.

[22] The acronym “LPG” as used herein refers to the well-known acronym for the term “liquefied petroleum gas,” and generally is a mixture of C3-C4 hydrocarbons. In certain embodiments, these are also referred to as “light ends.”

[23] The term “naphtha” as used herein refers to hydrocarbons boiling in the range of about 20-205, 20-193, 20-190, 20-180, 20-170, 32-205, 32-193, 32-190, 32-180, 32-170, 36-205, 36-193, 36-190, 36-180 or 36-170°C.

[24] The term “light naphtha” as used herein refers to hydrocarbons boiling in the range of about 20-110, 20-100, 20-90, 20-88, 32-110, 32-100, 32-90, 32-88, 32-80, 36-110, 36-100, 36-90, 36-88 or 36-80°C.

[25] The term “heavy naphtha” as used herein refers to hydrocarbons boiling in the range of about 80-205, 80-193, 80-190, 80-180, 80-170, 88-205, 88-193, 88-190, 88-180, 88-170, 90-205, 90-193, 90-190, 90-180, 90-170, 93-205, 93-193, 93-190, 93-180, 93-170, 100-205, 100-193, 100-190, 100-180, 100-170, 110-205, 110-193, 110-190, 110-180 or 110-170°C.

[26] In certain embodiments naphtha, light naphtha and/or heavy naphtha refer to such petroleum fractions obtained by crude oil distillation, or distillation of intermediate refinery processes as described herein.

[27] The terms “pyrolysis gasoline” and its abbreviated form “py-gas” are used herein having their well-known meaning, that is, thermal cracking products generally including aromatic, olefinic and paraffinic hydrocarbons in the range of C5s to C9s or even including

C10, C11 and even some C12 hydrocarbons, for instance having an end boiling point in the range of about 170-210 or 170-215°C

[28] The terms “pyrolysis oil” and its abbreviated form “py-oil,” and “pyrolysis fuel oil” and its abbreviated form “PFO,” are used herein having their well-known meaning, that is, a heavy oil fraction, C9+, that is derived from steam cracking.

[29] The terms “light pyrolysis oil” and its acronym “LPO” as used herein in certain embodiments refer to pyrolysis oil having an end boiling point of about 340, 360, 380 or 400°C.

[30] The terms “heavy pyrolysis oil” and its acronym “HPO” as used herein in certain embodiments refer to pyrolysis oil having an initial boiling point of about 340, 360, 380 or 400°C.

[31] The embodiments herein include processes and systems that integrate steam cracking with treatment of the PFO obtained from such steam cracking operations. The steam cracking feedstock can be selected from a treated crude oil stream and other treated heavy oil streams such as those in the atmospheric gas oil range, atmospheric residue range, vacuum gas oil range and/or vacuum residue range. The steam cracking feed is treated prior to steam cracking by hydroprocessing / hydrotreating and/or solvent deasphalting. The rejected PFO bottoms stream from the steam cracking unit contains large amount of polyaromatics (for example, with polyaromatics having an average molecular weight that varies between about 150 to 300 kg/kmol and higher), and is conventionally recovered as PFO for use as a fuel oil component. In the process disclosed herein, the PFO obtained from steam cracking of treated crude oil or other treated heavy oil feed is referred to as “refractory PFO.” This refractory PFO contains a very high amount of polyaromatics, for

instance, at least about 20, 30, 40, 50, or 60 wt% of poly-aromatics having three or more aromatic rings, and total poly-aromatics composition of at least about 50, 60, 70, 80, 90, or 94 wt%. The PFO is considered “refractory” due to its high content of polyaromatics hydrocarbons and heavier molecular weight components.

[32] Refractory PFO is used as feedstock to produce additional BTX/BTEX, and co-produced LPG is recycled to the steam cracking zone as additional feed. BTX/BTEX production and refractory PFO treatment are integrated to minimize loss of aromatics to a fuel oil stream and maximize steam cracking feed. Overall operation efficiencies of steam cracking processes are increased. By converting the polyaromatics into useful chemical building blocks BTX/BTEX rather than combusting them as part of fuel oil, additional higher value products can be obtained from the integrated processes and systems herein. Further, co-produced LPG, and in certain embodiments naphtha-range byproducts, serve as additional steam cracker feed. These co-produced components can be introduced before hydroprocessing of the initial feed, before steam cracking of the hydroprocessed feed, or within the steam cracking. In certain operations, co-produced LPG, and in certain embodiments naphtha-range byproducts components, can pass to a pyrolysis section combined with heated hydroprocessed feed from a convection section of a steam cracking unit so that the light components bypass the convection section. In certain operations, co-produced LPG, and in certain embodiments naphtha-range byproducts components can pass to the convection section with the feed to the steam cracking unit.

[33] FIGs. 1 and 2 are process flow diagrams of embodiments of integrated steam cracking processes and systems including refractory PFO treatment. The systems generally include a steam cracker/separation zone **10**; a PFO treatment zone **20** including a selective

hydrogenation zone **30**, an optional separation zone **36**, a selective hydrocracking zone **42**, and a BTX splitting zone **56**; and a gas treatment zone **74**. In certain embodiments, a trans-alkylation zone **66** is also integrated in the PFO treatment zone **20**. In the embodiment of FIG. 1 the PFO treatment zone **20** also includes a refractory PFO separation zone **22**.

[34] The steam cracking reaction and separation zone is schematically shown at **10**. The steam cracking reaction and separation zone includes heaters, furnaces, separation vessels and auxiliary units for steam cracking of an initial steam cracking feed **12** and recycle streams (including LPG and in certain embodiments one or more naphtha streams) created during one or more PFO treatment steps disclosed herein, for production of one or more mixed hydrocarbon product streams, and for separation generally into light gases, olefins, pygas and PFO. The steam cracking reaction separation occurs as is commonly known, for instance, using primary fractionating, quench separation and olefins recovery to generally obtain one or more C2, C3 and/or C4 olefins streams **14**, a pygas (C5-C9 range) stream **16** and a PFO (C9+) stream **18**. In operations in which the steam cracker is operable to treat an initial stream **12** including or consisting of treated crude oil and/or heavy feedstocks, a refractory PFO stream **18** is produced that is processed in accordance with embodiments described herein.

[35] In the embodiments of FIG. 1, the steam cracking reaction and separation zone **10** is in fluid communication with the separation zone **22** to separate the PFO stream **18** into a first stream **24** containing C9+ aromatics compounds with one benzene ring (a “one-ring C9+” stream), a second stream **26** containing C10+ aromatics compounds with no less than 2 and up to 6 (typically between 2 and 4) benzene rings (a “two-ring C10+” stream), and a third stream **28** containing heavy C20+ polyaromatics such as those having 6 or more

benzene rings (a “poly C20+” stream). In certain embodiments, a substantial portion, a significant portion or a major portion of PFO stream **18** produced from the steam cracking zone **10** is passed to the separation zone **22**. The separation zone **22** can include one or more flash vessels and/or one or more simple or fractional distillation columns. Recovered streams from the separation zone **22** include the one-ring C9+ stream **24** containing hydrocarbons having a lower limit in the range of about 130-150°C and an upper limit in the range of about 165-215°C, for instance, about 130-215, 140-215, 150-215, 130-180, 140-180, 150-180, 130-175, 140-175, 150-175, 130-165, 140-165 or 150-165°C, the two-ring C10+ stream **26** containing hydrocarbons having a lower limit in the range of about 165-215°C and an upper limit in the range of about 350-430, for instance about 165-430, 175-430, 180-430, 215-430, 165-400, 175-400, 180-400, 215-400, 165-375, 175-375, 180-375, 215-375, 165-350, 175-350, 180-350, or 215-350°C, and the poly C20+ stream **28** containing hydrocarbons boiling above about the range of about 350-430, for instance above about 350, 375, 400 or 430°C.

[36] The separation zone **22** is in fluid communication with the selective hydrocracking zone **42** to pass all or a portion of the one-ring C9+ stream **24**, bypassing the selective hydrogenation zone **30**. In certain embodiments, a substantial portion, a significant portion or a major portion of the one-ring C9+ stream **24** is passed from the separation zone **22** to the selective hydrocracking zone **42**. The separation zone **22** is in fluid communication with the selective hydrogenation zone **30** to pass all or a portion of the two-ring C10+ stream **26** (also referred to as a light PFO two-ring C10+ stream). In certain embodiments, a substantial portion, a significant portion or a major portion of the two-ring C10+ stream **26** is passed from the separation zone **22** to the selective hydrogenation zone **30**. In certain

embodiments, the separation zone **22** is in fluid communication with a fuel oil pool or the initial feed treatment zone upstream of the steam cracker to pass all or a portion of the poly C20+ stream **28** (also referred to as a heavy PFO poly C20+ stream) for processing outside of the integrated system, for instance in a fuel oil blending step (not shown), or as a recycle stream to the initial feed treatment zone. In certain embodiments, all, a substantial portion, a significant portion or a major portion of the poly C20+ stream **28** is recycled to the initial feed treatment zone upstream of the steam cracker.

[37] In certain embodiments (shown in dashed lines), the separation zone **22** is in fluid communication with the selective hydrogenation zone **30** to pass all or a portion of the poly C20+ stream **28**. In embodiments in which all of the poly C20+ stream **28** is passed to the selective hydrogenation zone **30**, the separation zone **22** may be operable to separate the PFO C9+ stream **18** into a one-ring C9+ stream **24** and a combined stream **26/28**, containing the two-ring C10+ aromatic fraction with all components of the previously described two-ring C10+ stream **26** and the poly C20+ stream **28**. The combined stream **26/28** is routed to the selective hydrogenation zone **30**. In certain embodiments, a substantial portion, a significant portion or a major portion of the poly C20+ stream **28** is routed to the selective hydrogenation zone **30**. In certain embodiments, 50-90 wt% of the poly C20+ stream **28** is routed to the selective hydrogenation zone **30**.

[38] In certain embodiments, with reference to FIG. 2, the separation zone **22** shown in FIG. 1 is not used, so that all or a portion of the full range of the C9+ PFO stream **18** is sent to the selective hydrogenation zone **30**. In certain embodiments, a substantial portion, a significant portion or a major portion of the full range of the C9+ PFO stream **18** is routed

to the selective hydrogenation zone **30**. In these embodiments, the full range of PFO including heavy aromatics is sent through the selective hydrogenation zone **30**.

[39] The selective hydrogenation zone **30** is in fluid communication with stream **26**, stream **26** and all or a portion of stream **28**, or stream **18**. The selective hydrogenation zone **30** contains one or more reactors in series or parallel arrangement operating under conditions effective for, and using catalyst effective for, selective hydrogenation of the polyaromatics compounds contained in stream **26**, stream **26** and all or a portion of stream **28**, or stream **18**. A hydrogen stream **32** is in fluid communication with the reactor(s) at one or more locations as is known, and can be derived from recycled hydrogen from the integrated steam cracking unit (not shown in FIGs. 1 and 2) and produced hydrogen **76** from the gas treatment zone **74**. A make-up hydrogen stream from another source (not shown) can also be in fluid communication with the reactor(s) at one or more locations as is known. Reaction conditions are set in the selective hydrogenation zone **30** to maximize the conversion of polyaromatics, such as naphthalene, methylnaphthalene, anthracene, naphtheno-diaromatics (three rings, one saturated and two aromatic), by selective hydrogenation into aromatic compounds with one benzene ring. The catalysts used in the selective hydrogenation zone can be, for instance, an acid or metal catalyst, and in certain embodiments dual functionality catalyst materials or a combination of catalyst materials having different functionalities of cracking and hydrogenation. An effluent stream **34** from the selective hydrogenation zone **30** contains one-ring C9+ aromatic compounds (also referred to as a “one-ring C9+ stream”), for instance, in a concentration range of about 30-90, 30-80, 30-70, 50-90, 50-80 or 50-70 wt% based on the total feed to the selective hydrogenation zone **30**. LPG is a byproduct of this selective hydrogenation process LPG,

and can be recovered together with hydrogen and other gases can (described below) or passed to the selective hydrocracking zone **42** as part of the effluent stream **34**.

[40] The selective hydrocracking zone **42** is in fluid communication with the effluent stream **34** from the selective hydrogenation zone **30**. The selective hydrocracking zone **42** contains one or more reactors in series or parallel arrangement operating under conditions effective for, and using catalyst effective for, selective ring opening functions and hydrodealkylation functions, targeting aromatic compounds with one benzene ring and producing an effluent product stream **46** that is passed to the BTX splitting zone **56**. A hydrogen stream **44** is in fluid communication with the reactor(s) at one or more locations as is known, and can be derived from sources including recycled hydrogen from the integrated steam cracking unit (not shown in FIGs. 1 and 2) and hydrogen **76** from the gas treatment zone **74**. A make-up hydrogen stream from another source (not shown) can also be in fluid communication with the reactor(s) at one or more locations as is known. Reaction conditions are set in the selective hydrocracking zone **42** to maximize the selective ring opening (preserving the aromatic ring structure) into benzene, toluene, and xylenes (BTX), and/or ethylbenzene. The effluent product stream **46** containing BTX and other generally heavier components is sent to the BTX splitting zone **56** for separation. LPG is a byproduct of this selective hydrocracking process and is recovered typically in combination with hydrogen and other gases, as a light gas stream **48**. Conditions and catalysts are selected in the selective hydrocracking zone **42** to minimize production of non-aromatic naphtha range products, and any naphtha including light naphtha in the effluent **46** can be passed to the BTX splitting zone **56**. In operations in which appreciable

naphtha is formed, it can be passed to the steam cracking zone **10** as additional feed (not shown).

[41] In certain embodiments, the separation zone **36** is included between the selective hydrogenation zone **30** and the selective hydrocracking zone **42** for separation of the light gases, stream **38** including LPG and H₂, from the remainder of the one-ring C₉+ effluent stream **34**, stream **40**. In certain embodiments, the separation zone **36** can be a fractionator associated with the selective hydrogenation reactor which operates similarly to a fractionator conventionally used in conjunction with a hydroprocessing zone. The LPG/H₂ stream **38** is passed to the gas treatment zone **74**. The one-ring C₉+ stream **40** having a light gas stream **38** removed is routed to the selective hydrocracking zone **42**.

[42] In certain embodiments, conditions and catalysts are selected in the selective hydrogenation zone **30** to minimize production of non-aromatic naphtha range products, and any naphtha including light naphtha is passed with the effluent stream **34** to the selective hydrocracking zone **42**. In further embodiments, naphtha that is formed can be separated in the separation zone **36**, and a separated naphtha stream can be in fluid communication with the steam cracking zone **10** as additional feed (not shown).

[43] In embodiments in which the separation zone **36** is not used, all or a portion of the one-ring C₉+ effluent stream **34** can be routed to the selective hydrocracking zone **42** with the gases, that is, so that the gases are separated with the light gas stream **48** from the selective hydrocracking zone **42** and passed to the gas treatment zone **74**.

[44] In certain embodiments, all or some of the gas treatment steps for the LPG/H₂ stream **38** and the light gas stream **48**, or the light gas stream **48** (in embodiments in which the separation zone **36** is not used), is accomplished by a separate gas treatment zone **74** as

shown, or alternatively with other gas treatment operations. In certain embodiments, recovered hydrogen 76 is passed to hydrogen users in the integrated process and system. In certain embodiments, an LPG stream 78 obtained from stream 38 (as shown via the gas treatment zone 74) is passed to the steam cracker as additional feed (not shown). In other embodiments, the light gas streams 38 and 48, or stream 48, can be routed to gas treatment operations associated with the steam cracking and separation zone and/or gas treatment operations within a hydroprocessing unit used for treatment of the initial feed upstream of the steam cracking zone (not shown).

[45] In certain optional embodiments (shown in dashed lines), the effluent 46 can be passed to an aromatics separation unit 50, whereby an aromatics rich stream 52 (typically an extract stream) is passed to the BTX splitting zone 56, and an aromatics lean stream 54 (typically a raffinate stream) which can include C5 and non-aromatic C6 components (light wild naphtha) is separately processed. In certain embodiments, all, a substantial portion, a significant portion or a major portion of the aromatics lean stream 54 is recycled to the steam cracking zone 10.

[46] The BTX splitting zone 56 separates the BTX+ stream 46 from the selective hydrocracking zone 42 into a BTX product stream 58, which can be one or more streams that are typically passed to a BTX complex (not shown) for separation into C6, C7 and C8 streams, benzene, toluene and one more xylene products (BTX), and in certain embodiments benzene, toluene, one more xylene products and ethylbenzene (BTXE). The BTX splitting zone 56 can include one or more simple or fractional distillation columns.

[47] In certain optional embodiments (shown in dashed lines), the BTX splitting zone 56 is operable to remove at least a portion of non-aromatic content from BTX+ stream 46,

for instance by including an aromatics extraction step, and an aromatics lean stream **60** (typically a raffinate stream) which can include non-aromatic components, including C5 and non-aromatic C6 components (light wild naphtha), is recovered and separately processed. In certain embodiments, all, a substantial portion, a significant portion or a major portion of the aromatics lean stream **60** is recycled to the steam cracking zone **10**.

[48] In other optional embodiments, the aromatics separation unit **50** is included upstream of the BTX splitting zone **56** for removing the aromatics lean stream **54** containing non-aromatic components from the feeds to the BTX splitting zone **56**, including C5 and non-aromatic C6 components (light wild naphtha), and the aromatics rich stream **52** is passed to the BTX splitting zone **56**.

[49] In certain embodiments, a C9 stream **62** is recovered, which includes trimethylbenzene, methylethylbenzene, and other C9 compounds. In additional embodiments, the C9 stream **62** is passed to a transalkylation zone **66** to further produce BTX via transalkylation reactions, shown as a BTX stream **70**.

[50] A heavy product stream **64** from the BTX splitting zone **56** (a C10+ fraction) can be purged as stream **64(p)** and used, for instance, as fuel oil, recycled back to the selective hydrocracking zone **42** for further conversion as stream **64(r)**, recycled to the initial feed treatment zone upstream of the steam cracker (not shown), recycled to the steam cracker (not shown), or a combination of these. In certain embodiments, all, a substantial portion, a significant portion or a major portion of the heavy product stream **64** recycled as stream **64(r)** to the selective hydrocracking zone **42** for further conversion into BTX and C9s. In certain embodiments, all, a substantial portion, a significant portion or a major portion of the heavy product stream **64** recycled to the initial feed treatment zone upstream of the

steam cracker. In certain embodiments, all, a substantial portion, a significant portion or a major portion of the heavy product stream **64** recycled to the steam cracker.

[51] In embodiments in which a transalkylation step is integrated, the transalkylation zone **66** operates in the presence of hydrogen, stream **68**, to catalytically convert the C₉+ aromatic stream **62** into additional BTX components, stream **70**, through transalkylation and disproportionation reactions. In certain embodiments (not shown) all or a portion of benzene and/or toluene recovered from stream **58**, or benzene and/or toluene from another source, is also introduced to the transalkylation zone **66** for production of additional xylenes. In the integrated process and system herein, the light gases by-product stream **72** from the transalkylation zone **66**, including C₁-C₄ and hydrogen, is routed to the gas treatment zone **74** (or alternatively to the steam cracker/separation zone **10**, not shown), and the effluent stream **70** containing BTX is passed back to the BTX splitting zone **56**. In certain optional embodiments, the effluent stream **70** is passed to an aromatics extraction step within the BTX splitting zone **56** and non-aromatic components are included with an aromatics lean stream **60**. In certain optional embodiments, the effluent stream **70** can be passed to an aromatics separation unit, for instance unit **50** or a separate extraction unit, whereby an aromatics rich stream (typically an extract stream) is passed back to the BTX splitting zone **56**, and an aromatics lean stream (typically a raffinate stream), which can include C₅ and non-aromatic C₆ components (light wild naphtha), is recovered and separately processed. In certain embodiments, all, a substantial portion, a significant portion or a major portion of the aromatics lean stream derived from the transalkylation effluent stream **70** is recycled to the steam cracking zone **10**.

[52] The gas treatment zone 74 collects light gas streams from the integrated process and system including from the transalkylation zone (stream 72), from the selective hydrogenation zone (stream 38 from the optional separation zone 36), and/or from the selective hydrocracking zone (stream 48). The gas treatment zone 74 can be a suitable known system including hydrogen purification units, such as a pressure swing adsorption (PSA) unit to obtain a hydrogen stream 76 having a purity of 99.9%+, or a membrane separation unit to obtain a hydrogen stream 76 with a purity of about 95%. In certain embodiments, the gas treatment zone 74 is also configured and arranged for recovery of naphtha range products, such as light naphtha. LPG and heavier components, stream 78, is passed to the steam cracking zone 10. Recovered hydrogen, stream 76, is sent to one or more of the hydrogen users in the integrated process and system.

[53] Steam pyrolysis is a relatively complex process employing very high temperatures, high flow rates and production of large amounts of flammable gases. Steam cracker arrangements are well known and typically include several furnaces which are divided in a radiation (or pyrolysis) section, and a convection section. In a typical configuration, vaporization of the feed occurs in the convection section, recovering the flue gases heat from the radiation section. Vaporization is facilitated by mixing the hydrocarbons and steam. Steam is also produced in the convection section. Typically steam to oil ratio values range from about 0.3:1.0 to about 1.0:1.0, with the lower end suitable for lighter feeds such as ethane and the higher end suitable for heavier feeds. In steam cracking of heavier feeds including treated crude oil, the steam to oil ratio can be as high as 1:0:1:0 to 5:0:1:0. Steam cracker furnaces maximize recovery of flue gas energy via production of high pressure

steam, which can be recovered for use elsewhere in the refinery and/or petrochemical operations.

[54] The thermal cracking reactions occur mainly in the radiation section, typically at a set of coils. The number and shape of coils depend of the type of feed, and varies, for instance, depending on the selected configuration. Hydrocarbon steam cracking is an endothermic reaction that commences at coil inlet temperature (CIT), for instance, in the range of about 600-650°C, and finishes at a coil outlet temperature (COT), for instance, in the range of about 800-850°C. The values of the CIT and COT vary, for instance, +/- 25%, based on factors such as the severity of the operation, the type of feed and the selected configuration. The furnaces are followed in the process by a temperature quench down targeting to halt thermal cracking reactions and to avoid recombination of olefins. Following quenching the coil effluent is routed to a separation section to produce hydrogen, which is can be recovered for use elsewhere in the refinery and/or petrochemical operations or used as fuel gas in the steam cracker furnaces, methane which is used as fuel gas in the steam cracker furnaces, ethylene as desired olefin product, propylene as desired olefin product, a mix of C4 olefins (butadiene, isobutene, butenes) and normal and iso butanes, a pyrolysis gasoline stream rich in aromatics and a PFO stream. Purified hydrogen gas can also be recovered with an integrated hydrogen purification system, for instance using a pressure swing adsorption (PSA) unit to obtain a hydrogen stream having a purity of 99.9%+, or a membrane separation unit to obtain a hydrogen stream with a purity of about 95%. In certain embodiments, the gas treatment zone **74** described above associated with the PFO treatment steps could be integrated with gas treatment operations for steam cracker products.

[55] Units that are included in separation section include a primary fractionator after quench, water tower(s), gas compressor(s), a cold box and a series of distillations columns such as a demethanizer, deethanizer, ethylene-ethane splitter, depropanizer and propane-propylene splitter. The ethane and propane produced are typically recycled to the furnaces to extinction.

[56] While a generalized description is provided above for steam cracking, it should be appreciated that other arrangements and conditions used for thermal cracking that produce the refractory PFO streams described herein can benefit from integration of the PFO treatments steps herein. In certain embodiments the feed to the steam cracker can be part of an integrated process and system as disclosed in commonly owned US Patents 9,255,230 (and its related US Patents 9,587,185 and 10,017,704), 9,284,497 (and its related US Patent 10,221,365), 9,279,088 (and its related US Patent 10,329,499), 9,296,961 (and its related US Patent 10,344,227), 9,284,502 (and its related US Patent 10,246,651), 9,382,486 (and its related US Patent 10,233,400), 9,228,139, 9,228,140, 9,228,141 and 9,284,501 (and its related US Patents 9,771,530 and 10,011,788), which are all incorporated by reference herein in their entireties.

[57] In certain embodiments, a crude oil stream is fed to a hydrotreating zone, such as a fixed bed or slurry bed reactor in the presence of hydrogen, where the crude oil is hydrotreated to remove S, N, and other impurities. The gas and liquid product are separated, and a stripper is used to remove H₂S and NH₃ from other gas products. In certain embodiments of the processes disclosed in the above-mentioned commonly owned patents, treated crude oil is used as the feedstock to a steam cracker. In certain embodiments of the processes disclosed in the above-mentioned commonly owned patents, a heavy fraction of

treated crude oil is used as steam cracker feedstock. In certain embodiments, a feedstock hydroprocessing zone carries out selective hydroprocessing or hydrotreating of the initial feed that can increase the paraffin content (or decrease the BMCI) of a feedstock by saturation followed by mild hydrocracking of aromatics, especially polyaromatics. In certain embodiments, when hydrotreating a crude oil or other heavy oil feed, contaminants such as metals, sulfur and nitrogen can be removed by passing the feedstock through a series of layered catalysts that perform the catalytic functions of demetallization, desulfurization and/or denitrogenation, for example as disclosed in commonly owned US Patent 9,255,230 (and its related US Patents 9,587,185 and 10,017,704). In certain embodiments, hydrotreating a crude oil or other heavy oil feed to remove contaminants such as metals, sulfur and nitrogen is accomplished by slurry hydroprocessing as disclosed in commonly owned US Patent 9,284,501 (and its related US Patents 9,771,530 and 10,011,788). In certain embodiments, hydrotreating a crude oil or other heavy oil feed to remove contaminants such as metals, sulfur and nitrogen is preceded by solvent deasphalting, as disclosed in commonly owned US Patent 9,284,502 (and its related US Patent 10,246,651). In certain embodiments, the hydroprocessed effluent from hydrotreating a crude oil or other heavy oil feed to remove contaminants such as metals, sulfur and nitrogen is subjected to solvent deasphalting, as disclosed in commonly owned US Patent 9,382,486 (and its related US Patent 10,233,400).

[58] For instance, in one embodiment, a crude oil or other heavy oil feedstock and an effective amount of hydrogen, are charged to a hydroprocessing reaction zone operating generally at a temperature in the range of from 300-450°C. In certain embodiments, the hydroprocessing reaction zone includes one or more unit operations. In certain

embodiments, the feed is crude oil and the operations are as described in commonly owned US Patent Publication 2011/0083996 and in PCT Patent Application Publications WO2010/009077, WO2010/009082, WO2010/009089 and WO2009/073436, all of which are incorporated by reference herein in their entireties. The crude oil feedstock hydroprocessing zone can include one or more beds containing an effective amount of hydrodemetallization catalyst, and one or more beds containing an effective amount of hydroprocessing catalyst having hydrodearomatization, hydrodenitrogenation, hydrodesulfurization and/or hydrocracking functions. In additional embodiments the feedstock hydroprocessing zone includes more than two catalyst beds. In further embodiments a feedstock hydroprocessing zone includes plural reaction vessels each containing one or more catalyst beds, for example, of different function. The reaction vessels(s) in the feedstock hydroprocessing zone operates under parameters effective to hydrodemetallize, hydrodearomatize, hydrodenitrogenate, hydrodesulfurize and/or hydrocrack the crude oil feedstock. In certain embodiments, hydroprocessing is carried out using the following conditions: operating temperature in the range of from about 300-450°C; operating pressure in the range of from about 30-180 kg/cm²; and a liquid hour space velocity in the range of from 0.1-10 h⁻¹. In embodiments using crude oil as the initial feed to the feedstock hydroprocessing zone, certain advantages are realized as compared to the same hydroprocessing unit operation employed for atmospheric residue. For instance, at a start of run temperature in the range of 370-375°C, the deactivation rate is around 1°C per month. In contrast, if residue were to be processed, the deactivation rate would be closer to about 3 to 4°C per month. The treatment of atmospheric residue typically employs pressure of around 200 kg/cm² whereas the present process in which

crude oil is treated can operate at pressures as low as 100 kg/cm^2 . Additionally, to achieve the high level of saturation required for the increase in the hydrogen content of the feed, this process can be operated at a high throughput when compared to atmospheric residue. The LHSV can be as high as 0.5 hr^{-1} while that for atmospheric residue is typically 0.25 hr^{-1} . The deactivation rate when hydroprocessing crude oil is going in the inverse direction from that which is usually observed. Deactivation at low throughput (0.25 hr^{-1}) is $4.2 \text{ }^\circ\text{C}$ per month and deactivation at higher throughput (0.5 hr^{-1}) is $2.0 \text{ }^\circ\text{C}$ per month; this can be attributed to the washing effect of the catalyst.

[59] Reactor effluents from the feedstock hydroprocessing zone are typically cooled in an exchanger and sent to a high pressure cold or hot separator. Separator tops are cleaned in an amine unit and the resulting hydrogen rich gas stream is passed to a recycling compressor and can be used as a recycle gas in the feedstock hydroprocessing reaction zone. Separator bottoms from the high pressure separator, which are in a substantially liquid phase, are cooled and then introduced to a low pressure cold separator. Remaining gases, including hydrogen, H_2S , NH_3 and any light hydrocarbons, which can include C_1 - C_4 hydrocarbons, can be conventionally purged from the low pressure cold separator and sent for further processing, such as flare processing or fuel gas processing. In certain embodiments of the present process, hydrogen is recovered by combining low pressure separator gases with gases in the steam cracker products. The hydroprocessed effluent contains a reduced content of contaminants (such as metals, sulfur and nitrogen), an increased paraffinicity, reduced BMCI, and an increased American Petroleum Institute (API) gravity.

[60] In one embodiment, the sequence of catalysts to perform hydrodemetallization (HDM) and hydrodesulfurization (HDS) is as follows: (i) A hydrodemetallization catalyst. The catalyst in the HDM section are generally based on a gamma alumina support, with a surface area of about 140 – 240 m²/g. This catalyst is best described as having a very high pore volume, for example, in excess of 1 cm³/g. The pore size itself is typically predominantly macroporous. This is required to provide a large capacity for the uptake of metals on the catalysts surface and optionally dopants. Typically, the active metals on the catalyst surface are sulfides of nickel and molybdenum in the ratio Ni/Ni+Mo < 0.15. The concentration of nickel is lower on the HDM catalyst than other catalysts as some nickel and vanadium is anticipated to be deposited from the feedstock itself during the removal, acting as catalyst. The dopant used can be one or more of phosphorus (see, for example, US Patent Publication US 2005/0211603 which is incorporated by reference herein), boron, silicon and halogens. The catalyst can be in the form of alumina extrudates or alumina beads. In certain embodiments alumina beads are used to facilitate un-loading of the catalyst HDM beds in the reactor as the metals uptake will range between from 30 to 100 % at the top of the bed. (ii) An intermediate catalyst can also be used to perform a transition between the HDM and HDS function. It has intermediate metals loadings and pore size distribution. The catalyst in the HDM/HDS reactor is essentially alumina based support in the form of extrudates, optionally at least one catalytic metal from the Periodic Table of the Elements IUPAC Group 6 (for example, molybdenum and/or tungsten), and/or at least one catalytic metal from the Periodic Table of the Elements IUPAC Groups 9 or 10 (for example, nickel and/or cobalt). The catalyst also contains optionally at least one dopant selected from boron, phosphorous, halogens and silicon. Physical properties

include a surface area of about 140 – 200 m²/g, a pore volume of at least 0.6 cm³/g and pores which are mesoporous and in the range of 12 to 50 nm. (iii) The catalyst in the HDS section can include those having gamma alumina based support materials, with typical surface area towards the higher end of the HDM range, for example about ranging from 180 – 240 m²/g. This required higher surface for HDS results in relatively smaller pore volume, for example, lower than 1 cm³/g. The catalyst contains at least one element from the Periodic Table of the Elements IUPAC Group 6, such as molybdenum and at least one element from the Periodic Table of the Elements IUPAC Groups 9 or 10, such as nickel. The catalyst also comprises at least one dopant selected from boron, phosphorous, silicon and halogens. In certain embodiments cobalt is used to provide relatively higher levels of desulfurization. The metals loading for the active phase is higher as the required activity is higher, such that the molar ratio of Ni/Ni+Mo is in the range of from 0.1 to 0.3 and the (Co+Ni)/Mo molar ratio is in the range of from 0.25 to 0.85. (iv) A final catalyst (which could optionally replace the second and third catalyst) is designed to perform hydrogenation of the feedstock (rather than a primary function of hydrodesulfurization), for instance as described in Appl. Catal. A General, 204 (2000) 251. The catalyst will be also promoted by Ni and the support will be wide pore gamma alumina. Physical properties include a surface area towards the higher end of the HDM range, for example, 180 – 240 m²/g This required higher surface for HDS results in relatively smaller pore volume, for example, lower than 1 cm³/g.

[61] In certain embodiments the bottoms stream from the low pressure cold separator is the feed to the steam pyrolysis zone. In additional embodiments, bottoms from the low pressure separator are sent to a separation zone wherein heavy materials such as those in

the atmospheric or vacuum residue range are removed from the system, and the remainder is passed to the steam pyrolysis zone. In further embodiments, bottoms from the low pressure separator are sent to a separation zone wherein a light portion bypasses all or a portion of the steam pyrolysis zone, and a heavy portion serves as feed to a convection section of a steam pyrolysis zone. The separation zone can include a suitable separation unit operation such as a flash vessel or distillation column that separates based on boiling point, a separation device based on physical or mechanical separation of vapors and liquids, or a combination including at least one of these types of devices.

[62] FIGs. 3-6 schematically depict embodiments of steam cracking systems integrating pretreatment of the feed. The steam cracking zone **10** operates as described above and is schematically shown as including a steam cracking convection section **102** and a steam cracking pyrolysis section **112**. The steam cracking feed **12** (which can be a hydroprocessed initial feed **126** as in FIG. 3; a hydroprocessed initial feed having a bottom fraction removed, stream **136** as in FIG. 4; a hydroprocessed initial feed having tops removed, stream **144** as in FIG. 5; or a deasphalted stream **156** as in FIG. 6) is passed to the steam cracking convection section **102** along with steam for vaporization of the feed. A heated stream **104** is passed to the steam cracking pyrolysis section **112** for thermal cracking reactions and to produce a thermally cracked mixed product stream **114**. In certain embodiments, a separation zone **106** is included between the steam cracking convection section **102** and the steam cracking pyrolysis section **112**. A light portion, stream **108** from the separation zone **106**, is passed to the steam cracking pyrolysis section **112**, and a heavy portion **110** is discharged. The thermally cracked mixed product stream **114** is passed to a steam cracking effluent separation zone **116** which can operate as is

commonly known, for instance, using primary fractionating, quench separation and olefins recovery to generally obtain one or more C2, C3 and/or C4 olefins streams **14**, a pygas (C5-C9 range) stream **16** and a PFO (C9+) stream **18**. In certain embodiments, the steam cracking effluent separation zone **116** also includes or is integrated with a suitable hydrogen purification units, such as a pressure swing adsorption (PSA) unit to obtain a hydrogen stream **118** having a purity of 99.9%+, or a membrane separation unit to obtain a hydrogen stream **118** with a purity of about 95%. Methane (not shown) can also be recovered and used as fuel gas in the steam cracker furnaces or other fuel gas users within the integrated system. The PFO stream **18** is passed to a PFO treatment zone **20**.

[63] In one embodiment, with reference to FIG. 3, a schematic process flow diagram of a feedstock hydroprocessing zone and a steam cracking zone is shown, including a feedstock hydroprocessing zone **122** for treating an initial feedstock **120** (and optionally a recycle stream **64(r)** as described herein) in the presence of hydrogen, shown as hydrogen stream **124**, to produce a hydroprocessed effluent stream **126** that serves as the steam cracking feed **12**. As noted herein, the effluent can be subjected to a high pressure cold or hot separator to obtain a hydrogen rich gas stream that is used as a recycle gas in the reactor of the feedstock hydroprocessing zone **122**. A separator bottoms stream from the high pressure separator, in a substantially liquid phase, is cooled and then introduced to a low pressure cold separator. A separator bottoms stream from the low pressure separator, in a substantially liquid phase, is the stream **126** that serves as the steam cracking feed **12**.

[64] In another embodiment, with reference to FIG. 4, a schematic process flow diagram of a feedstock hydroprocessing zone and a steam cracking zone is shown, including a feedstock hydroprocessing zone **122** for treating an initial feedstock **120** (and optionally a

recycle stream **64(r)** as described herein) in the presence of hydrogen, shown as hydrogen stream **124**, to produce a hydroprocessed effluent stream **126**. The hydroprocessed effluent is passed to a separation zone **132** upstream of the steam cracking zone to remove heavy components such as residual range components as a stream **134**, and the remainder of the bottomless feed, in certain embodiments bottomless crude oil, stream **136**, serves as the steam cracking feed **12**. The hydroprocessed effluent can be subjected to a high pressure cold or hot separator to obtain a hydrogen rich gas stream that is used as a recycle gas in the reactor of the feedstock hydroprocessing zone **122**. A separator bottoms stream from the high pressure separator, in a substantially liquid phase, is cooled and then introduced to a low pressure cold separator. A separator bottoms stream from the low pressure separator, in a substantially liquid phase, is the stream **126** that is passed to the separation zone **132** to remove residual range components as a heavy stream **134**; the remaining stream **136** serves as the steam cracking feed **12**. In certain embodiments the heavy stream **134** has an initial boiling point corresponding to vacuum residue, for instance in the range of about 500-550, 500-540, 500-530, 510-550, 510-540 or 510-530°C. The bottomless stream **136** can have, for instance, an initial boiling point corresponding to that of the stream **126** and an end boiling point corresponding to the initial boiling point of the heavy stream **134**.

[65] In another embodiment, with reference to FIG. 5, a schematic process flow diagram of a feedstock hydroprocessing zone and a steam cracking zone is shown, including a feedstock hydroprocessing zone **122** for treating an initial feedstock **120** (and optionally a recycle stream **64(r)** as described herein) in the presence of hydrogen, shown as hydrogen stream **124**, to produce a hydroprocessed effluent stream **126**. The hydroprocessed effluent

is passed to a separation zone **142** upstream of the steam cracking zone to remove light components, stream **146**, and the remaining heavy components, in certain embodiments a topped hydroprocessed initial feed, stream **144**, serves as the steam cracking feed **12**. The hydroprocessed effluent can be subjected to a high pressure cold or hot separator to obtain a hydrogen rich gas stream that is used as a recycle gas in the reactor of the feedstock hydroprocessing zone **122**. A separator bottoms stream from the high pressure separator, in a substantially liquid phase, is cooled and then introduced to a low pressure cold separator. A separator bottoms stream from the low pressure separator, in a substantially liquid phase, is the stream **126** that is passed to the separation zone **142** to separate remove light components, stream **146**; the remainder, stream **144**, serves as the steam cracking feed **12**. In certain embodiments the stream **146** has an end boiling point corresponding to that of naphtha or light naphtha, and the stream **144** has an initial boiling point corresponding to the end boiling point of the stream **146**.

[66] In the embodiments of FIGs. 3, 4 and 5, the initial feedstock **120** can be as described herein, for instance selected from crude oil and other heavy oil streams such as those in the atmospheric gas oil range, atmospheric residue range, vacuum gas oil range and/or vacuum residue range.

[67] In another embodiment, with reference to FIG. 6, a schematic process flow diagram of a feedstock deasphalting zone and a steam cracking zone is shown, including a feedstock deasphalting zone **152** for treating a deasphalting feedstock **154** (and optionally a recycle stream **64(r)** as described herein) to produce a deasphalted oil stream **156** and an asphalt phase stream **158**. In certain embodiments, the deasphalting feedstock **154** can be an initial feed as described herein, for instance selected from a treated crude oil stream and other

treated heavy oil streams such as those in the atmospheric gas oil range, atmospheric residue range, vacuum gas oil range and/or vacuum residue range. In certain embodiments, the deasphalting feedstock **154** can be all or a portion of a hydroprocessed effluent, for instance, a hydroprocessed initial feed **126** as described with respect to FIG. 3; a hydroprocessed initial feed having a bottom fraction removed, stream **136** as described with respect to FIG. 4; or a hydroprocessed initial feed having tops removed, stream **144** as described with respect to FIG. 5. In further embodiments, the deasphalting feedstock **154** can be an initial feed as described herein, and the deasphalted oil stream **156** is passed to an optional hydroprocessing zone, schematically shown as zone **162**. For instance, the deasphalted oil stream **156** can serve as the initial feed **120** in the integrated systems described with respect to FIGs. 3, 4 and 5. In certain embodiments, the optional zone **162** can be a separation zone, for instance that operates similar to the pre-steam cracking separation zone **132** described with respect to FIG. 4 to pass a bottomless stream **136** as the steam cracking feed **12**, or similar to the pre-steam cracking separation zone **142** described with respect to FIG. 5 to pass a topped feed **144** as the steam cracking feed **12**.

[68] In embodiments in which solvent deasphalting is employed prior to the steam cracking zone (either before hydroprocessing of the initial feed, between hydroprocessing of the initial feed and steam cracking, or in the absence of hydroprocessing of the initial feed), solvent deasphalting can be carried out with paraffin streams having carbon number ranging from 3-7, in certain embodiments ranging from 4-5, at conditions that are below the critical temperature and pressure conditions of the solvent. The feed is mixed with the light paraffinic solvent, where the deasphalted oil is solubilized in the solvent. The insoluble pitch will precipitate out of the mixed solution and is separated from the DAO

phase (solvent-DAO mixture) in the extractor. Solvent deasphalting is carried-out in liquid phase and therefore the temperature and pressure are set accordingly. There are typically two stages for phase separation in solvent deasphalting. In the first separation stage, the temperature is maintained lower than that of the second stage to separate the bulk of the asphaltenes. The second stage temperature is maintained to control the deasphalted / demetalized oil (DA/DMO) quality and quantity. The temperature impacts the quality and quantity of DA/DMO. An increase in the extraction temperature will result in a decrease in deasphalted / demetalized oil yield, which means that the DA/DMO will be lighter, less viscous, and contain less metals, asphaltenes, sulfur, and nitrogen. A temperature decrease will have the opposite effects. In general, the DA/DMO yield decreases, having higher quality, by raising extraction system temperature; and increases, having lower quality, by lowering extraction system temperature. The composition of the solvent is an important process variable. The solubility of the solvent increases with increasing critical temperature, generally according to $C_3 < iC_4 < nC_4 < iC_5$. An increase in critical temperature of the solvent increases the DA/DMO yield. However, it should be noted that the solvent having the lower critical temperature has less selectivity resulting in lower DA/DMO quality. The volumetric ratio of the solvent to the solvent deasphalting unit charge impacts selectivity and to a lesser degree on the DA/DMO yield. Higher solvent-to-oil ratios result in a higher quality of the DA/DMO for a fixed DA/DMO yield. Higher solvent-to-oil ratio is desirable due to better selectivity. The composition of the solvent will also help to establish the required solvent to oil ratios. The required solvent to oil ratio decreases as the critical solvent temperature increases. The solvent to oil ratio is, therefore, a function of desired selectivity, operation costs and solvent composition.

[69] The selective hydrogenation zone **30** includes an effective reactor configuration with the requisite reaction vessel(s), feed heaters, heat exchangers, hot and/or cold separators, product fractionators, strippers, and/or other units to process all or a portion of the two-ring C10+ stream **26** from the PFO separation zone **22**, or all or a portion of the PFO C9+ stream **18** from the steam cracker/separation zone **10**. The selective hydrogenation zone **30** generally contains one or more fixed bed, fluidized bed, ebullated bed, slurry bed, moving bed, continuous stirred tank, or tubular reactors, in series or parallel arrangement, which is/are generally operated in the presence of hydrogen under conditions, and utilizes catalyst(s), effective for selective hydrogenation of polyaromatics compounds in the two-ring C10+ stream **26**. In certain embodiments, multiple reactors can be provided in parallel in hydrogenation zone **30** to facilitate catalyst replacement and/or regeneration. The selective hydrogenation zone **30** generally has one or more inlets in fluid communication with a source of feedstock. In certain embodiments, the feedstock is all or a portion of the light PFO two-ring C10+ stream **26** from the PFO separation zone **22** (as disclosed in conjunction with the embodiment of FIG. 1). In certain embodiments, the feedstock is all or a portion of the full range PFO C9+ stream from the steam cracker/separation zone **10** (as disclosed in conjunction with the embodiment of FIG. 2). The selective hydrogenation zone **30** is in fluid communication with a hydrogen stream **32**. The hydrogen stream **32** can be passed to the reactors at one or more locations as is known, and can be derived from sources including recycled hydrogen from the integrated steam cracking unit (not shown in FIGs. 1 and 2) and produced hydrogen **76** from the gas treatment zone **74**. Make-up hydrogen from another source (not shown) is also typically added. Reaction conditions are set to maximize the conversion of polyaromatics, such as

naphthalene, methylnaphthalene, anthracene, naphtheno-diaromatics (three rings, one saturated and two aromatic), and other polyaromatics contained in refractory PFO streams such as C10+, C20+ and even C30+ polyaromatics, by selective hydrogenation into aromatic compounds with one benzene ring. Aromatic compounds with one benzene ring include benzene, toluene, xylene, triethyl-benzene, methyl-ethylbenzene, trimethylbenzene, di-ethyl-benzene, propyl-methyl-benzene, butyl-methyl-benzene, butyl-ethyl-benzene, and others including alkyl benzenes.

[70] The outlet(s) of the selective hydrogenation zone **30** discharge the effluent stream **34**, and in fluid communication with the selective hydrocracking zone **42**. In certain embodiments (not shown), the hydrogenation reaction vessel outlet(s) are in fluid communication with one or more heat exchangers and separators (such as a high pressure cold or hot separator) for cooling and separation of reaction gases, and discharged as the effluent stream **34**. In certain embodiments, one or more outlets of the selective hydrogenation zone **30** that discharge the effluent stream **34** are in fluid communication with one or more inlets of the separation zone **36**. The separation zone **36** can include one or more simple or fractional distillation columns and generally includes one or more outlets for discharging light gases, stream **38** including LPG and H₂, and the remainder of the one-ring C₉+ effluent stream **34**, stream **40**. The outlet discharging the one-ring C₉+ stream **40** in fluid communication with the selective hydrocracking zone **42**. In certain embodiments, the one-ring C₉+ effluent stream **34** is in fluid communication with the selective hydrocracking zone **42** without a distinct separation zone, and light gases pass with the remainder of the one-ring C₉+ components.

[71] In operation, the selective hydrogenation feedstock and a hydrogen stream are charged to the reactor(s) of the selective hydrogenation zone **30**. The hydrogen stream contains an effective quantity of hydrogen to support the selective hydrogenation of the polyaromatics compounds in the feed, the reaction conditions, the selected catalysts and other factors, and can be any combination including recycle hydrogen from optional gas separation subsystems (not shown) between the reaction zone and fractionating zone, hydrogen derived from the hydrogen producers within the integrated system and process, stream **76**, and make-up hydrogen as necessary.

[72] The hydrogenation reaction effluent stream is typically passed to one or more high pressure and low pressure separation stages recover recycle hydrogen. For example, effluents from the hydrogenation reaction vessel are cooled in an exchanger and sent to a high pressure cold or hot separator. Separator tops are cleaned in an amine unit and the resulting hydrogen rich gas stream is passed to a recycling compressor to be used as a recycle gas in the hydrogenation reaction vessel. Separator bottoms from the high pressure separator, which are in a substantially liquid phase, are cooled and then introduced to a low pressure cold separator. Remaining gases including hydrogen and any light hydrocarbons, which can include C₁-C₄ hydrocarbons, can be conventionally purged from the low pressure cold separator and sent for further processing, for instance to the gas treatment zone **74**. The liquid stream from the low pressure cold separator is passed to the fractionating zone, or to the selective hydrocracking zone **42** without fractionating.

[73] The hydrogenation reaction effluent stream can be passed to the separation zone **36** generally to recover a gas stream LPG/H₂ and liquid products, a one ring C₉+ stream. The gas stream, typically containing H₂, and light hydrocarbons (C₁-C₄), is discharged and

recovered and can be further processed as is known in the art, including for recovery of recycle hydrogen. In certain embodiments one or more gas streams are discharged from one or more separators between the reactor and the fractionator (not shown), and gas stream can be optional from the fractionator. One or more cracked product streams are discharged from appropriate outlets of the fractionator and can be further processed and/or blended in downstream refinery operations to produce fuel products, or other hydrocarbon mixtures that can be used to produce petrochemical products. In certain embodiments, the separation zone **36** can operate as one or more flash vessels to separate heavy components at a suitable cut point, for example, a range corresponding to the one ring C₉⁺ stream that is passed to the selective hydrocracking zone **42**.

[74] Reaction operating conditions and catalysts are selected so as to maximize the conversion of polyaromatics, such as naphthalene, methylnaphthalene, anthracene, naphtheno-diaromatics (three rings, one saturated and two aromatic), by selective hydrogenation into aromatic compounds with one benzene ring. While not wishing to be bound by theory, it is understood that selective hydrogenation of the polycyclic aromatic compounds proceeds via initial hydrogenation of their peripheral ring into a naphthenic ring, cleaves to aliphatic substituents, isomerizes to a branched naphthenic ring, and dealkylates. Dual functionality, hydrogenating and cracking, catalysts are useful for conversion of selective conversion of polycyclic aromatic compounds into aromatic compounds or bicyclic aromatic compounds.

[75] The selective hydrogenation zone **30** generally operates under effective conditions including:

a reaction temperature ($^{\circ}\text{C}$) in the range of about 250-500, 250-480, 250-450, 250-400, 280-500, 280-480, 280-450, 280-400, 300-500, 300-480, 300-450, 300-400, 320-500, 320-480, 320-450 or 320-400 $^{\circ}\text{C}$;

a reaction pressure (hydrogen partial pressure, kg/cm^2) in the range of about 10-70, 10-50, 10-30, 20-70, 20-50 or 20-30 kg/cm^2 ;

a hydrogen feed rate (standard liters per liter of hydrocarbon feed, SLt/Lt) in the range of about 30-5000, 30-4000, 30-3000, 30-2000, 50-5000, 50-4000, 50-3000, 50-2000, 100-5000, 100-4000, 100-3000, 100-2000, 300-5000, 300-4000, 300-3000 or 300-2000 SLt/Lt ; and

a LHSV in the range of about 0.1-20, 0.1-10, 0.1-5, 0.5-20, 0.5-10, 0.5-5, 1-20, 1-10, 1-5, 2-20, 2-10, or 2-5.

[76] In certain embodiments, in which C9s and C20+ are substantially removed, the selective hydrogenation zone **30** generally operates under effective conditions including

a reaction temperature ($^{\circ}\text{C}$) in the range of about, 250-480, 250-450, 250-400, 280-480, 280-450, 280-400, 300-480, 300-450, or 300-400 $^{\circ}\text{C}$;

a reaction pressure (hydrogen partial pressure, kg/cm^2) in the range of about 10-50, 10-30, 20-50 or 20-30 kg/cm^2 ;

a hydrogen feed rate (standard liters per liter of hydrocarbon feed, SLt/Lt) in the range of about 30-4000, 30-3000, 30-2000, 50-4000, 50-3000, 50-2000, 100-4000, 100-3000, 100-2000, 300-4000, 300-3000, or 300-2000 SLt/Lt ; and

a LHSV in the range of about 0.1-20, 0.1-10, 0.1-5, 0.5-20, 0.5-10, 0.5-5, 1-20, 1-10, 1-5, 2-20, 2-10, or 2-5.

[77] In certain embodiments, in which the C9+ PFO stream is used as feed, without separation of C9s or C20+, the selective hydrogenation zone **30** generally operates under effective conditions including:

reaction temperatures (°C) in the range of about 250-500, 250-480, 250-450, 250-400, 280-500, 280-480, 280-450, 280-400, 300-500, 300-480, 300-450, 300-400, 320-500, 320-480, 320-450 or 320-400°C;

a reaction pressure (hydrogen partial pressure, kg/cm²) in the range of about 10-70, 10-50, 10-30, 20-70, 20-50 or 20-30 kg/cm²;

a hydrogen feed rate (standard liters per liter of hydrocarbon feed, SLt/Lt) in the range of about 30-5000, 30-4000, 30-3000, 50-5000, 50-4000, 50-3000, 100-5000, 100-4000, 100-3000, 300-5000, 300-4000, or 300-3000 SLt/Lt; and

a LHSV in the range of about 0.1-20, 0.1-10, 0.1-5, 0.5-20, 0.5-10, 0.5-5, 1-20, 1-10, 1-5, 2-20, 2-10, or 2-5.

[78] In certain embodiments, in which C9s are removed and a portion of C20+ are removed (with the remainder passing to selective hydrogenation), the selective hydrogenation zone **30** generally operates under effective conditions including:

a reaction temperature (°C) in the range of about 250-480, 250-450, 250-400, 280-480, 280-450, 280-400, 300-480, 300-450, 300-400, 320-480, 320-450 or 320-400°C;

a reaction pressure (hydrogen partial pressure, kg/cm²) in the range of about 10-50, 10-30, 20-50 or 20-30 kg/cm²;

a hydrogen feed rate (standard liters per liter of hydrocarbon feed, SLt/Lt) in the range of about 30-4000, 30-3000, 30-2000, 50-4000, 50-3000, 50-2000, 100-4000, 100-3000, 100-2000, 300-4000, 300-3000, or 300-2000 SLt/Lt; and

[79] a LHSV in the range of about 0.1-20, 0.1-10, 0.1-5, 0.5-20, 0.5-10, 0.5-5, 1-20, 1-10, 1-5, 2-20, 2-10, or 2-5.

[80] In certain embodiments, in which C9s are removed and the C20+ are not removed, the selective hydrogenation zone **30** generally operates under effective conditions including:

a reaction temperature (°C) in the range of about 250-500, 250-480, 250-450, 250-400, 280-500, 280-480, 280-450, 280-400, 300-500, 300-480, 300-450, 300-400, 320-500, 320-480, 320-450 or 320-400°C;

a reaction pressure (hydrogen partial pressure, kg/cm²) in the range of about 10-70, 10-50, 10-30, 20-70, 20-50 or 20-30 kg/cm²;

a hydrogen feed rate (standard liters per liter of hydrocarbon feed, SLt/Lt) in the range of about 30-5000, 30-4000, 30-3000, 50-5000, 50-4000, 50-3000, 100-5000, 100-4000, 100-3000, 300-5000, 300-4000, or 300-3000 SLt/Lt; and

a LHSV in the range of about 0.1-20, 0.1-10, 0.1-5, 0.5-20, 0.5-10, 0.5-5, 1-20, 1-10, 1-5, 2-20, 2-10, or 2-5.

[81] The catalyst used in the selective hydrogenation zone **30** can be one or more conventionally known, commercially available or future developed hydrogenation catalysts effective to maximize the conversion of polyaromatics, such as naphthalene, methylnaphthalene, anthracene, naphtheno-diaromatics (three rings, one saturated and two aromatic), by selective hydrogenation into aromatic compounds with one benzene ring. The selection, activity and form of the selective hydrogenation catalyst can be determined based on factors including but not limited to operating conditions, selected reactor configuration, feedstock composition, and desired degree of conversion. Dual

functionality, hydrogenating and cracking, catalysts are useful for conversion of selective conversion of polycyclic aromatic compounds into aromatic compounds or bicyclic aromatic compounds. Suitable catalysts generally contain one or more first active components of metals or metal compounds (oxides, carbides or sulfides), for instance a metal selected from the Periodic Table of the Elements IUPAC Groups 6, 9, 10, 13 and/or 14, such as Mo, Co, Ir, Pd, Pt, Ni, W, Sn or Ga, and one or more second active components, for instance a metal, metal compound, non-metal such as P, or other non-metal compound. In certain embodiments two or more of the first active components mentioned above are used. One, two or more of the above-mentioned active components are typically deposited or otherwise incorporated on a catalyst support, which can be amorphous and/or structured, such as silica-alumina, silica, titania, titania-silica, titania-silicates, zeolites (including HY, beta, mordenite, ZSM-5, ZSM-12, ZSM-22, ZSM-11, MCM-22, MCM-56, or SSZ-26/33 zeolites), or similar crystalline materials to zeolites such as SAPO. The catalyst support(s) can be subjected to treatment whereby support properties such as pore volume, surface area, and average pore size are altered, such as by meso-structuring treatments which include one or more of desilication, de-alumination, steaming, acid leaching, and templated re-crystallization. In embodiments in which P is used, elemental form of P can be added and treated with H_2SO_4 , whereby after treatment P remains in the structure of the catalyst. Combinations of active components can be composed of different particles/granules containing a single active metal species, or particles containing multiple active components. In embodiments in which zeolites or other crystalline materials are used, they are conventionally formed with one or more binder components such as alumina, silica, silica-alumina, clay, titania and mixtures thereof. In certain embodiments, the catalyst

particles have a pore volume in the range of about (cc/gm) 0.15-1.70, 0.15-1.50, 0.30-1.50 or 0.30-1.70; a specific surface area in the range of about (m^2/g) 100-900, 100-500, 100-450, 180-900, 180-500, 180-450, 200-900, 200-500 or 200-450; and an average pore diameter of at least about 30, 45 or 50, in certain embodiments in the range of about 30-80, 45-80, 50-80, 30-100, 45-100 or 50-100, 30-200, 45-200 or 50-200 angstrom units. The active component(s) are incorporated in an effective concentration, for instance, in the range of (wt% based on the mass of the active component(s) relative to the total mass of the catalysts including the support and binders) 1-40, 1-30, 1-10, 1-5, 2-40, 2-30, 2-10, 3-40, 3-30 or 3-10. Effective catalysts to promote hydrogenation reactions include but are not limited to those having one or more effective first active components, for instance, Mo, Co, Ir, Pd, Pt, Ni, W, Sn or Ga, and optionally a second active components such as P, deposited or otherwise incorporated on a support formed of alumina and/or zeolite. Examples include but are not limited to MoP/zeolite (including HY zeolites), Pd/alumina (for instance catalysts similar to selective acetylene hydrogenation catalysts for ethylene production while minimizing ethane formation which are known), Pd/zeolite, MoP/alumina, NiP/alumina, NiP/zeolite, WP/alumina, WP/zeolite, or sulfided NiMo/alumina.

[82] In certain embodiments, the catalyst and/or the catalyst support is prepared in accordance with US Patents 9,221,036 and its continuation patent 10,081,009 (jointly owned by the owner of the present application, and subject to a joint research agreement), which is incorporated herein by reference in its entirety. Such a support includes a modified zeolite support having one or more of Ti, Zr and/or Hf substituting the aluminum atoms constituting the zeolite framework thereof. For instance, the catalyst effective for

hydrogenation can include one or more active component carried on a support containing a framework-substituted zeolite such as a ultra-stable Y-type zeolite, in which a part of aluminum atoms constituting a zeolite framework thereof is substituted one, two or all of Ti, Zr and Hf, for instance 0.1-5 mass % of each calculated on an oxide basis.

[83] The selective hydrocracking zone **42** includes an effective reactor configuration with the requisite reaction vessel(s), feed heaters, heat exchangers, hot and/or cold separators, product fractionators, strippers, and/or other units to process the selective hydrocracking feed, the effluent stream **34** from the selective hydrogenation zone **30**, (or the portion, stream **40** from the separation zone **36**), and in certain embodiments all or a portion of the one-ring C₉⁺ stream **24**. The selective hydrocracking zone **42** generally contain one or more fixed bed, fluidized bed, ebullated bed, slurry bed, moving bed, continuous stirred tank, or tubular reactors, in series or parallel arrangement, which is/are generally operated in the presence of hydrogen under conditions, and utilizes catalyst(s), effective for selective ring opening and hydrodealkylation, in certain embodiments selective to aromatic compounds with one benzene ring. Aromatic compounds with one benzene ring include benzene, toluene, xylene, triethyl-benzene, methyl-ethylbenzene, trimethylbenzene, di-ethyl-benzene, propyl-methyl-benzene, butyl-methyl-benzene, butyl-ethyl-benzene, and others including alkyl benzenes. In certain embodiments, multiple reactors can be provided in parallel in hydrocracking zone **42** to facilitate catalyst replacement and/or regeneration.

[84] The selective hydrocracking zone **42** generally includes a reaction zone having one or more inlets in fluid communication with a source of feedstock, all or a portion of the one-ring C₉⁺ stream from the selective hydrogenation zone **30**, and all or a portion of the

one-ring C9+ stream **24**. In certain embodiments the reaction zone is also in fluid communication with a recycle stream from the BTX splitting zone **56**. In addition, the hydrocracking zone **42** is in fluid communication with a hydrogen stream **44**. The hydrogen stream **44** can be passed to the reactors at one or more locations as is known, and can be derived from sources including recycled hydrogen from the integrated steam cracking unit (not shown in FIGs. 1 and 2) and produced hydrogen **76** from the gas treatment zone **74**. Make-up hydrogen from another source (not shown) is also typically added. Reaction conditions are set, and catalyst are selected, so as to maximize selective ring opening and hydrodealkylation, in certain embodiments selective to aromatic compounds with one benzene ring.

[85] One or more outlets of reaction zone that discharge a BTX+ effluent stream are in fluid communication with one or more inlets of the BTX splitting zone **56**. In certain embodiments (not shown), effluents from the hydrocracking reaction vessels are cooled in an exchanger and sent to a high pressure cold or hot separator and liquid effluents are passed to the BTX splitting zone **56**. The fractionating zone can include one or more simple or fractional distillation columns and generally includes one or more outlets for discharging the BTX+ stream and one or more outlets for discharging the LPG/H₂ stream. In certain embodiments, the one or more outlets of reaction zone that discharge the BTX+ effluent stream are in fluid communication with one or more inlets of the aromatics extraction zone **50**, whereby the extract **52** is passed to the BTX splitting zone **56**.

[86] In operation, the selective hydrocracking feedstock and a hydrogen stream are charged to the reactor of the selective hydrocracking zone **42**. The hydrogen stream contains an effective quantity of hydrogen to support the selective ring opening functions

and hydrodealkylation functions, the reaction conditions, the selected catalysts and other factors, and can be any combination including recycle hydrogen from optional gas separation subsystems (not shown) between the reaction zone and fractionating zone, hydrogen derived from the hydrogen producers within the integrated system and process, stream 76, and make-up hydrogen as necessary.

[87] The hydrocracking reaction effluent stream is typically passed to one or more high pressure and low pressure separation stages recover recycle hydrogen. For example, effluents from the hydrocracking reaction vessel are cooled in an exchanger and sent to a high pressure cold or hot separator. Separator tops are cleaned in an amine unit and the resulting hydrogen rich gas stream is passed to a recycling compressor to be used as a recycle gas in the hydrocracking reaction vessel. Separator bottoms from the high pressure separator, which are in a substantially liquid phase, are cooled and then introduced to a low pressure cold separator. Remaining gases including hydrogen and any light hydrocarbons, which can include C₁-C₄ hydrocarbons, can be conventionally purged from the low pressure cold separator and sent for further processing, for instance to the gas treatment zone 74. The liquid stream from the low pressure cold separator is passed to a fractionating zone associated with the hydrocracking reactor, or directly to the BTX separation zone 56.

[88] The hydrocracking reaction effluent stream can be passed to a fractionating zone, generally to recover a gas stream, liquid products and a bottoms fraction. The gas stream, typically containing H₂ and light hydrocarbons (C₁-C₄), is discharged and recovered and can be further processed as is known in the art, including for recovery of recycle hydrogen. In certain embodiments one or more gas streams are discharged from one or more separators between the reactor and the fractionator (not shown), and gas stream can be

optional from the fractionator. One or more cracked product streams are discharged from appropriate outlets of the fractionator and can be further processed and/or blended in downstream refinery operations to produce fuel products, or other hydrocarbon mixtures that can be used to produce petrochemical products. In certain embodiments, the fractionating zone can operate as one or more flash vessels to separate heavy components at a suitable cut point, for example, a range corresponding to the BTX+ stream that is passed to the BTX splitting zone **56**.

[89] Reaction conditions and catalysts are selected so as to maximize selective ring opening and hydrodealkylation, in certain embodiments selective to aromatic compounds with one benzene ring. For example, the selective hydrocracking zone **42** can generally operate under effective conditions including:

a reaction temperature (°C) in the range of about 300-550, 300-500, 300-450, 320-550, 320-500, 320-450, 350-550, 350-500, or 350-450°C;

a reaction pressure (hydrogen partial pressure, kg/cm²) in the range of about 3-30, 3-25, 3-20, 5-30, 5-25, 5-20, 10-30, 10-25, 10-20 kg/cm²;

a hydrogen feed rate (standard liters per liter of hydrocarbon feed, SLt/Lt) in the range of about 1-30, 1-25, 1-20, 5-30, 5-25, 5-20 SLt/Lt; and

a LHSV in the range of about 0.1-10, 0.1-8, 0.1-5, 0.5-10, 0.5-8, 0.5-5, 1-10, 1-8, or 1-5.

[90] In certain embodiments, in which C₉s and C₂₀+ are substantially removed prior to selective hydrogenation, the selective hydrocracking zone **42** generally operates under effective conditions including:

a reaction temperature ($^{\circ}\text{C}$) in the range of about 300-500, 300-450, 320-500, or 320-450 $^{\circ}\text{C}$;

a reaction pressure (hydrogen partial pressure, kg/cm^2) in the range of about 3-25, 3-20, 5-25, 5-20, 10-25, 10-20 kg/cm^2 ;

a hydrogen feed rate (standard liters per liter of hydrocarbon feed, SLt/Lt) in the range of about 1-25, 1-20, 5-25, 5-20 SLt/Lt; and

a LHSV in the range of about 0.1-8, 0.1-5, 0.5-8, 0.5-5, 1-8, or 1-5.

[91] In certain embodiments, in which the C9+ PFO stream is used as feed (without separation of C9s or C20+) to selective hydrogenation, the selective hydrocracking zone **42** generally operates under effective conditions including:

a reaction temperature ($^{\circ}\text{C}$) in the range of about 300-550, 300-500, 300-450, 350-550, 350-500, or 350-450 $^{\circ}\text{C}$;

a reaction pressure (hydrogen partial pressure, kg/cm^2) in the range of about 3-30, 3-25, 3-20, 5-30, 5-25, 5-20, 10-30, 10-25, 10-20 kg/cm^2 ;

a hydrogen feed rate (standard liters per liter of hydrocarbon feed, SLt/Lt) in the range of about 1-30, 1-20, 5-30, 5-20 SLt/Lt; and

a LHSV in the range of about 0.1-10, 0.1-8, 0.1-5, 0.5-10, 0.5-8, 0.5-5, 1-10, 1-8, or 1-5.

[92] In certain embodiments, in which C9s are removed and a portion of C20+ are removed prior to selective hydrogenation, the selective hydrocracking zone **42** generally operates under effective conditions including:

a reaction temperature ($^{\circ}\text{C}$) in the range of about 300-500, 300-450, 320-500, or 320-450 $^{\circ}\text{C}$;

a reaction pressure (hydrogen partial pressure, kg/cm²) in the range of about 3-25, 3-20, 5-25, 5-20, 10-25, 10-20 kg/cm²;

a hydrogen feed rate (standard liters per liter of hydrocarbon feed, SLt/Lt) in the range of about 1-25, 1-20, 5-25, 5-20 SLt/Lt; and

a LHSV in the range of about 0.1-8, 0.1-5, 0.5-8, 0.5-5, 1-8, or 1-5.

[93] In certain embodiments, in which C₉s are removed and the C₂₀+ are not removed prior to selective hydrogenation, the selective hydrocracking zone **42** generally operates under effective conditions including:

a reaction temperature (°C) in the range of about 300-550, 300-500, 300-450, 350-550, 350-500, or 350-450°C;

a reaction pressure (hydrogen partial pressure, kg/cm²) in the range of about 3-30, 3-25, 3-20, 5-30, 5-25, 5-20, 10-30, 10-25, 10-20 kg/cm²;

a hydrogen feed rate (standard liters per liter of hydrocarbon feed, SLt/Lt) in the range of about 1-30, 1-20, 5-30, 5-20 SLt/Lt; and

a LHSV in the range of about 0.1-10, 0.1-8, 0.1-5, 0.5-10, 0.5-8, 0.5-5, 1-10, 1-8, or 1-5.

[94] The catalyst used in the selective hydrocracking zone **42** can be one or more conventionally known, commercially available or future developed catalyst materials effective for selective ring opening and hydrodealkylation. The selection, activity and form of the selective ring opening and hydrodealkylation catalyst can be determined based on factors including but not limited to operating conditions, selected reactor configuration, feedstock composition, and desired degree of conversion. Suitable catalysts contain one or more active components that are metals or metal compounds (oxides, carbides or

sulfides) selected from the Periodic Table of the Elements IUPAC Groups 6, 7, 8, 9 and 10, such as Ni, W or Mo. In certain embodiments two or more of the active components mentioned above are used. One, two or more of the above-mentioned active components are typically deposited or otherwise incorporated on a support, which can be amorphous and/or structured, such as silica-alumina, silica, titania, titania-silica, titania-silicates, zeolites (including HY, beta, mordenite, ZSM-5, ZSM-12, ZSM-22, ZSM-11, MCM-22, MCM-56, or SSZ-26/33 zeolites), or similar crystalline materials to zeolites such as SAPO. The catalyst support(s) can be subjected to treatment whereby support properties such as pore volume, surface area, and average pore size are altered, such as by meso-structuring treatments which include one or more of desilication, de-alumination, steaming, acid leaching, and templated re-crystallization. Combinations of active components can be composed of different particles/granules containing a single active metal species, or particles containing multiple active components. In embodiments in which zeolites or other crystalline materials are used, they are conventionally formed with one or more binder components such as alumina, silica, silica-alumina, clay, titania and mixtures thereof. In certain embodiments, the catalyst particles have a pore volume in the range of about (cc/gm) 0.15-1.70, 0.15-1.50, 0.30-1.50 or 0.30-1.70; a specific surface area in the range of about (m²/g) 100-900, 100-500, 100-450, 180-900, 180-500, 180-450, 200-900, 200-500 or 200-450; and an average pore diameter of at least about 30, 45 or 50, in certain embodiments in the range of about 30-80, 45-80, 50-80, 30-100, 45-100 or 50-100, 30-200, 45-200 or 50-200 angstrom units. The active component(s) are incorporated in an effective concentration, for instance, in the range of (wt% based on the mass of the active component(s) relative to the total mass of the catalysts including the support and binders)

1-40, 1-30, 1-10, 1-5, 2-40, 2-30, 2-10, 3-40, 3-30 or 3-10. Effective hydrocracking catalysts include but are not limited to one or more active components selected from the group consisting of Ni, W, Mo (metals, oxides, carbides or sulfides), deposited or otherwise incorporated on a support formed of acidic alumina, silica alumina and/or zeolite. Examples include but are not limited to Ni/HY zeolite, Ni/alumina, W/alumina, Mo/zeolite, NiMo/alumina-USY zeolite, NiMo/silica alumina, or MoS₂/alumina.

[95] In certain embodiments, the catalyst and/or the catalyst support is prepared in accordance with US Patents 9,221,036 and its continuation patent 10,081,009 (jointly owned by the owner of the present application, and subject to a joint research agreement), which is incorporated herein by reference in its entirety. Such a support includes a modified zeolite support having one or more of Ti, Zr and/or Hf substituting the aluminum atoms constituting the zeolite framework thereof. For instance, the catalyst effective for hydrocracking can include one or more active component carried on a support containing a framework-substituted zeolite such as a ultra-stable Y-type zeolite, in which a part of aluminum atoms constituting a zeolite framework thereof is substituted one, two or all of Ti, Zr and Hf, for instance 0.1-5 mass % of each calculated on an oxide basis.

[96] The transalkylation zone **66** can contain one or more fixed bed, fluidized bed, ebullated bed, slurry bed, moving bed, continuous stirred tank, or tubular reactors, in series or parallel arrangement, which is/are generally operated in the presence of hydrogen under conditions, and utilizes catalyst(s), effective for conversion of a portion of the C₉ stream from the BTX splitting zone **56** to xylenes. In certain embodiments, multiple reactors can be provided in parallel in transalkylation zone **66** to facilitate catalyst replacement and/or regeneration. The transalkylation zone **66** can also be in fluid communication with a source

of toluene to react with C9 via transalkylation reactions to produce additional xylenes. In certain embodiments toluene and benzene used to react with C9s can be from the BTX stream in the BTX splitting zone **56**. In general, the transalkylation zone **66** includes an inlet in fluid communication with an outlet of the BTX splitting zone **56** discharging the C9 stream **62**, which includes trimethyl-benzene, methylethylbenzene, and other C9 compounds. The transalkylation zone **66** also includes one or more outlets for discharging product streams of BTX and C9+ aromatics, shown as stream **70** and the light gases by-product including C₁-C₄ and hydrogen, stream **72**. The transalkylation zone **66** is in fluid communication with a hydrogen gas stream **68**, which can be passed to the reactors at one or more locations as is known, and can be derived from sources including recycled hydrogen from the integrated steam cracking unit (not shown) and produced hydrogen **76** from the gas treatment zone **74**. Make-up hydrogen from another source (not shown) is also typically added.

[97] The transalkylation zone **66** includes an effective reactor configuration with the requisite reaction vessel(s), feed heaters, heat exchangers, hot and/or cold separators, product fractionators, strippers, and/or other units to process the C9 stream from the BTX splitting zone **56**. The transalkylation zone **66** operates in the presence of hydrogen, stream **68**, under conditions effective to, and using catalyst effective to, maximize the transalkylation of unconverted trimethyl-benzene C9 aromatics and toluene to produce xylenes. The transalkylation zone **66** can also be configured to perform isomerization of mixed xylenes to promote production of para-xylene. The light gases stream **72** (which in certain embodiments can contain naphtha-range byproducts such as light naphtha) is in fluid communication with the gas treatment zone **74** for recovery of hydrogen and recovery

of LPG and optionally naphtha-range components as additional feed to the steam cracking zone.

[98] The C9 stream from the BTX splitting zone **56** and a hydrogen stream **68** are charged to the reactor of the transalkylation zone **66**. The hydrogen stream contains an effective quantity of hydrogen to support the mixed xylene production from the feed, the reaction conditions, the selected catalysts and other factors, and can be any combination including hydrogen derived from the hydrogen producers within the integrated system and process, stream **76**, and in certain embodiments make-up hydrogen from another source.

[99] Mixed xylenes that form part of the transalkylation reaction effluent stream **70** include the less commercially valuable m-xylene forms in greater amounts than either p- or o-xylenes because of thermodynamic equilibrium relationships between the three isomers. In certain embodiments separation of p-xylene is desired, for instance when market demand favors p-xylene over o-xylene and m-xylene. In some embodiments, the transalkylation reaction zone can also include an isomerization reactor to isomerize para-xylene-free mixed xylenes received from a para-xylene separator to reestablish the thermodynamic equilibrium of C8 aromatics (that is, xylene isomers) para-xylene. A para-xylene separator can separate and produce product streams of para-xylene and para-xylene-free mixed xylenes (that is, ortho- and meta-xylenes) from the transalkylation reaction effluent. In some embodiments, the para-xylene separator can be an adsorptive process or a crystallization process. In some embodiments, the para-xylene-free mixed xylenes stream produced by the para-xylene separator can be provided to the transalkylation reaction zone **66** for reestablishing a C8 aromatics thermodynamic equilibrium of xylene isomers and promoting formation of additional para-xylene.

[100] Reaction conditions are set to maximize the conversion of the C9 stream from the BTX splitting zone **56** to xylenes by transalkylation reactions. In general, the operating conditions for the reactor of a suitable transalkylation reaction zone **66** include:

a reaction temperature ($^{\circ}\text{C}$) of from about 300-450, 300-420, 320-450 or 320-420;

an operating pressure (hydrogen partial pressure, kg/cm^2) of from about 5-30, 5-25, 5-20, 10-30, 10-25 or 10-20;

a hydrogen feed rate (SL/L) of from about 1-10, 1-8, 2-10 or 2-8; and

a feed rate (liquid hourly space velocity, h^{-1}) of from about 1-10, 1-8, 2-10 or 2-8.

[101] The catalyst used in the transalkylation zone **66** can be one or more conventionally known, commercially available or future developed transalkylation catalyst zone **66** are effective to maximize selective conversion of trimethyl-benzene and toluene into mixed xylenes. In certain embodiments the catalyst used in the transalkylation zone **66** are capable of converting a significant portion and, in some embodiments, all, of the trimethyl-benzene in the C9 aromatics stream to mixed xylenes under effective operating conditions. An appropriate, commercially available transalkylation catalyst can be used. The selection, activity and form of the transalkylation catalyst can be determined based on factors including but not limited to operating conditions, selected reactor configuration, feedstock composition, ratios of toluene to trimethyl-benzene, and desired degree of conversion. For example, suitable catalysts generally contain one or more active components selected from the group consisting of silicon, phosphorus, boron, magnesium, tin, titanium, zirconium, molybdenum, germanium, indium, lanthanum, cesium, and any oxide thereof. The active component is typically deposited or otherwise incorporated on a support such as a beta zeolite support catalyst support, which can be a zeolite material such as USY zeolite, NaHY

zeolite, ZSM-12 zeolite, mesoporous surface area (MSA) zeolite, Al_2O_3 zeolite, beta zeolite, mordenite zeolite or silicate-1 zeolite.

[102] The method and system of the present invention have been described above and in the attached drawings; however, modifications will be apparent to those of ordinary skill in the art and the scope of protection for the invention is to be defined by the claims that follow.

Claims

1. A process for treatment of PFO from a steam cracking zone that produces light olefins and PFO from a steam cracking feed, the process comprising:

optionally separating the PFO into at least a first stream containing C₉+ aromatics compounds with one benzene ring, and a second stream containing C₁₀+ aromatic compounds;

selectively hydrogenating all or a portion of the PFO, or all or a portion of the second stream containing C₁₀+ aromatics compounds, using catalysts and conditions, including hydrogen, effective for conversion of polyaromatics compounds contained in the PFO into aromatic compounds with one benzene ring to produce a selectively hydrogenated stream;

selectively hydrocracking all or a portion of the selectively hydrogenated stream, and optionally all or a portion of the first stream containing C₉+ aromatics compounds with one benzene ring, using catalysts and conditions, including hydrogen, effective for selective ring opening and dealkylation to produce a selectively hydrocracked BTX+ stream;

separating at least a portion of the selectively hydrocracked BTX+ stream into BTX compounds.

2. The process as in claim 1, wherein the PFO is obtained from steam cracking of treated crude oil or other treated heavy oil feeds, and comprises at least 40 wt% of polyaromatics having three or more aromatic rings including triaromatics, naphtho-triaromatics, tetraaromatics, penta-aromatics and heavier poly-aromatics including asphaltenes and coke.

3. The process as in claim 1, wherein all or a portion of C₂₀+ polyaromatic compounds are separated from the PFO or from the second stream, prior to selectively hydrogenating all or a portion of the PFO or all or a portion of the second stream containing C₁₀+ aromatics compounds.

4. The process as in claim 1, wherein the PFO is separated into the first stream, the second stream, and a third stream containing C₂₀+ polyaromatic compounds, and wherein the second stream contains C₁₀+ compounds with no less than 2 and up to 6 benzene rings.

5. The process as in claim 1, wherein all or a portion of C₉+ aromatics with one benzene ring are selectively hydrogenated with all or a portion of the PFO or all or a portion of the second stream containing C₁₀+ aromatics compounds.

6. The process as in claim 1, wherein the PFO is separated into at least the first stream and the second stream, and wherein all or a portion of the first stream containing C₉+ aromatics compounds with one benzene ring bypasses selective hydrogenating and is selectively hydrocracked.

7. The process as in claim 1, wherein the PFO stream or the second stream contains C₂₀+ polyaromatic compounds, and wherein:

selective hydrogenating occurs in the presence of a selective hydrogenating catalyst, and wherein selective hydrogenating conditions comprise a reaction temperature (°C) in the range of about 250-500, a reaction pressure (hydrogen partial pressure, kg/cm²) in the range of about 10-70, a hydrogen feed rate (standard liters per liter of hydrocarbon feed, SLt/Lt) in the range of about 30-5000, and a LHSV in the range of about 0.1-20; and

selective hydrocracking occurs in the presence of a selective hydrocracking catalyst, and wherein selective hydrocracking conditions comprise a reaction temperature

(°C) in the range of about 300-550, a reaction pressure (hydrogen partial pressure, kg/cm²) in the range of about 3-30, a hydrogen feed rate (standard liters per liter of hydrocarbon feed, SLt/Lt) in the range of about 1-30, and a LHSV in the range of about 0.1-10.

8. The process as in claim 1, wherein all or a portion of C₂₀+ polyaromatic compounds are removed prior to selective hydrogenation, and wherein:

selective hydrogenating occurs in the presence of a selective hydrogenating catalyst, and wherein selective hydrogenating conditions comprise a reaction temperature (°C) in the range of about 250-480, a reaction pressure (hydrogen partial pressure, kg/cm²) in the range of about 10-50, a hydrogen feed rate (standard liters per liter of hydrocarbon feed, SLt/Lt) in the range of about 30-4000, and a LHSV in the range of about 0.1-20; and

selective hydrocracking occurs in the presence of a selective hydrocracking catalyst, and wherein selective hydrocracking conditions comprise a reaction temperature (°C) in the range of about 300-500, a reaction pressure (hydrogen partial pressure, kg/cm²) in the range of about 3-25, a hydrogen feed rate (standard liters per liter of hydrocarbon feed, SLt/Lt) in the range of about 1-25, and a LHSV in the range of about 0.1-8.

9. The process as in claim 1, wherein light gases from selective hydrogenating and/or selective hydrocracking are treated and one or more LPG streams are recovered, wherein the one or more LPG streams are passed to the steam cracking zone as additional steam cracking feed.

10. The process as in claim 1, wherein the selectively hydrogenated stream is separated into an LPG stream that is treated and passed to the steam cracking zone, and a stream containing one-ring C₉+ hydrocarbon compounds that is passed to selective hydrocracking as all or a portion of the selectively hydrogenated stream.

11. The process as in claim 1, wherein separating at least a portion of the selectively hydrocracked stream into BTX compounds further comprises separating C9 aromatic compounds, and wherein the process further comprises transalkylating the separated C9 aromatic compounds to produce a transalkylated effluent containing additional BTX compounds.

12. The process as in claim 11, wherein light gases from transalkylating are treated and one or more LPG streams are recovered, and wherein the one or more LPG streams are passed to the steam cracking zone as additional steam cracking feed.

13. The process as in claim 11, further comprising separating naphtha-range hydrocarbon compounds from the transalkylated effluent prior to separation into BTX compounds, and passing all or a portion of said naphtha-range hydrocarbon compounds to the steam cracking zone as additional steam cracking feed.

14. The process as in claim 11, further comprising recovering a raffinate stream comprising non-aromatic compounds from the transalkylated effluent, and passing all or a portion of said raffinate stream to the steam cracking zone as additional steam cracking feed.

15. The process as in claim 14, wherein recovering a raffinate stream is by aromatics extraction to separate the selectively hydrocracked stream into the raffinate stream and an extract stream comprising aromatic compounds, and wherein the extract stream is separated into the BTX compounds.

16. The process as in claim 1, wherein separating the selectively hydrocracked stream into BTX compounds further comprises separating C10+ compounds from the selectively hydrocracked stream.

17. The process as in claim 16, wherein at least a portion of the separated C10+ compounds are selectively hydrocracked together with the selectively hydrogenated stream.

18. The process as in claim 16, wherein an initial feed is subjected to treatment upstream of the steam cracking zone, and wherein at least a portion of the separated C10+ compounds are subjected to treatment with the initial feed.

19. The process as in claim 1, further comprising separating naphtha-range hydrocarbon compounds from the selectively hydrogenated stream prior to selective hydrocracking, and passing all or a portion of said naphtha-range hydrocarbon compounds to the steam cracking zone as additional steam cracking feed.

20. The process as in claim 1, further comprising separating naphtha-range hydrocarbon compounds from the selectively hydrocracked stream prior to separation into BTX compounds, and passing all or a portion of said naphtha-range hydrocarbon compounds to the steam cracking zone as additional steam cracking feed.

21. The process as in claim 1, further comprising separating at least a portion of the selectively hydrocracked stream into BTX compounds includes recovering a raffinate stream comprising non-aromatic compounds, and passing all or a portion of said raffinate stream to the steam cracking zone as additional steam cracking feed.

22. The process as in claim 21, wherein recovering a raffinate stream is by aromatics extraction to separate the selectively hydrocracked stream into the raffinate stream and an extract stream comprising aromatic compounds, and wherein the extract stream is separated into the BTX compounds.

23. A steam cracking process comprising

steam cracking a steam cracker feed to produce olefins, pyrolysis gasoline and PFO;
and

treating the PFO as in the process of claim 1.

24. A system for treatment of PFO from a steam cracking zone that produces at least light olefins and PFO from a steam cracking feed, the system comprising:

an optional PFO separation zone having one or more inlets in fluid communication with the steam cracking zone, one or more outlets for discharging a fraction of the PFO including C₉+ aromatics compounds with one benzene ring, and one or more outlets for discharging a fraction of the PFO including containing C₁₀+ aromatic compounds;

a selective hydrogenation zone having one or more inlets in fluid communication with the steam cracking zone to receive PFO or the second outlet of the PFO separation zone to receive C₁₀+ aromatic compounds from the PFO, and hydrogen, and one or more outlets for discharging reaction effluent including selectively hydrogenated aromatic compounds;

a selective hydrocracking zone having one or more inlets in fluid communication with the one or more outlets of the selective hydrogenation zone, and hydrogen, and one or more outlets for discharging reaction effluent including selectively hydrocracked BTX+ compounds;

a BTX splitting zone having one or more inlets in fluid communication with the one or more outlets of the selective hydrocracking zone for discharging reaction effluent including selectively hydrocracked BTX+ compounds, and one or more outlets for discharging BTX compounds.

25. The system as in claim 24, comprising the PFO separation zone including the one or more outlets for discharging C₉⁺ aromatics compounds with one benzene ring, and the one or more outlets for discharging C₁₀⁺ aromatic compounds, the PFO separation zone further comprising one or more outlets for discharging a fraction of the PFO including C₂₀⁺ polyaromatic compounds.

26. The system as in claim 25, further comprising an initial feed treatment zone upstream of the steam cracking zone having one or more inlets in fluid communication with a source of initial feed, and one or more outlets in fluid communication with the steam cracking zone, and wherein the one or more outlets for discharging C₂₀⁺ polyaromatic compounds are in fluid communication with one or more inlets of the initial feed treatment zone.

27. The system as in claim 24, comprising the PFO separation zone including the one or more outlets for discharging C₉⁺ aromatics compounds with one benzene ring, and the one or more outlets for discharging C₁₀⁺ aromatic compounds, further wherein the one or more outlets for discharging C₉⁺ aromatics compounds with one benzene ring is in fluid communication with the selective hydrocracking zone.

28. The system as in claim 24, wherein the selective hydrogenation zone and/or selective hydrocracking zone include one or more outlets for discharging LPG, and wherein the one or more outlets for discharging LPG are in fluid communication with the steam cracking zone.

29. The system as in claim 24, further comprising an LPG separation zone between the selective hydrogenation zone and selective hydrocracking zone, wherein the LPG separation zone includes one or more inlets in fluid communication with one or more

outlets of the selective hydrogenation zone, one or more outlets for discharging LPG, and one or more outlets for discharging selectively hydrogenated aromatic compounds, and wherein the one or more outlets for discharging selectively hydrogenated aromatic compounds are in fluid communication with the selective hydrocracking zone.

30. The system as in claim 29, further wherein the one or more outlets of the LPG separation zone for discharging LPG are in fluid communication with the steam cracking zone.

31. The system as in claim 24, wherein the BTX splitting zone further comprises one or more outlets for discharging C9 aromatic compounds, the system further comprising a transalkylation zone having one or more inlets in fluid communication with the one or more outlets of the BTX splitting zone for discharging C9 aromatic compounds, and hydrogen, and one or more outlets for discharging a transalkylated reaction effluent containing BTX compounds.

32. The system as in claim 31, wherein the transalkylation zone includes one or more outlets for discharging LPG, and wherein the one or more outlets for discharging LPG are in fluid communication with the steam cracking zone.

33. The system as in claim 31, wherein the transalkylation zone includes one or more outlets for discharging naphtha-range hydrocarbon compounds, and wherein the one or more outlets for discharging naphtha-range hydrocarbon compounds are in fluid communication with the steam cracking zone.

34. The system as in claim 31, further comprising an aromatics separation zone having one or more inlets in fluid communication within the one or more outlets of the transalkylation zone for discharging C9 aromatic compounds, one or more outlets for

discharging a raffinate comprising non-aromatic compounds from the transalkylated effluent, and one or more outlets for discharging an extract stream comprising aromatic compounds, wherein the one or more outlets for discharging the extract are in fluid communication with the BTX splitting zone, and wherein the one or more outlets for discharging the raffinate are in fluid communication with the steam cracking zone.

35. The system as in claim 24, wherein the BTX splitting zone comprises one or more outlets for discharging C10+ compounds.

36. The system as in claim 35, wherein the one or more outlets for discharging C10+ compounds are in fluid communication with one or more inlets of the selective hydrocracking zone.

37. The system as in claim 35, further comprising an initial feed treatment zone upstream of the steam cracking zone having one or more inlets in fluid communication with a source of initial feed, and one or more outlets in fluid communication with the steam cracking zone, and wherein the one or more outlets for discharging C10+ compounds are in fluid communication with one or more inlets of the initial feed treatment zone.

38. The system as in claim 24, wherein the selective hydrogenation zone includes one or more outlets for discharging naphtha-range hydrocarbon compounds, and wherein the one or more outlets for discharging naphtha-range hydrocarbon compounds are in fluid communication with the steam cracking zone; or the selective hydrocracking zone includes one or more outlets for discharging naphtha-range hydrocarbon compounds, and wherein the one or more outlets for discharging naphtha-range hydrocarbon compounds are in fluid communication with the steam cracking zone.

39. The system as in claim 24, wherein an aromatics separation zone having one or more inlets in fluid communication within the one or more outlets of the selective hydrocracking zone for discharging reaction effluent including selectively hydrocracked BTX+ compounds, one or more outlets for discharging a raffinate comprising non-aromatic compounds from the reaction effluent, and one or more outlets for discharging an extract stream comprising aromatic compounds, wherein the one or more outlets for discharging the extract are in fluid communication with the BTX splitting zone, and wherein the one or more outlets for discharging the raffinate are in fluid communication with the steam cracking zone.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2020/055892

A. CLASSIFICATION OF SUBJECT MATTER INV. C10G65/12 C10G69/06 ADD.		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols) C10G		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) EPO-Internal, WPI Data		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2019/161683 A1 (NARAYANASWAMY RAVICHANDER [IN] ET AL) 30 May 2019 (2019-05-30) paragraphs [0076], [0083] figure 1 -----	1-39
X	US 2015/141717 A1 (FREY STANLEY J [US] ET AL) 21 May 2015 (2015-05-21) claims 1, 7 figures 1-3 -----	1,24
X	GB 2 104 544 A (HYDROCARBON RESEARCH INC [US]) 9 March 1983 (1983-03-09) page 1, lines 51-60 claim 1 ----- -/--	1-39
☒ Further documents are listed in the continuation of Box C. ☒ See patent family annex.		
* Special categories of cited documents : "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search 18 January 2021		Date of mailing of the international search report 26/01/2021
Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016		Authorized officer Pardo Torre, J

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2020/055892

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2015/267130 A1 (BUTLEY GANESH VITTHALRAO [IN] ET AL) 24 September 2015 (2015-09-24) claims 1, 11 -----	1-39
X	US 2019/203130 A1 (MUKHERJEE UJJAL K [US]) 4 July 2019 (2019-07-04) claims 1, 3, 5 paragraphs [0041], [0047] figures 1, 3 -----	1,23,24

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2020/055892

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
US 2019161683	A1	30-05-2019	CN	109642164 A		16-04-2019
			EP	3516012 A1		31-07-2019
			JP	2019533041 A		14-11-2019
			US	2019161683 A1		30-05-2019
			WO	2018055555 A1		29-03-2018

US 2015141717	A1	21-05-2015	CN	105722951 A		29-06-2016
			US	2015141717 A1		21-05-2015
			US	2015259612 A1		17-09-2015
			WO	2015076993 A1		28-05-2015

GB 2104544	A	09-03-1983	CA	1191806 A		13-08-1985
			GB	2104544 A		09-03-1983
			NL	8202997 A		16-02-1983
			ZA	825157 B		29-06-1983

US 2015267130	A1	24-09-2015	NONE			

US 2019203130	A1	04-07-2019	CN	111836875 A		27-10-2020
			EP	3732269 A1		04-11-2020
			KR	20200091497 A		30-07-2020
			SG	11202006256T A		29-07-2020
			TW	201930574 A		01-08-2019
			US	2019203130 A1		04-07-2019
			WO	2019133880 A1		04-07-2019
