



Europäisches Patentamt
European Patent Office
Office européen des brevets



⑪ Publication number: **0 169 454 B1**

⑫

EUROPEAN PATENT SPECIFICATION

④⑤ Date of publication of patent specification: **02.05.91** ⑤① Int. Cl.⁵ **G06F 15/16**

②① Application number: **85108691.8**

②② Date of filing: **12.07.85**

⑤④ Name usage support through distributed processing networks linked by bridges and/or gateways.

③⑥ Priority: **20.07.84 US 631567**

④③ Date of publication of application:
29.01.86 Bulletin 86/05

④⑤ Publication of the grant of the patent:
02.05.91 Bulletin 91/18

⑥④ Designated Contracting States:
BE CH DE FR GB IT LI NL SE

⑤⑥ References cited:
EP-A- 0 074 865
FR-A- 2 472 234
US-A- 3 890 471
US-A- 4 287 592

⑦③ Proprietor: **International Business Machines Corporation**
Old Orchard Road
Armonk, N.Y. 10504(US)

⑦② Inventor: **Doster, William Allen**
8213 Overlake Drive, West
Bellevue, WA. 98004(US)
 Inventor: **Sachsenmaier, Robert**
7320 NE 8th Court
Boca Raton, Fl. 33431(US)

⑦④ Representative: **Bonneau, Gérard**
Compagnie IBM France Département de Pro-
priété Intellectuelle
F-06610 La Gaude(FR)

EP 0 169 454 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

Description

Technical Field

This invention relates to a method for causing "name directed" communications in a data communication network to be transferred selectively across bridging and/or gateway elements which respectively link separate communication channels and/or media within the network. As just used, the term "name directed" is intended to refer to communications which are directed to logical names rather than to specific locations (addresses) in the network. Such names are associatable with a variety of entities within the network, including physical objects (computers, their I/O attachments, human operators, network access adaptors, etc.) and less tangible objects such as programs and data sets. For reasons which will become apparent as this description progresses, this invention operates most effectively in local area type network environments.

Background Art:

Numerous publications disclose communications between distributed stations system, also known as Local Area Network. European Patent Application 0 074 865 for example describes an improved communications protocol for such a network. When several networks interconnect, they form an interconnected multiloop communications system for which US Patent 4 287 592 provides a path for smoothing and optimizing the transfer of data between distributed stations or processors.

Data processing entities, located at various network nodes (a node being defined herein as a point of coupling to a communication medium or channel) may operate in a distributed mode to establish unique and non-unique name associations for entities served through respective nodes, and also to establish communication sessions (i.e. logical connections) between respectively served entities, without requiring intermediate translations of related communications through shared processing entities containing directory tables relating all names to physical address locations. Such "related communications" as disclosed in European Patent Application 85104887.6 (EP-A-0160263), filed on April 23, 1985 ("Distributed Control of Alias Names...") and US Patent Applications No. 631,566 ("Non-Unique Names...") filed on July 20, 1984 (EP-A-0169455), are termed Name Check and Call Name Check messages, and are respectively used for enabling the processing system at an originating node to determine: (a) if adoption of a name would conflict with uses of the same name else-

where in the network; and (b) if a called object of a communication session is reachable in the network by a name and distinguishable unambiguously from other entities. These messages are passed from originating nodes to network media and/or channels, and examined by processing equipment at all respectively linked nodes. Each examining node performs a lookup comparison between a name in the message and names in a local Name Table (the latter representing names adopted for locally attached entities), and returns an acknowledging message if a match is encountered. The acknowledgements are used by the originating equipment to determine the action to take with respect to related name adoption and session establishment processes (complete or abort).

The present invention concerns a method for selectively controlling the handling of such name checking communications, and related acknowledgements, across bridging/gateway boundaries within the network. In the absence of present controls, the originating equipment would be responsible for defining hop count parameters restricting the passage across such boundaries (in order to avoid the possibility of having such communications circulate redundantly through "loops" formed by sequentially linked media/channels), and this would require considerable storage of information associated with network topology at all network nodes. Furthermore, the present restrictions permit networks to be dynamically expanded, by joinder of sub-networks associated with separate media/channels through added bridges, without inconveniencing users by requiring reestablishment of name associations and yet avoiding problems which would otherwise be encountered where the same name is used on a unique basis in plural sub-networks.

In the above-mentioned "preferred" local network environment, equipment at any network node may use a "datagram" type message to distribute information restrictively to a select group of entities identified by a name contained in the message. Such messages differ from universally broadcast messages in that they require attention only at nodes serving the members of the named entity group the present invention makes special use of such datagram type messages for controlling handling of name creation and session establishment communications across bridges and gateways linking sub-networks formed by equipment coupled to single media or channels (such sub-networks also being referred to herein as "primitive networks", and distinguished thereby from "complex networks" characterized as networks formed by linkage of two or more primitive networks).

One difficulty with managing the use of distributively created names in such networks is that as

primitive networks are joined into larger complex networks, name associations adopted before the joiner may become ambiguous. Although this could be avoided by requiring cancellation and recreation of all name associations at joiner, this could be unwieldy or impractical in networks containing thousands of entities and name associations.

Another problem is that joiner of primitive networks gives rise to the possibility of linking three or more media and/or channels serially to form redundant circulation loops. It is possible to avoid redundant circulation of name-directed communications in such loops, by requiring the originator of each such communication to add to its message a "hop count" parameter limiting the number of bridges/gateways through which that communication can pass. However, this would require equipment at every network node to be able to store information effectively defining the entire topology of the network (which would be a heavy storage burden for such equipment), and such information would have to be changed with each physical change of the network configuration (a sizable communication burden).

Summary of the Invention

The present invention provides an efficient method of avoiding the foregoing problems, relative to the use of logical name-directed communications in changeable complex networks.

More particularly, the invention provides a method for facilitating handling of name directed messages in a data communication network having plural communication media or channels linked by bridging facilities, each medium or channel linking plural data processing stations, said stations being adapted for operating to share access to associated entities, across the network and to initiate communications with remote entities by means of messages directed to logical names assigned to the entities and not to addresses representing specific physical locations of respective entities, said messages not requiring intermediate handling within the network for translating respective names to addresses, characterized in that it comprises:
at any one of said stations, originating a first name directed message and transmitting said message over a first medium or channel to which said station is directly coupled; said first message containing a logical name and having a predetermined first form which restricts its handling so that the information therein is not transferred beyond said bridging facilities to media or channels other than said first medium or channel;
monitoring said first medium or channel at said one

station for communications representing responses to said first message;

if a response is received, adopting appropriate processing at said one station;

5 if no response to said first message is received at said one station, transmitting a second name directed message from said one station over said first medium or channel; said second message corresponding to said first message but having a predetermined second form different from said first form; said second form operating to allow responsive handling of the information contained in said message only at bridging facilities directly coupled to said first medium or channel;

10 15 monitoring said first medium or channel as said one station for responses to said second message; at each bridging facility receiving said second message, conditionally generating a third message corresponding to the second message and having a third predetermined form;

20 transmitting said third messages from respective facilities to other media or channels which are linked by respective facilities to said first medium or channel;

25 monitoring said other media or channels at respective facilities for responses to respectively forwarded third messages; and

30 forwarding responses to said third messages directly to said one station, via said first medium or channel, for handling as responses to said second message.

35 These and other aspects, features, advantages and benefits of the present invention may be more fully understood and appreciated by considering the following description and claims.

Description of the Drawings

40 FIGURE 1 illustrates a typical complex network configuration representing the environment in which the present invention will be used;

FIGURE 2 illustrates problems in such networks which are intended to be avoided by means of the present invention;

45 FIGURE 3 illustrates formats of Name Check and Call Name Check messages used respectively for name adoption and session establishment operations at nodes of the typical network shown in FIGURE 1;

50 FIGURE 4 illustrates the form of "bridge" datagrams used in accordance with the present invention for restrictively transferring Name Check and Call Name Check communications between bridged media/channels in the exemplary environment;

55 FIGURES 5-7 illustrate, by means of sequence flow diagrams, the handling of Name Check, Call Name Check and Datagram type communications in ac-

cordance with the present invention; and FIGURE 8 is a table illustrating the information used by bridging facilities in respect to establishing the timeout parameters of foregoing communication processes.

Detailed Description of the Invention

Table of Contents

1. Introduction
2. Statement of Problem
3. Present Solution (Overview)
4. Formats (Name Check, Call Name Check, Bridge Datagram
5. Name Check and Call Name Check Handling
6. Bridge Datagram Handling
7. Setting of Node Timeouts
8. Conclusion

1. Introduction

Referring to FIGURE 1, primitive networks A-D are linked into a complex network 10 by bridging facilities discussed below (refer to the definitions of "primitive" and "complex" given previously). Each primitive network contains a respective medium/channel 12A, 12B, 12C, 12D having respective nodes or taps 13A, 13B, 13C, 13D, such nodes serving respective communication and data processing facilities 14A, 14B, 14C, 14D. Bridging facilities shown at 15-18 link the media 12A-12D to form the complex configuration. Such bridging facilities may couple to respective media through nodes either physically separate from the nodes 13A-13D or they may reside physically within any of the facilities 14A-14D and share respective nodes. Each primitive network may serve multiple processing facilities or stations 14 through nodes 13 of the respective medium/channel.

Bridging facilities of the type represented at 15-18, but without the adaptations to be described presently for handling name-directed communications, are well known in the art. Such facilities are described, for example, in U. S. Patents US-A-4,287,592 and US-A-4,365,331. To the extent that these descriptions may be relevant to the present disclosure, they are incorporated herein by this reference. In general, such facilities are connected to two media or two channels (time or frequency divisions) of one medium, and they operate to pass information bearing signals bidirectionally between associated media/channels. These facilities may include programmed microprocessors and storage units permitting them to perform sophisticated buffering and format translation operations on information signals in transit between linked

media/channels. In the configuration exemplified in FIGURE 1, bridge facility 15 links media/channels 12A and 12B, bridge 16 links media/channels 12A and 12C, bridge 17 links media/channels 12B and 12C, and bridge 18 links media/channels 12C and 12D.

The foregoing processing facilities (14A-14D) operate through respective network nodes (13A-13D), in the manner described in the cross-referenced co-pending patent applications, to adopt logical (alias) names for respective entities (operators, programs, data sets, etc., served at the respective node sites). These names are characterized as logical because they need have no direct associations with physical locations of respective entities. The adoption procedure is characterized by communications over the network which do not require any intermediate handling to translate logical names into address parameters representing specific nodes or sites in the net work.

In general, and ignoring the handling across bridges to be described later, such communications involve broadcast transmission of a Name Check message from the facility seeking to adopt a name, and monitoring of the message by the other facilities. Each facility 14A-14D maintains Name Tables defining name associations adopted at the respective facility, and each facility may act independently of the others to initiate a communication process for adoption of a new name association. The initiating facility broadcasts a Name Check message, as mentioned above, which contains the name which that facility proposes to adopt. Other facilities monitor the message, compare the message name to names in respective name tables, and return an acknowledging communication if a match is found. If no match is found, the monitoring facility ignores the Name Check.

If a processor originating a Name Check receives one or more acknowledgements, and if the name sought to be adopted is intended to be used on a unique basis in the network, the originating processor recognizes a name conflict, rejects the name and ends the adoption process. If no acknowledgement is received, the name may be adopted (entered into the processor's Name Table).

A similar process pertains to session establishment. If, for instance, a program P, running on a processing facility at one node, requires access to a data set known by a particular name, the processing facility at the node executing P broadcasts a Call Name Check message directed to the needed data set by name. This message contains the logical names of the calling and called entities (in this case P and the name of the needed data set). Processing facilities receiving this message check respective Name Tables, and return an acknowl-

edging message if and only if an entry matching the called name is found. If the originating node receives no acknowledgements, it aborts the session call process. But if it receives an acknowledgement it continues the process with other communications until a session is established (see the above referenced European Patent Application). Thus, the node serving P could retrieve the data set by name; i.e. without any prior information as to the physical location of the data set in the network (and therefore transparent to all program processes running on the node processors serving P and the required data set.

2. Statement of The Problem

Now suppose that in the complex network environment exemplified in FIGURE 1, the name assigned to a data set which is the object of a session call is used conflictingly in several primitive networks. This could occur, for instance, if previously isolated primitive networks were joined to form a complex configuration, and several of the joined networks contained nodes using the above-mentioned data set name. This situation, and the problems it could present, are illustrated in FIGURE 2.

Operator "Bill", acting through keyboard/display terminal 51 and software running on processing facility 52 (application program, etc.) may require access to a data set "accounts receivable". Now assume that processor 52 is linked to network A as shown, and that the data set required by Bill's application is stored at 53 on a disk file 54 served by a processor 55 linked to network A. But assume also that other non-pertinent data sets named "accounts receivable" are being maintained on networks B and D; the one on network B stored at 60 on a disk file 61 accessible through processing facility 62, and the one on network D stored at 70 on disk file 71 accessible through processing facility 72.

Now assume that when Bill's application program calls for "accounts receivable", facility 52 checks its Name Table, determines that the required data set is not attached locally, and broadcasts a Call Name Check over medium 12A indicating "Bill" as the calling entity and "accounts receivable" as the called entity. If this message could be transferred through bridges without restriction, and monitored at nodes of all media 12A-12D, several problems occur. First, acknowledgements would be returned by facilities 55, 62 and 72 which to facility 52 could appear conflicting. Second, the Call Name Check message could circulate repeatedly through the loop formed by medium 12A, bridge 16, medium 12C, bridge 17, medium

12B, and bridge 15, and also through the loop formed by medium 12A, bridge 15, medium 12B, bridge 17, medium 12C and bridge 16.

This situation would not have arisen if each facility such as 52 could restrict the number of bridges allowed to be crossed by its Call Name Check (and Name Check) communications (e.g. by specifying a limiting "hop count" value of 1; see the cross-referenced "Distributed Control" application), or if the network were structured to prevent conflicting name adoptions. However, these solutions present other problems. Requiring the originating facility to specify a hop count value imposes a burden on all processing facilities of maintaining information relative to network topology sufficient to ensure that loops formed by bridges are not fully traversed. But a network such as 10 may serve many processing facilities, and it may be changing dynamically as new primitive networks are added, so that maintenance of suitable topology information at each facility would be quite difficult. On the other hand, structuring the network to prevent conflicting name adoption would require re-creation of all name associations after each network change; which also would not be practical.

3. The Present Solution (Overview)

The present invention provides a simpler solution, by organizing the processing facilities such as 52 to transmit their Name Check and Call Name Check communications in a series of discrete operations fanning out progressively through media and bridges further removed from the originating node. The fanning out process is transparent to the originating node, and requires the processing facilities at the bridges to bear the burden of determining "hop count" ranges for such communications. However, since such networks have far fewer bridging facilities than general purpose processing facilities, this tends to considerably lessen the processing burdens imposed on the non-bridging nodes, as well as considerably reduce the related volumes of network traffic, in comparison to requiring all nodes to determine respective hop count restrictions.

The technique used presently for controlling the foregoing fanout process involves transmission of Name Check and Call Name Check information in different first and second forms. These forms and the processes involved in their handling will be discussed at length later. For the present overview, it is observed that in the first form the information is arranged as a broadcast message which has a range of one primitive network medium or channel (i.e. cannot pass across bridges), and in the second form, the information is encapsulated in a

"datagram" (see the cross-referenced "Non-Unique Name" application) directed exclusively to bridges which are directly linked to the primitive medium.

Upon originating a Name Check or Call Name Check communication in the first form, the processing facility at the respective origin node times out for a predetermined first time period allowing for acknowledgements to return from nodes within the "primitive" range of that communication. If no acknowledgements are received, this communication and timeout procedure may be repeated one or more times, up to a predetermined retry limit.

This type of repetition is generally desirable, because these name checking requests are transmitted in a broadcast mode. Therefore, an error in the transmission or reception of the associated signals could cause the receiving processor to misinterpret and mis-handle the request (for instance, an error in transfer of the message type information or the name to be checked could cause a node having a potential name match to ignore the message).

If one or more acknowledgements are received, the action taken by the originating facility depends on the related communication process (name adoption or session establishment). If the process is for name adoption, and if the proposed name is intended for use on a unique basis, receipt of acknowledgement represents a conflict, and the name is rejected. If the process is for session establishment, acknowledgement represents confirmation of the existence of the called entity within the directly linked primitive network, and the process is continued with other communications, over the same primitive network, which are not relevant to the present invention (see the "Distributed Control" reference).

If a processing facility originating a Name Check or Call Name Check broadcast (first form) communication receives no acknowledgement (after all repetitions if the first form broadcast is repeated up to a retry limit), it sends the same information out over its primitive net medium in the second form. In this form, the information is encapsulated in a datagram directed to the name "bridge", and is given special interpretive handling at each bridge facility linked to the originating facility through a primitive net. In such handling, each bridge extracts the information constituting the original Name Check or Call Name Check broadcast and re-broadcasts that information in its original (first) form. The bridge processing facility then times out for a predetermined time period allowing for acknowledgement by nodes linked to the bridged medium.

If a bridge which has re-broadcast a Name Check or Call Name Check receives one or more acknowledgements, it forwards the first acknowl-

edgment to the originating node (via the medium/channel linked to that node). If more than one acknowledgement is received, and if that represents a network conflict, the bridge processor determines the nature of the conflict and issues a communication over the bridged medium remote from the originating node, informing acknowledging nodes of the conflict. If no acknowledgements are received, the action taken by the bridge facility depends on its hop count distance from the originating node (a bridge directly linked to the originating node via a common medium or channel is at a hop count distance of 0, and bridges linked through additional media or channels are at higher valued hop count distances directly corresponding to the number of intervening additional media or channels).

A bridge at hop count 0 distance, which receives no acknowledgement of the foregoing re-broadcast, consults a local table of network topology, and if the medium or channel to which it links is not coupled to a further bridge (one "further removed" from the originating node) the bridge terminates its handling of the respective Name Check or Call Name Check communication. If a bridge at 0 hop count distance receives no acknowledgement, and is capable of reaching a further bridge without looping (i.e. without passing through another bridge at 0 hop count distance from the origin node), it forms a second datagram containing a hop count value related to the number of further bridges which can be successively reached from this bridge without looping.

Each bridge receiving the above-mentioned second datagram decrements the hop count and repeats the process performed by the preceding bridge relative to a respective further removed medium or channel (i.e. re-broadcasting the Name Check or Call Name Check; timing out for acknowledgements, relaying the first acknowledgement if one is received, and if none is received, either extending the process to the next level of bridging, if the hop count value is not 0, or concluding the process).

At any level of bridge handling, termination of an extended and unacknowledged communication handling process requires no further communication back to the originating node. The absence of such acknowledgement is effectively inferred by the originating node due to a timeout process conducted at that node. The latter timeout is established in accordance with a "process timeout" parameter determined by inter-action between the non-bridging and bridging nodes when any non-bridging node is first activated on the network.

Before a newly activated non-bridging node can enable itself for name adoption or session establishment communications (i.e. Name Check or

Call Name Check broadcasts), it is required (by protocol) to send an initial datagram addressed to "bridges" and containing a request for timeout initialization. The processing facilities at bridges distinguish such initial requests from datagrams containing encapsulated Name Check or Call Name Check functions by checking local tables and recognizing that the origin node is in an uninitiated state (see "Setting Of Node Timeouts" infra). The local table at each bridge receiving this request datagram (i.e. each bridge at hop count distance 0 from the requesting node) contains information related to the topology of the network on either side of the bridge, which is stored when the network is either initialized or reconfigured. In response to an initialization request, the bridge processor consults its table, and extracts a process delay factor which is sent back to the node requesting initialization in a response message.

This delay factor is just larger than the projected "worst case" delay in signal propagation and information handling between the request originator and the most distant node accessible through the respective bridge without passing through a further bridge forming a looping path back to the originator. The processing facility at the node requesting initialization examines the returned delay factors and selects the largest value as its "process timeout" function. In subsequent name adoption and session establishment operations, the respective facility uses this function to set a time limit for receiving acknowledgements. Thus, if any bridge completes its handling of a respective Name Check or Call Name Check operation without receiving an acknowledgement, and thereby terminates its handling of the operation, the termination will fall within the timeout set at the originating node and effectively dealt with as an absence of acknowledgement.

Each node is also initialized with a "primitive timeout" function, for timing its Name Check and Call Name Check operations relative to its primitive network. This function is related to the longest propagation and processing delay normally anticipated within the respective primitive network. A node originating a Name Check or Call Name Check, and receiving no acknowledgement within the interval measured by its primitive timeout factor, effectively may infer that that communication will not be acknowledged, and proceed accordingly with the next appropriate action (retry the communication, send bridge datagram, etc.)

4. Formats (Name Check, Call Name Check, Bridge Datagram)

FIGURES 3 and 4 illustrate formats of pres-

ently relevant Name Check, Call Name Check and datagram communication functions. Name Check and Call Name Check have control fields 100-105 which include destination field 100, origin address field 101, type field 102, hop count field 103, name field 104 and other information 105. The value in the type field distinguishes between Name Check and Call Name Check functions (N1 for Name Check; N2 for Call Name Check). The value in the destination field indicates a broadcast destination for both types of functions (or it may be treated as a "don't care" value if the type field values N1 and N2 are taken to imply broadcast handling). As broadcast type communications, these functions require special treatment, since traditional broadcast type functions are usually not acknowledged and these functions require conditional acknowledgement (if the name field 104 matches a name in the receiving node's Name Table). The origin address 101 is the address of the node originating the communication. It is used as the destination address in not-shown acknowledgements (see cross-referenced "Distributed Control" application for information on acknowledgement formats). The name field contains either a name proposed for adoption, if the communication is a Name Check, or the name of an entity which is the object of a session call if the communication is a Call Name Check.

The rest of the information, field 105, depends on the communication type. For Call Name Check, this includes the caller's name (the entity for which the session is being called), and for both types N1 and N2 it includes various numbers permitting acknowledgers to identify the communication and the matched name with abbreviated codes (as in any contemporary communication system, it is expected that each node may issue a number of communications of this nature with overlapping timeouts; thus, it is important to be able to identify individual communications and their names, and being able to do so with abbreviated codes is obviously efficient).

Datagram type communications contain control fields 120 - 125 which direct their handling at receiving nodes. The type (N3) distinguishes datagrams (see the "Non-Unique" application previously referenced) from other forms of communication. The destination is indicated as "broadcast", but the accompanying "other" information is processed only at nodes which have Name Table matches for the "non-unique" datagram name (which, for datagrams presently of interest, would be "bridge" or a name having similar meaning of association with bridging nodes). The origin address is the address of the node originating the datagram transmission. The other information in the "bridge" type datagram includes either a request for initialization sent by a non-bridging node or the content of a pre-

viously unacknowledged Name Check or Call Name Check communication.

The values set in hop count fields 103 and 123 depend on the nature of the communication and its origin. Field 103 is either to be ignored (treated as "don't care" condition) or set to a 0 value if the respective Name Check/Call Name Check originates at a non-bridging node. If the respective Name Check or Call Name Check originates at a bridging node, field 123 is always set to 0. Field 123 is set to 0 if the datagram originates at a non-bridging node. If the datagram is one issued from a bridging node, its value will depend on the position of the respective node in the network path through which the respective information is being handled. If the node is the first bridge in the handling path, the value set will be one selected by that bridge. If the datagram is issued by a bridge other than a first bridge, the value in field 123 will depend on the number of preceding bridges which have handled the same information (i.e., the value is decremented by the first bridge and each subsequent bridge).

5. Name Check And Call Name Check Handling

In the preferred environmental system, each node includes a processing facility (e.g., an IBM Personal Computer and supporting microprocessing equipment) for performing general purpose data processing operations, and signalling operations relative to local area networks; e.g., networks of the type described in the referenced U.S. Patent 4,365,331 to Biba et al. Such facilities operate under the direction of supervisory and application programs of presently well known form to perform such operations. When a node's processing facility arrives at a stage of a task or process where it requires a name-related operation presently of interest either adoption of a name for a locally served entity, or initiation of a session (i.e., logical connection) between a locally served entity and another entity known only by a logical name, it performs the name checking process which is described next with reference to Figures 5 - 7.

FIGURE 5 describes the process of name checking communication generally. FIGURE 6 details parts of the process of FIGURE 5 relating to handling of timeout and acknowledgements at the node originating a name checking communication. FIGURE 7 details the handling of datagram communications at various network nodes in the present environment.

This process, which may require plural discrete stages of data handling and signal communication, is used to check if the object entity name (i.e., the name proposed for adoption, or the name which

represents the object of a session call), has conflicting or ambiguous usage in the network; i.e., if a name proposed for adoption is assigned to another entity, or if the object of a session call can be contacted by the Call Name Check name. On determining that its current task requires name usage (step 140, Fig. 5), the processing facility checks a local name table (141, Fig. 5; also refer to the "Distributed Control" application previously referenced for the format of such tables). If the name to be checked matches a local entry, the process is concluded locally (stage 142, Fig. 5).

In the case of proposed name adoption, a match at this stage represents prior usage for another locally served entity, and the process concludes with posting of "in use" status to the program requesting the adoption (which then aborts or discontinues the name use process if such use requires exclusive association with a single entity) adoption process. In respect to session establishment, a local match at this stage indicates that both entities (the called and calling entities) are accessible locally (i.e., without signal communication through the network), and the process is carried forward to conclusion locally (i.e., the session is established or the process is aborted, depending on other local conditions not presently relevant).

If the name being checked does not match a local table entry, the process for broadcasting a Name Check or Call Name Check signal over the directly accessible primitive network is started. The previously mentioned primitive and process timeouts are started (stage 143, Fig. 5), and the retry count is updated (stage 144, Fig. 5); in this instance, set to an initial value representing the first try. The next action is conditioned on the process type (stage 145, Fig. 5). For name adoption, a Name Check message (Fig. 3) is prepared, and when the network becomes available (the method of access to the network medium is not relevant presently), corresponding signals are broadcast over the locally accessible medium (or channel) which forms the primitive network directly linked to the respective node (stage 146, Fig. 5). If the process is to establish a session, a Call Name Check message is prepared, and corresponding signals are broadcast over the local medium (stage 147, Fig. 5).

After either of the foregoing operations, the local processor is released to perform other functions, but remains accessible, through interruption, for handling information arriving through the network, including acknowledgements of its Name Check or Call Name Check signals (148, Fig. 5 and Fig. 6 to be discussed later). When the primitive timeout concludes, the originating facility conditions its next action on the state of the retry count (150, Fig. 5). The presently preferred practice is to take

the retry action only if the system has received no acknowledgement of its last name checking signal. However, it would not be considered inconsistent with the present invention to conditionally retry the primitive network communications (up to the retry limit) even if previous communications have been acknowledged.

If the retry limit has not been reached, the primitive timeout is restarted (151, Fig. 5), and actions 144 - 149 are repeated via recursion path 152, 153 (circled "a"). If the associated broadcast communication is acknowledged, the process is concluded in a manner described later with reference to Fig. 6. If the broadcast communication is unacknowledged when the retry limit is exhausted, a datagram is prepared (154, Fig. 5) and corresponding signals are sent to bridges, for extending the name checking process across bridges in the respective primitive network. Specifics of datagram processing are given later in the discussion of Fig. 7.

The right side of Fig. 5 indicates the operations performed at nodes within the primitive network in response to the signals broadcast at step 146 or step 147. On receiving and buffering these signals (170, Fig. 5), the node processing facility distinguishes between name checking requests and other functions not presently relevant (171, Fig. 5). If a name checking request has been received, the respective name is compared with entries in the local Name Table (172, Fig. 5). If the comparison fails (no matches), the communication is ignored, but if a match is found the node transmits an acknowledging signal (173, Fig. 5). As suggested at 174, the acknowledging signal is directed specifically to the node which requested the check (using the origin address 101, Fig. 3, contained in the request).

The handling of Name Check and Call Name Check acknowledgements at the request origin is shown in Fig. 6. After starting the (primitive and process) timeouts, and sending the associated Name Check or Call Name Check request, the originating processing system is released to perform other operations (181, Fig. 6). While performing such other operations, the processor may be interrupted (182, Fig. 6) to attend to unscheduled events, including presently relevant events such as ending of a timeout related to a communicated request or reception of a request acknowledgement.

If an interruption is caused by an incoming communication, the communication type is distinguished (183, Fig. 6). If it is an acknowledgement of a pending Name Check or Call Name Check request the acknowledgement is associated to the related software process (184, Fig. 6), via the sequence information contained in both the original

request and the acknowledgement, and corresponding status information is passed to that process (185 or 186, Fig. 6).

If the related process concerns name adoption, the reported status 185 indicates existing use of the subject name at another network node identified in the acknowledgement and the adoption is discontinued (see the "Distributed Control" reference). If the related process concerns session establishment, the reported status 186 indicates existence and location of the called entity (permitting other communications for completing the session establishment function to be carried out on a point-to-point basis). The handling of acknowledgements relating to communications other than name checking requests is not relevant to the present discussion, and therefore is not shown in Fig. 6. The handling of plural acknowledgements of a single name checking request is explained later in the discussion of datagram handling.

If the previously mentioned interruption was caused by expiration of one of the presently relevant timeouts, the action taken in the interruption process depends on the specific timeout. If the primitive timeout has concluded without an acknowledgement, and the retry limit has not been reached (149, 150 Fig. 5), the processor restarts the primitive timeout (151, Fig. 5) and repeats the request transmission and acknowledgement monitoring process (144 - 148, Fig. 5; 183 - 186, Fig. 6). If the primitive timeout ends and the retry limit is reached, processor initiates process 154 (Fig. 5) for sending a bridge datagram containing the associated Name Check or Call Name Check request, and thereby extending the name checking process across bridges linked to the requesting processor's primitive network. This extension process is discussed below in reference to Fig. 7.

If the interruption was caused by expiration of the process timeout function without acknowledgement, the processor concludes the respective process (operation 190, Fig. 6); either adopting the proposed name (if the original request was a Name Check) or abandoning the session establishment effort (if the request was a Call Name Check). The actions taken in respect to interruptions other than those discussed above are not relevant to the present invention, and therefore are not shown or discussed.

6. Bridge Datagram Handling

The handling of bridge type datagrams at bridging and non-bridging nodes is indicated in Fig. 7. Non-bridging nodes originate such datagrams for one of two purposes: to request initialization, or to extend a name checking process across bridges

interfacing to associated primitive networks. Bridging nodes originate bridge datagrams to communicate with other bridging nodes; either to extend name checking requests to networks further removed from a non-bridging request originator, or to exchange other information (e.g., information relating to changes in network topology).

Initialization requests from non-bridging nodes are instigated by respective processors at "start-up" times (presently meaning times when respective nodes are first actively coupled to the network, or re-coupled after having been taken down to correct associated system failures). The information for such request, which is preset in the system's memory, is retrieved by the system (200, Fig. 7) and encapsulated in a bridge datagram (201, Fig. 7; see Fig. 4 for the datagram form). The datagram is broadcast over the associated primitive network (202, Fig. 7). As explained previously, only processors at bridges respond to such requests and do so by returning acknowledging signals containing delay factor information. The formation of such responses is discussed later under "setting of node timeouts". As noted previously, the longest delay factor is selected by the request originator as its process timeout function.

Bridge datagrams to extend name checking from non-bridging to bridging nodes are formed in the manner illustrated at 204 - 206 (Fig. 7). When the processor at a node originating a name checking request detects the limit of its primitive retry action, without having received an acknowledgement of its associated communications (operations 204), it retrieves the related information (205) and forms the datagram (206). Corresponding signals are placed on the directly accessible communication medium (operation 207) to communicate the information to bridges linked to that medium. The bridges extend the respective name checking communication by actions discussed later. A bridge receiving one or more acknowledgements of its extended communications passes the first such back to the originating processor through the network. Each bridge monitors its media on both "sides" (including the medium directly linked to the datagram origin), and the bridges thereby cooperate to ensure that no more than a single acknowledgement of such a datagram returns to the originating node (from all of the bridges primitively linked to that node).

The processing facility which originated the datagram is eventually interrupted (208) by a condition related to that communication; either a returning acknowledgement (209) or a local process timeout condition (210). When this occurs, the associated name checking process is concluded. If that process was for unique name adoption, and the datagram was acknowledged, "in use" status is

posted to the associated process program. If the process was for session establishment, and was acknowledged, information indicating a "good response" and identifying the first acknowledging node is posted to the associated program. If the process timeout expired without acknowledgement, and the process related to name adoption, "good status" is posted to the associated program which causes the name to be adopted (entered into the local name table in association with the respective local entity). If the timeout expired for a datagram containing a Call Name Check, "unsuccessful" status is posted indicating to the associated program that the name of the entity sought to be contacted is not recognizable within the network.

When a bridging node receives a datagram (220, Fig. 7), its processor inspects the type field (221) to distinguish between datagrams directed to bridges and other datagrams (refer to the referenced "Non-Unique" application for descriptions of other datagram forms and their usage). Datagrams not directed to bridges are not relevant to the present discussion. On recognizing a "bridge" type datagram, the respective bridge processor inspects the datagram origin (222, Fig. 7), since different handling is required for bridge datagrams received from bridging nodes and non-bridging nodes. If the datagram source is a non-bridging node, the form of the datagram information is inspected (223, Fig. 7) to distinguish between requests for initialization and datagrams requesting extension of name checking operations. If such a datagram contains a request for initialization, the bridge processor consults its table (see discussion of Fig. 8 below), and returns a related delay factor to the request origin (224, Fig. 7).

If a datagram originated by a non-bridging node contains a name checking request, the bridge processor extracts a hop count factor from its associated table (225, Fig. 7), and initiates the process for extending that request to network paths spanned by the respective bridge. The extracted hop count is a value designed to extend the range of the name checking request through networks spanned by other bridges, and out to a medium furthest removed from the original requesting node, but restricted so that the request can not circulate through another bridge forming a looping path back to the originating node. A bridge receiving a name checking datagram from a preceding bridge initiates the same extension process, but with a hop count value contained in the received datagram (226, Fig. 7).

The process performed by a bridge for extending a name checking request to a respectively spanned medium (226 - 241, Fig. 7) includes: decrementing the hop count (226), either the count set at 225 or the count contained in a datagram

Received from a preceding bridge: starting primitive process timeouts related to the path beyond the bridge (227); broadcasting the name checking message contained in the received datagram over the spanned medium (228); and incrementing a retry count (229). The primitive timeout set at 227 is a function of the longest handling and response delays anticipated relative to the primitive path beyond the bridge, and the process timeout is a function of the longest delays anticipated over the full hop count range of the path beyond the bridge (including successive bridges and media).

The extension process yields either one or more acknowledgements (230 - 233) or actions evoked by timeout interruptions (234 - 241).

If an acknowledgement is received (230) an acknowledgement count is incremented (231). The first received acknowledgement is passed back, along the path from which the related datagram was received (232), either to a preceding bridge or the node which originated the request (whichever is directly accessible from the node handling the acknowledgement). If more than one acknowledgement is received during one timeout period, a conflict signal is transmitted (233) towards the sources of acknowledgement. The foregoing statement applies only to acknowledgements received from the side of the bridge which is remote from the source of the respective datagram. However, in the primitive network serving a non-bridging node which originates a name check datagram, each bridge should be adapted to recognize an acknowledgement of the datagram transferred from another bridge to the medium which links directly to the originating node, and increment its acknowledgement count in response to that acknowledgement. This would lessen signal traffic in the primitive network, since only the first acknowledgement of a datagram would be relayed through bridges, even if acknowledgements are received at plural bridges. Furthermore, it would simplify the handling of signal transmissions indicating conflicting name usage since each bridge would be responsible for sending such signals to the respective path extending beyond the primitive network, and would do so even if it received only one acknowledgement from the respective path when another bridge transferred an earlier acknowledgement to the primitive path.

If the primitive timeout ends without acknowledgement (234, Fig. 7) and the retry limit has not been exhausted, the primitive timeout is restarted (235, Fig. 7) and operations 228 and 229 are repeated. If the retry count reaches the limit (recognized at 236, Fig. 7) the action taken next is conditioned (237) on the value of the hop count as decremented at 226. If the value is other than 0, the bridge forms a datagram containing the de-

cremented hop count (but corresponding otherwise to the datagram received at 220), and transmits that datagram to the path directed away from the request originator (action 238, Fig. 7). That transmission is followed either by receipt of acknowledgement (230) or expiration of the respective process timeout (240). If the process timeout expires, or the hop count value inspected at stage 237 is 0, the handling of the datagram communication process at the respective bridge is concluded (241). At such conclusion (no acknowledgements after full term handling), the bridge takes no further action relative to the network.

7. Setting Of Node Timeouts

Each bridge maintains a table having the form suggested in Fig. 8, for responding to requests for initialization from non-bridging nodes (see 223, 224, Fig. 7). The table reflects the topology of the network on both sides of the respective bridge (sides "1" and "2"). The entries in the table rows are established when the bridge is first introduced into the network (e.g., through information keyed into the bridge processing facility by a technician responsible for setting up the bridge attachment).

The table columns indicate the parameters associated with the nodes directly linked to each side of the respective bridge. There is at least one column of entries for each node address (addresses A_i and A_j are illustrated as representative), and columns may be provided for bridging nodes (type B) as well as non-bridging nodes (type NB). As indicated in the footnotes to Fig. 8, there may be more than one column of entries for a node having plural co-active requests. The columns associated with bridging nodes can be used to enable the respective bridge to ascertain the hop count topology extending beyond another bridge primitively linked to the respective bridge.

The delay factor for bridging type nodes is "X" ("don't care"). The delay factor for non-bridging nodes is a constant; "D1" for nodes accessed through side 1 and "D2" for nodes accessed through side 2. The value of the constant is a function of the network topology extending beyond the opposite side of the bridge. Thus, D1 is a function of the topology viewed at side 2 and D2 is a function of the topology viewed at side 1. The timer values are the values used at the respective bridge for setting its datagram handling timeouts relative to the nodes designated in each column. The hop count values are the values used for initializing hop count functions relative to name checking datagrams received from associated non-bridging nodes (see 225, Fig. 7). The sequence number and frame identity (ID) terms are set in

accordance with information in name checking datagrams currently being processed, and permit the bridge to associate acknowledgements with respective request origins. The state information distinguishes between initiated and uninitiated node states, allowing the bridge to reject name checking datagram requests erroneously issued by uninitiated nodes.

8. Conclusion

We have described above a method for extending name checking communications, which are originated independently by "peer" processors across bridging interfaces between primitive portions of a complex network. Such extensions are handled without ambiguity, and with minimal burdening of the originating processors, by processors located at the bridging interfaces. This tends to lessen the traffic burden on the network (since acknowledgements of an extended name checking communication, other than the first acknowledgement, are "trapped" at the first bridge sensing such acknowledgements), as well as the processing burdens imposed on the non-bridging processors.

The foregoing techniques can be modified in several ways without departing from what we presently consider to be our invention.

For example, the function achieved by setting the hop count at the first bridge in the extension path of a name checking request could also be realized by requiring each bridge to compare identities of newly received name checking datagrams with identities of datagrams currently being timed out. Thus, if an extension process transferred across several bridges enters a bridge completing a looping path, the latter bridge would detect conflict with a datagram transferred earlier in the opposite direction, and suppress (ignore) the newly received datagram.

Furthermore, the extended communication effect achieved by means of bridge datagrams could be realized (less efficiently, but possibly more reliably) by means of point-to-point communications. Instead of sending a datagram, a node originating a name checking process could establish individual sessions with each bridge linked to its primitive network, and transfer the information to be handled across each bridge in a session communication (see the referenced "Distributed Control" application for the form of such communications). Each bridge could do the same for communicating with the next further level of bridges relative to a name checking process. Furthermore, the timeout initialization process could also be conducted by means of separate session communications between a

non-bridging node and each primitively coupled bridging node.

Claims

1. In a data communication network having plural communication media or channels (Fig.1, 12A, 12B, 12C, 12D), linked by bridging facilities (Fig.1, 15 to 18), each medium or channel linking plural data processing stations (Fig.1, 14A, 14B, 14C, 14D), said stations being adapted for operating to share access to associated entities across the network and to initiate communications with remote entities by means of messages directed to logical names assigned to the entities and not to addresses representing specific physical locations of respective entities, said messages not requiring intermediate handling within the network for translating respective names to addresses, a method for facilitating handling of said messages, characterized in that it comprises:

A. at anyone of said stations, originating a first message and transmitting said message over a first medium or channel to which said station is directly coupled; said first message containing a logical name and having a predetermined first form which restricts its handling so that the information therein is not transferred beyond said bridging facilities to media or channels other than said first medium or channel;

B. monitoring said first medium or channel at said one station for communications representing responses to said first message;

C. if a response is received, adopting appropriate processing at said one station;

D. if no response to said first message is received at said one station, transmitting a second name directed message from said one station over said first medium or channel; said second message corresponding to said first message but having a predetermined second form different from said first form; said second form operating to allow responsive handling of the information contained in said message only at bridging facilities directly coupled to said first medium or channel;

E. monitoring said first medium or channel at said one station for responses to said second message;

F. at each bridging facility receiving said second message, conditionally generating a third message corresponding to the second message and having a third predetermined

form;

transmitting said third messages from respective facilities to other media or channels which are linked by respective facilities to said first medium or channel;

G. monitoring said other media or channels at respective facilities for responses to respectively forwarded third messages; and

forwarding responses to said third messages directly to said one station, via said first medium or channel, for handling as responses to said second message.

2. The method according to claim 1 characterized in that:

said monitoring for responses to said first message of said one station is timed for a predetermined first timeout interval;

the activities at said one station relative to said first and second messages, including the monitoring for responses to said second message, are timed by a second predetermined timeout interval; and

the monitoring for responses to said third messages at said bridging facilities is timed for a predetermined third timeout interval which may be different at different said facilities.

3. The method according to claim 2 characterized in that said second timeout interval is established at the initial powering up of said one station and thereafter maintained by the station.

4. The method according to claim 3 characterized in that the second timeout interval is established via initial communications between said one station and bridging facilities coupled to said first medium or channel and determined by information furnished by said facilities in said communications.

5. The method according to claim 4 characterized in that:

said facilities act in said initial communications to furnish delay factor information representing longest delays in request and response handling relative to portions of the network spanned by respective facilities; and

the value chosen for timing said second timeout interval is the largest of the values

furnished by said facilities.

6. The method according to anyone of the claims 2 to 4 characterized in that:

said first message is a message of either a first or second type, both types being used for different purposes but having a common effect of providing indication to said one station of whether or not a name contained in the message is associated with an entity remote from said one station.

7. The method according to claim 6 characterized in that:

messages of said first type are Name Check messages used for the purpose of enabling the originating one station to determine if a name which that station is seeking to adopt for a locally served entity is currently in use at a remote station; and

messages of said second type are Call Name Check messages sent for the purpose of initiating a communication session between a local entity served by the originating one station and a remote entity having a name contained in the respective message.

8. The method according to anyone of the claims 2 to 7 characterized in that at least one of said bridging facilities coupled to said first medium or channel spans a medium linking to a further bridging facility, and wherein:

said third timeout value employed at said at least one bridging facility is determined by:

selecting a value sufficient to allow for request and response communications through said further facility and to stations linked to said further facility.

9. The method according to anyone of the claims 2 to 8 intended for facilitating name adoption communications, further characterized in that it comprises:

at any one of said stations selecting a tentative name for association with an entity attached to that stations, and then proceeding to verify the status of use of that name in said network by successively:

A. broadcasting a Name Check message over a first medium or channel to which said one station is directly linked; said message having a first form preventing bridging

- facilities linked to said first medium or channel from forwarding information in the message to other media or channels in said network;
- B. monitoring said first medium or channel for a first predetermined timeout interval for responses to said message;
- C. if a response is received, rejecting said tentative name;
- D. if no response to said message within said first interval is received, transmitting a second Name Check message corresponding to said first message over said first medium or channel; said second message having a second form causing said bridging facilities to process the information therein and to selectively forward said information in a third form to other media or channels; facilities forwarding information in said third form monitoring respective other media or channels for predetermined third timeout intervals unique to respective facilities and forwarding responses to said third form messages to the one medium or channel as responses to said second message;
- E. monitoring said first medium or channel for a predetermined second timeout interval at said one station for responses to said second Name Check messages; and
- E. conditional on responses to said first and second messages recognized it said one station, either adopting or rejecting said name.
10. The method according to anyone of the claims 2 to 8 intended for facilitating the establishment of communications between pairs of entities located at different stations, further characterized in that it comprises :
- A. at a station serving one entity of a pair, broadcasting a first Call Name Check message broadcast, over a first medium or channel to which that station is directly coupled; said first message having a form restricting handling of the information therein, to stations directly coupled to said first medium, said information including the name of a called entity;
- at any other station directly coupled to said first medium, transmitting a response to said first Call Name Check broadcast if said called name in said message corresponds to a name adopted for an entity at said other stations;
- B. monitoring said first medium, at the station serving said one entity, for responses to said message;
- C. if a response is detected, analyzing the response and conditionally initiating further communications with the responding station to establish a session with an entity at the responding station;
- D. if no response is detected, originating a second Call Name Check transmission from the station which sent the first Call Name Check; said second Call Name Check having a form restricting direct handling of its information to bridging facilities directly coupled to said first medium or channel;
- E. monitoring said medium or channel, for responses to said second Call Name Check;
- F. at each bridging facility receiving said second Call Name Check selectively generating a corresponding third Call Name Check message and transmitting that message to a further medium or channel which is linked by the respective facility to the first medium or channel;
- at any station coupled to a said further medium or channel transmitting a response to said third message if that message names an entity served by the respective station;
- G. monitoring said further media or channels at respective facilities for responses to said respective third messages;
- forwarding responses to said third messages to said one medium or channel as responses to said second message; and
- H. conditional on responses to said second Call Name Check received by the station originating that message, initiating other communications directed to a responding station to establish a session between the one entity served by the originating station and an entity served by the responding station.
11. A method for establishing a communication session in accordance with claim 10 characterized in that it comprises :
- at each said bridging facility receiving said second Call Name Check message, making a selective determination of whether or not to forward the information in that message on the basis of the information in the message and information stored at the respective facility; and
- conditionally forwarding the information in the message to respective said other media or channels on the basis of said determination.

12. The method of claim 11 characterized in that it comprises:

at each said bridging facility making a determination to forward the information in said received second Call Name Check message, adding control information to the forwarded message information for restricting the number of subsequent bridging facilities through which the forwarded information may be passed.

13. The method of claim 11 characterized in that it comprises:

conditioning each of said stations at power on time to engage in initial communications with bridging facilities coupled to media or channels to which the stations are directly coupled, for establishing timeout parameters under the direction of said facilities for determining the time periods to be allowed at respective stations for monitoring respective media or channels for responses to respective Call Name Check broadcasts thereafter originated by respective stations.

14. The method of claim 13 characterized in that said conditioning step includes:

selecting timeout values at respectively coupled bridging facilities sufficient to allow respectively forwarded third Call Name Checks to reach and be processed by all stations within predetermined forwarding ranges of the respective facilities, and also sufficient to allow for responses from the stations within said ranges to be passed back to the station originating the respective second Call Name Check; and

at each newly powered on station receiving more than one timeout value, selecting and thereafter using the largest such value.

15. The method of claim 14 characterized in that each bridging facility sustains a timeout for each respectively forwarded Check message, using said largest value, said timeout restricting said response monitoring operations.

Revendications

1. Dans un réseau de communication de données comportant plusieurs supports ou canaux de communication (figure 1, 12A, 12B, 12C, 12D), raccordés par des installations de pontage (figure 1, 15 à 18), chaque support ou canal

raccordant plusieurs stations de traitement de données (figure 1, 14A, 14B, 14C 14D), lesdites stations étant prévues pour partager l'accès aux entités associées au travers du réseau et pour lancer des communications avec des entités à distance au moyen de messages orientés vers des noms logiques attribués aux entités et non aux adresses représentant les emplacements physiques spécifiques des entités respectives, lesdits messages ne nécessitant aucun traitement intermédiaire à l'intérieur du réseau pour translater les noms respectifs en adresses, un procédé pour faciliter le traitement desdits messages, caractérisé en ce qu'il comprend:

A. à l'une quelconque desdites stations, l'émission d'un premier message et la transmission dudit message sur un premier support ou canal auquel ladite station est directement couplée; ledit premier message contenant un nom logique et présentant une première forme prédéterminée qui restreint son traitement en sorte que l'information qui s'y trouve n'est pas transférée au-delà desdites installations de pontage vers les supports ou canaux autres que ledit premier support ou canal;

B. la surveillance dudit premier support ou canal à ladite station pour des communications représentant les réponses audit premier message;

C. si une réponse est reçue choisir le traitement approprié à ladite station;

D. si aucune réponse audit premier message n'est reçue à ladite station, transmettre un second message orienté nom depuis ladite station sur ledit premier support ou canal; ledit second message correspondant audit premier message mais présentant une seconde forme prédéterminée différente de ladite première forme; ladite seconde forme ne permettant le traitement en conséquence des informations contenues dans ledit message qu'aux installations de pontage directement couplées audit premier support ou canal;

E. la surveillance dudit premier support ou canal à ladite station pour les réponses audit second message;

F. à chaque installation de pontage recevant ledit second message produire de manière conditionnelle un troisième message correspondant au second message et présentant une troisième forme prédéterminée;

la transmission desdits troisièmes messages depuis les installations respectives aux autres supports ou canaux qui sont raccordés par des installations respectives audit

- premier support ou canal ;
 G. la surveillance desdits autres supports ou canaux aux installations respectives pour les réponses aux troisièmes messages respectivement envoyés, et
 l'envoi des réponses auxdits troisièmes messages directement à ladite station, par l'intermédiaire dudit premier support ou canal, pour le traitement comme réponses audit second message.
2. Procédé selon la revendication 1, caractérisé en ce que ;
 ladite surveillance des réponses audit premier message de ladite station est établie pendant un premier délai d'attente prédéterminé ;
 les activités à ladite station par rapport auxdits premier et second messages, comprenant la surveillance pour des réponses, audit second message, sont établies pendant un second délai d'attente prédéterminé, et
 la surveillance des réponses auxdits troisièmes messages auxdites installations de ponts est établie pendant un troisième délai d'attente prédéterminé qui peut être différent aux différentes dites installations.
3. Procédé selon la revendication 2, caractérisé en ce que ledit second délai d'attente est établi à la mise en route initiale de ladite station et maintenu après par la station.
4. Procédé selon la revendication 3 caractérisé en ce que le second délai d'attente est établi par des communications initiales entre ladite station et les installations de pontage couplées audit premier support ou canal et déterminé par des informations fournies par lesdites installations dans lesdites communications.
5. Procédé selon la revendication 4, caractérisé en ce que :
 lesdites installations, au cours desdites communications initiales, fournissent des informations de facteur de retard représentant les retards les plus longs dans le traitement de demande et de réponse par rapport aux portions du réseau reliées par les installations respectives; et en ce que la valeur choisie pour établir ledit second délai d'attente est la plus grande des valeurs fournies par lesdites installations.
6. Procédé selon l'une quelconque des revendications 2 à 5, caractérisé en ce que :
 ledit premier message est un message d'un premier type ou d'un second type; les deux types étant utilisés à des fins différentes mais ayant l'effet commun d'indiquer à ladite station si un nom contenu dans le message est associé ou non à une entité à distance de ladite station.
7. Procédé selon la revendication 6, caractérisé en ce que :
 les messages dudit premier type sont des messages de Contrôle de Nom utilisés dans le but d'autoriser la station d'émission à déterminer si un nom que cette station cherche à choisir pour une entité servie localement est actuellement en utilisation dans une station à distance et
 les messages dudit second type sont des messages de Contrôle de Nom d'Appels envoyés dans le but d'initialiser une session de communication entre une entité locale servie par la station d'émission et une entité à distance ayant un nom contenu dans le message respectif.
8. Procédé selon l'une quelconque des revendications 2 à 7, caractérise en ce qu'au moins l'une desdites installations de pontage couplée audit premier support ou canal réunit une liaison de support à une autre installation de pontage et dans lequel ;
 ladite troisième valeur de délai d'attente employée à ladite au moins une installation de pontage est déterminée par : la sélection d'une valeur suffisante pour permettre les communications de demande et de réponse à travers ladite autre installation et aux stations raccordées à ladite autre installation.
9. Procédé selon l'une quelconque des revendications 2 à 8 destiné à faciliter les communications d'adoption de nom, caractérisé en outre en ce qu'il comprend :
 à l'une quelconque desdites stations, sélectionner un nom éventuel pour association avec une entité attachée à ces stations, et ensuite vérifier l'état, l'utilisation de ce nom dans ledit réseau en effectuant successivement les opérations suivantes :
 A. diffuser un message de Contrôle de Nom sur un premier support ou canal auquel ladite station est directement raccordée ;
 ledit message présentant une première forme empêchant les installations de pontage raccordées audit premier support ou canal d'envoyer l'information contenue dans le message aux autres supports ou canaux dans ledit réseau ;
 B. surveiller ledit premier support ou canal pendant un premier délai d'attente prédéterminé pour des réponses audit message ;

C. si une réponse est reçue, rejeter ledit nom éventuel;

D. si aucune réponse audit message à l'intérieur dudit premier délai d'attente n'est reçue, transmettre un second message de Contrôle de Nom correspondant audit premier message sur ledit premier support ou canal; ledit second message présentant une seconde forme amenant lesdites installations de pontage à traiter les informations qui s'y trouvent et à envoyer sélectivement lesdites informations sous une troisième forme à d'autres supports ou canaux; les installations envoyant des informations sous ladite troisième forme surveillant des autres supports ou canaux respectifs pendant des troisièmes délais d'attente prédéterminés particuliers à des installations respectives et envoyant des réponses auxdits messages de troisième forme au support ou canal comme réponses audit second message ;

E. surveiller ledit premier support ou canal pendant un second délai d'attente prédéterminé à ladite station pour des réponses auxdits seconds messages de Contrôle de Nom, et

F. en fonction des réponses auxdits premier et second messages reconnus à ladite station, adopter ou rejeter ledit nom.

10. Procédé selon l'une quel conque des revendications 2 à 8 a destiné à faciliter l'établissement de communications entre des paires d'entités situées à des stations différentes, caractérisé en outre en ce qu'il comprend :

A. à une station servant une entité d'une paire, la diffusion d'un premier message de Contrôle de Nom d'Appel sur un premier support ou canal auquel cette station est directement couplée; ledit premier message présentant une forme limitant le traitement des informations qui s'y trouvent aux stations directement couplées audit premier support, lesdites informations comprenant le nom d'une entité appelée ;

à toute autre station directement couplée audit premier support, la transmission d'une réponse à ladite première diffusion de Contrôle de Nom d'Appel si ledit nom appelé dans ledit message correspond à un nom adopté pour une entité auxdites autres stations ;

B. la surveillance dudit premier support à la station servant ladite première entité, pour des réponses audit message ;

C. si une réponse est détectée, analyser la réponse et initialiser de manière conditionnelle d'autres communications avec la sta-

tion répondante pour établir une session avec une entité à la station répondante ;

D. si aucune réponse n'est détectée, émettre une seconde transmission de Contrôle de Nom d'Appel depuis la station qui a envoyé le premier Contrôle de Nom d'Appel; ledit second Contrôle de Nom d'Appel présentant une forme limitant le traitement direct de ses informations aux installations de pontage directement couplées audit premier support ou canal;

E. la surveillance dudit premier support ou canal pour des réponses audit second Contrôle de Nom d'Appel ;

F. à chaque installation de pontage recevant ledit second Contrôle de Nom d'Appel, produire sélectivement un troisième message de Contrôle de Nom d'Appel correspondant et transmettre ce message à un autre support ou canal qui est raccordé par l'installation respective au premier support ou canal;

à toute station couplée audit autre support ou canal transmettre une réponse audit troisième message si ce message nomme une entité servie par la station respective ;

G. la surveillance desdits autres supports ou canaux des installations respectives pour des réponses auxdits troisièmes messages respectifs ;

l'envoi des réponses auxdits troisièmes messages vers ledit support ou canal comme réponses audit second message, et

H. en fonction des réponses audit second Contrôle de Nom d'Appel reçues par la station émettant ce message, initialiser d'autres communications dirigées vers une station répondante pour établir une session entre l'entité servie par la station d'émission et une entité servie par la station répondante.

11. Procédé pour établir une session de communication selon la revendication 10 caractérisé en ce qu'il comprend :

à chaque installation de pontage recevant ledit second message de Contrôle de Nom d'Appel, déterminer sélectivement l'envoi ou non des informations de ce message sur la base des informations du message et des informations stockées à l'installation respective, et envoyer de manière conditionnelle les informations du message auxdites autres supports ou canaux respectifs sur la base de ladite détermination.

12. Procédé selon la revendication 11, caractérisé en ce qu'il comprend :

à chaque dite installation de pontage déterminant l'envoi des informations dudit second message de Contrôle de Nom d'Appel reçu, ajouter des informations de commande aux informations de message envoyées pour restreindre le nombre des installations de pontage suivantes au travers desquelles les informations envoyées pourront passer.

13. Procédé selon la revendication 11, caractérisé en ce qu'il comprend :

la mise sous tension de chacune desdites stations au moment prévu pour lancer des communications initiales avec des installations de pontage couplées aux supports ou aux canaux auxquels les stations sont directement couplées, pour l'établissement de paramètres de délai d'attente sous la direction desdites installations pour la détermination des temps à allouer aux stations respectives pour surveiller des supports ou canaux respectifs pour des réponses aux diffusions de Contrôle de Nom d'Appel émis ensuite par des stations respectives.

14. Procédé selon la revendication 13, caractérisé en ce que ladite étape de mise sous tension comprend :

la sélection de valeurs de délai d'attente aux installations de pontage respectivement couplées, suffisantes pour permettre aux troisièmes Contrôles de Nom d'Appel respectivement envoyés d'atteindre et d'être traités par la totalité des stations à l'intérieur de plages d'envoi prédéterminées des installations respectives et également suffisantes pour permettre aux réponses des stations à l'intérieur desdites plages d'être renvoyées à la station émettant le second Contrôle de Nom d'Appel respectif ; et à chaque station nouvellement mise sous tension recevant plus d'une valeur de délai d'attente, la sélection et ensuite l'utilisation de la valeur la plus grande.

15. Procédé selon la revendication 14, caractérisé en ce que chaque installation de pontage maintient un délai d'attente pour chaque message de Contrôle respectivement envoyé utilisant ladite valeur la plus grande, ledit délai d'attente limitant lesdites opérations de surveillance de réponse.

Ansprüche

1. Bei einem Datenkommunikationsnetzwerk mit mehrfachen Kommunikationsmedien oder Kanälen (Fig. 1, 12A, 12B, 12G, 12D), die durch

Brückenbildungseinrichtungen (Fig. 1, 15 bis 18) verbunden sind, wobei jedes Medium oder jeder Kanal mehrfache Datenverarbeitungsstationen (Fig. 1, 14A, 14B, 14G, 14dD) verbindet, die Stationen beim Arbeiten angepaßt sind, einen Zugriff auf zugeordnete Einheiten über das Netzwerk gemeinsam zu benutzen und Kommunikationen mit entfernten Einheiten mittels Nachrichten einzuleiten, die an logische Namen gerichtet sind, welche den Einheiten und nicht Adressen zugeordnet sind, die spezifische physische Stellen jeweiliger Einheiten repräsentieren, wobei die Nachrichten kein Zwischenbearbeiten innerhalb des Netzwerkes zum Übersetzen jeweiliger Namen in Adressen erfordern, ein Verfahren zum Erleichtern einer Bearbeitung der Nachrichten, dadurch gekennzeichnet, daß es umfaßt:

- A. Erzeugen einer ersten Nachricht und Übertragen der Nachricht über ein erstes Medium oder einen ersten Kanal, an welchem die Station unmittelbar gekoppelt ist, bei irgendeiner beliebigen der Stationen, wobei die erste Nachricht einen logischen Namen enthält und eine vorbestimmte erste Form aufweist, die ihre Bearbeitung so beschränkt, daß die Information darin über die Brückenbildungseinrichtungen an andere Medien oder Kanäle als das erste Medium oder der erste Kanal, nicht übertragen wird,
- B. Überwachen des ersten Mediums oder Kanals bei der einen Station für Kommunikationen, die Antworten auf die erste Nachricht repräsentieren,
- C. Übernehmen einer geeigneten Verarbeitung bei der einen Station, wenn eine Antwort empfangen wird,
- D. Übertragen einer zweiten namengerichteten Nachricht von der einen Station über das erste Medium oder den ersten Kanal, wenn keine Antwort auf die erste Nachricht bei der einen Station empfangen wird, wobei die zweite Nachricht der erste Nachricht entspricht, jedoch eine vorbestimmte zweite, von der ersten Form verschiedene Form aufweist, die zweite Form arbeitet, um eine ansprechende Bearbeitung der Information, die in der Nachricht enthalten ist, nur bei Brückenbildungseinrichtungen zu ermöglichen, die an dem ersten Medium oder Kanal unmittelbar gekoppelt sind,
- E. Überwachen des ersten Mediums oder Kanals bei der einen Station für Antworten auf die zweite Nachricht,
- F. Empfangen der zweiten Nachricht bei jeder Brückenbildungseinrichtung, bedingtes Erzeugen einer dritten Nachricht, welche der zweiten Nachricht entspricht und eine

dritte vorbestimmte Form aufweist,

Übertragen der dritten Nachrichten von jeweiligen Einrichtungen an andere Medien oder Kanäle, die durch jeweilige Einrichtungen mit dem ersten Medium oder Kanal verbunden sind,

G. Überwachen der anderen Medien oder Kanäle bei jeweiligen Einrichtungen für Antworten auf jeweilig gesendete dritte Nachrichten und

Senden von Antworten auf die dritte Nachrichten unmittelbar an die eine Station über das erste Medium oder den ersten Kanal zum Bearbeiten als Antworten auf die zweite Nachricht.

2. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß:

das Überwachen für Antworten auf die erste Nachricht der einen Station für ein vorbestimmtes erstes Zeitsperre-Intervall zeitlich abgestimmt ist,

die Aktivitäten bei der einen Station bezüglich der ersten und zweiten Nachrichten einschließlich des Überwachens für Antworten auf die zweite Nachricht durch ein zweites vorbestimmtes Zeitsperre-Intervall zeitlich abgestimmt sind und

das Überwachen für Antworten auf die dritte Nachrichten bei den Brückenbildungseinrichtungen für ein vorbestimmtes drittes Zeitsperre-Intervall zeitlich abgestimmt ist, das bei verschiedenen Einrichtungen verschieden sein kann.

3. Verfahren nach Anspruch 2, dadurch gekennzeichnet, daß das zweite Zeitsperre Intervall bei der anfänglichen Einschaltung der einen Station festgelegt wird und demnach durch die Station aufrechterhalten wird.

4. Verfahren nach Anspruch 3, dadurch gekennzeichnet, daß das zweite Zeitsperre-Intervall über anfängliche Kommunikationen zwischen der einen Station und Brückenbildungseinrichtungen festgelegt wird, die an das erste Medium oder Kanal gekoppelt sind und durch eine Information bestimmt wird, die durch die Einrichtungen in den Kommunikationen geliefert werden.

5. Verfahren nach Anspruch 4, dadurch gekennzeichnet, daß:

die Einrichtungen in den anfänglichen Kommunikationen wirken, um eine Verzögerungsfaktorinformation zu liefern, welche längste Verzögerungen in einer Forderungs- und Antwortbearbeitung bezüglich der Teile des Netzwerkes repräsentieren, das durch jeweilige Einrichtungen aufgespannt wird und

der zum zeitlichen Abstimmen des zweiten Zeitsperre-Intervalles gewählte Wert der größte der durch die Einrichtungen gelieferten Werte ist.

6. Verfahren nach irgendeinem der Ansprüche 2 bis 5, dadurch gekennzeichnet, daß:

die erste Nachricht eine Nachricht entweder einer ersten oder zweiten Art ist, wobei beide Arten für verschiedene Zwecke verwendet werden, jedoch einen gemeinsamen Effekt aufweisen, eine Anzeige an die eine Station zu liefern, ob ein in der Nachricht enthaltener Name einer von der einen Station entfernten Einheit zugeordnet ist oder nicht.

7. Verfahren nach Anspruch 6, dadurch gekennzeichnet, daß:

Nachrichten der ersten Art Namensprüfung-Nachrichten sind, die für den Zweck verwendet werden, es der erzeugenden einen Station zu ermöglichen, zu bestimmen, wenn ein Name sich gegenwärtig bei einer entfernten Station in Verwendung befindet, den jene Station für eine lokal bediente Einheit zu übernehmen sucht, und

Nachrichten der zweiten Art Rufe-Namensprüfung-Nachrichten sind, die für den Zweck gesendet werden, eine Kommunikationssitzung zwischen einer lokalen Einheit, die durch die erzeugende eine Station bedient wird, und einer entfernten Einheit mit einem in der jeweiligen Nachricht enthaltenen Namen einzuleiten.

8. Verfahren nach irgendeinem der Ansprüche 2 bis 7, dadurch gekennzeichnet, daß zumindest eine der Brückenbildungseinrichtungen, die an das erste Medium oder den Kanal gekoppelt sind, eine Mediumverbindung zu einer weiteren Brückenbildungseinrichtung spannt und bei welchem:

der dritte Zeitsperre-Wert, der bei der zumindest einer Brückenbildungseinrichtung verwendet wird bestimmt ist durch:

Auswählen eines ausreichenden Wertes, um Forderungs- und Antwortkommunikationen durch die weitere Einrichtung und zu Stationen zu ermöglichen, die mit der weiteren Einrichtung verbunden sind.

9. Verfahren nach irgendeinem der Ansprüche 2 bis 8, das zum Erleichtern von Namenübernahme-Kommunikationen vorgesehen ist, ferner dadurch gekennzeichnet, daß es umfaßt:

Auswählen eines Versuch-Namens zum Zuordnen einer Einheit, die mit jenen Stationen verbunden ist und ausschließendes Fortfahren, um den Verwendungsstatus jenes Namens bei irgendeiner der Stationen in dem Netzwerk zu prüfen durch aufeinanderfolgendes:

A. Rundrufen einer Namensprüfung-Nachricht über ein erstes Medium oder einen ersten Kanal, mit welchem die eine Station unmittelbar verbunden ist, wobei die Nachricht eine erste Form aufweist, die Brückenbildungseinrichtungen, die mit dem ersten Medium oder Kanal verbunden sind, verhindert, eine Information in der Nachricht an andere Medien oder Kanäle in dem Netzwerk zu senden.

B. Überwachen des ersten Mediums oder Kanals für ein erstes vorbestimmtes Zeitsperre-Intervall für Antworten auf die Nachricht,

C. Verwerfen des Versuch-Namens, wenn eine Antwort empfangen wird,

D. Übertragen einer zweiten Namensprüfung-Nachricht, welche der ersten Nachricht entspricht, über das erste Medium oder den ersten Kanal, wenn keine Antwort auf die Nachricht innerhalb des ersten Intervalles empfangen wird, wobei die zweite Nachricht eine zweite Form aufweist, welche bewirkt, daß die Brückenbildungseinrichtungen die Information darin verarbeiten und die Information in einer dritten Form an andere Medien oder Kanäle selektiv senden,

wobei Einrichtungen, die eine Information in der dritten Form senden, jeweilige andere Medien oder Kanäle für vorbestimmte dritte Zeitsperre-Intervalle überwachen, die jeweilige Einrichtungen betreffen und Antworten auf Nachrichten der dritten Form an das eine Medium oder einen Kanal als Antworten auf die zweite Nachricht senden,

E. Überwachen des ersten Mediums oder Kanals für ein vorbestimmtes zweites

Zeitsperre-Intervall bei der einen Station für Antworten auf die zweite Namensprüfung-Nachrichten und

F. entweder Übernehmen oder Verwerfen des Namens bedingt durch Antworten auf die ersten und zweiten, bei der einen Station erkannten Nachrichten.

10. Verfahren nach irgendeinem der Ansprüche 2 bis 8, das zum Erleichtern der Herstellung von Kommunikationen zwischen Paaren von bei verschiedenen Stationen liegenden Einheiten vorgesehen ist, ferner dadurch gekennzeichnet, daß es umfaßt:

A. Rundsprechen eines ersten Rufe-Namensprüfung-Nachricht-Rundspruches über ein erstes Medium oder ersten Kanal, an den jene Station unmittelbar gekoppelt ist bei einer Station, die eine Einheit eines Paares bedient, wobei die erste Nachricht eine Form aufweist, die ein Bearbeiten der Information darin auf Stationen einschränkt, die an das erste Medium unmittelbar gekoppelt sind, die Information den Namen einer aufgerufenen Einheit enthält,

Übertragen einer Antwort auf den ersten Rufe-Namensprüfung-Rundspruch bei irgendeiner anderen, unmittelbar an das erste Medium gekoppelten Station, wenn der aufgerufene Name in der Nachricht einem Namen entspricht, der für eine Einheit bei den anderen Stationen übernommen wird,

B. Überwachen des ersten Mediums bei der die eine Einheit bedienende Station für Antworten auf die Nachricht,

C. Analysieren der Antwort und bedingtes Einleiten weiterer Kommunikationen mit der antwortenden Station, wenn eine Antwort erfaßt wird, um eine Sitzung mit einer Einheit bei der antwortenden Station herzustellen,

D. Erzeugen einer zweiten Rufe-Namensprüfung-Übertragung von der Station, welche die erste Rufe-Namensprüfung gesendet hat, wenn keine Antwort erfaßt wird, wobei die zweite Rufe-Namensprüfung eine Form aufweist, die eine unmittelbare Bearbeitung ihrer Information auf Brückenbildungseinrichtungen einschränkt, die unmittelbar an das erste Medium oder Kanal gekoppelt sind,

E. Überwachen des Mediums oder Kanals für Antworten auf die zweite Rufe-Namensprüfung,

F. Erzeugen einer entsprechenden dritten Rufe-Namensprüfung-Nachricht und Übertragen jener Nachricht an ein weiteres Medium oder einen Kanal, das oder der durch

die jeweilige Einrichtung mit dem ersten Medium oder Kanal verbunden ist, bei jeder Brückenbildungseinrichtung, welche die zweite Rufe-Namensprüfung selektiv empfängt,

Übertragen einer Antwort auf die dritte Nachricht, wenn jene Nachricht eine Einheit nennt, die durch die jeweilige Station bedient wird bei irgendeiner Station, die an ein weiteres Medium oder Kanal gekoppelt ist, G. Überwachen der weiteren Medien oder Kanäle bei jeweiligen Einrichtungen für Antworten auf die jeweilige dritte Nachricht,

Senden von Antworten auf die dritten Nachrichten an das eine Medium oder den einen Kanal als Antworten auf die zweite Nachricht und

H. Einleiten anderer Kommunikationen, die an eine antwortende Station gerichtet werden, um eine Sitzung zwischen der einen durch die erzeugende Station bedienten Einheit und einer durch die antwortende Station bedienten Einheit herzustellen, bedingt durch Antworten auf die zweite Rufe-Namensprüfung, die durch die Station empfangen wird, die jene Nachricht erzeugt.

11. Verfahren zum Herstellen einer Kommunikationssitzung entsprechend Anspruch 10, dadurch gekennzeichnet, daß es umfaßt:

Durchführen einer selektiven Bestimmung, ob die Information in jener Nachricht auf der Grundlage der Information in der Nachricht und der Information, die bei der jeweiligen Einrichtung gespeichert wird, gesendet wird oder nicht bei jeder Brückenbildungseinrichtung, welche die zweite Rufe-Namensprüfung-Nachricht empfängt und bedingtes Senden der Information in der Nachricht an jeweilige andere Medien oder Kanäle auf der Grundlage dieser Bestimmung.

12. Verfahren nach Anspruch 11, dadurch gekennzeichnet, daß es umfaßt:

Hinzufügen einer Steuerinformation zu der gesendeten Nachrichtinformation zum Beschränken der Anzahl aufeinander-folgender Brückenbildungseinrichtungen, durch welche die gesendete Information übertragen werden kann bei jeder Brückenbildungseinrichtung, die eine Bestimmung durchführt, die Information in der empfangenen zweiten Rufe-Namensprüfung-Nachricht zu senden.

13. Verfahren nach Anspruch 11, dadurch gekennzeichnet, daß es umfaßt:

rechtzeitiges Bereitstellen einer Versorgung für jede der Stationen, um in anfänglicher Kommunikation mit Brückenbildungseinrichtungen einzugreifen, die an Medien oder Kanäle gekoppelt sind, an welche die Station unmittelbar gekoppelt sind, um Zeitsperre-Parameter unter der Leitung der Einrichtungen zum Bestimmen der Zeitperioden festzulegen, die bei jeweiligen Stationen zum Überwachen jeweiliger Medien oder Kanäle für Antworten auf jeweilige Rufe-Namensprüfung-Rundrufe, die demnach durch jeweilige Stationen erzeugt werden, ermöglicht werden sollen.

14. Verfahren nach Anspruch 13, dadurch gekennzeichnet, daß der Bereitstellungsschritt umfaßt:

Auswählen von Zeitsperre-Werten bei jeweils gekoppelten Brückenbildungseinrichtungen, die hinreichen, daß jeweils gesendete dritte Rufe-Namensprüfungen erreicht werden können und durch alle Stationen innerhalb vorbestimmter Sendebereiche der jeweiligen Einrichtungen verarbeitet werden können und die auch hinreichen, daß Antworten aus den Stationen innerhalb der Bereiche an die Station zurückgesendet werden, welche die jeweilige zweite Rufe-Namensprüfung erzeugt und

Empfangen von mehr als einem Zeitsperre-Wert, Auswählen und anschließendes Verwenden des größten solchen Wertes bei jeder neu eingeschalteten Station.

15. Verfahren nach Anspruch 14, dadurch gekennzeichnet, daß jede Brückenbildungseinrichtung eine Zeitsperre für jede jeweils gesendete Prüfungs-Nachricht aufrechterhält, indem sie den größten Wert verwendet, wobei die Zeitsperre die Antwortüberwachungsvorgänge beschränkt




FIG. 1




FIG. 2




FIG. 3
(NAME CHECK, CALL NAME CHECK)





FIG. 4
(BRIDGE DATAGRAM)



FROM 146 OR 147, FIG. 5
(START TIMEOUTS; SEND NAME CHECK OR CALL NAME CHECK)




FIG. 6




FIG. 7

BRIDGE TABLE

	NODES (SIDE 1)		NODES (SIDE 2)	
		Ai		Aj
* TYPE		B		NB
# DELAY FACTOR		X		D2
TIMER VALUE		T1		T2
HOP COUNT		--		H2
SEQ. NO.		--		--
FRAME ID		--		--
u STATE (I/U)		--		

* ENTRIES B/NB IN THIS ROW REPRESENT BRIDGING/NON-BRIDGING

ENTRIES X REPRESENT "DON'T CARE"

u ENTRIES I/U REPRESENT INITIATED/UNINITIATED NODE STATES

@ THE TABLE MAY HAVE MORE THAN ONE ENTRY PER NODE; FOR HANDLING PLURAL CO-ACTIVE NAME CHECKING TYPE REQUESTS

FIG. 8

TIMED: 15/07/91 15:01:13

PAGE: 1

REGISTER ENTRY FOR EP0169454

European Application No EP85108691.8 filing date 12.07.1985

Priority claimed:

20.07.1984 in United States of America - doc: 631567

Designated States BE CH DE FR GB IT LI NL SE

Title NAME USAGE SUPPORT THROUGH DISTRIBUTED PROCESSING NETWORKS LINKED BY
BRIDGES AND/OR GATEWAYS

Applicant/Proprietor

INTERNATIONAL BUSINESS MACHINES CORPORATION, Old Orchard Road, Armonk,
N.Y. 10504, United States of America [ADP No. 522880570011]

Inventors

WILLIAM ALLEN DOSTER, 8213 Overlake Drive, West, Bellevue, WA. 98004,
United States of America [ADP No. 538344120011]

ROBERT SACHSENMAIER, 7320 NE 8th Court, Boca Raton, Fl. 33431, United
States of America [ADP No. 538344200011]

Classified to

H4P

G06F

Address for Service

IBM UK LTD, Hursley Park, Winchester, Hampshire, SO21 2JN, United Kingdom
[ADP No. 000009190011]

EPO Representative

ALAIN DE PENA, Compagnie IBM France Département de Propriété
Intellectuelle, F-06610 La Gaude, France [ADP No. 501645810011]

Publication No EP0169454 dated 29.01.1986

Publication in English

Examination requested 12.07.1985

Patent Granted with effect from 02.05.1991 (Section 25(1)) with title NAME
USAGE SUPPORT THROUGH DISTRIBUTED PROCESSING NETWORKS LINKED BY BRIDGES
AND/OR GATEWAYS.

22.01.1988 EPO: Search report published on 27.01.1988

Entry Type 25.11 Staff ID.

Auth ID. EPT

05.02.1990 Notification from EPO of change of EPO Representative details from
ALAIN DE PENA, Compagnie IBM France Département de Propriété
Intellectuelle, F-06610 La Gaude, France [ADP No. 501645810011]
to

GÉRARD BONNEAU, Compagnie IBM France Département de Propriété
Intellectuelle, F-06610 La Gaude, France [ADP No. 507747770011]

Entry Type 25.14 Staff ID. RD06 Auth ID. EPT

TIMED: 15/07/91 15:01:13

REGISTER ENTRY FOR EP0169454 (Cont.)

PAGE: 2

16.04.1991 IBM UK LTD, Hursley Park, Winchester, Hampshire, SO21 2JN, United
Kingdom

[ADP No. 00000919001]

registered as address for service

Entry Type 8.11 Staff ID. CA1 Auth ID. AA

**** END OF REGISTER ENTRY ****

DA80-01
FG

OPTICS - PATENTS

15/07/91

15:01:52

PAGE: 1

RENEWAL DETAILS

PUBLICATION NUMBER

EP0169454 /

PROPRIETOR(S)

International Business Machines Corporation, Old Orchard Road,
Armonk, N.Y. 10504, United States of America /

DATE GRANTED

02.05.1991 /

DATE NEXT RENEWAL DUE

12.07.1992

DATE NOT IN FORCE

DATE OF LAST RENEWAL

21.06.1991

YEAR OF LAST RENEWAL

07

STATUS

PATENT IN FORCE /