



(51) International Patent Classification:

A61B 17/29 (2006.01) A61B 90/00 (2016.01)

(21) International Application Number:

PCT/US2019/060743

(22) International Filing Date:

11 November 2019 (11.11.2019)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/768,018 15 November 2018 (15.11.2018) US

(71) Applicant: **APPLIED MEDICAL RESOURCES CORPORATION** [US/US]; 22872 Avenida Empresa, Rancho Santa Margarita, CA 92688 (US).

(72) Inventors: **REINDEL, Eric S.**; 22872 Avenida Empresa, Rancho Santa Margarita, CA 92688 (US). **HOVAIDA,**

Javid E.; 22872 Avenida Empresa, Rancho Santa Margarita, CA 92688 (US). **FAST, Kyle R.**; 22872 Avenida Empresa, Rancho Santa Margarita, CA 92688 (US). **STROKOSZ, Arkadiusz A.**; 22872 Avenida Empresa, Rancho Santa Margarita, CA 92688 (US).

(74) Agent: **NGUYEN, Thomas**; Applied Medical Resources Corporation, 22872 Avenida Empresa, Rancho Santa Margarita, CA 92688 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA,

(54) Title: LAPAROSCOPIC GRASPER WITH FORCE-LIMITING GRASPING MECHANISM




FIG. 1

(57) Abstract: A surgical instrument is provided having an actuator (310) mechanism with an integrated extension element (316). The surgical instrument comprises a handle assembly (400), an elongate shaft (300), and an end effector (200). The end effector (200) can comprise a jaw assembly (200) having atraumatic pads (220, 240) positioned thereon to reduce force on grasped tissue. An actuator (310) is movable within the elongate shaft to actuate jaws (210, 230) of the jaw assembly (200) responsive to movement of a movable handle (420) of the handle assembly (400). The actuator (310) can have an integrated extension element (316) that allows the actuator (300) to translate within the elongate shaft upon application of a relatively low force and translate and extend upon application of a relatively higher force to the actuator (310) to limit the force applied by the jaw assembly (200). The actuator (310) is also able to utilize force stored with the integrated extension element (316) to provide a dynamic amount of force used to grasp the tissue in scenarios



SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- *with international search report (Art. 21(3))*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

LAPAROSCOPIC GRASPER WITH FORCE-LIMITING GRASPING MECHANISM

Cross-Reference to Related Applications

[0001] This application claims priority to and benefit of U.S. Provisional Patent Application Serial No. 62/768,018 entitled "Laparoscopic Grasper with Force-Limiting Grasping Mechanism" filed on November 15, 2018 which is incorporated herein by reference in its entirety.

Background

[0002] The present application relates to surgical devices and more particularly to instruments for use in minimally-invasive surgery such as laparoscopic grasping instruments.

[0003] In general and minimally invasive surgical procedures, surgeons frequently use grasping instruments to grasp and manipulate tissue, vasculature, or other objects within the surgical field. While it is desirable to maintain traction on the grasped tissue, it is undesirable to apply excess force to the tissue. The excess force on the tissue could lead to tissue trauma.

[0004] Conventional surgical grasping instruments have included grasping jaws comprised of a metallic material to grasp and manipulate tissue. Certain conventional surgical grasping instruments have also included force limiting mechanisms including relatively complex compression coil spring assemblies that require relatively large shaft diameters to accommodate. Other conventional grasping instruments have included no dedicated force limiting mechanism. Instead, these convention grasping instruments rely on flexibility and compliance of actuating handles to reduce the impact of forceful grasping.

[0005] Accordingly, it is desirable to provide a surgical grasping instrument that can reduce the potential for trauma to grasped tissue. It is likewise desirable to provide a surgical grasping instrument that has a simplified mechanism that facilitates relatively low-cost manufacture and assembly. Furthermore, it is desirable to provide a surgical

grasping instrument including atraumatic, force limiting features in a device configured for use with a small surgical access port diameter such as a port configured for use with 5mm instruments.

Summary of the Invention

[0006] In certain embodiments, a surgical grasping instrument is provided herein. The surgical grasping instrument comprises: a handle assembly, an elongate shaft, and a jaw assembly. The handle assembly comprises: a stationary handle, and a movable handle pivotably coupled to the stationary handle. The elongate shaft extends distally from the handle assembly. The elongate shaft has a proximal end coupled to the handle assembly, a distal end opposite the proximal end, and a central longitudinal axis defined by the proximal end and the distal end. The elongate shaft comprises: an outer tube, and an actuator positioned longitudinally within the outer tube. The actuator has a sliding fit within the outer tube and is responsive to pivotal movement of the movable handle. The jaw assembly is disposed at the distal end of the elongate shaft. The jaw assembly comprises a first jaw and a second jaw. The first and second jaws are pivotable between an open configuration of the jaw assembly and a closed configuration of the jaw assembly responsive to pivotal movement of the movable handle. The actuator has a first length along the central longitudinal axis. The actuator comprises an extension element configured to lengthen the actuator to a second length greater than the first length in response to a predetermined force applied to the actuator.

[0007] In certain embodiments, a surgical instrument is provided herein. The surgical instrument comprises: a handle assembly; an elongate shaft, and an end effector. The handle assembly comprises: a stationary handle; a movable handle pivotably coupled to the stationary handle; and a locking mechanism. The lock mechanism comprises: a locking member and a lock release. The locking member has a lock portion extending within the handle assembly and a trigger portion extending adjacent an outer surface of the stationary handle. The locking member is movable between a locked position and an unlocked position. The lock release is coupled to the stationary handle. The lock

release is configured to maintain the locking member in the locked position. The lock release is actuatable to release the locking member to the unlocked position. The elongate shaft extends distally from the handle assembly. The elongate shaft has a proximal end coupled to the handle assembly, a distal end opposite the proximal end, and a central longitudinal axis defined by the proximal end and the distal end. The elongate shaft comprises an outer tube and an actuator positioned longitudinally within the outer tube. The actuator has a sliding fit with the outer tube and the actuator is responsive to pivotal movement of the movable handle. The actuator has a proximal section extending within the handle assembly to a proximal end. The actuator comprises a locking surface adjacent the proximal end. The lock portion of the locking member is engaged with the locking surface of the actuator with the locking mechanism in the locked position. The end effector is disposed at the distal end of the elongate shaft. The end effector is movable between a first configuration and a second configuration responsive to pivotal movement of the movable handle.

[0008] In certain embodiments, a surgical instrument is provided herein. The surgical instrument comprises: a handle assembly; an elongate shaft; and an end effector. The handle assembly comprises: a stationary handle and a movable handle pivotably coupled to the stationary handle. The elongate shaft extends distally from the handle assembly. The elongate shaft has a proximal end coupled to the handle assembly, a distal end opposite the proximal end, and a longitudinal axis defined by the proximal end and the distal end. The elongate shaft comprises: an outer tube, and an actuator positioned longitudinally within the outer tube. The actuator has a sliding fit within the outer tube and is responsive to pivotal movement of the movable handle. The actuator has a length extending along the central longitudinal axis, a height, and a width. The width is substantially smaller than the height such that the actuator has a planar profile. The actuator comprises: a first segment having a first height; and a second segment having a second height smaller than the first height. The second segment defines an extension element longitudinally extendable responsive to force applied to the actuator. The second segment comprises: a plurality of longitudinal sections; a plurality of

transverse sections; and a plurality of bends. The plurality of longitudinal sections extends generally parallel to the longitudinal axis. The plurality of transverse sections extends transverse to the longitudinal axis. The plurality of bends are disposed between each longitudinal section of the plurality of longitudinal sections and an adjacent transverse section of the plurality of transverse sections. The end effector is disposed at the distal end of the elongate shaft. The end effector is movable between a first configuration and a second configuration responsive to pivotal movement of the movable handle.

Brief Description of the Drawings

[0009] In order to describe the manner which, the above-recited and other advantages and features of the disclosure can be obtained, a more particular description of the principles briefly described above will be rendered by reference to specific embodiments that are illustrated in the appended drawings. Understanding that these drawings depict only embodiments of the disclosure and are not therefore to be considered to be limiting of its scope, the principles herein are described and explained with additional specificity and detail through the use of the accompanying drawings in which the reference numerals designate like parts throughout the figures thereof.

[00010] Figure 1 is a perspective view of an embodiment of a surgical grasping instrument;

[00011] Figure 2 is an exploded view of the grasping instrument of Figure 1;

[00012] Figure 2A is an exploded view of the handle assembly of the grasping instrument of Figure 1;

[00013] Figure 2B is an exploded view of the jaw assembly of the grasping instrument of Figure 1;

[00014] Figure 2C is an exploded view of the jaw assembly coupled to a distal end of an actuator having a tracked head member of the grasping instrument of Figure 1;

[00015] Figure 2D is an exploded view of the jaw assembly, tracked head member, and actuator of Figure 2C;

[00016] Figure 3 is a side view of a jaw assembly of the grasping instrument of Figure 1 with the jaw assembly in an open configuration;

[00017] Figure 3A is a side view of a jaw assembly of the grasping instrument of Figure 1 with the jaw assembly in an open configuration and with an outer tube and sleeve removed;

[00018] Figure 4 is a side view of a jaw assembly of the grasping instrument of Figure 1 with the jaw assembly in a partially closed configuration;

[00019] Figure 4A is a side view of a jaw assembly of the grasping instrument of Figure 1 with the jaw assembly in a partially closed configuration and with an outer tube and sleeve removed;

[00020] Figure 5 is a side view of a jaw assembly of the grasping instrument of Figure 1 with the jaw assembly in a closed configuration;

[00021] Figure 5A is a side view of a jaw assembly of the grasping instrument of Figure 1 with the jaw assembly in a closed configuration and with an outer tube and sleeve removed;

[00022] Figure 6 is a partial cut away side view of a handle assembly of the grasping instrument of Figure 1 positioned with the jaw assembly in an open configuration;

[00023] Figure 7 is a partial cut away side view of a handle assembly of the grasping instrument of Figure 1 positioned with the jaw assembly in a partially closed configuration;

[00024] Figure 8 is a partial cut away side view of a handle assembly of the grasping instrument of Figure 1 positioned with the jaw assembly in a closed configuration with a latch mechanism engaged in a latched configuration;

[00025] Figure 9 is a partial cut away side view of a handle assembly of the grasping instrument of Figure 1 positioned with the jaw assembly in a closed configuration with a latch mechanism engaged in an unlatched configuration;

[00026] Figure 10 is a side view of an actuator of shaft assembly of the grasping instrument of Figure 1 in an undisturbed state and an extended state;

[00027] Figure 11A is a side view of a portion of the actuator of Figure 10 in the undisturbed state;

[00028] Figure 11B is a side view of a portion of the actuator of Figure 10 in the extended state;

[00029] Figure 12 is a side view of various embodiments of actuator having an extension element;

[00030] Figure 13 is a partial cut away side view of a shaft assembly of an embodiment of surgical instrument with an embodiment of actuator with an extension element;

[00031] Figure 14 is a partial cut away side view of a section of the shaft assembly of Figure 13; and

[00032] Figure 15 is a partial cut away side view of a shaft assembly of an embodiment of surgical instrument with an embodiment of actuator with an extension element.

Detailed Description of the Invention

[00033] With reference to Figure 1, an embodiment of a surgical grasping instrument 100 is illustrated. The surgical grasping instrument 100 can extend between a proximal end and a distal end and can comprise an end effector such as a jaw assembly 200 at the distal end, a shaft assembly 300 extending between the proximal end and the distal end, and a handle assembly 400 at the proximal end. In some embodiments, the surgical grasping instrument 100 can be configured for use in minimally-invasive surgical procedures such that it is sized and configured to be extended through a trocar cannula or other surgical access port. For example, in some embodiments, the shaft assembly 300 can comprise a generally tubular body having a smooth outer surface and an outer diameter sized for passage through a trocar cannula having a size classification to receive certain instruments such as, for example, a 12mm trocar, a 10mm trocar, and a 5mm trocar. In other embodiments, certain aspects of the surgical instruments described

herein can be adapted for use with surgical access ports having different sizes or in open surgical procedures.

[00034] With reference to Figure 2 and Figure 2B, an exploded view of the surgical grasping instrument 100 of Figure 1 is illustrated. In the illustrated embodiment, the jaw assembly 200 of the surgical grasping instrument 100 comprises a first jaw 210 coupled to a second jaw 230 at a pivot 250. Thus, by pivoting the first and second jaws 210, 230 with respect to one another, the jaw assembly 200 can be actuated between an open configuration in which the first jaw 210 is spaced from the second jaw 230 and a closed configuration in which the first jaw 210 is approximated with the second jaw 230 to grasp an object such as tissue, vasculature, or another surgical instrument therebetween.

[00035] In some embodiments, the jaw assembly 200 can be configured to reduce the potential for tissue trauma during use. For example, the first and/or second jaws 210, 230 can include an atraumatic pad formed thereon. As illustrated in both Figure 2 and Figure 2B, the first jaw 210 comprises a first atraumatic jaw pad 220 and the second jaw 230 comprises a second atraumatic jaw pad 240. In some embodiments, the first and second atraumatic pads 220, 240 can comprise soft, relatively low durometer atraumatic pads sold under the trademark LATIS®. In other embodiments, the jaw assembly 200 can include pad-less first and second jaws 210, 230 and pressure reduction at the jaws can be enhanced by a force reducing or limiting actuation mechanism.

[00036] With reference to Figure 2, Figure 2C, and Figure 2D, an exploded view of the surgical grasping instrument 100 of Figure 1 is illustrated. In the illustrated embodiment, the first and second jaws 210, 230 are pivotally coupled to one another and to shaft (not illustrated) at the pivot 250. An actuation post or pin 254 protrudes from each of the first and second jaws 210, 230 proximal of engagement with the pivot 250. The jaw assembly 200 is coupled to the distal end of the actuator 310 by a head member 360, which is positioned between proximal ends of each of the first and second jaws 210, 230. Each side of the head member 360 has a track 364 formed therein. The actuation posts or pins 254 of each of the first and second jaws 210, 230 are positioned within respective tracks 364 such that proximal and distal movements of the actuator 310 and

head member 360 with respect to the outer tube of the shaft moves the actuation pins 254 to open and close the first and second jaws 210, 230. A shim 370 can be positioned at the distal end of the head member 360 to maintain a desired spacing of the jaw assembly 200 and head member 360 within the outer tube. In the illustrated embodiment, the shim 370 can have a saddle configuration positioned astride the head member 360 and proximal ends of the first and second jaws 210, 230 to reduce any tendency of the actuation post or pin 254 to become disengaged from the track 364 under load.

[00037] With continued reference to Figure 2, the elongate shaft assembly 300 can comprise an actuator 310, an outer tube 330 and a dielectric sleeve 340. The actuator can be slidably positioned within the outer tube 330. The dielectric sleeve 340 can be disposed around an outer surface of the outer tube 330 and provide electrical insulation for the elongate shaft assembly 300. In certain embodiments, the actuator 310 can comprise a substantially planar member extending generally longitudinally between a proximal end 312 and a distal end 314. The substantially planar geometry of the actuator 310 can be defined by a length between the proximal end 312 and the distal end 314, a height orthogonal to the length, and a width orthogonal to both the length and the height. The width is substantially smaller than the height and the length. In certain embodiments, the actuator 310 can comprise a stack of a plurality of actuator strips, such as, for example, two actuator strips to provide an actuator 310 having desired stiffness, extension, and fatigue life characteristics.

[00038] With continued reference to Figure 2 and Figure 2A, in the illustrated embodiment, the handle assembly 400 comprises a housing formed of a pair of housing halves that define a stationary handle 410, a movable handle 420 pivotably coupled to the stationary handle 410 at a pivot pin of a locking mechanism 430, and a rotation knob 460. In the illustrated embodiment, the stationary handle 410 can be contoured to be grasped in the fingers of a user's hand and the movable handle 420 can include a thumb ring to be engaged by a user's thumb and moved by flexion and extension of the user's thumb. It is contemplated that in other embodiments, other configurations of handle

assembly can be used with the elongate shaft assemblies and end effector assemblies described herein.

[00039] With reference to Figure 3 – Figure 5 and Figure 3A – Figure 5A, the jaw assembly 200 of the surgical grasping instrument is illustrated in open (Figure 3 and Figure 3A), partially closed (Figure 4 and Figure 4A), and closed configurations (Figure 5 and Figure 5A). As illustrated in Figures 3 and 3A, with the jaw assembly 200 in the open configuration, the first jaw 210 is spaced from the second jaw 230 such that a user can position the surgical grasping instrument in a surgical site with an object to be grasped positioned between the first and second jaws 210, 230. The first jaw 210 and the second jaw 230 are pivotably coupled to one another at a pivot 250 such as a linkage rivet, pin, or other pivotable assembly.

[00040] With continued reference to Figure 3 and Figure 3A, the pivot 250 is also coupled to the outer tube 330 of the elongate shaft assembly 300 at the distal end of the elongate shaft assembly 300. The elongate shaft assembly 300 can further comprise a head member 360 that engages the first and second jaws 210, 230 of the jaw assembly 200 at engagement locations proximal the pivot 250. For example, in certain embodiments, the first and second jaws 210, 230 can each comprise an actuation pin protruding radially inwardly with respect to the elongate shaft assembly 300 at a location proximal the pivot 250, and the head member 360 can include a first groove, slot, or track 364 positioned to receive the actuation pin of the first jaw 210 and a second groove, slot, or track formed therein positioned to receive the actuation pin of the second jaw 230. The first track and the second track can extend transversely relative to the central longitudinal axis of the elongate shaft assembly 300 such that proximal and distal movement of the head member 360 pivots the first and second jaws 210, 230 relative to one another about the pivot 250.

[00041] With continued reference to Figure 3 and Figure 3A, in some embodiments, the elongate shaft assembly 300 can further include a jaw support member such as at least one shim member positioned within the outer tube 330 at the distal end to longitudinally align and maintain spacing of the head member 360 and the jaw assembly

200 relative to the central longitudinal axis. In the illustrated embodiments, the elongate shaft assembly 300 can include a seal element 350 disposed between the head member 360 and an inner surface of the outer tube 330 to prevent fluid and gas ingress or leakage from a surgical site into the elongate shaft assembly. For example, the elongate shaft assembly 300 can comprise an O-ring disposed retained by a groove in the head member 360.

[00042] With continued reference to Figure 3 and Figure 3A, a proximal end of the head member 360 can be coupled to a distal end of the actuator 310. In some embodiments, the proximal end of the head member 360 and the distal end of the actuator 310 can be configured to provide a coupling that is rotatable about the central longitudinal axis of the elongate shaft assembly 300. For example, as illustrated, the proximal end of the head member 360 comprises a protruding annular post 362, and the distal end 314 of the actuator 310 can comprise a cutout sized and configured to receive the annular post 362 and allow rotation of the jaw assembly 200 relative to the central longitudinal axis of the elongate shaft assembly 300. As further described with reference to Figure 6, rotation of the rotation knob 460 of the handle assembly 400 can thus rotate the outer tube 330 of the elongate shaft assembly 300 to rotate the jaw assembly 200 to a desired orientation relative to the central longitudinal axis.

[00043] With continued reference to Figure 3 and Figure 3A, in some embodiments, the head member 360 can be formed by a metal injection molding (MIM) process. Advantageously, this MIM process can allow the efficient, rapid manufacture of a head member 360 of a metallic material having desirable strength and fatigue life characteristics and being formed to have desired geometric features, with integrated tracks or slots to engage the jaw assembly 200 and a post or positioning pin to engage the actuator 310 as described above. In other embodiments, the head member 360 can be formed of a metallic material that has been cast, machined, or otherwise processed to have the desired geometry. In other embodiments, the head member 360 can be formed of a non-metallic material.

[00044] With reference to Figure 4 and Figure 4A, an embodiment of jaw assembly 200 is illustrated in a partially closed configuration. As illustrated, proximal translation of the actuator 310 along the central longitudinal axis pivots the first jaw 210 and the second jaw 230 relative to one another to approximate the first jaw pad 220 and the second jaw pad 240.

[00045] With continued reference to Figure 4 and Figure 4A, the first jaw 210 and the second jaw 230 have the same geometric features and pivot about the same pivot axis, which extends transversely to the central longitudinal axis. In the illustrated embodiment, the pivot axis of the first and second jaws 210, 230 extend generally perpendicularly to the central longitudinal axis. The first jaw 210 has a generally elongate configuration defining a first jaw axis, and the second jaw 230 has a generally elongate configuration defining a second jaw axis. In certain embodiments, proximal translation of the actuator 310 pivots the first and second jaws 210, 230 from an open position in which an angle defined between the first jaw axis and the second jaw axis is approximately 45 degrees, and a closed position in which the angle defined between the first jaw axis and the second jaw axis is approximately 0 degrees.

[00046] With reference to Figures 5 and 5A, an embodiment of jaw assembly 200 is illustrated in a closed configuration. In the closed configuration, the first jaw 210 and the second jaw 230 are approximated such that the first jaw pad 220 is adjacent the second jaw pad 240 or separated by an object being grasped. As noted above, the first jaw pad 220 and second jaw pad 240 can be formed of a material selected to be atraumatic to tissue grasped therebetween. Moreover, the first jaw pad 220 and second jaw pad 240 can be disposed over a relatively large surface area relative to the first jaw 210 and the second jaw 230. For example, desirably, the first and second jaw pads 220, 240 can extend along at least about 20% of a length of the first and second jaws 210, 230 distal the pivot 250. More desirably, the jaw pads 220, 240 can extend along at least about 25% of a length of the first and second jaws 210, 230 distal the pivot 250. Advantageously, this relatively large atraumatic contact surface can distribute pressure applied to a grasped object over a large surface area to reduce the risk of trauma to

grasped tissue. Moreover, the first and second jaw pads 220, 240 can be disposed at a transverse angle relative to a longitudinal axis defined by respective first and second jaws 210, 230. Thus, the angular seating of the first and second jaw pads 220, 240 can tend to draw a grasped object proximally with respect to the central longitudinal axis. This angular seating of the first and second jaw pads 220, 240 can advantageously increase the tractive ability of the surgical grasping instrument without significantly increasing the pressure applied to a grasped object.

[00047] With continued reference to Figure 5, in the illustrated embodiment of the jaw assembly 200, the first and second jaws 210, 230 can be configured to further reduce the incidence of trauma to tissue in the surgical site, the surgical access port, and other surgical instruments. For example, the first and second jaws 210, 230 can each be formed of a composite construction comprising a rigid metallic inner jaw spine to which an atraumatic non-metallic outer surface is applied. The first and second jaw pads 220, 240 can be disposed on the atraumatic non-metallic outer surface. Desirably, in some embodiments, the first and second jaws 210, 230 can each comprise a metallic inner jaw spine to which a plastic overmolded outer surface is applied. The plastic overmolds can each have a pad surface sized and be configured to receive the respective first and second jaw pads 220, 240. The pad surfaces can be formed at a transverse angle relative to a longitudinal axis of the respective first and second jaws 210, 230 to position the first and second jaw pads 220, 240 at an angled orientation. The first and second jaw pads 220, 240 can be adhered or otherwise bonded to the pad surface.

[00048] With reference to Figure 6, an embodiment of the handle assembly 400 for the surgical grasping instruments 100 described herein is illustrated. As illustrated, the movable handle 420 is spaced from the stationary handle 410 to position the jaw assembly 200 in an open configuration, as illustrated in Figure 3. Desirably, in certain embodiments, the stationary handle 410 can have an ergonomic finger grip comprising an elastomeric finger grip insert 415 (Figure 2) removably positioned in the grip to provide a soft touch surface for a user. Likewise, a thumb ring of the movable handle 420 can comprise an elastomeric thumb ring insert 425 (Figure 2) removably positioned

in the thumb ring to provide a soft touch surface for a user. A user can additionally rotate rotation knob 460 relative to the handle assembly 400 to rotate the outer tube 330 relative to the handle assembly 400. For example, the handle assembly 400 can be configured with an ergonomic profile such that a user's index finger can easily be extended to rotate the rotation knob 460. This rotation can orient the jaw assembly 200 coupled to the outer tube 330 in a desired orientation about tissue, vasculature, or another object to be grasped.

[00049] With reference to Figure 7, the handle assembly 400 is illustrated in a partially closed configuration corresponding to the jaw assembly 200 in a partially closed configuration as illustrated in Figure 4. In the partially closed configuration, the movable handle 420 is pivoted relative to the stationary handle 410 about the pivot pin of the locking mechanism 430. In the illustrated embodiment, the movable handle extends from a first end 422 having the thumb ring to a second end 424. The pivot pin of the locking mechanism 430 is disposed between the first end 422 and the second end 424. The second end 424 of the movable handle 420 is coupled to the proximal end 312 of the actuator 310. In some embodiments the proximal end 312 of the actuator 310 can comprise a proximal coupler 313 such as a recess, bore, slot, or other feature that is configured to be coupled to with the second end 424 of the movable handle 420 and allow the transfer of force therebetween. In the illustrated embodiment, the proximal coupler comprises a bore that can receive a post protruding from the second end 424 of the movable handle 420 or can be coupled thereto by a coupling pin or rivet. Thus, as the movable handle 420 is pivoted about the pivot pin of the locking mechanism 430, the actuator 310 is pulled proximally with respect to the central longitudinal axis. This proximal movement likewise moves the head member 360 of the elongate shaft assembly 300 proximally to close the jaw assembly 200, as shown in Figure 4.

[00050] With reference to Figure 8 and Figure 9, further movement of the movable handle 420 can further actuate the surgical grasping instrument to move the jaw assembly 200 to a closed configuration as shown in Figure 5. In some embodiments, the handle assembly 400 further comprises the locking mechanism therein to maintain the

movable handle 420 in a desired position relative to the stationary handle 410. In certain embodiments, the locking mechanism 430 can comprise a trigger lock 440 and a lock release 450 that are actuated by a user to latch and unlatch the locking mechanism.

[00051] With continued reference to Figure 8 and Figure 9, an embodiment of the locking mechanism 430 is illustrated in latched (Figure 8) and unlatched (Figure 9) configurations. The trigger lock 440 of the locking mechanism 430 extends from a first end having a trigger portion 444 extending adjacent the stationary handle 410 to a second end having a locking portion 442 and positioned within the handle assembly 400 adjacent the actuator 310. In some embodiments, the actuator 310 can have an engagement surface such as a latch recess formed therein and sized and configured to be selectively engaged by the locking portion 442 of the trigger lock 440 when the locking mechanism 430 is in a latched configuration. The locking mechanism 430 can further comprise a locking spring 446 within the handle assembly to bias the locking portion 442 of the trigger lock 440 to maintain the engagement of the locking portion 442 with the latch recess when the locking mechanism 430 is in the latched configuration.

[00052] With reference to Figure 8, with the locking mechanism 430 in a latched configuration, the locking portion 442 of the trigger lock 440 is positioned and oriented to restrict the actuator 310 from freely translating proximally and distally with respect to the central longitudinal axis. For example, in some embodiments, the locking portion 442 can comprise a passage or generally rectangular window formed therein through which the actuator 310 can freely translate when the locking portion 442 is oriented generally perpendicularly to the actuator 310 (as illustrated in Figure 9) and which engages the actuator 310 when passage of the locking portion is misaligned with an axis perpendicular to the longitudinal axis of the actuator (Figure 8). The locking spring 446 biases the locking portion 442 of the trigger lock 440 into binding engagement with the actuator 310 once the lock release 450 has been depressed to allow the trigger lock 440 to separate from the stationary handle 410. Thus, this engagement between the trigger lock 440 and actuator 310 locks the jaw assembly 200 in a desired position.

[00053] In some embodiments, the trigger lock 440 of the locking mechanism 430 may define a reverse limit for the jaw assembly 220 preventing attempts by the jaw assembly 220 to revert from the closed position to the open position beyond the point defined by the locking mechanism 430. However, the restrictions imposed by the trigger lock 440 may not define a forward limit corresponding to an extent the jaw assembly 220 compresses the tissue in the closed position.

[00054] With reference to Figure 9, when a user desires to reposition the first and second jaws to grasp tissue specimens, the movable handle 420 can be moved to a desired position such as a partially closed or closed position with the locking mechanism 430 in an unlatched configuration having the trigger lock 440 approximated with the stationary handle 410 by latching engagement with the lock release 450. As illustrated, an end of the trigger portion 444 can be advanced over the lock release 450 and maintained adjacent the stationary handle 410 by the lock release 450. With the trigger lock 440 positioned adjacent the stationary handle 410, the locking portion 442 of the trigger lock 440 is oriented to allow free translation of actuator 310 through the passage formed in the locking portion 442 responsive to movement of the movable handle 420.

[00055] With continued reference to Figure 9, in certain embodiments, the lock release 450 can be pivotally coupled to the stationary handle 410 at a lock release pivot 452. The lock release 450 can be biased to maintain the trigger portion 444 of the trigger lock 440 adjacent the stationary handle 410. In the illustrated embodiment, the lock release 450 can be biased with a lock release spring 454 disposed within the handle assembly. It is contemplated that in other embodiments, the lock release 450 can be formed of a flexible member extending from the stationary handle 410 with the desired bias and without a lock release pivot. When a user desires to engage the locking mechanism 430 to maintain a fixed position of the movable handle 420, actuator 310, and jaw assembly 200, the user can depress the lock release 450 to overcome the bias of the lock release spring 454 and pivot the lock release 450 out of engagement with the end of the trigger portion 444 of the trigger lock 440.

[00056] With reference to Figure 10, an embodiment of actuator 310 for use in the elongate shaft assemblies described herein is illustrated in undisturbed (upper) and extended (lower) states. The actuator 310 has a substantially planar configuration with a significantly small width relative to its length and height. Advantageously, this planar configuration can be efficiently manufactured from a coil or sheet of a metallic material that can be heat treated to achieve desired tensile strength and durability characteristics. For example, in some embodiments, the actuator 310 can be stamped from a sheet of a metallic material having desired structural properties. In some embodiments, the actuator 310 can be formed from a metallic material such as a coil sheet of 17-7 PH stainless steel. In certain embodiments of the surgical grasping instrument, two or more stamped sheet actuators can be arranged in parallel in an adjoining orientation to achieve desired extension properties and durability characteristics while being relatively rapidly manufacturable by progressive stamping. In some embodiments, the actuator 310 can be configured to limit the force applied to an object being grasped, which advantageously can reduce the incidence of trauma to grasped tissue.

[00057] With continued reference to Figure 10, in some embodiments, the actuator 310 can comprise a segment formed to define an integrated extension element 316. Advantageously, the extension element 316 can function as a force-limiting spring mechanism for the actuator 310 having an integrated construction that allows for low-cost, efficient manufacture of the actuator 310. As illustrated, the extension element 316 can be disposed between the proximal end 312 and distal end 314 of the actuator 310, with the remaining segments of the actuator defining a non-extending, or rigid elements 324. As illustrated, in one embodiment, the extension element 316 can have a height orthogonal to the length of the actuator 310 that is smaller than a corresponding height of the rigid elements 324. In the illustrated embodiment, the extension element 316 comprises a height that is approximately half of the height of the rigid elements 324.

[00058] With reference to Figure 10, Figure 11A, and Figure 11B in some embodiments the extension element 316 can comprise a geometric profile defining a desired spring constant for the actuator 310. For example, in certain embodiments, the extension

element 316 comprises a plurality of longitudinal sections 322 extending generally parallel to the central longitudinal axis, a plurality of transverse sections 318 extending transverse to the central longitudinal axis, and a plurality of bends 320 disposed between each longitudinal section of the plurality of longitudinal sections and an adjacent transverse section of the plurality of transverse sections. In certain embodiments, each bend 320 can comprise an arc segment having an inner radius and an outer radius. In certain embodiments, the extension element 316 can comprise a plurality of extension sections 317. In certain embodiments, each individual extension section 317 is a full section defined by a segment of a generally waveform-like profile extending from a peak to an adjacent peak (or a trough to an adjacent trough). Thus, each extension section 317 can comprise a first longitudinal segment 322, a first bend 320, a first transverse segment 318, a second bend 321, a second longitudinal segment 323, a third bend 325, a second transverse segment 319, and a fourth bend 327.

[00059] With continued reference to Figure 10, Figure 11A, and Figure 11B, when a tensile force is applied to the actuator 310, a distance (X) (Figure 11A) between adjacent longitudinal segments 322 will extend to an extended length ($X+\Delta X$) (Figure 11B) such that the overall length between the proximal end 312 and the distal end 314 is extended (Figure 10). Thus, this extension characteristic of the actuator 310 can desirably limit a force applied by the jaw assembly of a surgical grasping instrument. In the event a user applies a relatively high force or attempts to grasp a relatively thick tissue sample, a portion of the applied force will extend the actuator, rather than being directly applied to grasped tissue.

[00060] With continued reference to Figure 10, Figure 11A, and Figure 11B in certain embodiments, the dimensions of the longitudinal segments 322, bends 320, and transverse segments 318 can be sized and configured to provide an extension element 316 having a desired spring constant and resistance to fatigue. In certain embodiments, the actuator 310 is formed of a rigid material, such as a stainless-steel sheet material, which has elastic properties under controlled tensile loads. Desirably, the actuator 310 can have a substantially planar configuration with a width or thickness dimension being

significantly smaller than a height or length dimension. In certain embodiments, whereas the surgical grasping instrument is introduced within 5mm trocar delivery systems, the outer tube can have a maximum outer diameter of 0.197 inch and a minimum inner diameter of 0.140 inch. In certain embodiments, the actuator 310 positioned within the outer tube can have a height between .190 inch and .100 inch and have a thickness between .010 inch and .110 inch. Desirably, two actuators can have a combined thickness between .020 inch and .110 inch. In certain embodiments, multiple actuators can be assembled together in parallel, having a combined thickness between .020 inch and .110 inch. In certain embodiments, although the surgical grasping instrument is introduced within greater than 5mm trocar delivery systems, the actuator 310 can have a maximum height of .350 inch and have a thickness between .010 inch and .250 inch. In some embodiments for use with an instrument sized and configured for placement through a 5mm category access port such as a 5mm trocar, the actuator 310 can have a thickness of approximately .040 inch. In certain embodiments, the actuator 310 can comprise a stack of two adjoining actuator members each having a thickness of approximately .020 inch.

[00061] With continued reference to Figure 10, Figure 11A, and Figure 11B in certain embodiments, the extension element 316 can comprise at least 20 extension sections 317. Desirably, the extension element can comprise at least 30 extension sections 317. More desirably, in certain embodiments, the extension element 316 can comprise at least 40 extension sections 317. In certain embodiments, the extension element 316 can comprise 48 extension sections 317. While the illustrated embodiment includes a plurality of extension sections 317 that each have a consistent geometry, repeating to form the extension element 316, in other embodiments, the extension element 316 can be formed of various segment and bend geometries that have a variable pattern along a length of the actuator 310.

[00062] With continued reference to Figure 10, Figure 11A, and Figure 11B, in certain embodiments the bends 320 can have an arc geometry defined by an inner radius and an outer radius. In other embodiments, the bends 320 can be formed by sections having

sharp angles with no fillet or radii. In certain embodiments, the inner radius can be between about 0.02 inch and 0.08 inch. Desirably, a full radius defined by the inner radius can be between approximately 0.05 inch and 0.06 inch. In certain embodiments, the outer radius can be between approximately 0.024 inch and 0.054 inch. In some embodiments, the inner radius is greater than the outer radius. In other embodiments, the inner radius is less than the outer radius. In certain embodiments, a full radius defined by the inner radius is approximately 0.05 inch and the outer radius is approximately 0.044 inch. In other embodiments, a full radius defined by the inner radius is approximately 0.06 inch and the outer radius is approximately 0.036 inch.

[00063] In certain embodiments, the inner and outer radii can be sized and configured to provide an extension element 316 having a relatively constant width defined by a line tangent to an upper edge and a lower edge of the extension element 316. In certain embodiments, the width defined by the line tangent to the upper edge and the lower edge of the extension element 316 is between about 0.060 inch and 0.080 inch. Desirably, the width of the extension element 316 defined by the tangent line can be between about 0.065 inch and 0.075 inch. In certain embodiments, the width of the extension element 316 defined by the tangent line can be about 0.07 inches.

[00064] With continued reference to Figure 10, Figure 11A, and Figure 11B, the extension element 316 of the actuator 310 can be spaced from the distal end 314 by a rigid element 324 defining a connector end with a straight section having a height greater than the width defined by the line tangent to the upper edge and the lower edge of the extension element 316. In some embodiments, the extension element 316 can be spaced apart from the distal end 314 by at least 0.2 inch. In other embodiments, the extension element 316 can be spaced from the distal end 314 by a connector end straight section having a minimal distance of as approximately 0.02 inch.

[00065] With continued reference to Figure 10, Figure 11A, and Figure 11B, in certain embodiments, a total length of each full extension section 317 can be sized and configured to provide a desired spring constant and fatigue strength. In some embodiments, the length of each full extension section 317 can be between

approximately 0.200 inch and 0.360 inch. Desirably, the length of each extension section 317 can be between approximately 0.240 inch and 0.260 inch. In certain embodiments, each extension section can have a length of approximately 0.240 inch. In other embodiments, each extension section can have a length of approximately 0.260 inch.

[00066] With continued reference to Figure 10 and Figure 11A, desirably, when a force applied to the actuator 310 by actuation of the movable handle is below a predetermined level, the actuator 310 translates within the outer tube 330 with the extension element 316 maintaining a constant length. Thus, with a relatively low force applied to the actuator 310, the actuator 310 functions as a solid rod actuator. The actuator 310 has a first length along the central longitudinal axis that remains constant on translation with application of a relatively low force to move the actuator 330 as a solid rod.

[00067] With reference to Figure 10 and Figure 11B, when a relatively high force is applied to the actuator 310, such as when a thick tissue specimen is inserted between the first and second jaws of the jaw assembly, the extension element 316 can stretch in response, thereby reducing the effective stroke length of the actuator 310 at the distal end 314. In some embodiments, the actuator 310 functions as a spring-like actuator. Thus, upon application of a predetermined extension force, the actuator 310 extends to a second length greater than the first length. In this higher force loading condition, the actuator 310 both translates within the outer tube 330 and extends in length between the proximal end 312 and the distal end 314. This reduced effective stroke length provided by extension of the extension element 316 advantageously limits the force applied by the end effector or jaw assembly and correspondingly reduces a risk of trauma to tissue grasped by the jaw assembly. The actuator 310 provides this force limiting performance as a single, integral component without the added mechanical and manufacturing complexities and increased expenditures of one or more additional springs. Desirably, the extension element 316 of the actuator 310 is sized and configured to deform elastically when a relatively high force is applied thereto as illustrated in Figure 11B such that once the force is released, the actuator 310 returns to its original, undeformed state and length.

[00068] In a further embodiment, the actuator 310 is also sized and configured to supplement the first and second jaws of the jaw assembly with force that was loaded into the actuator 310 (which caused the actuator 310 to deform elastically as described above). In some cases, the jaw assembly may be locked in a closed position with tissue that is being grasped between the first and second jaw. The extent that the jaw assembly is in contact with the tissue is based on the thickness and/or volume of the tissue being grasped as well as the pre-determined amount of force that is provided to the tissue. However, if the tissue deforms (*e.g.*, as fluids leave or are pushed out of the cells associated with the grasped tissue) which causes the thickness and volume of tissue being initially grasped to decrease, the original contact between the tissue and the jaw assembly may no longer be possible. Furthermore, in a conventional surgical grasper with a rigid, non-elastic actuator, since the first and second jaws of the jaw assembly are locked, tissue deformation may prevent the jaw assembly from properly grasping the tissue possibly causing the contact with the tissue to become loose or even slip from the jaw assembly.

[00069] Desirably, certain embodiments of the surgical grasping device described herein can provide a dynamic amount of force from the actuator 310 in order to maintain constant and/or consistent contact with the tissue between the first and second jaws of the jaw assembly as the tissue deforms. The dynamic amount of force being provided to the jaw assembly is supplied from the excess force that was previously loaded into the actuator 310. As discussed above, the actuator 310 may extend from a first length to a second greater length when loading force being provided by the user (via the movable handle). As the thickness and volume of tissue that was initially grasped between the first and second jaws of the jaw assembly changes (*e.g.*, via deformation), a response from the actuator 310 can provide the force that was loaded into the actuator 310 to the jaw assembly so that the first and second jaws are pivoted closer towards each other in order to maintain contact with the tissue. This force, as it leaves the actuator 310, causes the actuator 310 to retract from the second greater length back towards the first length. The response from the actuator 310 provides additional force to the first and second jaws

as needed to maintain contact with the deforming/deformed tissue based on the extent the thickness and volume of the tissue changes over time. In this way, contact with the tissue, as the tissue deforms, can be made constant/consistent between the first and second jaws of the jaw assembly.

[00070] With reference to Figure 10 and Figure 12, various embodiments of the actuator 310 are illustrated having different lengths of rigid element 324 adjacent the proximal end. As illustrated, the extension element 316 of the actuator 310 can be spaced from the proximal end 312 by a rigid element 324 having a height greater than a width of the extension element 316 defined by a line tangent to the upper edge and the lower edge of the extension element 316. In certain embodiments, it can be desired that the length of rigid element 324 adjacent the proximal end be relatively long to conform to surgical instruments having different dimensions or operational configurations. For example, as illustrated in Figure 12, an extension element 316 having a substantially similar configuration can be used in each of a 35 cm length single-use grasper (uppermost illustrated actuator), a 45 cm single-use grasper (second actuator from top), a 38 cm reusable grasper shaft (third actuator from top), and a 45 cm reusable grasper shaft (lowermost actuator). Alternatively, by varying the length of the extension element 316 relative to the lengths of the rigid elements 324 at the proximal and distal ends 213, 314 of the actuator 310, desired extension properties of the actuator 310 can be achieved.

[00071] With reference to Figure 10 – Figure 12, the illustrated embodiments include a planar actuator 310 with an extension element 316 integrally formed therewith. Advantageously, this planar actuator can provide manufacturing efficiencies and can fit within and be constrained for translation within a relatively small space, such as an elongate shaft assembly sized for insertion through a surgical access port for 5mm laparoscopic instruments. In other embodiments, it is contemplated that other actuator configurations can provide a desired integrated force-limiting extension element.

[00072] With reference to Figure 13 and Figure 14, a partial cut-away side view of an embodiment of elongate shaft assembly 300' for use in a surgical instrument is

illustrated. In the illustrated embodiment, the elongate shaft assembly 300' comprises an actuator 310' having a non-planar configuration with a generally repeating waveform or convoluted profile. This convoluted profile can desirably allow the actuator 310' to extend when a relatively high force is applied while still performing as a solid rod actuator, as discussed above with respect to actuator 300. In some embodiments, the non-planar actuator 310' configuration can provide flexibility such that the actuator 310' can be disposed within a flexible outer tube 330' or an outer tube having a curvature, rather than constrained within a relatively rigid outer tube. In some embodiments, the actuator 310' can comprise a metallic material, in other embodiments, the actuator 310' can comprise a polymeric material, and in other embodiments, the actuator 310' can comprise a polymer-metal composite material. In certain embodiments, a convoluted, non-planar actuator 310' can be formed of a polymeric material through an injection molding process. In other embodiments, a convoluted, non-planar actuator 310' can be formed of a polymeric material through an extrusion process.

[00073] With continued reference to Figure 13 and Figure 14, the convoluted profile of the actuator 310' defining a relieved cylindrical outer surface. This convoluted profile can desirably provide enhanced flexibility about two orthogonal axes such that the actuator 310' can be disposed within a flexible outer tube 330' or an outer tube having a curvature, rather than constrained within a relatively rigid outer tube.

[00074] With reference to Figure 15, in some embodiments, an actuator 310'' can comprise a hollow tubular member with relief slots 316'' formed therein to define a flexible and extendable segment therein. These relief slots can desirably allow the slotted-tube actuator to extend when a relatively high force is applied while still performing as a solid rod actuator, as discussed above with respect to actuator 300. In some embodiments, as with the non-planar actuators 310' the slotted-tube actuator 310'' can provide flexibility about multiple orthogonal axes such that the slotted-tube actuator can be disposed within a flexible outer tube or an outer tube having a curvature, rather than constrained within a relatively rigid outer tube. In some embodiments, the slotted-tube actuator can comprise a metallic material, in other embodiments, the slotted-tube

actuator can comprise a polymeric material, and in other embodiments, the slotted-tube actuator can comprise a polymer-metal composite material.

[00075] It is contemplated that various other actuator configurations can provide similar integrated extension element performance as described herein with respect to a planar sheet actuator. For example, in certain other embodiments, surgical instruments can include an actuator comprised of or formed from a wire, such as for example a wire having a solid, round, semi-circular, rectangular, or square cross-sectional profile, or braided rope cables formed of multiple wire or filament strands. Additionally, it is contemplated that while certain embodiments of planar actuator are described as formed of a metallic material, in other embodiments, the actuator can be formed of a polymeric material. Furthermore, while the actuation mechanisms are discussed herein with respect to certain advantages in a surgical grasper instrument, it is contemplated that various aspects of the actuation mechanisms can likewise provide advantages in other surgical instruments and in various devices outside the medical field in which it can be desirable to provide an extension element that operates as a solid rod actuator with a relatively low applied force and an extension element with a relatively high applied force.

[00076] Although this application discloses certain preferred embodiments and examples, it will be understood by those skilled in the art that the present inventions extend beyond the specifically disclosed embodiments to other alternative embodiments and/or uses of the invention and obvious modifications and equivalents thereof. Further, the various features of these inventions can be used alone, or in combination with other features of these inventions other than as expressly described above. Thus, it is intended that the scope of the present inventions herein disclosed should not be limited by the particular disclosed embodiments described above but should be determined only by a fair reading of the claims granted on a related non-provisional application.

CLAIMS

What is claimed is:

1. A surgical grasping instrument comprising:
 - a handle assembly comprising:
 - a stationary handle, and
 - a movable handle pivotably coupled to the stationary handle;
 - an elongate shaft extending distally from the handle assembly, wherein the elongate shaft having a proximal end coupled to the handle assembly, a distal end opposite the proximal end, and a central longitudinal axis defined by the proximal end and the distal end, the elongate shaft comprising:
 - an outer tube, and
 - an actuator positioned longitudinally within the outer tube, wherein the actuator having a sliding fit with the outer tube, and wherein the actuator being responsive to pivotal movement of the movable handle; and
 - a jaw assembly at the distal end of the elongate shaft, wherein the jaw assembly comprises a first jaw and a second jaw, wherein the first jaw and the second jaw are pivotable between an open configuration of the jaw assembly and a closed configuration of the jaw assembly responsive to pivotal movement of the movable handle,
 - wherein the actuator has a first length along the central longitudinal axis, and wherein the actuator comprises an extension element that lengthens the actuator to a second length greater than the first length in response to a predetermined force applied to the actuator.
2. The surgical grasping instrument of claim 1, wherein the actuator is formed of a material having elastic material properties during axial plane motion within the outer tube.

3. The surgical grasping instrument of claim 2, wherein the actuator deforms elastically under reciprocating tensile and compressive stress loading in response to pivotal movement of the movable handle.

4. A surgical instrument comprising:

a handle assembly comprising:

a stationary handle,

a movable handle pivotably coupled to the stationary handle, and

a locking mechanism comprising:

a locking member having a lock portion extending within the handle assembly and a trigger portion extending adjacent an outer surface of the stationary handle, the locking member movable between a locked position and an unlocked position, and

a lock release coupled to the stationary handle, wherein the lock release maintains the locking member in the unlocked position, and wherein the lock release is actuatable to release the locking member to the locked position;

an elongate shaft extending distally from the handle assembly, the elongate shaft having a proximal end coupled to the handle assembly, a distal end opposite the proximal end, and a central longitudinal axis defined by the proximal end and the distal end, the elongate shaft comprising:

an outer tube, and

an actuator positioned longitudinally within the outer tube, the actuator having a sliding fit with the outer tube, and the actuator being responsive to pivotal movement of the movable handle, the actuator having a proximal section extending within the handle assembly to a proximal end and the actuator comprising a locking surface adjacent the proximal end, wherein the lock portion of the locking member is engaged with the locking surface of the actuator with the locking mechanism in the locked position; and

an end effector at the distal end of the elongate shaft, the end effector movable between a first configuration and a second configuration responsive to pivotal movement of the movable handle.

5. The surgical instrument of claim 4, wherein the actuator has elastic material properties during axial plane motion within the outer tube.

6. The surgical instrument of claim 5, wherein the actuator has a relatively high fatigue strength and creep resistance under normal use loading.

7. The surgical instrument of claim 6, wherein the actuator deforms elastically under reciprocating tensile and compressive loading responsive to pivotal movement of the movable handle.

8. A surgical instrument comprising:

a handle assembly comprising:

a stationary handle; and

a movable handle pivotably coupled to the stationary handle;

an elongate shaft extending distally from the handle assembly, the elongate shaft having a proximal end coupled to the handle assembly, a distal end opposite the proximal end, and a longitudinal axis defined by the proximal end and the distal end, the elongate shaft comprising:

an outer tube, and

an actuator positioned longitudinally within the outer tube, the actuator having a sliding fit with the outer tube and the actuator being responsive to pivotal movement of the movable handle, the actuator having a length extending along the longitudinal axis, a height, and a width, wherein the width being substantially smaller than the height such that the actuator has a planar profile, and wherein the actuator comprises:

a first segment having a first height, and

a second segment having a second height defined by a line tangent to an upper edge and a lower edge of the second segment, the second height smaller than the first height and the second segment defining an extension element longitudinally extendable responsive to force applied to the actuator, and the second segment comprising:

a plurality of longitudinal sections extending generally parallel to the longitudinal axis,

a plurality of transverse sections extending transverse to the longitudinal axis, and

a plurality of bends disposed between each longitudinal section of the plurality of longitudinal sections and an adjacent transverse section of the plurality of transverse sections; and

an end effector at the distal end of the elongate shaft, the end effector movable between a first configuration and a second configuration responsive to pivotal movement of the movable handle.

9. The surgical instrument of claim 8, wherein the extension element of the second segment is defined by a repeating sequence of extension segments, each extension section comprising: a first longitudinal section, a first bend, a first transverse section, a second bend, a second longitudinal section, a third bend, a second transverse section, a fourth bend, and a third longitudinal section.

10. The surgical instrument of claim 8, wherein the extension element deforms elastically in response to rectilinear tensile and compressive forces.

11. A surgical instrument for grasping tissue, the surgical instrument comprising:

a handle assembly comprising a movable handle pivotably coupled to a stationary handle;

a jaw assembly, wherein the jaw assembly comprises a first jaw and a second jaw, and wherein the first jaw and the second jaw are pivotable between an open configuration of the jaw assembly and a closed configuration of the jaw assembly responsive to pivotal movements of the movable handle; and

an elongate shaft assembly having a proximal end coupled to the handle assembly and a distal end coupled to the jaw assembly, the elongate shaft assembly comprising:

an outer case;

at least one actuator enclosed in the outer case, and

the at least one actuator having a proximal end and a distal end, wherein each of the at least one actuator comprises a plurality of extension elements disposed between the proximal end and the distal end, wherein the extension elements have a geometric profile that corresponds to a pre-defined spring constant, and wherein the at least one actuator limit an amount of force above a pre-determined threshold that is provided to the jaw assembly, the force being received via the pivotal movements of the movable handle.

12. The surgical instrument of claim 11, wherein the at least one actuator is created via a stamping process that stamps a sheet of metallic material having desired structural properties.

13. The surgical instrument of claim 11, wherein the at least one actuator comprises two or more actuators, and wherein the two or more actuators are arranged in parallel in an adjoining orientation.

14. The surgical instrument of claim 13, wherein the arrangement of the two or more actuators provide a pre-determined extension property.
15. The surgical instrument of claim 13, wherein the arrangement of the two or more actuators provide a pre-determined durability property.
16. The surgical instrument of claim 13, wherein the arrangement of the two or more actuators provide a pre-determined resistance to fatigue.
17. The surgical instrument of claim 13, wherein the arrangement of the two or more actuators provide a pre-determined spring constant.
18. The surgical instrument of claim 13, wherein the arrangement of the two or more actuators establish a pre-determined limit to an amount of force that can be provided to the jaw assembly.
19. The surgical instrument of claim 13, wherein the one or more actuators further includes non-extending elements.
20. The surgical instrument of claim 13, wherein the elongate shaft assembly has a central longitudinal axis extending between the proximal end thereof and the distal end thereof, and wherein the geometric profile for the extension elements comprises:
 - a plurality of longitudinal sections extending parallel to the central longitudinal axis;
 - a plurality of transverse sections extending transverse to the central longitudinal axis; and
 - a plurality of bends, each disposed between one of the plurality of longitudinal section and an adjacent one of the plurality of traverse sections.

21. The surgical instrument of claim 20, wherein at least one of the plurality of bends comprises an arc segment having an inner radius and an outer radius.
22. The surgical instrument of claim 20, wherein at least one of the plurality of bends has sharp angles with no fillet or radii.
23. The surgical instrument of claim 11, wherein each of the extension elements comprises a plurality of extension sections that each have a waveform-like profile comprising a peak and a trough.
24. The surgical instrument of claim 23, wherein each of the extension sections comprises a first longitudinal segment, a first bend, a first transverse segment, a second bend, a second longitudinal segment, a third bend, a second transverse segment, and a fourth bend.
25. The surgical instrument of claim 11, wherein a distance that the actuator extends and an amount of force that the jaw assembly exhibits is based on an amount of force applied to the actuator via the movable handle.
26. The surgical instrument of claim 11, wherein the elongate shaft assembly is flexible.
27. The surgical instrument of claim 11, wherein the elongate shaft assembly is curved.
28. The surgical instrument of claim 11, further comprising a locking mechanism, wherein the locking mechanism comprises:
- a locking member having a lock portion extending within the handle assembly and a trigger portion extending adjacent an outer surface of the stationary handle, wherein the locking member is movable between a locked position and an unlocked position;

a lock release coupled to the stationary handle, wherein the lock release maintains the locking member in the unlocked position, and wherein the lock release is actuatable to release the locking member to the locked position; and

a locking spring within the handle assembly that biases the lock portion of the locking member to maintain an engagement with the at least one actuator when in the locked position, wherein the engagement restricts the at least one actuator from freely translating proximally and distally.

29. The surgical instrument of claim 11, wherein the at least one actuator exhibits characteristics of a solid rod when the amount of force received from the movable handle is below the pre-determined threshold.

30. The surgical instrument of claim 11, wherein the at least one actuator exhibits characteristics of a spring when the amount of force received from the movable handle is above the pre-determined threshold to limit the amount of force that is provided to the jaw assembly.

31. The surgical instrument of claim 11, wherein the at least one of actuator is configured to provide the jaw assembly with a dynamic amount of force in response to deformation of tissue initially grasped by the jaw assembly in the closed position, and wherein the dynamic amount of force provided by the at least one actuator configures the jaw assembly to exhibit constant contact to the tissue initially grasped between the jaw assembly as the tissue deforms over a period of time.

32. The surgical instrument of claim 31, wherein the dynamic amount of force consists of a first threshold that corresponds to a maximum limit of force that is provided to the jaw assembly by the one or more actuators, wherein force above the first threshold is loaded into the one or more actuators.

33. The surgical instrument of claim 32, wherein a first state of the tissue corresponds to a volume of the tissue when initially grasped between the jaw assembly in the closed position having a first amount of contact between the jaw assembly.

34. The surgical instrument of claim 33 further comprising a second state of the tissue corresponding to deformation of the tissue such that the volume of the tissue grasped between the jaw assembly in the closed position is less than the volume of the tissue in the first state, and wherein an amount of contact of the tissue between the jaw assembly in the second state is less than the first amount of contact.

35. The surgical instrument of claim 11, wherein the at least one actuator has a first length in an undisturbed state, wherein the at least one actuator is extendable to a second length greater than the first length upon application of a force greater than the pre-determined threshold when tissue having a first thickness is positioned between the first jaw and the second jaw of the jaw assembly and the first and second jaws are pivoted towards the closed configuration to provide contact to the tissue.

36. The surgical instrument of claim 35, wherein upon deformation of the tissue to a second thickness smaller than the first thickness, the at least one actuator retracts from the second length to provide a supplemental amount of force to the first and second jaws in order to maintain the contact with the tissue via the first jaw and the second jaw with the tissue.




FIG. 1




FIG. 2




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3




FIG. 4




FIG. 5




FIG. 3A




FIG. 4A






FIG. 5A






FIG. 8




FIG. 9






FIG. 10

*FIG. 11A**FIG. 11B*




FIG. 12




FIG. 13




FIG. 14




FIG. 15

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2019/060743

A. CLASSIFICATION OF SUBJECT MATTER

INV. A61B17/29 A61B90/00
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2008/255608 A1 (HINMAN CAMERON D [US] ET AL) 16 October 2008 (2008-10-16) figures 1, 20 paragraph [0063] - paragraph [0064] -----	1-3
X	DE 200 20 192 U1 (STORZ KARL GMBH & CO KG [DE]) 15 March 2001 (2001-03-15) -----	1-3, 11-27, 29-36
Y	the whole document -----	8-10
Y	WO 2007/146842 A2 (SURGICAL SOLUTIONS LLC [US]) 21 December 2007 (2007-12-21) figures 8A, 8B paragraph [0074] - paragraph [0075] ----- -/-	8-10



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

29 January 2020

Date of mailing of the international search report

26/03/2020

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Emirdag, Eda

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2019/060743

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6 500 189 B1 (LANG DIETER [DE] ET AL) 31 December 2002 (2002-12-31) figures 12, 12a, 13 column 13, line 8 - column 14, line 7 -----	1-3, 8-27, 29-36
A	US 5 395 375 A (TURKEL DAVID [US] ET AL) 7 March 1995 (1995-03-07) figures 2a-2c column 3, line 55 - column 4, line 31 -----	1-3, 8-27, 29-36

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2019/060743

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fees, this Authority did not invite payment of additional fees.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

1-3, 8-27, 29-36

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- ☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- ☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. claims: 1-3, 8-27, 29-36

Force limiting mechanism

2. claims: 4-7, 28

Locking mechanism

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2019/060743

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2008255608 A1	16-10-2008	US 2008255608 A1	16-10-2008
		US 2013218140 A1	22-08-2013
DE 20020192 U1	15-03-2001	DE 20020192 U1	15-03-2001
		US 6589259 B1	08-07-2003
WO 2007146842 A2	21-12-2007	AU 2007257754 A1	21-12-2007
		AU 2011202493 A1	16-06-2011
		CA 2622731 A1	21-12-2007
		EP 2024259 A2	18-02-2009
		JP 4731606 B2	27-07-2011
		JP 2009506804 A	19-02-2009
		US 2008221393 A1	11-09-2008
		US 2010160736 A1	24-06-2010
		WO 2007146842 A2	21-12-2007
US 6500189 B1	31-12-2002	DE 50011194 D1	27-10-2005
		DE 59900101 D1	28-06-2001
		EP 1055397 A1	29-11-2000
		US 6500189 B1	31-12-2002
		US 2003028207 A1	06-02-2003
US 5395375 A	07-03-1995	NONE	