



(12) **United States Patent**  
**Emerick et al.**

(10) **Patent No.:** **US 11,534,311 B2**  
(45) **Date of Patent:** **Dec. 27, 2022**

(54) **ADJUSTABLE INTERBODY FUSION DEVICE AND METHOD OF USE**

(56) **References Cited**

(71) Applicant: **BioSpine, LLC**, Columbia City, IN (US)

U.S. PATENT DOCUMENTS

4,759,769 A 7/1988 Hedman  
4,951,519 A 8/1990 Ohtsuka  
(Continued)

(72) Inventors: **Brian G. Emerick**, Columbia City, IN (US); **Daniel Refai**, Atlanta, GA (US); **Ross R. Nichols**, North Webster, IN (US)

FOREIGN PATENT DOCUMENTS

EP 2226039 9/2010  
WO 2009064787 A 5/2009  
(Continued)

(73) Assignee: **BioSpine, LLC**, Columbia City, IN (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 80 days.

OTHER PUBLICATIONS

International Search Report and Written Opinion of the International Searching Authority for PCT/US2014/012848, dated Apr. 18, 2015, 12 pages. 2015.

(21) Appl. No.: **16/890,051**

(Continued)

(22) Filed: **Jun. 2, 2020**

(65) **Prior Publication Data**

US 2020/0289287 A1 Sep. 17, 2020

**Related U.S. Application Data**

(63) Continuation of application No. 15/985,301, filed on May 21, 2018, now Pat. No. 10,667,925, which is a (Continued)

*Primary Examiner* — Eduardo C Robert  
*Assistant Examiner* — Christina Negrelli-rodriguez  
(74) *Attorney, Agent, or Firm* — Heslin Rothenberg Farley & Mesiti P.C.; Jacquelyn A. Graff, Esq.

(51) **Int. Cl.**

*A61F 2/44* (2006.01)  
*A61F 2/46* (2006.01)  
*A61F 2/30* (2006.01)

(57) **ABSTRACT**

Interbody fusion devices, interbody fusion device systems, insertion tools, methods for assembling an interbody fusion device, and methods a method for inserting a medical device between two vertebral bodies are disclosed. The interbody fusion device includes a body member with a pivot cylinder, a superior member with a pivot channel that is configured to engage the pivot cylinder, and a movement mechanism for moving the superior member relative to the body member. The interbody fusion device systems may include an interbody fusion device and an insertion tool. Also disclosed is a method of assembling an interbody fusion device. In addition, a method for inserting a medical device between two vertebral bodies in a spine is disclosed.

(52) **U.S. Cl.**


CPC ..... *A61F 2/447* (2013.01); *A61F 2/4611* (2013.01); *A61F 2/4603* (2013.01); (Continued)

(58) **Field of Classification Search**

CPC .. *A61F 2/442*; *A61F 2002/443*; *A61F 2/4455*; *A61F 2/447*; *A61F 2/446*; *A61F 2/4465*; *A61F 2/4611*

(Continued)

**20 Claims, 18 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 14/763,311, filed as application No. PCT/US2014/012848 on Jan. 24, 2014, now Pat. No. 9,974,664.

(60) Provisional application No. 61/756,048, filed on Jan. 24, 2013.

(52) **U.S. Cl.**

CPC ..... *A61F 2002/3054* (2013.01); *A61F 2002/3082* (2013.01); *A61F 2002/30471* (2013.01); *A61F 2002/30476* (2013.01); *A61F 2002/30525* (2013.01); *A61F 2002/30579* (2013.01); *A61F 2002/30593* (2013.01); *A61F 2002/30601* (2013.01); *A61F 2002/30772* (2013.01); *A61F 2002/30797* (2013.01); *A61F 2002/30828* (2013.01); *A61F 2002/30904* (2013.01); *A61F 2002/4627* (2013.01); *Y10T 29/25* (2015.01)

(58) **Field of Classification Search**

USPC ..... 606/247–249; 623/17.11–17.16  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,522,899	A	6/1996	Michaelson
5,554,191	A	9/1996	Lahille
5,653,763	A	8/1997	Errico
5,658,335	A	8/1997	Allen
6,176,882	B1	1/2001	Biedermann et al.
6,190,414	B1	2/2001	Young
6,562,074	B2	5/2003	Gerbec
6,685,742	B1	2/2004	Jackson
6,719,796	B2	4/2004	Cohen et al.
6,723,126	B1	4/2004	Berry
6,953,477	B2	10/2005	Berry
6,962,606	B2	11/2005	Michaelson
7,584,682	B2	9/2009	Hsiao
7,655,046	B2	2/2010	Dryer
7,708,779	B2	5/2010	Ede
7,981,157	B2	7/2011	Castleman
8,011,551	B2	9/2011	Marczyk
8,070,813	B2	12/2011	Grotz
8,075,600	B2	12/2011	Schlapfer
8,303,663	B2	11/2012	Jimenez
8,491,657	B2	7/2013	Attia
8,685,095	B2	4/2014	Miller
9,066,813	B2	6/2015	Farris et al.
9,271,777	B2	3/2016	Nichols et al.
10,117,755	B2	11/2018	Emerick
2002/0173817	A1	11/2002	Kletschka et al.
2003/0130739	A1	7/2003	Gerbec
2004/0167626	A1	8/2004	Geremakis
2006/0004447	A1	1/2006	Mastorio et al.
2006/0058877	A1	3/2006	Gutlin
2006/0069436	A1	3/2006	Sutton
2006/0100710	A1	5/2006	Gutlin
2006/0224241	A1	10/2006	Butler et al.
2006/0235389	A1	10/2006	Albert

2006/0293755	A1	12/2006	Lindner
2007/0191954	A1	8/2007	Hansell et al.
2007/0198089	A1	8/2007	Moskowitz et al.
2007/0255407	A1	11/2007	Castleman
2007/0255415	A1	11/2007	Edie et al.
2008/0091211	A1	4/2008	Gately
2008/0147193	A1	6/2008	Matthis et al.
2008/0161933	A1	7/2008	Grotz et al.
2008/0243254	A1	10/2008	Butler
2009/0112325	A1	4/2009	Refai
2009/0118765	A1	5/2009	Mueller et al.
2009/0299478	A1	12/2009	Carls et al.
2010/0057204	A1	3/2010	Kadaba
2010/0168861	A1	7/2010	Yundt
2010/0274299	A1	10/2010	Lawson et al.
2011/0035011	A1	2/2011	Cain
2011/0106172	A1	5/2011	Wallenstein et al.
2011/0130835	A1	6/2011	Ashley
2011/0160861	A1*	6/2011	Jimenez ..... F16H 25/20 623/17.16
2011/0172716	A1	7/2011	Glerum
2011/0245927	A1	10/2011	Farris
2011/0251692	A1	10/2011	McLaughlin
2011/0257751	A1	10/2011	Sherman
2011/0282453	A1	11/2011	Greenhalgh
2012/0029636	A1	2/2012	Ragab
2012/0209386	A1	8/2012	Triplett et al.
2012/0271422	A1	10/2012	Miller
2012/0310350	A1	12/2012	Farris et al.
2014/0288652	A1	9/2014	Boehm
2015/0025634	A1	1/2015	Boehm
2015/0094814	A1	4/2015	Emerick
2015/0351925	A1	12/2015	Emerick
2016/0151172	A1	6/2016	Nichols

FOREIGN PATENT DOCUMENTS

WO	2010033445	3/2010
WO	2010120782	10/2010
WO	2011011609	1/2011
WO	2013155418	10/2013
WO	2013158294	10/2013
WO	2014116891	7/2014

OTHER PUBLICATIONS

Preliminary Report on Patentability for PCT/US2014/012848, dated Aug. 6, 2015, 11 pages. 2015.  
Response to Communication Pursuant to Rules 161(1) and 162 EPC for European Application No. 14742780.1, dated Sep. 1, 2015, 12 pages. 2015.  
Extended European Search Report for European Application No. 14742780.1, dated Dec. 20, 2016, 6 pages. 2016.  
Response to Communication Pursuant to Rules 70(2) and 70a(2) for European Application No. 14742780.1, dated Jul. 19, 2017, 14 pages. 2017.  
Extended European Search Report issued for European Application No. 14798042.9 dated Dec. 20, 2016.  
International Preliminary Report on Patentability issued for PCT Application PCT/US2014/037884 dated Nov. 17, 2015.  
Written Opinion of the International Searching Authority issued for PCT Application PCT/US2014/037884 dated 1C Dec. 10, 2014.

\* cited by examiner

100




FIG. 1

100




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

100




FIG. 9

100




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16






FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25





FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34

## ADJUSTABLE INTERBODY FUSION DEVICE AND METHOD OF USE

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 15/985,301 filed on May 21, 2018, which will issue as U.S. Pat. No. 10,667,925 on Jun. 2, 2020, which is a continuation of U.S. application Ser. No. 14/763,311 filed Jul. 24, 2015, which issued as U.S. Pat. No. 9,974,664 on May 22, 2018, which is a U.S. National Stage Filing under 35 U.S.C. § 371 from International Application No. PCT/US2014/012848 filed on Jan. 24, 2014, and published as WO 2014/116891 on Jul. 31, 2014, which claims priority benefit under 35 U.S.C. § 119(e) of U.S. provisional application No. 61/756,048 filed Jan. 24, 2013, which all applications are incorporated herein by reference in their entireties.

### TECHNICAL FIELD

The present invention relates generally to general surgery, orthopaedic and neurosurgical implants used for insertion within a space between hard tissue structures, and more specifically, but not exclusively, concerns devices implanted between bones to replace resected, fractured or diseased structures and to maintain or reestablish proper spacing between two bones.

### BACKGROUND OF THE INVENTION

Damage or disease that affects the integral structure of a bone or other structures, may lead to neurologic impairment or loss of structural support integrity with possible permanent damage to the surrounding soft tissue and adjacent neurologic, vascular and systemic structures. Maintaining or reestablishing anatomic spacing within a bone structure or other structural tissue is critical to ensuring continued functionality and mobility of the patient and avoidance of long-term serious neurological, vascular or other systemic impairments. Please note that the terms “implant” and “device” may be used interchangeably and have the same meaning herein.

### SUMMARY OF THE INVENTION

Advancement of the state of interbody fusion devices and implants and the surgical management relating to the clinical presentation of damaged tissue structures within the body is believed desirable. Example embodiments of the invention that satisfies the need for improvements to an expandable interbody fusion device used to treat patients suffering from either diseased or damaged disc or other tissue structures includes a superior member coupled to a body member.

The present invention provides in one aspect, an interbody fusion device having a body member including a pivot cylinder, a superior member including a pivot channel, and a movement mechanism for moving the superior member relative to the body member. The pivot cylinder being configured to engage the pivot channel.

The present invention provides in another aspect, an interbody fusion device system. The system including an interbody fusion device and an insertion tool. The interbody fusion device may include a base member with a pivot cylinder, a top member with a hinge channel, and an expansion mechanism for moving the top member relative to

the base member. The pivot cylinder may be configured to engage the hinge channel. The insertion tool may include a handle, an insertion end, at least one tube extending away from the handle and connecting the handle and the insertion end. The tool may also include a first knob configured to couple to the handle. The tool may further include an actuation bar moveable between a first and second position to enable the first knob to engage an adjustment mechanism in the first position and a securement mechanism in the second position.

The present invention also provides in another aspect, a method for assembling an interbody fusion device, including obtaining a bottom member, an expansion mechanism, and a top member. The method may also include inserting the expansion mechanism into the bottom member and securing a first portion of the expansion mechanism in the bottom member. In addition, the method may include coupling the top member to the bottom member. The method may further include aligning the top member with the bottom member and a second portion of the expansion mechanism.

The present invention provides in yet another aspect, a method for inserting a medical device between two vertebral bodies in a spine. The method may include obtaining a medical device. The medical device may include a base member, a top member configured to be coupled to the base member, and a movement mechanism engaging the top member and the base member. The method may also include inserting and coupling a tool into at least two openings within the medical device. The method may further include slidingly inserting the medical device into a space between two vertebral bodies. The method may also include rotating a knob of the tool to move a first end of the top member in a vertical direction relative to the base member.

Further, additional features and advantages are realized through the techniques of the present invention. Other embodiments and aspects of the invention are described in detail herein and are considered a part of the claimed invention.

### BRIEF DESCRIPTION OF THE DRAWINGS

The subject matter which is regarded as the invention is particularly pointed out and distinctly claimed in the claims at the conclusion of the specification. It is emphasized that, in accordance with the standard practice in the industry, various features are not drawn to scale. In fact, the dimensions of the various features may be arbitrarily increased or reduced for clarity of discussion. The foregoing and other objects, features and advantages of the invention are apparent from the following detailed description taken in conjunction with the accompanying drawings in which:

FIG. 1 is a posterior perspective view of one embodiment of an expandable interbody fusion device, in accordance with an aspect of the present invention;

FIG. 2 is an isometric view of the expandable interbody fusion device of FIG. 1 with the moveable member extended, in accordance with an aspect of the present invention;

FIG. 3 is a side view of the expandable interbody fusion device of FIG. 1 with a moveable member extended, in accordance with an aspect of the present invention;

FIG. 4 is an exploded view of the expandable interbody fusion device of FIG. 1, in accordance with an aspect of the present invention;

3

FIG. 5 is a superior perspective view of the expandable interbody fusion device of FIG. 1, showing only the base or bottom member, in accordance with an aspect of the present invention;

FIG. 6 is an inferior perspective view of the expandable interbody fusion device of FIG. 1, showing only the top or superior member, in accordance with an aspect of the present invention;

FIG. 7 is a posterior elevational view of the expandable interbody fusion device of FIG. 1 without the top member, showing the expansion assembly extended and tilted to accommodate the slanted top member, in accordance with an aspect of the present invention;

FIG. 8 is an exploded view of the expansion mechanism of the expandable interbody fusion device of FIG. 1, in accordance with an aspect of the present invention;

FIG. 9 is an isometric view of another expandable interbody fusion device with a transparent base member showing a drive rod and locking mechanism, in accordance with an aspect of the present invention;

FIG. 10 is a partially exploded isometric view of the expandable interbody fusion device of FIG. 9 showing the locking mechanism being inserted into the interbody fusion device, in accordance with an aspect of the present invention;

FIG. 11 is an isometric view of the locking mechanism of FIGS. 9 and 10, in accordance with an aspect of the present invention;

FIG. 12 is a perspective view of the expandable interbody fusion device of FIG. 1 and an expansion tool, in accordance with an aspect of the present invention;

FIG. 13 is a top perspective view of the expansion tool of FIG. 12, in accordance with an aspect of the present invention;

FIG. 14 is a truncated anterior view of the attachment end of the expansion tool of FIG. 12, in accordance with an aspect of the present invention;

FIG. 15 is a perspective view of the expansion tool of FIG. 13 with a transparent outer housing and the knob in a first position, in accordance with an aspect of the present invention;

FIG. 16 is a truncated distal view of the handle end of the expansion tool of FIG. 15, in accordance with an aspect of the present invention;

FIG. 17 is a perspective view of the expansion tool of FIG. 13 with a transparent outer housing and the knob in a second position, in accordance with an aspect of the present invention;

FIG. 18 is truncated distal view of the handle end of the expansion tool of FIG. 17, in accordance with an aspect of the present invention;

FIG. 19 is an exploded view of the tool of FIG. 13, in accordance with an aspect of the present invention;

FIG. 20 is a perspective view of the expandable interbody fusion device of FIG. 1 and another embodiment tool, in accordance with an aspect of the present invention;

FIG. 21 is a perspective view of the tool of FIG. 20 with a transparent outer housing and intermediate housing, in accordance with an aspect of the present invention;

FIG. 22 is an exploded view of the tool of FIG. 20, in accordance with an aspect of the present invention;

FIG. 23 is an exploded view of the handle portion of the tool of FIG. 20, in accordance with an aspect of the present invention;

FIG. 24 is a truncated view of the adjustment end of the adjustment mechanism of the tool of FIG. 20, in accordance with an aspect of the present invention;

4

FIG. 25 is a perspective view of the locking mechanism inserter of the tool of FIG. 20, in accordance with an aspect of the present invention;

FIG. 26 is a truncated view of the locking mechanism inserter of the tool of FIG. 20 and the locking mechanism of FIG. 11, in accordance with an aspect of the present invention;

FIG. 27 is a truncated view of the tool of FIG. 20 with the locking mechanism inserter inserted into the implant of FIG. 1, in accordance with an aspect of the present invention;

FIG. 28 is a perspective view of an implant with the locking mechanism of FIG. 11 inserted into the base member, in accordance with an aspect of the present invention;

FIG. 29 is a posterior perspective view of another embodiment of an expandable interbody fusion device, in accordance with an aspect of the present invention;

FIG. 30 is a side view of the expandable interbody fusion device of FIG. 29 with a moveable member extended, in accordance with an aspect of the present invention;

FIG. 31 is an exploded view of the expandable interbody fusion device of FIG. 29, in accordance with an aspect of the present invention;

FIG. 32 is a superior perspective view of the expandable interbody fusion device of FIG. 29, in accordance with an aspect of the present invention;

FIG. 33 is an inferior perspective view of the expandable interbody fusion device of FIG. 29, in accordance with an aspect of the present invention; and

FIG. 34 depicts an embodiment of a surgical method for maintaining a space between two vertebral bodies in a spine.

#### DETAILED DESCRIPTION

Generally stated, disclosed herein is an interbody fusion device or interbody device that typically includes a top member, a base member, and at least one expansion mechanism. Further, the interbody fusion device may include an extendable/retractable member or expansion assembly and an expansion tool for expansion and contraction of the interbody device. The retractable member extending in a vertical direction. As used herein, the terms “interbody fusion device,” “medical device,” “device,” “interbody device” and “implant” may be used interchangeable as they essentially describe the same type of device. Further, the corresponding expansion tool may also be referred to as “tool” or “instrument” and these terms may be used interchangeably. Finally, described herein is a surgical method for using the interbody fusion device to maintain a space between two vertebral bodies within a patient suffering from a diseased or damaged disc or spinal column.

As depicted in FIGS. 1-8, the general arrangement of an adjustable interbody fusion device 100, in accordance with an aspect of the present invention, includes a base member 110, a top member 130, and an expansion mechanism 140. In this detailed description and the following claims, the words proximal, distal, anterior, posterior, medial, lateral, superior and inferior are defined by their standard usage for indicating a particular part of a bone or implant according to the relative disposition of the natural bone or directional terms of reference. For example, “proximal” means the portion of an implant nearest the torso, while “distal” indicates the portion of the implant farthest from the torso. As for directional terms, “anterior” is a direction towards the front side of the body, “posterior” means a direction towards the back side of the body, “medial” means towards the midline of the body, “lateral” is a direction towards the sides

or away from the midline of the body, “superior” means a direction above and “inferior” means a direction below another object or structure.

It is shown in FIGS. 1-3, the example of the adjustable interbody fusion device **100**. The device **100** as seen in FIG. **1** may have, for example, a generally rectangular geometry with various configured long sides to facilitate insertion and bone coverage. Although it would be understood by one skilled in the art that other outside configurations can be used. The implant **100** may likely include at least one moveable top or superior member **130** and a base, body, or bottom member **110**. The top member **130** may be detachably coupled to the base member **110**.

As seen in FIGS. **1** and **2**, base member **110** may have at least one through hole or central opening **102** for insertion of bone graft material disposed on the inferior and superior bone contacting surfaces **104**. The opening **102** typically extends through both bone contacting surfaces **104** of the base and top members **110**, **130** and into the inner cavity of the assembled device **100**. The size and configuration of the opening **102** allow the surgeon to place bone graft material inside the implant **100** to achieve a continuous fusion between the inferior and superior vertebral bodies.

As shown in FIG. **1**, the superior and inferior bone contacting surfaces **104** may be generally parallel to each other. However, the expansion mechanism or movement mechanism **140** (these names may be used interchangeably), (see FIG. **8**), will allow the user to angle one end of the bone contacting surface **104** of the top member **130** relative to the bone contacting surface **104** of the base member **110** as seen in FIGS. **2** and **3**, wherein the far end is fully expanded and the near end remains retracted. FIGS. **1-4** show the bone contacting surfaces **104** to have teeth-like or tine structures projecting away from the superior and inferior surfaces. One skilled in the art would recognize that other surface treatments may be applied to the bone contacting surfaces **104** to enhance fixation with the opposing bone surface. Although not shown, it is understood by one skilled in the art that modular bone contacting surfaces, caps or plates may be used to provide for varying types of bone contacting surfaces and structures, including, but not limited to sharp tines, porous coatings, biomaterial or ingrowth surfaces, and ridge structures. It is also understood that the bone contacting surfaces **104** may be coated with nano-surfacing, bioactive or bone/tissue ingrowth coatings.

As seen in FIGS. **4** and **5**, the base member **110** may also include a tool alignment channel **112** extending along a side of the base member **110** from the posterior end, a tool attachment opening **114** on the posterior end of the base member **110**, and an adjustment opening **116** on the posterior end of the base member **110** and which may be opposite the tool alignment channel **112**, as seen in FIGS. **1** and **2**. The base member **110** may also include a hole or lumen **118** near the proximal end of the base member **110** to house an expansion mechanism **140** (see FIG. **8**), which will be discussed in greater detail below. The hole **118** may have a smooth vertical wall to facilitate insertion and unrestricted rotation of a cylindrical gear **150** of the expansion mechanism **140** (see FIG. **8**). The hole **118** of the base member **110** may also include an internal circumferential shoulder **120** and a notch **121**. In addition, the base member **110** may include a channel **122** extending from the adjustment opening **116** interiorly along a lateral side of the base member **110** to engage the hole **118**. The base member **110** may also include a pivot cylinder **124**, an alignment protrusion **126**, and an opening **128**.

As seen in FIGS. **4** and **6**, the top or superior member **130** also includes an undersurface **132** with a relief area **134** that is adjacent to the central opening **102**. The central opening **102** may be configured to permit the surgeon to insert bone graft material into the inner cavity of the implant **100** prior to implantation. The relief area **134** may be substantially planar and the relief area **134** may be aligned with the hole **118** in the base member **110**. The relief area **134** is relatively rectangular with the long axis of the rectangle extending along the longitudinal axis of the top member **130**. The relief area **134** is configured to mate with a correspondingly shaped load head **170** of the expansion mechanism **140** (see FIG. **8**). The top member **130** may also include a hinge channel or pivot channel **136** for mating with the pivot cylinder **124** of the base member **110** to enable the implant **100** to extend on the proximal end while remaining closed on the distal end. The pivot cylinder **124** and hinge channel **136** allow the top member **130** to pivot or rotate around the outer diameter of the pivot cylinder **124** of the base member **110** when expansion assembly **142** (see FIG. **8**) is extended or retracted causing the top member **130** to tilt or slant relative to the base member **110**. In addition, the top member **130** may include an opening **138** for mating with the alignment protrusion **126** of the base member **110**.

Referring now to FIG. **4** with continued reference to FIGS. **5** and **6**, an exploded view of all of the components that comprise the implant **100** is shown. As shown in FIG. **8**, the expansion mechanism **140** of the implant **100** includes an expansion assembly **142** and a drive rod **180**. The expansion assembly **142** may include a cylindrical gear **150**, a support means **158**, a threaded rod **160**, and a load head **170**. The vertical cylinder or cylindrical gear **150** (these names may be used interchangeably) may nest or be suspended within the hole **118** of the base member **110**. The cylindrical gear **150** may include external substantially vertical depressions or circumferential serial depressions **152** positioned on the outer surface of the gear **150** which extend around the entire circumference. For example purposes, the gear **150** may have a smooth surface, above and below the substantially vertical depressions **152**. Positioning the circumferential serial depressions **152** around the central portion of the gear **150** may maximize strength and improve trackability when the cylindrical gear **150** engages the drive rod **180**. The circumferential serial depressions **152** may also include uniquely oriented thread patterns. In addition, the gear **150** may include internal threads **154** on the interior surface of the gear **150**.

As shown in FIG. **7**, the support means **158** may sit on the shoulder **120** (see FIG. **5**) of the base member **110** and function to maintain the expansion assembly **142** (see FIG. **8**) in a vertical orientation relative to the base member **110** and aligned with the hole **118**. The support means **158** may also be used adjacent to the gear **150** and threaded rod **160** and may hold the gear **150** in the hole **118** (see FIG. **5**). The support means may, for example, be in the form of a ring, snap ring, washer or other similar type of structure that will secure the expansion assembly **142** (see FIG. **8**) to the base member **110**. The shoulder **120** may also operate as a bearing surface against which the support means **158** contacts to facilitate the rotation of the expansion assembly **142** when actuated. As shown in FIG. **5**, the notch **121** in the hole **118** of the base member **110** may enable the support means **158** to be inserted into the shoulder **120**.

As shown in FIGS. **4**, **7** and **8**, the threaded rod **160** may include a pivot cylinder **162** located on the top or superior end of the threaded rod **160**. The threaded rod **160** may also include external threads **164** extending along its length. The

external threads **164** may be configured to match the internal threads **154** of the gear **150**. The pivot cylinder **162** of the threaded rod **160** may be inserted into a distal channel **172** of the load head **170**. These constructs allow the load head **170** to pivot, slide, or rotate around the outer diameter of the pivot cylinder **162** when the threaded rod **160** is extended causing the top member **130** to tilt or slant. A tilted or slanted load head **170** is shown in FIGS. **3** and **7**. The load head **170** may also include a superior head surface **174**. The superior head surface **174** may be shaped to match with the corresponding relief area **134** (see FIG. **6**) on the undersurface **132** of the top member **130**. The superior head surface **174** is configured to slide along the relief **134** of the undersurface **132**, if necessary, to allow for the expansion assembly **142** to lengthen to create the angled relationship of the top member **130** relative to the base member **110**. The relief **134** in the undersurface **132** and the correspondingly shaped load head **170** facilitates the angulation process and the load transfer between the top member **130** and the base member **110** while avoiding potential binding of the expansion assembly **142** during the expansion and retraction process.

The drive rod **180** of the expansion mechanism **140** (see FIG. **8**) may be inserted into the adjustment opening **116** and sit in the channel **122** of the base member **110**, as shown in FIGS. **4** and **7**. The drive rod **180** may be comprised of a cylindrical shaft **182** with a worm gear **184** at one end of the cylindrical shaft **182**. The cylindrical shaft **182** may also have an opening **186** at a second end of the cylindrical shaft **182** opposite the worm gear **184** for coupling with a tool **200**. In addition, the cylindrical shaft **182** may include a channel **188** for mating with a pin **190** to secure the drive rod **180** in the base member **110** to enable adjustment of the top member **130** without the drive rod **180** backing out of the implant **100**. The pin **190** may also prevent the drive rod **180** from backing out of the implant **100** after implantation into the patient's spine. By off-centering the adjustment opening **116** and the channel **122** from the longitudinal axis of the device **100**, the worm gear **184** of the drive rod **180**, which is inserted into the channel **122**, intersects with the hole **118** of the base member **110**. The worm gear **184** may be configured to engage with the gear **150** of the expansion assembly **142** which sits in the hole **118** of the base member **110**. FIG. **7** shows the assembled implant **100** without the top member **130** with the drive rod **180** positioned and extending through the length of the base member **110**.

When the implant **100** is inserted into a patient using tool **200**, as shown in FIG. **12**, the tool **200** engages the alignment channel **112**, the attachment opening **114** and the adjustment opening **116**, as described in greater detail below. Once the tool **200** is inserted into the patient between two vertebrae, the drive rod **180** with the gear **150** function to mirror the rotational movement exerted by the tool **200**, described in greater detail below, and translate the movement to the gear **150**. The expansion mechanism **140** functions to convert rotation movement of the gear **150** into linear or translational movement of the load head **170** positioned at the superior end of the threaded rod **160**. Rotation of the gear **150** will result in a travel distance of the threaded rod **160** when the expansion mechanism **140** is actuated by the tool **200**. As the gear **150** is coupled to the drive rod **180**, the coupled gear **150** will turn as the drive rod **180** is rotated, thus avoiding the need for the tool **200** to pass through the entire length of the channel **122** to engage the gear **150** on the far end of the implant **100**.

With continued reference to FIGS. **1-8**, as the drive rod **180** is rotated by the tool **200**, the teeth **178** of the worm gear **184** positioned on the end of the drive rod **180** are configured

to mate with the substantially vertical depressions **152** of the gear **150**. As described above, the expansion assembly **142** acts to convert rotational movement of the gear **150** into translational movement of the threaded rod **160**. This is achieved by allowing free rotational movement of the gear **150** while restricting the rotation of the threaded rod **160**. By restricting the rotation of the threaded rod **160**, the rod translates in either an upward or downward direction relative to the gear **150** depending upon whether the threads (external and internal) **154**, **164** are oriented in a right-handed or left-handed direction. As discussed above, when the threaded rod **160** moves, the load head **170** contacts the relief area **134** of the undersurface **130** of the top member **130** to either move it away from or towards the base member **110**. In other words, the height of the implant **100** either increases or decreases or the bone contacting surface **104** will be angled relative to the base member **110** depending on the rotational direction of the tool **200**.

Referring now to FIGS. **9-11**, an alternative embodiment adjustable interbody fusion device **100** including a locking mechanism **192** is shown. As shown in FIG. **11**, the locking mechanism **192** may include a shaft **194** extending out from a head **196**. The head **196** may include a plurality of protrusions **198** for engaging the lip **129** (see FIG. **10**) in the adjustment opening **116** of the base member **110** to secure the locking mechanism **192** in the base member **110**. The head **196** may also include an opening **199** for engaging the insertion tool **200** or a similar tool. The shaft **194** of the locking mechanism **192** may have a shape which corresponds to the shape of the tool opening **186** of the drive rod **180**, for example, the shape may be a hexagon, square, or other multi-lobed configuration allowing the shaft **194** of the locking mechanism **192** to fit securely within the opening **186** of the drive rod **180**. Similarly, the head **196** may have a shape which corresponds to the shape of the adjustment opening **116**, for example, the shape may be a circle, hexagon, square, or other multi-lobed configuration allowing the locking mechanism **192** to securely fit within the adjustment opening **116** of the base member **110** to secure the locking mechanism **192** in the implant **100** to maintain a desired expansion or retraction. Other shapes for the shaft **194** and the head **196** of the locking mechanism **192** are also contemplated. The locking mechanism **192** may be, for example, made of a rigid material or a deformable material. If the locking mechanism **192** is made of a deformable material it may be made slightly larger than the opening **186** in the drive rod **180** and/or the adjustment opening **116** in the base member **110**, such that once it is inserted the larger size locks the drive rod **180** in the desired position.

Referring now to FIGS. **12-19**, a tool **200** for inserting the implant **100** into a patient is shown. The tool **200** and the implant **100** may form an interbody fusion device system, as shown in FIG. **12**. The tool **200** is designed to engage the expansion mechanism **140** (see FIG. **8**). The insertion end **202** of the tool **200** may be configured with a housing **204** including a protrusion or alignment protrusion **206** shaped to correspond to the alignment channel **112** in the base member **110**. The insertion end **202** may also include an adjustment mechanism **208** and a securement mechanism **210** which protrude out of the distal end of the housing **204**. The adjustment mechanism **208** may be configured, for example, to have a hex male head, square, or other multi-lobed configuration that will allow for the user to rotate the knob **224** of the tool **200** and cause the expansion mechanism **140** to rotate. Opposite the insertion end **202**, the tool **200** has a handle **212** which may be connected to the housing **204** of the insertion end **202** by a tube **214**. The tube **214** may be

coupled to the housing 204 on the distal end and secured to the handle 212 at the proximal end by fasteners 248, for example, screws. The tube 214 may house the securement mechanism 210 which may extend from the handle 212 to the housing 204 inside the tube 214. In addition, the adjust-  
 5 ment mechanism 208 may also extend between the housing 204 at the insertion end 202 and the handle 212, relatively parallel to and outside the tube 214.

As seen in FIGS. 15-18, the handle 212 of the tool 200 may also include a first opening 216 and a second opening 218 along the longitudinal axis of the handle 212. In addition, the handle 212 of tool 200 may include a third opening 220 extending perpendicular to and engaging the first and second openings 216, 218. A fourth opening 222 may also be in the handle 212 and may extend into the handle 212 from the proximal end of the handle 212 into the third opening 220 and may run parallel with the first and second openings 216, 218. The handle 212 may also include a knob 224 which may be inserted into both the first and second openings 216, 218 at a proximal end of the handle 212, an actuation bar 226 for insertion into the third opening 220, and a spring plunger 228 for insertion into the fourth opening 222. The knob 224 may include a head 236 with a shaft 238 extending out away from the inferior surface of the head 236. The shaft 238 of the knob 224 may also include a channel 240 for mating with the actuation bar 226 to secure the knob 224 in the inserted opening 216, 218.

As seen in FIGS. 16 and 18, the adjustment mechanism 208 may pass into the first opening 216 from the distal end of the handle 212 enabling engagement with the distal end of the shaft 238 of the knob 224 when inserted into the first opening 216 from the proximal end of the handle 212. A tool engagement end 242 (see FIGS. 15-16) of the adjustment mechanism 208 couples with the distal end of the shaft 238 to enable rotation of the adjustment mechanism 208. The securement mechanism 210 may pass into the second opening 218 from the distal end of the handle 212 enabling engagement with the distal end of the shaft 238 of the knob 224 when inserted into the second opening 218 from the proximal end of the handle 212. In addition, the securement mechanism 210 may include a spring mechanism 246 inserted over the proximal end of the securement mechanism 210 to spring load the securement mechanism 210. A tool engagement end 244 of the securement mechanism 210 couples with the distal end of the shaft 238 to enable rotation of the securement mechanism 210. The tool engagement ends 242, 244 may have, for example, a hex male head, square, or other multi-lobed configuration to enable rotation of the adjustment mechanism 208 or securement mechanism 210, respectively. The shaft 238 of the knob 224 when inserted into either the first or second openings 216, 218 passes through a hole 230 in the actuation bar 226 before engaging the adjustment mechanism 208 or securement mechanism 210, respectively. The channel 240 in the shaft 238 of the knob 224 engages the hole 230 in the actuation bar 226 to lock the knob 224 in the first or second opening 216, 218.

During use a surgeon may insert the tool 200 into the implant 100 by aligning the protrusion 206 of the insertion end 202 of the tool 200 with the alignment channel 112 of the implant 100. Once the tool 200 and implant 100 are aligned and the actuation bar 226 is in an unlocked position the shaft 238 of the knob 224 may be inserted into the second opening 218 and coupled to the tool engagement end 244 of the securement mechanism 210. After the shaft 238 has coupled to the tool engagement end 244 of the securement mechanism 210, the actuation bar 226 may be moved to the

first locked position, as shown in FIGS. 12, 15 and 16, and the actuation bar 226 engages the channel 240 in the shaft 238 of the knob 224, as shown in FIGS. 15, 16 and 19. As the actuation bar 226 is moved to lock the knob 224 into the second opening 218, the spring plunger 228 in the fourth opening 222 may engage a first channel 232 of the actuation bar 226 to lock the knob 224 in place in the handle 212. The head 236 of the knob 224 of the tool 200 may then be rotated which in turn will rotate the securement mechanism 210. As the knob 224 rotates the securement mechanism 210, the distal end of the securement mechanism 210 engages the threads 108 of the attachment opening 114 of the implant 100. The securement mechanism 210 of the tool will couple with the attachment opening 114 of the implant 100 to secure the implant 100 to the tool 200 for insertion into a patient. In addition, as the securement mechanism 210 engages the attachment opening 114 of the implant 100, the adjustment mechanism 208 of the tool will engage the opening 186 in the drive rod 180 of the implant 100.

Once the implant 100 is secured to the tool 200, the physician may remove the knob 224 from the second opening 218 of the handle 212 by moving the actuation bar 226 to the unlocked position. As the actuation bar 226 is moved from the first locked position, shown in FIGS. 12, 15 and 16, to the unlocked position the spring plunger 228 disengages the first channel 232. With the actuation bar 226 in an unlocked position the shaft 238 of the knob 224 may be inserted into the proximal end of the first opening 216 in the handle 212 to engage the tool engagement end 242 of the adjustment mechanism 208. Once the shaft 238 has coupled to the tool engagement end 242 of the adjustment mechanism 208, the actuation bar 226 may be moved to the second locked position, shown in FIGS. 17 and 18. As the actuation bar 226 is moved to the second locked position, the spring plunger 228 may engage a second channel 234 of the actuation bar 226 to lock the knob 224 into the first opening 216 in the handle 212. After the actuation bar 226 of the handle 212 is in the second locked position, the implant 100 may then be inserted into the desired position in the patient. The physician may then rotate the head 236 of the knob 224 which in turn will rotate the distal end of the adjustment mechanism 208. As the head 236 of the knob 224 is rotated, the adjustment mechanism 208, which is coupled to the opening 186 in the drive rod 180, engages the expansion mechanism 140 and expands the far end of the implant 100 to angle the top member 130 relative to the base member 110. The cogs or teeth 178 of the worm gear 184 on the end of the drive rod 180 are sized to mate with the corresponding serial depressions 152 of the gear 150 to facilitate rotation of the gear 150 when the knob 224 of the tool 200 is turned. Once the desired expansion of the implant 100 is achieved, the tool 200 may then be removed from the patient.

In the alternative embodiment shown in FIGS. 9-11, prior to removing the tool 200, the locking mechanism 192 may be inserted into the implant 100 to secure the top member 130 of the implant 100 in the desired expansion and/or retraction relative to the base member 110. The locking mechanism 192 may be inserted into the opening 186 in the drive rod 180 by first securing the insertion tool 200 or a similar tool to the opening 199 of the locking mechanism 192. As the locking mechanism 192 is inserted into the base member 110 and the drive rod 180, the shaft 194 of the locking mechanism 192 fits securely within the opening 186 of the drive rod 180. In addition, the plurality of protrusions 198 on the head 196 may engage the lip 129 in the adjustment opening 116 of the base member 110. In addition, the drive rod 180 may be recessed within the base

member 110 to provide a cavity for insertion of the locking mechanism 192 into the base member 110, such that when the locking mechanism 192 is inserted into the base member 110 of the implant 100 it is flush with the exterior surface of the base member 110.

The tool 200 may be removed from the patient by removing the knob 224 from the first opening 216 of the handle 212. The knob 224 may be removed from the first opening 216 by moving the actuation bar 226 to the unlocked position to disengage the actuation bar 226 from the knob channel 240 and the spring plunger 228 from the first channel 232 in the actuation bar 226. Once the actuation bar 226 is in an unlocked position the shaft 238 of the knob 224 may be removed from the first opening 216 and inserted into the second opening 218 to engage the securement mechanism 210. After inserting the shaft 238 of the knob 224 in the second opening 218, the actuation bar 226 may be moved to the first locked position, as shown in FIGS. 15 and 16 to secure the knob shaft 238 in the second opening 218 of the handle 212. In the first locked position, the spring plunger 228 may again engage the first channel 232 to secure the knob 224 in the handle 212. The head 236 of the knob 224 may then be rotated to remove the distal end of the securement mechanism 210 from the attachment opening 114. As the securement mechanism 210 rotates it disengages the threads 108 of the attachment opening 114 and the protrusion 206 and adjustment mechanism 208 of the insertion end 202 of the tool 200 slide out of the alignment channel 112 and adjustment opening 116, respectively. It is also contemplated that the above method for inserting the implant 100 using tool 200 may be performed in alternative orders.

Referring now to FIGS. 20-28, an alternative embodiment tool 300 for inserting the implant 100 into a patient is shown. The tool 300 and the implant 100 may form an interbody fusion device system as shown in FIG. 20. The tool 300 is designed to engage the expansion mechanism 140 (see FIG. 8). The insertion end 302 of the tool 300 may be configured with a housing 304 including a protrusion 306 shaped to correspond to the alignment channel 112 in the base member 110. The insertion end 302 may also include an opening 308 for adjustment mechanism 342 or locking mechanism inserter 344 and a securement mechanism 310 which protrude out of the distal end of the housing 304. The adjustment mechanism 342 may be configured, for example, to have a hex male head, square, or other multi-lobed configuration that will allow for the user to rotate the knob 324 of the tool 300 and cause the expansion mechanism 140 to rotate. Opposite the insertion end 302, the tool 300 has a handle 312 which may be connected to the housing 304 of the insertion end 302 by a tube 314. The tube 314 may be coupled to the housing 304 on the distal end and secured to the handle 312 at the proximal end. The tube 314 may house the securement mechanism 310 which may extend from the handle 312 to the housing 304 inside the tube 314. In addition, a second tube 315 may extend between the housing 304 at the insertion end 302 and the handle 312, relatively parallel to and outside the tube 314, to house the adjustment mechanism 342 or locking mechanism inserter 344.

As seen in FIGS. 21-23, the handle 312 of the tool 300 may also include a first opening 316 along the longitudinal axis of the handle 312. The handle 312 may also include a second opening 318 which may extend into the handle 312 from the proximal end of the handle 312 and run parallel with the first opening 316. In addition, the handle 312 of tool 300 may include a third opening 320 extending perpendicular to and engaging the first opening 316. The handle 312

may also include a knob 324 for attachment to a shaft 336, 338 of the adjustment mechanism 342 or locking mechanism inserter 344, respectively, which may be inserted into the first opening 316 at a proximal end of the handle 312, a gear shaft 328 for insertion into the second opening 318, and an actuation bar 326 for insertion into the third opening 320. The knob 324 may be attached to a shaft 336, 338 of the adjustment mechanism 342 or locking mechanism 344, respectively, and the shaft 336, 338 may extend out away from the inferior surface of the knob 324 when inserted. The shafts 336, 338 of the adjustment mechanism 342 or locking mechanism inserter 344 may also include a channel 340 for mating with the actuation bar 326 to secure the adjustment mechanism 342 or locking mechanism inserter 344 in the opening 316. The shafts 336, 338 of the adjustment mechanism 342 or locking mechanism inserter 344 when inserted into the first openings 316 pass through a hole 330 in the actuation bar 326. The channel 340 in the shafts 336, 338 of the adjustment mechanism 342 or locking mechanism inserter 344 engage the hole 330 in the actuation bar 326 to lock the adjustment mechanism 342 or locking mechanism inserter 344 in the first opening 316. The handle 312 may further include a fourth opening 322 in the distal end of the handle 312. The fourth opening 322 may allow the adjustment mechanism 342 or locking mechanism inserter 344 to pass out of the handle at the insertion end 302 of the tool 300. In addition, the fourth opening 322 may allow for the securement mechanism 310 to be attached to the distal end of the handle 312.

As shown in FIGS. 21-23, the handle 312 may also include an intermediate housing 348 that mates with the fourth opening 322 to secure the securement mechanism to the handle 312. A spring mechanism 346 may be inserted into the fourth opening 322 of the handle 312 to hold a first gear 350 inside of a second knob 352. The first gear 350 mates with the end of the securement mechanism 310 to enable rotation of the securement mechanism 310 by rotating the second knob 352 which in turn rotates the first gear 350 and the coupled securement mechanism 310. The rotation of the second knob 352 allows a physician to rotate the engagement end of the securement mechanism 310 to attach the implant 100 to the tool 300.

The proximal end of the handle 312 may also include a second gear 354 that sits in the first opening 316 and a third gear 356 that sits in the second opening 318, as shown in FIGS. 22 and 23. The first opening 318 may engage the second opening 318 to enable the gear teeth on the second and third gears 354, 356 to overlap such that rotation of the second gear 354 causes rotation of the third gear 356 and alternatively, such that rotation of the third gear 356 causes rotation of the second gear 354. The second opening 318 may also include a longitudinal opening enabling the gear teeth of the second gear 356 to engage the interior surface of the third knob 358, which engages the proximal end of the handle 312. The handle 312 may further include an end member 360 for mating with the third knob 358. The end member 360 may be secured to the third knob 358 using fasteners, not shown, such as screws. A gear shaft 328 may be inserted into handle 312 through an opening 362 in the end member 360 to engage a passage through the third gear 356.

As seen in FIGS. 21-24, the adjustment mechanism 342 may pass into the first opening 316 from the proximal end of the handle 312, through the handle 312 and the second tube 315 and extend out of the opening 308 in the housing 304 enabling engagement with the implant 100. The proximal end of the adjustment mechanism 342 may extend

through a passage in the second gear 354 and into the knob 324. The adjustment mechanism 342 may be coupled to the second gear 354 and the knob 324 enabling rotation of the proximal end of the adjustment mechanism 342 by the knob 324 and the third knob 358. The adjustment mechanism 352 may also pass through an intermediate housing 348 as it passes through the fourth opening 322 in the distal end of the handle 312 and into the second tube 315. When the adjustment mechanism 342 is in place within the tool 300, the adjustment end 364 extends out of the opening 308 in the housing 304 to enable engagement with the adjustment opening 116 in the implant 100. As shown in FIG. 24, the adjustment end 364 may have, for example, a hex male head, square, or other multi-lobed configuration to enable rotation of the drive rod 180 with a correspondingly shaped engagement end. Once the implant 100 is in a desired expansion or retraction, the physician may remove the adjustment mechanism 342 and insert the locking mechanism inserter 344 to lock the implant 100 in the desired expansion or retraction. The locking mechanism inserter 344, shown in FIGS. 25 and 26, may include an engagement end 366 with a shape corresponding to the opening 199 in the locking mechanism 192. The engagement end 366 of the tool 300 may be inserted into the opening 199 in the locking mechanism 192 for insertion of the locking mechanism 192 into the implant 100. During surgery, the locking mechanism inserter 344 with the locking mechanism 192 attached to the engagement end 366 will be inserted into tool 300 through the opening 316 in the handle 312, through the intermediate housing 348, through the second tube 315, and out of the opening 308 in the housing 304 of the tool 300 to engage the implant 100.

As shown in FIGS. 27 and 28, the locking mechanism 192 may be inserted into the base member 110 and drive rod 180 using the locking mechanism inserter 344 (see FIG. 25-26) of the tool 300 to secure the implant 100 in the desired expansion or retraction. The drive rod 180 may be recessed within the adjustment opening 116 in the base member 110 of the implant 100 when the locking mechanism 192 is used. The tool 300 may be used in place of the tool 200 in the above surgical method to insert the implant 100 into a patient. If tool 300 was used in the above described method, the method may also include the steps of removing the adjustment mechanism 342 after expansion or retraction and inserting the locking mechanism inserter 344 to lock the implant 100 in the desired expansion or retraction using the locking mechanism 192.

As shown in FIG. 34 and described in greater detail above, the method may include obtaining a medical device 500, inserting and coupling a tool to the medical device 510, slidably inserting the medical device into a space between two vertebral bodies 520, rotating a knob of the tool to move a first end of a top member in a vertical direction relative to a body member 530, and removing the tool from the medical device 540.

Another adjustable interbody fusion device 400 is shown in FIGS. 29-33. The device 400, as seen in FIGS. 29-30, may include at least one moveable top or superior member 430 and a base or bottom member 410. The top member 430 may be detachably coupled to the base member 410. The base member 410 and top member 430 may have at least one through hole or central opening 102. The base member 410 may include a bone contacting surface 104 and the top member 430 may also include a bone contacting surface 104. The at least one through hole or central opening 102 and the bone contacting surface 104 may be of the types described in greater detail above with reference to device 100.

As shown in FIGS. 29, 31 and 32, the base member 410 may include a tool alignment channel 112, a tool attachment opening 114, and an adjustment opening 116, as described above in greater detail with reference to device 100. The base member 410 may also include a hole or lumen 118 configured to receive the expansion mechanism 140 (see FIG. 8), as described in greater detail above with reference to device 100. The base member 410 may further include an internal circumferential shoulder 120, a notch 121, a channel 122, and an opening 128, as described in greater detail above with reference to device 100. The base member 410 may also include at least two pivot cylinders 412 each with at least one opening 414 and at least one hinge channel 416.

The top or superior member 430 is shown in greater detail in FIG. 33 and may include an undersurface 132 with a relief area 134 as described above in greater detail with respect to device 100. The top member 430 may also include at least two hinge channels 432 and at least one pivot cylinder 434 with at least one opening 436. The at least two hinge channels 432 of the top member 430 may be configured to mate with the at least two pivot cylinders 412 of the base member 410 (see FIG. 32). Likewise, the at least one pivot cylinder 434 may be configured to mate with the at least one hinge channel 416 of the base member 410 (see FIG. 32). The openings 414, 436 are configured to align and receive a pin 420 when the top member 430 is placed on the base member 410 to enable the implant 400 to pivot on one end such that the implant 400 extends on a first end while remaining closed on a second end. The pivot cylinders 412, 434, hinge channels 416, 432, and pin 420 allow the top member 430 to pivot or rotate around the outer diameters of the pivot cylinders 412, 434 when the expansion assembly 142 (see FIG. 8) is extended or retracted causing the top member 430 to tilt or slant relative to the base member 410.

An exploded view of the implant 400 is shown in FIG. 31. The implant 400 includes the expansion mechanism 140 as shown in FIG. 8. As described in greater detail above with reference to device 100, the expansion mechanism 140 may include an expansion assembly 142 and a drive rod 180. The expansion assembly 142 may include the cylindrical gear 150, the support means 158, the threaded rod 160, and the load head 170 as described above with reference to device 100.

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms "a", "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms "comprise" (and any form of comprise, such as "comprises" and "comprising"), "have" (and any form of have, such as "has", and "having"), "include" (and any form of include, such as "includes" and "including"), and "contain" (and any form of contain, such as "contains" and "containing") are open-ended linking verbs. As a result, a method or device that "comprises," "has," "includes," or "contains" one or more steps or elements possesses those one or more steps or elements, but is not limited to possessing only those one or more steps or elements. Likewise, a step of a method or an element of a device that "comprises," "has," "includes," or "contains" one or more features possesses those one or more features, but is not limited to possessing only those one or more features. Furthermore, a device or structure that is configured in a certain way is configured in at least that way, but may also be configured in ways that are not listed.

Although the example embodiments have been depicted and described in detail herein, it will be apparent to those

## 15

skilled in the relevant art that various modifications, additions and substitutions can be made without departing from its essence and therefore these are to be considered to be within the scope of the following claims.

What is claimed:

1. An expansion mechanism for moving a first member relative to a second member, the expansion mechanism comprising:

a cylindrical gear sized to rest within an opening, the opening positioned within the first member;

a threaded rod having a pivot cylinder on a first end, wherein the threaded rod comprises a plurality of external threads extending along the length of the threaded rod;

a load head having a top surface and a bottom surface, wherein the load head is configured to couple and move relative to the threaded rod; and

a support member, the support member being sized to be partially positioned within the opening in the first member, and wherein the support member is at least one of a ring, a snap ring, a washer and an o-ring.

2. The expansion mechanism of claim 1, wherein the top surface of the load head is planar and is configured to engage a relief area disposed within the second member.

3. The expansion mechanism of claim 2, wherein the bottom surface of the load head comprises a distal channel configured to moveably engage the pivot cylinder of the threaded rod.

4. The expansion mechanism of claim 1, wherein the support member is positioned adjacent to the cylindrical gear.

5. The expansion mechanism of claim 1, wherein the cylindrical gear further comprises a plurality of serial depressions disposed on an outer surface of the cylindrical gear.

6. The expansion mechanism of claim 5, wherein the plurality of serial depressions extend around the circumference of the cylindrical gear and are oriented in a vertical direction.

7. The expansion mechanism of claim 5, wherein the plurality of serial depressions have a length that is less than the length of the cylindrical gear.

8. The expansion mechanism of claim 5, wherein the outer surface further comprises a first circumferential smooth surface and a second circumferential smooth surface.

9. The expansion mechanism of claim 8, wherein the plurality of serial depressions are positioned intermediate the first circumferential smooth surface and the second circumferential smooth surface.

10. The expansion mechanism of claim 1, wherein the cylindrical gear further comprises an internal central bore opening extending from a first end to a second end of the cylindrical gear, wherein the internal central bore opening is threaded.

11. The expansion mechanism of claim 10, wherein the threads of the internal central bore opening of the cylindrical gear mate with the plurality of external threads of the threaded rod when the expansion mechanism is assembled.

12. The expansion mechanism of claim 11, wherein the threads of the internal central bore opening of the cylindrical gear are right-handed threads and the plurality of external threads of the threaded rod are left-handed threads.

13. The expansion mechanism of claim 11, wherein the threads of the internal central bore opening of the cylindrical gear are left-handed threads and the plurality of external threads of the threaded rod are right-handed threads.

## 16

14. The expansion mechanism of claim 1, further comprising a drive rod, wherein the drive rod is configured for insertion into an adjustment opening of the first member to engage the cylindrical gear.

15. The expansion mechanism of claim 14, wherein the drive rod comprises:

a cylindrical shaft with a first end and a second end;

a worm gear at the first end;

a tool opening at the second end; and

a channel in the cylindrical shaft positioned between the first end and the second end.

16. The expansion mechanism of claim 15, wherein the channel is circumferentially positioned around the cylindrical shaft.

17. The expansion mechanism of claim 15, wherein the worm gear is sized to mate with a plurality of serial depressions disposed on an outer surface of the cylindrical gear.

18. The expansion mechanism of claim 15, further comprising a pin, wherein the pin is fixed to an inner surface of the first member, wherein the pin is sized to articulate with the channel of the cylindrical shaft to maintain the position of the cylindrical shaft of the drive rod within the first member when rotated during the operation of the expansion mechanism.

19. An expansion mechanism for moving a first member relative to a second member, the expansion mechanism comprising:

a cylindrical gear sized to rest within an opening, the opening positioned within the first member;

a threaded rod having a pivot cylinder on a first end, wherein the threaded rod comprises a plurality of external threads extending along the length of the threaded rod;

a load head having a top surface and a bottom surface, wherein the load head is configured to couple and move relative to the threaded rod;

a drive rod, wherein the drive rod is configured for insertion into an adjustment opening of the first member to engage the cylindrical gear, wherein the drive rod comprises:

a cylindrical shaft with a first end and a second end;

worm gear at the first end;

a tool opening at the second end; and

a channel in the cylindrical shaft positioned between the first end and the second end; and

a locking mechanism, wherein the locking mechanism is configured to engage an adjustment opening in the first member and the tool opening in the drive rod, the locking mechanism comprising:

a head including an opening for engaging an insertion tool and a plurality of protrusions configured to engage the adjustment opening; and

a shaft extending away from the head and configured to engage the tool opening in the drive rod.

20. A method of using an interbody fusion device, comprising:

obtaining an interbody fusion device, wherein the interbody fusion device comprises

a base member comprising a first end, a second end, a first bone contacting surface, a first inner surface opposite the first bone contacting surface, and at least one projection extending from the first inner surface along a first end portion of the base member forming a pivot cylinder, wherein the pivot cylinder is fixed to the first inner surface;

17

a top member comprising a first end, a second end, a second bone contacting surface, and a second inner surface opposite the second bone contacting surface including a hinge channel extending along a first end portion of the top member, wherein the pivot cylinder is configured to engage the hinge channel to enable the hinge channel to pivot on and about the pivot cylinder; and  
an expansion mechanism for moving the top member relative to the base member to cause the top member to pivot relative to the base member on and about the pivot cylinder  
making an incision to expose a first vertebral body and a second vertebral body of a patient's spine;  
preparing a space between the first vertebral body and the second vertebral body for receiving the interbody fusion device;  
obtaining an insertion tool, the insertion tool comprising:  
a handle;  
an insertion end;

18

at least one tube extending away from the handle and connecting the handle and the insertion end;  
a first knob configured to couple to the handle; and  
an actuation bar moveable between a first position and a second position to enable the first knob to engage an adjustment mechanism in the first position and a securement mechanism in the second position;  
inserting the insertion tool into an opening in the base member and coupling the insertion tool to the interbody fusion device;  
inserting the interbody fusion device into the space between the first vertebral body and the second vertebral body;  
rotating the insertion tool to move the top member relative to the base member;  
uncoupling the insertion tool from the interbody fusion device; and  
closing the incision.

\* \* \* \* \*