



⑫ **EUROPEAN PATENT SPECIFICATION**

④⑤ Date of publication of patent specification :  
**25.10.95 Bulletin 95/43**

⑤① Int. Cl.<sup>6</sup> : **H01J 65/00**

②① Application number : **92200131.8**

②② Date of filing : **17.01.92**

⑤④ **Electrodeless low-pressure discharge lamp.**

③⑩ Priority : **25.01.91 NL 9100124**

④③ Date of publication of application :  
**29.07.92 Bulletin 92/31**

④⑤ Publication of the grant of the patent :  
**25.10.95 Bulletin 95/43**

⑧④ Designated Contracting States :  
**BE DE ES FR GB IT NL**

⑤⑥ References cited :  
**EP-A- 0 384 520**  
**DE-A- 3 838 121**

⑦③ Proprietor : **Philips Electronics N.V.**  
**Groenewoudseweg 1**  
**NL-5621 BA Eindhoven (NL)**

⑦② Inventor : **Eggink, Hendrik Jan**  
**c/o INT. OCTROOIBUREAU B.V.**  
**Prof. Holstlaan 6**  
**NL-5656 AA Eindhoven (NL)**  
Inventor : **Friederichs, Winand Hendrik Anna**  
**Maria**  
**c/o INT. OCTROOIBUREAU B.V.**  
**Prof. Holstlaan 6**  
**NL-5656 AA Eindhoven (NL)**  
Inventor : **Van Gennip, Nicasius Gerardus**  
**Tielemanus**  
**c/o INT. OCTROOIBUREAU B.V.**  
**Prof. Holstlaan 6**  
**NL-5656 AA Eindhoven (NL)**

⑦④ Representative : **Rooda, Hans et al**  
**INTERNATIONAAL OCTROOIBUREAU B.V.,**  
**Prof. Holstlaan 6**  
**NL-5656 AA Eindhoven (NL)**

**EP 0 496 464 B1**

Note : Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

## Description

The invention relates to an electrodeless low-pressure discharge lamp comprising

- a lamp vessel which is sealed in a vacuumtight manner, contains ionizable metal vapour and rare gas, and has a cavity at an end portion of said vessel,
- an electric coil around a sleeve of synthetic material in the cavity of the lamp vessel,
- a core of soft magnetic material in the sleeve of synthetic material,
- a tube containing a liquid in the core of soft magnetic material, which tube projects to outside the cavity and has a flange there.

Such a lamp is known from EP-0 384 520.

The lamp is provided with a tube containing liquid in order to discharge heat generated during operation of the lamp, to prevent *inter alia* that the core of soft magnetic material will assume too high a temperature. This is because the specific magnetic losses of the core increase with increasing temperature, whereas the magnetic permeability starts to decrease from a raised temperature. It is the object of the cooling by means of the tube containing liquid to suppress these factors, which adversely affect the luminous efficacy of the lamp.

There is a risk that the temperature of the core of the known lamp is comparatively high.

The invention has for its object to provide a lamp of the kind described in the opening paragraph which is of a simple construction and in which nevertheless the temperature of the core can be relied on to have a comparatively low value.

This object is achieved in that the sleeve is at least substantially filled with an elastic polymer such that in particular a good thermal connection is obtained between the core and the tube.

The core and the tube each have their own thermal coefficient of expansion. As a result of this and of the tolerances which have to be accepted with regard to the dimensions of these bodies, it is difficult to achieve a close contact between the tube and the core and also to prevent stresses to occur owing to which the core is cracked.

It is true that one can aim at a close fit of the tube in the core during operation, but even then heat transfer must take place through a slit between the tube and the core. Since the tube, being the innermost body, has the smaller surface, a comparatively great heat flow must still run per unit area.

Since the space inside the sleeve is at least substantially filled with an elastic polymer, there is a close connection between the core and the tube.

The sleeve and the core may be made closely fitting, for example, in that the core is ground to the correct diameter. There is a good heat transfer between

the sleeve and the core then, also because the core has a comparatively large outer surface. Alternatively, there may be a clearance between the sleeve and the core which is filled up with the elastic polymer. A better heat transfer to the tube, and from there to the surroundings of the lamp, is achieved by the measure according to the invention.

In a favourable embodiment, the sleeve is not only filled with, but also enveloped in the elastic polymer. A lower heat resistance is realised in this way, so that the cavity of the lamp vessel forms a cooler ambience for the core. An enveloped sleeve also has the advantage that the coil remains fixed around the sleeve. Expansion of the coil at operating temperature could cause the coil to sag in the long run, turns getting a greater pitch.

It is favourable for easy manufacture of the lamp if the lamp vessel on the one hand and the assembled body in the cavity on the other hand are separate sub-assemblies. In view of the tolerances which must be permitted for the dimension of the cavity in the lamp vessel, a body which consists mostly of glass, it is not safeguarded then that the enveloped sleeve is in contact with the lamp vessel all around. The surface of the envelope of the sleeve, being the outermost surface, however, is much greater than the surface of the tube. The heat flow per unit area is therefore much smaller, so that a less close contact between the lamp vessel and the envelope is of minor influence.

The use of an elastic polymer is also advantageous in that differences in coefficient of expansion between the materials on which the various bodies are manufactured, especially those of the tube and the core, can be easily accommodated. Frequently used materials are: glass for the lamp vessel; synthetic material, for example liquid crystalline polymer, for the tube; ferrite, for example Philips 4C6, for the core; metal, for example copper, for the tube; and, for example, rubber, such as silicone rubber, as an elastic polymer.

In addition, the lamp is better resistant to shocks and vibrations, for example, during transport.

This and other more detailed aspects of the invention are described and explained with reference to the drawing in which a lamp is shown partly in cross-section, partly in elevation.

The electrodeless low-pressure discharge lamp has a lamp vessel 1 which is closed in a vacuumtight manner, is made of, for example, lime glass, contains ionizable metal vapour and rare gas, and comprises a cavity 2, for example of lead glass, at an end portion 3 of said vessel.

An electric coil 4 around a sleeve 5 of synthetic material is present in the cavity 2. A core 6 of soft magnetic material is present in the sleeve 5 of synthetic material. A tube 7 containing liquid is present in the core 6, projects to outside the cavity 2, and has a flange 8 there.

In the embodiment drawn, the lamp vessel 1 contains a rare gas and mercury as an ionizable metal and is coated with a fluorescent powder 1a.

The sleeve 5 is filled with an elastic polymer 9. The polymer fills the gap between the tube 7 and the core 6. In the embodiment drawn, the polymer also envelops the sleeve 5.

The tube 7, the core 6 and the sleeve 5 with the coil 4 in the drawing together with the polymer 9 form a sub-assembly which is provided as such in the cavity 2. The sub-assembly 4, 5, 6, 7, 9 is thus removable from the cavity 2. Silicone rubber is used as the polymer 9.

In the drawing, the sleeve 5 is fastened with a snap connection 12, 13 to a support 14 of synthetic material which has a flange 15, on which are present hooks 16, at a free end. The flange 8 of the tube 7 and the flange 15 of the support 14 are fastened to one another and a foil 17 of synthetic material, for example silicone rubber, is provided against the flange 8. As a result, the lamp may be mounted against a metal support without the risk of a galvanic element being formed by this support and the flange 8. A collar 19 of synthetic material, which is held by the hooks 16, is mounted to the lamp vessel 1, for example with silicone compound 18. A cable leading to an electric supply may be connected to contacts 20 at the flange 15, to which the coil 4 is connected.

## Claims

### 1. An electrodeless low-pressure discharge lamp comprising

- a lamp vessel (1) which is sealed in a vacuumtight manner, contains ionizable metal vapour and rare gas, and has a cavity (2) at an end portion (3) of said vessel,
- an electric coil (4) around a sleeve (5) of synthetic material in the cavity (2) of the lamp vessel (1),
- a core (6) of soft magnetic material in the sleeve (5) of synthetic material,
- a tube (7) containing a liquid in the core (6) of soft magnetic material, which tube (7) projects to outside the cavity (2) and has a flange (8) there,

characterized in that

the sleeve (5) is at least substantially filled with an elastic polymer (9), such that in particular a good thermal connection is obtained between the core and the tube.

### 2. An electrodeless low-pressure discharge lamp as claimed in Claim 1, characterized in that the sleeve (5) is enveloped in the polymer (9).

### 3. An electrodeless low-pressure discharge lamp as

claimed in Claim 1 or 2, characterized in that the enveloped sleeve (5) with the coil (4), the core (6), and the tube (7) form a sub-assembly which is separate from the lamp vessel (1).

### 4. An electrodeless low-pressure discharge lamp as claimed in Claim 1, 2 or 3, characterized in that the polymer (9) is silicone rubber.

## Patentansprüche

1. Elektrodenlose Niederdruckentladungslampe mit
  - einem vakuumdicht geschlossenen Lampenkolben (1), der ionisierbares Metall- dampf- und Edelgas und einen Hohlraum (2) an einem Endanteil (3) des Kolbens enthält,
  - einer elektrischen Spule (4) um eine Hülse (5) aus Kunststoff im Hohlraum (2) des Lampenkolbens (1),
  - einem Kern (6) aus weichmagnetischem Material in der Kunststoffhülse (5),
  - einem Rohr (7) mit einer Flüssigkeit im Kern (6) aus weichmagnetischem Material, und dieses Rohr (7) ragt aus dem Hohlraum (2) heraus und hat an dieser Stelle einen Flansch (8),

dadurch gekennzeichnet, daß die Hülse (5) wenigstens hauptsächlich mit einem elastischen Polymer (9) derart gefüllt ist, daß insbesondere eine gute Wärmeleitung zwischen dem Kern und dem Rohr erhalten wird.

### 2. Elektrodenlose Niederdruckentladungslampe nach Anspruch 1, dadurch gekennzeichnet, daß die Hülse (5) vom Polymer (9) umgeben wird.

### 3. Elektrodenlose Niederdruckentladungslampe nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß die umhüllte Hülse (5) mit der Spule (4) dem Kern (6) und dem Rohr (7) eine Untereinheit bildet, der vom Lampenkolben (1) getrennt ist.

### 4. Elektrodenlose Niederdruckentladungslampe nach Anspruch 1, 2 oder 3, dadurch gekennzeichnet, daß das Polymer (9) Silikonengummi ist.

## Revendications

### 1. Lampe à décharge à basse pression sans électrodes comportant

- un récipient de lampe (1) fermé de manière étanche au vide, contenant une vapeur métallique ionisable et un gaz rare, et présentant une cavité (2) pratiquée dans une partie terminale (3) dudit récipient,

- une bobine électrique (4) entourant un manchon (5) en matériau synthétique, disposée à l'intérieur de la cavité (2) du récipient de lampe (1),
  - un noyau (6) en matériau magnétique doux 5  
situé dans le manchon (5) en matériau synthétique,
  - un tube (7) contenant un liquide dans le noyau (6) en matériau synthétique doux, le-  
dit tube (7) traverse la cavité (2) et il présente 10  
une bride (8) à cet endroit-là,
- caractérisée en ce que  
le manchon (5) est au moins rempli sensiblement  
d'un polymère élastique (9) de façon à obtenir  
particulièrement une connexion thermique 15  
convenable entre le noyau et le tube.
2. Lampe à décharge à basse pression sans électrodes selon la revendication 1, caractérisée en ce que le manchon (5) est noyé dans le polymère (9). 20
3. Lampe à décharge à basse pression sans électrodes selon la revendication 1 ou 2, caractérisée en ce que le manchon enrobé (5) conjointement 25  
avec la bobine (4), le noyau (6) et le tube (7) constituent un sous-ensemble séparé du récipient de lampe (1).
4. Lampe à décharge à basse pression sans électrodes selon la revendication 1, 2 ou 3, caractérisée en ce que le polymère (9) est un caoutchouc 30  
silicone.

35

40

45

50

55

