



US010114182B2

(12) **United States Patent**  
**Zbinden et al.**

(10) **Patent No.:** **US 10,114,182 B2**  
(45) **Date of Patent:** **Oct. 30, 2018**

(54) **RACK-MOUNTABLE EQUIPMENT WITH A HIGH-HEAT-DISSIPATION MODULE, AND TRANSCEIVER RECEPTACLE WITH INCREASED COOLING**

(71) Applicant: **Samtec, Inc.**, New Albany, IN (US)

(72) Inventors: **Eric J. Zbinden**, New Albany, IN (US); **Thomas A. Hall, III**, New Albany, IN (US)

(73) Assignee: **SAMTEC, INC.**, New Albany, IN (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/261,295**

(22) Filed: **Sep. 9, 2016**

(65) **Prior Publication Data**

US 2017/0077643 A1 Mar. 16, 2017

**Related U.S. Application Data**

(60) Provisional application No. 62/216,609, filed on Sep. 10, 2015, provisional application No. 62/341,650, filed on May 26, 2016, provisional application No. 62/350,368, filed on Jun. 15, 2016.

(51) **Int. Cl.**  
**G02B 6/42** (2006.01)  
**G02B 6/38** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **G02B 6/4268** (2013.01); **G02B 6/3897** (2013.01); **G02B 6/4249** (2013.01)

(58) **Field of Classification Search**  
CPC ... G02B 6/4268; G02B 6/3897; G02B 6/4249  
USPC ..... 439/487  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,345,267 A	8/1982	Corman et al.	
6,142,802 A	11/2000	Berg et al.	
6,319,075 B1	11/2001	Clark et al.	
6,592,401 B1 *	7/2003	Gardner .....	G02B 6/3817
			439/101
6,824,426 B1 *	11/2004	Spink, Jr. ....	H01R 24/62
			439/579
6,848,953 B2	2/2005	Schell et al.	
7,070,446 B2	7/2006	Henry et al.	
7,249,966 B2	7/2007	Long	
7,422,483 B2	9/2008	Avery et al.	

(Continued)

FOREIGN PATENT DOCUMENTS

JP	2013-102163 A	5/2013
WO	2017/123574 A1	7/2017

OTHER PUBLICATIONS

Official Communication issued in International Patent Application No. PCT/US2016/051072, dated Dec. 23, 2016.


*Primary Examiner* — Alexander Gilman

(74) *Attorney, Agent, or Firm* — Keating & Bennett, LLP

(57) **ABSTRACT**

An electrical connector includes a heat dissipation module with a first end and a second end opposed to the first end and two receptacle connectors located at the second end. The first and second ends define a transceiver-mating direction such that, when a transceiver is inserted into the first end of the heat dissipation module in the transceiver-mating direction, the transceiver mates with one of the two receptacle connectors, and in the heat dissipation module, air flows parallel to the transceiver-mating direction between the first and second ends and flows between the two receptacle connectors.

**44 Claims, 32 Drawing Sheets**








FIG. 1




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 5C





FIG. 6






FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12





FIG. 13







FIG. 15






FIG. 17





FIG. 18







FIG. 20



**FIG. 21**  
**(PRIOR ART)**




FIG. 22  
(PRIOR ART)






FIG. 23  
(PRIOR ART)



**FIG. 24**  
**(PRIOR ART)**






FIG. 26




FIG. 27






FIG. 29

# RACK-MOUNTABLE EQUIPMENT WITH A HIGH-HEAT-DISSIPATION MODULE, AND TRANSCEIVER RECEPTACLE WITH INCREASED COOLING

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

The present invention relates to rack-mountable equipment with a heat-dissipation module and data interconnects, and also relates to a receptacle that receives an optical transceiver and that has increased cooling.

### 2. Description of the Related Art

Electronics racks are standard components for mounting a wide variety of electronic components and equipment in data, computing, and/or communication systems. Data centers typically have large numbers of racks, each filled with various pieces of electronic equipment, such as servers. A standard electrical rack has a 19" width, which can support assemblies that mount into the rack with a width of 17.25". Multiple assemblies can be mounted in each rack, one above the other. These assemblies typically are supported by a front bezel formed from cut outs in a flat piece of sheet metal that has clearance holes or slots along its edges to secure the bezel to the rack.

The rack-mountable electronic components often generate heat that needs to be removed from the rack to avoid overheating of the various electronic components. Typically cooling is provided by a fan that forces air across a heat sink that is in thermal contact with the temperature-sensitive, heat-producing electronic components.

The rapid increase in data storage and high-bandwidth communication driven by Internet expansion is increasing the need for dense interconnection systems in data centers. These data centers are typically composed of rows of racks of servers. These servers need to be in high-bandwidth communication with other servers in the data centers. The high-bandwidth communication can be supported by either shielded electrical cables or increasingly active optical cables. Active optical cables support longer transmission distances and higher transmission bandwidths. An active optical cable typically has an optical engine incorporated into a transceiver on at least one end of the cable that transforms electrical signals into optical signals (transmission (Tx) function) and transforms optical signals into electrical signals (receiver (Rx) function). An electronics rack can have hundreds or even thousands of interconnections, each of which generates heat that must be removed from the electronics rack. The inability to remove this heat can result in accelerated aging and/or premature failure of the interconnection or other components in the electronics rack. There is a need to provide a rack mounting system that facilitates high-heat removal and dense packaging of the interconnections.

FIG. 21 shows a known active optical cable 200 including a cable 201 and a transceiver 203. The transceiver 201 shown in FIG. 21 is compatible with SFF-8436 QSFP+ multi-source agreement revision 4.8, Oct. 31, 2013, hereby incorporated by reference in its entirety. Other known types of transceivers include SFP, QSFP, microQSFP, etc. The transceiver 203 can mate and unmate with receptacles in a rack (the receptacles and the rack are not shown in FIG. 21). The receptacles can be mounted to a printed circuit board (PCB). Mating the transceiver 203 to the receptacle creates mechanical and electrical connections. Electrical signals can be transported between the receptacle and the PCB. The transceiver 203 includes a pull tab 202 and an edge card 204.

The pull tab 202 is optional and can be used to unmate the transceiver 203. The edge card 204 can mate with a connector within the receptacle. The edge card 204 can transport electrical signals to/from the transceiver 203.

The transceiver 203 can be optical, electrical, or hybrid of optical and electrical. If the transceiver 203 is optical, then the cable 201 includes optical fibers that transport, in which transport means receive and/or transmit, optical signals. The optical fibers can be single-mode or multimode fibers. The transceiver 201 can include an optical engine for transforming optical signals to electrical signals and/or electrical signals into optical signals.

If the transceiver 203 is electrical, then the cable 201 includes electrically conductive wires that transport electrical signals. The cable 201 can be, for example, coaxial cable, which is sometimes referred to as coax and which includes a single conductor surrounded by a dielectric and a shield layer, and twinaxial cable, which is sometimes referred to as twinax and which includes two conductors surrounded by a dielectric and shield layer. The cable 201 can also include other suitable transmission lines. The transceiver 201 can include contain electronic circuitry that transport electrical signals, including, for example, high-bandwidth electrical signals.

If the transceiver is a hybrid, then the cable 201 includes both optical and electrical cables. The transceiver 203 includes both an optical engine that transforms optical signals into electrical signals and/or electrical signals into optical signals and electronic circuitry that are appropriate for transmitting and/or receiving electrical signals from the electrical cable.

There is an increasing need for smaller transceivers that can be more tightly packed together and higher bandwidth transceivers. However, as channel density and bandwidth increased, the heat generated by the transceiver increases, which can cause excessive temperatures in the transceiver. Excessive temperatures can lead to premature failure and poor performance. Thus, there is a need for a transceiver receptacle that provides improved cooling for densely packaged, high-bandwidth transceivers.

FIGS. 22-24 show a known receptacle 205 that can be used with an electronics rack. The receptacle 205 can be mounted to a rack mount, which can then be mounted to an electronics rack. The receptacle 205 includes a cage 216 with mounting pins 217 and receptacle connectors 220 within the cage connected to wafers 222. Each wafer 222 is a module that includes a molded insert and a lead frame. The lead frame includes electrical contacts that each provide an electrical path for transmitting electrical signals. The molded insert is molded around the lead frame so that the electrical contacts are fixed with respect to each other within the wafer 222. The wafers 222 can be inserted into the receptacle connector 220 such that the wafers 222 are arranged side-by-side to each other so that the electrical contacts of adjacent wafers 222 are fixed with respect to each other in the receptacle connector 220. The cage 216 includes electromagnetic shields 218, faceplate 219, and slots 211. Transceivers can be inserted into the slots 211 to engage with the receptacle connectors 220. The receptacle connectors 220 are connected to wafers 222 that block or impede air flow.

During operation, the electronic components of the transceivers generate heat, which is mostly dissipated through the upper and lower walls, with a small amount being dissipated through the side walls. The heat dissipated into the passage 207 cannot be adequately removed because the wafers 222 block the flow of air in a direction from faceplate 219 to

receptacle connector 220. As shown in FIG. 23, it is known to use holes in the sides of the cage 216. The location and size of the holes restrict the amount of air that is available to move through the cage 216 for cooling, particularly when a transceiver is inserted into the cage 216. But these side holes do not effectively remove the heat within the passage 207 (FIG. 22) and thus do not effectively remove heat from the transceivers. For interior transceivers in arrays 3x2 and bigger, the holes in the sides are not effective or adequate because the heat has to flow from an interior passage to an exterior passage with the sides holes. If the heat in the passage 207 cannot be adequately removed, the transceivers can undergo accelerated aging and/or prematurely fail. Thus, there is need for a receptacle with improved heat management.

### SUMMARY OF THE INVENTION

To overcome the problems described above, preferred embodiments of the present invention provide an air-cooled heat sink that is located in the front bezel of a rack. Robust physical contact is provided between the heat sink and the heat generating components of the interconnection system, including, for example, the transceiver of an active optical cable. The robust physical contact and large heat dissipating surface of the heat sink provide a low impedance thermal path between the transceiver and the ambient environment. In addition to providing heat dissipation, the heat sink can also serve as an electromagnetic radiation shield, reducing radiated stray electromagnetic radiation outside of the rack enclosure.

To overcome the problems described above, preferred embodiments of the present invention provide a receptacle with a cage that can be mounted to a PCB and with a receptacle connector in the cage. Electrical connections between the PCB and the receptacle are made by flyover cables. A transceiver can be mated and unmated to the receptacle.

An electrical connector according to a preferred embodiment of the present invention includes a heat dissipation module with a first end and a second end opposed to the first end and two receptacle connectors located at the second end. The first and second ends define a transceiver-mating direction such that, when a transceiver is inserted into the first end of the heat dissipation module in the transceiver-mating direction, the transceiver mates with one of the two receptacle connectors, and in the heat dissipation module, air flows parallel to the transceiver-mating direction between the first and second ends and flows between the two receptacle connectors.

The two receptacle connectors are preferably vertically stacked in relation to a base substrate. The two receptacle connectors preferably each receive a card-edge of a mating transceiver. Preferably, the heat dissipation module includes a cage, and the cage further defines two slots that extend between the first and second ends, and the air flows between the slots. The two receptacle connectors are preferably electrically isolated from one another.

Preferably, the two receptacle connectors each include a housing, high-speed and low-speed electrical contacts in the housing, high-speed cables electrically connected to the high-speed electrical contacts, and low-speed cables and a power filter electrically attached to the low-speed electrical contacts.

The electrical connector further preferably includes a heat sink located between the two receptacle connectors. The heat sink preferably is an extrusion or bent sheet metal. The

heat sink preferably defines air flow paths. The heat sink is preferably mounted to the heat dissipation module such that a position of the heat sink is fixed when the transceiver is mated with the one of the receptacle connectors. Channels in the heatsink are preferably no larger than one quarter of a wavelength of a dominant emitted electromagnetic interference generated, when the transceiver is mated with the transceiver, by electrical signals transmitted and/or received by the transceiver.

A blower is preferably mounted adjacent to the heat sink such that the blower directs forced air over the heat sink. Air preferably flows in one or more air-flow paths between the two receptacle connectors.

Only the cage is preferably configured to be press-fit or surface mounted to a substrate.

An electrical connector according to a preferred embodiment of the present invention includes a housing, high-speed and low-speed electrical contacts in the housing, high-speed cables electrically connected to the high-speed electrical contacts, and low-speed cables and a power filter electrically attached to the low-speed electrical contacts.

Preferably, high-speed is at least 25 Gbits/sec data transmission speed, and low-speed is less than 25 Gbits/sec data transmission speed.

An electrical connector system according to a preferred embodiment of the present invention includes a cage with a first end and a second end opposed to the first end, and two electrical connectors located at the second end. The first and second ends define a transceiver-mating direction such that when a transceiver is inserted into the first end of the cage in the transceiver-mating direction the transceiver mates with one of the two electrical connectors, and in the cage, air flows parallel to the transceiver-mating direction between the first and second ends and flows between the two electrical connectors.

Preferably, the cage includes press-fit tails, and the two electrical connectors do not include press-fit tails, through-hole tails, or surface-mount tails. Preferably, the two electrical connectors are receptacle connectors each including a signal conditioner electrically connected to cables. Preferably, only the cage is configured to be press-fit or surface mounted to a substrate.

An electrical connector system according to a preferred embodiment of the present invention includes a cage with a first end and a second end opposed to the first end, and two electrical connectors located at the second end. The first and second ends define a transceiver-mating direction such that, when a transceiver is inserted into the first end of the cage in the transceiver-mating direction, the transceiver mates with one of the two electrical connectors, and the two electrical connectors are spaced apart from each other such that, in the cage, air flows parallel to the transceiver-mating direction between the first and second ends and flows between the two electrical connectors.

The electrical connector system further preferably includes a heat sink located between the two electrical connectors. Preferably, air flows in one or more air-flow paths between the two electrical connectors.

A rack mount according to a preferred embodiment of the present invention includes an electrical connector or an electrical connector system according to the various preferred embodiments of the present invention. An electronics enclosure according to a preferred embodiment of the present invention includes one or more rack mounts of according to various preferred embodiments of the present invention.

A preferred embodiment of the present invention includes a QSFP electrical connector and cage according to SFF-

8438, in which the QSFP electrical connector is an edge-card connector that is devoid of press-fit or mounting tails. A preferred embodiment of the present invention includes a stacked QSFP electrical connector and a cage, in which the stacked QSFP type of electrical connector includes an edge-card connector that is devoid of press-fit or mounting tails.

An electrical connector system according to a preferred embodiment of the present invention includes a substrate, a first cage with a first end and a second end opposed to the first end and mounted to a first side of the substrate, a first electrical connector located at the second end of the first cage, a second cage with a first end and a second end opposed to the first end and mounted to a second side of the substrate opposite the first side, and a second electrical connector located at the second end of the second cage. The first and second ends of the first and second cages define a transceiver-mating direction such that, when a transceiver is inserted into the first end of the first or second cage in the transceiver-mating direction, the transceiver mates with the first or second electrical connectors, and air flows parallel to the transceiver-mating direction between the first and second ends of both the first and second cages.

An electrical connector system according to a preferred embodiment of the present invention includes a cage with a first end and a second end opposed to the first end and with a slot extending between the first and second ends, an electrical connector located at the second end, and a heat sink or a heat spreader rigidly attached to the cage. The first and second ends define a transceiver-mating direction such that, when a transceiver is inserted into the slot at the first end of the cage in the transceiver-mating direction, the transceiver mates with the electrical connector, and when a transceiver is inserted into the slot, the transceiver is pushed against a side of the slot in the cage adjacent the heat sink or the heat spreader.

Preferably, a spring pushes the transceiver against the side of the slot.

An electrical connector system according to a preferred embodiment of the present invention includes a cage with a first end and a second end opposed to the first end and with a slot that extends between the first and second ends, and an electrical connector located at the second end. The first and second ends define a transceiver-mating direction such that, when a transceiver is inserted into the slot at the first end of the cage in the transceiver-mating direction, the transceiver mates with the electrical connector, and the electrical connector mechanically floats in a direction orthogonal or substantially orthogonal to the transceiver-mating direction and does not mechanically float in a direction parallel or substantially parallel to the transceiver-mating direction.

The electrical connector is preferably removed using a tool inserted into the first end of the slot.

An electrical connector system according to a preferred embodiment of the present invention includes a substrate, a cage connected to the substrate, including a first end and a second end opposed to the first end, and including a slot that extends between the first and second ends, and an electrical connector located at the second end. The first and second ends define a transceiver-mating direction such that, when a transceiver is inserted into the slot at the first end of the cage in the transceiver-mating direction, the transceiver mates with the electrical connector, and the distance between the electrical connector and substrate is allowed to float and a flexible electrical connection connects the electrical connector and the substrate.

An electrical connector according to a preferred embodiment of the present invention includes a heat dissipation

module with a first end and a second end opposed to the first end, two receptacle connectors located at the second end, and a passageway that extends from the first end to the second end and that is positioned adjacent to one of the two receptacle connectors. The first and second ends define a transceiver-mating direction such that, when a transceiver is inserted into the first end of the heat dissipation module in the transceiver-mating direction, the transceiver mates with one of the two receptacle connectors, and in the heat dissipation module, heat in the passageway travels through the passageway parallel to the transceiver-mating direction and escapes through the first and second ends.

The above and other features, elements, characteristics, steps, and advantages of the present invention will become more apparent from the following detailed description of preferred embodiments of the present invention with reference to the attached drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a portion of rack mount according to a preferred embodiment of the present invention.

FIG. 2A is a front view of the rack mount shown in FIG. 1.

FIG. 2B is a perspective view of the rack mount shown in FIG. 1.

FIG. 3 is a perspective view of a portion of a heat-dissipation module shown in FIG. 1.

FIG. 4 is a schematic cross-section of a portion of a rack mount in a belly-to-belly configuration according to a preferred embodiment of the present invention.

FIGS. 5A, 5B, and 5C are schematic cross-sections of a portion of a rack mount in a stacked configuration according to a preferred embodiment of the present invention.

FIG. 6 shows a schematic cross-section of a portion of a rack mount in a belly-to-belly configuration with electrical connectors according to a preferred embodiment of the present invention.

FIG. 7 is a perspective view of heat-dissipation module made of sheet metal according to a preferred embodiment of the present invention.

FIG. 8 is a perspective view of a receptacle according to a preferred embodiment of the present invention.

FIG. 9 is a perspective view of a transceiver and a receptacle connector according to a preferred embodiment of the present invention.

FIG. 10 is a rear perspective view of a receptacle connector being plugged into the cage.

FIG. 11 is a front perspective view of the receptacle connector.

FIG. 12 is a top exploded view of a receptacle connector.

FIG. 13 is a rear perspective view of the receptacle connector.

FIG. 14 is a rear perspective view of an alternative receptacle connector.

FIG. 15 is a front perspective view of a cage according to a preferred embodiment of the present invention.

FIG. 16 is a perspective view of a tool according to a preferred embodiment of the present invention.

FIG. 17 is a perspective view of a receptacle with a blower according to a preferred embodiment of the present invention.

FIG. 18 is a perspective view of the blower shown in FIG. 17.

FIG. 19 is perspective sectional view of the receptacle.

FIG. 20 is a side sectional view of the receptacle shown in FIG. 19.

FIG. 21 shows a prior art active cable.

FIG. 22 is perspective sectional view of a known receptacle.

FIG. 23 is rear perspective view of the known receptacle shown in FIG. 22.

FIG. 24 is a side sectional view of the known receptacle shown in FIG. 22.

FIG. 25 is a perspective sectional view of a receptacle with a heatsink.

FIG. 25 is a perspective sectional view of a receptacle with heat-transferring fins.

FIGS. 26-29 are perspective views of a receptacle with a double-walled cage.

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

A preferred embodiment of the present invention provides a low-impedance thermal path between a transceiver and the ambient environment. Heat transfer to the ambient environment is provided by forced convective air flow across a heat sink. The heat sink is incorporated into the front bezel of a heat-dissipation module that can be mounted to an electronics rack. The heat sink can provide cooling for a plurality of transceivers. This contrasts with many prior art transceivers in which the heat sink is incorporated directly into the transceiver. The preferred embodiments of the present invention advantageously provide superior cooling for a large number of transceivers that are densely connected in an electronics rack.

FIG. 1 shows a portion of rack mount 60. The rack mount 60 includes a heat-dissipation module 10, a printed circuit board (PCB) 50, a heat sink 12, a transceiver 30, and a cable 31. The transceiver 30 is preferably an optical transceiver, and the cable 31 is preferably an optical cable. The transceiver 30 can use one of many industry standard transceiver formats such as QSFP+, PCIe, CXP, CFP, SFP, etc. In particular, the transceiver 30 can meet the requirement of SFF-8438 (INF-8438i, Rev. 1.0, hereby incorporated by reference in its entirety). The preferred embodiments of the present invention are not limited to these standard transceiver formats, and any transceiver can be used including proprietary transceivers or developing transceiver formats, such as OSFP and mini-OSFP. The OSFP format, Octal Small Form-Factor Package, supports 8 fully duplexed communication channels. That is, the format has 8 independent transmission channels and 8 independent receiver channels. Incorporated into any of these transceiver formats can be a silicon photonic element that provides modulation and/or receive functions; however, this is not a requirement. In FIG. 1, the transceivers 30 are shown adjacent to their respective mating slot 11 in the heat-dissipation module 10. In operation, the transceivers 30 can be plugged into their respective slots 11. The rack mount 60 does not need to include spring-biased heat sinks. The heat sinks 12 can be formed directly by the heat-dissipation module 10 and not separate finned structures positioned behind a front bezel or a panel of a system or a rack.

For clarity, the PCB 50 shown in FIG. 1 is not populated with any electronic components; however, in practice the PCB 50 can have various electronic components that support high-speed computing and communication. The PCB 50 can be connected to a plurality of heat-dissipation modules 10. Each module 10 includes a heat sink 12, a cage 16, and a slot 11 for a transceiver 30. The heat-dissipation module 10 is

described in more detail below. Connected in the slots 11 of the heat-dissipation module 10 can be one or more transceivers 30. In FIG. 1, four transceivers 30 are connected to each module; however, the module can be configured to accept more or less than four transceivers 30. Each transceiver 30 is connected to a cable 31 that provides communication between the PCB 50 and some other element in a data network. As previously mentioned, the transceiver 30 is preferably an optical transceiver, and the cable 31 is preferably an optical cable that contains one or more optical fibers. In FIG. 1, four heat-dissipation modules 10 are connected to the top the PCB 50, and four heat-dissipation modules 10 are connected to the bottom of the PCB 50. Each heat-dissipation module 10 is capable of accepting four transceivers 30 so a total of 32 transceivers can be connected to the PCB 50 as shown in FIG. 1. The transceivers 30 mounted above the PCB 50 can make electrical connections to the top of the PCB 50, and the transceivers 30 mounted below the PCB 50 can make electrical connections to the bottom of the PCB 50. This transceiver configuration is referred to as "belly-to-belly" and allows for short electrical paths between the transceiver 30 and the PCB 50 facilitating transmission of high-bandwidth signals, such as, 10 Gbps, 28 Gbps, 56 Gbps, or even higher bandwidths.

FIG. 2A shows an end view of a portion of a rack mount 60. In FIG. 2A, the transceivers 30 have been removed for clarity. FIG. 2A shows eight heat-dissipation modules 10. Each heat-dissipation module 10 has slots 11 for four transceivers 30. Each slot 11 is surrounded by an electrical conductor, such as a metal, forming a cage 16 that provides electromagnetic shielding between transceivers 30 situated in adjacent slots 11. The PCB 50 is not clearly visible in FIG. 2A, but would be situated between the upper and lower rows of heat-dissipation modules 10 as shown in FIG. 1. Connectors, which would be mounted to the PCB 50 to accept each transceiver 30, are also not shown in FIG. 2A. Each heat-dissipation module 10 has a heat sink 12 including a web of material with air passages running completely through the heat sink 12 along a front to back transceiver insertion direction. In FIG. 2A, the transceiver insertion direction extends into the drawing page. The heat sink 12 associated with each heat-dissipation module 10 provides cooling for all four transceivers 30 that can be mounted in the slots 11. The transceivers 30 themselves do not need any type of finned structure to dissipate heat into the surrounding atmosphere because they are cooled by conduction to the heat sink 12 of the heat-dissipation module 10 and perhaps forced air blowing through the heat sinks 12 along the transceiver insertion direction. Electromagnetic shielding (not visible in FIG. 2A) can be provided between the heat-dissipation modules 10 to reduce stray electromagnetic radiation.

FIG. 2B shows a perspective view of a rack mount 60 with a heat-dissipation module 10. Four heat-dissipation modules 10 are situated above an edge of PCB 50 and four heat-dissipation modules 10 are situated below an edge of the PCB 50. The heat-dissipation modules 10 are fully populated with transceivers 30. A cable 31 is connected to each transceiver 30, and each transceiver 30 can have a pull ring 32 for easy removal from the heat-dissipation module 10. Flanges 15 can be located on the sides of the heat-dissipation module 10 to secure the rack mount 60 to the sides of an electronics rack. Representative dimensions for a rack mount 60 are shown in FIG. 2B. Rack mount 60 can be compatible with mounting in a 19-inch rack. The height rack mount 60 can be approximately 1.375 inches, and the opposing sides of the mounted transceivers 30 can be

separated by approximately 0.582 inches. These dimensions are compatible with the heat-dissipation module **10** occupying 1 U of rack height (1 U=1 rack unit=1.75" high). These values are exemplary only, and the dimensions can be adjusted as required to best suit the intended application. In practice, many of these rack mounts **60** can be stacked one above the other in an electronics rack.

FIG. **3** shows a single heat-dissipation module **10**. The heat-dissipation module **10** includes slots **11** for four transceivers **30** and a heat sink **12**. The slots **11** can include latching features, not shown in FIG. **3**, that help to secure a plugged transceiver **30** in position. The slots **11** can also include flexible members, not shown in FIG. **3**, that lightly slide against the sides of the transceiver **30** to provide electromagnetic shielding. The heat sink **12** includes a web of material providing a large surface area for convective heat transfer of air flowing through the heat sink **12**. In FIG. **3**, the air is depicted as flowing out the heat sink **12** in direction A; however, the air direction can be reversed, i.e. the front-to-back transceiver insertion direction instead of back-to-front as shown. A fan (not shown in FIG. **3**) can be mounted on the front, back, or sides of the heat-dissipation module **10**, although this is not a requirement. A fan can be mounted somewhere else in the electronics rack (not shown in FIG. **3**) that supports the heat-dissipation module **10**. Instead of a fan, a duct can bring forced air to the electronics rack. The fan or duct can then draw or force air through the heat sink **12** along direction A or along the transceiver insertion direction (180 degrees opposite of direction A). The heat sink **12** webbing can be designed so that it is thicker in the region of the heat sink **12** adjacent to the slot **11** to provide enhanced thermal conductance to regions of the heat sink **12** farther away from the slot **11**. A hexagonal web pattern is shown in FIG. **3**; however, the web pattern can take many forms such as squares, rectangles, diamonds, triangles, serpentine, etc. The web pattern also need not be a regular pattern, but could have a random structure. The heat sink **12** provides a large surface area for convective heat transfer and a low-impedance conductive path between the transceiver **30** and the convective surface area.

The heat-dissipation module **10** can be fabricated from a metal extrusion or from sheet metal. The heat-dissipation module **10** can be made of aluminum, copper, steel, or some composite of these materials; however, any material that has high electrical and thermal conductivity can be used. A coating or surface treatment can be applied to the material forming the heat-dissipation module **10**. Electrical conductivity is important because the heat sink **12** can help provide electromagnetic shielding to reduce electromagnetic interference (EMI) between the many transceivers **30** that can populate an electrical rack and to reduce stray EMI outside of the rack to acceptable levels. To provide adequate EMI shielding, gaps between the webbing of the heat sink **12** should be less than a quarter of the shortest wavelength of interest in the radiated electromagnetic energy spectrum. For a system operating at 28 Gbps the EMI is predominately emitted up to a frequency of 14 GHz, so that a gap between the web elements can be approximately 5 mm or less. For units with higher frequencies of interest, the gaps can be proportionally smaller to achieve a similar level of shielding. The depth *d* of the heat sink **12** should be adequate to completely cover the electrical connection into the PCB **50** to provide effective EMI shielding and provide for adequate heat transfer. Thermal modeling indicates that the depth *d* is preferably between 20 mm and 60 mm, although shorter and longer depths can be used. The height *h* of the heat sink **12** can also be chosen to provide adequate heat transfer as well

as a compact design so that the belly-to-belly transceiver configuration shown in FIG. **2A** can be mounted in a 1 U (1 U=1 rack unit=1.75" high) rack opening. Thermal modeling indicates that a height *h* of approximately 18 mm should provide adequate thermal dissipation and fit within a 1U rack opening. Smaller or larger heights *h* can be used, for example, if the system is designed to fit into a 2U rack opening or to accommodate different connector or transceiver sizes in different configurations.

FIG. **4** shows a rack mount **60** with a belly-to-belly configuration. Upper and lower connectors **20a**, **20b** are mounted to the top and bottom of PCB **50**, respectively. The upper connector **20a** provides electrical paths between the upper transceiver **30a** and PCB **50**. Similarly, the lower connector **20b** provides electrical paths between the lower transceiver **30b** and the PCB **50**. These electrical paths can use one or more central conductors surrounded as much as possible by an electrically grounded shield to maximize transmission and minimize distortion of high bandwidth signals transmitted along the electrical connectors. Both the upper and lower transceivers **30a**, **30b** are pluggable and can mate and unmate with their respective electrical connector **20a**, **20b**. Upper and lower cables **31a**, **31b** are attached to the upper and lower transceivers **30a**, **30b**, respectively. These cables **31a**, **31b** transmit and/or receive data.

Also shown in FIG. **4** are two springs **14a**, **14b**. The springs **14a**, **14b** ensure robust physical contact between the heat sink **12a**, **12b** and the transceivers **30a**, **30b**, which are the major heat generating components. The springs **14a**, **14b** force the upper and lower transceivers **30a**, **30b** against their respective heat sinks **12a**, **12b**. This ensures a low-impedance thermal path between the transceivers **30a**, **30b** and the heat sinks **12a**, **12b**, minimizing the operational temperature of the transceivers **30a**, **30b**. It is generally desirable to operate the transceivers **30a**, **30b** at temperatures as close to room temperature as possible. Operating temperatures equal or less than 30° C. above an ambient data center environment are generally acceptable. Thermal modeling has indicated that the design shown in FIG. **4** provides heat dissipation well in excess of this requirement. The modeling indicates that the transceiver operating temperature can be approximately 6° C. above ambient for a 5 watt heat load from each transceiver **30a**, **30b**. Providing better cooling and a lower transceiver operating temperature advantageously increases the operating lifetime of any laser diodes in the upper and lower transceivers **30a**, **30b**. While the springs **14a**, **14b** are shown as leaf springs in FIG. **4**, the springs **14a**, **14b** can take many forms, or the force between the transceivers **30a**, **30b** and heat sinks **12a**, **12b** can be provided by some other mechanism that ensures robust physical contact between the transceivers **30a**, **30b** and the heat sink **12a**, **12b**.

An advantage of the belly-to-belly configuration shown in FIG. **4** is that both the upper and lower transceiver **30a**, **30b** are located adjacent to the PCB **50** such that the electrical paths between the transceivers **30a**, **30b** and PCB **50** is short. This allows transmission of high-bandwidth signals with minimal loss and interference. However, other suitable configurations can be used. Although upper and lower connectors **20a**, **20b** are shown as PCB mounted board connectors, connectors **20**, **20b** can also be cable connectors that include cable connectors as shown in FIG. **8**.

FIGS. **5A-5C** show alternative stacked configurations. In these stacked configurations, the lower transceiver **30b** is adjacent to the PCB **50**, and the upper transceiver **30a** is positioned above the lower transceiver **30b** farther from the

PCB 50. The upper and lower transceivers 30a, 30b are connected to upper and lower cables 31a, 31b, respectively.

As shown in FIGS. 5A and 5B, the lower connector 20b can be identical or similar to the lower connector 20b in FIG. 4 in which the lower connector 20b is directly connected to the PCB 50. In FIG. 5A, above the lower transceiver 30b is a lower heat sink 12b, which serves to dissipate heat generated in the lower transceiver 30b. A lower spring 14b forces the lower transceiver 30b against the lower heat sink 12b, ensuring a low impedance thermal path between them. An upper spring 14a, which can be identical or different than the lower spring 14b, is positioned between the lower heat sink 12b and the upper transceiver 30a. The upper spring 14a can also be positioned so it is fully contained into the heat-dissipation module 10. The upper spring 14a forces the upper transceiver 30a against the upper heat sink 12a, ensuring a low impedance thermal path between them. The upper heat sink 12a serves to dissipate heat generated in the upper transceiver 30a. An upper connector 20a mates with the upper transceiver 30a. Flyover cables 22 provide an electrical path between the upper connector 20a and the PCB 50. The cables 22 can be any suitable shielded electrical connections, including one or more coaxial, or twin axial cables. The cables 22 can be rigid, semi-rigid, or flexible. Flexible twin axial, i.e. twinax, cable is preferably used because it readily allows propagation of differential high-speed electrical signals and can be easily routed to any location on the PCB 50 with minimal loss and distortion. The cables 22 can fly over the PCB 50 as described in commonly assigned U.S. provisional patent application 62/131,989, which is hereby incorporated by reference in its entirety. An advantage of the stacked configuration is that all the high-speed electrical connections can be made on a single side of the PCB 50. Also, the component height on the PCB 50 can be approximately twice as high compared to that available in the belly-to-belly configuration. Another advantage of this preferred embodiment is that both the upper and lower heat sinks 12b can be formed monolithically in a single extrusion step.

In FIGS. 5B and 5C, the heat-dissipation module 10 includes a single heat sink 12. A lower spring 14b forces the lower transceiver 30b against the heat sink 12, ensuring a low impedance thermal path between them, and an upper spring 14a, which can be identical or different than the lower spring 14b, forces the upper transceiver 30a against the heat sink 12, ensuring a low impedance thermal path between them. In FIG. 5B, the lower connector 20b is connected directly to the PCB 50, and the upper connector 20a is connected to the PCB 50 by cables 22. In FIG. 5C, the lower connector 20b is connected to the PCB 50 by cables 22b, and the upper connector 20a is connected to the PCB 50 by cables 22a. It is also possible that the lower connector 20b includes some electrical paths that are directly connected to the PCB 50 as shown in FIG. 5B and some electrical paths that are connected to the PCB 50 by cables 22b as shown in FIG. 5C.

FIG. 6 shows a portion of a rack mount 60 with a belly-to-belly configuration with connectors 20a, 20b attached to heat sinks 12a, 12b. This preferred embodiment is similar to that shown FIG. 4, and so, only the differences between the figures will be described. A difference between the preferred embodiment shown in FIG. 4 and the preferred embodiment shown in FIG. 6 is the mounting of the connectors 20a, 20b. In FIG. 4, the connectors 20a, 20b are connected directly to the PCB 50. As mentioned above, this has the advantage of providing a short, rigid electrical path between the connectors 20a, 20b and the PCB 50. However,

this fixed, rigid mounting can result in an unfavorable tolerance stack up. In some cases it can be difficult to force the transceivers 30a, 30b to be flush with the heat sinks 12a, 12b while they are simultaneously mating with the connectors 20a, 20b. The preferred embodiment shown in FIG. 6 solves this problem. In FIG. 6, the upper and lower connectors 20a, 20b are mounted on the upper and lower heat sinks 12a, 12b, respectively. The upper and lower connectors 20a, 20b can be mounted to surfaces 19a, 19b of heat sinks 12a, 12b so that the upper and lower connectors 20a, 20b can move in directions parallel to surfaces 19a, 19b of the heat sinks 12a, 12b. Similarly the connectors 20a, 20b can be mounted within the length of the heat dissipation module 10 in such a way, with guides or grooves for examples but not so limited, that the connectors 20a, 20b are free to move in a direction parallel or substantially parallel to surface 19a, 19b of the heat sinks 12a, 12b. The connectors 20a, 20b in FIG. 6 are, however, constrained in a direction parallel or substantially parallel to the insertion direction of the transceivers 30a, 30b, which is perpendicular or substantially perpendicular to surfaces 19a, 19b. This mounting configuration allows the connectors 20a, 20b to float in directions perpendicular or substantially perpendicular to the transceiver mating direction, but be rigidly constrained in the mating direction. Because the connectors 20a, 20b can float in a vertical direction, the springs 14a, 14b can force the transceivers 30a, 30b against their respective heat sinks 12a, 12b with little concern for possible lack of contact between the transceivers 30a, 30b and heat sinks 12a, 12b because of tolerance stack up. Because the upper and lower connector positions relative to the PCB 50 in this preferred embodiment are no longer fixed, cables 22a, 22b similar to those described in relation to FIG. 5C can be used to provide the electrical paths between the connectors 20a, 20b and PCB 50. It is also possible that the connectors 20a, 20b can include some electrical paths that are directly connected to the PCB 50 as shown in FIG. 4 and some electrical paths that are connected to the PCB 50 by cables 22a, 22b as shown in FIG. 6.

Further configurations are possible. Both the belly-to-belly configuration shown in FIGS. 1, 2, 4, and 6 and the stacked configuration shown in FIGS. 5A-5C have the major surfaces, i.e., surfaces with the largest surface areas, of the transceivers 30, 30a, 30b parallel or substantially parallel to the plane of the PCB 50. This is not a requirement. The major surfaces of the transceivers 30, 30a, 30b can be oriented perpendicular or substantially perpendicular within manufacturing tolerances to the PCB plane. In this case, a flyover style electrical connection can be made to the PCB 50 as described in commonly assigned U.S. patent application No. 62/136,059, 62/107,671, and Ser. No. 14/845,990, which are each hereby incorporated by reference in their entirety. In these perpendicular configurations, heat sinks can be provided adjacent at least one of the major surfaces of the transceivers. In the stacked configuration, the position of the upper transceiver 30a and the upper heat sink 12a can be reversed, so that the lower and upper heat sinks 12b, 12a are adjacent to each other. Depending on the PCB component layout, these various configurations can be mixed and matched in any system to achieve an optimal layout to maximize signal integrity, thermal performance, density or other metrics, or any combinations thereof, for all channels in the communication network.

As previously mentioned, a heat-dissipation module 10 can be formed from sheet metal. FIG. 7 shows a sheet-metal heat-dissipation module 10. The overall layout is similar to that shown for an extruded heat-dissipation module 10

13

shown in FIG. 3. The heat-dissipation module 10 has a number of slots 11 to accept transceivers 30. Surrounding each slot 11 is a cage 16 to minimize EMI between the transceivers 30 and any circuitry. A heat spreader 13 is adjacent the top of the cage 16. The heat spreader 13 can be formed from a solid piece of metal and serves to distribute heat generated by transceivers 30 (not shown in FIG. 7) to the heat sink 12. The heat sink 12 can be formed from a web of bent-and-cut sheet metal. In FIG. 7, the web is shown as having square openings to allow air passage through the heat sink 12. As previously described, air passages of other shapes can be used. The heat-dissipation module 10 has a plurality of mounting pins 17 which connect to a PCB (not shown in FIG. 7). The sheet-metal heat-dissipation module 10 can be arranged in any of the above-described preferred embodiments. An advantage of the sheet metal formed heat-dissipation module 10 is that it can be cheaper and easier to manufacture than an extruded heat-dissipation module 10.

Instead of optical transceivers, electrical transceivers can be used. Also independent transmitters and/or receivers can be used instead of a transceiver. The placement of various components in the system can also be varied. For example, FIG. 4 shows the non-mating ends of the upper and lower transceivers 30a, 30b substantially flush with the end of the PCB 50. This is not a requirement. The transceivers can extend past the end of the PCB 50 or be recessed such that the end of the PCB 50 extends past the transceiver ends. The component placement has often been described in terms of an upper and lower component. It should be appreciated that these terms are relative to the PCB mounting orientation and can be exchanged or substituted by left/right depending on the orientation.

Preferred embodiments of the present invention also include a receptacle that can receive one or more transceivers and that includes a cage and electrical connectors in the cage. The electrical connectors can include both high- and low-speed cables that flyover a PCB to different locations on the PCB. Using low-speed cables provides additional space between the slots in a multi-slot cage, which allows increased airflow between the transceivers, improving cooling and heat management of the transceivers. The electrical connectors can be plugged into the rear of the cage. The electrical connectors can include latches that engage with latch slots in the cage. A blower can be used to improve cooling. Heat sinks (with or without forced air) can be provided in the extra space to improve cooling. A fluid-cooled heat sink, such as a heat pipe, can be provided in the extra space to further improve cooling.

An electrical-connector removal tool can be inserted into the front of the cage assembly to remove an electrical connector from the cage.

FIG. 8 shows a receptacle 100 according to a preferred embodiment to the present invention. The receptacle 100 includes a cage 116 with four slots 111 arranged in two rows. Each slot 111 can accept one transceiver 130. FIG. 8 shows three slots 111 mated with three transceivers 130 and one slot 111 that is empty. The bottom of the cage 116 includes mounting pins 116 that allow the receptacle 100 to be mounted to a PCB (not shown in FIG. 8). The receptacle 100 can include an optional a faceplate 119 between the upper and lower slots 111. The faceplate 119 can include a plurality of openings or louvers that allow air flow through the faceplate 119, through passageway 107 (FIG. 19), between receptacle connectors 120 (FIG. 19), and over cables 122. Stated another way, the openings or louvers are fluidly connected to an opening defined by the passageway 107

14

between receptacle connectors 120. The passageway 107 can extend from the first end to the second end and can be positioned adjacent to one of the two receptacle connectors. Air can also flow over the cables 122, between the receptacle connectors 120, through the passageway 107, and through the faceplate 119. In non-forced air systems, heat can escape from the passageway 107 through the first and second ends or through the faceplate 119 openings and a second-end opening positioned between the receptacle connectors 120. Stated another way, heat in the passageway can travel through the passageway 107 parallel to the transceiver-mating direction and escape through the first and second ends. The passageway 107 can be positioned adjacent and parallel to one of the slots 111, positioned between and parallel to two adjacent slots 111, or be positioned adjacent and parallel to at least one receptacle connector 120. The cage 116 can include a plurality of electromagnetic interference (EMI) shields 118 around its perimeter to limit radiated EM fields. The height of the cage 116 assembly can be compatible with mounting cage 116 and attached PCB within a 1 U rack opening. The receptacle 100 can be mounted in an electronics rack. The receptacle 100 includes cables 122 that extend from the rear of the cage 116. The cables 122 can transmit both high and low speed signals between the receptacle 100 and a PCB.

The transceiver 130 includes a cable 131 that transmit signals to and from the transceiver 130. The transceiver 130 can include a pull tab 132 that can be used to remove the transceiver 130 from the receptacle 130. The cables 131 flyover the PCB. The benefits of using of flyover cables for high-speed signals is described in commonly assigned U.S. patent application No. 62/136,059, 62/107,671, and Ser. No. 14/845,990.

FIG. 9 shows a transceiver 130 and receptacle connector 120. The receptacle connector 120 is located within the cage 116 shown in FIG. 8. The transceiver 130 is mated to the receptacle 100 by inserting the transceiver 130 into the receptacle 100 such that the edge card 134 is inserted into the receptacle connector 120. The cables 122 extend from the rear of the receptacle connector 120. The cables 122 can be terminated to contacts in the receptacle connector 120 and to the PCB, creating an electrical path between the receptacle connector 120 and the PCB. The transceiver 130 can use one of many industry standard transceiver formats such as QSFP+, PCIe, CXP, CFP, SFP, etc. In particular, the transceiver 30 can meet the requirements of SFF-8438 (INF-8438i, Rev. 1.0).

FIG. 10 shows a receptacle connector 120 being plugged into the rear of the cage 116. FIGS. 11-13 show the receptacle connector 120. The receptacle includes a clip 128, a lead frame 124, and a housing 125. The housing 120 can be made of any suitable electrically insulating material, such as molded plastic. The lead frame 124 is inserted into the housing 120 and is kept in place with the clip 128. The lead frame 124 includes an overmold over the cables 122 and the contacts 123a, 123b. The upper contacts 123a mate with electrical lands on the top of the edge card 134 of the transceiver 130, and the lower contacts 123b mate with electrical lands on the bottom of the edge card 134 of the transceiver 130. Any number of contacts 123a, 123b can be used. It is also possible to only use the upper contacts 123a or the lower contacts 123b.

The clip 128 includes latches 121. When the receptacle connector 120 is inserted into the cage 116, the latches 121 engage with latch slots 103 in the cage 116. Although FIG. 11 shows two latches 121 on top and two latches 121 on bottom, any number and any location of latches 121 can be

15

used. The clip **128** can also include openings **129** that engage with bosses **126** on the housing **125** when the clip **128** is connected to the housing **125**. The clip **128** can be made of stamped and formed sheet metal. The clip **121** can include one or more openings for the cables **122**.

As shown in FIG. **13**, the cables **122** can include high-speed cables **122a** and low-speed cables **122b**. Any number of high-speed **122a** and low-speed cables **122b** can be used. The high speed cables **122a** can transmit, for example, high-bandwidth signals in excess of 10 Gbps and can include, for example, twinax, coax, triax, or some other suitable electrical transmission line. In some applications, high speed is at least 25 Gbits/sec data transmission speed, and low speed is less than 25 Gbits/sec data transmission speed. Low-speed cables **122b** can transmit, for example, control signals and power and can include, for example, an insulated wire without a ground shield. One end of the cables **122a**, **122b** can be terminated to a corresponding contact **123a**, **123b**, the other end of the cables can be terminated to the PCB. If the cables **122a** are twinax, then the two center conductors of the twinax can be terminated to adjacent signal contacts and the shield can be connected to a ground contact(s).

FIG. **14** shows an alternative receptacle connector **120** that includes a PCB assembly (PCBA) **127**. PCBA **127** can include electrical components that provide signal and/or power conditioning and/or filtering. PCBA **127** can improve the performance and simplify the design of the transceiver **130** because the power and control signals will have less electrical noise.

FIGS. **15**, **19**, and **20** show the cage **116**. The cage **116** can include mounting pins **117** that can be used to mount the cage **116** to a PCB (a PCB is not shown in FIG. **15**). The mounting pins **117** can be "eye-of-the-needle" type suitable for press-fit mounting. The receptacle connectors **120** do not need to have any mounting pins, including, for example, press-fit pins, through-hole pins, surface-mount pins, etc., to mount the receptacle connector **120** to the PCB. The cage **116** includes walls **106** that define slots **111**. Although four slots **111** in a 2x2 array are shown in FIG. **15**, the cage **116** can include any number of slots **111** in any arrangement. For example, the cage **116** can have two slots arranged in 1x2 array (horizontally spaced along a substrate) or in a 2x1 array (vertically stacked with respect to a substrate). The walls **106** can include latches **104** that engage the transceiver **130** when the transceiver **130** is mated with the receptacle **100**. Similar to springs **14a**, **14b** in FIGS. **4-6**, each slot **111** could include one or more springs to press the transceiver **130** toward the passage **107** to ensure robust physical contact between the transceiver **130** and the passage **107**. The cage **116** can be made in any suitable manner, including being made of stamped and formed metal.

As shown in FIG. **19**, the cage **116** also includes a passage **107** that provides an air-flow path. The passage **107** allows air to flow between the front of the receptacle **100** (where the transceivers **130** can be plugged in) and the rear of the receptacle **100** (where the receptacle connectors **120** are plugged in). When transceivers **130** are plugged into the top and bottom slots **111** in the receptacle, air can flow between the top and bottom transceivers **130** and from front to back (or back to front) of the receptacle, cooling the heat-producing transceivers **130**. The front of the passage **107** can include a faceplate **119** (faceplate **119** is not shown in FIG. **15** but is shown in FIGS. **19** and **20**), and the rear of the passage **107** can be uncovered. By not using wafers, the receptacle connectors **120** can be arranged to not block or to minimize impeding the air flow completely through both

16

opposed ends of the passage **107** such that air passes fluidly through the faceplate **119**, through the passage **107**, and between the receptacle connectors **120**. The cables **122** can be arranged to not block or impede air flow. In addition to not blocking air flow, the cables **122** provide better signal integrity than that the wafers **222** used in the known receptacle **205**. Thus, an air-flow path from the front to the back (or from the back to the front as described above) of the receptacle **100** can be provided.

Instead of having an open passage **107** as shown in FIGS. **15**, **19**, and **20**, the passage **107** could include heat-transferring fins similar to the fins **171** shown in FIG. **26** that extend from the wall adjacent to the transceiver **130** into the interior of the passage **107** or could include a heat sink such as heat sink **162** shown in FIG. **25**. The hexagonal pattern of such can provide multiple air paths from the front to the back of the receptacle **100**. The webbing could have a constant thickness or could have a variable thickness. For example, the webbing could be thicker at the top and bottom and thinner near the middle.

The cage **116** can include a light pipe **105** in the passage **107**. As shown in FIG. **15**, each passage **107** can include two light pipes **105**. The light pipes **105** can transmit light from an LED on a PCB to the front of the receptacle **100**. The cross-sectional area of the light pipes **105** is preferably less than 15% of the total cross-sectional area of the passage **107**. For example, a passage **107** can have a cross-sectional area of 450 mm<sup>2</sup>, and the light pipes **105** can have a cross-sectional area of 25 mm<sup>2</sup>. If there are two light pipes **105** per passage **107**, then the total cross-section of the two light pipes is 50 mm<sup>2</sup>, which is about 11% of the total cross-sectional area of the passage **107**.

The cage **116** of FIG. **15** can be used with the stacked configurations shown in FIGS. **5B** and **5C**. If the receptacle connectors **120** include cables **122**, then the cage **116** can be used in the stacked configuration shown in FIG. **5C**. If the bottom receptacle connector **120** provides direct electrical paths to the PCB, then the cage **116** can be used in the stacked configuration shown in FIG. **5B**. Other configurations are also possible. For example, if the bottom receptacle connectors **120** includes cables **122** and direct electrical paths to the PCB, then the cage **116** can be used in a stacked configuration that is a combination of FIGS. **5B** and **5C**.

FIG. **25** shows receptacle **100** with a cage **166**. Cage **166** is similar to cage **116** but includes a heat sink **162** in the passage **107** and is double walled. The heat sink **162** extends along the passage **107**. The front opening of the passage **107** can be covered by faceplate **119**, and the rear opening of the passage can be covered by faceplate **169**. It is not necessary to use faceplates **119**, **169** separate from the heat sink **162**. It possible that the faceplates **119**, **169** are part of the heat sink **162**. The heat sink **162** can be similar to the heat sink **12** shown in FIG. **3** with, for example, hexagonal webbing. Other webbing patterns are also possible. The heat sink **162** defines air flow paths between the front and rear of the passage **107**.

The cage **166** includes four slots **111** arranged in a 2x2 array. Other numbers and arrangements of slots **111** can also be used. The two columns of slots **111** are separated by an interior double wall defining a passage between the columns of slots **111**. The opening of the passage between the interior double walls is covered by faceplate **168** with holes. The faceplate plate **168** can be separate from faceplate **119** or can be connected to faceplate **119** as a single unitary body. The size and shape of the holes in faceplate **168** can be the same or can be different from the holes in faceplate **119**. Holes **167** are arranged in the top of the cage **166** along the passage

between the interior double walls. The size and shape of holes **167** can be the same as or can be different from the size and shape of the holes in the faceplate **168**.

As shown in FIG. **25**, the exterior walls of the cage **166** can be a double wall. Only one exterior double wall is shown in FIG. **25** because FIG. **25** is a sectional view. As with the interior double wall, the exterior double walls can be covered by a faceplate **168** with holes and can include holes **167** along the top of the cage **166**. Holes in faceplate **168** can be fluidly connected to a cavity between adjacent slots **111**. The cavity can extend from the faceplate **168**, through the cage **166**, and to the optional rear faceplate **169**. Alternatively, or in addition, holes in faceplate **168** can be fluidly connected to holes **167**. The exterior double walls can include holes **167** (not shown in FIG. **35** but shown in FIG. **27**) adjacent to passages **107** to provide air flow through the exterior double walls and at the bottom of the exterior double wall to provide air flow at the bottom of the exterior double wall. The interior double walls can include similarly arranged holes. Although not shown in FIG. **25**, it is possible to add top and bottom exterior double walls to cage **166** so that each slot **111** has passages on four sides.

FIG. **26** shows receptacle **100** with cage **116**. Cage **116** in FIG. **26** includes fins **171** extending into the passage **107**. Fins **171** can help in transferring heat from transceivers in the slots **111** to the passage **107**. Any number, size, and shape of fins **171** can be used. The faceplate **119** in FIG. **26** includes a hole through which the light pipe **105** extends. The end of the light pipe **105** can be flush or substantially flush with the front of the receptacle **100**.

FIGS. **27-29** show receptacle **100** with cage **166**. Cage **166** in FIGS. **27-29** is similar to cage **166** shown in FIG. **25** but without the heat sink **162**. In FIG. **27**, the cage **166** includes faceplates **119**, **168**, and in FIG. **28**, the cage **166** is without faceplates **119**, **168**. FIG. **28** shows light pipes **105** in the interior and exterior double walls. Although FIG. **28** shows four light pipes **105** (two in one exterior double wall and two in the interior double wall), any number and any arrangement of light pipes **105** can be used. The cage **166** includes two exterior double walls and one interior double wall. Cage **166** can include double walls that extend across the top and bottom of the cage **166**. A different arrangement of double walls could be used with a different array of slots **111**. For example, a 2x3 array of slots **112** could include two interior double walls and two exterior double walls. As shown in FIG. **28**, the double walls, both interior and exterior, can include holes **167** adjacent to passage **107**. The double walls can also include holes **167** near the bottom of the double walls. The top of the cage **166** can also include holes **167** over the passages defined by the double walls. Although not shown in FIG. **28**, the passage **107** could also include fins similar to fins **171** in FIG. **26**.

FIG. **29** shows two rear faceplates **169**. Any number and any arrangement of faceplates **169** can be used depending on the arrangement of the slots **111**. The size and shape of the holes can be the same as or can be different from the size and shape of the holes in the faceplates **119**, **168**.

Air can be forced through passage **107** to increase the cooling of the transceivers **130**. If the receptacle **100** is included on a rack mount in an electronics rack, then a fan mounted on the rack mount or in the electronics rack can force air through the passage **107**. It is also possible, that as shown in FIG. **17**, the receptacle **100** includes a blower **140** attached to the cage **116**. FIG. **18** shows the blower **140**. The blower **140** includes a guide **141** to direct the blown air. As shown in FIG. **18**, the blower **140** can receive air in direction C and blow the air out in direction D through guide **141** into

holes in the outer wall of the cage **116**. Each of the three fingers of the guide **141** can direct air into one of the passages **107** connected to the top, middle, and bottom faceplates **119a**, **119b**, **119c**. In this manner, blower **140** can blow ambient air through the passages **107** and over the transceivers **130**. The blower **140** can also blow air in the opposite direction, from within the receptacle **100** to the outside ambient air. The blower **140** can also be used, possibly with ducting, if there is a heat sink in the passage **107**. Any suitable blower can be used. The blower **140** could be a 30-mm diameter fan with rotating blades, a piezoelectric actuated fan, a corona (ion) fan, etc. Instead of being mounted to the exterior of the cage **116**, the blower **140** could be mounted within one or more of the passages **107**.

In addition to blower **140**, FIG. **17** also shows other possible arrangements of the receptacle **100**. For example, the slots **111** can be arranged in a 2x4 array so that the receptacle can receive eight total transceivers **130**. Instead of a single faceplate **119**, the receptacle **100** can include a top faceplate **119a**, a middle faceplate **119b**, and a bottom faceplate **119c**. Each faceplate **119a**, **119b**, and **119c** covers a separate passage that allows air to flow from front to back (or back to front) of the receptacle **100**. This arrangement is similar to the stacked arrangement shown in FIG. **5A** but with an additional heat sink located between the PCB **50** and the lower transceiver **30b** and lower connector **20b**. In such an arrangement, the lower connector **20b** would include cables **22b** to provide electrical paths from the lower connector **20b** and the PCB **50**.

If the cages **116** shown in FIGS. **8** and **17** are the same height, then the slots **111** in FIG. **17** are closer together than the slots **111** in FIG. **8**.

The cage can include a liquid-filled heat pipe that facilitates heat transfer away from transceiver mated with the cage. The heat pipe can be used to spread the heat from localized heat sources, such as the optical engine of the transceiver **130**. For example, the heat spreader **13** shown in FIG. **7** can include a heat pipe to facilitate heat transfer between a transceiver in the slot **11** and the heat sink **12**. The heat pipe allows the thickness of the heat spreader to be reduced, reducing weight and increasing the available area for the heat sink.

FIG. **16** shows a receptacle-connector removal tool **190**. To remove a receptacle connector **120**, the receptacle-connector removal tool **190** is inserted into a slot **111** from the front side of the cage **116** as shown, for example, in FIG. **26**. Upper beveled surface **191a** and lower beveled surface **191b** elastically deform the clip **128** so that latches **121** disengage from the latch slots **103**. Continuing to push receptacle-connector removal tool **190** into slot **111** will push the receptacle connector **120** out of the back the cage **116**. The ability to rework or replace a receptacle connector **120** with a simple tool provides flexibility and ease in system maintenance and debugging. No desoldering of any connection is required to remove receptacle connector **120**, and thus there is little chance of inadvertent damage during the removal operation.

It should be understood that the foregoing description is only illustrative of the present invention. Various alternatives and modifications can be devised by those skilled in the art without departing from the present invention. Accordingly, the present invention is intended to embrace all such alternatives, modifications, and variances that fall within the scope of the appended claims.

19

What is claimed is:

**1.** An electrical connector comprising:

a heat dissipation module with a first end and a second end opposed to the first end; and

two receptacle connectors that are located at the second end and that are vertically stacked in relation to a base substrate; wherein

the first and second ends define a transceiver-mating direction such that, when a transceiver is inserted into the first end of the heat dissipation module in the transceiver-mating direction, the transceiver mates with one of the two receptacle connectors;

the heat dissipation module includes a passage that extends between the first and second ends and that is located between the two receptacle connectors; and in the passage, air flows unblocked parallel to the transceiver-mating direction between the first and second ends and flows unblocked between the two receptacle connectors.

**2.** The electrical connector of claim 1, wherein the two receptacle connectors each receive a card-edge of a mating transceiver.

**3.** The electrical connector of claim 1, wherein the heat dissipation module includes a cage, and the cage defines two slots that extend between the first and second ends, and the air flows between the two slots.

**4.** The electrical connector of claim 3, wherein only the cage is configured to be press-fit or surface mounted to the base substrate.

**5.** The electrical connector of claim 1, wherein the two receptacle connectors are electrically isolated from one another.

**6.** The electrical connector of claim 1, wherein the passage includes a heat sink located between the two receptacle connectors.

**7.** The electrical connector of claim 6, wherein the heat sink includes an extruded metal or bent sheet metal.

**8.** The electrical connector of claim 6, wherein the heat sink defines air flow paths.

**9.** The electrical connector of claim 6, wherein the heat sink is mounted to the cage such that a position of the heat sink is fixed when the transceiver is mated with the one of the two receptacle connectors.

**10.** The electrical connector of claim 6, wherein channels in the heat sink are no larger than one quarter of a wavelength of a dominant emitted electromagnetic interference generated, when the transceiver is mated with the electrical connector, by electrical signals transmitted and/or received by the transceiver.

**11.** The electrical connector of claim 6, wherein a blower is mounted adjacent to the heat sink such that the blower directs forced air over the heat sink.

**12.** The electrical connector of claim 1, wherein air flows in one or more air-flow paths in the passage between the two receptacle connectors.

**13.** The electrical connector of claim 1, wherein the two receptacle connectors each comprise:

a housing;

high-speed and low-speed electrical contacts in the housing;

high-speed cables electrically connected to the high-speed electrical contacts; and

low-speed cables directly attached and electrically connected to the low-speed electrical contacts.

**14.** The electrical connector of claim 13, wherein high-speed is at least 25 Gbits/sec data transmission speed.

20

**15.** The electrical connector of claim 13, wherein low-speed is less than 25 Gbits/sec data transmission speed.

**16.** The electrical connector of claim 13, further comprising a power filter electrically attached to the low-speed electrical contacts.

**17.** The electrical connector of claim 13, further comprising a receptacle connector located within the housing and having an at least 25 Gbits/sec data transmission speed.

**18.** A rack mount including an electrical connector of claim 1.

**19.** An electronics enclosure comprising one or more rack mounts of claim 18.

**20.** A system comprising:

a base substrate; and

the electrical connector of claim 1 attached to the base substrate.

**21.** The electrical connector of claim 1, wherein:

the two receptacle connectors include upper and lower receptacle connectors;

an upper flyover cable includes a first end connected to the upper receptacle connector;

a lower flyover cable includes a first end connected to the lower receptacle connector; and

the first end of the upper flyover cable is located farther away from the base substrate than the first end of the lower flyover cable.

**22.** The electrical connector of claim 1, wherein the two receptacle connectors mechanically float in a direction orthogonal or substantially orthogonal to the transceiver-mating direction and do not mechanically float in a direction parallel or substantially parallel to the transceiver-mating direction.

**23.** The electrical connector of claim 1, wherein distances between the two receptacle connectors and the base substrate are allowed to float.

**24.** The electrical connector of claim 1, wherein one of the two receptacle connectors is devoid of press-fit or mounting tails.

**25.** An electrical connector system comprising:

a cage with a first end and a second end opposed to the first end; and

two electrical connectors that are located at the second end and that are vertically stacked in relation to a base substrate; wherein

the first and second ends define a transceiver-mating direction such that when a transceiver is inserted into the first end of the cage in the transceiver-mating direction the transceiver mates with one of the two electrical connectors;

the cage includes a passage that extends between the first and second ends and that is located between the two electrical connectors; and

in the passage, air flows unblocked parallel to the transceiver-mating direction between the first and second ends and flows unblocked between the two electrical connectors.

**26.** The electrical connector system of claim 25, wherein the cage includes press-fit tails.

**27.** The electrical connector system of claim 26, further comprising cables connected to the two electrical connectors.

**28.** The electrical connector system of claim 25, wherein the two electrical connectors are receptacle connectors each comprising a signal conditioner electrically connected to cables.

21

29. The electrical connector system of claim 25, wherein only the cage is configured to be press-fit or surface mounted to the base substrate.

30. A system comprising:  
a base substrate; and  
the electrical connector system of claim 25 attached to the base substrate.

31. The electrical connector system of claim 25, wherein: the two electrical connectors include upper and lower electrical connectors;

an upper flyover cable includes a first end connected to the upper electrical connector;

a lower flyover cable includes a first end connected to the lower electrical connector; and

the first end of the upper flyover cable is located farther away from the base substrate than the first end of the lower flyover cable.

32. The electrical connector system of claim 25, wherein the two electrical connectors mechanically float in a direction orthogonal or substantially orthogonal to the transceiver-mating direction and do not mechanically float in a direction parallel or substantially parallel to the transceiver-mating direction.

33. The electrical connector system of claim 25, wherein distances between the two electrical connectors and the base substrate are allowed to float.

34. The electrical connector system of claim 25, wherein one of the two electrical connectors is devoid of press-fit or mounting tails.

35. A stacked electrical connector and cage compatible with QSFP standards, the stacked electrical connector comprising top and bottom edge-card connectors and a passage that extends between the top and bottom edge-card connectors; wherein

the top and bottom edge-card connectors are devoid of press-fit or mounting tails and  
air flows unblocked in the passage between the top and bottom edge-card connectors.

36. The stacked electrical connector and cage of claim 35, further comprising:

an upper flyover cable that includes a first end connected to the top edge-card connector; and

a lower flyover cable that includes a first end connected to the bottom edge-card connector; wherein

the first end of the upper flyover cable is located above the first end of the lower flyover cable.

37. The stacked electrical connector and cage of claim 35, wherein the top and bottom edge-card connectors mechanically float in a direction orthogonal or substantially orthogonal to a transceiver-mating direction defined by first and

22

second ends of the passage and do not mechanically float in a direction parallel or substantially parallel to the transceiver-mating direction.

38. The stacked electrical connector and cage of claim 35, wherein distances between the top and bottom edge-card connectors and the base substrate are allowed to float.

39. An electrical connector comprising:  
a heat dissipation module with a first end and a second end opposed to the first end;

two receptacle connectors that are located at the second end and that are vertically stacked in relation to a base substrate; and

a passageway that extends from the first end to the second end and that is located between the two receptacle connectors; wherein

the first and second ends define a transceiver-mating direction such that, when a transceiver is inserted into the first end of the heat dissipation module in the transceiver-mating direction, the transceiver mates with one of the two receptacle connectors; and

in the heat dissipation module, heat in the passageway travels unblocked through the passageway parallel to the transceiver-mating direction and escapes unblocked through the first and second ends.

40. A system comprising:  
a base substrate; and  
the electrical connector of claim 39 attached to the base substrate.

41. The electrical connector of claim 39, wherein: the two receptacle connectors include upper and lower receptacle connectors;

an upper flyover cable includes a first end connected to the upper receptacle connector;

a lower flyover cable includes a first end connected to the lower receptacle connector; and

the first end of the upper flyover cable is located farther away from the base substrate than the first end of the lower flyover cable.

42. The electrical connector of claim 39, wherein the two receptacle connectors mechanically float in a direction orthogonal or substantially orthogonal to the transceiver-mating direction and do not mechanically float in a direction parallel or substantially parallel to the transceiver-mating direction.

43. The electrical connector of claim 39, wherein distances between the two receptacle connectors and a base substrate are allowed to float.

44. The electrical connector of claim 39, wherein one of the two receptacle connectors is devoid of press-fit or mounting tails.

\* \* \* \* \*