



(86) Date de dépôt PCT/PCT Filing Date: 2012/08/30
(87) Date publication PCT/PCT Publication Date: 2013/04/11
(85) Entrée phase nationale/National Entry: 2014/04/04
(86) N° demande PCT/PCT Application No.: US 2012/053131
(87) N° publication PCT/PCT Publication No.: 2013/052219
(30) Priorité/Priority: 2011/10/06 (US13/267,264)

(51) Cl.Int./Int.Cl. *B65D 41/32* (2006.01)
(71) Demandeur/Applicant:
WORLD BOTTLING CAP, LLC, US
(72) Inventeur/Inventor:
FRISHMAN, ABE, US
(74) Agent: DEETH WILLIAMS WALL LLP

(54) Titre : CAPSULE DE BOUTEILLE A TRACTION FACILE
(54) Title: EASY-PULL BOTTLE CAP




FIG. 13

(57) Abrégé/Abstract:

A crown for a bottle or other container has a top portion and an annular skirt that descends contiguously from the top portion. An opener assembly and an arrangement of frangible scoring lines on the crown allow for ease of opening the bottle or container. Corrugated embodiments provide material strengthening for a reduced gauge crown.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau

(43) International Publication Date
11 April 2013 (11.04.2013)



(10) International Publication Number
WO 2013/052219 A1

(51) International Patent Classification:
B65D 41/32 (2006.01)

(21) International Application Number:
PCT/US2012/053131

(22) International Filing Date:
30 August 2012 (30.08.2012)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
13/267,264 6 October 2011 (06.10.2011) US

(72) Inventor; and

(71) Applicant : FRISHMAN, Abe [US/US]; 2924 Cambridgehire, Carrollton, TX 75007 (US).

(74) Agent: BURR, Matthew, E.; Mwr Legal, 620 Congress Avenue, Ste 320, Austin, TX 78701 (US).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,

BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: EASY-PULL BOTTLE CAP




FIG. 13

(57) Abstract: A crown for a bottle or other container has a top portion and an annular skirt that descends contiguously from the top portion. An opener assembly and an arrangement of frangible scoring lines on the crown allow for ease of opening the bottle or container. Corrugated embodiments provide material strengthening for a reduced gauge crown.

EASY-PULL BOTTLE CAP

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is related to, claims the benefit of and priority from co-pending United States patent application of the same title Serial Number 13/267,264 filed October 6, 2011 entitled EASY-PULL BOTTLE CAP, by Abe Frishman, the disclosures of which is incorporated herein by reference.

FIELD OF THE DISCLOSURE

[0002] The present disclosure relates to caps and crowns for beverage bottles and other containers, and in particular, to a manual pull-to-open bottle cap.

BACKGROUND

[0003] A beverage bottle that opens manually with relative ease, without the use of a bottle opener, has been a long-felt need for beverage providers. Bottle caps must be tightly secured to the bottle opening to prevent spillage of the contents, loss of pressure (in the case of pressurized or carbonated beverages) and to maintain the hygienic conditions of the contents. The tight seal makes it difficult to open a bottle by hand.

[0004] Caps, also referred to interchangeably as crowns, are secured to the bottle opening by crimping the crown down over the open of the container in a series of concave arcs around the circumference of the opening. The arcs create sharp convex points between each concave arc. The arcs and points are often referred to by those skilled in art as “angels.”

[0005] The advent of the familiar twist-off bottle cap was a significant advance for manual bottle opening, but all too frequently one has to grip the cap so hard to twist the cap free that the points of the cap angels inflict pain on the hands or fingers. To protect the hands from injury, it is a common practice to wrap the bottle cap in the tail of a shirt or in a cloth before twisting the cap.

[0006] Bottle caps adapted with pull tabs, similar to those used for beverage cans, have been known in China and other territories of Asia. See, for example, International Patent Application PCT/CN00/00040 by Liu, priority date March 4, 1999, International Publication No. WO00/51906. Such pull tab bottle caps, however, are notoriously difficult to open because they require the exertion of an uncomfortable amount of force to break the seal and then pull the tab back (tearing the metal) to remove the cap.

[0007] Another pull-tab solution for bottle caps is known as the MaxiCrown[®] such as is described U.S. Patent 4,768,667 issued September 6, 1988, to Magnusson. The MaxiCrown[®] provides a pull ring disposed along the side of the neck of the bottle as an extension of the crown and thus is problematic for use with standard angel-crimping bottle capping machines. Indeed, a special capping machine is recommended to cap bottles with the MaxiCrown[®].

[0008] There is a need, therefore, for a bottle crown that is easy to open manually yet which may be tightly sealed around the bottle opening using standard bottle capping machines common in the art.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The detailed description that follows, by way of non-limiting examples of embodiments, makes reference to the noted drawings in which reference numerals represent the same parts throughout the several views of the drawings, and in which:

[0010] **Figure 1** is a diagrammatic representation of a top view of a specific exemplary embodiment of a bottle cap of the prior art.

[0011] **Figure 2A** is a diagrammatic representation of a side view vertical cross-section of a specific exemplary embodiment of a bottle cap of the present disclosure.

[0012] **Figure 2B** is a diagrammatic representation of a side view vertical cross-section of an alternative specific exemplary embodiment of the bottle cap of Fig. 2A.

[0013] **Figure 3A** is a diagrammatic representation of a side view vertical cross-section of an alternative specific exemplary embodiment of a bottle cap of the present disclosure.

[0014] **Figure 3B** is a diagrammatic representation of a side view vertical cross-section of an alternative specific exemplary embodiment of the bottle cap of Fig. 3A.

[0015] **Figure 4** is a diagrammatic representation of a side view vertical cross-section of an alternative specific exemplary embodiment of a bottle cap of the present disclosure.

[0016] **Figure 5** is a diagrammatic illustration of a side view cross-section of an alternative embodiment of a crown of the present disclosure.

[0017] **Figure 6** is a diagrammatic illustration of a side view cross-section of yet another alternative embodiment of a crown of the present disclosure.

[0018] **Figure 7** is a diagrammatic illustration of a side view cross-section of an alternative embodiment of a crown of Fig. 6.

[0019] **Figure 8** is a diagrammatic illustration of a side view cross-section of another alternative embodiment of a crown of the present disclosure.

[0020] **Figure 9** is a diagrammatic illustration of a side view cross-section of still another alternative embodiment of a crown of the present disclosure.

[0021] **Figure 10** is a diagrammatic illustration of a top view of a further alternative embodiment of a crown of the present disclosure.

[0022] **Figure 11** is a diagrammatic illustration of an isometric top view of an alternative embodiment of a crown of the present disclosure.

[0023] **Figure 12** is a diagrammatic illustration of an isometric top view of an alternative embodiment of a crown of Fig. 11.

[0024] **Figure 13** is a diagrammatic illustration of an isometric top view of an alternative embodiment of a crown of Fig. 11.

[0025] **Figure 14** is a diagrammatic illustration of a side cross sectional view of an alternative embodiment of a crown of Fig. 13.

[0026] **Figure 15** is a diagrammatic illustration of a side cross sectional view of an alternative embodiment of a crown of Fig. 14.

[0027] **Figure 16** is a diagrammatic illustration of an isometric top view of an alternative embodiment of a crown of Fig. 13.

[0028] **Figure 17** is a diagrammatic illustration of a top view of an alternative embodiment of a crown of Fig. 13.

[0029] **Figure 18A** is a diagrammatic illustration of a side cross section view of an embodiment of a cut line of the present disclosure.

[0030] **Figure 18B** is a diagrammatic illustration of a side cross section view of an alternative embodiment of a cut line of Fig. 18A.

[0031] **Figure 18C** is a diagrammatic illustration of a side cross section view of an alternative embodiment of a cut line of Fig. 18A.

[0032] **Figure 19** is a diagrammatic illustration of an isometric view of the bottom of a crown of the present disclosure.

[0033] **Figures 20A – 20E** are top view schematic illustrations of alternative embodiments of a crown of the present disclosure each embodiment having a curvilinear left score line extending from the center of the top of the crown to the annular edge of the crown.

[0034] **Figure 21** is a top view schematic representation of an alternative embodiment of a crown of the present disclosure illustrating an off-center location for the pull tab.

[0035] **Figure 22** is a top view schematic representation of an alternative embodiment of the crown of Fig. 21 with an alternative score line.

[0036] **Figure 23** is a top view schematic representation of an alternative embodiment of the crown of Fig. 21 with another alternative score line.

[0037] **Figure 24** is an isometric view schematic representation of an alternative embodiment of a crown of the present disclosure having no crimping angels.

[0038] **Figure 25A** is a cross-section schematic illustration of an unbroken score line of a crown of the present disclosure.

[0038] **Figure 25B** is a cross-section schematic illustration of a broken score line of the embodiment of Fig. 24A.

[0039] **Figure 26** is an isometric side view illustration of a reduced gauge crown of the present invention.

[0040] **Figure 27A** is a top view illustration of the crown of Fig. 26.

[0041] **Figure 27B** is a side cross-section view of the crown of Fig. 27A.

[0042] **Figure 28A** is a top view illustration of an alternative embodiment of a crown of the present disclosure.

[0043] **Figure 28B** is a side cross-section view of the crown of Fig. 28A.

[0044] **Figure 29A** is a top view illustration of another alternative embodiment of a crown of the present disclosure.

[0045] **Figure 29B** is a side cross-section view of the crown of Fig. 29A.

DETAILED DESCRIPTION

[0046] In view of the foregoing, through one or more various aspects, embodiments and/or specific features or sub-components, the present disclosure is thus intended to bring out one or more of the advantages that will be evident from the description. The present disclosure makes reference to one or more specific embodiments by way of illustration and example. It is understood, therefore, that the terminology, examples, drawings and embodiments are illustrative and are not intended to limit the scope of the disclosure. The terms “crown” and “cap” may be used interchangeably in the description that follows.

[0047] **Figure 1** is a diagrammatic representation of a top view of a specific exemplary embodiment of a bottle cap of the prior art. The lever-type, easy-opening cap shown in Fig. 1 may have crown 1, pull tab ring 2, pull tab 3, rivet 4, and lever 5. Cutting lines 6 may form a horizontal angle of approximately 30 degrees may be

provided at the back of the crown cap 1. Significantly, cutting lines 6 do not extend all the way to the rim edge of crown 1, but instead terminate at or near ring 2. A plurality of angels 7 may be formed by crimping cap 1 around a circular bottle opening. Not shown in this view is that, in vertical cross section, cutting lines 6 of the prior art maintain substantially the same depth profile along the length of the cut. A consequence of these various features is that undue manual force may be required to open and remove a crown of Fig. 1 from a container opening.

[0048] Crown or cap 1 may be connected to pull tab 3 by lever 5. Lever 5 and pull tab 3 may be joined to make a single unit. Likewise, pull tab 3 and pull tab ring 2 may be a unitary piece. The other end of pull tab 3 may be riveted to the approximate center of the surface on the body of the cap of crown cap 1 by rivet 4.

[0049] **Figure 2A** is a diagrammatic representation of a side view vertical cross-section of a specific exemplary embodiment of a bottle cap of the present disclosure. Pull tab ring 2, pull tab 3 and rivet 4 in combination may be referred to herein from time to time as an opener assembly. Interior threads 8 may be provided for selectively removing crown 1 from a bottle by manually twisting instead of using the opener assembly mechanism.

[0050] Cutting line 6 tapers downward from angel 7 at the rim of cap 1 toward the approximate center of cap 1 to provide a tapered tearing groove. For example, the depth of the tapered groove may graduate from a depth in the range of approximately 0.03 to 0.02mm near the rim of cap 1 to a depth in the range of approximately 0.10 to 0.08 mm by rivet 4 near the center of cap 1.

[0051] **Figure 2B** is a diagrammatic representation of a side view vertical cross-section of an alternative specific exemplary embodiment of the bottle cap of Fig. 2A. The embodiment of Fig. 2B lacks threads 8 and is thus adapted to be opened

manually using the opener assembly as described above. Also shown is rim or rim area 7a, which may be considered the portion of crown 1 that may be crimped over the opening of a bottle, forming the angels, to secure the crown onto the bottle. Rim 7a may be considered to extend from approximately the portion of crown 1 that begins to curve over a bottle opening, or slightly interior to that portion, to the terminus of angel 7.

[0052] While terminus 9 of the tearing groove near the center of cap 1 is depicted in Figures 2A and 2B as being substantially vertical, it will be understood by those skilled in the art that a selected profile or dimensions of the tearing groove employed in a specific embodiment of a bottle cap of the present disclosure are a question of design and engineering choice, and as such the present disclosure should not be read as limiting in such regards. For instance, the present disclosure contemplates that terminus 9 may be curved, slanted, or otherwise shaped consistent with aims of the present disclosure.

[0053] **Figure 3A** is a diagrammatic representation of a side view vertical cross-section of an alternative specific exemplary embodiment of a bottle cap of the present disclosure. In the embodiment of Fig. 3A, cutting line 6 tapers at terminus 9 as well as toward angel 7 at the rim of cap 1 to provide an alternatively tapered tearing groove in contrast to the embodiment depicted in Figs 2A and 2B. By tapering the groove of cutting line 6 such that the thickness of cap 1 increases toward the center and toward the rim, an alternative tearing groove may be provided so that only a reasonable amount of force is called upon to manually tear open cap 1.

[0054] **Figure 3B** is a diagrammatic representation of a side view vertical cross-section of an alternative specific exemplary embodiment of the bottle cap of

Fig. 3A. The embodiment of Fig. 3B lacks threads 8 and is thus adapted to be opened manually using the opener assembly as described above.

[0055] By varying the depth of the groove along cutting line 6, as in either of the embodiments of Figures 2A, 2B, 3A, or 3B, cap 1 provides a tearing groove which makes it more likely that only a reasonable amount of manual force is called upon to tear open crown 1. As will be discussed in more detail below, a recommended range of dimensions and material composition of crown 1 are disclosed to further provide a crown that may be manually opened with only reasonable force.

[0056] In operation, a person grasps ring 2 near tab 3 so as to pivot ring 2 on lever 5 while pulling up and back along cutting line 6. Lever 5 and rivet 4 may act in concert to crack open cap 1 at the center while manual force continues tearing cap 1 along lines 6 until cap 1 is substantially split apart so that cap 1 may be easily removed from a bottle. The tearing groove of cutting line 6 facilitates manually tearing cap 1 along line 6.

[0057] Advantageously, the embodiments of Figures 2A and 3A may be provided with mating threads 8 along the interior of angels 7 such that crown 1 is adapted to alternatively be opened by twisting or unscrewing crown 1 from a bottle. Also alternatively, cap 1 may be removed using a bottle opener or other means to pop the cap off of the bottle.

[0058] **Figure 4** is a diagrammatic representation of a side view vertical cross-section of an alternative specific exemplary embodiment of a bottle cap of the present disclosure. Alternatively or additionally to threads 8, crown 1 may be formed, as shown in Fig. 4, having an elongated rim 7b relative to rim 7a of Figure 2. Securing a standard crown over a threaded bottle opening may be problematic because the threads add surface area to the exterior of the bottle opening. A standard crown may

not be big enough to extend over the extra surface area of a threaded bottle. Elongated rim 7b may be an advantageous alternative embodiment that allows crown 1 to be crimped over a threaded bottle opening to provide elongated angel 7c. A further advantage is that a crown of Fig 4 may be twisted off of a threaded bottle without the crown itself being interiorly threaded such as depicted in Figs 2A and 3A.

[0059] Lever 5 is provided for leverage and additional shearing force to rend open the tinplate material of crown 1.

[0060] **Figure 5** is a diagrammatic illustration of a side view cross-section of an alternative embodiment of a crown of the present disclosure. In the embodiment of Fig. 5, lever 5 is omitted such that pull tab ring 2 and pull tab 3 are proximate to the top of crown 1. A crown of the present disclosure may provide divot 10 under pull tab ring 2 to facilitate manual grasping of ring 2. That is, divot 10 may provide a void into which a finger tip or a finger nail may fit to exert upward force on ring 2.

[0061] **Figure 6** is a diagrammatic illustration of a side view cross-section of yet another alternative embodiment of a crown of the present disclosure. Cut line 6 extends into rim area 7a so as to curve downward toward angel 7 to the edge of crown 1.

[0062] **Figure 7** is a diagrammatic illustration of a side view cross-section of an alternative embodiment of a crown of Fig. 6. Cut line 6 into extends into rim 7a, as with Fig. 6, but the depth of cut line 6 is substantially uniform along its length rather than having a variable depth as previously described.

[0063] **Figure 8** is a diagrammatic illustration of a side view cross-section of another alternative embodiment of a crown of the present disclosure. Pull tab ring 2 may be provided with one or more arcuate portions 11 to facilitate manual grasping of ring 2 by providing an uplifted space to accommodate a finger tip or finger nail

underneath. Arcuate portion 11 is shown for illustration purposes only. The amount or angle of uplift or curvature may be a matter of design choice for a specific embodiment.

[0064] **Figure 9** is a diagrammatic illustration of a side view cross-section of still another alternative embodiment of a crown of the present disclosure. Liner 12 is secured under crown 1 with rivet 4. Cushion 13 is disposed under pull tab ring 2 to facilitate manual grasping of ring 2 and further to provide tactile comfort by reducing metal-to-skin contact when ring 2 is grasped by a person. Divot 14, similar to divot 10 in Fig. 5, may be an indented portion of crown 1 such that the indentation extends under pull tab ring 2 so that a finger tip or finger nail may be more easily positioned under pull ring 2 to facilitate manual crown removal.

[0065] **Figure 10** is a diagrammatic illustration of a top view of a further alternative embodiment of a crown of the present disclosure. Pull tab ring 2, pull tab 3 and rivet 4 are not shown. Cut lines 6 typically diverge toward rim 7a from imaginary center line 6a. The present disclosure contemplates alternative degrees of divergence 6b (dashed lines), for example, or that cut lines 6c (dotted lines) may converge toward rim 7a. The lines may even be substantially parallel. Convergence or divergence, and the selected degrees or angle separating the lines, is a matter of design choice, as is the number of cut lines, which may be as few as one or even zero. Accordingly, the present invention contemplates all and every permutation of cut lines which may be selected for the engineering design of a particular crown. Additionally, Fig. 10 illustrates an embodiment of the present crown formed to have 28 angles around the circumference of the crown.

[0066] **Figure 11** is a diagrammatic illustration of an isometric top view of an alternative embodiment of a crown of the present disclosure. The Easy Pull[™] pull tab

apparatus is not shown in order to illustrate more plainly the cut lines 6d and 6e. In a preferred embodiment, one of the cut lines 6e provides an S-curve or tail segment 6f that extends along the angel portion 7 of crown 1. Portion 7 may also be referred to herein as skirt 7, which descends contiguously from the top of crown 1. Skirt 7 is described in more detail further below in the disclosure. S-curve 6f may facilitate the removal of crown 1 from a container opening. In operation, a person tears from center 15 along cut lines 6d and 6e. When the tear reaches S-curve 6f, the tearing force follows the S-curve away from cut line 6d and impels the tear along cut line 6d to terminus 16 which breaks open crown 1. Continued tearing force along S-curve 6f pulls angel portion 7 away from the container opening (not shown) and releases crown 1 from the container (not shown). S-curve 6f consists of a scoring line having an upper radial segment extending from the opener assembly to the skirt along a radial axis and a lower annular segment extending circumferentially along the skirt in an annular direction and extending from a terminus of the upper radial segment, the lower annular segment defined in a second horizontal plane equidistant to the first horizontal plane associated with the lower edge of the skirt.

[0067] Another feature illustrated in Fig. 11 is one or more spoilage indicators 17 such as dimples depressed in crown 1 and positioned so as not to be obscured by the pull ring apparatus of the present disclosure. For containers that are vacuum sealed, spoilage indicators 17 pop up in the event that the pressure seal is lost.

[0068] **Figure 12** is a diagrammatic illustration of an isometric top view of an alternative embodiment of a crown of Fig. 11. Again, the Easy Pull[™] pull tab apparatus is not shown in order to illustrate more plainly the cut lines. The embodiment of Fig. 12 may provide a single cut line 6 extending outward from center

15. Cut line 6 branches or forks in to cut line 6d which extends to the edge of crown 1 and cut line 6e which curves into S-curve portion 6f as described above for Fig. 11.

[0069] **Figure 13** is a diagrammatic illustration of an isometric top view of an alternative embodiment of a crown of Fig. 11. The crown 1 of Fig. 11 is shown popped open in the center 15a with pull ring 2. Pull tab 3 is connected to crown 1 with rivet 4 and is in position to tear along cut lines 6d and 6e with application of manual force. One or more circular depressions 18 create space in the top 17 of crown 1 to seat pull ring 2 and the rest of the opener apparatus.

[0070] **Figure 14** is a diagrammatic illustration of a side cross sectional view of an alternative embodiment of a crown of Fig. 13. Skirt 7 descends from shoulder 19 which is contiguous with top 17. Seat 18 is of sufficient depth that pull ring 2 is substantially flush with the top 17 of crown 1. Such an embodiment advantageously is suitable for use in conventional bottle capping machines without having to re-tool or – refit the machine. A further advantage of seat 18 is that seat 18 forms a corrugated perimeter around the seat and corrugation is well known to strengthen flat sheets against bending in directions substantially perpendicular to the direction of corrugation. Seat 18, therefore, provides the additional advantage of strengthening crown 1. A further advantage of a strengthened crown as provided by seat 18 is that the thickness of crown may be reduced to a lower gauge (thinner) crown material than would be utilized in a standard crown, thus lowering the costs of manufacturing materials. Although Fig. 14 shows an embodiment of the present crown formed to have 27 angels in circumference around the crown, it will be understood by those skilled in art that the advantages of seat 18 do not depend on the presence or number of angels.

[0071] **Figure 15** is a diagrammatic illustration of a side cross sectional view of an alternative embodiment of a crown of Fig. 14. Seat 18 is shallower than as shown in Fig. 14, so that pull ring 2 is seated slightly or partially above the top 19 of crown 1. Such an embodiment may provide the advantage of having pull ring 2 easily accessible for manual opening. Depending on the acceptable tolerances, such an embodiment may also be suitable for use with a standard bottle capping machine.

[0072] Fig. 15 also illustrates an alternative embodiment in which liner 12 is mounted on the under surface of crown 1 with a suitable adhesive and is disposed so as to cover the bottom of rivet 4. Such embodiment may be distinguished from that illustrated in Fig. 9, in which rivet 4 secures liner 12 in position to the underside of crown 1.

[0073] **Figure 16** is a diagrammatic illustration of an isometric top view of an alternative embodiment of a crown of Fig. 13. Here, crown 1 is broken open at terminus 16 of cut line 6d. Further tearing with pull ring 2 along S-curve 6f will liberate a container (not shown) from angels 7 and detach crown 1 from the container.

[0074] **Figure 17** is a diagrammatic illustration of a top view of an alternative embodiment of a crown of Fig. 13. The embodiment of Fig. 17 provides printed matter such as a bent arrow 20 printed on pull tab 3 to indicate generally how a person should pull ring 2 in order to exploit the cut lines 6 for easy opening. Further instructions may be provided with printed instructions 21, which may read, for example: "LIFT RING PULL DOWN TO REMOVE". Additionally a caution warning 22 may be printed on crown 1.

[0075] **Figure 18A** is a diagrammatic illustration of a side cross section view of an embodiment of a cut line of the present disclosure. To form a tearing groove, cut line 6 may be machined to have any one or more of a variety of cross-sectional

profiles, depending on the engineering choice of a particular manufacturer. For instance, Fig.18A illustrates a square or rectangular cross section profile.

[0076] **Figure 18B** is a diagrammatic illustration of a side cross section view of an alternative embodiment of a cut line of Fig. 18A. Here, a curved cross section profile for cut line 16 is illustrated.

[0077] **Figure 18C** is a diagrammatic illustration of a side cross section view of an alternative embodiment of a cut line of Fig. 18A. A V-shaped cross section profile for cut line 6 is illustrated.

[0078] **Figure 19** is a diagrammatic illustration of an isometric view of the bottom of a crown of the present disclosure. Liner 12 adheres to the top of the underside of the crown and is disposed over the bottom of rivet 4. Additionally, Fig. 19 illustrates an embodiment of the present crown formed to have 21 angels in circumference around the edge of the crown.

[0079] **Figures 20A – 20E** are top view schematic illustrations of alternative embodiments of a crown of the present disclosure each embodiment having a curvilinear left score line extending from the center of the top of the crown to the annular edge of the crown. To reduce the risk of generating sharps from opening a crown of the present disclosure, various alternative embodiments provide score, cut or tear lines that create a gentle curve along the edge of the crown after the pull tab portion has been torn away. Accordingly, alternative cut lines 20, 22, 24, 26, and 28, of Figs 20A through 20E, respectively, arc to the left (as seen looking down on the top of the crown) so that when the pull tab portion is torn and pulled away from the crown it leaves behind a gently curving shape along the edge of the crown rather than a sharp. Each embodiment 20A – 20E, illustrating curvilinear score lines 20, 22, 24, 26, and 28, has a different degree of curvature one from the next and it is a matter of

engineering or design choice as to the amount of curvature selected to obtain the desired performance characteristics. A relatively flat score line 20, for example, yields a smooth edge but might require more force to tear, whereas a relatively more curved score line such as 28, for example, may require less force to tear but yields a differently shaped edge from that of score line 20. Score line 30 arcs to the right and terminates before the edge of the crown so that the crown is preserved as a unitary piece after the crown has been removed from the bottle or whatever container it was sealing.

[0080] **Figure 21** is a top view schematic representation of an alternative embodiment of a crown of the present disclosure illustrating an off-center location for the pull tab. Embodiments of the present crown having an off-center location for rivet 4 and the rest of the opener assembly are advantageous, for example, for non-beverage containers such as containers for canned goods like soup or beans, which familiarly have opener assemblies close to the edge to the container. Tear lines 6G and 6H traverse across top 17 of the crown 1 in a substantially rectilinear fashion to edge 16. Accordingly, the location of rivet hole or rivet 4 or of the crown 1 opener assemble on the top of crown 1 is largely a matter of engineering design choice. A crown of the off-center rivet embodiments is opened as described herein above of the other embodiments.

[0039] **Figure 22** is a top view schematic representation of an alternative embodiment of the crown of Fig. 21 with an alternative score line. Scoring lines 6G and 6H in the embodiment of Fig. 22 descend to skirt 7 directly from rivet 4, in contrast to Fig. 21, but similar to lines 6 in the previously described embodiments. Score line 6G descends to edge 16, whereas line 6H trails in the opposite direction maintaining for its length a substantially equal distance from edge 16 and top 7.

Scoring line 6H consist of a scoring line having an upper radial segment extending from the opener assembly to skirt 7 along a radial axis and a lower annular segment extending circumferentially along skirt 7 in an annular direction and extending from a terminus of the upper radial segment to an end point substantially spaced from the bottom annular edge 16 of the skirt 7. Preferably the lower annular segment defines a longer horizontal plane than that defined in the S-curve of scoring line 6f, described above, extending, for example approximately one quarter of the circumference of skirt 7.

[0040] **Figure 23** is a top view schematic representation of an alternative embodiment of the crown of Fig. 21 with an alternative score line. The score line for tearing crown 1 open circumscribes an almost complete circle around top 17 only to descend into skirt 7 at the end and all the way to crown edge 16. The embodiment of Fig. 23 is advantageous, for example, when employed with containers for products other than a beverage, such as soup or stew, where a large mouth opening provides easy access to the contents.

[0041] **Figure 24** is an isometric view schematic representation of an alternative embodiment of a crown of the present disclosure having no crimping angels. A crown of the embodiment of Fig. 24 is comparable to pressure-sealed crowns for fruit juices and the like which curl over the top of a container without crimping. The embodiment is also advantageous for use with medical containers and vials. The opener assembly with rivet 4 is off-center, but otherwise crown 1 opens as previously described.

[0042] **Figure 25A** is a cross-section schematic illustration of an unbroken score line of a crown of the present disclosure. **Figure 25B** is a cross-section schematic illustration of a broken score line of the embodiment of **Fig. 25A**. An

advantageous safety feature of a crown of the present disclosure is achieved in the manufacture of score lines 6. Describing **Figs 25A** and **25B** together, line 6 is scored on crown 1 in such a way that the moieties on either side of line 6 have curved edges 6M and 6N in cross-section profile. The seal formed by line 6 may be analogized to the seal formed by pressing the fingers of opposing hands together. The tip of each finger is curved and when two fingers are brought together, a seal can be formed. When score line 6 in **Fig. 25A** is torn as one opens crown 1 using the present opener assembly, crown 1 forms two edges 6M and 6N, which are curved or rounded, analogous to pulling the fingers apart. Non-sharp edges 6M and 6N, respectively, are formed upon breaking the frangible scoring line 6.

[0043] The reason score line 6 of **Figs 25A** and **25B** is advantageous is that it reduces the sharps produced by tearing open crown 1 with the opener assembly. Round tear edges 6M and 6N render the opened crown dramatically less dangerous from sharps than would otherwise be the case.

[0044] Further regarding score line 6, one consideration of a crown of the present disclosure is the ease with which the material of crown 1 can be torn once opened by the opener assembly. The ease of tearing relates to the amount of pull force that needs to be applied to tear the crown material. Pulling force may be reduced, that is, ease of tearing may be increased, with the use of crown coatings or lacquers known in the art that contain additives which increase the ease of tearing, by reducing the required pull force, of the crown 1 material along line 6. Specific embodiments may also include degradable plastic additives for the liner attached to the underside of the crown to facilitate biodegradation of the liner after a used crown has been disposed of as waste. A variety of commercially available bio-degradable plastic additives are known in the art and the selection of one or more such additives is a matter of design

choice. [0052] In addition to the various structures described herein, certain advantages over the prior art are bestowed on the present crown by the recommended specifications shown in Table 1.

TABLE 1

<u>Items</u>	<u>Acceptable Range/Target</u>
1. Appearance	Disc properly adhering
	White, clear or color pigmented liner
	Complete liner
	Clean liner
	Clean crown and ring
	No rust and scratch for crown and ring
	Two cut lines on the downward surface of crown
	Rivet
	Crown
2. Dimensions	Thickness (mm): 0.12- 0.28
	Inside diameter (mm): 32.08 – 32.12
	Outside diameter (mm): 26.60 – 26.90
	Radius of angle (mm): 1.5 – 1.9
	Number of angels: 21 - 32
	<u>Ring</u>
	Diameter (mm): 21.1 – 21.5
	Thickness (mm): 0.28 – 0.32
	<u>Liner</u>

	Diameter (mm): 20.00 – 20.50
3. Rockwell Hardness	T4 on the Rockwell 30T scale
4. Secure Seal	Greater than/equal to 150 PSI for 1 minute
5. Finish Hardness	Should not scratch with “H” pencil
6. Sensory	No significant differences with an identified control after 12 weeks at 20 degrees C
7. Lubricant Migration	No particles or lubricant should be present
8. Simulated Palletizing	CO2 loss should not differ against control caps when stored for 1 week with max weight of 45 Kgs over each bottle
9. Corrosion	Maximum corrosion: slight to moderate
10. Odor	No off odors detected
11. Pulling Force of Ring (kg)	less than or equal to 2.5kg
12. Composition of Material	Tinplate crown and ring; food class non-PVC for liner

13. Package	10000 crowns per box
14. Pressure (kg)	10kg
15. Container 40' Loading	1,247 Master Cartons
16. Printing	Logo/other design may be printed on the Easy Pull™ Cap
17. Crown Anti-Oxidation	Material used is “food grade” PET; clear, with no odor, 1.2 UM (micrometers)

[0053] In particular, a tinplate material which demonstrates an approximate hardness of T-4 on the Rockwell 30T Hardness Scale is preferred for the present cap (see item 3 in table 1), although embodiments of T-3 and T-5 are advantageous for particular products. The preferred soft tinplate material requires less force to open and tear with the opener assembly of the present crown while still providing sufficient sealing of the container contents. For the purposes of this disclosure, tinplate refers to any material, including tin or tin alloys, from which a crown may be fabricated and does not necessarily mean that the crown is made from tin or a tin alloy.

[0054] A pulling force for a pull ring of the present disclosure of approximately 2.5 kg (kilograms) or less is preferred (see item 11 of Table1). A relatively small pull force such as this is recommended so that virtually everyone will have sufficient strength to open a bottle using a crown of the present disclosure. In

contrast, a relatively large pull force has the disadvantage of requiring a great amount of initial force to tear the tinplate material, and once the tinplate is torn open the sudden release of pulling force causes the bottle to jerk away from the user, spilling the contents often in dramatic fashion.

[0055] In addition to the low hardness of the tinplate, the thinness or gauge of the crown may also contribute to achieving a small pull force. For example, a crown of the present invention is recommended to have a thickness of less than 0.28 mm (see item 2 in Table 1). Typical bottle crowns have a thickness of 0.28mm or greater. Embodiments in which the crown material is strengthened by corrugation, such as in seated embodiments, may be thinner than standard crowns, having, for example, a gauge as thin as approximately 0.16mm.

[0056] In addition to the foregoing embodiments described above,, an additional embodiment provides a reduced gauge crown that delivers additional advantages.

[0057] Billions of bottle caps are used worldwide and the cost of the caps is largely determined by the amount of material required for the caps. One way to reduced such costs is to reduce the amount of material used in each crown. The amount of material can be reduced by making the crown thin, or reducing the gauge of the crown. A reduced gauge could be achieved by using less material but this might compromise the integrity of the crown by making the crown weaker. Another approach would be to use less material but use a stronger material. However, stronger materials might be more expensive than standard tin plate typically used in crown manufacture, which would defeat the cost savings purpose. An approach that reduces the amount of material but uses the same material without compromising strength is to corrugate the crown. Such corrugation is described herein in regards to Fig 13, for

example, which describes the present crown having a seat formed in the top to receive the opener assembly. The following is a description of a low gauge embodiment of the present crown in which the advantages of corrugation are exploited.

[0058] Turning now to **Figure 26**, Crown 1 includes top portion 110 contiguous with recess 120 which terminates in seat 18. Skirt 7 downwardly extends from top 110. In some specific embodiments a flange extends obliquely from skirt 7. Alternating flutes 150 and lands 152 are formed on a circumferential portion of skirt 7. Crown 1, and other crowns shown in the figures, is shown as a pry-off type that is opened with a lever. The present invention also encompasses a twist-off type (not shown in the figures) that is opened by twisting, as will be understood by persons familiar with crown cap technology. Finally, crown 1 is suitable for use with pull tab type assemblies mounted to seat 130 with effective score lines embossed on crown 100, as described above.

[0059] Seat 18 is recessed, that is, it is lower than top 110 but is contiguous with top 110 by virtue of transition surface 120, which will be referred to herein for convenience as recess 120. Recess 120 may be formed in crown 1 in a variety of suitable ways to provide advantageous shapes. For example, in specific exemplary embodiments concentric tiers, grooves or steps are integrally formed in the crown 1 material until the desired depth of seat 18 is obtained, as illustrated in Fig. 26. In alternative embodiments, recess 120 is formed with a smoothly curved surface from top 110 to seat 18. The form of recess 120 functions as ribs or structural reinforcements that, it is surmised, help to stiffen seat 18 against deflection or deformation.

[0060] Skirt 7 descends from top 110 along the external perimeter of crown 1 and in specific exemplary embodiments smoothly merges into a downwardly and

radially outwardly extending flange. The skirt 7 is preferably adapted to be crimped onto the neck of a bottle for sealing. Specific exemplary embodiments of skirt 7 are divided into undulating, repeating portions that define the flutes 150 and lands 152. Preferably, the repeating portions are circumferentially evenly spaced apart such that each flute 150 is identical to all other flutes 150 around the circumference of the crown cap 1, and each land 152 is identical to all other lands 152 around the circumference of the crown cap 1. It should be understood that the crown cap 1 may include any number of flutes 150 and lands 152.

[0061] Referring to now to Figs 27A and 27B, 28A and 28B and 29A and 29B, the “B” figure of each depicted embodiment is the horizontal cross section of its “A” counterpart through line B-B. Each embodiment, designated 27A/B, 28A/B and 29A/B, is characterized by a particular diameter of its seat 18, as represented by width B 210, 310 and 410 of each embodiment, respectively, and depth A of recess 120 represented by depths 220, 320 and 420, respectively.

[0062] A specific amount of material strengthening from corrugation is achieved by selecting an embodiment with a particular combination of seat diameter 210, 310 or 410, for example, and recess depth 220, 320 or 420, for example. Exemplary embodiment 27A/B, for instance, has seat diameter 210, which is relatively wide, and recess depth 220, which is intermediately deep. Exemplary embodiment 28A/B has seat width 310, which is of intermediate width, and recess depth 320, which is the deepest of the three exemplary embodiments. Exemplary embodiment 29A/B has seat diameter 410, which is the narrowest of the embodiments, and recess depth 420, which is the shallowest depth of the three embodiments. To obtain a desired amount of material strengthening from corrugation, a combination of seat width 210, 310, or 410, for example, and recess depth 220, 320

or 420, for example, is selected to achieve a specific embodiment. [0018] Corrugation strengthens materials. This is particularly true of laminar materials formed into a sheet or plane. A laminar product can use less of a material if the material is corrugated to provide lateral strength. A bottle cap is a laminar product in which the sheet material, often steel or tin plate, is shaped to be affixed to the top of a bottle or other container. A standard pry-off or twist off cap has a thickness of material that is predominantly determined by considerations of leak prevention and the secureness of the attachment of the cap to the container.

[0063] Corrugation allows caps that use less material to have the equivalent strength of a standard thick crown. A corrugated crown is thinner, that is, it has a reduced gauge, in comparison to a standard bottle cap. An advantage of a reduced gauge cap is the money savings obtained by using less material.

[0064] Another advantage of a reduced gauge corrugated cap comes into play with innovated “pull-off” caps, which have a pull tab assembly attached to the crown as described herein above. The pull tab breaks the cap material and the crown is torn off the bottle using the pull tab ring of an opener assembly. A reduced gauge cap facilitates the tear off because the cap material is thin and the tearing action is parallel to the direction of material strengthening provided by the corrugation and therefor the tearing force does not have to overcome the material strengthening of the corrugation. Corrugation affords material strengthening perpendicular to the direction of corrugation.

[0065] In addition to the structures illustrated in the figures herein, it is understood that other structures will imbue a cap of the present disclosure with the advantages of corrugation and provide a reduced gauge crown for a bottle. For instance, concentric rings, which progress from the top of the skirt toward the center

of the seat, and decorative shapes such as stars, brand logos, sports team logos, religious insignia, and the like, formed in the plane of the cap, are embraced in the present disclosure.

[0066] Corrugation forms may be provided to a bottle cap by a variety means, including without limitation, metal stamping, pressing, embossing and so forth. Non-metal crowns of the present disclosure may be formed by injection molding for plastic crowns, or by other suitable means of production.

[0067] Specific embodiments of the corrugated crown caps described herein, such as embodiments for pry-off or twist off, are formed with steel of increased hardness compared with conventional crown caps presently in commercial production. For example, conventional crown caps are often formed of single reduced, T4, tinplate having a thickness of from 0.21 mm to 0.23 mm. Such tinplate has an average hardness (that is, the reported hardness value regardless of +/- variations) of approximately 61 on a 30T hardness scale, in accordance with ASTM 623. Crown caps 1 described herein may be made thinner and lighter weight compared with the prior art, for example, crown caps 1 may be formed of a material having a thickness of about 0.16 mm to 0.18 mm that have the same or roughly equal performance as conventional, thicker caps. These decreases in metal usage are more easily achieved when the structure of crown caps 1 are made with steel having increased hardness. For example, the inventor has demonstrated the effectiveness of low gauge crowns having grooves using DR8 (according to ASTM 623) or DR550 (according to EN 10203). Optionally, the inventor surmises that other materials may be used, such as single reduced tinplate or like material having enhance tempering, tin-free steel having similar properties as those described herein, and the like.

[0068] The crown caps 1 preferably have an average hardness of greater than 62 on the 30T scale (conforming to ASTM 623), more preferably greater than about 65, more preferably greater than about 68, more preferably greater than about 71. The embodiments shown in FIG. 26 and FIG. 28A were demonstrated to be effective using steel having a hardness of 73. The upper limit of hardness is set by the maximum stress acceptable to the glass bottle during the crimping process or the spring back (which may tend to urge the crimped flanges toward an uncrimped state) associated with harder plate.

[0069] The crown caps 1 may be formed with conventional press equipment, with only minor changes to parts of the tooling to form the structure (such as the grooves, crosses, stars, and dimples). And crown caps 1 may be crimped with conventional equipment, only modified to have a smaller throat compared with existing, conventional crimpers.

[0070] Because hardness has a relationship to strength as reflected in the yield point, the aspect of the hardness of the crown may be expressed in yield point on a corresponding scale. For example, DR8 or DR550 tinplate may has a yield point (in a tensile test) of 550 MPA.

[0071] However, it will be understood that for pull tab opener embodiments, softer materials, such as softer tinplate than T4 or even aluminum, are advantageous because they facilitate ease of opening and tearing. The strength provided by corrugation permits the use of a relatively soft crown material while preserving the strength required for secure closure of the container. The inventor believes that the most advantageous crown cap embodiment has a combination of strength for secure closure and softness for ease of opening and tearing that is a matter of design and

engineering choice. A crown of the present disclosure encompasses crown caps that do not have all of the structure, materials, and/or advantages in this specification.

[0072] According to this description, commercially acceptable crown caps formed according to the present disclosure can be commercially made with up to 25 percent less material (e.g., steel or tinplate) compared with many conventional crown caps, which has corresponding advantages in carbon emissions. The savings in material weight are approximately proportionate to the reduction in metal thickness. Further, even though energy required to cool an individual crown is tiny, the energy required to cool the total number of crowns produced each year (approximately 45 billion in North America and approximately 300 billion throughout the world), and the corresponding reduction in that energy, is significant.

[0073] The Reduced Gauge Crown has an impact on reducing the cost of the tinplate or steel, and the PVC / PVC free liner material, which is available with an additive, making both the metal crown and PVC or PVC free liner, biodegradable in an “active landfill”.

[0074] With the resulting lower production and weight in transportation costs in the RGC, in turn, reduce CO2 emissions.

[0075] Tinplate or steel used to produce crowns for the beer or soda industry varies between 0.21mm – 0.24mm. The present reduced gauge crown may use a thickness of between 0.17mm – 0.19mm. A standard pry-off or twist-off crown, weighs approximately 2.38 grams, whereas the reduced gauge crown weighs approximately 2.14 grams, a 10% reduction in weight yielding a savings in material costs.

[0076] A further benefit of the reduced gauge crown is seen in the transportation costs of crowns. A reduction in weight relates to a savings in

transportation fuel costs, wear and tear on the transportation vehicles, and reduced transportation carbon dioxide emissions. Standard bottle crowns are traditionally packed 10,000 per carton, as indicated in Table 1, but with the reduced gauge crown embodiment of the present crown, a carton holds 11,000 crowns, thus providing reduced energy, transportation, and carbon dioxide emissions.

[0077] Advantages of the reduced gauge crown embodiment include, without limitation, cost savings in production, lower price per crown, lower transportation costs, lower loading costs, as well as reduced carbon dioxide emissions.

[0078] In addition to all of the embodiments described herein above, an additional feature is suitable for use with of each of the embodiments as a matter of engineering, design or marketing choice, which is the employment of temperature-sensitive color-changing ink, so-called thermochromic ink, such as described, for example, in United States Patent No. 6,634,516 to Carballido, which is incorporated herein by reference in its entirety. Such thermochromic inks have the property of changing color so as to be one color at room temperature (approximately 21⁰C) and a different color when refrigerated to, for example standard retail refrigeration temperature of 4⁰ C. In an exemplary application, the ink is transparent, for example, at room temperature but becomes relatively opaque and visible at chilled temperature, such that a customer has visual confirmation of the approximate temperature without touching the container.

[0079] The illustrations of embodiments described herein are intended to provide a general understanding of the structure of various embodiments, and they are not intended to serve as a complete description of all the elements and features of apparatus and systems that might make use of the structures described herein. Many other embodiments will be apparent to those of skill in the art upon reviewing the

above description. Other embodiments may be utilized and derived therefrom, such that structural, materials, and logical substitutions and changes may be made without departing from the scope of this disclosure. Figures are merely representational and may not be drawn to scale. Certain proportions thereof may be exaggerated, while others may be minimized. Accordingly, the specification and drawings are to be regarded in an illustrative rather than a restrictive sense.

[0080] Such embodiments of the inventive subject matter may be referred to herein, individually and/or collectively, by the term “invention” merely for convenience and without intending to voluntarily limit the scope of this application to any single invention or inventive concept if more than one is in fact disclosed. Thus, although specific embodiments have been illustrated and described herein, it should be appreciated that any arrangement calculated to achieve the same purpose may be substituted for the specific embodiments shown. This disclosure is intended to cover any and all adaptations or variations of various embodiments. Combinations of the above embodiments, and other embodiments not specifically described herein, will be apparent to those of skill in the art upon reviewing the above description.

[0081] The Abstract of the Disclosure is provided to comply with 37 C.F.R. §1.72(b), requiring an abstract that will allow the reader to quickly ascertain the nature of the technical disclosure. It is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims. In addition, in the foregoing Detailed Description, it can be seen that various features are grouped together in a single embodiment for the purpose of streamlining the disclosure. This method of disclosure is not to be interpreted as reflecting an intention that the claimed embodiments require more features than are expressly recited in each claim. Rather, as the claims reflect, inventive subject matter lies in less than all features of a single

disclosed embodiment. Thus the following claims are hereby incorporated into the Detailed Description, with each claim standing on its own as a separate embodiment.

[0082] The description has made reference to several exemplary embodiments. It is understood, however, that the words that have been used are words of description and illustration, rather than words of limitation. Changes may be made within the purview of the appended claims, as presently stated and as amended, without departing from the scope and spirit of the disclosure in all its aspects. Although description makes reference to particular means, materials and embodiments, the disclosure is not intended to be limited to the particulars disclosed; rather, the disclosure extends to all functionally equivalent technologies, structures, methods and uses such as are within the scope of the appended claims.

}

I claim:

1. A frangible reduced gauge crown for a container opening, the crown comprising:
 - a crown thickness gauge in the range of 0.12mm to 0.23mm;
 - a top portion having an attachment portion;
 - an annular skirt descending from the top portion and terminating at a bottom annular edge;
 - an opener assembly attached to the top at the attachment portion;
 - a frangible scoring arrangement comprising:
 - a first scoring line extending in a continuous radial direction from the attachment portion to the bottom edge of the skirt; and
 - a second curvilinear scoring line comprising:
 - an upper radial segment extending in a continuous radial direction from the attachment portion of the top to the annular sidewall of the skirt, and
 - a lower annular segment extending circumferentially along the annular side wall of the skirt from the upper radial segment to an endpoint substantially spaced from the bottom annular edge of the skirt;
- wherein at least one of the first scoring line and the second curvilinear scoring line are formed by touching moieties having opposing curved edges when viewed in cross-section.

2. The crown of claim 1, wherein the opener assembly further comprises
a pull tab ring;
a pull tab attached to the pull tab ring; and
a rivet attached to the pull tab and to the attachment portion of the top.
3. The crown of claim 2, the opener assembly further comprising a lever under the pull tab.
4. The crown of claim 1, wherein the top further comprises a center portion and wherein the attachment portion is at the center portion of the top.
5. The crown of claim 1, wherein the top further comprises a center portion and wherein the attachment portion is off-center from the center portion of the top.
6. The crown of claim 2, where in the top portion further comprises a recessed seat.
7. The crown of claim 1, wherein at least one of the scoring lines is tapered to have greater depth near the annular edge of the skirt than near the attachment portion.
8. The crown of claim 1, comprising a divot on the top portion to facilitate manual crown removal.
9. The crown of claim 1, further comprising an interior under portion opposite of and defined by the top portion and the skirt; a liner fastened to the under portion.
10. The crown of claim 1, further comprising a cushion on the pull tab ring.
11. The crown of claim 1, wherein the top is corrugated.
12. The crown of claim 1, further comprising a crown thickness gauge in the range of 0.12mm to 0.18mm.

13. The crown of claim 1, wherein the frangible scoring arrangement defines a frangible portion of the frangible crown, the frangible portion extending outward from the attachment portion to the bottom edge of the skirt, the frangible portion having a curved profile shape in cross-section.
14. The crown of claim 1, wherein the frangible scoring arrangement defines a frangible portion of the frangible crown, the frangible portion extending outward from the attachment portion to the bottom edge of the skirt, the frangible portion having a square shape in cross-section.
15. The crown of claim 1, wherein the frangible scoring arrangement defines a frangible portion of the frangible crown, the frangible portion extending outward from the attachment portion to the bottom edge of the skirt, the frangible portion having a V shape in cross-section.
16. The crown of claim 1, wherein at least one of the scoring lines of the frangible scoring arrangement produces a non-sharp edge upon breaking.
17. The crown of claim 1, wherein the skirt comprises a plurality of angels.
18. The crown of claim 1, wherein the skirt comprises no angels.
19. The crown of claim 1, wherein the first scoring line is curvilinear.

20. A frangible reduced gauge crown for a container opening, the crown comprising:
- a crown thickness gauge in the range of 0.12mm to 0.23mm;
 - a top portion having an attachment portion;
 - an annular skirt descending from the top portion and terminating at a bottom annular edge;
 - an opener assembly attached to the top at the attachment portion;
 - a frangible scoring arrangement comprising:
 - a first curvilinear scoring line extending in a continuous radial direction from the attachment portion to the bottom edge of the skirt; and
 - a second curvilinear scoring line comprising:
 - an upper radial segment extending in a continuous radial direction from the attachment portion of the top to the annular sidewall of the skirt, and
 - a lower annular segment extending circumferentially along the annular side wall of the skirt from the upper radial segment to an endpoint substantially spaced from the bottom annular edge of the skirt;
- wherein at least one of the first curvilinear scoring line and the second curvilinear scoring line are formed by touching moieties having opposing curved edges when viewed in cross-section.




FIG. 1
Prior Art




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5




FIG. 6




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18A




FIG. 18B




FIG. 18C




FIG. 19




FIG. 20A




FIG. 20B




FIG. 20C




FIG. 20D




FIG. 20E




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25A




FIG. 25B




FIG. 26




FIG. 27A




FIG. 27B




FIG. 28A




FIG. 28B




FIG. 29A




FIG. 29B




FIG. 13