



(22) Date de dépôt/Filing Date: 2020/02/21

(41) Mise à la disp. pub./Open to Public Insp.: 2020/08/21

(45) Date de délivrance/Issue Date: 2023/11/28

(30) Priorité/Priority: 2019/02/21 (US62/808,555)

(51) Cl.Int./Int.Cl. *H04L 41/22* (2022.01),
H04L 41/5009 (2022.01), *H04L 41/5067* (2022.01),
H04L 43/065 (2022.01), *H04L 43/08* (2022.01),
H04L 43/0817 (2022.01), *H04L 43/12* (2022.01)


(72) Inventeurs/Inventors:
FAICZAK, KENNETH, CA;
TAMASKE, SHERYL, CA;
SRIDHAR, KAMAKSHI, US;
CULLEN, SAMUEL CAMERON, US

(73) Propriétaire/Owner:
SANDVINE CORPORATION, CA

(74) Agent: AMAROK IP INC.

(54) Titre : SYSTEME ET PROCEDE POUR FOURNIR UN PORTAIL DE TRAFIC DE RESEAU

(54) Title: SYSTEM AND METHOD FOR PROVIDING A NETWORK TRAFFIC PORTAL



(57) Abrégé/Abstract:

A method for providing a network portal including: collecting network data for at least one network provider; analyzing the network data; determining a user role of a user accessing the network portal to review the network data; and providing a visualization of the analyzed network data based on the user role of the user accessing the portal. A system for providing a network portal including: a data collection module configured to collect network data for at least one network provider; an analysis module configured to analyze the network data; a user module configured to determine a user role of a user accessing the network portal to review the network data; and a reporting module configured to provide a visualization of the analyzed network data based on the user role of the user accessing the portal.

ABSTRACT:

A method for providing a network portal including: collecting network data for at least one network provider; analyzing the network data; determining a user role of a user accessing the network portal to review the network data; and providing a visualization of the analyzed network data based on the user role of the user accessing the portal. A system for providing a network portal including: a data collection module configured to collect network data for at least one network provider; an analysis module configured to analyze the network data; a user module configured to determine a user role of a user accessing the network portal to review the network data; and a reporting module configured to provide a visualization of the analyzed network data based on the user role of the user accessing the portal.

SYSTEM AND METHOD FOR PROVIDING A NETWORK TRAFFIC PORTAL

FIELD

[0001] The present disclosure relates generally to a system and method for monitoring computer network traffic and communicating information about the computer network traffic. More particularly, the present disclosure relates to a system and method for providing a network traffic portal.

BACKGROUND

[0002] Internet Service Providers (ISPs) and other network operators are generally looking for intelligent ways to efficiently manage their network traffic in a more granular fashion. For example, ISPs are attempting to balance higher bandwidth demands with limited operating budgets while improving subscriber quality of experience. As more subscribers access greater levels of content online, ISPs are frequently required to balance various demands to ensure subscribers' needs are being met. It is often difficult to monitor the performance and operation of the network and receive appropriate analytics that would allow the network operator to make informed network planning decisions. It is, therefore, desirable to provide an improved method and system for monitoring network traffic and communicating information regarding the network traffic, for example, by providing a network traffic portal.

[0003] The above information is presented as background information only to assist with an understanding of the present disclosure. No determination has been made, and no assertion is made, as to whether any of the above might be applicable as prior art with regard to the present disclosure.

SUMMARY

[0004] In a first aspect, there is provided a method for providing a network portal, the method including: collecting network data for at least one network provider; analyzing the network data; determining a user role of a user accessing the network portal to review the network data; and providing a visualization of the analyzed network data based on the user role of the user accessing the portal.

[0005] In some cases, the network data may include: network traffic flow data selected from the group including: Quality of Service data, composition of network traffic,

services, Quality of Experience, and network congestion; and network subscriber data selected from the group including: subscriber device type, subscriber plan, and subscriber traffic flow.

[0006] In some cases, the method may further include determining network performance based on the analyzed network data; and providing a traffic action to the network based on the network performance.

[0007] In some cases, traffic action may be reprioritizing at least some of the network traffic.

[0008] In some cases, the traffic action may include notifying at least one user of the network portal of the network performance.

[0009] In some cases, at least some of the analyzed network data may be hidden from a user based on the user's role.

[0010] In some cases, the method may further include: presenting traffic actions available to the user based on the analyzed network data and the user's role.

[0011] In some cases, the visualization may provide the user an ability to view further levels of granularity with respect to the analyzed network data.

[0012] In some cases, the visualization may be customized by the user.

[0013] In another aspect, there is provided a system for providing a network portal, the system including: a data collection module configured to collect network data for at least one network provider; an analysis module configured to analyze the network data; a user module configured to determine a user role of a user accessing the network portal to review the network data; and a reporting module configured to provide a visualization of the analyzed network data based on the user role of the user accessing the portal.

[0014] In some cases, the network data may include: network traffic flow data selected from the group comprising: Quality of Service data, composition of network traffic, services, Quality of Experience, and network congestion; and network subscriber data selected from the group comprising: subscriber device type, subscriber plan, and subscriber traffic flow.

[0015] In some cases, the analysis module may be configured to determine network performance based on the analyzed network data; and a traffic action module is configured to provide a traffic action to the network based on the network performance.

[0016] In some cases, the traffic action may include reprioritizing at least some of the network traffic.

[0017] In some cases, the traffic action may include notifying at least one user of the network portal of the network performance.

[0018] In some cases, at least some of the analyzed network data may be hidden from a user based on the user's role.

[0019] In some cases, the system may further include a traffic action module configured to present traffic actions available to the user based on the analyzed network data and the user's role.

[0020] In some cases, the visualization may provide the user an ability to view further levels of granularity with respect to the analyzed network data.

[0021] In some cases, the visualization may be customized by the user.

[0022] Other aspects and features of the present disclosure will become apparent to those ordinarily skilled in the art upon review of the following description of specific embodiments in conjunction with the accompanying figures.

BRIEF DESCRIPTION OF FIGURES

[0023] Embodiments of the present disclosure will now be described, by way of example only, with reference to the attached Figures.

[0024] Fig. 1 illustrates an environment for a system for providing a network traffic portal according to an embodiment;

[0025] Fig. 2 illustrates a system for providing a network traffic portal according to an embodiment;

[0026] Fig 3. is a flow chart illustrating a high level method for providing a network traffic portal according to an embodiment;

[0027] Fig. 4 illustrates a flow chart for the system and method for providing a network traffic portal according to an embodiment;

[0028] Fig. 5 is a table illustrating a relationship between solution area and use case for the system for providing a network portal according to an embodiment;

[0029] Fig. 6 is a table illustrating a relationship between phenomena and use case;

[0030] Fig. 7 is a table illustrating an example of teams and user types according to an example;

[0031] Fig. 8 is a table illustrating permissions and portal user types according to a specific example; and

[0032] Figs. 9 to 16 illustrate various solution areas visualizations according to a specific example of the system for providing a network portal;

[0033] Figs. 17 to 21 illustrate various phenomena visualizations for gaming services according to a specific example of the system for providing a network portal;

[0034] Figs. 22 to 29 illustrate various phenomena visualizations for video services according to a specific example of the system for providing a network portal; and

[0035] Fig. 30 illustrates a visualization showing network element health according to a specific example.

DETAILED DESCRIPTION

[0036] Generally, there is provided a system and method for providing a network traffic portal. The system and method provided herein are intended to review various statistics and data points in relation to, for example, Quality of Service (QoS), Quality of Experience (QoE), subscriber traffic flows, network congestions and the like. The system and method are intended to provide analytics about the overall network traffic and each subscriber's traffic. With the analytics reviewed and displayed in a graphic report, the network operator may quickly review updates related to congestions, regulatory compliance, fraud, and the like. Embodiments of the system and method may further provide for traffic actions or suggest traffic actions to the network provider via the network portal. The traffic actions are intended to provide an increase in QoS or QoE, reduce network congestion, provide for upgrades or other actions intended to help improve the service provide by the network operator.

[0037] Generally, there is provided a method and system for providing a network traffic portal that includes gathering network traffic data of various kinds and at various levels, organizing and/or aggregating the data and presenting the data in various formats, including visual, and at various levels of granularity. The visual representation may include bar graphs, heat maps, and the like.

[0038] Figure 1 shows a diagram of an example of a Long Term Evolution (LTE) network 10 architecture. It will be understood that at least one Evolved Node Base station (eNodeB) resides within the LTE Radio Access Network (RAN) 20. The eNodeB is configured to

allocate the network resources among the various LTE users 25. The RAN 20 is in communication with the core network 30. The eNodeB 15 connects to the core network 30 via a serving gateway (SGW) 35, which is further in communication with a packet data network gateway (PGW) 40 which is in communication with the Internet 45. The LTE network 10 further includes a Mobility Management entity (MME) 50, which is configured to track the LTE users 25. The MME 50 interacts with a Home Subscriber Server (HSS) database 55 to provide information with respect to the various users 25 of the LTE 10. The LTE 10 includes a Policy and Charging Rules Function (PCRF) 60, which is intended to provide policy control and flow based charging decisions. It will be understood that figure 1 illustrates a high level network architecture and that an LTE network may include further aspects not illustrated. The system and method described herein may further be applied to other networks, for example, LTE-A, 3G networks, 4G networks, 5G networks, Satellite networks, mobile networks or other networks.

[0039] A system 100 for providing a network portal is intended to reside in the core network 30. In particular, the system 100 may be an inline probe north of the PGW 40, between the SGW 35 and PGW 40, or in another location where the system is able to access the data noted herein. It will be understood that in some cases the system may be a physical network device, or may be a virtual network device. In some cases, the system 100 may send data to the cloud to be processed or the system may process the data internally. One of skill in the art will understand that cloud processing includes processing by one or more remote processors and use of remote memory to store data during processing.

[0040] By conducting qualitative and quantitative analytics of changes in the telecommunications industry and the impact on service provider businesses, it was determined that there was a lack of analytics configured to help service providers understand their networks. In particular, service providers were looking for analytics in the following areas, for example:

- Telecommunications industry disruption
- Business response to disruption and evolution
- Network Operations
- Network Engineering
- Regulatory Operations
- User personas in telecommunications

- User experience design

[0041] Business Operations generally need to be reviewed regularly because more and more essential services are becoming digital, more content providers move into the cloud and user expectations to access service or content from any device continues to grow. The change in consumption, demand, delivery and content ownership are causing a transformation of the telecommunication industry from traditional transformation to a cross-functional dev-ops model.

[0042] Intent-based networking and the associated visualization of that activity are intended to provide better operational management and decision making for the cross-functional teams. The intent of the network operator may be considered in the analysis of the data and the subscriber QoE and network QoS. The network provider may wish to ensure a certain level of QoE for certain services and the data collected and analyzed by the system detailed herein is intended to provide the network operator results associated with the intent.

[0043] The system and method described herein are intended to provide a single closed-loop platform that provides the features to support both network monitoring and management activity based on contextual insight into user behavior patterns and network response. Navigation may be presented in context to both a portal users chosen view (for example, solution area, phenomena, network elements or the like) and the user's responsibility for the network, for example, business strategy, network operations, or the like.

[0044] Access to the portal may be role based controlled which may provide insight to all teams while security access to user identified data or network settings is maintained. Authenticated service identification is intended to provide significant reductions in unidentified traffic, which may provide for greater insight to user intent based on service identification. Further, confirmed service identification at a location level may be provided to identify services congestion at each network layer.

[0045] Methods used for providing the network portal are intended to detect user demand and manage network response to deliver services. The system and method may further provide a clear metric for how the end user experience measures up to the user demand and adjustments that can be made.

[0046] Network or service providers may have custom visualizations within the network traffic portal. Embodiments of the system and method may benefit from conducted customer

and end-user research to understand applicable persuasive patterns. Roles based controls from a network provider may limit access to visualizations with user identified data.

[0047] Embodiments of the system and method may provide for a custom look and feel including:

- Network User type – Categorization of user behavior on the network
- Quality of Service visualization - Summary of service-specific performance in one visualization
- Quality of Experience visualization – Summary of metrics to evaluate the subscribers experience while using a service on the network.
- Key performance indicators – Score, throughput, latency, and packet loss as a single data set
- Intent - layering user intent over key performance indicators visualization to map the relationships.

[0048] Embodiments of the system and method for providing a network portal provide for live and historical visual representations of subscriber demand on the network and network response which is intended to optimize the delivery. The data may be shared in its visual format or used as raw data.

[0049] In a modern telecommunications business more teams, from business to engineering, may benefit from on-demand visibility into how the network demand is being managed and met from a single source that provides insight into user intent and not just data without context.

[0050] Visualizations provided by the method and system are intended to be representative of activity on the network. The visualizations are designed to provide insight to the subscriber and/or network user intent and network response for different teams in the organization from any device at any device and any time. By understanding purpose, the network operators may be in a better position to respond appropriately to any gaps in a network response to user demand from various departments.

[0051] The portal is intended to begin with a visualization of Quality of Experience highlights key performance indicators (KPIs) by for phenomena. Phenomena categories are defined through analysis of deidentified global user activity. From there, the phenomena categories can be expand upon to provide more context to the subscriber activity within the scope of the use case.

[0052] In a specific example, Social Sharing is the combination of not only social networking, but also the ecosystem that enables and feeds it. Subscribers download applications that they can use on their devices to edit photos and videos, they take pictures or videos (which may get uploaded to the cloud), edit them (which may have them go to the cloud again), and then post on one or more commonly now a plurality of social network sites or applications. Then subscribers may message others (either on the social messaging app or in a separate one) to tell them to check out what the subscriber just posted. These activities may be identified and grouped in different sub-categories of Social Sharing.

[0053] The system and method detailed herein allow network operators to see these patterns as they evolve worldwide. The system and method are intended to be able to spot trends in user behaviors along with service adoption or abandonment that may aid in this behavior.

[0054] Network Performance Monitoring and Analysis is intended to deliver a historical as well as a real-time view of how well the network is delivering services and applications. As detailed herein, the system is intended to closely monitor the metrics that allow the system to determine if subscriber expectations are met, from detailed transport measurements to application-aware performance information to scores.

[0055] The historical perspective on key network performance quality indicators (for example, throughput, packet loss, and latency) identifies network trends requiring further in-depth investigation. Optional real-time capabilities may enable network operations teams to proactively understand, troubleshoot, and respond to network application issues quickly before users are impacted. In some cases, the system and method may perform automated traffic actions in order to maintain or improve network performance based on the analyzed data.

[0056] Gaming QoE Analysis focuses on user activity specific to gaming on the network. With the rise in Cloud gaming more gamers are moving away from game downloads and interactive gaming. These gamers want premium service with low latency and high volume service for the games. A gamer who spends 8+ hour gaming in a week, is most likely to change providers based on high latency that create a poor quality of experience casual mobile gamer might be interested in. The visualization provided by the system is intended to provide a high level summary of user behaviors for business decision makers and drill down into more levels of granularity for more technically detailed portal users. The system may be

configured to also notify all teams or certain individuals if there are sudden changes in gaming activity or other network activity.

[0057] Regulatory Quality Monitoring is intended to provide transparency for both the regulatory bodies that hold operators accountable to their network performance obligations in that region. Regulatory bodies may be able to receive an overview of various network conditions for each operator, including, for example Quality of Experience (QoE) KPIs. It will be understood that a network operator can only access reports for their own services. Accountable resources may be able to see the same reports the regulatory bodies are monitoring. Operators can receive a notification if services or KPIs are dropping below a regulated thresholds in order to take action to avoid financial repercussions. Operator who have automated services may be able to monitor the regulatory view to verify the regulatory bodies are seeing appropriate results.

[0058] The responsive nature of the various visualizations allows for embodiments of the system and method to provide secure access from a broad range of devices. The embodiments of the system and method are intended to provide, for example, insight to network user patterns and the intent for their actions; immediate network response and outcomes of the response; early alarming to behavior or demand that cannot be met; faster decision making as a business based on user or subscriber behavior, and the like.

[0059] The system and method may address the need for pockets of data in various formats. Further, the system and method may provide for multiple account access to independent vendor platforms to monitor, manage and market to user demands. The roles based visualizations and dashboards provide insight based on network user intent in the content for various user roles, for example, marketing, network operations, engineering, and the like.

[0060] Embodiments of the system and method may use persuasive patterns to visualize intent and network management activity for executive, business and technical users.

[0061] Embodiments of the system and method for providing a network traffic portal are designed to visualize outcome-driven use cases for network operators. As operators deploy use cases to solve business problems, the visualization and workflow of the use cases may be exposed within the portal. Analytics may provide a foundation for the system, which may enable operators to improve subscriber experience by applying policies and optimizing the network, based on targeted intelligence. Embodiments of the system and method may help visualize contextual use case information by subscriber, device, service, technology, network

access type, and the like. Operators may be able to determine their return on investment (ROI) based on factual, instantly visualized data for the broadest set use cases. In addition, operations teams can configure, visualize, and get performance reporting on various network devices and solution elements.

[0062] Embodiments of the system and method for a system and method for a network traffic portal may be optimized for persona-based workflows. Executive summaries may include an overall analytics view on how the network is delivering services to the enterprise and consumer subscriber base. Each use case may have a different visualization that aligns with the business needs of the operator group that has deployed the use case – whether it be engineering, operations, marketing, product management, customer care, information technology, or the like.

[0063] Embodiments of the system may include a cloud-based software solution that may allow for a single point of access visualizations of user demand on the network, the network's response to optimize the delivery. Visualizations and workflows may be designed for different user personas across teams within an organization. Secured access controls for sensitive data systems or business critical systems, visualizations from the portal can be shared between teams in the original visual format or as a raw data export.

[0064] Figure 2 illustrates an embodiment of the system for providing a network traffic portal. The system includes a data collection module 105, an analysis module 110, a reporting module 115, a traffic action module 120, a user module 125, at least one processor 130 and at least one memory component 135. The system 100 is intended to reside on the core network but, as noted, may be remote or access remote resources, while having a connection to the core network. The modules, including the processor 120 and memory 125, are in communication with each other but may be distributed over various network devices or may be housed within a single network device. The system 100 is intended to receive information from the network equipment that allows the system 100 to determine traffic flow criteria, including application type, device characteristics, user quota, time of day, ongoing events and the like per subscriber as well as overall network congestions data. In some cases, the system may determine whether an ongoing event may be affecting the traffic flow, for example, a large congregation of people at a single venue may adversely affect traffic in an associated cell.

[0065] The data collection module 105 is configured to monitor traffic of each subscriber on the network and collect data with respect to application use, QoS and QoE aspects. The analysis module 110 is configured to review the data and determine trends and points of interest as detailed herein.

[0066] In some cases, the analysis module 110 may include at least one Business Intelligence (BI) platform that may be designed with the need of data scientists and analysts in general. Traditionally, teams may have taken manual steps to merge the data with a disconnected data source then analyze data and share findings. Traditionally, sourcing and consolidating data into a BI platform was a manual collection process across different solutions that may have taken 6-9 months to gather.

[0067] Further, in conventional solutions data may also be skewed depending on how it was calculated, aggregated, and/or combined with other data or scrubbed before sharing between teams. Two teams may get different results when working with the same data source, interpret user intent differently or have user demand will change faster than an organization can understand and respond to it.

[0068] Conventional solutions relating to network traffic often do not communicate user intent and network response to meet it. These solutions are often focused on detailed visualizations of raw data for network engineering and operations personas and do not present the data in context for the user persona viewing it. Further, in the telecommunications industry, service providers may have a variety of solutions vendors in the network. Each vendor may offer their own set of independent solutions that represent a set of data without providing further insight. These conventional solutions, supplied by each vendor, often operate independently. The complexity of vendor solutions, even within a single vendor portfolio, creates an extra layer of complexity within the services provider in just managing the data to find insights and stay competitive in a changing marketplace.

[0069] The user module 125 is intended to determine a role of a particular user of the system 100. In some cases, the memory component may have predefined user roles and on accessing the system, the user module 125 may determine the role of the user based on, for example, log in credentials, access parameters, or the like. The user module 125 may be used to determine the visualizations and reports received by a user. It will be understood that depending on the type of user, data may be displayed differently and certain data may be hidden in order to protect subscriber privacy. In a specific example, a regulatory body user

may be able to view specific network information related to a plurality of network operators. A CEO or CFO of a network operator may have a dashboard that includes high level analysis of the network as a whole and a network system operator may have specific visualizations of each component of the network. It is intended that the user module 125 determines the user's role and is able to prepare dashboard and visualizations that may be tailored to the current user.

[0070] The reporting module 115 of the system for providing a network portal is configured to report the analyzed data received from the analysis module 110 via, for example the network portal display. In some cases, the reporting module may provide for the display of the data as detailed herein. In other cases, the reporting module 115 may provide reports, alarms or other notifications to an administrator, network system engineer, or other designated user role. In some cases, the reporting module 115 may push an alarm when the analysis module has detected fraud or regulatory compliance issue. In other cases, the reporting module 115 may provide a designated user or administrator of the network operator a banner or badge regarding an issue when the designated user or administrator logs into the network portal.

[0071] The traffic action module 120 may provide a designated user, network system engineer, or other user role with a list of traffic actions that may aid in a specific network issue. In some cases, the traffic action module 120 may provide for shaping specific applications in order to improve overall subscriber QoE. In other cases, the traffic action may be to reroute traffic, change a traffic policy, or change priority for certain subscribers or services based on the current network conditions. Still other traffic actions may include upgrading network equipment or providing software updates for particular applications. In still other cases, the traffic action module 120 may provide for the traffic action automatically.

[0072] Embodiments of the system and method disclosed herein are intended to create a closed loop single source of insights for solutions on the network and access to insights driven visualizations designed to provide insights to business and engineering personas across the organization. Subscriber experience insights are presented in context of what activities each subscriber is using the network for, while network performance insights are provided by measuring how the network is responding to subscriber demand.

[0073] There has been a change in consumption, demand, delivery, and content ownership transformation of telecommunication industry from traditional transformation to a matrix structure with strategic initiatives based on business analytics. In the telecommunications

industry, intent-based networking and the associated visualization of that activity may be at the center of better operational management and decision making for the cross-functional teams. This visualization is intended to be addressed in the embodiments of the system and method.

[0074] The system is intended to provide for a single closed-loop platform that provides the features to support both network monitoring and management activity based on contextual awareness of subscriber behavior and network access. Secured roles-based access to persona specific dashboards designed to put data into context for that persona type.

[0075] In some cases, second stage authentication to restrict access to sensitive subscriber data such as personal identification usage or billing may be provided, by for example, the user module. Further, second stage authentication may restrict access to review of make changed to business-critical systems or policies.

[0076] In some cases, executive and business leaders may have access to responsive use case dashboards that communicate current status and performance against strategic initiatives on an as-needed basis.

[0077] In some cases, relationship building teams such as marketing, sales or new product development have access to subscriber behavioral trends and related network performance metrics, but may not have access subscriber-specific details or detailed traffics flows data.

[0078] In some cases, authorized customer-facing teams may have access to subscriber-specific information, including user categorization, service score, and network scoring to provide the appropriate level of support to the subscribers.

[0079] In some cases, network operations and engineering teams may have access to use cases dashboards that related to subscriber demand and network performance. These use cases may include specific performance detail applicable to these personas' area of expertise. Leadership from other teams may have access to an overview dashboard for the use cases but not the drill down or administration tools. A specific subset of these users may have restricted access to make changes to the system, threshold or policies that manage the network.

[0080] Navigation within solutions areas and use cases are intended to be contextual to the users' role, permission, and access to a use case or network management features.

[0081] Embodiments of the system and method for providing a network traffic portal are intended to organize solution areas and use cases based on various parameters, for

example, the Return on Investment (ROI) for strategic initiatives in telecommunications. In some cases, each solution area may have a unique icon and color associated with it. As network traffic and subscriber patterns change, the portal may grow to include further solutions areas and use cases.

[0082] Figure 3 is a flow chart of a method 200 for providing a network portal according to an embodiment. At 205, the data collection module 105 collects data associated with the network traffic and subscribers associated with the network traffic. The data may be collected via, for example, deep packet inspection, monitoring traffic flows, subscriber data retrieved from a network provider, or other manner. The data collection module may store the data or have it stored by the memory component of the system.

[0083] At 210, the analysis module 110 analyzes the network traffic data. The analysis module 110 may be configured to attribute various traffic flows to various subscribers to determine the services used by the subscriber and the Quality of Experience (QoE) and Quality of Service (QoS) experienced by the subscriber. The analysis module 110 may also aggregate a plurality of subscriber associated data to determine the network performance for various categories or phenomena of the network. The analysis module 110 may anonymize the data where required for privacy reasons and may also determine which users may have access to which data.

[0084] At 215, the user module 125 may determine a user accessing the network portal via the system 100. The user module 125 is configured to determine the portal user's role in order to provide appropriate data to the user. In some cases the user module 125 may be in communication with the analysis module 110 to determine which users may access what level of data.

[0085] At 220, the reporting module 115 is configured to prepare the dashboard. The reporting module 115 may determine which visualizations are appropriate for the user accessing the network portal. The reporting module 115 may also provide for graphical displays of the analyzed data. In some cases, the reporting module 115 may also send reports or alarms once the data has been analyzed, at 225. The reporting module 115 on determining for example, IPTV fraud, regulatory misalignment, spike in user activity or other issue, may notify an appropriate user or regulatory body via an alarm, for example, an email, a text message, or other form of alarm.

[0086] In still other cases, the reporting module 115 on determining an issue may provide for a traffic action to be issued by the traffic action module 120. In some case, the traffic action may be to prioritize a category of traffic, modify the bandwidth allocation, update or modify a policy, or other action which is intended to provide for a better QoE for subscribers amend the traffic priorities in order to meet certain regulatory requirements.

[0087] Figure 4 illustrates a method 300 for user access to a network portal according to an embodiment. The user logs in at 305. The user module may authenticate the user at 310. The system may also determine the visualizations as well as any licensing or user management determined during authentication. At 315, the portal user is provided access to the QoE portal home to review the analyzed network data. The portal user may then navigate between solution areas at 320 and phenomena at 325 as detailed herein. The user is able to accesses various data based on the user role and the analytics provided. At least some of the analyzed network data may be hidden from the user based on the user's role determined at log in. Other data may be only shown in an amalgamated or aggregated form to some users, based on the user role, while other users may have the ability to see further levels of granularity based on the user's role.

[0088] Use cases may be a defined set of team activities and tasks. Use cases may have a management overview, and may have progressively more detailed dashboards designed with the context of the user personas for that use case. Not all use cases may be designed for all user personas. In some cases, users may be given permissions to a licensed dashboard by a user recognized within the customer's organization to access it.

[0089] Figures 5 to 8 are tables illustrating relationships between various use cases and user roles in an example embodiment of the system for providing a network portal. Figure 5 illustrates solution areas in an example embodiment. The system and method provided herein may provide visualizations in various areas of network operations, for example, analytics, network optimization, revenue generation, revenue assurance, regulatory compliance, automation and the like. Each visualization may have levels of granularity where further details are provided based on the user and the use case.

[0090] Figure 6 is a table illustrating various phenomena or user services according to a specific example. Again, each area may be drilled down or further reviewed to provide a greater level of detail depending on the portal user permissions.

[0091] Figure 7 is a table illustrating various user type and corporation roles of each user type according to a specific example. It would be understood that various networks may refer to their teams in different vernacular and may provide different teams with different access ability.

[0092] Figure 8 is a table illustrating permissions and user roles according to a specific example. It will be understood that the various network operators and regulatory bodies using the system may define user permissions differently.

[0093] In some cases, to provide value to team members from login, embodiments of the system and method for providing a network traffic portal are intended to support the ability for each user to set any dashboard as a preferred landing page.

[0094] Users can set delivery method, frequency, thresholds for when they want to be notified of network performance based on network activity, subscriber activity, score, intent and other key performance indicators. Administrators can set performance thresholds for network activity, subscriber activity, score, intent, and other key performance indicators. Administrators can set decision parameters for use case and network management actives related to network activity, subscriber activity, score, intent, and other key performance indicators.

[0095] In some cases, embodiments of the system and method may include identification of over the top (OTT) service via, for example an operatively connected classification engine which may provide the portal the details of how to identify activity and classify services. The classification engine may also associate user activity with subscribers on the network. The API may result in significant reductions in unidentified traffic and equally significant insight to user intent.

[0096] Service identification at a location level may identify congestion at each network layer for the methods to allow for managing network resources to meet the subscriber demand in the context of the intent. The system may further include service health visualizations (sometimes referred to as tiles) which may be a preformatted way of summarizing and visualizing through a network traffic score and other key performance indicators. Depending on the use case, service visualizations may appear in order of organizational priorities, subscriber use, status or the like. The clear display of score and key performance indicators in the visualizations is intended to allow network operators to track the performance of multiple services. The use case and order of the visualizations within the portal may provide

context to the severity of any issue. In a specific example, in the Service Operations Center, the service tiles represent the subscriber experience across the network. These services health visualizations may provide SOC team to perform some triage investigation before sending on to another team to resolve. Various teams can refer back to the service visualizations to confirm whether resolution appears to be stable. Because the visualizations are displayed in a meaningful relationship, the SOC team can also quickly check the health of related services and quality of experience is also stable.

[0097] In subscriber focused use case, a service visualization might be ordered by top applications used by a specific subscriber. A weak performance visualization at this level may be particular to the subscriber and not reflected up at the network level. The top-level dashboard of the subscriber use case may include a roll-up of the subscriber experience akin to what the SOC may be seeing and provide insight into the subscriber experience specific to the subscriber or a boarder group of subscribers. Providing contextual awareness to the call center or call support team is intended to provide the representative further understanding into how to investigate the issue and escalate where needed.

[0098] In each use case, the team may be working from a single source visualization using data from the same closed-loop system and putting the information in the context of the responsibilities of that user persona.

[0099] Figures 9 to 16 illustrate various solution areas visualizations according to a specific example of the system for providing a network portal. Figure 9 provides an example visualization of a network overview illustrating the traffic profile and various quality levels for subscribers. Figure 10 illustrates a visualization showing the service health of various services in the network. Figure 11 illustrates a visualization of subscriber service performance including latency, throughput and packet-loss the network is currently experiencing. Figure 12 illustrates a specific example of a subscriber's experience with the network and the Quality of Experience the subscriber is experiencing.

[00100] Figure 13 illustrates a specific example of a regulatory body's view of various networks to determine whether each of a plurality of network operators are achieving their stated quality and intent for their subscribers. Figure 14 illustrates a specific example of a network operator's view of quality monitoring of various services. Figure 15 illustrates a specific example of a visualization of a home screen showing QoE KPIs according to a

network operator. Figure 16 illustrates a further level of granularity of QoE KPIs according to a specific example.

[00101] Figs. 17 to 21 illustrate various phenomena visualizations for gaming services according to a specific example of the system for providing a network portal. Figure 17 illustrates a specific example visualization showing analytics of a gaming subscribers. Figure 18 illustrates a specific example visualization showing KPIs associated with cloud gaming. Figure 19 is a specific example showing intent based shaping associated with gaming services. Figure 20 is a specific example visualization showing network optimization in association with gaming services. Figure 21 is a specific example visualization showing revenue generation in relation to gaming services.

[00102] Figs. 22 to 29 illustrate various phenomena visualizations for video services according to a specific example of the system for providing a network portal. Figure 22 shows a specific example visualization of video QoE overview according to a specific use case. Figure 23 shows a specific example visualization of video QoE according to location for a network operator. Figure 24 illustrates a visualization showing potential churn for users of various video services. Figure 25 illustrates an example visualization of intent based shaping for video services. Figure 26 illustrates an example visualization of network optimization for video streaming management. Figure 27 illustrates another example visualization of network optimization for video streaming management. Figure 28 illustrates an example visualization of revenue generation with respect to video services. Figure 29 illustrates an example visualization of revenue assurance and TV fraud management according to a use case.

[00103] Figure 30 illustrates a visualization for a specific example of a health of network elements of the network operator or network associated with the user. The visualization is intended to provide overall network health data as well as individual network element data. From here, it is intended the user is able to determine if there is a network policy that may be updated or another traffic action that may be implemented to improve the network conditions. In some cases, the traffic actions available to the user may be based on the analyzed network data and the user's role determined by the user module.

[00104] As can be seen from the figures, the visualizations may include bar graphs, heat maps, and the like or combinations of a plurality of visual representations.

[00105] Embodiments of the method may include providing a measurement for how the subscriber experience measures up to a strategic performance goal of the organization.

A score for this metric may be represented as a color code numeric value within at least one dashboard of some or all use cases.

[00106] User categorization may be used to define the resource demand from a user's current pattern of activity. The labels indicate what kind of performance the network user type is most likely to expect from the operator. A high spike of light users can create a collective demand on the network that warrants action from the network through social sharing activities over holidays such as New Year's Eve. The launch of a new a new Video on Demand (VOD) services or cloud game can also introduce a spike of high volume users can create demand on the network. The network user type combined with their activity informs how the network should perform to provide good quality of experience. When an administrator sets a threshold, the system and method may actively manage resources in relations to the types of service being used and raise awareness in the content of the user persona viewing the information. For a network engineer persona, it may be that capacity is being rerouted to meet demand. For a customer support persona, it may be an indication of activity on the network that may result in an increase in support investigations.

[00107] Use cases may include a custom visualization design to display various metrics such as, throughput, latency, packet loss, and the like. By displaying these as a single set of metrics, the user can see each data point in relation to each other with a single action for fast decision making.

[00108] In some cases, intent visualizations may map the subscriber activity over the network optimization activity designed to meet the demand signaled by the subscriber intent on a timeline.

[00109] In the network traffic portal, use cases are generally accessed through the corresponding solution area menu. In some embodiments, licensed use cases may display in a particular color (e.g. black) to illustrate that they are available, while unlicensed use cases may display in a different color (e.g. grey) to indicate that they are not currently available. Selecting a licensed use case from the top menu will open the dashboard visualizations and workflow specific to the user role. On the other hand, selecting an unlicensed use case from the menu will show an example dashboard that demonstrates information that will help the end user determine if there would be value in making the changes needed to be able to use the selected unlicensed use case. For example, the demo dashboard may illustrate the return on investment (ROI) if the customer had that use case enabled on their network. In

some cases, the user will be able to interact with the data that demonstrate the ROI of the use case but may not be able to access the features that enable it.

[00110] Examples of the information provided on the example dashboard may include:

- What is the QoE for my subscriber activities?
- How consistent is my QoE?
- How much capacity can be saved with improved heavy user management
- How is the network meeting the demand from Cloud Gamers on the network
- How the demand on the network can be optimized with Fair Usage and capacity management to improve Quality of Experience for each network user type and service.
- How much capacity can be saved to optimize CAPEX
- The projected reduction in customer churn by early identification and better network management
- How much malicious activity appears to be happening and its impact on the network
- How much of the network activity is content video, gaming, social sharing and TV fraud-related
- The projected reduction in truck rolls to a customer site based on additional monitoring or the like
- Example insights to create value and increase revenue by offering innovative plans
- Measurement of the network performance to determine if it is delivering on the brand or plan promise

[00111] Once a new use case is licensed, the feature that manages resources, mitigate risk or offer insight to attract and retain customers; authorized roles will have access to the appropriate dashboards, visualization, and settings features. In some cases, the user may be offered the opportunity to purchase the required upgrade on-line through the network traffic portal itself or via redirection to an on-line store or the like.

[00112] In this description, for purposes of explanation, numerous details are set forth in order to provide a thorough understanding of the embodiments. However, it will be apparent to one skilled in the art that these specific details may not be required. In other instances, well-known structures may be shown in block diagram form in order not to obscure the understanding. For example, specific details are not provided as to whether the

embodiments described herein are implemented as a software routine, hardware circuit, firmware, or a combination thereof. Further, elements of an embodiment may be used with other embodiments and/or substituted with elements from another embodiment as would be understood by one of skill in the art.

[00113] Embodiments of the disclosure can be represented as a computer program product stored in a machine-readable medium (also referred to as a computer-readable medium, a processor-readable medium, or a computer usable medium having a computer-readable program code embodied therein). The machine-readable medium can be any suitable tangible, non-transitory medium, including magnetic, optical, or electrical storage medium including a diskette, compact disk read only memory (CD-ROM), memory device (volatile or non-volatile), or similar storage mechanism. The machine-readable medium can contain various sets of instructions, code sequences, configuration information, or other data, which, when executed, cause a processor to perform steps in a method according to an embodiment of the disclosure. Those of ordinary skill in the art will appreciate that other instructions and operations necessary to implement the described implementations can also be stored on the machine-readable medium. The instructions stored on the machine-readable medium can be executed by a processor or other suitable processing device, and can interface with circuitry to perform the described tasks.

[00114] Applicants reserve the right to pursue any embodiments or sub-embodiments disclosed in this application; to claim any part, portion, element and/or combination thereof of the disclosed embodiments, including the right to disclaim any part, portion, element and/or combination thereof of the disclosed embodiments; or to replace any part, portion, element and/or combination thereof of the disclosed embodiments.

[00115] The above-described embodiments are intended to be examples only. Alterations, modifications and variations can be effected to the particular embodiments by those of skill in the art without departing from the scope, which is defined solely by the claims appended hereto.

What is Claimed is:

1. A method for providing a network portal, the method comprising:

collecting network data for at least one network provider;

analyzing the network data wherein, analyzing the network data comprises:

determining a contextual situation for the analysis of the network data; and

analyzing the data based on the contextual situation;

determining a user role of a user accessing the network portal to review the network data, wherein the user role is based on a corporation role;

providing a visualization of the analyzed network data based on the user role of the user accessing the portal wherein the user role visualization provides network performance based on the analyzed network data and adapts the information displayed depending on the corporate role and the contextual situation;

determining phenomena categories within the network data based on global user activity; and

updating visualizations based on the phenomena categories.

2. A method according to claim 1 wherein the network data comprises:

network traffic flow data selected from the group comprising: Quality of Service data, composition of network traffic, services, Quality of Experience, and network congestion; and

network subscriber data selected from the group comprising: subscriber device type, subscriber service plan, and subscriber traffic flow.

3. A method according to claim 1 further comprising:

determining network performance based on the analyzed network data; and

providing a traffic action to the network based on the network performance.

4. A method according to claim 3 wherein the traffic action comprises reprioritizing at least some of the network traffic.

5. A method according to claim 3 wherein the traffic action comprises notifying at least one user of the network portal of the network performance.

6. A method according to claim 1 wherein at least some of the analyzed network data is hidden from a user based on the user's role.

7. A method according to claim 1 further comprising:

presenting traffic actions available to the user based on the analyzed network data and the user's role.

8. A method according to claim 1 wherein the visualization provides the user an ability to view further levels of granularity with respect to the analyzed network data.

9. A method according to claim 1 wherein the visualization is customized by the user.

10. A system for providing a network portal, the system comprising:

a data collection module configured to collect network data for at least one network provider;

an analysis module configured to analyze the network data, wherein, analyzing the network data comprises:

determining a contextual situation for the analysis of the network data;

analyzing the data based on the contextual situation;

determining phenomena categories within the network data based on global user activity; and

updating visualizations based on the phenomena categories;

a user module configured to determine a user role of a user accessing the network portal to review the network data, wherein the user role is based on corporation role; and

a reporting module configured to provide a visualization of the analyzed network data based on the user role and adapts the information displayed depending on the corporate role and the contextual situation.

11. A system according to claim 10 wherein the network data comprises:

network traffic flow data selected from the group comprising: Quality of Service data, composition of network traffic, services, Quality of Experience, and network congestion; and

network subscriber data selected from the group comprising: subscriber device type, subscriber service plan, and subscriber traffic flow.

12. A system according to claim 10 wherein the analysis module is configured to determine network performance based on the analyzed network data; and
a traffic action module is configured to provide a traffic action to the network based on the network performance.
13. A system according to claim 12 wherein the traffic action comprises reprioritizing at least some of the network traffic.
14. A system according to claim 12 wherein the traffic action comprises notifying at least one user of the network portal of the network performance.
15. A system according to claim 10 wherein at least some of the analyzed network data is hidden from a user based on the user's role.
16. A system according to claim 10 further comprising:
a traffic action module configured to present traffic actions available to the user based on the analyzed network data and the user's role.
17. A system according to claim 10 wherein the visualization provides the user an ability to view further levels of granularity with respect to the analyzed network data.
18. A system according to claim 10 wherein the visualization is customized by the user.
19. A method for providing a network portal, the method comprising:
collecting network data for at least one network provider;
analyzing the network data wherein, analyzing comprises:
determining a contextual situation for the analysis of the network data; and
analyzing the data based on the contextual situation;
determining a user role of a user accessing the network portal to review the network data, wherein the user role is based on corporation role;
providing a user role visualization of the analyzed network data based on the user role of the user accessing the portal, wherein the user role visualization provides network performance based on the analyzed network data and adapts the information displayed depending on the corporate role and contextual situation;

determining phenomena categories within the network data based on global user activity;
updating visualizations based on the phenomena categories; and
providing a traffic action to the network based on the network performance, wherein the traffic action comprises reprioritizing at least some of the network traffic.

20. A method according to claim 19 wherein the network data comprises:

network traffic flow data selected from the group comprising: Quality of Service data, composition of network traffic, services, Quality of Experience, and network congestion; and

network subscriber data selected from the group comprising: subscriber device type, subscriber service plan, and subscriber traffic flow.

21. A method according to one of claim 19 and 20 wherein the traffic action further comprises notifying at least one user of the network portal of the network performance.

22. A method according to any one of claims 19 to 21 wherein at least some of the analyzed network data is hidden from a user based on the user's role.

23. A method according to any one of claims 19 to 22 further comprising:

presenting further traffic actions available to the user based on the analyzed network data and the user's role.

24. A method according to any one of claims 19 to 23 wherein the user role visualization provides the user an ability to view further levels of granularity with respect to the analyzed network data.

25. A system for providing a network portal, the system comprising:

a data collection module configured to collect network data for at least one network provider;

an analysis module configured to analyze the network data and to provide network performance based on the analyzed network data, wherein, analyzing the network data comprises:

determining a contextual situation for the analysis of the network data;

analyzing the data based on the contextual situation;

determining phenomena categories within the network data based on global user activity; and

- updating visualizations based on the phenomena categories;
- a user module configured to determine a user role of a user accessing the network portal to review the network data, wherein the user role is based on corporation role;
- a reporting module configured to provide a user role visualization of the network performance based on the user role and adapts the information displayed depending on the corporate role and the contextual situation; and
- a traffic action module configured to provide a traffic action to the network based on the network performance, wherein the traffic action comprises reprioritizing at least some of the network traffic.

26. A system according to claim 25 wherein the network data comprises:

- network traffic flow data selected from the group comprising: Quality of Service data, composition of network traffic, services, Quality of Experience, and network congestion; and
- network subscriber data selected from the group comprising: subscriber device type, subscriber service plan, and subscriber traffic flow.

27. A system according to one of claim 25 and 26 wherein the traffic action further comprises notifying at least one user of the network portal of the network performance.

28. A system according to any one of claims 25 to 27 wherein at least some of the analyzed network data is hidden from a user based on the user's role.

29. A system according to any one of claims 25 to 28 wherein the traffic action module is configured to present further traffic actions available to the user based on the analyzed network data and the user's role.

30. A method for providing a platform portal, the method comprising:

- collecting network data for at least one platform associated with a network;
- analyzing the network data;
- determining phenomena categories within the network data based on global user activity; and
- determining a user role of a user accessing the portal to review the network data, wherein the user role is based on a corporation role; and

providing a user role visualization of the analyzed network data based on the user role of the user accessing the portal and the phenomena categories; and
updating visualizations based on the phenomena categories.

31. A method according to claim 30 wherein the network data comprises:

traffic flow data selected from the group comprising: Quality of Service data, composition of network traffic, services, Quality of Experience, and network congestion; and
subscriber data selected from the group comprising: subscriber device type, subscriber service plan, and subscriber traffic flow.

32. A method according to one of claim 30 or 31 further comprising:

determining network performance based on the analyzed network data; and
providing a traffic action to the network based on the network performance.

33. A method according to claim 32 wherein the traffic action comprises reprioritizing at least some of the network traffic.

34. A method according to claim 32 wherein the traffic action comprises notifying at least one user of the portal of the performance.

35. A method according to any one of claims 30 to 34 wherein at least some of the analyzed network data is hidden from a user based on the user's role.

36. A method according any one of claims 30 to 35 further comprising:

presenting traffic actions available to the user based on the analyzed network data and the user's role.

37. A method according to any one of claims 30 to 36 wherein the visualization provides the user an ability to view further levels of granularity with respect to the analyzed network data.

38. A method according to any one of claims 30 to 37 wherein the visualization is customized by the user.

39. A method according to any one of claims 30 to 38 wherein the portal provides access to an independent vendor platform.

40. A method according to claim 39 wherein the access to the vendor platform provides for monitoring, managing and marketing to subscriber demands.

41. A system for providing a platform portal, the system comprising:

- a data collection module configured to collect network data for at least one platform associated with a network;

- an analysis module configured to analyze the network data and determine phenomena categories within the network data based on global user activity and update the data based on the phenomena categories;

- a user module configured to determine a user role of a user accessing the portal to review the network data, wherein the user role is based on a corporation role; and

- a reporting module configured to provide a user role visualization of the network performance based on the user role of the user accessing the portal and the phenomena categories.

42. A system according to claim 41 wherein the network data comprises:

- traffic flow data selected from the group comprising: Quality of Service data, composition of network traffic, services, Quality of Experience, and network congestion; and

- subscriber data selected from the group comprising: subscriber device type, subscriber service plan, and subscriber traffic flow.

43. A system according to one of claim 41 or 42, wherein the analysis module is configured to determine performance based on the analyzed network data; and

- a traffic action module is configured to provide a traffic action to the network based on the performance.

44. A system according to claim 43 wherein the traffic action comprises reprioritizing at least some of the network traffic.

45. A system according to claim 43 wherein the traffic action comprises notifying at least one user of the portal of the performance.

46. A system according to any one of claims 41 to 45 wherein at least some of the analyzed network data is hidden from a user based on the user's role.

47. A system according to any one of claims 41 to 46 further comprising:

a traffic action module configured to present traffic actions available to the user based on the analyzed network data and the user's role.

48. A system according to any one of claims 41 to 47 wherein the visualization provides the user an ability to view further levels of granularity with respect to the analyzed network data.

49. A system according to any one of claims 41 to 48 wherein the visualization is customized by the user.

50. A system according to any one of claims 41 to 49 wherein the analysis module comprises at least one business intelligence platform configured to merge data from a disconnected data source.

51. A method for providing a portal, the method comprising:

collecting network data;

analyzing the network data;

identifying network trends based on key network performance quality indicators;

determining a user role of a user accessing the portal to review the network data,

wherein the user role is based on a corporation role;

providing a user role visualization of the analyzed network data based on the user role of the user accessing the portal, wherein the user role visualization provides network performance based on the analyzed network data and identified network trends

determining phenomena categories within the network data based on global user activity; and

updating visualizations based on the phenomena categories.

52. A method according to claim 51 wherein the network data comprises:

traffic flow data selected from the group comprising: Quality of Service data, composition of network traffic, services, Quality of Experience, and network congestion; and

subscriber data selected from the group comprising: subscriber device type, subscriber service plan, and subscriber traffic flow.

53. A method according to one of claim 51 or 52 further comprising:
determining network performance based on the analyzed network data; and
providing a traffic action to the network based on the network performance.
54. A method according to claim 53 wherein the traffic action comprises reprioritizing at least some of the network traffic.
55. A method according to claim 53 wherein the traffic action comprises notifying at least one user of the portal of the performance.
56. A method according to any one of claims 51 to 55 wherein at least some of the analyzed network data is hidden from a user based on the user's role.
57. A method according any one of claims 51 to 56 further comprising:
presenting traffic actions available to the user based on the analyzed network data and the user's role.
58. A method according to any one of claims 51 to 57 wherein the visualization provides the user an ability to view further levels of granularity with respect to the analyzed network data.
59. A method according to any one of claims 51 to 58 wherein the visualization is customized by the user.
60. A method according to any one of claims 51 to 59 wherein the portal provides access to an independent vendor platform.
61. A method according to claim 60 wherein the access to the vendor platform provides for monitoring, managing and marketing to subscriber demands.
62. A system for providing a portal, the system comprising:
a data collection module configured to collect network data;
an analysis module configured to analyze the network data;
to identify network trends based on key network performance quality indicators;

determine phenomena categories within the network data based on global user activity;
and
update visualizations based on the phenomena categories;
a user module configured to determine a user role of a user accessing the portal to review the network data, wherein the user role is based on a corporation role; and
a reporting module configured to provide a visualization of the analyzed network data based on the user role of the user accessing the portal and identified network trends.

63. A system according to claim 62 wherein the network data comprises:

traffic flow data selected from the group comprising: Quality of Service data, composition of network traffic, services, Quality of Experience, and network congestion; and
subscriber data selected from the group comprising: subscriber device type, subscriber service plan, and subscriber traffic flow.

64. A system according to one of claim 62 or 63, wherein the analysis module is configured to determine performance based on the analyzed network data; and

a traffic action module is configured to provide a traffic action to the network based on the performance.

65. A system according to claim 64 wherein the traffic action comprises reprioritizing at least some of the network traffic.

66. A system according to claim 64 wherein the traffic action comprises notifying at least one user of the portal of the performance.

67. A system according to any one of claims 62 to 66 wherein at least some of the analyzed network data is hidden from a user based on the user's role.

68. A system according to any one of claims 62 to 67 further comprising:

a traffic action module configured to present traffic actions available to the user based on the analyzed network data and the user's role.

69. A system according to any one of claims 62 to 68 wherein the visualization provides the user an ability to view further levels of granularity with respect to the analyzed network data.

70. A system according to any one of claims 62 to 69 wherein the visualization is customized by the user.

71. A system according to any one of claims 62 to 70 wherein the analysis module comprises at least one business intelligence platform configured to merge data from a disconnected data source.




FIG. 1




FIG. 2




FIG. 3




Fig. 4

Solution Area	Use Case Name
QoE KPIs	ScoreCard Analysis
Analytics	Network Performance Monitoring and Analysis
Network intelligence in context of subscribers, services, devices and plans	Subscriber Service Analysis
	Capacity Planning Analysis
	User Behavior and Demographic Analysis
	Video QoE Analysis
	VoIP and VoLTE QoE Analysis
	Gaming QoE Analysis
Network Optimization	Cyber Threat Analysis
	Fair Usage and Congestion Management
	Video Streaming Management
	Heavy User Management
	Wholesale and Peering Link Management
	Carrier-Grade NAT (CGNAT)
	Traffic Steering/Diversion
	TCP Optimization
	Gaming QoE Management
	Cyber Threat Management and Mitigation
Revenue Generation	Zero-Rating and Application Based Plans
Network intelligence to deliver services to meet subscriber intent	Usage-Based Services
	Parental Control
Revenue Assurance	Interconnect Bypass Fraud
Protect your revenue streams from fraud with granular network intelligence	Video and Television Fraud Management
	Data Revenue Leakage Management
	Data Fraud Management
Regulatory Compliance	Regulatory Quality Monitoring
Comply with changing network operator regulations with network intelligence-based solutions	Regulatory Voice-over-IP Management
	Regulatory Traffic Management
	Regulatory Data Retention
	Regulatory Quality Monitoring

Fig. 5

Phenomena	Use Case
QoE KPIs	QoE KPI Analysis
Video	Video QoE Analysis
Intent focused cross functional view of use cases	Video Streaming Management
	Zero-Rating and Application Based Plans
	Video and Television Fraud Management
	Intent-Based Congestion Management
	Automated Churn Prediction and Prevention
Gaming	Gaming QoE Analysis
Intent focused cross functional view of use cases	Gaming QoE Management
	Zero-Rating and Application Based Plans
	Intent-Based Congestion Management
	Automated Churn Prediction and Prevention
	Subscriber Service Analysis
Social Sharing	Zero-Rating and Application Based Plans
Intent focused cross functional view of use cases	Data Fraud Management

FIG.6

Team	Portal User Types
Executive	CEO
Information focused on providing status for strategic business initiatives facing Network operators today.	CTO
	CSIO
	CMO
	VP Product
Sales and Marketing	CMO
Monitor subscriber trends and deliver to meet intent.	VP Marketing
	Product Marketers
	Sales Leadership
Network Operations	Network Operations Leadership
Monitor trends and manage resources and deliver consistent QoE	Network Operation Center
	Service Operations Center
	Network Planning
Network Engineering	Network Engineers
Monitor trends, manage resources and make modifications to deliver consistent QoE	RAN Engineers
	RAN Development
Revenue Assurance	Revenue Assurance Leadership
Monitor and manage fraud in the network.	Fraud Monitoring Teams
	Loyalty and Retention
Retention	Level 2 and 3 Customer Support Teams
Monitor trends and QoE	
Support	Regulatory Governing Body Officer
Monitor and investigate QoE	
Regulatory	Operator Regulatory Compliance Officer
Monitor and investigate QoE	

Fig. 7

Permissions	Portal User Types
Notifications	Thresholds notifications managed by authorized portal administrator
	Delivery preferences by authorized portal user
Settings	Thresholds notifications managed by authorized portal administrator
	Delivery preferences by authorized portal user
Use Case Access	Managed by authorized portal administrator
Subscriber Personal Information	Managed by authorized portal administrator

Fig. 8





Fig. 10






Fig. 13

Fig. 15






Fig. 16



📶 Network: Mobile 4G 📶 Filter ➡ Share 📅 Last 24 hours


Top 10 Cloud Services	Volume	Subscriber count
GeForce NOW	↑ 901 GB	↑ 13,923
Microsoft xCloud	↑ 891 GB	↑ 13,174
Google Stadia	↑ 875 GB	↑ 12,923
Shadow	↑ 812 GB	↑ 12,906
Parsec Cloud	↑ 793 GB	↑ 11,901
Blacknut	↑ 789 GB	↑ 11,874
Playkey	↓ 771 GB	↓ 10,345
Liquid Sky	↑ 641 GB	↑ 10,113



Latency Score Distribution



Top 10 Gaming Plans	Volume	Subscriber count
Fios Gigabit internet	↑ 901 GB	↑ 13,923
Ultra 1 Gbps Broadband	↑ 891 GB	↑ 13,174
Gigablast	↑ 875 GB	↑ 12,923
Fibre Gold Unlimited	↑ 812 GB	↑ 12,906
Bundle Unlimited	↑ 793 GB	↑ 11,901
Silver Unlimited	↑ 789 GB	↑ 11,874
Limitless 6 Month	↓ 771 GB	↓ 10,345
Internet Ultimate	↑ 641 GB	↑ 10,113
Internet Preferred 150	↓ 569 GB	↓ 10,104
Premium Month-to-Month	↓ 561 GB	↓ 10,045




Google Stadia
23 TB
50.4%


- Google Stadia
- Project xCloud
- nVidia Shield
- PS4
- Xbox One
- Switch
- PS3
- Xbox 360
- iPhone
- Android

Google Stadia	Popularity	Play Time		Latency	
Game Service	Subscriber count	Total time	Average time	Latency In	Latency out
Google Stadia	80,421	323:53:25	02:53:25	21 ms	22 ms

Date Recue/Date Received 2021-10-01

Fig. 19





Usage patterns

Sunday

Monday

Tuesday

Wednesday

Thursday

Friday

Saturday

Subscriber count

140K

120K

100K

80K

60K

40K

20K

0K

Total volume (GB)

0

200

300

350

400

450

500

550

600

650

700

750

800

Volume (GB)

1000

750

500

250

0

Peak hour

0

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

0-10%

11-19%

20-25%

30-39%

40-49%

50-59%


60-69%

70-79%

80-89%

90-100%

Fig. 21



Heavy Gamer (8+ hours)
6%
3,456 subs +3% from previous 24 hours

Services

Volume

Netflix
Amazon Prime
HTTP media stream
Hulu
Disney+
HBO Now
Google Play
iTunes purchase
Xbox
Playstation Vue

0 100 200 300 400 500
Total GB

Frequent Gamer (4-6 hours)
13%
8,571 subs +3% from previous 24 hours

Devices

Volume

Galaxy 9
iPhone 11
Galaxy 10
iPad Pro
Note 10
LG C9 OLED TV
Samsung Q90
QLED TV
iPhone X
Windows

0 100 200 300 400 500
Total GB

Average Gamer (1-4 hours)
41%
18,456 subs -2% from previous 24 hours

Locations

Volume

IDF-APC450M-IA1-225-57-35
TXV-APC450-STN-NO-57567
G4-APC450M-UTEDN240-060
SCO-APC450M-CAL-300-105
TXL-APC450M-VEN-045-214
OKF-APC450M-LUH-150-004
OF7LW25-UCSSTWE4-556
OKB-APZ-POT-SW-25
OBZPOT32
OKD-APZ-CDL-EA-25

0 100 200 300 400 500
Total GB

Occasional Gamer (0-1 hour)
30%
16,456 subs -2% from previous 24 hours


Locations

Volume

IDF-APC450M-IA1-225-57-35
TXV-APC450-STN-NO-57567
G4-APC450M-UTEDN240-060
SCO-APC450M-CAL-300-105
TXL-APC450M-VEN-045-214
OKF-APC450M-LUH-150-004
OF7LW25-UCSSTWE4-556
OKB-APZ-POT-SW-25
OBZPOT32
OKD-APZ-CDL-EA-25


0 100 200 300 400 500
Total GB

Fig. 22



Automated Churn Prediction and Prevention Overview

Network Mobile Filter Share Last week



Feature Importance			Subscriber count							% of total		
Network Performance												
Throughput	↑	155	↑ 0.32%		7911 123456		↑	72%	Shared 20GB	Netflix	Score	Most frequent location
Latency	↑	147	↓ 2.05%		7911 234567		↓	71%	Shared 7GB	YouTube		
Loss / Latency	↓	142	↑ 0.29%		7911 345678		↑	71%	Shared 10GB	Xbox Live TLS		
Location	↑	138	↓ 1.31%		7911 456789		↑	70%	Shared 7GB	Playstation net download		
Plan	↓	126	↑ 1.91%		7911 567890		↑	68%	Shared 5GB	Amazon Prime		
Quality of Experience												
Video	↑	108	↑ 3.07%		7911 678901		↓	68%	Shared 2GB	Netflix		
Gaming	↓	106	↓ 2.3%		7911 789012		↑	67%	Shared 1GB	Hulu		
Social Sharing	↑	109	↑ 1.1%		7911 890123		↑	67%	Shared 5GB	HTTP media stream		
Business VoIP	↑	138	↑ 1.91%		7911 567890		↑	65%	Shared 1GB	iTunes purchase		
IoT	↓	126	↑ 1.17%		7911 678901		↓	65%	Shared 1GB	SSL v3		
Threats	↑	109	↑ 3.07%		7911 789012		↑	63%	Shared 5GB	Xbox Live Update		
					7911 890123		↓	63%	Shared 2GB	Netflix		

Fig. 24


Performance - OBZPOT32 N7CWDEA7

Did not meet minimum score **+1%** **↑**
30 (3%) did not meet minimum
 Met minimum score **+8%** **↑**
 Intent target score met **+17%** **↑**
900 (90%) meet minimum
170 (17%) target

📶 Network: Mobile 📅 Next 3 months

🔗 Share

🔍 Filter



Locations in congestion




Fig. 25




Fig. 28




Fig. 29

System Health

Status

Unassigned_system_name
...

23
Elements

9 **online**

! 32 > critical

Configuration

34 misconfig

302 changes

NA - West

Performance

Subscriber count

Subscriber count
3,124,578 subscribers

Bandwidth

↓↑ 9,876 Gbps

NA - South

200 PRE

204 MPE

10 IDS

2 ANI Portal

8%

16 of are below acceptable thresholds.

Element name	Classification Accuracy	Packet Drops	Bandwidth	Packet Processing CPU load	System CPU load
KOKA-APZ-ENS-NW-25 ODZENS42	98%	1,521 / sec	200 Gbps	95%	98%
NVW-APC450M-SNT-90-200 IWCS	98%	1,349 / sec	200 Gbps	90%	98%
KOKB-APZ-POT-SW-25 OBZPOT32	98%	1,012 / sec	200 Gbps	88%	94%
KOKD-APZ-CDL-EA-25 ODZCOLE2	98%	1,921 / sec	200 gbps	87%	88%
KOKD-APZ-CDL-EA-25 ODZCDLE7	98%	1,191 / sec	200 Gbps	83%	81%
KOKF-APZ-BRG-NW-25 OFZBRG42	98%	1,261 / sec	200 Gbps	83%	78%
				83%	75%

Fig. 30

