



(86) Date de dépôt PCT/PCT Filing Date: 2014/05/30

(87) Date publication PCT/PCT Publication Date: 2015/01/08

(45) Date de délivrance/Issue Date: 2017/04/11

(85) Entrée phase nationale/National Entry: 2015/12/30

(86) N° demande PCT/PCT Application No.: JP 2014/064511

(87) N° publication PCT/PCT Publication No.: 2015/001884

(30) Priorité/Priority: 2013/07/05 (JP2013-141932)


(51) Cl.Int./Int.Cl. *C02F 5/00* (2006.01),
B01D 9/02 (2006.01), *C02F 1/52* (2006.01),
C02F 1/66 (2006.01), *C02F 5/06* (2006.01),
C02F 5/08 (2006.01), *C02F 9/00* (2006.01),
C02F 9/04 (2006.01)

(72) Inventeurs/Inventors:
EDA, MASAYUKI, JP;
OKINO, SUSUMU, JP;
YOSHIYAMA, RYUJI, JP;
SAKURAI, HIDEAKI, JP;
UKAI, NOBUYUKI, JP;
...

(73) Propriétaire/Owner:

(54) Titre : PROCEDE DE TRAITEMENT D'EAU, ET SYSTEME DE TRAITEMENT D'EAU

(54) Title: WATER TREATMENT PROCESS AND WATER TREATMENT SYSTEM



(57) Abrégé/Abstract:

Provided are a water treatment system and a water treatment method with which salt-containing water can be recycled with a high water recovery rate. In this water treatment system (300) and water treatment method, a scale inhibitor is supplied to water to be

(72) **Inventeurs(suite)/Inventors(continued):** SUZUKI, HIDEO, JP; NAKASHOJI, HIROSHI, JP; YOSHIOKA, SHIGERU, JP

(73) **Propriétaires(suite)/Owners(continued):** MITSUBISHI HEAVY INDUSTRIES, LTD., JP

(74) **Agent:** SMART & BIGGAR

(57) **Abrégé(suite)/Abstract(continued):**

treated including Ca ions, SO₄ ions, carbonate ions, and silica, and the water to be treated is adjusted to a pH capable of dissolving silica. Having had a calcium-scale inhibitor added thereto and the pH thereof adjusted, the water to be treated is separated by a first desalination unit (10) into treated water, and concentrated water in which the Ca ions, SO₄ ions, carbonate ions, and silica are concentrated. In a first crystallization unit (20), gypsum seed crystals are supplied to first concentrated water, and gypsum crystallizes and is removed from the first concentrated water. The silica in the water to be treated is removed from the first concentrated water at a downstream side of the first crystallization unit (20) with respect to the water to be treated. Calcium carbonate in the water to be treated is removed from the first concentrated water at an upstream side of the first desalination unit (10), or at a downstream side of the first crystallization unit (20).

(12) 特許協力条約に基づいて公開された国際出願

(19) 世界知的所有権機関
国際事務局(43) 国際公開日
2015 年 1 月 8 日(08.01.2015)(10) 国際公開番号
WO 2015/001884 A1

(51) 国際特許分類:

C02F 9/00 (2006.01)	C02F 1/42 (2006.01)
B01D 9/02 (2006.01)	C02F 1/44 (2006.01)
B01D 19/00 (2006.01)	C02F 1/469 (2006.01)
B01D 61/08 (2006.01)	C02F 1/52 (2006.01)
B01D 61/42 (2006.01)	C02F 5/00 (2006.01)
B01D 61/58 (2006.01)	C02F 5/10 (2006.01)
C02F 1/20 (2006.01)	C02F 5/14 (2006.01)

(21) 国際出願番号: PCT/JP2014/064511

(22) 国際出願日: 2014 年 5 月 30 日(30.05.2014)

(25) 国際出願の言語: 日本語

(26) 国際公開の言語: 日本語

(30) 優先権データ:

特願 2013-141932 2013 年 7 月 5 日(05.07.2013) JP


(71) 出願人: 三菱重工業株式会社 (MITSUBISHI HEAVY INDUSTRIES, LTD.) [JP/JP]; 〒1088215 東京都港区港南二丁目 1 6 番 5 号 Tokyo (JP).

(72) 発明者: 江田 昌之(EDA, Masayuki); 〒1088215 東京都港区港南二丁目 1 6 番 5 号 三菱重工業株式会社内 Tokyo (JP). 沖野 進(OKINO, Susumu); 〒1088215 東京都港区港南二丁目 1 6 番 5 号 三菱重工業株式会社内 Tokyo (JP). 吉山 隆士(YOSHIYAMA, Ryuji); 〒1088215 東京都港区港南二丁目 1 6 番 5 号 三菱重工業株式会社内 Tokyo (JP). 櫻井 秀明(SAKURAI, Hideaki); 〒1088215 東京都港区港南二丁目 1 6 番 5 号 三菱重工業株式会社内 Tokyo (JP). 鵜飼 展行(UKAI, Nobuyuki); 〒1088215 東京都港区港南二丁目 1 6 番 5 号 三菱重工業株式会社内 Tokyo (JP). 鈴木 英夫(SUZUKI, Hideo); 〒1088215 東京都港区港南二丁目 1 6 番 5 号 三菱重工業株式会社内 Tokyo (JP). 中小路 裕(NAKASHOJI, Hiroshi); 〒1088215 東京都港区港南二丁目 1 6 番 5 号 三菱重工業株式会社内 Tokyo (JP). 吉岡 茂(YOSHIOKA, Shigeru); 〒1088215 東京都港区港南二丁目 1 6 番 5 号 三菱重工業株式会社内 Tokyo (JP).

[続葉有]

(54) Title: WATER TREATMENT METHOD, AND WATER TREATMENT SYSTEM

(54) 発明の名称: 水処理方法及び水処理システム



AA WATER TO BE TREATED
BB POLYMER
CC FIRST CONCENTRATED WATER
DD TREATED WATER
EE GYPSUM
FF SECOND CONCENTRATED WATER
GG CONCENTRATED WATER

(57) Abstract: Provided are a water treatment system and a water treatment method with which salt-containing water can be recycled with a high water recovery rate. In this water treatment system (300) and water treatment method, a scale inhibitor is supplied to water to be treated including Ca ions, SO₄ ions, carbonate ions, and silica, and the water to be treated is adjusted to a pH capable of dissolving silica. Having had a calcium-scale inhibitor added thereto and the pH thereof adjusted, the water to be treated is separated by a first desalination unit (10) into treated water, and concentrated water in which the Ca ions, SO₄ ions, carbonate ions, and silica are concentrated. In a first crystallization unit (20), gypsum seed crystals are supplied to first concentrated water, and gypsum crystallizes and is removed from the first concentrated water. The silica in the water to be treated is removed from the first concentrated water at a downstream side of the first crystallization unit (20) with respect to the water to be treated. Calcium carbonate in the water to be treated is removed from the first concentrated water at an upstream side of the first desalination unit (10), or at a downstream side of the first crystallization unit (20).

(57) 要約:

[続葉有]

WO 2015/001884 A1



- (74) 代理人: 藤田 考晴, 外(FUJITA, Takaharu et al.);
〒2208137 神奈川県横浜市西区みなとみらい2
- 2 - 1 横浜ランドマークタワー37F
Kanagawa (JP).

(81) 指定国 (表示のない限り、全ての種類の国内保護が可能): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) 指定国 (表示のない限り、全ての種類の広域保護が可能): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), ユーラシア (AM, AZ, BY, KG, KZ, RU, TJ, TM), ヨーロッパ (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

添付公開書類:
— 国際調査報告 (条約第 21 条(3))

高い水回収率で塩類を含む水を再生することができる水処理システム及び水処理方法を提供する。本発明の水処理システム（300）及び水処理方法において、Ca²⁺イオン、SO₄²⁻イオン、炭酸イオン及びシリカを含む被処理水に対してスケール防止剤を供給され、シリカが溶解可能なpHに被処理水が調整される。カルシウムスケール防止剤が添加されpHが調整された被処理水が、第1脱塩部（10）でCa²⁺イオン、SO₄²⁻イオン、炭酸イオン及びシリカが濃縮された濃縮水と処理水とに分離される。第1晶析部（20）において第1濃縮水に石膏の種結晶が供給され、石膏が晶析して第1濃縮水から除去される。被処理水中のシリカは、第1晶析部（20）の被処理水下流側で、第1濃縮水から除去される。被処理水中の炭酸カルシウムは、第1脱塩部（10）の上流側、または、第1晶析部（20）の下流側で、第1濃縮水から除去される。

{DESCRIPTION}

{Title of Invention}

WATER TREATMENT PROCESS AND WATER TREATMENT SYSTEM

{Technical Field}

{0001}

The present invention relates to a water treatment process and a water treatment system for reproducing water to be treated containing Ca ions (Ca^{2+}), sulfate ions (SO_4^{2-}), carbonate ions, and silica.

{Background Art}

{0002}

It is known that industrial waste water, saline water, and sewage contain large amounts of ions and silica. In addition, in a cooling tower, heat is exchanged between a high-temperature exhaust gas discharged from the boiler, etc., and cooling water. As a result of this heat exchange, some of the cooling water turns into steam, and, accordingly, ions and silica in the cooling water are concentrated. Therefore, the cooling water discharged from the cooling tower (blowdown water) has increased concentrations of ions and silica.

{0003}

Water containing a large amount of ions is subjected to a demineralization treatment and then discharged into the environment. As devices that perform the demineralization treatment, a reverse osmosis membrane device, a nanofiltration

membrane device, an ion-exchange equipment, and the like are known.

{0004}

Among ions contained in the water mentioned above, monovalent cations such as Na^+ , K^+ , and NH_4^+ and anions such as Cl^- and NO_3^- are highly soluble in water. On the other hand, divalent metal ions such as Ca^{2+} , anions such as SO_4^{2-} and CO_3^{2-} , and silica are scale-forming components. Salts and silica of scale-forming components have low solubility in water, and thus they tend to be deposited as scales. In particular, the saline water, industrial waste water, and blowdown water from a cooling tower mentioned above contain large amounts of Ca^{2+} , SO_4^{2-} , carbonate ions (CO_3^{2-} , HCO_3^-), and silica. An example of the property is as follows: pH: 8, Na ions: 20 mg/L, K ions: 5 mg/L, Ca ions: 50 mg/L, Mg ions: 15 mg/L, HCO_3^- ions: 200 mg/L, Cl ions: 200 mg/L, SO_4^{2-} ions: 120 mg/L, PO_4^{3-} ions: 5 mg/L, SiO_2 ions: 35 mg/L. Among these, the concentrations of Ca ions, Mg ions, SO_4^{2-} ions, and HCO_3^- ions are high, and as a result of their reaction, scales (CaSO_4 , CaCO_3 , etc.) are formed. In addition, depending on the concentration percentage, silica components present in waste water also serve as scale components adhering to the instrument, etc. When scales are produced in the device that performs a demineralization treatment, the treatment capacity is reduced. Therefore, it is required to perform a demineralization

treatment without allowing for the production of scales.

{0005}

Here, examples of plants using a water-cooling-type cooling tower are plants equipped with power generation facilities (power generation facilities include those for business purposes for electric power selling and those for industrial purposes for in-house electricity use, and the power generation is thermal power generation, geothermal power generation, etc.), plants equipped with power generation facilities and cooling facilities, etc. In addition, plants include ordinary chemical plants, steel plants, mining plants, oil field plants, gas field plants, mechanical plants, etc.

{0006}

As a process for removing Ca ions, a lime soda process is known. According to the lime soda process, sodium carbonate is added to water to be treated, and Ca ions in the water to be treated are deposited/precipitated as calcium carbonate and thereby removed from the water.

{0007}

Patent Literature 1 discloses a waste water treatment device including a combination of a chemical softening device, an ion-exchange equipment, a reverse osmosis membrane device, and the like using the lime soda process.

{Citation List}

{Patent Literature}

{0008}

{PTL 1} U.S. Pat. No. 7815804

{Summary of Invention}

{Technical Problem}

{0009}

The lime soda process requires the addition of sodium carbonate for the treatment, and thus the treatment cost is high. In the lime soda process, when 1 mol of Ca ions are precipitated as calcium carbonate, 2 mol of Na^+ is produced. Meanwhile, in the case where SO_4^{2-} is contained in water to be treated, it is not removed by the lime soda process. That is, in the lime soda process, water after the treatment contains an increased number of moles of ions.

{0010}

Also in the case where Ca ions are removed using an ion-exchange equipment, the treatment of 1 mol of Ca ions results in the production of 2 mol of Na^+ , and water the after treatment contains an increased number of moles of ions.

{0011}

According to the system of Patent Literature 1, water that has been treated by the lime soda process and in an ion-exchange equipment is further treated in a reverse osmosis membrane device to remove ion components. Accordingly, the system of Patent Literature 1 has a problem in that because of the increased number of moles of ions, the osmotic pressure in

the reverse osmosis membrane device is high, resulting in an increased treatment load. In addition, with the device of Patent Literature 1, SO_4^{2-} is not removed but remains in the treated water, and it has been difficult to obtain high water recovery.

In addition, the waste water treatment device of Patent Literature 1 requires a large amount of chemicals for the reproduction of the ion-exchange equipment, and thus there has also been the problem of high treatment cost.

{0012}

An object of the present invention is to provide a water treatment process and a water treatment system, which are capable of reproducing water containing salts with high water recovery.

{Solution to Problem}

{0013}

A first aspect of the present invention is a water treatment process including:

a first scale inhibitor supplying step of supplying a calcium scale inhibitor which is a scale inhibitor for inhibiting the deposition of a scale containing calcium to water to be treated containing Ca ions, SO_4 ions, carbonate ions, and silica;

a first pH adjusting step of adjusting the water to be treated to a pH at which the silica is soluble in the water to

be treated;

a first demineralizing step of separating the water to be treated into first concentrated water in which the Ca ions, the SO₄ ions, the carbonate ions, and the silica are concentrated and treated water after the first scale inhibitor supplying step and the first pH adjusting step; and

a first crystallizing step of supplying seed crystals of gypsum to the first concentrated water so that gypsum is crystallized from the first concentrated water;

wherein the water treatment process further includes after the first crystallizing step,

a second scale inhibitor supplying step of supplying the calcium scale inhibitor and a silica scale inhibitor which is a scale inhibitor for inhibiting the deposition of silica to the water to be treated;

a second demineralizing step of separating the water to be treated into second concentrated water in which the Ca ions, the SO₄ ions, the carbonate ions, and the silica are concentrated and treated water after the second scale inhibitor supplying step; and

a second crystallizing step of supplying seed crystals of gypsum to the second concentrated water so that gypsum is crystallized from the second concentrated water.

{0014}

A second aspect of the present invention is a water

treatment system including:

a first scale inhibitor supplying section that supplies a calcium scale inhibitor which is a scale inhibitor for inhibiting the deposition of a scale containing calcium to water to be treated containing Ca ions, SO₄ ions, carbonate ions, and silica;

a first pH adjusting section that supplies a pH adjuster to the water to be treated to adjust the pH of the water to be treated to such a value that the silica is soluble in the water to be treated;

a first demineralizing section that is installed on the downstream side of the first scale inhibitor supplying section and the first pH adjusting section and separates the water to be treated into first concentrated water in which the Ca ions, the SO₄ ions, the carbonate ions, and the silica are concentrated and treated water; and

a first crystallizing section including a first crystallizing tank that is installed on the downstream side of the first demineralizing section and crystallizes gypsum from the first concentrated water and a first seed crystal supplying section that supplies seed crystals of gypsum to the first crystallizing tank;

wherein the water treatment system further includes on the downstream side of the first crystallizing section with respect to the water to be treated ;

a second scale inhibitor supplying section that supplies the calcium scale inhibitor and a silica scale inhibitor which is a scale inhibitor for inhibiting the deposition of silica to the water to be treated;

a second demineralizing section that is installed on the downstream side of the second scale inhibitor supplying section and separates the water to be treated into second concentrated water in which the Ca ions, the SO₄ ions, the carbonate ions, and the silica are concentrated and treated water; and

a second crystallizing section including a second crystallizing tank that is installed on the downstream side of the second demineralizing section and crystallizes gypsum from the second concentrated water and a second seed crystal supplying section that supplies seed crystals of gypsum to the second crystallizing tank.

{0015}

According to the first aspect and the second aspect, in the first scale inhibitor supplying step, the first scale inhibitor supplying section, the first pH adjusting step, and the first pH adjusting section, a calcium scale inhibitor is added, and also the water to be treated is adjusted to a pH at which silica is soluble, followed by a water treatment. Accordingly, the production of scales in the first demineralizing section and the first demineralizing step can

be inhibited. In addition, by adding seed crystals of gypsum to the first concentrated water in the first crystallizing section and the first crystallizing step, even when a scale inhibitor is present, gypsum can be crystallized and separated from the water to be treated. As a result, while inhibiting the production of scales, the water to be treated containing Ca ions, SO₄ ions, carbonate ions, and silica can be treated with high water recovery. In addition, the amount of chemicals required for the treatment and the power required for the operation can be reduced, and also maintenance is facilitated. Accordingly, the operation cost can be reduced.

{0016}

In the first aspect and the second aspect, owing to the effects of the calcium scale inhibitor and the silica scale inhibitor supplied in the second scale inhibitor supplying step and the second scale inhibitor supplying section, the production of scales in the second demineralizing section and the second demineralizing step can be inhibited. In addition, by adding seed crystals of gypsum to the second concentrated water in the second crystallizing section and the second crystallizing step, even when a scale inhibitor is present, gypsum can be crystallized and separated from the water to be treated. As a result, the water to be treated containing Ca ions, SO₄ ions, and silica can be treated with high water recovery, and the operation cost can be reduced. Further,

this is also advantageous in that high-purity gypsum can be recovered.

{0017}

In the above aspect, the water treatment process includes a downstream side demineralizing step of separating the second concentrated water after the second crystallizing step on the most downstream of the water to be treated into concentrated water and treated water, and recovering the separated treated water.

{0018}

In the above aspect, the water treatment system includes, on the downstream side of the second crystallizing section on the most downstream of the water to be treated, a downstream side demineralizing section that separates the second concentrated water discharged from the second crystallizing section into concentrated water and treated water.

{0019}

When the downstream side demineralizing step and the downstream side demineralizing section are provided, the water recovery can be further improved. In addition, in the invention, the number of moles of ions in the water to be treated is significantly reduced. Accordingly, the amount of salts flowing into the downstream side demineralizing section can be reduced, and thus the power of the downstream side demineralizing section can be reduced.

{0020}

In the above aspect, it is preferable that the water treatment process includes a second pH adjusting step of adjusting the second concentrated water to a pH at which a scale inhibition function of the calcium scale inhibitor is reduced, thereby promoting the deposition of the gypsum in the second crystallizing step.

In the above aspect, it is preferable that the water treatment system includes a second pH adjusting section that is installed on the downstream side of the second demineralizing section and supplies a pH adjuster to the second concentrated water to adjust the pH of the second concentrated water to such a value that a scale inhibition function of the calcium scale inhibitor is reduced, and the deposition of the gypsum is promoted.

{0021}

In this case, it is preferable that after the second crystallizing step, the second concentrated water after the adjustment of the pH in the second pH adjusting step is adjusted to a pH at which the calcium scale inhibitor exerts its function.

It is also preferable that the water treatment system includes, on the downstream side of the second crystallizing section, a third pH adjusting section that supplies a pH adjuster to the second concentrated water after the adjustment

of the pH in the second pH adjusting section to adjust the pH of the second concentrated water to such a value that the calcium scale inhibitor exerts its function.

{0022}

Alternatively, in the above aspect, the water treatment process may include a second pH adjusting step of adjusting the second concentrated water to a pH at which the silica is soluble in the second crystallizing step. In the above aspect, it is preferable that the water treatment system includes a second pH adjusting section that is installed on the downstream side of the second demineralizing section and supplies a pH adjuster to the second concentrated water to adjust the pH of the second concentrated water to such a value that the silica is soluble in the second concentrated water in the second crystallizing section.

{0023}

As a result of this configuration, the formation of scales containing calcium in the downstream side demineralizing section can be suppressed.

{0024}

In the first aspect, it is preferable that the water treatment process includes a first upstream side precipitating step of precipitating at least calcium carbonate from the water to be treated so that the concentration of the calcium carbonate in the water to be treated is reduced, before the

first scale inhibitor supplying step and the first pH adjusting step on the most upstream side of the water to be treated. In this case, it is preferable that the water treatment process includes a first deaerating step of removing CO₂ from the water to be treated before the first upstream side precipitating step or after the first upstream side precipitating step and before the first scale inhibitor supplying step and the first pH adjusting step.

{0025}

In the second aspect, it is preferable that the water treatment system includes, on the upstream side of the first scale inhibitor supplying section and the first pH adjusting section located on the most upstream of the water to be treated, a first upstream side precipitating section that precipitates at least calcium carbonate from the water to be treated so that the concentration of the calcium carbonate in the water to be treated is reduced. In this case, it is preferable that the water treatment system includes a first deaerating section that removes CO₂ from the water to be treated on the upstream side of the first upstream side precipitating section or on the downstream side of the first upstream side precipitating section and on the upstream side of the first scale inhibitor supplying section and the first pH adjusting section.

{0026}

In this way, by previously removing calcium carbonate from the water to be treated before flowing into the demineralizing section, the deposition of calcium carbonate as scales during the water treatment can be inhibited. By removing calcium carbonate, the purity of gypsum crystallized in the crystallizing step and the crystallizing section can be increased.

{0027}

In the above aspect, it is preferable that the water to be treated contains metal ions, and the water treatment process includes a first precipitating step of precipitating at least one of calcium carbonate and a metal compound so that the concentration of at least one of the calcium carbonate and the metal ions is reduced from the first concentrated water, after the first crystallizing step. It is preferable that the water treatment process includes a second precipitating step of precipitating at least one of calcium carbonate and a metal compound so that the concentration of at least one of the calcium carbonate and the metal ions is reduced from the second concentrated water, after the second crystallizing step.

In this case, at least one of seed crystals of the silica and a precipitant for the silica is supplied to the first concentrated water in the first precipitating step. In the second precipitating step, at least one of seed crystals of

the silica and a precipitant for the silica is supplied to the second concentrated water.

{0028}

In the above aspect, it is preferable that the water to be treated contains metal ions, and the water treatment system includes, on the downstream side of the first crystallizing section, a first precipitating section that precipitates at least one of calcium carbonate and a metal compound so that the concentration of at least one of the calcium carbonate and the metal ions in the first concentrated water is reduced. It is preferable that the water treatment system includes, on the downstream side of the second crystallizing section, a second precipitating section that precipitates least one of calcium carbonate and a metal compound so that the concentration of at least one of the calcium carbonate and the metal ions in the second concentrated water is reduced.

In this case, at least one of seed crystals of the silica and a precipitant for the silica is supplied to the first precipitating section. At least one of seed crystals of the silica and a precipitant for the silica is supplied to the second precipitating section.

{0029}

By removing calcium carbonate and a metal compound from the water to be treated in the precipitating section and the precipitating step provided after the crystallizing section

and the crystallizing step, high water recovery can be obtained.

The dissolution state of silica changes depending on the pH of the water to be treated, but silica tends not to be deposited only by changing the pH. Thus, seed crystals of silica are added in the precipitating section and the precipitating step to promote the deposition of silica, whereby the silica removal efficiency can be improved. As a result, the water recovery can be further improved, and the operation power can be further lowered.

{0030}

In the water treatment process of the above aspect, it is preferable that when the water to be treated contains Mg ions, the amount of the precipitant for silica to be supplied is adjusted according to the concentration of the Mg ions.

In the above aspect, it is preferable that when the water to be treated contains Mg ions, the amount of the precipitant for silica to be supplied is adjusted according to the concentration of the Mg ions in the first precipitating section. It is preferable that when the water to be treated contains Mg ions, the amount of the precipitant for silica to be supplied is adjusted according to the concentration of the Mg ions in the second precipitating section.

{0031}

In the above aspect, it is preferable that when the water

to be treated contains Mg ions, the first concentrated water in the first precipitating step is adjusted to a pH at which a magnesium compound is deposited so that the concentration of the Mg ions is reduced, and after the first precipitating step, the first concentrated water is adjusted to a pH at which the magnesium compound is soluble. It is preferable that the second concentrated water in the second precipitating step is adjusted to a pH at which a magnesium compound is deposited so that the concentration of the Mg ions is reduced, and after the second precipitating step, the second concentrated water is adjusted to a pH at which the magnesium compound is soluble.

{0032}

In the above aspect, it is preferable that when the water to be treated contains Mg ions, the first concentrated water in the first precipitating section is adjusted to a pH at which a magnesium compound is deposited so that the concentration of the Mg ions is reduced, and, on the downstream side of the first precipitating section, the first concentrated water is adjusted to a pH at which the magnesium compound is soluble. It is preferable that when the water to be treated contains Mg ions, the second concentrated water in the second precipitating section is adjusted to a pH at which a magnesium compound is deposited so that the concentration of the Mg ions is reduced, and, on the downstream side of the

second precipitating section, the second concentrated water is adjusted to a pH at which the magnesium compound is soluble.

{0033}

In the case where Mg ions are contained in the water to be treated, Mg ions react with silica in the concentrated water in the precipitating step and the precipitating section, resulting in precipitation. In the present invention, the amount of precipitant to be supplied is adjusted according to the balance between Mg ions and silica in the concentrated water, whereby the precipitant is efficiently supplied. In the case where the concentration of Mg ions is high relative to silica, the pH of the concentrated water is adjusted so that a magnesium compound is deposited in the precipitating step and the precipitating section. Subsequently, the concentrated water is adjusted to a pH at which the magnesium compound is soluble, thereby suppressing the formation of scales in the demineralizing section located on the downstream side of the precipitating section.

{0034}

In the above aspect, it is preferable that when the water to be treated contains Mg ions, the water to be treated in the first upstream side precipitating step is adjusted to a pH at which a magnesium compound is deposited so that the concentration of the Mg ions is reduced, and, after the first upstream side precipitating step, the water to be treated is

51258-103

19

adjusted to a pH at which the magnesium compound is soluble.

{0035}

In the above aspect, it is preferable that when the water to be treated contains Mg ions, the water to be treated in the first upstream side precipitating section is adjusted to a pH at which a magnesium compound is deposited so that the concentration of the Mg ions is reduced, and, on the downstream side of the first upstream side precipitating section, the water to be treated is adjusted to a pH at which the magnesium compound is soluble.

{0036}

In this way, in the case where Mg ions are contained in the water to be treated, by efficiently removing Mg ions before a demineralization treatment, the formation of scales containing magnesium in the course of water treatment can be inhibited.

{0037}

In the above aspect, it is preferable that moisture is evaporated from the concentrated water in the downstream side demineralizing step, so that a solid in the concentrated water is recovered. It is preferable that the water treatment

system includes, on the downstream side of the concentrated water of the downstream side demineralizing section, an evaporator that evaporates moisture from the concentrated water to recover a solid in the concentrated water.

{0038}

According to the water treatment process and the water treatment system thus configured, when solid matters produced in the course of water treatment are discharged out of the system as waste, the volume of waste can be reduced.

{Advantageous Effects of Invention}

{0039}

According to the water treatment system and the water treatment process of the present invention, while inhibiting the production of scales such as calcium carbonate and silica during the treatment, Ca^{2+} and SO_4^{2-} can be removed as gypsum from the water to be treated. Accordingly, the water recovery can be further improved.

Also in the case where magnesium ions are contained in the water to be treated, when the water treatment system or the water treatment process of the present invention is used, they can be removed from the water to be treated while inhibiting the production of scales containing magnesium during the treatment.

{0040}

Water treated by the present invention has a

significantly reduced number of moles of ions on the downstream side. Therefore, the power of the demineralizing section located downstream can be significantly reduced.

{0041}

Further, the present invention is also advantageous in that high-purity gypsum can be crystallized and recovered.

{Brief Description of Drawings}

{0042}

{Fig. 1}

Fig. 1 is a schematic diagram of a water treatment system according to the first reference embodiment.

{Fig. 2}

Fig. 2 shows simulation results for the pH dependency of the amount of gypsum deposited.

{Fig. 3}

Fig. 3 shows simulation results for the pH dependency of the amount of calcium carbonate deposited.

{Fig. 4}

Fig. 4 is a graph showing the pH dependency of the amount of silica dissolved.

{Fig. 5}

Fig. 5 shows the results of gypsum deposition experiments performed using simulated water in which gypsum is supersaturated with changing the pH of the simulated water.

{Fig. 6}

Fig. 6 shows the results of gypsum deposition experiments performed using simulated water in which gypsum is supersaturated with changing the concentration of seed crystals.

{Fig. 7}

Fig. 7 is a microphotograph of gypsum crystallized under Condition 5.

{Fig. 8}

Fig. 8 is a microphotograph of gypsum crystallized under Condition 3.

{Fig. 9}

Fig. 9 is a schematic diagram of a water treatment system according to the second reference embodiment.

{Fig. 10}

Fig. 10 is a schematic diagram of a water treatment system according to the third reference embodiment.

{Fig. 11}

Fig. 11 is a schematic diagram of a water treatment system according to the first embodiment.

{Fig. 12}

Fig. 12 is a schematic diagram of a water treatment system according to the fourth reference embodiment.

{Fig. 13}

Fig. 13 is a schematic diagram explaining a water treatment system according to the fifth reference embodiment.

{Fig. 14}

Fig. 14 is a schematic diagram explaining a water treatment system according to the sixth reference embodiment.

{Fig. 15}

Fig. 15 is a schematic diagram explaining a water treatment system according to the seventh reference embodiment.

{Fig. 16}

Fig. 16 is a schematic diagram explaining a water treatment system according to the eighth reference embodiment.

{Description of Embodiments}

{0043}

Water that is an object to be treated in the present invention (water to be treated) contains Ca^{2+} , SO_4^{2-} , carbonate ions, and silica. Specifically, the water to be treated (raw water) is saline water, sewage, industrial waste water, blowdown water from a cooling tower, or the like. The water to be treated may also contain metal ions, such as Mg ions.

{0044}

{First Reference Embodiment}

Fig. 1 is a schematic diagram of a water treatment system according to the first reference embodiment of the present invention. The water treatment system 1 of Fig. 1 is configured such that two water treatment sections are connected in the flow direction of the water to be treated.

In the water treatment system 1 of this reference embodiment, depending on the properties of the water to be treated, the number of water treatment sections may be one, and it is also possible that three or more water treatment sections are connected.

{0045}

Each water treatment section includes, from the upstream side of the water to be treated, a first demineralizing section 10 (10a, 10b) and a first crystallizing section 20 (20a, 20b). The concentration sides of the first demineralizing sections 10a and 10b are connected to the first crystallizing sections 20a and 20b, respectively. The water treatment section includes a first scale inhibitor supplying section 30 (30a, 30b) and a first pH adjusting section 40 (40a, 40b) in the flow path on the upstream side of each first demineralizing section 10 (10a, 10b).

{0046}

The first scale inhibitor supplying section 30 (30a, 30b) is made up of a tank 31 (31a, 31b), a valve V1 (V1a, V1b), and a control section 32 (32a, 32b). The control sections 32a and 32b are connected to the valves V1a and V1b, respectively. The tanks 31a and 31b have stored therein a scale inhibitor.

{0047}

The scale inhibitor used in this reference embodiment serves to inhibit the deposition of scales containing calcium

in the water to be treated. It will be hereinafter referred to as "calcium scale inhibitor".

The calcium scale inhibitor suppresses the crystal nucleation of gypsum or calcium carbonate in the water to be treated. At the same time, the calcium scale inhibitor adheres to the surface of crystal nucleus of gypsum or calcium carbonate contained in the water to be treated (seed crystals, small-diameter scales deposited due to the exceeding of the saturation concentration, etc.), and functions to suppress the crystal growth of gypsum or calcium carbonate. Alternatively, there is another type of calcium scale inhibitor, which has the function of dispersing particles in the water to be treated (inhibiting aggregation), such as deposited crystals.

Examples of calcium scale inhibitors include phosphonic-acid-based scale inhibitors, polycarboxylic-acid-based scale inhibitors, and mixtures thereof. A specific example is FLOCON260 (trade name, manufactured by BWA).

{0048}

In the case where Mg ions are contained in the water to be treated, a scale inhibitor that inhibits the deposition of scales containing magnesium (e.g., magnesium hydroxide) in the water to be treated can be used. It will be hereinafter referred to as "magnesium scale inhibitor".

Examples of magnesium scale inhibitors include polycarboxylic-acid-based scale inhibitors, etc. A specific

example is FLOCON 295N (trade name, manufactured by BWA).

{0049}

Although Fig. 1 shows only one first scale inhibitor supplying section 30a/30b in each position, in the case where two or more kinds of scale inhibitors are loaded, it is preferable that two or more first scale inhibitor supplying sections are installed. In this case, the scale inhibitors are sorted according to kind and stored in the respective tanks.

{0050}

The first pH adjusting section 40 (40a, 40b) is made up of a tank 41 (41a, 41b), a valve V2 (V2a, V2b), a control section 42 (42a, 42b), and a pH meter 43 (43a, 43b). The tanks 41a and 41b have stored therein an alkali as a pH adjuster. The alkali is calcium hydroxide or sodium hydroxide, for example. Calcium hydroxide is particularly preferable because Ca ions are recovered as gypsum in the below-mentioned crystallizing step, and thus the amount of ions that reach the demineralizing section on the downstream side is reduced. The control sections 42a and 42b are connected to the valves V2a and V2b and the pH meters 43a and 43b, respectively.

{0051}

In Fig. 1, the first demineralizing sections 10a and 10b are reverse osmosis membrane devices. In addition, the first

demineralizing sections 10a and 10b may also be electrodialyzers (ED), electro dialysis reversal devices (EDR), electro de-ionization devices (EDI), ion-exchange equipments (IEx), capacitive de-ionization devices (CDI), nanofilters (NF), evaporators, etc.

Here, in a nanofilter (NF), an electrodialyzer (ED), an electro dialysis reversal device (EDR), an electro de-ionization device (EDI), and an capacitive de-ionization device (CDI), scale components (divalent ions, Ca^{2+} , Mg^{2+} , etc.) are selectively removed, while monovalent ions such as Na^+ and Cl^- permeate. The use of these demineralizers suppresses an increase in the ion concentration of ions that serve as scale components in concentrated water. Accordingly, the water recovery can be improved, and also energy saving (e.g., the reduction of pump power, etc.) can be achieved.

In addition, in the case where the water to be treated is blowdown water from a cooling tower, the reclaimed water does not have to be pure water, and what is necessary is that scale components (divalent ions, Ca^{2+} , Mg^{2+} , etc.) are removed. Accordingly, it is advantageous to use a nanofilter (NF), etc.

{0052}

Although only one first demineralizing section 10a/10b is shown in Fig. 1, the system may also be configured such that two or more demineralizers are connected in parallel or in series in the flow direction of the water to be treated.

{0053}

The first crystallizing section 20 (20a, 20b) is made up of a first crystallizing tank 21 (21a, 21b) and a first seed crystal supplying section 22 (22a, 22b). The first seed crystal supplying sections 22a and 22b are connected to the first crystallizing tanks 21a and 21b, respectively. The first seed crystal supplying sections 22a and 22b have a seed crystal tank 23 (23a, 23b), a valve V3 (V3a, V3b), and a control section 24 (24a, 24b). The control sections 24a and 24b are connected to the valves V3a and V3b, respectively. The seed crystal tanks 23a and 23b store gypsum particles as seed crystals.

{0054}

In the water treatment system 1 of Fig. 1, a first precipitating section 50 (50a, 50b) may be installed on the downstream side of each of the first crystallizing sections 20a and 20b. The first precipitating sections 50a and 50b each include a first precipitating tank 51 (51a, 51b) and a first filtration device 52 (52a, 52b).

{0055}

The water treatment system 1 includes a downstream side demineralizing section 60 on the downstream side of the water to be treated of the first crystallizing section 20b located on the most downstream.

{0056}

In Fig. 1, the downstream side demineralizing section 60 is a reverse osmosis membrane device. The downstream side demineralizing section 60 may also be an electrodialyzer (ED), an electro dialysis reversal device (EDR), an electro de-ionization device (EDI), an ion-exchange equipment, a capacitive de-ionization device (CDI), a nanofilters (NF), an evaporator, etc.

{0057}

In the water treatment system 1, a precipitating tank 71 and a filtration device 72 are installed as a first upstream side precipitating section 70 on the upstream side of the first scale inhibitor supplying section 30a and the first pH adjusting section 40a which are located on the most upstream of the water to be treated. The precipitating tank 71 and the filtration device 72 have the same configuration as the first precipitating tank 51 and the first filtration device 52 of the first precipitating section 50.

In particular, in the case where Mg ions are contained in the water to be treated, the first upstream side precipitating section can be configured such that two or more precipitating tanks 71 are connected in series in the flow direction of the water to be treated.

{0058}

In the water treatment system 1 shown in Fig. 1, a first deaerating section 73 may be provided on the upstream side of

the first upstream side precipitating section 70.

Specifically, the first deaerating section 73 is a deaeration tower equipped with a filler for removing carbon dioxide or is a separation membrane. On the upstream side of the water to be treated of the first deaerating section 73, a pH adjusting section (not shown) that adjusts the water to be treated to a pH at which carbonate ions are present in the form of CO_2 may be installed.

The first deaerating section 73 may also be installed on the downstream side of the water to be treated of the first upstream side precipitating section 70 and on the upstream side of the first scale inhibitor supplying section 30a and the first pH adjusting section 40a.

{0059}

It is also possible that a deaerating section having the same configuration as the first deaerating section 73 is installed in the flow path between the first demineralizing section 10 and the first crystallizing section 20, in the flow path between the first crystallizing section 20 and the first precipitating section 50, and on the downstream side of the first precipitating section 50 and in the flow path between it and the first demineralizing section 10b or the downstream side demineralizing section 60.

{0060}

In the case where the concentration of Ca ions in the

water to be treated is high, an ion-exchange equipment (not shown) may be installed on the downstream of the filtration device 72 and on the upstream of the first scale inhibitor supplying section 30a and the first pH adjusting section 40a which are located on the most upstream. The ion-exchange equipment may be an ion-exchange resin column or an ion-exchange membrane device, for example.

{0061}

When gypsum in the water to be treated flowing into the first demineralizing section 10a is already supersaturated, because ions are further concentrated in the first demineralizing section 10a, the resulting gypsum concentration is even higher. In this case, the loading of a large amount of calcium scale inhibitor is required. Further, the concentration of gypsum may become too high for the calcium scale inhibitor to exert its effect, resulting in the production of scales in the first demineralizing section 10a.

Thus, in the case where gypsum in the raw water (water to be treated) is supersaturated, it is possible that an upstream side crystallizing section (not shown) having the same configuration as the first crystallizing tanks 21a and 21b are provided on the upstream of the first scale inhibitor supplying section 30a and the first pH adjusting section 40a on the most upstream, so that the concentration of gypsum is reduced, and then the water to be treated is fed to the first

demineralizing section 10a.

{0062}

A process for treating water to be treated using the water treatment system 1 of the first reference embodiment will be described hereinafter.

First, the deposition behaviors of gypsum, silica, and calcium carbonate in water will be explained. Fig. 2 shows simulation results for the pH dependency of the amount of gypsum deposited. Fig. 3 shows simulation results for the pH dependency of the amount of calcium carbonate deposited. In the figures, the abscissa is pH, and the ordinate is the amount of gypsum or calcium carbonate deposited (mol). Using a simulation software manufactured by OLI, the simulation was performed under the conditions where 0.1 mol/L of each solid component was mixed with water, and H_2SO_4 and $\text{Ca}(\text{OH})_2$ were added as an acid and an alkali, respectively.

Fig. 4 is a graph showing the pH dependency of the amount of silica dissolved (source: Fig. 4 of U.S. Pat. No. 7815804). In the figure, the abscissa is pH, and the ordinate is the amount of silica dissolved (mg/L).

{0063}

From Fig. 2, it can be understood that gypsum deposition has no pH dependency, and deposition is possible over the entire pH range. However, when a calcium scale inhibitor is added, in a high-pH region, gypsum is present in the state of

being dissolved in water. From Fig. 3, calcium carbonate is deposited when the pH is more than 5. From Fig. 4, silica tends to dissolve in water when the pH is 10 or more.

{0064}

<Pretreatment>


In the case where the water to be treated is industrial waste water, etc., before the water to be treated flows into the first upstream side precipitating section 70, a step of removing oils, floating particles, and the like from the water to be treated and a step of removing organic substances by a biological treatment or a chemical oxidation treatment are performed.

{0065}

<First Deaerating Step>

In the water treatment system 1 of Fig. 1, the water to be treated before flowing into the first deaerating section 73 is adjusted to a low pH. Carbonic acid in the water to be treated is in the following equilibrium depending on the pH of the water to be treated.

{Chemical Formula 1}



In the case where the pH is as low as 6.5 or less, it is mainly present as HCO_3^- and CO_2 in the water to be treated.

{0066}

The water to be treated containing CO₂ flows into the first deaerating section 73. CO₂ is removed from the water to be treated in the first deaerating section 73. When the water to be treated has been previously adjusted to a pH at which carbonate ions are present as CO₂, carbon dioxide can be efficiently removed.

The water to be treated, whose carbonate ion concentration has been reduced in the first deaerating step, is fed into the first upstream side precipitating section 70.

{0067}

<First Upstream Side Precipitating Step>

In the first upstream side precipitating section 70, some of Ca ions and carbonate ions are previously removed from the water to be treated as calcium carbonate.

In the case where metal ions other than Ca ions are contained in the water to be treated, in the first upstream side precipitating section 70, some of the metal ions are previously removed from the water to be treated as a metal compound having low solubility in water. This metal compound is mainly a metal hydroxide, but may also include a carbonate.

In the precipitating tank 71, Ca(OH)₂ and an anionic polymer (manufactured by Mitsubishi Heavy Industries Mechatronics Systems, Ltd., trade name: Hishifloc H305) are loaded to the water to be treated, and the pH in the

precipitating tank 71 is controlled to 4 or more and 12 or less, and preferably 8.5 or more and 12 or less.

{0068}

As shown in Fig. 3, the solubility of calcium carbonate is low in this pH range. When calcium carbonate is supersaturated, calcium carbonate is deposited and precipitated at the bottom of the precipitating tank 71.

The solubility of a metal compound depends on pH. A more acidic pH leads to a higher solubility of metal ions in water. For many metal compounds, the solubility is low in the above pH range. In the above pH range, a metal compound having low solubility in water aggregates in the precipitating tank 71, resulting in precipitation at the bottom of the precipitating tank 71.

The precipitated calcium carbonate and metal compound are discharged from the bottom of the precipitating tank 71.

{0069}

Mg ions form salts that are poorly soluble in water, and thus are components that tend to be deposited as scales. $\text{Mg}(\text{OH})_2$ is deposited at pH 10 or more.

In the case where the water to be treated containing Mg ions is treated by the water treatment system 1 of this reference embodiment, the pH of the water to be treated in the precipitating tank 71 is adjusted to a pH at which a magnesium compound (mainly magnesium hydroxide) is deposited.

Specifically, the pH of the water to be treated is adjusted to 10 or more, preferably 10.5 more, and more preferably 11 or more. Accordingly, a magnesium compound is deposited from the water to be treated, precipitated at the bottom of the precipitating tank 71, and removed. As a result, some of Mg ions in the water to be treated are removed, resulting in a decrease in the concentration of Mg ions in the water to be treated.

In the above case, it is preferable that the water to be treated after being discharged from the first upstream side precipitating section 70 is adjusted to a pH at which the above magnesium compound is soluble. Specifically, the pH is adjusted to less than 10. Accordingly, the formation of scales in devices and steps on the downstream side, particularly the first demineralizing section 10a and the first demineralizing step, can be inhibited.

{0070}

In the case where two or more stages of precipitating tanks 71 are provided, Mg ions in the water to be treated can be reliably removed, and the concentration of Mg ions in the water to be treated fed to the downstream side can be reduced.

{0071}

The supernatant in the precipitating tank 71, which is the water to be treated, is discharged from the precipitating tank 71. FeCl_3 is added to the discharged water to be treated,

and solids in the supernatant, such as calcium carbonate and a metal compound, aggregate with $\text{Fe}(\text{OH})_3$.

The water to be treated is fed to the filtration device 72. The solids aggregated with $\text{Fe}(\text{OH})_3$ are removed through the filtration device 72.

{0072}

In the case where the first deaerating step is performed after the first upstream side precipitating step, the pH of the water to be treated is adjusted to a pH at which carbonate ions can be present as CO_2 , specifically 6.5 or less.

{0073}

Incidentally, depending on the properties of the water to be treated, the first deaerating step and the first upstream side precipitating step may be omitted.

{0074}

In the case where an ion-exchange equipment is installed, Ca ions in the water to be treated are removed by the ion-exchange equipment. In the case where Mg ions are contained in the water to be treated, the Mg ions are also removed by the ion-exchange equipment.

{0075}

In the case where gypsum in the raw water is supersaturated, seed crystals of gypsum are loaded to the water to be treated in the upstream side crystallizing section installed immediately after the filtration device 72, and

gypsum is crystallized, thereby reducing the concentration of gypsum in the water to be treated. The water to be treated having a reduced concentration of gypsum is fed to the first demineralizing section 10a.

{0076}

<First Scale Inhibitor Supplying Step>

The control section 32a of the first scale inhibitor supplying section 30a opens the valve V1a and supplies a predetermined amount of calcium scale inhibitor to the water to be treated from the tank 31a. The control section 32a adjusts the opening of the valve V1a so that the concentration of the calcium scale inhibitor is a predetermined value set according to the properties of the water to be treated.

{0077}

In the case where Mg ions are contained in the water to be treated, a magnesium scale inhibitor is supplied to the water to be treated in the first scale inhibitor supplying step in the same manner as above. In this case, the calcium scale inhibitor and the magnesium scale inhibitor are stored in the tank of each of two or more first scale inhibitor supplying sections, and each control section adjusts the amounts of calcium scale inhibitor and magnesium scale inhibitor to be supplied.

{0078}

<First pH Adjusting Step>

The control section 42a of the first pH adjusting section 40a controls the pH of the water to be treated at the entrance of the first demineralizing section 10a to such a value that silica is soluble in the water to be treated. Specifically, the pH of the water to be treated fed to the first demineralizing section 10a is adjusted to 10 or more, preferably 10.5 or more, and more preferably 11 or more.

The pH meter 43a measures the pH of the water to be treated at the entrance of the first demineralizing section 10a. The control section 42a adjusts the opening of the valve V2a so that the value measured by the pH meter 43a is a predetermined pH control value, and allows an alkali to be loaded to the water to be treated from the tank 41a.

{0079}

<First Demineralizing Step>

In the first demineralizing section 10a, the pH-adjusted water to be treated is treated. In the case where the first demineralizing section 10a is a reverse osmosis membrane device, the water that has passed through the reverse osmotic membrane is recovered as treated water. Ions and scale inhibitors contained in the water to be treated cannot pass through the reverse osmosis membrane. Therefore, on the non-permeate side of the reverse osmosis membrane, there is concentrated water having a high concentration of ions. Also in the case where other demineralizers, such as a capacitive

de-ionization device, are used, for example, the water to be treated is separated into treated water and concentrated water having a high concentration of ions (first concentrated water).

{0080}

As shown in Fig. 4, as a result of the first demineralizing step, silica is contained in the first concentrated water in the state of being dissolved in the water to be treated. Even in the case where gypsum and calcium carbonate in the first concentrated water are concentrated to the saturation concentration or higher, the production of scales is suppressed by the calcium scale inhibitor.

In the case where Mg ions are contained in the water to be treated, the concentration of Mg ions contained in the first concentrated water increases as a result of the first demineralizing step. However, the production of scales containing magnesium is suppressed by the magnesium scale inhibitor.

The first concentrated water is fed toward the first crystallizing section 20a.

{0081}

<First Crystallizing Step>

The first concentrated water discharged from the first demineralizing section 10a is stored in the first

51258-103

41

crystallizing tank 21a of the first crystallizing section 20a. The control section 24a of the first seed crystal supplying section 22a opens the valve V3a and adds seed crystals of gypsum to the first concentrated water in the first crystallizing tank 21a from the seed crystal tank 23a.

The pH of the first concentrated water from the first demineralizing section 10a is 10 or more. As mentioned above, gypsum is in the state of being dissolved in water in a high-pH region where a calcium scale inhibitor is present. However, when seed crystals are sufficiently present, even when a scale inhibitor is present, gypsum is crystallized using the seed crystals as nuclei. In the water treatment system 1 of Fig. 1, the crystal-grown gypsum having a large diameter (e.g., having a particle diameter of 10 μm or more, more preferably 20 μm or more) is precipitated at the bottom of the first crystallizing tank 21a. The precipitated gypsum is discharged from the bottom of the first crystallizing tank 21a.

{0082}

Meanwhile, when the pH 10 is or more, silica is present in the state of being dissolved in the first concentrated water in the first crystallizing tank 21a. Even in the case where the concentration of silica in the first concentrated water exceeds the saturation solubility, because seed crystals of silica are not present, silica is deposited as floating

matters in a colloidal form or the like and unlikely to be precipitated.

With reference to Fig. 3, calcium carbonate tends to be deposited at pH 10 or more. However, because the calcium scale inhibitor has been added, the deposition of calcium carbonate is suppressed in the first crystallizing tank 21a. In addition, in the case where the first upstream side precipitating section or the first deaerating section is provided, the concentration of calcium carbonate has been previously reduced. As a result, in the first crystallizing tank 21a, calcium carbonate is unlikely to be crystallized using the seed crystals of gypsum as nuclei.

{0083}

Incidentally, although gypsum is crystallized independent of pH when seed crystals of gypsum are present, the crystallization rate increases with a decrease in pH.

Fig. 5 shows the result of gypsum deposition experiments with changing the pH of simulated water in the case where a scale inhibitor (FLOCON260) is added to simulated water (containing Ca^{2+} , SO_4^{2-} , Na^+ , and Cl^-) in which gypsum is supersaturated. The experimental conditions are as follows:

The degree of gypsum supersaturation in simulated water (25°C): 460%,

The amount of scale inhibitor to be added: 2.1 mg/L,

pH: 6.5 (Condition 1), 5.5 (Condition 2), 4.0 (Condition

3), 3.0 (Condition 4),

The amount of seed crystals to be added: 0 g/L.

{0084}

Two hours and 6 hours immediately after the pH adjustment, the concentration of Ca in the simulated water treated under each condition was measured using an atomic absorption spectrometer (manufactured by Shimadzu Corporation, AA-7000), and the degree of supersaturation was calculated. The results are shown in Fig. 5. In the figure, the ordinate is the degree of supersaturation (%).

{0085}

With reference to Fig. 5, even under conditions where seed crystals are absent, the crystallization rate increases with a decrease in pH. From this, it can be understood that in the case where seed crystals are present, gypsum is crystallized even under Condition 1 (pH 6.5), and the relation of the crystallization rate is such that the crystallization rate increases with a decrease in pH as shown in Fig. 5.

{0086}

In the case where carbonate ions are contained in the water to be treated, under low-pH conditions, carbonate ions are removed from the water to be treated as CO_2 as in chemical formula (1). In addition, as can be understood from Fig. 3, in the case where the pH is low, calcium carbonate is in a dissolved state.

{0087}

From these results, when the first crystallizing step is performed under low-pH conditions, because of the low content of calcium carbonate and silica, high-purity gypsum is crystallized and recovered from the bottom of the first crystallizing tank 21a. In the case where the first crystallizing step is performed at low pH, a third pH adjusting section (not shown) that supplies an acid as a pH adjuster is installed in the first crystallizing tank 21a or in the flow path between the first demineralizing section 10a and the first crystallizing tank 21a. The pH adjusting section has the same configuration as the below-mentioned second pH adjusting section.

{0088}

Meanwhile, in order to change the pH in the course of water treatment, it is necessary to supply a large amount of chemicals (acid or alkali). The use of an acid or an alkali leads to an increase in the amount of ions transferred to the downstream side of the first crystallizing section 20a, and this causes an increase in the power of demineralizing sections on the downstream side (in Fig. 1, the first demineralizing section 10b or the downstream side demineralizing section 60). In terms of operation cost, it is more advantageous that the pH is not changed between the first demineralizing step and the first crystallizing step.

{0089}

The gypsum crystallization rate depends on the loading of seed crystals. Fig. 6 shows the results of gypsum deposition experiments with changing the amount of seed crystals to be added in the case where a calcium scale inhibitor (FLOCON260) is added to simulated water. The experimental conditions were the same as in Fig. 5 except that the pH was 4.0, and that gypsum ($\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$) was added as seed crystals in the following amounts:

The amount of seed crystals to be added: 0 g/L (Condition 3), 3 g/L (Condition 5), 6 g/L (Condition 6), 3 g/L (Condition 7).

Under Conditions 5 and 6, seed crystals and sulfuric acid for pH adjustment were added to the simulated water having added thereto a scale inhibitor. Under Condition 7, seed crystals pre-immersed with the above scale inhibitor were added to the simulated water having added thereto a scale inhibitor, and sulfuric acid was added for pH adjustment.

{0090}

Two hours immediately after the pH adjustment, the concentration of Ca in the simulated water treated under each condition was measured by the same technique as in Fig. 5. In Fig. 6, the ordinate is the degree of supersaturation (%).

{0091}

From the results of Fig. 6, it can be understood that

although the degree of supersaturation was 215% under Condition 3 where seed crystals are not added, the degree of supersaturation decreases to 199% (Condition 5) and 176% (Condition 6) with an increase in the concentration of seed crystals, leading to an increase in the gypsum deposition rate. Also under high-pH conditions, similarly, the gypsum deposition rate tends to increase with an increase in the loading of seed crystals. Condition 5 and Condition 7 are the same test conditions, except for whether the used seed crystals are not immersed or immersed with a scale inhibitor. Also under Condition 7 where seed crystals have a scale inhibitor previously adhering thereto, the degree of supersaturation is 199%, and it has been confirmed that gypsum is deposited at the same level as under Condition 5. That is, the results under Condition 5 and 7 show that independent of the immersion time of seed crystals with a calcium scale inhibitor, when the pH is reduced to 4.0, the function of the scale inhibitor is reduced.

{0092}

Fig. 7 and 8 each show a microphotograph of gypsum resulting from crystallization. Fig. 7 shows results under Condition 5 (seed crystals added), and Fig. 8 shows results under Condition 3 (no seed crystals added). Under Condition 5, gypsum having a larger size was deposited than under Condition 3. Generally, the water content decreases with an

increase in the size of deposited gypsum. A low water content leads to high-purity gypsum. When the average particle diameter is 10 μm or more, preferably 20 μm or more, the resulting gypsum has a sufficiently reduced water content. The "average particle diameter" in the present invention is a particle diameter measured by the method specified in JIS Z 8825 (laser diffractometry).

{0093}

<First Precipitating Step>

The supernatant (first concentrated water) in the first crystallizing section 20a is fed to the first precipitating section 50a. In the first precipitating section 50a, $\text{Ca}(\text{OH})_2$ and an anionic polymer (Hishifloc H305) are loaded to the first concentrated water after the crystallizing step, and the pH in the first precipitating tank 51a is controlled to 4 or more and 12 or less, and preferably 8.5 or more and 12 or less. In the first precipitating tank 51a, calcium carbonate and a metal compound are precipitated and removed from the first concentrated water. The precipitated calcium carbonate and metal compound having low solubility in water are discharged from the bottom of the first precipitating tank 51a.

{0094}

The water to be treated, which is the supernatant in the first precipitating tank 51a, is discharged from the first

precipitating tank 51a. FeCl_3 is added to the discharged water to be treated, and solids in the water to be treated, such as calcium carbonate and a metal compound, aggregate with $\text{Fe}(\text{OH})_3$.

The water to be treated is fed to the first filtration device 52a. The solids aggregated with $\text{Fe}(\text{OH})_3$ are removed through the first filtration device 52a.

{0095}

Silica in the supernatant in the first crystallizing section 20a may be removed from the first concentrated water in the first precipitating step, or may also be fed to the downstream side without being removed.

Whether silica is removed in the first precipitating step is determined according to the properties of the water to be treated or the first concentrated water.

{0096}

In the case where silica is not removed, the first precipitating step is performed without supplying seed crystals of silica and a precipitant for silica to the first precipitating tank 51a. In this case, silica is separated from the treated water in demineralizing sections located on the downstream side (the first demineralizing section 10b and the downstream side demineralizing section 60).

{0097}

In the case where silica is removed, at least one of seed

crystals of silica and a precipitant for silica is supplied into the first concentrated water in the first precipitating section 50a from a supply section (not shown). The seed crystals of silica are a silica gel, for example, and the precipitant for silica is MgSO_4 or Na aluminate ($\text{Na}[\text{Al}(\text{OH})_4]$), for example. In the case where silica is removed, it is preferable that the first concentrated water in the first precipitating tank 51a is adjusted to pH 8 or more and 10 or less. In the case where seed crystals of silica are used, silica is crystallized using the seed crystals as nuclei. In the case where MgSO_4 is used as a precipitant for silica, magnesium silicate is deposited. The crystallized silica or the crystallized magnesium silicate is precipitated at the bottom of the first precipitating tank 51a and discharged from the bottom of the first precipitating tank 51a.

{0098}

In the case where Mg ions are contained in the water to be treated, Mg ions react with silica in the first concentrated water in the first precipitating step, resulting in precipitation. The steps for silica/Mg ion removal vary depending on the balance between the content of Mg ions and the content of silica in the first concentrated water in the first precipitating tank 51a.

{0099}

In the case where the first concentrated water in the

first precipitating step has a lower concentration of Mg ions relative to the silica content, Mg ions are consumed by precipitation with silica. In order to remove an excess of silica that is not consumed by precipitation with Mg ions, a precipitant for silica (MgSO_4) is supplied. With respect to the amount of precipitant for silica to be supplied, according to the content of silica and the content of Mg ions in the first precipitating step, the precipitant is supplied in such an amount that the excess of silica is consumed.

{0100}

In the case where the first concentrated water in the first precipitating step has a higher concentration of Mg ions relative to the silica content, Mg ions remain as a result of the precipitation of Mg ions and silica. When the first concentrated water having a high concentration of residual Mg ions is discharged from the first precipitating tank 51a, scales containing Mg may be deposited in demineralizing sections of subsequent stages (the first demineralizing section 10b in Fig. 1; in the case of the first precipitating section on the most downstream, the downstream side demineralizing section 60).

Thus, the first concentrated water in the first precipitating tank 51a is adjusted to such a value that a magnesium compound (mainly magnesium hydroxide) can be deposited. Accordingly, a magnesium compound is precipitated

in the first precipitating tank 51a, thereby reducing the concentration of Mg ions in the first concentrated water in the first precipitating tank 51a. Further, after the first precipitating step, the first concentrated water discharged from the first precipitating tank 51a is adjusted to a pH at which the magnesium compound is soluble, specifically to a pH of less than 10. Accordingly, the deposition of scales containing Mg in a demineralizing section can be suppressed.

{0101}

In the case where the treatment is performed in several stages, the first concentrated water that has passed through the first filtration device 52a of the first water treatment section of the previous stage flows into the water treatment section of the subsequent stage as water to be treated. In the water treatment section of the subsequent stage, the steps from the first scale inhibitor supplying step to the first precipitating step mentioned above are performed.

{0102}

<Downstream Side Demineralizing Step>

The concentrated water (first concentrated water) that has passed through the first precipitating section 50b located on the most downstream of the water to be treated is fed to the downstream side demineralizing section 60. The water that has passed through the downstream side demineralizing section 60 is recovered as treated water. The concentrated water in

the downstream side demineralizing section 60 is discharged out of the system. The installation of the downstream side demineralizing section 60 makes it possible to further recover treated water from water that has been treated in a water treatment section. Accordingly, the water recovery is improved.

{0103}

In the water treatment system 1 of this reference embodiment, ions are concentrated in the first demineralizing section 10. However, gypsum, calcium carbonate, silica, etc., have been removed in the first crystallizing section, the first precipitating section, etc. Accordingly, the water flowing into the downstream side demineralizing section 60 has a smaller number of moles of ions than before the treatment. Accordingly, the osmotic pressure is low in the first demineralizing section 10b or the downstream side demineralizing section 60 located downstream, and the required power is reduced.

{0104}

An evaporator (not shown in Fig. 1) may be installed on the downstream on the concentrated-water side of the downstream side demineralizing section 60. In the evaporator, water is evaporated from the concentrated water, and ions contained in the concentrated water are deposited as a solid and recovered as a solid. Because water is recovered on the

upstream side of the evaporator, and the amount of concentrated water significantly decreases, the evaporator can be reduced in size, and the energy required for evaporation can be reduced.

{0105}

{Second Reference Embodiment}

Fig. 9 is a schematic diagram of a water treatment system of the second reference embodiment of the present invention. In Fig. 9, the same configurations as in the first reference embodiment are indicated with the same reference numerals. In the water treatment system 100 of the second reference embodiment, a first separating section 180 (180a, 180b) is installed on the downstream side of the first crystallizing sections 20a and 20b. The water treatment system 100 of Fig. 9 is configured such that two water treatment sections are connected in the flow direction of the water to be treated. In the water treatment system 100 of this reference embodiment, depending on the properties of the water to be treated, the number of water treatment sections may be one, and it is also possible that three or more water treatment sections are connected.

In Fig. 9, the first separating section 180 (180a, 180b) includes a classifier 181 (181a, 181b) and a dehydrator 182 (182a, 182b). The classifiers 181a and 181b are liquid cyclones, for example. The dehydrators 182a and 182b are belt

filters, for example.

{0106}

Although the first separating section 180 has only one classifier installed in Fig. 9, it is also possible that two or more classifiers are connected in series in the flow direction of the water to be treated.

{0107}

In the water treatment system 100 of the second reference embodiment, the water to be treated is treated through the same steps as in the first reference embodiment, except that the first separating step is performed immediately after the first crystallizing step.

<First Separating Step>

First concentrated water in the first crystallizing tanks 21a and 21b is transferred to the first separating sections 180a and 180b. The first concentrated water transferred here is water containing solid matters deposited in the first crystallizing tanks 21a and 21b.

{0108}

The first concentrated water discharged from the first crystallizing tanks 21a and 21b contains gypsum having various particle diameters, as well as calcium carbonate and silica deposited due to the exceeding of the saturation concentration. Because the deposition of calcium carbonate and silica has taken place in the absence of seed crystals,

they have small diameters or are floating matters in a colloidal form.

When the first concentrated water flows into the classifiers 181a and 181b, gypsum having a predetermined size, for example, gypsum having an average particle diameter of 10 μm or more, sediments at the bottom of the classifiers 181a and 181b, and gypsum having a small particle diameter, calcium carbonate, and silica remain in the supernatant. The gypsum sedimented at the bottom of the classifiers 181a and 181b is further dehydrated by the dehydrators 182a and 182b and recovered. The supernatant containing gypsum having a small particle diameter, calcium carbonate, and silica is fed to the first precipitating sections 50a and 50b.

{0109}

In this reference embodiment, seed crystals are added to cause crystallization. Therefore, gypsum having an average particle diameter of 10 μm or more is mainly deposited, and the proportion of gypsum having a small diameter is low. Through the first separating step, gypsum having a low water content and containing no impurities (i.e., high-purity gypsum) can be separated and recovered with high recovery.

{0110}

Some of the gypsum recovered in the first separating sections 180a and 180b may be circulated through the seed crystal tanks 23a and 23b as seed crystals.

{0111}

{Third Reference Embodiment}

Fig. 10 is a schematic diagram of a water treatment system of the third reference embodiment of the present invention. The water treatment system 200 of Fig. 10 is configured such that two water treatment sections are connected in the flow direction of the water to be treated. Depending on the properties of the water to be treated, the number of water treatment sections may be one, and it is also possible that three or more water treatment sections are connected.

{0112}

In the water treatment system 200 of the third reference embodiment, each water treatment section includes, from the upstream side of the water to be treated, a second demineralizing section 210 (210a, 210b) and a second crystallizing section 220 (220a, 220b). The concentration sides of the second demineralizing sections 210a and 210b are connected to the second crystallizing sections 220a and 220b, respectively. The water treatment section includes a second scale inhibitor supplying section 230 (230a, 230b) in the flow path on the upstream side of each second demineralizing section 210 (210a, 210b).

{0113}

The second scale inhibitor supplying sections 230a and

230b are each made up of a tank 231 (231a, 231b), a valve V4 (V4a, V4b), and a control section 232 (232a, 232b). The control sections 232a and 232b are connected to the valves V4a and V4b, respectively. The tanks 231a and 231b of the second scale inhibitor supplying sections 230a and 230b have stored therein a scale inhibitor.

{0114}

Scale inhibitors used in the third reference embodiment are the calcium scale inhibitor described in the first reference embodiment and a scale inhibitor that inhibits the deposition of silica as scales in the water to be treated (referred to as "silica scale inhibitor"). Examples of silica scale inhibitors include phosphonic-acid-based scale inhibitors, polycarboxylic-acid-based scale inhibitors, and mixtures thereof. A specific example is FLOCON260 (trade name, manufactured by BWA).

Fig. 10 shows two tanks 231a. For example, a calcium scale inhibitor is stored in one tank 231a, and a silica scale inhibitor is stored in the other tank 231a.

{0115}

In Fig. 10, the second demineralizing section 210 is a reverse osmosis membrane device. In addition, the second demineralizing section 210 may also be an electrodialyzer (ED), an electro dialysis reversal device (EDR), an electro de-ionization device (EDI), an ion-exchange equipment, a

capacitive de-ionization device (CDI), a nanofilters (NF), an evaporator, etc.

Although only one second demineralizing section 210 is shown in Fig. 10, the system may also be configured such that two or more demineralizers are connected in parallel or in series in the flow direction of the water to be treated.

{0116}

The second crystallizing section 220 (220a, 220b) is made up of a second crystallizing tank 221 (221a, 221b) and a second seed crystal supplying section 222 (222a, 222b). The second seed crystal supplying section 222 is connected to the second crystallizing tank 221. The second seed crystal supplying section 222 has a seed crystal tank 223 (223a, 223b), a valve V5 (V5a, V5b), and a control section 224 (224a, 224b). The control section 224 is connected to the valve V5. The seed crystal tank 223 stores gypsum particles as seed crystals.

{0117}

In the water treatment system 200 of the third reference embodiment, a second pH adjusting section 240 (240a, 240b) may be installed between the second demineralizing section 210 and the second crystallizing section 220. The second pH adjusting section 240 is made up of a tank 241 (241a, 241b), a valve V6 (V6a, V6b), a pH meter 243 (243a, 243b), and a control section 242 (242a, 242b). The tank 241 has stored therein an acid as

a pH adjuster. The acid used may be hydrochloric acid, sulfuric acid, nitric acid, or the like, for example. Sulfuric acid is particularly preferable because SO_4^{2-} is removed as gypsum in the crystallizing step, and thus the amount of ions that reach the demineralizing section on the downstream side can be reduced. The control section 242 is connected to the valve V6 and the pH meter 243. The pH meter 243 may be installed in the flow path between the second demineralizing section 210 and the second crystallizing section 220 as shown in Fig. 10, or may also be installed in the second crystallizing tank 221.

{0118}

In the water treatment system 200, a precipitating tank 271 and a filtration device 272 are installed as a second upstream side precipitating section 270 on the upstream side of the second scale inhibitor supplying section 230a located on the most upstream of the water to be treated. The second upstream side precipitating section 270 has the same configuration as the first upstream side precipitating section 70. As in the first reference embodiment, two or more stages of precipitating tanks 271 may be connected in series in the flow direction of the water to be treated.

{0119}

In the water treatment system 200, a second deaerating section 273 may be provided on the upstream side of the second

upstream side precipitating section 270 as shown in Fig. 10. The second deaerating section 273 has the same configuration as the first deaerating section 73 of the first reference embodiment.

The second deaerating section 273 may be installed on the downstream side of the water to be treated of the second upstream side precipitating section 270 and on the upstream side of the second scale inhibitor supplying section 230a.

{0120}

It is also possible that a deaerating section having the same configuration as the second deaerating section 273 is installed in the flow path between the second demineralizing section 210a and the second crystallizing section 220a, in the flow path between the second crystallizing section 220 and the second precipitating section 250, and on the downstream side of the second precipitating section 250 and in the flow path between it and the second demineralizing section 210b or the downstream side demineralizing section 60.

{0121}

As in the first reference embodiment, an ion-exchange equipment (not shown) may be installed on the downstream of the filtration device 272 and on the upstream of the second scale inhibitor supplying section 230a located on the most upstream. In addition, depending on the concentration of gypsum in the water to be treated, an upstream side

crystallizing section (not shown) having the same configuration as the second crystallizing section may be installed on the upstream of the second scale inhibitor supplying section 230a on the most upstream.

{0122}

In this reference embodiment, a second separating section 280 (280a, 280b) may be installed on the downstream side of the second crystallizing section 220 as shown in Fig. 10. The second separating section 280 has the same configuration as the first separating section 180 and includes a classifier 281 (281a, 281b) and a dehydrator 282 (282a, 282b).

{0123}

In the water treatment system 200 of Fig. 10, a second precipitating section 250 (250a, 250b) may be installed on the downstream side of the second crystallizing section 220. The second precipitating section 250 has the same configuration as the first precipitating section 50 and includes a second precipitating tank 251 (251a, 251b) and a second filtration device 252 (252a, 252b).

{0124}

The water treatment system 200 includes a downstream side demineralizing section 60 on the downstream side of the water to be treated of the first water treatment section. An evaporator (not shown in Fig. 10) may be installed on the downstream on the concentrated-water side of the downstream

side demineralizing section 60.

{0125}

A process for treating water to be treated using the water treatment system 200 of the third reference embodiment will be described hereinafter.

{0126}

<Pretreatment>

The water to be treated is subjected to the pretreatment described in the first reference embodiment.

{0127}

<Second Deaerating Step>

In the same manner as in the first deaerating step described in the first reference embodiment, CO₂ in the water to be treated is removed in the second deaerating section 273, whereby the concentration of carbonate ions in the water to be treated is reduced.

{0128}

<Second Upstream Side Precipitating Step>

In the second upstream side precipitating section 270, some of Ca ions and carbonate ions are previously removed from the water to be treated as calcium carbonate. In the case where metal ions other than Ca ions are contained in the water to be treated, in the second upstream side precipitating section 270, some of a metal compound having low solubility in water is previously removed from the water to be treated.

The second upstream side precipitating step is performed in the same manner as in the first upstream side precipitating step.

In the case where water to be treated containing Mg ions is treated in the water treatment system 200 of this reference embodiment, as in the first reference embodiment, the water to be treated is adjusted to a pH at which a magnesium compound is deposited in the second upstream side precipitating section 270, and some of Mg ions in the water to be treated are removed. Subsequently, it is preferable that the water to be treated is adjusted to a pH at which the magnesium compound is soluble on the downstream side of the second upstream side precipitating section 270. Specifically, the pH is adjusted to less than 10. Accordingly, the formation of scales in devices and steps on the downstream side, particularly the second demineralizing section 210 and the second demineralizing step, can be inhibited.

{0129}

In the case where the second deaerating step is performed after the second upstream side precipitating step, the pH of the water to be treated is adjusted to a pH at which carbonate ions can be present as CO_2 , specifically 6.5 or less.

{0130}

Depending on the properties of the water to be treated, the second deaerating step and the second upstream side

precipitating step may be omitted.

{0131}

In the case where an ion-exchange membrane device is installed, in the water treatment system 200 of the third reference embodiment, Ca ions and Mg ions in the water to be treated are removed by the ion-exchange membrane device.

In the case where an upstream side crystallizing section is installed, the concentration of gypsum in the water to be treated is reduced in the upstream side crystallizing section through the same steps as in the first reference embodiment.

{0132}

<Second Scale Inhibitor Supplying Step>

The control section 232a of the second scale inhibitor supplying section 230a opens the valve V4a and supplies a predetermined amount of calcium scale inhibitor to the water to be treated from the tank 231a. The control section 232b of the second scale inhibitor supplying section 230b opens the valve V4b and supplies a predetermined amount of silica scale inhibitor to the water to be treated from the tank 231b. The control section 232a and the control section 232b adjust the valve opening of the valve V4a and the valve V4b, respectively, so that the concentrations of the calcium scale inhibitor and the silica scale inhibitor are predetermined values set according to the properties of the water to be treated.

{0133}

In the water treatment system 200 of the third reference embodiment, the pH adjustment of the water to be treated immediately before flowing into the second demineralizing section 210 is optionally performed.

For example, in the configuration of Fig. 10, as a result of the addition of FeCl_3 , the water to be treated is adjusted to about pH 5 to 6 and then flows into the second demineralizing section 210a. As shown in Fig. 3, the solubility of calcium carbonate in water is high when the pH of the water to be treated is 6.5 or less. In addition, as in formula (1), in the above pH range, carbonic acid is present mainly in the form of HCO_3^- and CO_2 in water. The water to be treated flowing into the second demineralizing section 210a has a reduced concentration of calcium carbonate. In such a case, it is not necessary to adjust the pH immediately before the second demineralizing section 210a.

Incidentally, in the case where the pH of the water to be treated, which is to be treated in the second demineralizing step, is adjusted, it is possible that a pH adjusting section having the same configuration as the first pH adjusting section of the first reference embodiment is installed on the upstream of the second demineralizing section 210a, and the pH-adjusted water to be treated is fed to the second demineralizing section 210a.

{0134}

<Second Demineralizing Step>

In the second demineralizing section 210a, the water to be treated containing the scale inhibitors is treated. In the case where the second demineralizing section 210a is a reverse osmosis membrane device, the water that has passed through the reverse osmotic membrane is recovered as treated water. The water containing ions and the scale inhibitors is discharged from the non-permeate side of the reverse osmosis membrane as concentrated water (second concentrated water).

As a result of the treatment in the second demineralizing section 210a, gypsum and silica is concentrated in the second concentrated water. However, the production of scales is suppressed by the calcium scale inhibitor and the silica scale inhibitor.

{0135}

Also in the case where other demineralizers, such as a capacitive de-ionization device, are used, for example, the water to be treated is separated into treated water and concentrated water having a high concentration of ions (second concentrated water). The second concentrated water is fed toward the second crystallizing section 220a.

{0136}

<Second pH Adjusting Step>

In this reference embodiment, the pH of the water to be

treated (second concentrated water) may be adjusted by the second pH adjusting section 240a between the second demineralizing section 210a and the second crystallizing section 220a.

The second pH adjusting section 240a controls the pH of the second concentrated water to such a value that the function of the calcium scale inhibitor is reduced and gypsum in the second concentrated water can be deposited. The pH meter 243a measures the pH of the second concentrated water. The control section 242a adjusts the opening of the valve V6a so that the value measured by the pH meter 243a is a predetermined pH control value.

{0137}

<Second Crystallizing Step>

The second concentrated water is stored in the second crystallizing tank 221 of the second crystallizing section 220a. The control section 224a of the second seed crystal supplying section 222a opens the valve V5 and adds seed crystals of gypsum from the seed crystal tank 223a to the second concentrated water in the second crystallizing tank 221a. Although the second concentrated water contains a calcium scale inhibitor, when seed crystals are loaded, gypsum is crystallized, followed by crystal growth.

{0138}

As shown in Fig. 5, under Condition 1 (pH 6.5), the

degree of supersaturation is 460%, and there is no change from the initial degree of supersaturation even after the elapse of 6 hours. Under Condition 1, the scale inhibitor exerts its function to suppress the deposition of gypsum. Meanwhile, under Condition 4 and Condition 2, the degree of supersaturation decreases.

That is, it has been confirmed that even when seed crystals are not loaded, a decrease in pH leads to a decrease in the function of the scale inhibitor, whereby gypsum is crystallized. In addition, according to the results of Fig. 5, the deposition rate increases with a decrease in pH.

{0139}

In Fig. 6, as a comparison with Condition 5 (pH 4.0), under Condition 7 (pH 4.0), seed crystals pre-immersed with the above calcium scale inhibitor were added to simulated water having added thereto a calcium scale inhibitor, and sulfuric acid was added for pH adjustment. Condition 5 and Condition 7 are otherwise the same, and gypsum deposition experiments were performed under such conditions. Two hours after the pH adjustment, the concentration of Ca in the simulated water was measured by the same technique as in Fig. 3.

As a result, as shown in Fig. 6, the degree of supersaturation was 199% or less both under Condition 5 and Condition 7. From this, it can be said that independent of

the immersion time of seed crystals with a calcium scale inhibitor, when the pH is reduced to 4.0, the function of the calcium scale inhibitor is reduced.

{0140}

In consideration of the effects of the calcium scale inhibitor, the pH of the second concentrated water is adjusted in the second pH adjusting step to 6.0 or less, preferably 5.5 or less, and more preferably 4.0 or less. In particular, when the second concentrated water is adjusted to pH 4.0 or less, the function of the calcium scale inhibitor can be significantly reduced. By adjusting the pH of the second concentrated water to such a value that the scale inhibition function of the calcium scale inhibitor is reduced, crystallization in the second crystallizing section 220a is promoted. According to the kind of scale inhibitor, the pH range in the second pH adjusting step is suitably determined.

{0141}

With reference to Fig. 4, in the case where pH is low, silica may exceed the saturation solubility. However, in this reference embodiment, a silica scale inhibitor is loaded in the second water treatment section. Accordingly, the deposition of silica is suppressed even at low pH. Even when silica is deposited in the second crystallizing tank 221a, such silica is present as small-diameter particles or floating matters in a colloidal form.

In addition, with reference to Fig. 3, calcium carbonate dissolves in water at pH 6.0 or less.

From the above, high-purity gypsum can be recovered in the second crystallizing tank 221a of the second water treatment section.

{0142}

Meanwhile, the second concentrated water in the second crystallizing step may also be adjusted in the second pH adjusting step to a pH at which silica is soluble in the second concentrated water. Accordingly, in the second crystallizing tank 221a, the deposition of silica from the second concentrated water is suppressed. As a result, in the case where the second concentrated water discharged from the second crystallizing tank 221a in the second separating section 280a is classified, the purity of the recovered gypsum can be increased.

{0143}

<Second Separating Step>

In the case where the second separating section 280a is installed, the second concentrated water containing solid matters deposited in the second crystallizing tank 221a is transferred to the second separating section 280a. In the second concentrated water in the second crystallizing tank 221a, gypsum deposited by crystallization is present. In addition, the second concentrated water may also contain

silica deposited because of an increase in the silica concentration to be equal to or higher than the concentration at which the silica scale inhibitor exerts its function due to the quality change or concentration of the raw water. Silica is present in the second concentrated water as small-diameter particles or floating matters in a colloidal form.

{0144}

Through the same steps as in the second reference embodiment, the classifier 281a of the second separating section 280a performs separation into gypsum having a predetermined size (e.g., having an average particle diameter of 10 μm or more) and a supernatant containing small-diameter precipitates (gypsum, silica). Large-diameter gypsum is further dehydrated by the dehydrator 282a and recovered. According to this reference embodiment, high-purity gypsum can be recovered. Some of the recovered gypsum may be circulated through the seed crystal tank 223a as seed crystals.

{0145}

In the case where the second separating section 280a is not installed, gypsum precipitated at the bottom of the second crystallizing tank 221a of the second crystallizing section 220a is discharged from the second crystallizing tank 221a. The supernatant of the second crystallizing tank 221a is fed to the second precipitating section 250a.

{0146}

<Second Precipitating Step>

The supernatant (second concentrated water) in the second crystallizing section 220a or the supernatant (second concentrated water) discharged from the second separating section 280a is fed to the second precipitating section 250a.

In the second precipitating step, in the same manner as in the first precipitating step described in the first reference embodiment, calcium carbonate and metal compounds in the second concentrated water are removed in the second precipitating tank 251a and the second filtration device 252a.
{0147}

In the second precipitating step, it is also possible that in the same manner as in the first precipitating step, at least one of seed crystals of silica and a precipitant for silica is added to the second precipitating tank 251a to remove silica from the second concentrated water.
{0148}

In the case where the treatment is performed in several stages as shown in Fig. 10, the second concentrated water that has passed through the second filtration device 252a of the second water treatment section of the previous stage flows into the water treatment section of the subsequent stage as water to be treated. In the water treatment section of the subsequent stage, the steps from the second scale inhibitor supplying step to the second precipitating step mentioned

above are performed.

{0149}

<Downstream Side Demineralizing Step>

The second concentrated water that has passed through the second precipitating section 250b located on the most downstream of the water to be treated is treated in the downstream side demineralizing section 60. The water that has passed through the downstream side demineralizing section 60 is recovered as water to be treated. The concentrated water in the downstream side demineralizing section 60 is discharged out of the system.

Also in this reference embodiment, an evaporator (not shown) may be installed on the downstream on the concentrated-water side of the downstream side demineralizing section 60.

{0150}

In the third reference embodiment, in the case where the second concentrated water is adjusted in the second pH adjusting step to a pH at which the function of the calcium scale inhibitor is reduced, as a third pH adjusting step, the pH of the second concentrated water may be adjusted after the second crystallizing step in order for the calcium scale inhibitor to exert its function. Specifically, the pH is preferably adjusted to 4.0 or more, preferably 5.5 or more, and more preferably 6.0 or more. The third pH adjusting step is performed after the second crystallizing step and before

the second demineralizing step, or after the second crystallizing step and before the downstream side demineralizing step.

{0151}

In the water treatment system 200 of this reference embodiment, in order to perform the third pH adjusting step, a third pH adjusting section (not shown in Fig. 10) having the same configuration as the second pH adjusting section is installed between the second crystallizing section and the second demineralizing section immediately thereafter (in Fig. 10, between the second crystallizing section 220a and the second demineralizing sections 210b, particularly the second precipitating section 250a and the second demineralizing section 210b). In addition, a third pH adjusting section (not shown in Fig. 10) having the same configuration as the second pH adjusting section is installed between the second precipitating section 250b and the downstream side demineralizing section 60 on the most downstream. Accordingly, even in the case where the second concentrated water is treated in the downstream side demineralizing step, and the concentration of Ca ions is high on the concentrated-water side, the formation of scales can be suppressed by the function of the calcium scale inhibitor.

{0152}

In the water treatment system 200 of this reference

embodiment, silica is concentrated by the treatment in the second water treatment section. When the concentration of silica in the second concentrated water is equal to or higher than the concentration at which the silica scale inhibitor effectively works, scales of silica may be formed from the second concentrated water. For example, in the case where FLOCON260 is used as a silica scale inhibitor, the scale-production-inhibiting effect can be obtained at a silica concentration up to about 200 mg/L. Therefore, the number of stages of the second water treatment sections is determined so that silica is concentrated to the concentration at which the silica scale inhibitor can exert its effect.

{0153}

By using the water treatment system 200 of the third reference embodiment, water to be treated containing ions can be treated with high water recovery.

In particular, in the third reference embodiment, gypsum is mainly deposited in the second crystallizing section 220. Accordingly, the gypsum recovery in the second crystallizing section 220 is high, and the number of moles of ions fed to the downstream side is further reduced. In addition, the purity of the gypsum recovered in the second crystallizing section 220 can be increased.

{0154}

{First Embodiment}

Fig. 11 is a schematic diagram of a water treatment system of the first embodiment of the present invention. In Fig. 11, the same configurations as in the first to third reference embodiments are indicated with the same reference numerals.

In the water treatment system 300 of the first embodiment, the water treatment section described in the first reference embodiment is installed. On the downstream side of the water to be treated of this water treatment section, the water treatment section described in the third reference embodiment is installed.

{0155}

In the water treatment system 300 of Fig. 11, a first separating section 180 is installed on the downstream side of the first crystallizing section 20. In addition, a second separating section 280, which is the same as the first separating section 180, is installed on the downstream side of the second crystallizing section 220.

{0156}

A downstream side demineralizing section 60 is installed on the downstream side of the water to be treated of the second crystallizing section 220 located on the most downstream.

{0157}

The water treatment system 300 of the first embodiment

51258-103

77

includes the first upstream side precipitating section 70 described in the first reference embodiment on the upstream side of the first scale inhibitor supplying section 30 and the first pH adjusting section 40 which are located on the most upstream of the water to be treated.

{0158}

Further, the water treatment system 300 of the first embodiment includes a first deaerating section 73, which is the same as in the first reference embodiment, on the upstream side of the first upstream side precipitating section 70 as shown in Fig. 11. The first deaerating section 73 may also be installed on the downstream side of the water to be treated of the first upstream side precipitating section 70 and on the upstream side of the first scale inhibitor supplying section 30 and the first pH adjusting section 40.

{0159}

Incidentally, a deaerating section having the same configuration as the first deaerating section 73 may be installed in the flow path between the first demineralizing section 10 and the first crystallizing section 20, in the flow path between the first crystallizing section 20 and the first precipitating section 50, in the flow path between the second crystallizing section 220 and the second precipitating section 250, and in the flow path between the first precipitating section 50 and the second demineralizing section 210.

{0160}

Also in the water treatment system 300 of this embodiment, an ion-exchange equipment (not shown) and an upstream side crystallizing section (not shown) may be provided on the upstream of the first scale inhibitor supplying section 30 and the first pH adjusting section 40.

{0161}

In Fig. 11, the water treatment sections from the first scale inhibitor supplying section 30 to the first precipitating section 50 and from the second scale inhibitor supplying section 230 to the second precipitating section 250 are each shown as one stage. However, it is also possible that for each section, two or more stage of water treatment sections are connected.

{0162}

In the water treatment system 300 of the first embodiment, first, water to be treated is treated by the water treatment process described in the first reference embodiment and the second reference embodiment. First concentrated water after being treated by the process of the first reference embodiment and the second reference embodiment is treated as water to be treated through the steps from the second scale inhibitor supplying step to the second precipitating step described in the third reference embodiment.

Second concentrated water that has passed through the

second precipitating section 250 on the most downstream is treated in the downstream side demineralizing section 60. The water that has passed through the downstream side demineralizing section 60 is recovered as treated water. The concentrated water in the downstream side demineralizing section 60 is discharged out of the system.

Also in this embodiment, an evaporator (not shown) may be installed on the downstream on the concentrated-water side of the downstream side demineralizing section 60.

{0163}

In the first embodiment, in the case where the second concentrated water is adjusted to a pH at which the function of the calcium scale inhibitor is reduced in the second pH adjusting step, the third pH adjusting step described in the third reference embodiment may be performed.

{0164}

{Fourth Reference Embodiment}

Fig. 12 is a schematic diagram of a water treatment system of the fourth reference embodiment of the present invention. In Fig. 12, the same configurations as in the first to third reference embodiments are indicated with the same reference numerals.

In the water treatment system 400 of the fourth reference embodiment, the water treatment section described in the third reference embodiment is installed. On the downstream side of

the water to be treated of this water treatment section, the water treatment section described in the first reference embodiment is installed.

{0165}

In the water treatment system 400 of Fig. 12, a first separating section 180 and a second separating section 280 are installed.

{0166}

A downstream side demineralizing section 60 is installed on the downstream side of the water to be treated of the first crystallizing section 20 located on the most downstream.

{0167}

The water treatment system 400 of the fourth reference embodiment includes the second upstream side precipitating section 270 described in the third reference embodiment on the upstream side of the second scale inhibitor supplying section 230 located on the most upstream of the water to be treated.

Further, the water treatment system 400 of the fourth reference embodiment has a second deaerating section 273, which is the same as in the third reference embodiment, on the upstream side of the second upstream side precipitating section 270 as shown in Fig. 12. The second deaerating section 273 may be installed on the downstream side of the water to be treated of the second upstream side precipitating section 270 and on the upstream side of the second scale

inhibitor supplying section 230.

{0168}

Incidentally, a deaerating section having the same configuration as the second deaerating section 273 may be installed in the flow path between the second demineralizing section 210 and the second crystallizing section 220, in the flow path between the first crystallizing section 20 and the first precipitating section 50, in the flow path between the second crystallizing section 220 and the second precipitating section 250, and in the flow path between the second precipitating section 250 and the first demineralizing section 10.

{0169}

Also in the water treatment system 400 of this reference embodiment, an ion-exchange equipment (not shown) and an upstream side crystallizing section (not shown) may be provided on the upstream of the second scale inhibitor supplying section 230.

{0170}

In the water treatment system 400 of this reference embodiment shown in Fig. 12, a first separating section 180 and a second separating section 280 may be installed on the downstream side of the first crystallizing tank 21 and the second crystallizing tank 221, respectively.

{0171}

In Fig. 12, the water treatment sections from the second scale inhibitor supplying section 230 to the second precipitating section 250 and from the first scale inhibitor supplying section 30 to the first precipitating section 50 are each shown as one stage. However, it is also possible that for each section, two or more stage of water treatment sections are connected.

{0172}

In the water treatment system 400 of the fourth reference embodiment, first, water to be treated is treated by the water treatment process described in the third reference embodiment. Second concentrated water after being treated by the process of the third reference embodiment is treated as water to be treated through the steps from the first scale inhibitor supplying step to the first precipitating step described in the first reference embodiment and the second reference embodiment.

First concentrated water that has passed through the first precipitating section 50 on the most downstream is treated in the downstream side demineralizing section 60. The water that has passed through the downstream side demineralizing section 60 is recovered as treated water. The concentrated water in the downstream side demineralizing section 60 is discharged out of the system.

Also in this reference embodiment, an evaporator (not

shown) may be installed on the downstream on the concentrated-water side of the downstream side demineralizing section 60.

{0173}

In the fourth reference embodiment, in the case where the second concentrated water is adjusted to a pH at which the function of the calcium scale inhibitor is reduced in the second pH adjusting step, the third pH adjusting step described in the third reference embodiment may be performed.

{0174}

Also by the water treatment system 300 of the first embodiment and the water treatment system 400 of the fourth reference embodiment, water to be treated containing ions can be treated with high water recovery.

In particular, the fourth reference embodiment is configured such that gypsum is mainly deposited in the second crystallizing section 220 on the upstream side of the water to be treated. Accordingly, the gypsum recovery in the second crystallizing section 220 is high, and the number of moles of ions fed to the downstream side is further reduced. Further, the purity of the gypsum recovered in the second crystallizing section 220 can be increased.

{0175}

{Fifth Reference Embodiment}

According to the fifth reference embodiment of the present invention, the amount of seed crystals of gypsum to be

51258-103

84

supplied to the first crystallizing tank 21 and the second crystallizing tank 221 in the first to fourth reference embodiments is controlled. The configuration that controls the amount of seed crystals to be supplied to the first crystallizing tank 21 will be described with reference to Fig. 13. The same configuration is also applied to the second crystallizing tank 221.

{0176}

In the fifth reference embodiment, a first pH measuring section 543 that measures the pH of the first concentrated water in the first crystallizing tank 21 is installed. The first pH measuring section 543 may be installed in the flow path that connects the first demineralizing section 10 and the first crystallizing tank 21, or may also be directly installed in the first crystallizing tank 21. The first pH measuring section 543 is connected to the control section 24 of the first seed crystal supplying section 22.

{0177}

In the fifth reference embodiment, as shown in Fig. 13, a pH adjusting section 540 is installed. The pH adjusting section 540 includes a tank 541, a control section 542, and a valve V7. The first pH measuring section 543 is connected to the control section 542 of the pH adjusting section 540. The pH adjusting section 540 controls the pH of the first concentrated water in the first crystallizing tank 21 to a

predetermined value based on the value measured by the first pH measuring section 543.

Incidentally, in the case where the amount of seed crystals of gypsum to be supplied to the second crystallizing tank 221 is controlled, the pH meter 243a described in the third reference embodiment corresponds to the second pH measuring section, and the control section 242 of the second pH adjusting section corresponds to the control section 542.

{0178}

Seed crystals stored in the seed crystal tank 23 of the first seed crystal supplying section 22 may be new chemicals. However, in the case where a first separating section 180 is installed, the seed crystal tank 23 may also store gypsum separated by the classifier 181, whose particle diameter is equal to or greater than a predetermined particle diameter, or gypsum after being dehydrated by the dehydrator 182.

{0179}

The control of the amount of seed crystals to be supplied in the fifth reference embodiment is performed through the following steps. Hereinafter, the case where the amount of seed crystals to be supplied is constantly controlled during continuous operation will be explained as an example.

The first pH measuring section 543 measures the pH of the first concentrated water in the first crystallizing tank 21. The measured pH value is sent to the control section 24 of the

seed crystal supplying section 22.

{0180}

The control section 24 stores the pH range where the scale inhibition function of a calcium scale inhibitor is reduced. Specifically, as described for the second crystallizing step, the pH range where the scale inhibition function of a calcium scale inhibitor is reduced is 6.0 or less, preferably 5.5 or less, and more preferably 4.0 or less.

{0181}

The control section 24 compares the value measured by the first pH measuring section 543 with the above pH range. In the case where the measured value is within the above pH range, the control section 24 reduces the opening of the valve V3 to reduce the amount of seed crystals of gypsum to be supplied. In the case where the measured value is greater than the above pH range, the control section 24 increases the opening of the valve V3 to increase the amount of seed crystals of gypsum to be supplied.

{0182}

Gypsum is deposited when seed crystals are present. However, in the case where the calcium scale inhibitor exerts its function, the crystallization rate is low. Accordingly, the amount of seed crystals is increased to promote crystallization. Meanwhile, in the case where the function of the calcium scale inhibitor is reduced, a sufficient

crystallization rate can be obtained even when the amount of seed crystals is small.

In this way, by adjusting the amount of seed crystals to be supplied according to the pH, the amount of seed crystals used can be reduced.

{0183}

In this reference embodiment, it is also possible that the pH is regularly measured during continuous operation, and seed crystals are supplied intermittently. Alternatively, it is also possible that the time-dependent variation of pH is obtained at the time of the test run of the system, for example, and the amount of seed crystals to be supplied is increased or decreased based on the obtained time-dependent variation.

{0184}

{Sixth Reference Embodiment}

The sixth reference embodiment of the present invention is a water treatment system 600 provided with at least either a first separating section 180 or a second separating section 280. The water treatment system 600 differs from the fifth reference embodiment in that gypsum separated in the separating section is directly supplied to a first crystallizing tank or a second crystallizing tank as seed crystals.

{0185}

The configuration that controls the amount of seed crystals to be supplied to the first crystallizing tank 21 in this reference embodiment will be described with reference to Fig. 14. The same configuration is also applied to the second crystallizing tank 221.

In Fig. 14, a first circulation line 601, which performs transfer so that some of the gypsum sedimented at the bottom of the classifier 181 of the first separating section 180 is supplied directly to the first crystallizing tank 21, is installed. In addition, a second circulation line 602, which performs transfer so that some of the gypsum after being dehydrated by the dehydrator 182 is supplied directly to the first crystallizing tank 21, is installed. A valve V8 is installed in the first circulation line 601, and a valve V9 is installed in the second circulation line 602. Incidentally, this reference embodiment may also be configured such that either the first circulation line 601 or the second circulation line 602 is installed.

The control section 610 is connected to a first pH measuring section 543, which is the same as in the fifth reference embodiment, the valve V8, and the valve V9.

{0186}

The control of the amount of seed crystals to be supplied in the sixth reference embodiment is performed through the following steps. Hereinafter, the case where the amount of

seed crystals to be supplied is constantly controlled during continuous operation will be explained as an example.

The first pH measuring section 543 measures the pH of the first concentrated water in the first crystallizing tank 21. The measured pH value is sent to the control section 610.

The control section 610 stores the pH range where the scale inhibition function of a calcium scale inhibitor is reduced. Through the same steps as in the fifth reference embodiment, the control section 610 compares the value measured by the first pH measuring section 543 with the above pH range to adjust the opening of the valve V8 and the valve V9.

{0187}

In the fifth reference embodiment and the sixth reference embodiment, a seed crystal concentration measuring section (not shown) that measures the concentration of gypsum seed crystals in the first concentrated water in the first crystallizing tank 21 may be installed in the first crystallizing tank 21. The seed crystal concentration measuring section measures the concentration of seed crystals in the first crystallizing tank 21. The measured concentration value is sent to the control section 24 or the control section 610. The control section 24 or the control section 610 stores the threshold for the concentration of seed crystals, and increases the amount of seed crystals to be

supplied in the case where the concentration of seed crystals is equal to or less than the threshold.

{0188}

As a modification of the fifth reference embodiment and the sixth reference embodiment, a first concentration measuring section (not shown) is installed on the downstream side of the first crystallizing tank 21 and on the upstream side of the first precipitating section 50. In the case where the first separating section 180 is provided, the first concentration measuring section is preferably installed on the downstream side of the first separating section 180, but may also be installed on the upstream side of the first separating section 180. The first concentration measuring section is connected to the control section 24 or the control section 610.

In the case of the second crystallizing tank 221, a second concentration measuring section is installed in place of the first concentration measuring section.

{0189}

The first concentration measuring section measures at least one of the concentration of Ca ions and the concentration of sulfate ions in the first concentrated water discharged from the first crystallizing tank 21. The measured concentration is sent to the control section 24 or the control section 610.

{0190}

The concentration of Ca ions and the concentration of sulfate ions measured by the first concentration measuring section depend on the crystallization rate in the first crystallizing tank 21. In the case where the residence time is the same, lower concentrations of Ca ions and sulfate ions lead to a higher crystallization rate.

{0191}

The control section 24 and the control section 610 store the threshold for at least one of the concentration of Ca ions and the concentration of sulfate ions.

{0192}

In the case where at least one of the concentration of Ca ions and the concentration of sulfate ions measured by the first concentration measuring section is equal to or higher than the threshold, the control section 24 increases the opening of the valve V3 to increase the amount of seed crystals to be supplied. In the case where at least one of the concentration of Ca ions and the concentration of sulfate ions measured by the first concentration measuring section is lower than the threshold, the control section 24 reduces the opening of the valve V3 to reduce the amount of seed crystals to be supplied.

In the case where at least one of the concentration of Ca ions and the concentration of sulfate ions measured by the

first concentration measuring section is equal to or higher than the threshold, the control section 610 increases the opening of the valve V8 and the valve V9 to increase the amount of seed crystals to be supplied. In the case where at least one of the concentration of Ca ions and the concentration of sulfate ions measured by the first concentration measuring section is lower than the threshold, the control section 610 reduces the opening of the valve V8 and the valve V9 to reduce the amount of seed crystals to be supplied.

{0193}

Also in the case of the second crystallizing tank 221, the amount of seed crystals to be supplied is controlled through the same steps as above.

In this way, by controlling the amount of seed crystals to be supplied depending on at least one of the concentration of Ca ions and the concentration of sulfate ions after the crystallizing step, the amount of seed crystals used can be reduced.

{0194}

{Seventh Reference Embodiment}

Fig. 15 is a partial schematic diagram of a water treatment system of the seventh reference embodiment of the present invention. In Fig. 15, the same configurations as in the first to third reference embodiments are indicated with

the same reference numerals.

The water treatment system 700 of Fig. 15 is configured such that the gypsum separated from the first concentrated water in the first crystallizing section 20 in the water treatment system of the fourth reference embodiment is recovered and supplied to the second crystallizing tank 221 of the second crystallizing section 220. Also in the water treatment system of the first embodiment, the same configuration can be employed.

{0195}

As described in the first reference embodiment, the pH of concentrated water (first concentrated water) in the first crystallizing tank 21 of the first crystallizing section 20 is not particularly limited. However, in terms of operation cost, it is more advantageous to perform the first crystallizing step without changing the pH from the first demineralizing step. In this case, the first crystallizing step is performed at a pH at which silica is soluble (10 or more), but the solubility of calcium carbonate is low in this pH range.

{0196}

Meanwhile, as described in the third reference embodiment, in the second crystallizing section 220 (second crystallizing step), gypsum is crystallized in a still lower pH range. At the pH range in the second crystallizing step

51258-103

94

(6.0 or less, more preferably 4.0 or less), calcium carbonate is soluble in water. When gypsum containing calcium carbonate recovered in the first crystallizing section 20 is supplied to the second crystallizing tank 221 of the second crystallizing section 220, calcium carbonate, which is an impurity, dissolves in the second concentrated water, and gypsum is present as a solid in the second concentrated water. By using the water treatment system 700 of the seventh reference embodiment, water to be treated can be treated with high water recovery, and also high-purity gypsum can be recovered.

{0197}

{Eighth Reference Embodiment}

Fig. 16 is a partial schematic diagram of a water treatment system of the eighth reference embodiment of the present invention. In Fig. 16, the same configurations as in the second reference embodiment are indicated with the same reference numerals.

Incidentally, the eighth reference embodiment will be described hereinafter using a water treatment process including a first separating step and a water treatment system including a first separating section. However, the same configuration is also applicable to the case of a second separating step and a second separating section.

{0198}

In Fig. 16, the water treatment system 800 includes,
for

one first crystallizing section 20, two or more classifiers (first classifiers) 181 in the flow direction of the water to be treated. In Fig. 16, two first classifiers 181a and 181b are installed. The size of gypsum to be separated is different between the first classifier 181a located on the most upstream and the first classifier 181b located on the downstream side. In this reference embodiment, the size of gypsum to be separated by the first classifier 181b is smaller than that of gypsum to be separated by the first classifier 181a. For example, the first classifier 181a is a classifier that separates particles having an average particle diameter of 10 μm or more, and the first classifier 181b is a classifier that separates particles having an average particle diameter of 5 μm or more.

{0199}

In the case where three or more first classifiers 181 are installed, they are designed such that the size of gypsum to be separated by each first classifier 181 decreases in the direction from the upstream side toward the downstream side. The number of first classifiers installed in the flow direction of the water to be treated and the particle diameter of solid matters that can be separated by each classifier are suitably determined in consideration of the water recovery, gypsum recovery, treatment cost, etc.

{0200}

In the water treatment system 800 of the eighth reference embodiment, the following treatment is performed in the first separating step.

In the first classifier 181a located on the most upstream, gypsum having an average particle diameter of 10 μm or more is classified and sedimented at the bottom of the first classifier 181a. The sedimented gypsum is discharged from the first classifier 181a and fed to the dehydrator 182. The supernatant in the first classifier 181a is fed to the first classifier 181b on the downstream side. This supernatant mainly contains particles having a particle diameter of less than 10 μm (gypsum, calcium carbonate, silica, etc.).

{0201}

In the first classifier 181b located on the downstream side, gypsum having an average particle diameter of 5 μm or more is classified and sedimented at the bottom of the first classifier 181b. The supernatant in the first classifier 181b is fed to the first precipitating section 50.

{0202}

The sedimented gypsum is discharged from the first classifier 181b. The discharged gypsum is fed to the first crystallizing tank 21 through a solid matter circulation line 801 and supplied into the first concentrated water in the first crystallizing tank 21.

51258-103

97

The circulated gypsum functions as seed crystals in the first crystallizing tank 21, and the circulated gypsum is crystallized, followed by crystal growth. The crystal-grown circulated gypsum having an average particle diameter of 10 μm or more is fed from the first crystallizing tank 21 to the first classifier 181a together with the first concentrated water, then separated from the first concentrated water by the first classifier 181a, and transferred to the dehydrator 182.

{0203}

10 The supernatant in the first classifier 181b contains particles having a relatively small diameter of less than 5 μm , such as those having a particle diameter of about 2 to 3 μm . In particular, in the early stage of the operation of the water treatment system (immediately after start-up, etc.), gypsum is
15 discharged from the first crystallizing tank 21 before it grows to a sufficient size in the first crystallizing tank 21, and an increased amount of gypsum flows into the first precipitating tank 51. In such a case, a large amount of gypsum is contained in the precipitate in the first precipitating tank 51. Thus,
20 in this reference embodiment, it is also possible that a circulation line 802 that connects the bottom of the first precipitating tank 51 to the first crystallizing tank 21 is provided, and solid matters containing gypsum precipitated at the bottom of the first precipitating tank 51 are circulated
25 through the first crystallizing tank 21.

{0204}

According to this reference embodiment, the amount of gypsum recovered in the first separating section is increased,

51258-103

98

and also the water content of the recovered gypsum can be reduced. The use of the water treatment process and the water treatment system of this reference embodiment leads to the reduction of the amount of gypsum particles having a relatively
 5 small diameter flowing out to the downstream side. Accordingly, the water recovery can be improved, and also the amount of waste resulting from the water treatment can be reduced.

{Reference Signs List}

{0205}

10 1, 100, 200, 300, 400, 500, 600, 700, 800: Water treatment system

10: First demineralizing section

20: First crystallizing section

21: First crystallizing tank

15 22: First seed crystal supplying section

23, 223: Seed crystal tank

24, 32, 42, 224, 232, 242, 542, 610: Control section

30: First scale inhibitor supplying section

31, 41, 231, 241, 541: Tank

20 40: First pH adjusting section

43, 243: pH meter

50: First precipitating section

51: First precipitating tank

52: First filtration device

60: Downstream side demineralizing section

70: First upstream side precipitating section

71: Precipitating tank

72: Filtration device

73: First deaerating section

180: First separating section

181, 181a, 181b, 281: Classifier

182, 282: Dehydrator

210: Second demineralizing section

220: Second crystallizing section

221: Second crystallizing tank

222: Second seed crystal supplying section

230: Second scale inhibitor supplying section

240: Second pH adjusting section

250: Second precipitating section

251: Second precipitating tank

252: Second filtration device

280: Second separating section

540: pH adjusting section

543: First pH measuring section

601: First circulation line

100

602: Second circulation line

801, 802: Solid matter circulation line

{CLAIMS}

{Claim 1}

A water treatment process comprising:

a first scale inhibitor supplying step of supplying a calcium scale inhibitor which is a scale inhibitor for inhibiting the deposition of a scale containing calcium to water to be treated containing Ca ions, SO₄ ions, carbonate ions and silica;

a first pH adjusting step of adjusting the water to be treated to a pH at which the silica is soluble in the water to be treated;

a first demineralizing step of separating the water to be treated into first concentrated water in which the Ca ions, the SO₄ ions, the carbonate ions and the silica are concentrated and treated water after the first scale inhibitor supplying step and the first pH adjusting step; and

a first crystallizing step of supplying seed crystals of gypsum to the first concentrated water so that gypsum is crystallized from the first concentrated water,

wherein the water treatment process further comprises, after the first crystallizing step:

a second scale inhibitor supplying step of supplying the calcium scale inhibitor and a silica scale inhibitor which is a scale inhibitor for inhibiting the deposition of the silica to the water to be treated;

a second demineralizing step of separating the water to be treated into second concentrated water in which the Ca ions, the SO_4 ions, the carbonate ions and the silica are concentrated and treated water after the second scale inhibitor supplying step; and

a second crystallizing step of supplying seed crystals of gypsum to the second concentrated water so that gypsum is crystallized from the second concentrated water.

{Claim 2}

The water treatment process according to claim 1, comprising a second pH adjusting step of adjusting the second concentrated water to a pH at which a scale inhibition function of the calcium scale inhibitor is reduced, thereby promoting the deposition of the gypsum in the second crystallizing step.

{Claim 3}

The water treatment process according to claim 1 or 2, comprising, after the second crystallizing step on a most downstream of the water to be treated, a downstream side demineralizing step of separating the second concentrated water into concentrated water and treated water, and recovering the separated treated water.

{Claim 4}

The water treatment process according to claim 2, wherein, after the second crystallizing step, the second

concentrated water after the adjustment of the pH in the second pH adjusting step is adjusted to a pH at which the calcium scale inhibitor exerts its function.

{Claim 5}

The water treatment process according to claim 1, comprising a second pH adjusting step of adjusting the second concentrated water to a pH at which the silica is soluble in the second crystallizing step.

{Claim 6}

The water treatment process according to any one of claims 1 to 5, comprising a first upstream side precipitating step of precipitating at least calcium carbonate from the water to be treated so that the concentration of the calcium carbonate in the water to be treated is reduced, before the first scale inhibitor supplying step and the first pH adjusting step on a most upstream side of the water to be treated.

{Claim 7}

The water treatment process according to claim 6, comprising a first deaerating step of removing CO₂ from the water to be treated before the first upstream side precipitating step or after the first upstream side precipitating step and before the first scale inhibitor supplying step and the first pH adjusting step.

{Claim 8}

The water treatment process according to any one of claims 1 to 7,

wherein the water to be treated contains metal ions; and

wherein the process comprises a first precipitating step of precipitating at least one of calcium carbonate and a metal compound so that the concentration of at least one of the calcium carbonate and the metal ions is reduced from the first concentrated water, after the first crystallizing step.

{Claim 9}

The water treatment process according to claim 8, wherein at least one of seed crystals of the silica and a precipitant for the silica is supplied to the first concentrated water in the first precipitating step.

{Claim 10}

The water treatment process according to claim 1 or 2,

wherein the water to be treated contains metal ions; and

wherein the process comprises a second precipitating step of precipitating at least one of calcium carbonate and a metal compound so that the concentration of at least one of the calcium carbonate and the metal ions is reduced from the second concentrated water, after the second crystallizing step.

{Claim 11}

The water treatment process according to claim 10, wherein at least one of seed crystals of the silica and a

precipitant for the silica is supplied to the second concentrated water in the second precipitating step.

{Claim 12}

The water treatment process according to claim 9 or 11, wherein, when the water to be treated contains Mg ions, the amount of the precipitant for the silica to be supplied is adjusted according to the concentration of the Mg ions.

{Claim 13}

The water treatment process according to claim 8, wherein, when the water to be treated contains Mg ions, the first concentrated water in the first precipitating step is adjusted to a pH at which a magnesium compound is deposited so that the concentration of the Mg ions is reduced, and

wherein, after the first precipitating step, the first concentrated water is adjusted to a pH at which the magnesium compound is soluble.

{Claim 14}

The water treatment process according to claim 10, wherein, when the water to be treated contains Mg ions, the second concentrated water in the second precipitating step is adjusted to a pH at which a magnesium compound is deposited so that the concentration of the Mg ions is reduced, and

wherein, after the second precipitating step, the second concentrated water is adjusted to a pH at which the magnesium compound is soluble.

{Claim 15}

The water treatment process according to claim 6,
wherein, when the water to be treated contains Mg ions,
the water to be treated in the first upstream side
precipitating step is adjusted to a pH at which a magnesium
compound is deposited so that the concentration of the Mg ions
is reduced, and

wherein, after the first upstream side precipitating
step, the water to be treated is adjusted to a pH at which the
magnesium compound is soluble.

{Claim 16}

The water treatment process according to claim 3, wherein
moisture is evaporated from the concentrated water in the
downstream side demineralizing step, so that a solid in the
concentrated water is recovered.

{Claim 17}

A water treatment system comprising:

a first scale inhibitor supplying section that supplies a
calcium scale inhibitor which is a scale inhibitor for
inhibiting the deposition of a scale containing calcium to
water to be treated containing Ca ions, SO₄ ions, carbonate
ions and silica;

a first pH adjusting section that supplies a pH adjuster
to the water to be treated to adjust the pH of the water to be
treated to such a value that the silica is soluble in the

water to be treated;

a first demineralizing section that is installed installed on a downstream side of the first scale inhibitor supplying section and the first pH adjusting section and separates the water to be treated into first concentrated water in which the Ca ions, the SO₄ ions, the carbonate ions and the silica are concentrated and treated water; and

a first crystallizing section including a first crystallizing tank that is installed on a downstream side of the first demineralizing section and crystallizes gypsum from the first concentrated water and a first seed crystal supplying section that supplies seed crystals of gypsum to the first crystallizing tank,

wherein the water treatment system further comprises, on a downstream side of the first crystallizing section with respect to the water to be treated:

a second scale inhibitor supplying section that supplies the calcium scale inhibitor and a silica scale inhibitor which is a scale inhibitor for inhibiting the deposition of silica to the water to be treated;

a second demineralizing section that is installed on a downstream side of the second scale inhibitor supplying section and separates the water to be treated into second concentrated water in which the Ca ions, the SO₄ ions, the carbonate ions and the silica are concentrated and treated

water; and

a second crystallizing section including a second crystallizing tank that is installed on a downstream side of the second demineralizing section and crystallizes gypsum from the second concentrated water and a second seed crystal supplying section that supplies seed crystals of gypsum to the second crystallizing tank.

{Claim 18}

The water treatment system according to claim 17, comprising a second pH adjusting section that is installed on a downstream side of the second demineralizing section and supplies a pH adjuster to the second concentrated water to adjust the pH of the second concentrated water to such a value that a scale inhibition function of the calcium scale inhibitor is reduced, and the deposition of the gypsum is promoted.

{Claim 19}

The water treatment system according to claim 17, comprising, on a downstream side of the second crystallizing section on a most downstream of the water to be treated, a downstream side demineralizing section that separates the second concentrated water discharged from the second crystallizing section into concentrated water and treated water.

{Claim 20}

The water treatment system according to claim 18, comprising, on a downstream side of the second crystallizing section, a third pH adjusting section that supplies a pH adjuster to the second concentrated water after the adjustment of the pH in the second pH adjusting section to adjust the pH of the second concentrated water to such a value that the calcium scale inhibitor exerts a function.

{Claim 21}

The water treatment system according to claim 17, comprising a second pH adjusting section that is installed on a downstream side of the second demineralizing section and supplies a pH adjuster to the second concentrated water to adjust the pH of the second concentrated water to such a value that the silica is soluble in the second concentrated water in the second crystallizing section.

{Claim 22}

The water treatment system according to any one of claims 17 to 21, comprising, on an upstream side of the first scale inhibitor supplying section and the first pH adjusting section located on a most upstream of the water to be treated, a first upstream side precipitating section that precipitates at least calcium carbonate from the water to be treated so that the concentration of the calcium carbonate in the water to be treated is reduced.

{Claim 23}

The water treatment system according to claim 22, comprising a first deaerating section that removes CO₂ from the water to be treated on an upstream side of the first upstream side precipitating section or on a downstream side of the first upstream side precipitating section and on an upstream side of the first scale inhibitor supplying section and the first pH adjusting section.

{Claim 24}

The water treatment system according to any one of claims 17 to 23,

wherein the water to be treated contains metal ions; and

wherein the system comprises, on a downstream side of the first crystallizing section, a first precipitating section that precipitates at least one of calcium carbonate and a metal compound so that the concentration of at least one of the calcium carbonate and the metal ions in the first concentrated water is reduced.

{Claim 25}

The water treatment system according to claim 24, wherein at least one of seed crystals of the silica and a precipitant for the silica is supplied to the first precipitating section.

{Claim 26}

The water treatment system according to claim 17 or 18,

wherein the water to be treated contains metal ions; and

wherein the system comprises, on a downstream side of the

second crystallizing section, a second precipitating section that precipitates at least one of calcium carbonate and a metal compound so that the concentration of at least one of the calcium carbonate and the metal ions in the second concentrated water is reduced.

{Claim 27}

The water treatment system according to claim 26, wherein at least one of seed crystals of the silica and a precipitant for the silica is supplied to the second precipitating section.

{Claim 28}

The water treatment system according to claim 25, wherein, when the water to be treated contains Mg ions, the amount of the precipitant for the silica to be supplied is adjusted according to the concentration of the Mg ions in the first precipitating section.

{Claim 29}

The water treatment system according to claim 27, wherein, when the water to be treated contains Mg ions, the amount of the precipitant for the silica to be supplied is adjusted according to the concentration of the Mg ions in the second precipitating section.

{Claim 30}

The water treatment system according to claim 24, wherein, when the water to be treated contains Mg ions,

the first concentrated water in the first precipitating section is adjusted to a pH at which a magnesium compound is deposited so that the concentration of the Mg ions is reduced, and

wherein, on a downstream side of the first precipitating section, the first concentrated water is adjusted to a pH at which the magnesium compound is soluble.

{Claim 31}

The water treatment system according to claim 26,

wherein, when the water to be treated contains Mg ions, the second concentrated water in the second precipitating section is adjusted to a pH at which a magnesium compound is deposited so that the concentration of the Mg ions is reduced, and

wherein, on a downstream side of the second precipitating section, the second concentrated water is adjusted to a pH at which the magnesium compound is soluble.

{Claim 32}

The water treatment system according to claim 22,

wherein, when the water to be treated contains Mg ions, the water to be treated in the first upstream side precipitating section is adjusted to a pH at which a magnesium compound is deposited so that the concentration of the Mg ions is reduced, and

wherein, on a downstream side of the first upstream side

precipitating section, the water to be treated is adjusted to a pH at which the magnesium compound is soluble.

{Claim 33}

The water treatment system according to claim 19, comprising, on a downstream side of the concentrated water in the downstream side demineralizing section, an evaporator that evaporates moisture from the concentrated water to recover the solids in the concentrated water.

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7



FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16

