



US008585741B2

(12) **United States Patent**
Gabelberger et al.

(10) **Patent No.:** **US 8,585,741 B2**
(45) **Date of Patent:** **Nov. 19, 2013**

(54) **CLAMPS USED FOR INTERCONNECTING A BONE ANCHOR TO A ROD**

(75) Inventors: **Josef Gabelberger**, West Chester, PA (US); **Edward McShane**, Collegeville, PA (US); **Daniel Vennard**, Clayton, DE (US); **Nicholas Angert**, Paoli, PA (US); **Barclay Davis**, Downingtown, PA (US); **Stefan Schwer**, Loerrach (DE); **Manuel Schaefer**, Muttentz (CH); **Lee-Ann Norman**, Havertown, PA (US); **Reto Halbeisen**, Laufen (CH); **Benno Niedermann**, Gallen (CH)

(73) Assignee: **DePuy Synthes Products, LLC**, Raynham, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 615 days.

(21) Appl. No.: **12/668,862**

(22) PCT Filed: **Jan. 25, 2008**

(86) PCT No.: **PCT/US2008/052046**

§ 371 (c)(1),
(2), (4) Date: **Jun. 28, 2010**

(87) PCT Pub. No.: **WO2009/011929**

PCT Pub. Date: **Jan. 22, 2009**

(65) **Prior Publication Data**

US 2010/0268279 A1 Oct. 21, 2010

Related U.S. Application Data

(60) Provisional application No. 60/950,809, filed on Jul. 19, 2007.

(30) **Foreign Application Priority Data**

Jul. 27, 2007 (WO) PCT/US2007/074633

(51) **Int. Cl.**
A61B 17/70 (2006.01)
A61B 17/58 (2006.01)

(52) **U.S. Cl.**
USPC **606/264**; 606/60

(58) **Field of Classification Search**
USPC 606/60, 250-260, 264-279, 300-309, 606/319-320, 328
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,047,029 A 9/1991 Aebi et al.
5,344,422 A 9/1994 Frigg

(Continued)

FOREIGN PATENT DOCUMENTS

AU 697705 3/1996
DE 9215561 U1 2/1993

(Continued)

OTHER PUBLICATIONS

USS Fracture System Technique Guide dated 2001.

Primary Examiner — Ellen C Hammond


Assistant Examiner — Jacqueline Johanas

(74) *Attorney, Agent, or Firm* — Woodcock Washburn LLP

(57) **ABSTRACT**

The present invention relates to a clamp, and, more particularly, to a clamp for securing the position of a bone anchor with respect to a longitudinal rod, preferably for use in the spine. The clamp may include a housing, a rod clamping assembly, and a bone anchor clamping assembly. The clamp preferably enables the longitudinal axis of the rod to be offset or laterally displaced from the longitudinal axis of the bone anchor. The rod clamping assembly and the bone anchor clamping assembly are preferably moveably coupled to the housing in order to provide increased flexibility to better accommodate the location and geometry of the longitudinal rod and to better accommodate bone positioning.

19 Claims, 32 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,487,744 A 1/1996 Howland
 5,498,262 A 3/1996 Bryan
 5,501,684 A 3/1996 Schlapfer et al.
 5,562,661 A 10/1996 Yoshimi et al.
 5,611,800 A 3/1997 Davis et al.
 5,613,968 A 3/1997 Lin
 5,624,441 A 4/1997 Sherman et al.
 5,667,506 A 9/1997 Sutterlin
 5,885,285 A 3/1999 Simonson
 5,938,663 A 8/1999 Petreto
 6,022,350 A 2/2000 Ganem
 6,030,388 A 2/2000 Yoshimi et al.
 6,146,383 A 11/2000 Studer et al.
 6,179,838 B1 1/2001 Fiz
 6,187,005 B1 2/2001 Brace et al.
 6,235,028 B1 5/2001 Brumfield et al.
 6,402,749 B1 6/2002 Ashman
 6,579,292 B2 6/2003 Taylor
 6,626,906 B1 9/2003 Young
 6,673,074 B2 1/2004 Shluzas
 6,676,661 B1 1/2004 Martin Benlloch et al.
 6,716,214 B1 4/2004 Jackson
 6,736,816 B2 5/2004 Ritland
 6,755,830 B2 6/2004 Minfelde et al.
 6,835,196 B2 12/2004 Biedermann et al.
 6,866,664 B2 3/2005 Schar et al.
 6,872,209 B2 3/2005 Morrison
 7,066,939 B2 6/2006 Taylor
 7,094,237 B2 8/2006 Gradel et al.
 7,104,992 B2 9/2006 Bailey
 7,166,109 B2 1/2007 Biedermann et al.
 7,186,255 B2* 3/2007 Baynham et al. 606/266
 7,211,087 B2 5/2007 Young
 7,270,665 B2 9/2007 Morrison et al.
 7,648,522 B2 1/2010 David
 7,651,516 B2 1/2010 Petit et al.
 7,678,112 B2* 3/2010 Rezach 606/60
 7,678,136 B2 3/2010 Doubler et al.
 7,704,270 B2 4/2010 De Coninck
 7,722,645 B2 5/2010 Bryan
 7,744,635 B2* 6/2010 Sweeney et al. 606/264
 7,753,940 B2 7/2010 Veldman et al.
 7,763,047 B2 7/2010 Ritland
 7,763,054 B2 7/2010 Clement et al.
 7,789,897 B2 9/2010 Sanders
 7,799,059 B2 9/2010 Kramer et al.
 7,819,902 B2 10/2010 Abdelgany et al.
 7,837,715 B2 11/2010 Petit et al.
 7,850,715 B2* 12/2010 Banouskou et al. 606/246
 7,850,716 B2 12/2010 Taylor
 7,850,719 B2 12/2010 Gournay et al.

7,896,902 B2* 3/2011 Jeon et al. 606/246
 8,021,398 B2* 9/2011 Sweeney et al. 606/269
 8,029,546 B2 10/2011 Capote et al.
 8,128,665 B2* 3/2012 Banouskou et al. 606/250
 8,262,702 B2* 9/2012 Giger et al. 606/252
 2004/0092930 A1 5/2004 Petit et al.
 2004/0153068 A1 8/2004 Janowski et al.
 2004/0254574 A1 12/2004 Morrison et al.
 2005/0070901 A1* 3/2005 David 606/61
 2005/0096654 A1 5/2005 Lin
 2005/0228382 A1 10/2005 Richelsof et al.
 2006/0036252 A1* 2/2006 Baynham et al. 606/73
 2006/0167455 A1 7/2006 Clement et al.
 2006/0206114 A1 9/2006 Ensign et al.
 2006/0241601 A1 10/2006 Trautwein et al.
 2006/0247624 A1 11/2006 Banouskou et al.
 2006/0253118 A1 11/2006 Bailey
 2007/0135817 A1 6/2007 Ensign
 2007/0161987 A1 7/2007 Capote et al.
 2007/0167946 A1* 7/2007 Triplett et al. 606/61
 2008/0167688 A1* 7/2008 Fauth et al. 606/265
 2009/0264926 A1 10/2009 Taylor et al.
 2009/0287253 A1* 11/2009 Felix et al. 606/278
 2009/0326585 A1 12/2009 Baccelli et al.
 2010/0049253 A1 2/2010 Miller
 2010/0063546 A1 3/2010 Miller
 2010/0094346 A1 4/2010 Matityahu
 2010/0168796 A1 7/2010 Eliassen et al.
 2010/0241171 A1 9/2010 Clement et al.
 2012/0303062 A1* 11/2012 Amstutz et al. 606/267

FOREIGN PATENT DOCUMENTS

EP 0814716 B1 1/1998
 EP 0938872 B1 9/1999
 EP 1196102 B1 4/2002
 EP 1330196 B1 7/2003
 EP 0814713 B1 4/2004
 EP 1635722 B1 3/2006
 EP 1708630 B1 11/2009
 JP 2004-512134 4/2004
 JP 2004-516040 6/2004
 WO WO 02/36026 5/2002
 WO WO 2005/020829 A1 3/2005
 WO WO 2007/022790 3/2007
 WO WO 2007/067443 6/2007
 WO WO 2007/070757 6/2007
 WO WO 2008/014477 1/2008
 WO WO 2009/133539 A1 11/2009
 WO WO 2010/103198 A1 9/2010
 WO WO 2010/150140 A1 12/2010
 WO WO 2011/012690 A1 2/2011

* cited by examiner




Fig.2

Fig.1




Fig.3






Fig.4






Fig.7




Fig.8




Fig.10




Fig.9




Fig.12




Fig.11




Fig.14




Fig.13




Fig.15




Fig.17

Fig.16




Fig.18




Fig.19




Fig.20




Fig.21






Fig.22








Fig. 27




Fig.28




Fig.29




Fig.30




Fig.31

200




Fig.32




Fig.33




Fig.34




Fig.35




Fig.36




Fig.36A




Fig.37




Fig.39

Fig.38






Fig.40








Fig.43






Fig.47




Fig.48




Fig.46




Fig.49




Fig.50






Fig. 51

Fig. 52

Fig. 53




Fig. 54




Fig. 55




Fig.56







Fig.57






Fig. 61




Fig. 62




Fig. 63




Fig. 64




Fig. 65

CLAMPS USED FOR INTERCONNECTING A BONE ANCHOR TO A ROD

CROSS REFERENCE TO RELATED APPLICATIONS

This application claims priority to U.S. provisional patent application Ser. No. 60/950,809, filed Jul. 19, 2007 and is a continuation-in-part of International patent application serial No. PCT/US2007/074633, filed Jul. 27, 2007. The content of these applications is hereby incorporated by reference in their entirety.

FIELD OF THE INVENTION

The present invention relates to a clamp, and, more particularly, to a clamp for securing the position of a bone anchor with respect to a longitudinal rod, preferably for use in the spine.

BACKGROUND OF THE INVENTION

Spinal fusion is a procedure that involves joining two or more adjacent vertebrae with a bone fixation device to restrict movement of the vertebra with respect to one another. Spinal fixation devices are used in spine surgery to align, stabilize and/or fix a desired relationship between adjacent vertebral bodies. Such devices typically include a spinal fixation element, such as, for example, a relatively rigid fixation rod, a dynamic or flexible spinal rod, etc. (collectively referred to herein as a longitudinal rod), that is coupled to adjacent vertebrae by attaching the spinal fixation element to various bone fixation elements, such as, for example, hooks, bolts, wires, screws, etc. (collectively referred to herein as a bone anchor). The bone anchor may commonly include heads with channels in which the longitudinal rod is inserted and subsequently clamped by a set screw or closure cap. Surgeons may commonly choose to install multiple bone anchors, as well as multiple longitudinal rods, to treat a given spinal disorder. The longitudinal rods may have a predetermined contour, and once installed, the longitudinal rod may hold the vertebrae in a desired spatial relationship, either until desired healing or spinal fusion has taken place, or for some longer period of time.

Surgeons have often encountered difficulty installing such devices because of trouble aligning the longitudinal rod(s) with the channels in the heads of the bone anchors. For example, the heads of bone anchors may often be out of vertical and/or horizontal alignment with one another because of the curvature of the spine or the size and shape of each vertebra.

The process of positioning and setting known bone anchors may be tedious and relatively time-consuming, typically requiring more than one surgical tool to clamp the longitudinal rods and the bone anchors in desired positions. Even with a high degree of skill and care, the process of positioning an assembly of known bone anchors and longitudinal rods, and clamping said bone anchors and longitudinal rods in place can take more time than desired during a surgical procedure, and may even result in longitudinal rods, bone anchors, or both moving out of position before clamping is completed.

Thus, it is desirable to have a spinal fixation device (also referred to herein as a clamp) that can secure longitudinal rods and bone anchors in place with a minimal amount of time and a minimal number of surgical tools. It is also desirable to have

a clamp that can secure a longitudinal rod at an axis that is offset or laterally displaced from the axis of the bone anchor.

SUMMARY OF THE INVENTION

The present invention relates to a clamp, and, more particularly, to a clamp for securing the position of a bone anchor with respect to a longitudinal rod in a posterior spinal fixation procedure. The clamp may include a housing, a rod clamping assembly, and a bone anchor clamping assembly. The clamp preferably enables the longitudinal axis of the rod to be offset or laterally displaced from the longitudinal axis of the bone anchor. The rod clamping assembly may be moveably associated, preferably slidably coupled, to the housing so that the rod clamping assembly may be moveable to provide increased flexibility to better accommodate the longitudinal rod or to better accommodate vertebrae positioning, and the bone anchor clamping assembly may be moveably associated, preferably pivotably coupled, to the housing so that the bone anchor clamping assembly can be moveable to provide increased flexibility to better accommodate the bone anchor. Alternatively and/or in addition, the bone anchor clamping assembly may be moveably associated, preferably slidably coupled, to the housing.

In one exemplary embodiment, the bone anchor may include a bone engaging portion and an extending portion. The clamp for securing the bone anchor with respect to a rod may include a housing having a first elongated opening sized and configured to receive at least a portion of the bone anchor, a second opening associated with the rod, and one or more slits in communication with the second opening, the slit dividing the housing into a first portion and a second portion so that the housing is elastically deflectable. The bone anchor clamping assembly may include a rotatable member; a slider member including a top surface, a bottom surface, and a bore extending from the top surface to the bottom surface, the slider member positioned between the rotatable member and the housing, the slider member translatable with respect to the housing; and a collet positioned at least partially within the first opening, the collet including a top portion, a bottom portion and a bore extending from the top portion to the bottom portion, the bore receiving at least a portion of the extending portion of the bone anchor, the bore including one or more threads for engaging the rotatable member, at least a portion of the collet extending through the bore of the slider member so that movement of the slider member with respect to the housing causes the collet and the bone anchor to move at least with respect to the housing. Preferably, the rod clamping assembly and the bone anchor clamping assembly are laterally spaced apart with respect to one another and are sized and configured so that rotation of the rotatable member fixes the position of the rod with respect to the housing and the position of the bone anchor with respect to the housing.

In use, rotation of the rotatable member to a locked position may cause a downward force onto the slider member, which in turn may cause the slider member to contact the housing and may cause the collet to move with respect to the housing, which in turn may cause the position of the slider member and the position of the bone anchor to be fixed with respect to the housing. In addition, rotation of the rotatable member to the locked position may cause the first and second portions of the housing to move with respect to one another which in turn may cause the slit formed in the housing to compress, thereby causing a diameter of the second opening formed in the housing to decrease so that the housing tightens around the rod thus fixing the position of the rod with respect to the housing.

The collet may include one or more slots extending upwards from the bottom portion of the collet, thereby defining one or more deflectable collet fingers. Preferably, the collet includes two slots and two collet fingers. The bottom portion of the collet may include a substantially curved outer surface for contacting a substantially corresponding internally curved surface formed in the first opening. The bore of the collet may be internally threaded so that the bone anchor can be threaded through the bore formed in the collet.

The slider member may be in the form of a plate-type member. In use, movement of the slider member generally parallel to a top surface of the housing may cause the bone anchor to angulate with respect to the housing.

The housing may include one or more upwardly projecting surfaces, preferably curved surfaces, extending from a top surface of the housing adjacent to the first opening.

The bone anchor clamping assembly may include a bushing, the bushing being polyaxially rotatable with respect to the housing.

In another exemplary embodiment, the bone anchor may include a bone engaging portion, an extending portion and an anchor axis, the bone engaging portion being sized and configured to be positioned at least partially within a bone. The clamp for securing the bone anchor to a rod may include a housing having a first opening and a second opening, the first opening being laterally spaced from the second opening, a bone anchor clamping assembly and a rod clamping assembly. The bone anchor clamping assembly may include a bore extending therethrough. The bone anchor clamping assembly is preferably positioned at least partially within the first opening formed in the housing and the extending portion of the bone anchor is preferably positioned at least partially within the bore of the bone anchor clamping assembly. The bone anchor is preferably polyaxially rotatable relative to the housing and the housing is preferably movable generally parallel to the anchor axis in an unlocked configuration. The bone anchor clamping assembly is preferably sized and configured to lock an angular orientation of the bone anchor relative to the housing and the position of the housing relative to the vertebra in a locked configuration. The rod clamping assembly is preferably positioned at least partially within the second opening. The rod clamping assembly is preferably sized and configured to engage the rod and is preferably movable within the second opening laterally relative to the first hole in a slack configuration, the rod clamping assembly locking the rod relative to the housing in a fastened configuration.

The bone anchor clamping assembly may include a bushing, a collet and a rotatable member. The bushing may include a top portion, a bottom portion, a bore extending from the top portion to the bottom portion and a plurality of slots extending upwards from the bottom portion of the bushing, thereby defining a plurality of deflectable bushing fingers. The collet may include a top portion, a bottom portion, a bore extending from the top portion to the bottom portion, and a plurality of slots extending upwards from the bottom portion, thereby defining a plurality of deflectable collet fingers. The collet is preferably at least partially received in the bore in the bushing. The bottom portion of the bushing may include a substantially spherical outer surface for contacting a substantially corresponding internal surface formed in the housing and defined by the first opening.

The first opening formed in the housing may include at least one protrusion and the bushing may include at least one recess, the at least one protrusion positioned within the at least one recess in the unlocked configuration to prevent rotation of the bushing with respect to the housing.

The bore formed in the bushing may include a narrower diameter portion and the collet may include a flared portion so that movement of the collet with respect to the bushing may cause the flared portion of the collet to contact the deflectable bushing fingers, thereby biasing the bushing fingers outward into contact with the first opening while simultaneously causing the deflectable collet fingers to be biased inwards against the extending portion of the bone anchor.

The bore formed in the collet may include a narrower portion having a smaller size than a size of the extending portion of the bone anchor so that insertion of the bone anchor into the bore formed in the collet causes the extending portion to frictionally couple the bone anchor to the collet.

Preferably, the anchor axis of the bone anchor and the longitudinal axis of the rod are spaced apart so that the anchor axis and the longitudinal axis do not intersect.

The housing may be in the form of a plate having a first portion and a second portion, the first opening being formed in the first portion and the second opening being formed in the second portion, the first portion may be angled with respect to the second portion.

The rod clamping assembly may include a gripping element having a lower portion and an upper portion, the lower portion receiving at least a portion of the rod in the slack and fastened configurations, the upper portion may be operably associated with the housing. Preferably, the upper portion of the gripping element is operably coupled to the housing via a second rotatable member. The upper portion of the gripping element may include a clip for preventing the second rotatable member from entering or exiting through the second opening.

In another exemplary embodiment, the bone anchor may include a bone engaging portion and an extending portion. The clamp for securing the bone anchor with respect to a rod may include a housing having a first opening, at least a portion of the bone anchor being received in the first opening. The housing may be integrally formed at an end of the rod. The bone anchor clamping assembly is preferably disposed at least partially within the first opening, at least a portion of the extending portion of the bone anchor being received within the bone anchor clamping assembly. The bone anchor clamping assembly may include a rotatable member whereby rotation of the rotatable member fixes the position of the bone anchor with respect to the housing.

In another exemplary embodiment, the bone anchor may include a bone engaging portion and an extending portion. The clamp for securing the bone anchor with respect to a rod may include a housing, a rod clamping assembly and a bone anchor clamping assembly. The housing may include a first opening sized and configured to receive at least a portion of the bone anchor, and a second opening sized and configured to receive at least a portion of the rod. The rod clamping assembly may be at least partially disposed within the second opening formed in the housing and may be sized and configured to at least partially contact the rod disposed therein. The bone anchor clamping assembly may be at least partially disposed within the first opening formed in the housing and may be sized and configured to receive at least a portion of the extending portion of the bone anchor. The rod clamping assembly and the bone anchor clamping assembly are preferably laterally spaced apart with respect to one another and the bone anchor clamping assembly may include a rotatable member whereby rotation of the rotatable member fixes the position of the rod with respect to the housing and the position of the bone anchor with respect to the housing.

The housing may also include one or more slits formed therein, the slit being in communication with the second

5

opening, the slit dividing the housing into a first portion and a second portion so that the housing is elastically deflectable.

The bone anchor clamping assembly may include a slider member and a collet, the slider member being sized and configured to reside between the rotatable member and the housing. The collet being sized and configured to partially fit inside the first opening formed in the housing, the collet including a top portion, a bottom portion, a bore extending from the top portion to the bottom portion, the bore being sized and configured to receive at least a portion of the bone anchor, and one or more slots extending upwards from the bottom portion of the collet thereby defining one or more deflectable collet fingers, the collet also including one or more threads for engaging the rotatable member. The bottom portion of the collet may include a substantially curved outer surface for contacting a substantially corresponding internal surface formed in the first opening formed in the housing so that the collet can move with respect to the housing. The collet preferably includes two slots forming two deflectable collet fingers. The bore formed in the collet may include an internal threading, the internal threading being sized and configured to match the threading formed on the bone engaging portion of the bone anchor so that the bone anchor can be threaded through the bore formed in the collet.

The slider member may be in the form of a plate-type member sized and configured to translate with respect to the housing. The slider member may include a top surface, a bottom surface, and a bore extending from the top surface to the bottom surface. The bore formed in the slider member may be sized and configured to receive at least a portion of the collet such that movement of the slider member causes movement of the collet.

The first opening formed in the housing may be in the form of an elongated slot.

The housing may include one or more upwardly projecting ridges or curved surfaces extending from the top surface of the housing adjacent to the first opening. Preferably, the housing includes at least two upwardly protruding ridges or curved surfaces, one on either side of the first opening. The upwardly projecting ridges or curved surfaces being sized and configured to contact the slider member so that movement of the slider member with respect to the housing causes the slider member, and hence the collet and bone anchor located partially therein, to pivot with respect to the housing.

In use, rotation of the rotatable member preferably causes a downward force onto the slider member, which in turn causes the slider member to contact the housing and causes the collet to move with respect to the housing, which in turn causes the position of the slider member and the position of the bone anchor to be fixed with respect to the housing. Rotation of the rotatable member preferably also causes the first and second portions of the housing to move with respect to one another which in turn causes the slit formed in the housing to compress thereby causing the second opening formed in the housing to decrease so that the housing tightens around the rod thus fixing the position of the rod with respect to the housing.

In another exemplary embodiment, the bone anchor may include a bone engaging portion and an extending portion. The clamp for securing the bone anchor with respect to a rod may include a housing, a bone anchor clamping assembly and a rod clamping assembly. The housing may include a top surface, a bottom surface, a first opening and a second opening, the first and second openings each extending from the top surface to the bottom surface. The bone anchor clamping assembly may include a bushing, a collet and a rotatable member. The bushing may include a top portion, a bottom

6

portion, a bore extending from the top portion to the bottom portion, a plurality of slots extending upwards from the bottom portion of the bushing thereby defining a plurality of deflectable bushing fingers, and one or more threads. The collet may be sized and configured to be at least partially received in the bore formed in the bushing. The collet may include a top portion, a bottom portion, a bore extending from the top portion to the bottom portion, a plurality of slots extending upwards from the bottom portion thereby defining a plurality of deflectable collet fingers, and one or more threads. The rod clamping assembly may include a gripping element. The gripping element may include a lower portion and an upper portion, the lower portion being sized and configured to receive at least some portion of the rod. The upper portion of the gripping element is preferably operably associated with the housing. The first opening formed in the housing is preferably sized and configured to receive at least a portion of the extending portion of the bone anchor, at least a portion of the bushing, and at least a portion of the collet. The rotatable member may include one or more inner threads and one or more outer threads, the inner threads being sized and configured to engage the threads formed on the collet while the outer threads are sized and configured to engage the threads formed on the bushing so that rotation of the rotatable member causes the collet to move with respect to the bushing, which in turn causes the position of the bone anchor to be fixed with respect to the housing.

The bottom portion of the bushing preferably includes a substantially spherical outer surface for contacting a substantially corresponding internal surface formed in the housing by the first opening so that the bushing can polyaxially angulate with respect to the housing.

The bushing is preferably structured and configured so that it is inhibited from rotating with respect to the housing about a longitudinal axis of the first opening. For example, the first opening may include at least one protrusion and the bushing may include at least one recess, the at least one recess being sized and configured to receive the at least one protrusion to prevent rotation of the bushing with respect to the housing.

The bore formed in the bushing may include a narrower diameter portion and the collet may include a flared portion so that movement of the collet with respect to the bushing causes the flared portion of the collet to contact the deflectable bushing fingers thereby biasing the bushing fingers outward into contact with the first opening while simultaneously causing the deflectable collet fingers to be biased inwards against the extending portion of the bone anchor.

The bore formed in the collet may include a narrower portion having a smaller size than a size of the extending portion of the bone anchor so that insertion of the bone anchor into the bore formed in the collet causes the extending portion to frictionally couple the bone anchor to the collet.

The second opening formed in the housing may be in the form of an elongated slot so that the position of the gripping element can be adjustable with respect to the housing. Preferably, the gripping element is slidably adjustable with respect to the housing so that the position of the rod is adjustable with respect to the position of the bone anchor. The upper portion of the gripping element preferably is operably coupled to the housing via a second rotatable member. Rotation of the second rotatable member preferably causes the lower portion of the gripping element to wedge the rod against the housing thereby fixing the position of the rod with respect to the housing. The upper portion of the gripping element may include a clip for preventing the rotatable member from passing through the second opening.

The housing may be in the form of a plate having a first portion and a second portion, the first opening being formed in the first portion while the second opening is formed in the second portion, the first portion being angled with respect to the second portion.

BRIEF DESCRIPTION OF THE DRAWINGS

The system is explained in even greater detail in the following exemplary drawings. The drawings are merely exemplary to illustrate the structure of preferred devices and certain features that may be used singularly or in combination with other features. The claims should not be limited to the embodiments shown.

FIG. 1 is a perspective view of an exemplary embodiment of a clamp;

FIG. 2 is a side view of the clamp of FIG. 1;

FIG. 3 is a cross-sectional view of the clamp of FIG. 1 in a first position;

FIG. 4 is cross-sectional view of the clamp of FIG. 1 in a second position;

FIG. 5 is a cross-sectional view of an exemplary embodiment of a rod clamping assembly that may be used in connection with the clamp of FIG. 1;

FIG. 6 is a cross-sectional view of an alternative exemplary embodiment of the rod clamping assembly;

FIG. 7 is an alternate side view of the clamp shown in FIG. 1;

FIG. 8 is a lateral view of the clamp shown in FIG. 1;

FIG. 9 is a cross-sectional perspective view of an exemplary embodiment of a bone anchor clamping assembly that may be used in connection with the clamp of FIG. 1;

FIG. 10 is an enlarged cross-sectional view of the bone anchor clamping assembly of FIG. 9;

FIG. 11 is a perspective view of an exemplary embodiment of the first throughbore formed in the housing that may be used in connection with the clamp of FIG. 1;

FIG. 12 is a bottom view of an exemplary embodiment of the housing and bone anchor clamping assembly that may be used in connection with the clamp of FIG. 1;

FIG. 13 is a cross-sectional view of an exemplary embodiment of a bone anchor clamping assembly and a bone anchor that may be used in connection with the clamp of FIG. 1, in a first position;

FIG. 14 is a cross-sectional view of the bone anchor clamping assembly and bone anchor in a second position;

FIG. 15 is a perspective view of an optional exemplary embodiment of an assembly mechanism formed on the bone anchor clamping assembly;

FIG. 16 is a perspective view of an alternate exemplary embodiment of a clamp;

FIG. 17 is another perspective view of the clamp shown in FIG. 16;

FIG. 18 is a side view of an exemplary embodiment of a housing that may be used in connection with the clamp shown in FIG. 16;

FIG. 19 is a perspective view of the housing shown in FIG. 18;

FIG. 20 is a lateral view of the housing shown in FIG. 18;

FIG. 21 is a perspective view of an exemplary embodiment of a collet that may be used in connection with the clamp shown in FIG. 16;

FIG. 22 is a cross-sectional view of the collet shown in FIG. 21;

FIG. 23 is a perspective view of alternate exemplary embodiment of a clamp;

FIG. 24 is another perspective view of the clamp shown in FIG. 23;

FIG. 25 shows an exemplary embodiment of a flexible guide wire and a guide wire holder which may be used in connection with implantation of a clamp;

FIG. 26 shows an exemplary embodiment of a clamp insertion instrument which may be used in connection with implantation of a clamp;

FIGS. 27-35 show an exemplary procedure for implanting a clamp;

FIG. 36 is an alternate exemplary embodiment of a clamp;

FIG. 36a is an exemplary embodiment of a set screw or nut incorporating concentric ridges which may be used in connection with one of the clamps;

FIG. 37 is an alternate exemplary embodiment of a clamp;

FIG. 38 is a side view of the clamp shown in FIG. 37;

FIG. 39 is a cross-sectional view of the clamp shown in FIG. 37;

FIG. 40 is an alternate exemplary embodiment of a clamp;

FIG. 41 is an alternate exemplary embodiment of a clamp;

FIG. 42 is a perspective view of the clamp shown in FIG. 41;

FIG. 43 is an alternate exemplary embodiment of a clamp;

FIG. 44 is a side view of the clamp shown in FIG. 43;

FIG. 45 is a lateral view of the clamp shown in FIG. 43;

FIG. 46 is a perspective view of an optional retention clip which may be used in connection with one of the clamps;

FIG. 47 is a perspective view of an exemplary embodiment of a bone anchor incorporating the retention clip of FIG. 46;

FIG. 48 is an alternate perspective view of the bone anchor of FIG. 47;

FIG. 49 is an alternate view of the retention clip of FIG. 46;

FIG. 50 is an alternate view of the retention clip of FIG. 46;

FIGS. 51-57 depict various views of an exemplary clamp insertion instrument that may be used for implanting a bone anchor and clamp;

FIGS. 58-64 depict various views of an alternate exemplary clamp insertion instrument that may be used for implanting a clamp; and

FIG. 65 depicts an alternate exemplary embodiment of an alternate drive/guide member that may be used in connection with implanting a clamp.

DETAILED DESCRIPTION

Certain exemplary embodiments will now be described with reference to the drawings. In general, such embodiments relate to a clamp, by way of non-limiting example, a clamp for use in securing a bone anchor, and hence a bone (preferably a vertebra), with respect to a longitudinal rod (preferably a spinal rod). The clamp may include a housing, a rod clamping assembly, and a bone anchor clamping assembly. The clamp preferably enables the longitudinal axis of the rod to be offset or laterally displaced from the longitudinal axis of the bone anchor such that the longitudinal rod may be secured at a position laterally offset or displaced from the bone anchor. The rod clamping assembly may include a first position (e.g., a slack configuration) and a second position (e.g., a fastened configuration) wherein, when in the first position, the rod is moveable with respect to the clamp and, when in the second position, the position of the rod is fixed with respect to the clamp. That is, the rod clamping assembly may be moveably associated, preferably slidably coupled, to the housing so that the rod clamping assembly may be moveable to provide increased flexibility to better accommodate the longitudinal rod or to better accommodate vertebrae positioning. The bone anchor clamping assembly may include a first position (e.g.,

an unlocked configuration) and a second position (e.g., a locked configuration) wherein, when in the first position, the bone anchor is moveable with respect to the clamp and, when in the second position, the position of the bone anchor is fixed with respect to the clamp. That is, the bone anchor clamping assembly may be moveably associated, preferably pivotably coupled, to the housing so that the bone anchor clamping assembly can be moveable to provide increased flexibility to better accommodate the bone anchor. That is, the longitudinal axis of the bone anchor may be spaced apart from the longitudinal axis of the rod by a distance X. More preferably, the distance X is adjustable. Preferably, the distance X may be adjustable from about 7.0 mm to about 40 mm, more preferably about 10 mm to about 25 mm. However, other ranges are contemplated.

The invention may have other applications and uses and should not be limited to the structure or use described and illustrated. That is, while the clamp will be described as and may generally be used in the spine (for example, in the lumbar, thoracic or cervical regions), those skilled in the art will appreciate that the clamp may also be used for fixation of other parts of the body such as, for example, joints, long bones or bones in the hand, face, feet, maxiofacial region, mandible, etc. In addition, the clamp may be used in the external fixation of the body such as, for example, where rods are joined outside of the patient's body along, for example, the patient's long bones, spine, etc. The clamp may also be used to connect proximal or distal extensions to a rib hook in an expandable prosthetic rib, as a clamping assembly/mechanism for a transconnector (e.g., a device that connects two rods with one another during spinal surgery), to connect and secure the pieces of a retractor system, or to attach components, for example, retractor systems to a surgical table. The clamp may be constructed from any biocompatible material known in the art including, but not limited to, stainless steel, titanium, titanium alloys, polymers, etc.

Referring to FIGS. 1-4, the clamp 10 may include a housing (shown and described as a plate) 12, a rod clamping assembly 30 and a bone anchoring clamping assembly 50 for interconnecting a bone anchor 6, and hence a bone (preferably a vertebra), to a longitudinal rod 4 (preferably a spinal rod).

As generally understood by one of ordinary skill in the art, it should be understood that the longitudinal rod 4 may include, but not be limited to, a solid rod, a non-solid rod, a flexible or dynamic rod, a plate including one or more holes, etc. It should be understood that the clamp 10 is not limited in use to any particular type of longitudinal rod 4.

The bone anchor 6 may include a bone engaging portion 6a, an extending or shaft portion 6b, and a longitudinal anchor axis 6c. As shown, the bone engaging portion 6a may include threads 7 for threadably engaging the targeted vertebra. As generally known by one of ordinary skill in the art, the bone engaging portion 6a may be in other forms, such as, for example, a hook, a pin with or without barbs, a nail, a helical nail, an implant, a wire, etc. It should be understood that the clamp 10 is not limited in use to any particular type of bone anchor 6.

The housing 12 may include a first portion 13 and a second portion 14. As shown, the first portion 13 may be angulated with respect to the second portion 14. The housing 12 may also include a top surface 15, a bottom surface 16, a first throughbore 17 and a second throughbore 18. Although the first throughbore is generally shown and described as having a generally circular shape and the second throughbore is generally shown and described as being an elongated slot, the

throughbores may have the same shape and may be in the form of any other shape including, but not limited to, C-shape, hook shape, etc.

The first throughbore 17 may be formed in either the first portion 13 or the second portion 14 (shown here as the first portion 13). The first throughbore 17 is preferably sized and configured to receive at least some portion of the shaft portion 6b of the bone anchor 6. Moreover, the first throughbore 17 may also be sized and configured to receive at least some portion of the bone anchor clamping assembly 50. Preferably, the first throughbore 17 has an internal shape that is sized and configured to substantially match the external shape of the bone anchor clamping assembly 50, more preferably the bushing, as will be described in greater detail below.

The second throughbore 18 preferably is formed in the other of the first portion 13 or the second portion 14 (shown here as the second portion 14). Moreover, the second throughbore 18 may be sized and configured to receive at least some portion of the rod clamping assembly 30, as will be described in greater detail below. Preferably, the second throughbore 18 is in the form of an elongated slot so that the position of the rod clamping assembly 30 can be varied with respect to the housing 12, as will be described in greater detail below.

As shown in FIGS. 5 and 6, the rod clamping assembly 30 may include a gripping element 32, the gripping element 32 may include a lower portion 33 and an upper portion 34. The upper portion 34 of the gripping element 32 is preferably coupled to the housing 12. More preferably, the upper portion 34 is moveably received within the second throughbore 18, which is preferably in the form of a slot, and coupled to the housing 12 via a nut 40, as will be described in greater detail below, so that the position of the gripping element 32 is moveable with respect to the housing 12 until the nut 40 is tightened. That is, preferably, the rod clamping assembly 30 has a slack or first configuration and a fastened or second configuration wherein, when in the slack or first configuration, the rod clamping assembly 30 is moveably associated with respect to the housing 10, while, when in the fastened or second configuration, the position of the rod clamping assembly 30 is fixed with respect to the housing 10.

The lower portion 33 is preferably sized and configured to receive at least some portion of the longitudinal rod 4, and may be shaped as a hook, loop, or any other shape. Preferably, the gripping elements 32 are sized and configured to be interchangeable with the clamp 10 so that, for example, the user can select between the hook shaped gripping element (shown in FIG. 5) and the loop shaped gripping element (shown in FIG. 6) as required. It should be understood however that the clamp 10 should not be limited by the shape of the gripping element 32.

The lower portion 33 of the gripping element 32 is preferably designed to extend below the bottom surface 16 of the housing 12 so that the longitudinal rod 4 may be received between the gripping element 32 and the housing 12. As shown, the upper portion 34 of the gripping element 32 may include an engagement portion 35. As shown, the engagement portion 35 preferably includes one or more threads for threadably engaging the nut 40. As shown, the engagement portion 35 may include an internally threaded portion sized and configured to engage a threaded outer portion formed on the nut 40.

The nut 40 may also include a rim 44, at least a portion of the rim 44 preferably being sized and configured to be larger than the second throughbore 18 so that the rim 44 acts as a stop to prevent the nut 40 from passing completely through the second throughbore 18. Moreover, the nut 40 may also include a notch (not shown), the notch being sized and con-

11

figured to receive a clip (not shown). Preferably, the clip is sized and configured to prevent the nut **40** from passing through the second throughbore **18** via the upper surface **15** of the housing **12**. Thus, preferably, once assembled, the nut **40** and the gripping element **32**, which is threadably engaged thereto, is prevented via the rim **44** and the clip from becoming disassembled from the housing **12**. Alternatively, any other mechanism known in the art for preventing the nut **40** and gripping element **32** from becoming disassembled from the housing **12** may be used including, but not limited to, dowel pins, splaying, welding, thread staking, etc.

In use, rotation of the nut **40** causes the rod clamping assembly **30** to move from the slack or first configuration to the fastened or second configuration. That is, in use, rotation of the nut **40** causes the nut **40** to engage the gripping element **32**, which in turn causes the lower portion **33** of the gripping element **32**, and hence the longitudinal rod **4**, to move upwards until the rod **4** contacts the housing **12**. At this point, the longitudinal rod **4** is wedged between the bottom surface **16** of the housing **12** and the gripping element **32** thereby fixing the position of the rod **4** with respect to the housing **12**. In addition, rotation of the nut **40** causes the housing **12** to be wedged between the gripping element **32** and the nut **40** thereby fixing the position of the gripping element **32** with respect to the housing **12**.

As best shown in FIG. 7, the bone anchor clamping assembly **50** may include a bushing **60**, a collet **70** and a nut **80** wherein the bushing **60** is preferably sized and configured to be at least partially received within the first throughbore **17** formed in the housing **12**, and the collet **70** is preferably sized and configured to be at least partially received in the bore **66** of the bushing **60** and to partially receive at least some portion of the shaft portion **6b** of the bone anchor **6**, as will be described in greater detail below.

The collet **70** may include a top portion **72**, a bottom portion **74**, and a bore **76** extending from the top portion **72** to the bottom portion **74**. Preferably, the top portion **72** includes one or more threads **73** for engaging the nut **80**, as will be discussed in greater detail below. Preferably, the bottom portion **74** includes an enlarged portion **75** such as, for example, a flared end portion. The collet **70** preferably also includes one or more longitudinal slots **78** (as best shown in FIG. 10) extending upwards from the bottom portion **74**, thereby creating a plurality of deflectable fingers **79**.

Additionally, the bore **76** formed in the collet **70** may include a narrower diameter portion (e.g., a shoulder, a tapered portion, etc.) (not shown). The narrower diameter portion may be located anywhere along the length of the bore **76**. The narrower diameter portion may have an internal diameter smaller than the outer diameter of the shaft portion **6b** of the bone anchor **6** so that insertion of the bone anchor **6** into the bore **76** formed in the collet **70** may cause the shaft portion **6b** to frictionally contact the fingers **79** so that the collet **70** is frictionally coupled to the bone anchor **6**. Thus, the collet **70** and bone anchor **6** are preferably prevented from becoming accidentally disassembled.

As best shown in FIG. 7, the bushing **60** may include a top portion **62**, a bottom portion **64**, and a bore **66** extending from the top portion **62** to the bottom portion **64**. Preferably, the top portion **62** includes one or more threads **63** for threadably engaging the nut **80**, as will be discussed in greater detail below.

The bottom portion **64** of the bushing **60** preferably includes a substantially spherical outer shape. As previously mentioned, the shape of the bottom portion **64** of the bushing **60** is preferably sized and configured to substantially match the shape of the first throughbore **17** formed in the housing **12**.

12

Thus, as shown, the spherically outer surface of the bushing **60** preferably facilitates polyaxially angulation of the bushing **60** with respect to the housing **12**, which in turn facilitates polyaxial angulation of the bone anchor **6** with respect to the housing **12** so that the longitudinal anchor axis **6c** of the bone anchor **6** can be adjusted.

The bushing **60** is preferably sized and configured so that the bushing **60** is capable of polyaxial angulation with respect to the housing **12** without causing the bushing **60** to rotate about an axis parallel to the longitudinal axis of the bone anchor **6**. For example, referring to FIGS. 11, 12 and 15, preferably the first throughbore **17** formed in the housing **12** includes one or more protrusions **82** and the bushing **60** includes one or more recesses **84**, the recesses **84** being sized and configured to receive the protrusions **82**. In this fashion, the bushing **60** is prevented from rotating about an axis parallel to the anchor axis **6c** of the bone anchor **6** but is permitted to angulate with respect to the housing **12**. Alternatively, the bushing **60** may include one or more projections while the housing **12** includes one or more recesses. Other ways of preventing the bushing **60** from rotating about an axis through its bore **66** are contemplated including, but not limited to, one or more dowel pins or setscrews mating with one or more recesses formed on the bushing.

Referring to FIGS. 8 and 10, the bushing **60** preferably also includes one or more longitudinal slots **68** extending upwards from the bottom portion **64** of the bushing **60**, thereby creating a plurality of deflectable fingers **69**. In use, the bore **66** formed in the bushing **60** may also include a narrower diameter portion **67** so that movement of the collet **70** with respect to the bushing **60** causes the enlarged bottom portion **74** of the collet **70** to contact the fingers **69** of the bushing **60** thereby biasing the fingers **69** formed on the bushing **60** outwards while preferably causing the fingers **79** formed on the collet **70** to be biased inwards against the shaft portion **6b** of the bone anchor **6**.

In use, the bone anchor clamping assembly **50** preferably has an unlocked or first configuration and a locked or second configuration wherein, when in the unlocked or first configuration, the bone anchor **6** is moveably associated with respect to the housing **12**, while, when in the locked or second configuration, the position of the bone anchor **6** is fixed with respect to the housing **12**. Preferably, when in the unlocked or first configuration, the bone anchor **6** is capable of polyaxially rotating with respect to the housing **12** and/or the housing **12** is capable of moving along the axis of the bone anchor **6** (e.g. the housing **12** can move generally parallel to the anchor axis **6c**) so that the distance between the housing **12** and the bone can be adjusted.

Referring to FIGS. 13 and 14, the nut **80** preferably includes a set of inner threads **81a** and a set of outer threads **81b**. The inner threads **81a** formed on the nut **80** being sized and configured to engage the threads **73** formed on the collet **70** while the outer threads **81b** formed on the nut **80** are sized and configured to engage the threads **63** formed on the bushing **60**. In use, rotation of the nut **80** preferably causes the bone anchor clamping assembly **50** to move from the unlocked configuration to the locked configuration. That is, in use, rotation of the nut **80** preferably causes the collet **70** to move with respect to the bushing **60**. Consequently, rotation of the nut **80** causes the enlarged bottom portion **75** of the collet **70** (as shown in FIG. 10) to become biased against both the shaft portion **6b** of the bone anchor **6** and the deflectable fingers **69** of the bushing **60**, which in turn causes the position of the bone anchor **6** to be fixed with respect to the collet **70** and the position of the collet **70** to be fixed with respect to the bushing **60**. In addition, rotation of the nut **80** causes the

13

fingers 69 formed on the bushing 60 to be biased against the first throughbore 17 formed in the housing 12 which in turn causes the position of the bushing 60, and hence the position of the collet 70 and bone anchor 6, to be fixed with respect to the housing 12.

Referring to FIG. 15, the collet 70 may also include one or more cutouts 85 formed in one or more of the fingers 79, the cutouts 85 being sized and configured to engage the tips formed on an insertion instrument so that the fingers 79 can be squeezed together and rotated thus facilitating insertion and removal of the collet 70 from the bushing 12.

In use, the clamp 10 preferably enables the position of the rod clamping assembly 30 to be moveably coupled, and more preferably slidably adjustable, with respect to the housing 12, and hence with respect to the bone anchor 6 secured thereto. Slidable adjustment of the rod clamping assembly 30 enables the position of the longitudinal rod 4 to be adjustable with respect to the position of the bone anchor 6. The position of the rod clamping assembly 30 and hence of the longitudinal rod 4 may be fixed with respect to the housing 12 by rotation of the nut 40. In addition, the clamp 10 enables the bone anchor 6 to angulate with respect to the housing 12 via the bone anchor clamping assembly 50. Moreover, the clamp 10 may also enable the position of the housing 12 to be vertically adjustable along the length of the shaft portion 6b of the bone anchor 6, which enables the user to adjust the height of the housing 12 with respect to bone anchor 6. The position of the bone anchor 6 may be fixed with respect to the housing 12 by rotation of nut 80.

Referring to FIGS. 16 and 17, an alternative exemplary embodiment of a clamp is shown. The clamp 100 may include a housing 110, a rod clamping assembly 130 and a bone anchor clamping assembly 150 for interconnecting a bone anchor 6, and hence a bone, to a longitudinal rod 4 or plate. In this embodiment, the rod clamping assembly 130 may be in the form of an elastically deflectable housing 110, as will be described in greater detail below. The bone anchor clamping assembly 150 may include a collet 160, a slider member 170, and a nut 180.

As best shown in FIGS. 18-20, the housing 110 may include a first side 111, a second side 112, a third side 113, a fourth side 114, a top surface 115 and a bottom surface 116 so that housing 110 may be generally in the form of a rectangular body. However, those skilled in the art will recognize that the housing 110 may be in the form of any number of shapes including, but not limited to, square, ellipsoid, spherical, etc. It should be understood the clamp 100 is not to be limited by the shape of the housing 110.

The housing 110 may also include a first throughbore 117 and a second throughbore 118. The second throughbore 118 may be sized and configured to receive at least some portion of the longitudinal rod 4. The axis of the first throughbore 117 is preferably perpendicular to the axis of the second throughbore 118 although other angles are contemplated. The second throughbore 118 may include a plurality of serrations 119 for contacting the outer surface of the longitudinal rod 4. As will be generally appreciated by one of ordinary skill in the art, incorporation of the serrations 119 increases the frictional contact between the longitudinal rod 4 and the housing 110 thus improving the rod push-through strength. The second throughbore 118 may be any length and any shape, but is preferably sized and configured to match the size and shape of the longitudinal rod 4. The serrations 119 may be any shape, size, depth, etc. The serrations 119 may further be teeth or any other structural element that increases rod push-through strength.

14

The housing 110 may also include one or more slits 120. As shown, the slit 120 preferably extends from one of the top surface 115, the bottom surface 116, or one of the sides 111, 112, 113, 114 thereof through to and in communication with the second throughbore 118. More preferably, the slit 120 may extend from two or more surfaces or sides of the housing 110 (shown as top surface 115 and sides 113 and 114) so that the housing 110 is divided into a first portion 122 and a second portion 124, the first and second portions 122, 124 being coupled together at one end thereof (shown as first 111). As will generally be appreciated by one of ordinary skill in the art, incorporation of the slit 120 enables the first and second portions 122, 124 of the housing 110 to move or deflect with respect to one another and enables the second throughbore 118 to be elastically deflectable. This, in turn, facilitates easier insertion of the longitudinal rod 4 into the second throughbore 118 and facilitates fixing the position of the rod 4 with respect to the housing 110, as will be described in greater detail below. It should be understood that the slit 120 may be any size and shape. By way of non-limiting example, the slit 120 may be tapered, straight, zigzag, etc. Preferably, the slit 120 is angled with respect to the horizontal plane of the housing 110. More preferably, the slit 120 is angled at an angle of about 45 degrees with respect to the horizontal plane of the housing 110, although other degrees are contemplated. The slit 120 may further incorporate one or more elastic elements such as springs or flexible materials such as rubber, PCU, etc.

The housing 110 may also include one or more recesses 126 for receiving a projection formed on a tool in order to facilitate handling of the clamp 100. It should be noted that the recess 126 may take on any shape necessary for mating with the tool. Alternatively, the housing 110 may include one or more projections for mating with one or more recesses formed on the tool.

As previously mentioned, the housing 110 also preferably includes a first throughbore 117 sized and configured to receive at least a portion of the bone anchor clamping assembly 150, and hence at least a portion of the bone anchor 6, as will be described in greater detail below. The first throughbore 117 preferably extends from the top surface 115 to the bottom surface 116 of the housing 110. The first throughbore 117 preferably is in the form of an elongated slot 117a, at least when viewed from above. The housing 110 may also include one or more upwardly projecting ridges 132 extending from the top surface 115 of the housing 110 adjacent to the first throughbore 117. The ridges 132 preferably include a plurality of serrations 133 formed thereon. Preferably, as shown, the housing 110 includes at least two upwardly protruding ridges 132, one on either side of the first throughbore 117. The ridges 132 preferably incorporate a convex upper surface for reasons that will become apparent below. The radius of curvature for the upwardly protruding ridges 132 may be between about 5 mm and about 15 mm, although any other radius may be used.

It should be understood that the first throughbore 117 may be any size and shape including, but not limited to square, hexagonal, polygonal, oval, etc. It should be further understood that the ridges 132 may project to any extent, if at all, and may have other shapes.

The first throughbore 117 may include top and bottom portions (not shown). The top portion of the first throughbore 117 may have a uniform width. The bottom portion of the first throughbore 117 may have a shape corresponding to the outer shape of the bone anchor clamping assembly 150, and in particular, to the outer shape of the collet 160. For example, the bottom portion of the first throughbore 117 may have a bell-shaped contour for contacting the corresponding shaped

15

outer surface of the bone anchor clamping assembly **150**. The first throughbore **117** may also include a narrower diameter portion (e.g., shoulder, tapered surface, etc.) It should be understood however that first throughbore **117** may have any size and shape including, but not limited to square, cylindrical, conical, etc.

As previously mentioned, the bone anchor clamping assembly **150** may include collet **160**, slider member **170**, and nut **180**. As best shown in FIGS. **21** and **22**, the collet **160** may include a top portion **161**, a bottom portion **162**, and a bore **163** extending from the top portion **161** to the bottom portion **162**. In use, the collet **160** is sized and configured to be at least partially received inside of the first throughbore **117** formed in the housing **110**. Preferably, the top portion **161** includes one or more threads **166** for engaging the nut **180**, as will be discussed in greater detail below. Preferably, the bottom portion **162** includes an enlarged portion **162a** such as, for example, a flared end portion or a lip so that at least a portion of the outer diameter of the collet **160** and the flared end portion is greater than at least a portion of the width of the first throughbore **117**, preferably the narrower diameter portion. The collet **160** preferably also includes one or more longitudinal slots **164** extending upwards from the bottom portion **162** thereof thereby creating a plurality of deflectable fingers **165**. More preferably, the bottom portion **162** of the collet **160** includes two slots **164** so that the collet **160** includes two deflectable fingers **165**. Incorporation of two deflectable fingers **165**, versus a larger number of deflectable fingers, increases the required torque to failure of the collet **160**. Moreover, incorporation of two deflectable fingers **165** produces increased clamping action and minimizes size. It should be understood however that any number of slots **164**, and hence deflectable fingers **165**, may be used.

As best shown in FIG. **22**, the bore **163** formed in the collet **160** may include a threading **167** formed therein. The threading **167** is preferably sized and configured to match the threads **7** formed on the bone engaging portion **6a** of the bone anchor **6** so that the bone anchor **6** can be threaded through the bore **163** formed in the collet **160**, thus enabling the clamp **100** to be inserted into the body of a patient prior to the implantation of the bone anchor **6**.

The collet **160** is preferably long enough to allow at least a portion of the threads **166** formed on the top portion **161** of the collet **160** to extend beyond the opposing ridges **132** formed on the housing **110** while permitting the flared end portion **162a** formed on the bottom portion **162** of the collet **160** to contact the first throughbore **117** formed in the housing **110** as the collet **160** is being moved with respect to the housing **110**, as will be described in greater detail below. It should be understood however that the clamp **100** should not be limited by the length of the collet **160**, and in other embodiments it is envisioned that the top portion **161** of the collet **160** does not extend beyond the top surface **115** of the housing **110**, as the nut **180** may be configured, for example, to be inserted into the first throughbore **117** to contact the collet **160**.

The collet **160** may be any size or shape including, but is not limited to, cylindrical, cone, parallelepiped, etc. The collet **160** may further include features for mating with a tool such as, for example, flattened areas, depressions, or any other structural element(s).

As previously mentioned, the bone anchor clamping assembly **150** may also include a slider member **170**. As best shown in FIG. **17**, the slider member **170** may be in the form of a plate **171**, the plate **171** being sized and configured to reside between the nut **180** and the housing **110**, and more preferably, between the nut **180** and the opposing convex ridges **132** formed on the top surface **115** of the housing **110**.

16

The slider member **170** may have a top surface, a bottom surface, and a bore **177** extending from the top surface to the bottom surface. The bottom surface of the slider member **170** preferably includes a plurality of serrations (not shown) for contacting the corresponding serrations **133** formed on the ridges **132** of the housing **110**. In use, the slider member **170** is preferably sized and configured to fit on and translate across the ridges **132** of the housing **110**. The corresponding serrations formed on the ridges **132** of the housing **112** and the slider member **170** facilitating securement of the slider member **170** with respect to the housing **110**, as will be described in greater detail below.

The bore **177** formed in the slider member **170** is preferably sized and configured to receive at least a portion of the collet **160** such that movement and/or translation of the slider member **170** results in movement and/or translation of the collet **160**, and hence the bone anchor **6**, with respect to the housing **110**. Preferably, the ridges **132** formed on the housing **110** include a convex top surface so that movement of the slider member **170** with respect to the housing **110** results in the collet **160** pivoting with respect to the housing **110**. The bore **177** is illustrated in the embodiment shown in FIG. **16** and **17**, however, it should be appreciated the slider members in other embodiments shown and described herein include similar bores.

It should be understood that the slider member **170** may be any size or shape, including a circle, oval, polygonal, square, etc. Alternatively, in some embodiments, the slider member **170** may be integrally formed with the nut **180**.

As previously mentioned, the bone anchor clamping assembly **150** may also incorporate a nut **180**. As shown, the nut **180** may include one or more threads for threadably engaging the threads **166** formed on the top portion **161** of the collet **160**. The nut **180** may also include one or more tool engaging elements **182** for facilitating engagement with one or more clamp insertion tools. The nut **180** may include any type of tool engaging elements **182** including, but not limited to, a plurality of angled flat surfaces along its perimeter that give the nut **180** a polygonal shape to facilitate rotation of the nut **180**. Alternatively, any other structural element, such as a depression or a projection, may be used.

As shown, the nut **180** preferably is disposed around at least a portion of the top portion **161** of the collet **160**, above the slider member **170**. The perimeter of the nut **180** may be smaller than the perimeter of the slider element **170** such that the edges of the nut **180** do not extend beyond the edges of the slider element **170** to minimize the amount of associated trauma.

In use, the collet **160** may be inserted into the first throughbore **117** formed in the housing **110**. The top portion **161** of the collet **160** extending beyond the top surface **115** of the housing **110**. Next, the slider member **170** may be placed on top of the housing **110** with the top portion **161** of the collet **160** extending therethrough. Thereafter, the nut **180** may be placed into threaded engagement with the threads **166** formed on the top portion **161** of the collet **160**. The nut **180** is preferably screwed down far enough so that the collet **160**, the slider member **170**, and the nut **180** are coupled to the housing **110**, but the user still has the ability to move and/or translate the slider member **170** with respect to the housing **110**, thereby enabling the collet **160** to pivot with respect to the housing **110**. Thereafter, the subassembly may be implanted as required.

The user may move or translate the slider member **170** along the ridges **132** on the housing **110** so that the collet **160** is moved to a desired angle. Next, the bone anchor **6** may be screwed through the bore **163** formed in the collet **160** and

17

into the patient's bone. Thereafter the longitudinal rod **4** may be inserted through the second throughbore **118** formed in the housing **110**. Alternatively, as will be appreciated by one of ordinary skill in the art, the bone anchor **6** may be implanted prior to the subassembly being inserted in-situ. In this embodiment, the collet **160** and subassembly would be slid over the shaft portion **6b** of the bone anchor **6**. Moreover, as will be appreciated by one of ordinary skill in the art, the longitudinal rod **4** may be inserted into the second throughbore **118** formed in the housing **110** prior to the subassembly being implanted in-situ or prior to the subassembly being coupled to the bone anchor **6**.

Once the bone anchor **6** has been implanted in the patient's bone, the longitudinal rod **4** has been inserted into the housing **110**, and the desired location of the bone anchor **6**, longitudinal rod **4** and clamp **100** has been achieved, the position of the rod **4** may be fixed with respect to the position of the bone anchor **6** by rotating the nut **180**. That is, rotation of the nut **180** causes the bone anchor clamping assembly **150** to move from the unlocked position to the locked position. More specifically, initial rotation of the nut **180** causes the nut **180** to apply a downward force onto the slider member **170**, which in turn causes the serrations formed on the bottom surface of the slider member **170** to contact the serrations **133** formed on the ridges **132** of the housing **110** thereby fixing the position of the slider member **170** with respect to the housing **110**. In addition, initial rotation of the nut **180** causes the collet **160** to move with respect to the first throughbore **117** formed in the housing **110** until the collet **160** contacts the inner surface of the first throughbore **117**, preferably until the flared end portion **162a** of collet **160** contacts the narrower diameter portion of the first throughbore **117**. This contacts causes the deflectable fingers **165** formed on the collet **160** to move towards one another and causes the collet **160** to be wedged between the bone anchor **6** and the housing **110**, which in turn fixes the position of the bone anchor **6** with respect to the housing **110**.

Additional rotation of the nut **180** causes the first and second portions **122**, **124** of the housing **110** to move with respect to one another which in turn causes the slit **120** formed in the housing **110** to compress. Compression of the slit **120**, in turn, causes the second throughbore **118** formed in the housing **110** to collapse or tighten around the longitudinal rod **4**, thus fixing the position of the rod **4** with respect to the housing **110**. One of the primary benefits of clamp **100** is that the position of the bone anchor **6** is fixed with respect to the housing **110** and the position of the rod **4** is fixed with respect to the housing **110** via rotation of a single element (e.g., nut **180**).

It should be understood that the method of use described above is only exemplary and non-limiting, the order of the steps described may be changed, and not every step may be necessary depending on the embodiment of the clamp employed and the procedure being performed.

Alternatively as shown in FIGS. **23** and **24**, an alternate exemplary embodiment of a clamp **200** is shown. In this embodiment, the housing **210** may be modified to include a monolithic and/or integral longitudinal rod **204**. The monolithic and/or integral rod **204** may extend from any side of the housing **110**, and may be any type of rod and may have any size or shape. It should be noted that the bone anchor clamping assembly in FIGS. **23** and **24** may be substantially the same as the bone anchor clamping assembly **150** described for FIGS. **16-22**. The rod may be pre-assembled and/or monolithic with the clamp, or may be assembled during surgery (e.g. screwed into the clamp body).

An exemplary embodiment of a method of performing spinal fusion using clamp **200** is shown in FIGS. **25-35**. It

18

should be understood that while the exemplary method of performing spinal fusion is shown and described in connection with clamp **200**, the exemplary method may be used in connection with any other clamps described herein or otherwise hereafter known. The method may be used in connection with an open midline approach, a minimal invasive procedure, etc. FIGS. **26** and **27** show exemplary tools that may be employed in the procedure, namely a flexible guide wire **300**, a flexible guidewire holder **310**, and a rod clamp insertion instrument **320**.

Referring to FIG. **27**, the guide wire **300** may be inserted through a small incision into a pre-made hole formed in the first (possibly caudal) vertebra using the guide wire holder **310**. An anterior-posterior and lateral image may be used to ensure proper guide wire **300** positioning. Subsequently a first bone anchor may be implanted using the implanted guide wire **300** as a guide. Thereafter, the guide wire **300** may be removed.

Referring to FIG. **28**, a second guide wire **300** may be inserted through a small incision into a pre-made hole formed in a second vertebra using the guide wire holder **310**. Once again, an anterior-posterior and lateral image may be used to ensure proper guide wire **300** positioning. This step may be repeated as often as necessary depending on the number of vertebrae being stabilized and/or fused and the procedure being performed.

Referring to FIG. **29**, a clamp **325**, preferably a lateral clamp, may be secured onto the first bone anchor, which has been implanted into the first vertebrae.

Referring to FIG. **30**, using the second guide wire **300**, which was inserted into the second vertebra, as a guide, the monolithic and/or integral rod **204** formed on the clamp **200** may be inserted into the clamp **325**. The clamp **200** may be implanted using the cannulated rod clamp insertion instrument **320**.

Referring to FIG. **31**, the monolithic and/or integral rod **204** formed on the clamp **200** may be inserted through the clamp **325**. Next, as shown in FIG. **32**, the rod clamp insertion instrument **320** may be removed.

Referring to FIGS. **33** and **34**, using the second guide wire **300** as a guide, a second bone anchor **6** may be implanted through the clamp **200** and into engagement with the patient's vertebra. The second guide wire **300** may then be removed. Finally, as shown in FIG. **35**, tightening of the nut on clamp **200** and clamp **325** is performed. In addition, optionally, lordosis and/or kyphosis correction may be performed and the ends of the bone anchors may be cut and removed.

Since clamp **200** incorporates a monolithic and/or integral rod **204** a shorter rod than would otherwise be necessary may be included on the clamp **200** and no assembly or set screw is required.

It should be understood that while the exemplary embodiment of performing spinal fusion was shown and described using clamp **200** and a lateral clamp **325**, any number of different clamps can be used. For example, two lateral clamps may be used wherein a first bone anchor and a first clamp is implanted. The rod may then be guided through a second clamp then through the already installed first clamp. Then a second screw may be inserted through the second clamp, once the rod is in place.

As shown in FIG. **36**, an alternate exemplary embodiment of a clamp **400** is shown. In this embodiment, the clamp **400** may include a housing **410** having a first throughbore **417** and a second throughbore **418**, a rod clamping assembly **430** and a bone anchor clamping assembly **450**. The first throughbore **417** being sized and configured to receive at least a portion of the bone anchor clamping assembly **450** for fixing the posi-

tion of a bone anchor **6** (not shown) with respect to the housing **410**. The structure and operation of the bone anchor clamping assembly **450** may be substantially similar to the bone anchor clamping assembly **50** described above in connection with clamp **10**.

The rod clamping assembly **430** may include a gripping element **432** (shown as a loop shaped gripping element), a slider member **436** (shown as a plate), a nut **440** and an optional collar (not shown). The collar preferably being located in-between the nut **440** and the gripping element **432** so that rotation of the nut **440** causes the collar to contact the rod **4** located within the gripping element **432**, as will be described in greater detail below. As will be generally appreciated by one of ordinary skill in the art, incorporation of the collar is optional. For example, the nut **440** may be configured to directly contact the longitudinal rod **4**. Preferably, if and when the nut **440** is sized and configured to directly contact the longitudinal rod **4**, the tip of the nut **440** is configured to incorporate a plurality of concentric ridges **1500** to increase rod push-through force. That is, when a nut or set screw is used to directly contact a rod, preferably the tip of the nut or set screw is equipped with two or more concentric circles **1500** in order to maximize rod push-through force for a given tightening torque, as schematically represented in FIG. **36a**.

The gripping element **432** may include a lower portion **433** and an upper portion **434**, the lower portion **433** being disposed within the second throughbore **418** for receiving at least a portion of the longitudinal rod **4**. The upper portion **434** of the gripping element **432** being operably coupled to the slider member **436**. The slider member **436** is operably coupled to the housing **410**. For example, as shown, the slider member **436** and housing **410** may be connected to one another via a dovetail arrangement. Alternatively, as will be appreciated by one of ordinary skill in the art, the slider member **436** may be moveably coupled to the housing **410** by any other means including, but not limited to, a track-plate system, tongue and groove connection, etc. Incorporation of the slider member **436** enables the position of the slider member **436**, and hence the gripping element **432** that is connected thereto, to be slidably adjustable with respect to the housing **410** in order to better accommodate the position of the rod **4**.

As will be generally appreciated by one of ordinary skill in the art, in use, the nut **440** and collar are operably coupled to one another so that once the position of the longitudinal rod **4** has been properly positioned with respect to the housing **410**, rotation of the nut **440** causes a force to be applied to the collar, which in turn compresses the collar against the longitudinal rod **4** causing the rod **4** to be wedged between the collar and gripping element **432**. In addition, rotation of the nut **440** causes a force to be applied to the slider member **436**, which in turn fixes the position of the slider member **436** with respect to the housing **410**.

As shown in FIGS. **37-39**, another exemplary embodiment of a clamp **500** is shown. In this embodiment, the clamp **500** may include a housing **510** having a first throughbore **517** and a second throughbore **518**, a rod clamping assembly **530** and a bone anchor clamping assembly **550**. In this embodiment, the rod clamping assembly **530** may be in the form of a set screw **532** sized and configured to be received within the housing **510** in operational engagement with the second throughbore **518** formed in the housing **510** so that rotation of the set screw **532** causes the set screw **532** to contact the portion of the longitudinal rod **4** located in the second throughbore **518** thereby fixing the position of the rod **4** with respect to the housing **510**. That is, in use, rotation of the set screw **532** causes the set screw **532** to move with respect to the

housing **510**, which in turn causes the rod **4** to be wedged between the set screw **532** and the housing **510**.

The first throughbore **517** is preferably sized and configured to receive at least a portion of the bone anchor clamping assembly **550**. Similar to previous embodiments, the bone anchor clamping assembly **550** may include a bushing **560**, a collet **570**, and a nut **580** for fixing the position of the bone anchor **6** with respect to the housing **510**. In this embodiment however, the bushing **560** and the collet **570** may be configured with corresponding tapered surfaces **561**, **571**. In use, as will be generally appreciated by one of ordinary skill in the art, since the nut **580** is in threaded engagement with the collet **570**, rotation of the nut **580** causes the collet **570** to move with respect to the nut **580**. Moreover, since the nut **580** is generally located above the bushing **560**, the nut **580** eventually may contact the bushing **560** and thus prevent it from moving with respect to the nut **580**. Thus rotation of the nut **580** causes the collet **570** to move with respect to the bushing **560**, which in turn causes the position of the bushing **560** and collet **570** to be fixed with respect to one another and with respect to the housing **510**. The bushing **560** and collet **570** may include any other corresponding shapes including, but not limited to, spherical, conical, etc.

The housing **510** also preferably includes a slider member **590** operably coupled thereto. As shown, the slider member **590** enables the position of the bone anchor clamping assembly **550**, and hence the position of the bone anchor **6**, to be moveably adjustable with respect to the housing **510**, and hence with respect to the longitudinal rod **4**. One of the unique features of this embodiment is that rotation of the rod clamping assembly (e.g. set screw **532**) causes a force to be applied to the slider member **590**, and hence causes the slider member **590** to be wedged between the rod clamping assembly **530** and the housing **510** which, in turn, fixes the position of the slider member **590** with respect to the housing **510**. That is, in contrast to the previously described embodiments of the clamp, the position of the slider member **590** is fixed by rotating the rod clamping assembly **530**. Thus, the lateral position of the longitudinal rod **4** is fixed with respect to the bone anchor **6** when the position of the rod **4** is fixed. Thereafter, the bone anchor **6** may still be able to polyaxially angulate with respect to the housing **510** until the nut **580** is tightened.

As best shown in FIG. **40**, another exemplary embodiment of a clamp **600** is shown. In this embodiment, the clamp **600** may include a housing **610** having a first throughbore **617** and a second throughbore **618**, a rod clamping assembly **630** and a bone anchor clamping assembly **650**. In this embodiment, the rod clamping assembly **630** may be in the form of a set screw **632**. Rotation of the set screw **632** causing the longitudinal rod (not shown) to be fixed with respect to the housing **610**. As shown, the first throughbore **617** preferably is in the form of an elongated slot so that the bone anchor clamping assembly **650**, which is operably coupled to the first throughbore **617**, can move within the slot so that the lateral position of the rod with respect to the bone anchor (not shown) can be adjusted.

Similar to the bone anchor clamping assembly **150** previously described, the bone anchor clamping assembly **650** may include a collet **660**, a bushing **665**, a slider member **670** and a nut **680**. In this embodiment however, the bushing **665** preferably includes one or more ridges **668** for contacting the slider member **670** as opposed to the ridges being formed on the housing. In this way, the slider member **670**, and hence the collet **660** and bone anchor, are able to translate and pivot with respect to the housing **610**.

21

As best shown in FIGS. 41 and 42, another exemplary embodiment of a clamp 700 is shown. In this embodiment, the clamp 700 may include a housing 710, preferably in the form of an L-shaped plate 712 to allow for medial-lateral and cranial-caudal offset, having a first throughbore 717 and a second throughbore 718 preferably located at opposite ends of the L-shaped plate 712. The shape and configuration of the clamp 700 makes it particularly useful for sparing the facet (e.g., avoiding contact with the facet so that the facet is not touched and/or damaged).

The clamp 700 may also include a rod clamping assembly 730 and a bone anchor clamping assembly 750, the rod clamping assembly 730 may be in the form of a set screw 732. Rotation of the set screw 732 causing the position of the longitudinal rod 4 to be fixed with respect to the housing 710. The first throughbore 717 is preferably in the form of an elongated slot so that the bone anchor clamping assembly 750, which is operably coupled to the first throughbore 717, can move within the slot so that the lateral position of the housing 710 can be moved with respect to the bone anchor 6. As previously described in connection with clamp 100, the bone anchor clamping assembly 750 may include a collet 760, a slider member 770, and a nut 780. As shown, the housing 710 may include one or more ridges 714 for contacting the slider member 770. In this way, the bone anchor clamping assembly 750, and hence the bone anchor 6, is able to pivot with respect to the housing 710. The portion of the L-shaped plate 712 that surrounds the bone anchor clamping assembly 750 is preferably minimized in size to preserve the superior facet of the patient's vertebra.

As shown in FIGS. 43-45, an alternate embodiment of a clamp 900 is shown. In this embodiment the clamp 900 may include a housing 910 having a first throughbore 917 and a second throughbore 918, a rod clamping assembly 930 and a bone anchor clamping assembly 950. In this embodiment, the rod clamping assembly 930 may be in the form of a set screw 932. The set screw 932 may include a plurality of concentric ridges (not shown) for contacting the outer surface of the longitudinal rod, as previously described. Rotation of the set screw 932 causes the position of the longitudinal rod to be fixed with respect to the housing 910. As shown, the bone anchor clamping assembly 950 may include a collet 960, a slider member 970 and a nut 980 as previously described herein, although other bone anchor clamping assemblies may be used.

Preferably, clamp 900 is sized and configured to minimize the distance between the bone anchor and the longitudinal rod. This object may be accomplished by positioning the first throughbore 917 for receiving the bone anchor clamping assembly 950 and the second throughbore 918 for receiving the longitudinal rod as close as possible to one another. Moreover, as best shown in FIG. 44, preferably the axis of the rod clamping assembly (e.g., set screw 932) is angled X with respect to the longitudinal axis of the second throughbore 918 and the axis of the bone anchor clamping assembly 930 is angled Y with respect to the longitudinal axis of the first throughbore 917 so that the rod to bone anchor offset is minimized. The axis of the rod clamping assembly (e.g., set screw 932) may be at an angle X of approximately 15 degrees with respect to the longitudinal axis of the second throughbore 918 and the axis of the bone anchor clamping assembly 930 may be angled Y at an angle of approximately 5 degrees with respect to the longitudinal axis of the first throughbore 917. It should be noted that other angles are envisioned. Moreover, as shown, preferably the collet 960 is truncated so that the width of the bone anchor clamping assembly 950 is minimized.

22

Referring to FIGS. 46-50, an exemplary embodiment of an optional retention clip for use in maintaining the bone anchor in the clamp, such as the clamps described above, will now be described. The retention clip 1000 may be located adjacent the proximal end of the bone anchor 6. As shown, the retention clip 1000 preferably includes a projection 1002 extending from the shaft portion 6b of the bone anchor 6. Preferably, the projection 1002 is integrally formed with the bone anchor 6. More preferably, the projection 1002 extends from the proximal end of the shaft portion 6b of the bone anchor 6 for reasons that will become apparent. The projection 1002 may include a ramp like surface in order to facilitate translation of the clamp over the bone anchor 6 and past the retention clip 1000. It should be noted however that the size and shape of the projection 1002 may be modified for various applications, and the retention clip 1000 should not be limited by the particular shape or size of the projection 1002.

The retention clip 1000 also preferably includes a slot 1004 formed in the bone anchor 6 adjacent to the projection 1002. As will be appreciated by one of ordinary skill in the art, the slot 1004 enables the retention clip part 1000 of the bone anchor 6 to be elastically flexible.

In use, the clamp, and in particular the bone anchor clamping assembly may be slid over the proximal end of the shaft portion 6b of the bone anchor 6. At this point, the retention clip 1000 flexes in order to permit the clamp to pass over the bone anchor 6. Once the clamp has been slid beyond the retention clip 1000, the clamp is prevented from accidentally becoming disassembled from the bone anchor 6 by the projection 1002. If the user desires to disassemble the bone anchor 6 from the clamp, the retention clip 1000 may enable the clamp and bone anchor 6 to be separated under additional load. That is, once the clamp has been slid beyond the retention clip 1000, the retention clip 1000 preferably deflects back to its original shape, thereby positioning the projection 1002 above the top surface of the clamp, and thus preventing the clamp from sliding apart from the bone anchor 6, without application of additional force.

Referring to FIGS. 51-57, an exemplary clamp insertion instrument 1100 that may be used to insert the bone anchor 6 and clamp 10 will be described. It should be understood however that while the clamp insertion instrument 1100 will be shown as and described in connection with implantation of clamp 10, the clamp insertion instrument 1100 may be easily modified to implant other clamps including those herein described or otherwise known.

The insertion instrument 1100 may include a handle member 1110 (shown as a T-handle), a sleeve member 1120, and a drive member 1130. The sleeve member 1120 preferably includes a proximal end 1122, a distal end 1124 and a bore 1126 extending from the distal end 1122 to the proximal end 1124. The bore 1126 being sized and configured to receive at least a portion of the drive member 1130. The proximal end 1122 may be operably associated with the handle member 1110 so that movement of the handle member 1110 results in movement of the sleeve member 1120.

The drive member 1130 preferably includes a proximal end 1132 and a distal end 1134, the distal end 1134 preferably includes one or more threads 1135 for threadably engaging a drive recess formed in the bone anchor 6 (although other type of connections may be used). The proximal end 1132 of the drive member 1130 is preferably coupled to a guide member 1140. More preferably, the drive member 1130 is rigidly coupled to the guide member 1140. Alternatively, however, the drive member 1130 and guide member 1140 may be

coupled by any other means. It is also contemplated that the drive member 1130 and guide member 1140 may be integrally formed.

The drive member 1130 also preferably includes a drive sleeve member 1150, the drive sleeve member 1150 may include a proximal end 1152, a distal end 1154 and a bore 1156 extending from the proximal end 1152 to the distal end 1154. The bore 1156 being sized and configured to receive the drive member 1130, and optional guide member 1140, therein. As shown, the distal portion 1154 of the drive sleeve member 1150 may also be sized and configured to contact the drive recess formed in the bone anchor 6. The drive sleeve member 1150 preferably also includes one or more threads 1158 for engaging one or more threads formed on the inner surface 1127 of the sleeve member 1120. The drive sleeve member 1150 preferably also includes one or more flexible fingers 1160 formed on the outer surface thereof. The fingers 1160 in their unflexed state are preferably wider than the diameter of the bore formed in the sleeve member 1120 such that moving the sleeve member 1120 over the drive sleeve member 1150 causes the fingers 1160 to inwardly deflect.

In use, the insertion instrument 1100 may be used to couple the clamp 10 to the bone anchor 6. Once the bone anchor 6 has been properly implanted, the drive member 1130 may be coupled to the bone anchor 6. Next, the drive sleeve member 1150 may be coupled to the bone anchor 6 using the guide member 1140, which may be operably coupled to the drive member 1130, as a guide. Thereafter, as best shown in FIG. 53, the guide member 1140 may be used to guide the clamp 10 into place on the shaft portion 6b of the bone anchor 6. As best shown in FIGS. 55-57, once the clamp 10 has been positioned onto the guide member 1140, the sleeve member 1120 may be placed over and moved with respect to the guide member 1140 until the threads formed on the inner surface 1127 of the sleeve member 1120 contact the threads 1158 formed on the drive sleeve member 1150. Thereafter, the sleeve member 1120 may be rotated, using the handle portion 1110, with respect to the drive member 1130 and drive sleeve member 1150. As will be generally appreciated by one of ordinary skill in the art, movement of the sleeve member 1120 with respect to the drive member 1130 and drive sleeve member 1150 causes the clamp 10 to move into operably engagement with the shaft portion 6b of the bone anchor 6. Once the clamp 10 has been properly positioned onto the bone anchor 6, the sleeve member 1120 may be removed. As best shown in FIG. 57, at this point in time, the flexible fingers 1160 formed on the drive sleeve member 1150 deflect outwards retaining the clamp 10 onto the bone anchor 6.

Referring to FIGS. 58-64, an alternate exemplary insertion instrument 1200 is shown. In this embodiment, as best shown in FIG. 61, the drive member 1230, the guide member 1240, and the drive sleeve member 1250 may be integrally formed. In use, the operation of the insertion instrument 1200 is substantially identical to the operation of insertion instrument 1100 described above.

An alternative exemplary embodiment of a drive member 1330 and a guide member 1340 are shown in FIG. 65. As shown, the drive member 1330 may be sized and configured to articulate with respect to the bone anchor 6. In addition and/or alternatively, the drive member 1330 may be sized and configured to articulate with respect to the guide member 1340.

As will be appreciated by those skilled in the art, any or all of the components described herein may be provided in sets or kits so that the surgeon may select various combinations of components to perform a fixation procedure and create a fixation system which is configured specifically for the par-

ticular needs/anatomy of a patient. It should be noted that one or more of each component may be provided in a kit or set. In some kits or sets, the same device may be provided in different shapes and/or sizes.

While directional terms such as vertical, horizontal, top, bottom, etc. were used in describing various embodiments, it will be understood that the terms were only used in reference to the illustrations. In use, the embodiments may be oriented in any direction and vertical may become horizontal, top may become bottom, etc.

While the foregoing description and drawings represent the preferred embodiments of the present invention, it will be understood that various additions, modifications, combinations and/or substitutions may be made therein without departing from the spirit and scope of the invention as defined in the accompanying claims. In particular, it will be clear to those skilled in the art that the invention may be embodied in other specific forms, structures, arrangements, proportions, and with other elements, materials, and components, without departing from the spirit or essential characteristics thereof. One skilled in the art will appreciate that the invention may be used with many modifications of structure, arrangement, proportions, materials, and components, which are particularly adapted to specific environments and operative requirements without departing from the principles of the invention. In addition, features described herein may be used singularly or in combination with other features. For example, the various housing, rod clamping assemblies and/or bone anchor clamping assemblies may be interchangeable. The presently disclosed embodiments are therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims, and not limited to the foregoing description.

What is claimed is:

1. A clamp for securing a bone anchor with respect to a rod, the bone anchor including a bone engaging portion and an extending portion, the clamp comprising:

a housing defining an external surface, a first housing portion and a second housing portion spaced apart from the first housing portion along a lateral direction, the first housing portion defining a first opening extending through housing along a vertical direction, the vertical direction being perpendicular to the lateral direction, wherein the first opening is configured to receive at least a portion of the extended portion of the bone anchor, the second housing portion defining a second opening, wherein the second opening is configured to receive the rod, the second opening defining a second opening inner surface, wherein the external surface of the housing defines one or more upwardly projecting curved surfaces that extend from the first portion of the housing along the vertical direction, the one or more curved surfaces adjacent to the first opening,

the housing further defining a slit extending from the inner surface of the second opening to the external surface adjacent to the first opening, the slit extending along an axis that is angularly offset relative to the vertical and lateral directions, the slit dividing the housing into the first housing portion and the second housing portion so that the housing is elastically deflectable; and

a bone anchor clamping assembly carried by the housing and spaced apart from the second opening along the lateral direction, the bone anchor clamping assembly including:

a slider member including a top surface, a bottom surface, and a bore extending from the top surface to the bottom

25

surface, the slider member carried by the first and second housing portions the slider member translatable with respect to the housing

a collet positioned at least partially within the first opening, the collet including a top portion, a bottom portion and a collet bore extending from the top portion to the bottom portion, the collet bore configured to receive at least a portion of the extending portion of the bone anchor, the collet including one or more threads, a portion of the collet extending through the bore of the slider member; and

a rotatable member carried by the slider member, the rotatable member configured to receive a portion of the extending portion of the bone anchor and at least a portion of the collet;

wherein the clamp has an unlocked configuration and a locked configuration, wherein the unlocked configuration is defined as when the slider member is moveable along the external surface of the first and second housing portions to cause the collet, the rotatable member and the bone anchor to move with respect to the housing, wherein the locked configuration is defined as when rotation of the rotatable member 1) reduces the size of the slit so as to fix the position of the rod received in the second opening with respect to the housing, and 2) engages the collet with the extending portion of the bone anchor so as to fix the position of the bone anchor with respect to the housing.

2. The clamp of claim 1, wherein the collet includes one or more slots extending upwards from the bottom portion, thereby defining one or more deflectable collet fingers.

3. The clamp of claim 2, wherein the bottom portion of the collet includes a substantially curved outer surface for contacting a substantially corresponding internally curved surface formed in the first opening.

4. The clamp of claim 2, wherein the one or more slots is comprised of two slots and the one or more deflectable collet fingers is comprised of two collet fingers.

5. The clamp of claim 2, wherein the collet bore includes an internal threading, the internal threading being engageable with a threading formed on the bone engaging portion of the bone anchor so that the bone anchor can be threaded through the collet bore.

6. The clamp of claim 1, wherein the slider member is in the form of a plate-type member.

7. The clamp of claim 1, wherein rotation of the rotatable member iterates the clamp between the unlocked and locked configurations, wherein rotation of the rotatable member in a first rotational direction moves the rotatable member toward the housing along the vertical direction to apply a force onto the slider member so that the position of the slider member and the position of the received bone anchor are fixed with respect to the housing.

8. The clamp of claim 7, wherein rotation of the rotatable member in the first rotational direction causes the first portion of the housing to move closer to the second portion to compress the slit, thereby decreasing a cross-sectional dimension of the second opening so as to fix the position of the received rod with respect to the housing.

9. The clamp of claim 1, wherein the one or more upwardly projecting curved surfaces is comprised of opposing convex ridges having serrations formed thereon.

10. The clamp of claim 1, wherein movement of the slider member generally parallel to the external surface of the housing causes the bone anchor to angulate with respect to the housing and the rod.

26

11. A clamping system for mounting to a vertebra, the clamping system comprising:

an elongate rod;

a bone anchor including a bone engaging portion, and an extending portion spaced apart from the bone engaging portion along an anchor axis, the bone engaging portion being sized and configured to be at least partially implanted into the vertebra;

a housing including a first opening and a second opening;

a bone anchor clamping assembly disposed at least partially in the first opening, the bone anchor clamping assembly being polyaxially rotatable relative to the housing,

the bone anchor clamping assembly comprising a bushing, a collet and a rotatable member, the bushing including a top portion, a bottom portion, a bore extending from the top portion to the bottom portion and a plurality of slots extending upwards from the bottom portion of the bushing, the slots defining therebetween a plurality of deflectable bushing fingers, the collet at least partially received in the bore of the bushing, the collet defining a top portion, a bottom portion, a collet bore extending from the top portion of the collet, to the bottom portion of the collet, the collet bore configured to receive at least a portion of the bone anchor, and a plurality of collet slots extending upwards from the bottom portion of the collet, thereby defining a plurality of deflectable collet fingers;

wherein the bone anchor clamping assembly has an unlocked configuration and locked configuration, the unlocked configuration is defined as when A) the bone anchor is polyaxially rotatable relative to the housing when the bone anchor is received by the bone anchor clamping assembly, and B) the housing is movable generally parallel to the anchor axis when the bone anchor is implanted in the vertebra, and

the locked configuration is defined as when the bone anchor clamping assembly locks 1) an angular orientation of the received bone anchor relative to the housing, and 2) the position of the housing relative to the vertebra when the bone anchor is implanted in the vertebra; and

a rod clamping assembly positioned at least partially within the second opening, the rod clamping assembly configured to receive the rod, wherein the rod clamping assembly has a slack configuration and a fastened configuration, wherein the slack configuration is defined as when the rod is movable within the second opening and the fastened configuration is defined as when the rod is fixed in position within the second opening.

12. The clamping system of claim 11, wherein the bottom portion of the bushing includes a substantially spherical outer surface for contacting a substantially corresponding internal surface formed in the housing and defined by the first opening.

13. The clamping system of claim 11 wherein the first opening includes at least one protrusion and the bushing includes at least one recess, the at least one protrusion positioned within the at least one recess in the unlocked configuration to prevent rotation of the bushing with respect to the housing.

14. The clamping system of claim 11, wherein the bore formed in the bushing includes a narrower diameter portion and the collet includes a flared portion so that movement of the collet with respect to the bushing causes the flared portion of the collet to contact the deflectable bushing fingers, thereby biasing the bushing fingers outward into contact with the first

opening while simultaneously causing the deflectable collet fingers to be biased inwards against the extending portion of the bone anchor.

15. The clamping system of claim 11, wherein the collet bore includes a narrower portion having a smaller size than a size of the extending portion of the bone anchor so that insertion of the bone anchor into the collet bore causes the extending portion to frictionally couple the bone anchor to the collet.

16. The clamping system of claim 11, wherein the rod has a longitudinal axis, the anchor axis of the bone anchor being spaced apart from the longitudinal axis of the rod so that the anchor axis and the longitudinal axis do not intersect.

17. The clamping system of claim 11, wherein the housing is in the form of a plate having a first portion and a second portion, the first opening being formed in the first portion and the second opening being formed in the second portion, the first portion being angled with respect to the second portion.

18. The clamping system of claim 11 wherein the rod clamping assembly includes a gripping element having a lower portion and an upper portion, the lower portion receiving at least a portion of the rod in the slack and fastened configurations, the upper portion being operably associated with the housing.

19. The clamping system of claim 18, wherein the upper portion of the gripping element is operably coupled to the housing via a second rotatable member.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 8,585,741 B2
APPLICATION NO. : 12/668862
DATED : November 19, 2013
INVENTOR(S) : Gabelberger et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the Title Page:

The first or sole Notice should read --

Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 894 days.

Signed and Sealed this
Twenty-second Day of September, 2015



Michelle K. Lee
Director of the United States Patent and Trademark Office