



(12) **United States Patent**
Philyaw et al.

(54) **METHOD AND APPARATUS FOR
ACCESSING A REMOTE LOCATION WITH
AN OPTICAL READER HAVING A
DEDICATED MEMORY SYSTEM**

FOREIGN PATENT DOCUMENTS

EP 0 961 250 A2 12/1999

(Continued)

(75) Inventors: **Jeffry Jovan Philyaw**, Dallas, TX
(US); **Douglas L. Davis**, Dallas, TX
(US)

OTHER PUBLICATIONS

“Group Decision Support System; Development and Application”, Energy Systems, James W. Thomas; Westinghouse, Pittsburgh, PA. “New Technologies in Credit Card Authentication”, Pieter de Bruyne; Institute for Communications Technology Zurich, Switzerland; CH2892-1990 IEEE.

(Continued)

Primary Examiner—Paul H. Kang

(74) *Attorney, Agent, or Firm*—Howison & Arnott, L.L.P.

(22) Filed: **Jun. 22, 2004**

(65) **Prior Publication Data**

(57) **ABSTRACT**

US 2005/0021672 A1 Jan. 27, 2005

Related U.S. Application Data

(63) Continuation of application No. 09/602,468, filed on Jun. 23, 2000, now Pat. No. 6,754,698, which is a continuation-in-part of application No. 09/598,886, filed on Jun. 21, 2000, now Pat. No. 6,758,398, which is a continuation-in-part of application No. 09/580,848, filed on May 30, 2000, now Pat. No. 6,860,424, which is a continuation-in-part of application No. 09/378,221, filed on Aug. 19, 1999, now Pat. No. 6,745,234, which is a continuation-in-part of application No. 09/151,471, filed on Sep. 11, 1998, now abandoned, and a continuation-in-part of application No. 09/151,530, filed on Sep. 11, 1998, now Pat. No. 6,098,106.

(51) **Int. Cl.**
G06F 15/16 (2006.01)

(52) **U.S. Cl.** **709/217; 709/219; 709/245**

(58) **Field of Classification Search** 709/217,
709/203, 202, 204, 245

See application file for complete search history.


(56) **References Cited**

U.S. PATENT DOCUMENTS

3,668,312 A 6/1972 Yamamoto et al.

(Continued)

16 Claims, 17 Drawing Sheets



U.S. PATENT DOCUMENTS					
4,002,886 A	1/1977	Sundelin	5,592,551 A	1/1997	Lett et al.
4,042,792 A	8/1977	Pakenham et al.	5,594,226 A	1/1997	Steger
4,365,148 A	12/1982	Whitney	5,602,377 A	2/1997	Beller et al.
4,621,250 A	11/1986	Schepers et al.	5,604,542 A	2/1997	Dedrick
4,654,482 A	3/1987	DeAngelis	5,640,193 A	6/1997	Wellner
4,780,599 A	10/1988	Baus	5,649,186 A	7/1997	Ferguson
4,785,296 A	11/1988	Tabata et al.	5,664,110 A	9/1997	Green et al.
4,816,904 A	3/1989	McKenna et al.	5,671,282 A	9/1997	Wolff et al.
4,817,136 A	3/1989	Rhoads	5,675,721 A	10/1997	Freedman et al.
4,833,308 A	5/1989	Humble	5,682,540 A	10/1997	Klotz, Jr. et al.
4,841,132 A	6/1989	Kajitani et al.	5,694,163 A	12/1997	Harrison
4,845,634 A	7/1989	Vitek et al.	5,708,780 A	1/1998	Levergood et al.
4,894,789 A	1/1990	Yee	5,710,887 A	1/1998	Chelliah et al.
4,899,370 A	2/1990	Kameo et al.	5,715,314 A	2/1998	Payne et al.
4,901,073 A	2/1990	Kibrick	5,724,424 A	3/1998	Gifford
4,905,094 A	2/1990	Pocock et al.	5,745,681 A	4/1998	Levine et al.
4,907,264 A	3/1990	Seiler et al.	5,754,906 A	5/1998	Yoshida
4,916,293 A	4/1990	Cartlidge et al.	5,757,917 A	5/1998	Rose et al.
4,937,853 A	6/1990	Brule et al.	5,761,606 A	6/1998	Wolzien
4,947,028 A	8/1990	Gorog	5,764,906 A	6/1998	Edelstein et al.
4,959,530 A	9/1990	O'Connor	5,765,176 A	6/1998	Bloomberg
4,975,948 A	12/1990	Andresen et al.	5,768,528 A	6/1998	Stumm
4,984,155 A	1/1991	Geier et al.	5,774,664 A	6/1998	Hidary et al.
5,038,023 A	8/1991	Saliga	5,774,870 A	6/1998	Storey
5,054,096 A	10/1991	Beizer	5,778,367 A	7/1998	Wesinger, Jr. et al.
5,088,045 A	2/1992	Shimanaka et al.	5,790,793 A	8/1998	Higley
5,111,391 A	5/1992	Fields et al.	5,791,991 A	8/1998	Small
5,115,326 A	5/1992	Burgess et al.	5,794,210 A	8/1998	Goldhaber et al.
5,128,752 A	7/1992	Von Kohorn	5,796,952 A	8/1998	Davis et al.
5,144,654 A	9/1992	Kelley et al.	5,804,803 A	9/1998	Cragun et al.
5,161,037 A	11/1992	Saito	5,812,776 A	9/1998	Gifford
5,161,214 A	11/1992	Addink et al.	5,815,776 A	9/1998	Nukada
5,182,705 A	1/1993	Barr et al.	5,832,223 A	11/1998	Hara et al.
5,189,630 A	2/1993	Barstow et al.	5,833,468 A	11/1998	Guy et al.
5,191,525 A	3/1993	LeBrun et al.	5,848,202 A	12/1998	D'Eri et al.
5,198,644 A	3/1993	Pfeiffer et al.	5,848,413 A	12/1998	Wolff
5,235,654 A	8/1993	Anderson et al.	5,854,897 A	12/1998	Radziewicz et al.
5,241,402 A	8/1993	Aboujaoude et al.	5,864,823 A	1/1999	Leviton
5,243,531 A	9/1993	DiPippo et al.	5,869,819 A	2/1999	Knowles et al.
5,247,347 A	9/1993	Litteral et al.	5,905,248 A	5/1999	Russell et al.
5,262,860 A	11/1993	Fitzpatrick et al.	5,905,251 A	5/1999	Knowles
5,285,278 A	2/1994	Holman	5,905,665 A	5/1999	Rim
5,287,181 A	2/1994	Holman	5,905,865 A	5/1999	Palmer et al.
5,288,976 A	2/1994	Citron et al.	5,907,793 A	5/1999	Reams
5,296,688 A	3/1994	Hamilton et al.	5,913,210 A	6/1999	Call
5,304,786 A	4/1994	Pavlidis et al.	5,915,090 A	6/1999	Joseph et al.
5,305,195 A	4/1994	Murphy	5,918,214 A	6/1999	Perkowski
5,319,454 A	6/1994	Schutte	5,925,865 A	7/1999	Steger
5,324,922 A	6/1994	Roberts	5,929,850 A	7/1999	Broadwin et al.
5,331,547 A	7/1994	Laszlo	5,932,863 A	8/1999	Rathus et al.
5,340,966 A	8/1994	Morimoto	5,933,829 A	8/1999	Durst et al.
5,357,276 A	10/1994	Banker et al.	5,948,061 A	9/1999	Merriman et al.
5,362,948 A	11/1994	Morimoto	5,957,695 A	9/1999	Redford et al.
5,382,779 A	1/1995	Gupta	5,960,411 A	9/1999	Hartman et al.
5,386,298 A	1/1995	Bronnenberg et al.	5,961,603 A	10/1999	Kunkel et al.
5,398,336 A	3/1995	Tantry et al.	5,970,471 A	10/1999	Hill
5,405,232 A	4/1995	Lloyd et al.	5,970,472 A	10/1999	Allsop et al.
5,418,713 A	5/1995	Allen	5,971,277 A	10/1999	Cragun et al.
5,420,403 A	5/1995	Allum et al.	5,974,443 A	10/1999	Jeske
5,420,943 A	5/1995	Mak	5,974,451 A	10/1999	Simmons
5,424,524 A	6/1995	Ruppert et al.	5,976,833 A	11/1999	Furukawa et al.
5,438,355 A	8/1995	Palmer	5,978,773 A	11/1999	Hudetz et al.
5,446,490 A	8/1995	Blahut et al.	5,991,739 A	11/1999	Cupps et al.
5,446,919 A	8/1995	Wilkins	5,992,752 A	11/1999	Wilz, Sr. et al.
5,491,508 A	2/1996	Friedell et al.	5,995,105 A	11/1999	Reber et al.
5,493,107 A	2/1996	Gupta et al.	6,002,394 A	12/1999	Schein et al.
5,519,878 A	5/1996	Dolin, Jr.	6,003,073 A	12/1999	Solvason
5,530,852 A	6/1996	Meske, Jr. et al.	6,006,257 A	12/1999	Slezak
5,570,295 A	10/1996	Isenberg et al.	6,009,410 A	12/1999	LeMole et al.
5,572,643 A	11/1996	Judson	6,009,465 A	12/1999	Decker et al.
5,578,818 A	11/1996	Kain et al.	6,009,480 A	12/1999	Pleso
			6,012,102 A	1/2000	Shachar
			6,018,764 A	1/2000	Field et al.

6,064,929	A	5/2000	Perkowski	
6,098,106	A	8/2000	Philyaw et al.	
6,108,656	A	8/2000	Durst et al.	
6,154,738	A	11/2000	Call	
6,199,048	B1	3/2001	Hudetz et al.	
6,260,763	B1	7/2001	Svetal	
6,424,830	B1	7/2002	O'Hagan et al.	
6,745,234	B1	6/2004	Philyaw et al.	
6,754,698	B1	6/2004	Philyaw et al.	
6,758,398	B1	7/2004	Philyaw et al.	
2001/0024189	A1	9/2001	Michie	
2002/0033418	A1*	3/2002	Knowles et al.	 235/472.01
2003/0042311	A1	3/2003	Longacre et al.	

FOREIGN PATENT DOCUMENTS

JP	10188140	A	12/1996
WO	WO 95/10813		10/1994
WO	WO 96/07146		9/1995
WO	WO 97/37319		2/1997
WO	WO 98/09243		8/1997
WO	WO 98/03923		1/1998
WO	WO 98/06055		2/1998
WO	WO 98/19259		5/1998
WO	WO 98/40823		9/1998
WO	WO 99/63457		6/1999

OTHER PUBLICATIONS

"AVITAL, a Private Teaching System by Fax Communication", Atsushi Iizawa et al.; Software Research Center, RICOH Company; 8186-2697; Jun. 1992; IEEE.

"Document on Computer" IPCC96; Fast Track; The US Postal Service . . . ; 7803-3689, 1996, IEEE.

"Development of a Commercially Successful Wearable Data Collection System" Robert Stein et al.; 8186-9074; Jul. 1998, IEEE.

"NESTLE, What Do Forward Looking Companies Consider in Their Plans and Developments?" A. G. Johnston; File Name: IEE Colloquium; Oct. 12, 1997.

"The Automation Synergy", Ricardo Neves et al.; IEEE Catalog No. 97TH8280.

"Integration of Hand-Written Address Interpretation Technology Into the United States Postal Service Remote Computer Reader System"; Sargur N. Srihari et al. 8186-7898; Apr. 1997; IEEE.

"Paper Based Document Security—A Review" Rudolf L. Van Renesse; European Conference on Security and Detection Apr. 28-30, 1997; Publication No. 437; IEE 1997.

"IEEE Standard for Bar Coding for Distribution Transformers", IEEE Std. C57, 1996; Copyright 1996 by the Institute of Electrical and Electronics Engineers, Inc.




"The Stylus" Shopping from Home; John W. Barrus et al.; Stylus Innovation, Cambridge, MA 02142; 8186-2730; IEEE, 1992.

"Distributing Uniform Resource Locators as Bar Code Images"; IBM Technical Disclosure Bulletin . . . , Jan. 1996; vol.-39; Pub. No. 1; pp. 167-168.

"Bar Code Method for Automating Catalog Orders"; IBM Technical Disclosure Bulletin, pp. 243-244; Sep. 1988.

"Bar Code Recognition System Using Image Processing"; Miko Kuroki et al.; Hitachi Process Computer Engineering, Inc.

* cited by examiner



PATH A: SOURCE TO ARS



FIG. 4a

PATH B: ARS TO SOURCE




FIG. 4b

PATH C: SOURCE TO ADVERTISER



FIG. 4c

PATH D: ADVERTISER TO SOURCE




FIG. 4d

PATH E: ARS TO ADVERTISER (OPTIONAL)




FIG. 4e




FIG. 6




FIG. 5










FIG. 7








FIG. 14




FIG. 15






FIG. 19




FIG. 20




FIG. 21

ARS DATABASE
2100

2102		2104		2106	2108	
PRODUCT		INPUT DEVICE		USER	E-COMMERCE	
BAR CODE	ROUTE	ID	DISTRIBUTOR	PROFILE	BAR CODE	INFORMATION

FIG. 22




FIG. 23





FIG. 24






FIG. 25




FIG. 27




FIG. 26











FIG. 28








FIG. 36




FIG. 39




FIG. 40




FIG. 37







FIG. 38






FIG. 45

FIG. 44




FIG. 46

1

METHOD AND APPARATUS FOR ACCESSING A REMOTE LOCATION WITH AN OPTICAL READER HAVING A DEDICATED MEMORY SYSTEM

CROSS REFERENCE TO RELATED APPLICATION

This application is a Continuation of U.S. patent application Ser. No. 09/602,468, filed Jun. 23, 2000 now U.S. Pat. No. 6,754,698, and entitled "METHOD AND APPARATUS FOR ACCESSING A REMOTE LOCATION WITH AN OPTICAL READER HAVING A DEDICATED MEMORY SYSTEM," which application is a Continuation-in-Part of U.S. patent application Ser. No. 09/598,886, filed Jun. 21, 2000 now U.S. Pat. No. 6,758,398, and entitled "OPTICAL READER WITH ULTRAVIOLET WAVELENGTH CAPABILITY", which is a Continuation-in-Part of U.S. patent application Ser. No. 09/580,848, filed May 30, 2000 now U.S. Pat. No. 6,860,424, and entitled "OPTICAL READER AND USE", which is a Continuation-In-Part of U.S. application Ser. No. 09/378,221, now U.S. Pat. No. 6,745,234, issued Jun. 1, 2004 and entitled "METHOD AND APPARATUS FOR ACCESSING A REMOTE LOCATION BY SCANNING AN OPTICAL CODE", which is a Continuation-In-Part of the following two U.S. patent applications Ser. No. 09/151,471, filed Sep. 11, 1998 now abandoned, and entitled, "METHOD FOR INTERFACING SCANNED PRODUCT INFORMATION WITH A SOURCE FOR THE PRODUCT OVER A GLOBAL NETWORK", and U.S. application Ser. No. 09/151,530, now U.S. Pat. No. 6,098,106, issued Aug. 1, 2000 and entitled, "METHOD FOR CONTROLLING COMPUTERS THROUGH A RADIO/TELEVISION COMMUNICATION HUB".

TECHNICAL FIELD OF THE INVENTION

This invention relates generally to optical readers. In one aspect, it relates to a method for using an optical reader to automatically direct a computer to retrieve and display information from a remote location on a network.

BACKGROUND OF THE INVENTION

With the growing numbers of computer users connecting to the "Internet," many companies are seeking the substantial commercial opportunities presented by such a large user base. For example, one technology which exists allows a television ("TV") signal to trigger a computer response in which the consumer will be guided to a personalized web page. The source of the triggering signal may be a TV, video tape recorder, or radio. For example, if a viewer is watching a TV program in which an advertiser offers viewer voting, the advertiser may transmit a unique signal within the television signal which controls a program known as a "browser" on the viewer's computer to automatically display the advertiser's web page. The viewer then simply makes a selection which is then transmitted back to the advertiser.

In order to provide the viewer with the capability of responding to a wide variety of companies using this technology, a database of company information and Uniform Resource Locator ("URL") codes is necessarily maintained in the viewer's computer, requiring continuous updates. URLs are short strings of data that identify resources on the Internet: documents, images, downloadable files, services, electronic mailboxes, and other resources. URLs make

2

resources available under a variety of naming schemes and access methods such as HTTP, FTP, and Internet mail, addressable in the same simple way. URLs reduce the tedium of "login to this server, then issue this magic command . . ." down to a single click. The Internet uses URLs to specify the location of files on other servers. A URL includes the type of resource being accessed (e.g., Web, gopher, FTP), the address of the server, and the location of the file. The URL can point to any file on any networked computer. Current technology requires the viewer to perform periodic updates to obtain the most current URL database. This aspect of the current technology is cumbersome since the update process requires downloading information to the viewer's computer. Moreover, the likelihood for error in performing the update, and the necessity of redoing the update in the event of a later computer crash, further complicates the process. Additionally, current technologies are limited in the number of companies which may be stored in the database. This is a significant limitation since world-wide access presented by the Internet and the increasing number of companies connecting to perform on-line E-commerce necessitates a large database.

Many types of optical readers are known, however, their cost and complexity have heretofore limited their use primarily to industrial and commercial users. Now, many new network-based technologies are being developed for home users which involve optical scanning. Thus, the need for a simple, low cost optical reader which can be attached to a personal computer has emerged.

SUMMARY OF THE INVENTION

The present invention disclosed and claimed herein comprises, in one aspect thereof, a method of accessing a remote location on a network using an optical reader. The optical reader has an optical scanning system and a dedicated address memory system. The optical scanning system, in response to the user scanning an encoded indicia therewith, sends to a first computer disposed on the network a scan code indicative of information encoded in the scanned indicia. The dedicated address memory system, in response to the user completing an activation sequence, sends to the first computer a dedicated code indicative of information corresponding to a particular remote location. The information from the dedicated address memory system corresponding to a particular remote location does not originate from the scanning of an encoded indicia by the user. One of the scan code and the dedicated code is transmitted from the optical reader to the first computer. In response to the first computer receiving either the scan code or the dedicated code from the optical reader, a second computer disposed on the network is accessed. A lookup operation is performed at the second computer to match the code received from the optical reader, i.e., the scan code or the dedicated code, with a routing information for a remote location on the network. The routing information is returned from the second computer to the first computer. The remote location on the network is then accessed in accordance with the routing information returned from the second computer.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention and the advantages thereof, reference is now made to the following description taken in conjunction with the accompanying Drawings in which:

FIG. 1 illustrates a block diagram of the preferred embodiment;

3

FIG. 2 illustrates the computer components employed in this embodiment;

FIG. 3 illustrates system interactions over a global network;

FIGS. 4a–4e illustrate the various message packets transmitted between the source PC and network servers used in the preferred embodiment;

FIG. 5 is a flowchart depicting operation of the system according to the preferred embodiment;

FIG. 6 illustrates a flowchart of actions taken by the Advertiser Reference Server (“ARS”) server;

FIG. 7 illustrates a flowchart of the interactive process between the source computer and ARS;

FIG. 8 illustrates a web browser page receiving the modified URL/advertiser product data according to the preferred embodiment;

FIG. 9 illustrates a simplified block diagram of the disclosed embodiment;

FIG. 10 illustrates a more detailed, simplified block diagram of the embodiment of FIG. 9;

FIG. 11 illustrates a diagrammatic view of a method for performing the routing operation;

FIG. 12 illustrates a block diagram of an alternate embodiment utilizing an optical region in the video image for generating the routing information;

FIG. 13 illustrates a block diagram illustrating the generation of a profile with the disclosed embodiment;

FIG. 14 illustrates a flowchart for generating the profile and storing at the ARS;

FIG. 15 illustrates a flowchart for processing the profile information when information is routed to a user;

FIG. 16 illustrates a general block diagram of a disclosed embodiment;

FIG. 17 illustrates the conversion circuit of the wedge interface;

FIG. 18 illustrates a sample message packet transmitted from the user PC to the ARS;

FIG. 19 illustrates a more detailed block diagram of the routing of the message packets between the various nodes;

FIG. 20 illustrates a block diagram of a browser window, according to a disclosed embodiment;

FIG. 21 illustrates a diagrammatic view of information contained in the ARS database;

FIG. 22 illustrates a flowchart of the process of receiving information from the user’s perspective;

FIG. 23 illustrates a flowchart according to the ARS;

FIG. 24 illustrates a flowchart of the process performed at the E-commerce node;

FIG. 25 illustrates reading a bar code with an optical reader according to an embodiment of the invention;

FIG. 26 illustrates a top plan view of an optical reader according to an embodiment of the invention;

FIG. 27 illustrates a front elevation view of the optical reader viewed from line 27—27 of FIG. 26;

FIG. 28 illustrates a general functional block diagram of the components of an optical reader in accordance with an embodiment of the invention;

FIG. 29 illustrates the optical reader of FIG. 26 with portions of the outer shell removed to show the interior components;

FIG. 30 illustrates an enlarged view of the optical system of the optical reader while reading a bar code;

FIG. 31 illustrates a perspective view of the detector unit used in an embodiment of the optical reader;

FIG. 32 illustrates an exploded view of the detector unit of FIG. 31;

4

FIG. 33 illustrates a top plan view of an optical reader according to another embodiment of the invention;

FIG. 34 illustrates a side elevation view of the optical reader of FIG. 33;

FIG. 35 illustrates a front elevation view of the optical reader viewed from line 35—35 of FIG. 33;

FIG. 36 illustrates a flowchart of one embodiment of the process for reading a barcode;

FIG. 37 illustrates a general functional block diagram of the components of an optical reader in accordance with another embodiment;

FIG. 38 illustrates an enlarged view, with portions broken away, of the front end of the embodiment;

FIG. 39 illustrates a portion of the optical system for an alternative embodiment;

FIG. 40 illustrates a general functional block diagram for the output circuit of the embodiment;

FIG. 41 illustrates a top plan view of an optical reader according to another embodiment;

FIG. 42 illustrates a front elevation view of the optical reader of FIG. 41;

FIG. 43 illustrates a general functional block diagram of the components of one embodiment of the optical reader;

FIG. 44 illustrates a sample scan code transmitted from the optical reader to the associated device;

FIG. 45 illustrates a sample dedicated code transmitted from the optical reader to the associated device; and

FIG. 46 illustrates a system in accordance with the current invention.

DETAILED DESCRIPTION OF THE INVENTION

Referring now to FIG. 1, there is illustrated a block diagram of a system for controlling a personal computer (“PC”) 112 via an audio tone transmitted over a wireless system utilizing a TV. In the embodiment illustrated in FIG. 1, there is provided a transmission station 101 and a receive station 117 that are connected via a communication link 108. The transmission station 101 is comprised of a television program source 104, which is operable to generate a program in the form of a broadcast signal comprised of video and audio. This is transmitted via conventional techniques along channels in the appropriate frequencies. The program source is input to a mixing device 106, which mixing device is operable to mix in an audio signal. This audio signal is derived from an audio source 100 which comprises a coded audio signal which is then modulated onto a carrier which is combined with the television program source 104. This signal combining can be done at the audio level, or it can even be done at the RF level in the form of a different carrier. However, the preferred method is to merely sum the audio signal from the modulator 102 into the audio channel of the program that is generated by the television program source 104. The output thereof is provided from the mixing device 106 in the form of broadcast signal to an antenna 107, which transmits the information over the communication link 108 to an antenna 109 on the receive side.

On the receive side of the system, a conventional receiver 110, such as a television is provided. This television provides a speaker output which provides the user with an audible signal. This is typically associated with the program. However, the receiver 110 in the disclosed embodiment, also provides an audio output jack, this being the type RCA jack. This jack is utilized to provide an audio output signal on a line 113 which is represented by an audio signal 111. This line 113 provides all of the audio that is received over the

5

communication link **108** to the PC **112** in the audio input port on the PC **112**. However, it should be understood that, although a direct connection is illustrated from the receiver **110** to the PC **112**, there actually could be a microphone pickup at the PC **112** which could pick the audio signal up. In the disclosed embodiment, the audio signal generated by the advertiser data input device **100** is audible to the human ear and, therefore, can be heard by the user. Therefore, no special filters are needed to provide this audio to the PC **112**.

The PC **112** is operable to run programs thereon which typically are stored in a program file area **116**. These programs can be any type of programs such as word processing programs, application programs, etc. In the disclosed embodiment, the program that is utilized in the system is what is referred to as a "browser." The PC **112** runs a browser program to facilitate the access of information on the network, for example, a global communication network known as the "Internet" or the World-Wide-Web ("Web"). The browser is a hypertext-linked application used for accessing information. Hypertext is a term used to describe a particular organization of information within a data processing system, and its presentation to a user. It exploits the computer's ability to link together information from a wide variety of sources to provide the user with the ability to explore a particular topic. The traditional style of presentation used in books employs an organization of the information which is imposed upon it by limitations of the medium, namely fixed sized, sequential paper pages. Hypertext systems, however, use a large number of units of text or other types of data such as image information, graphical information, video information, or sound information, which can vary in size. A collection of such units of information is termed a hypertext document, or where the hypertext documents employ information other than text, hypermedia documents. Multimedia communications may use the Hypertext Transfer Protocol ("HTTP"), and files or formatted data may use the Hypertext Markup Language ("HTML"). This formatting language provides for a mingling of text, graphics, sound, video, and hypertext links by "tagging" a text document using HTML. Data encoded using HTML is often referred to as an "HTML document," an "HTML page," or a "home page." These documents and other Internet resources may be accessed across the network by means of a network addressing scheme which uses a locator referred to as a Uniform Resource Locator ("URL"), for example, "http://www.digital.com."

The Internet is one of the most utilized networks for interconnecting distributed computer systems and allows users of these computer systems to exchange data all over the world. Connected to the Internet are many private networks, for example, corporate or commercial networks. Standard protocols, such as the Transport Control Protocol ("TCP") and the Internet Protocol ("IP") provide a convenient method for communicating across these diverse networks. These protocols dictate how data are formatted and communicated. As a characteristic of the Internet, the protocols are layered in an IP stack. At higher levels of the IP stack, such as the application layer (where HTTP is employed), the user information is more readily visible, while at lower levels, such as the network level (where TCP/IP are used), the data can merely be observed as packets or a stream of rapidly moving digital signals. Superimposed on the Internet is a standard protocol interface for accessing Web resources, such as servers, files, Web pages, mail messages, and the like. One way that Web resources can be accessed is by browsers made by Netscape® and Microsoft Internet Explorer®.

6

Referring again now to FIG. 1, the user can load this program with the appropriate keystrokes such that a browser window will be displayed on a display **118**. In one embodiment, the user can run the browser program on the PC **112** such that the browser window is displayed on the display **118**. While watching a preferred program, the user can also view display **118**. When an audio signal is received by the receiver **110** and the encoded information is contained therein that was input thereto by the advertiser, the PC **112** will then perform a number of operations. The first operation, according to the disclosed embodiment, is to extract the audio information within the received audio signal in the form of digital data, and then transmit this digital data to a defined location on the global communication network via a modem connection **114**. This connection will be described hereinbelow. This information will be relayed to a proprietary location and the instructions sent back to the PC **112** as to the location of the advertiser associated with the code, and the PC **112** will then effect a communication link to that location such that the user can view on the display **118** information that the advertiser, by the fact of putting the tone onto the broadcast channel, desires the viewer to view. This information can be in the form of interactive programs, data files, etc. In one example, when an advertisement appears on the television, the tone can be generated and then additional data displayed on the display **118**. Additionally, a streaming video program could be played on the PC received over the network, which streaming video program is actually longer than the advertising segment on the broadcast. Another example would be a sports game that would broadcast the tone in order to allow a user access to information that is not available over the broadcast network, such as additional statistics associated with the sports program, etc.

By utilizing the system described herein with respect to the disclosed embodiment of FIG. 1, an advertiser is allowed the ability to control a user's PC **112** through the use of tones embedded within a program audio signal. As will be described hereinbelow, the disclosed embodiment utilizes particular routing information stored in the PC **112** which allows the encoded information in the received audio signal to route this information to a desired location on the network, and then allow other routing information to be returned to the PC **112** for control thereof to route the PC **112** to the appropriate location associated with that code.

Referring now to FIG. 2, there is illustrated a computer **204**, similar to computer **112**, connected to display information on display **118**. The computer **204** comprises an internal audio or "sound" card **206** for receiving the transmitted audio signal through receive antenna **109** and receiver **110**. The sound card **206** typically contains analog-to-digital circuitry for converting the analog audio signal into a digital signal. The digital signal may then be more easily manipulated by software programs. The receiver **110** separates the audio signal from the video signal. A special trigger signal located within the transmitted advertiser audio signal triggers proprietary software running on the computer **204** which launches a communication application, in this particular embodiment, the web browser application located on the PC **204**. Coded advertiser information contained within the audio signal is then extracted and appended with the address of a proprietary server located on the communication network.

The remote server address is in the form of a URL. This appended data, in addition to other control codes, is inserted directly into the web browser application for automatic routing to the communication network. The web browser running on PC **204**, and communicating to the network with

7

an internal modem **208**, in this embodiment, transmits the advertiser information to the remote server. The remote server cross-references the advertiser product information to the address of the advertiser server located on the network. The address of the advertiser server is routed back through the PC **204** web browser to the advertiser server. The advertiser product information is returned to PC **204** to be presented to the viewer on display **118**. In this particular embodiment, the particular advertiser product information displayed is contained within the advertiser's web page **212**. As mentioned above, the audio signal is audible to the human ear. Therefore the audio signal, as emitted from the TV speakers, may be input to the sound card **206** via a microphone. Furthermore, the audio signal need not be a real-time broadcast, but may be on video tapes, CDs, DVD, or other media which may be displayed at a later date. With the imminent implementation of high definition digital television, the audio signal output from the TV may also be digital. Therefore, direct input into a sound card for A/D purposes may not be necessary, but alternative interfacing techniques to accommodate digital-to-digital signal formats would apply.

Referring now to FIG. 3, there is illustrated a source PC **302**, similar to PCs **204** and **112**, connected to a global communication network ("GCN") **306** through an interface **304**. In this embodiment, the audio signal **111** is received by PC **302** through its sound card **206**. The audio signal **111** comprises a trigger signal which triggers proprietary software into launching a web browser application residing on the PC **302**. The audio signal **111** also comprises advertiser product information which is extracted and appended with URL information of an Advertiser Reference Server ("ARS") **308**. The ARS **308** is a system disposed on the GCN **306** that is defined as the location to which data in the audio signal **111** is to be routed. As such, data in the audio signal **111** will always be routed to the ARS **308**, since a URL is unique on the GCN **306**. Connected to the ARS **308** is a database **310** of product codes and associated manufacturer URLs. The database **310** undergoes a continual update process which is transparent to the user. As companies sign-on, i.e., subscribe, to this technology, manufacturer and product information is added to the database **310** without interrupting operation of the source PC **302** with frequent updates. When the advertiser server address URL is obtained from the ARS database **310**, it and the request for the particular advertiser product information are automatically routed back through the web browser on PC **302**, over to the respective advertiser server for retrieval of the advertiser product information to the PC **302**. Additionally, although the disclosed invention discusses a global communication network, the system is also applicable to LANs, WANs, and peer-to-peer network configurations. It should be noted that the disclosed architecture is not limited to a single source PC **302**, but may comprise a plurality of source PCs, e.g., PC **300** and PC **303**. Moreover, a plurality of ARS **308** systems and advertiser servers **312** may be implemented, e.g., ARS **314**, and advertiser server A **316**, respectively.

The information transactions, in general, which occur between the networked systems of this embodiment, over the communication network, are the following. The web browser running on source PC **302** transmits a message packet to the ARS **308** over Path "A." The ARS **308** decodes the message packet and performs a cross-reference function with product information extracted from the received message packet to obtain the address of an advertiser server **312**. A new message packet is assembled comprising the advertiser server **312** address, and sent back to the source PC **302**

8

over Path "B." A "handoff" operation is performed whereby the source PC **302** browser simply reroutes the information on to the advertiser server **312** over Path "C," with the appropriate source and destination address appended. The advertiser server **312** receives and decodes the message packet. The request-for-advertiser-product-information is extracted and the advertiser **312** retrieves the requested information from its database for transmission back to the source PC **302** over Path "D." The source PC **302** then processes the information, i.e., for display to the viewer. The optional Path "E" is discussed hereinbelow. It should be noted that the disclosed methods are not limited to only browser communication applications, but may accommodate, with sufficient modifications by one skilled in the art, other communication applications used to transmit information over the Internet or communication network.

Referring now to FIG. 4a, the message packet **400** sent from the source PC **302** to ARS **308** via Path "A" comprises several fields. One field comprises the URL of the ARS **308** which indicates where the message packet is to be sent. Another field comprises the advertiser product code or other information derived from the audio signal **111**, and any additional overhead information required for a given transaction. The product code provides a link to the address of the advertiser server **312**, located in the database **310**. Yet another field comprises the network address of the source PC **302**. In general, network transmissions are effected in packets of information, each packet providing a destination address, a source address, and data. These packets vary depending upon the network transmission protocol utilized for communication. Although the protocols utilized in the disclosed embodiment are of a conventional protocol suite commonly known as TCP/IP, it should be understood that any protocols providing the similar basic functions can be used, with the primary requirement that a browser can forward the routing information to the desired URL in response to keystrokes being input to a PC. Within the context of this disclosure, "message packet" shall refer to and comprise the destination URL, product information, and source address, even though more than a single packet must be transmitted to effect such a transmission.

Upon receipt of the message packet **400** from source PC **302**, ARS **308** processes the information in accordance with instructions embedded in the overhead information. The ARS **308** specifically will extract the product code information from the received packet **400** and, once extracted, will then decode this product code information. Once decoded, this information is then compared with data contained within the ARS advertiser database **310** to determine if there is a "hit." If there is no "hit" indicating a match, then information is returned to the browser indicating such. If there is a "hit," a packet **402** is assembled which comprises the address of the source PC **302**, and information instructing the source PC **302** as to how to access, directly in a "handoff" operation, another location on the network, that of an advertiser server **312**. This type of construction is relatively conventional with browsers such as Netscape® and Microsoft Internet Explorer® and, rather than displaying information from the ARS **308**, the source PC **302** can then access the advertiser server **312**. The ARS **308** transmits the packet **402** back to source PC **302** over Path "B." Referring now to FIG. 4b, the message packet **402** comprises the address of the source PC **302**, the URL of the advertiser server **312** embedded within instructional code, and the URL of the ARS **308**.

Upon receipt of the message packet **402** by the source PC **302**, the message packet **402** is disassembled to obtain

pertinent routing information for assembly of a new message packet 404. The web browser running on source PC 302 is now directed to obtain, over Path "C," the product information relevant to the particular advertiser server 312 location information embedded in message packet 404. Referring now to FIG. 4c, the message packet 404 for this transaction comprises the URL of the advertiser server 312, the request-for-product-information data, and the address of the source PC 302.

Upon receipt of the message packet 404 from source PC 302, advertiser server 312 disassembles the message packet 404 to obtain the request-for-product-information data. The advertiser server 312 then retrieves the particular product information from its database, and transmits it over Path "D" back to the source PC 302. Referring now to FIG. 4d, the message packet 406 for this particular transaction comprises the address of the source PC 302, the requested information, and the URL of the advertiser server 312.

Optionally, the ARS 308 may make a direct request for product information over Path "E" to advertiser server 312. In this mode, the ARS 308 sends information to the advertiser server 312 instructing it to contact the source PC 302. This, however, is unconventional and requires more complex software control. The message packet 408 for this transaction is illustrated in FIG. 4e, which comprises the URL of the advertiser server 312, the request-for-product-information data, and the address of the source PC 302. Since product information is not being returned to the ARS 308, but directly to the source PC 302, the message packet 408 requires the return address to be that of the source PC 302. The product information is then passed directly to PC 302 over Path "D."

Referring now to FIG. 5, the method for detecting and obtaining product information is as follows. In decision block 500, a proprietary application running resident on a source computer PC 302 (similar to PC 204) monitors the audio input for a special trigger signal. Upon detection of the trigger signal, data following the trigger signal is decoded for further processing, in function block 502. In function block 504, the data is buffered for further manipulation. In decision block 506, a determination is made as to whether the data can be properly authenticated. If not, program flow continues through the "N" signal to function block 520 where the data is discarded. In function block 522, the program then signals for a retransmission of the data. The system then waits for the next trigger signal, in decision block 500. If properly authenticated in decision block 506, program flow continues through the "Y" signal path where the data is then used to launch the web browser application, as indicated in function block 508. In function block 510, the web browser receives the URL data, which is then automatically routed through the computer modem 208 to the network interface 304 and ultimately to the network 306. In function block 514, the ARS 308 responds by returning the URL of advertiser server 312 to the PC 302. In function block 516, the web browser running on the source PC 302, receives the advertiser URL information from the ARS 308, and transmits the URL for the product file to the advertiser server 312. In block 518, the advertiser server 312 responds by sending the product information to the source PC 302 for processing.

The user may obtain the benefits of this architecture by simply downloading the proprietary software over the network. Other methods for obtaining the software are well-known; for example, by CD, diskette, or pre-loaded hard drives.

Referring now to FIG. 6, there is illustrated a flowchart of the process the ARS 308 may undergo when receiving the message packet 400 from the source PC 302. In decision block 600, the ARS 308 checks for the receipt of the message packet 400. If a message packet 400 is not received, program flow moves along the "N" path to continue waiting for the message. If the message packet 400 is received, program flow continues along path "Y" for message processing. Upon receipt of the message packet 400, in function block 602, the ARS 308 decodes the message packet 400. The product code is then extracted independently in function block 604 in preparation for matching the product code with the appropriate advertiser server address located in the database 310. In function block 606, the product code is then used with a lookup table to retrieve the advertiser server 312 URL of the respective product information contained in the audio signal data. In function block 608, the ARS 308 then assembles message packet 402 for transmission back to the source PC 302. Function block 610 indicates the process of sending the message packet 402 back to the source PC 302 over Path "B."

Referring now to FIG. 7, there is illustrated a flowchart of the interactive processes between the source PC 302 and the advertiser server 312. In function block 700, the source PC 302 receives the message packet 402 back from the ARS 308 and begins to decode the packet 402. In function block 702, the URL of the advertiser product information is extracted from the message packet 402 and saved for insertion into the message packet 404 to the advertiser server 312. The message packet 404 is then assembled and sent by the source PC 302 over Path "C" to the advertiser server 312, in function block 704. While the source PC 302 waits, in function block 706, the advertiser server 312 receives the message packet 404 from the source PC 302, in function block 708, and disassembles it. The product information location is then extracted from the message packet 404 in function block 710. The particular product information is retrieved from the advertiser server 312 database for transmission back to the source PC 302. In function block 712, the product information is assembled into message packet 406 and then transmitted back to the source PC 302 over Path "D." Returning to the source PC 302 in function block 714, the advertiser product information contained in the message packet 406 received from the advertiser server 312, is then extracted and processed in function block 716.

Referring now to FIG. 8, after receipt of a trigger signal, a web browser application on a source PC 302 is automatically launched and computer display 800 presents a browser page 802. Proprietary software running on the source PC 302 processes the audio signal data after being digitized through the sound card 206. The software appropriately prepares the data for insertion directly into the web browser by extracting the product information code and appending keystroke data to this information. First, a URL page 804 is opened in response to a Ctrl-O command added by the proprietary software as the first character string. Opening URL page 804 automatically positions the cursor in a field 806 where additional keystroke data following the Ctrl-O command will be inserted. After URL page 804 is opened, the hypertext protocol preamble http:// is inserted into the field 806. Next, URL information associated with the location of the ARS 308 is inserted into field 806. Following the ARS 308 URL data are the characters /? to allow entry of variables immediately following the /? characters. In this embodiment, the variable following is the product information code received in the audio signal. The product code information also provides the cross-reference information

11

for obtaining the advertiser URL from the ARS database 310. Next, a carriage return is added to send the URL/product data and close the window 804. After the message packet 400 is transmitted to the ARS 308 from the source PC 302, transactions from the ARS 308, to the source PC 302, to the advertiser server 312, and back to the source PC 302, occur quickly and are transparent to the viewer. At this point, the next information the viewer sees is the product information which was received from the advertiser server 312.

Referring now to FIG. 9, there is illustrated a block diagram of a more simplified embodiment. In this embodiment, a video source 902 is provided which is operable to provide an audio output on an audio cable 901 which provides routing information referred to by reference numeral 904. The routing information 904 is basically information contained within the audio signal. This is an encoded or embedded signal. The important aspect of the routing information 904 is that it is automatically output in realtime as a function of the broadcast of the video program received over the video source 902. Therefore, whenever the program is being broadcast in realtime to the user 908, the routing information 904 will be output whenever the producer of the video desires it to be produced. It should be understood that the box 902 representing the video source could be any type of media that will result in the routing information being output. This could be a cassette player, a DVD player, an audio cassette, a CD ROM or any such media. It is only important that this is a program that the producer develops which the user 908 watches in a continuous or a streaming manner. Embedded within that program, at a desired point selected by the producer, the routing information 904 is output.

The audio information is then routed to a PC 906, which is similar to the PC 112 in FIG. 1. A user 908 is interfaced with the PC to receive information thereof, the PC 906 having associated therewith a display (not shown). The PC 906 is interfaced with a network 910, similar to the network 306 in FIG. 3. This network 910 has multiple nodes thereon, one of which is the PC 906, and another of which is represented by a network node 912 which represents remote information. The object of the present embodiment is to access remote information for display to the user 908 by the act of transmitting from the video program in block 902 the routing information 904. This routing information 904 is utilized to allow the PC 906 which has a network "browser" running thereon to "fetch" the remote information at the node 912 over the network 910 for display to the user 908. This routing information 904 is in the form of an embedded code within the audio signal, as was described hereinabove.

Referring now to FIG. 10, there is illustrated a more detailed block diagram of the embodiment of FIG. 9. In this embodiment, the PC 906 is split up into a couple of nodes, a first PC 1002 and a second PC 1004. The PC 1002 resides at the node associated with the user 908, and the PC 1004 resides at another node. The PC 1004 represents the ARS 308 of FIG. 3. The PC 1004 has a database 1006 associated therewith, which is basically the advertiser database 310. Therefore, there are three nodes on the network 910 necessary to implement the disclosed embodiment, the PC 1002, the PC 1004 and the remote information node 912. The routing information 904 is utilized by the PC 1002 for routing to the PC 1004 to determine the location of the remote information node 912 on the network 910. This is returned to the PC 1002 and a connection made directly with the remote information node 912 and the information retrieved therefrom to the user 908. The routing information 904 basically constitutes primary routing information.

12

Referring now to FIG. 11, there is illustrated a diagrammatic view of how the network packet is formed for sending the primary routing information to the PC 1004. In general, the primary routing information occupies a single field which primary routing information is then assembled into a data packet with the secondary routing information for transfer to the network 910. This is described hereinabove in detail.

Referring now to FIG. 12, there is illustrated an alternate embodiment to that of FIG. 9. In this embodiment, the video source 902 has associated therewith an optical region 1202, which optical region 1202 has disposed therein an embedded video code. This embedded video code could be relatively complex or as simple as a grid of dark and white regions, each region in the grid able to have a dark color for a logic "1" or a white region for a logic "0." This will allow a digital value to be disposed within the optical region 1202. A sensor 1204 can then be provided for sensing this video code. In the example above, this would merely require an array of optical detectors, one for each region in the grid to determine whether this is a logic "1" or a logic "0" state. One of the sensed video is then output to the PC 906 for processing thereof to determine the information contained therein, which information contained therein constitutes the primary routing information 904. Thereafter, it is processed as described hereinabove with reference to FIG. 9.

Referring now to FIG. 13, there is illustrated a block diagram for an embodiment wherein a user's profile can be forwarded to the original subscriber or manufacturer. The PC 906 has associated therewith a profile database 1302, which profile database 1302 is operable to store a profile of the user 908. This profile is created when the program, after initial installation, requests profile information to be input in order to activate the program. In addition to the profile, there is also a unique ID that is provided to the user 908 in association with the browser program that runs on the PC 906. This is stored in a storage location represented by a block 1304. This ID 1304 is accessible by a remote location as a "cookie" which is information that is stored in the PC 906 in an accessible location, which accessible location is actually accessible by the remote program running on a remote node.

The ARS 308, which basically constitutes the PC 1004 of FIG. 10, is operable to have associated therewith a profile database 1308, which profile database 1308 is operable to store profiles for all of the users. The profile database 1308 is a combination of the stored in profile database 1302 for all of the PCs 906 that are attachable to the system. This is to be distinguished from information stored in the database 310 of the ARS 308, the advertiser's database, which contains intermediate destination tables. When the routing information in the primary routing information 904 is forwarded to the ARS 308 and extracted from the original data packet, the lookup procedure described hereinabove can then be performed to determine where this information is to be routed. The profile database 1302 is then utilized for each transaction, wherein each transaction in the form of the routing information received from the primary routing information 904 is compared to the destination tables of database 310 to determine what manufacturer is associated therewith.

The associated ID 1304 that is transmitted along with the routing information in primary routing information 904 is then compared with the profile database 1308 to determine if a profile associated therewith is available. This information is stored in a transaction database 1310 such that, at a later time, for each routing code received in the form of the information in primary routing information 904, there will

13

associated therewith the IDs **1304** of each of the PCs **906**. The associated profiles in database **1308**, which are stored in association with IDs **1304**, can then be assembled and transmitted to a subscriber as referenced by a subscriber node **1312** on the network **910**. The ARS **308** can do this in two modes, a realtime mode or a non-realtime mode. In a realtime mode, each time a PC **906** accesses the advertiser database **310**, that user's profile information is uploaded to the subscriber node **1312**. At the same time, billing information is generated for that subscriber **1312** which is stored in a billing database **1316**. Therefore, the ARS **308** has the ability to inform the subscriber **1312** of each transaction, bill for those transactions, and also provide to the subscriber **1312** profile information regarding who is accessing the particular product advertisement having associated therewith the routing information field **904** for a particular routing code as described hereinabove. This information, once assembled, can then be transmitted to the subscriber **1312** and also be reflected in billing information and stored in the billing information database **1316**.

Referring now to FIG. **14**, there is illustrated a flowchart depicting the operation for storing the profile for the user. The program is initiated in a block **1402** and then proceeds to a function block **1404**, wherein the system will prompt for the profile upon initiation of the system. This initiation is a function that is set to activate whenever the user initially loads the software that he or she is provided. The purpose for this is to create, in addition to the setup information, a user profile. Once the user is prompted for this, then the program will flow to a decision block **1406** to determine whether the user provides basic or detailed information. This is selectable by the user. If selecting basic, the program will flow to a function block **1408** wherein the user will enter basic information such as name and serial number and possibly an address. However, to provide some incentive to the user to enter more information, the original prompt in function block **1404** would have offers for such things as coupons, discounts, etc., if the user will enter additional information. If the user selects this option, the program flows from the decision block **1406** to a function block **1410**. In the function block **1410**, the user is prompted to enter specific information such as job, income level, general family history, demographic information and more. There can be any amount of information collected in this particular function block.

Once all of the information is collected, in either the basic mode or the more specific mode, the program will then flow to a function block **1412** where this information is stored locally. The program then flows to a decision block **1414** to then go on-line to the host or the ARS **308**. In general, the user is prompted to determine whether he or she wants to send this information to the host at the present time or to send it later. If he or she selects the "later" option, the program will flow to a function block **1415** to prompt the user at a later time to send the information. In the disclosed embodiment, the user will not be able to utilize the software until the profile information is sent to the host. Therefore, the user may have to activate this at a later time in order to connect with the host.

If the user has selected the option to upload the profile information to the host, the program will flow to the function block **1416** to initiate the connect process and then to a decision block **1418** to determine if the connection has been made. If not, the program will flow along a "N" path to a time to decision block **1420** which will timeout to an error block **1422** or back to the input of the connect decision block **1418**. The program, once connected, will then flow along a

14

"Y" path from decision block **1418** to a function block **1428** to send the profile information with the ID of the computer or user to the host. The ID is basically, as described hereinabove, a "cookie" in the computer which is accessed by the program when transmitting to the host. The program will then flow to a function block **1430** to activate the program such that it, at later time, can operate without requiring all of the setup information. In general, all of the operation of this flowchart is performed with a "wizard" which steps the user through the setup process. Once complete, the program will flow to a Done block **1432**.

Referring now to FIG. **15**, there is illustrated a flowchart depicting the operation of the host when receiving a transaction. The program is initiated at a Start block **1502** and then proceeds to decision block **1504**, wherein it is determined whether the system has received a routing request, i.e., the routing information **904** in the form of a tone, etc., embedded in the audio signal, as described hereinabove with respect to FIG. **9**. The program will loop back around to the input of decision block **1504** until the routing request has been received. At this time, the program will flow along the "Y" path to a function block **1506** to receive the primary routing information and the user ID. Essentially, this primary routing information is extracted from the audio tone, in addition to the user ID. The program then flows to a function block **1508** to look up the manufacturer URL that corresponds to the received primary routing information and then return the necessary command information to the originating PC **108** in order to allow that PC **108** to connect to the destination associated with the primary routing information. Thereafter, the program will flow to a function block **1510** to update the transaction database **1310** for the current transaction. In general, the routing information **904** will be stored as a single field with the associated IDs. The profile database **1308**, as described hereinabove, has associated therewith detailed profiles of each user on the system that has activated their software in association with their ID. Since the ID was sent in association with the routing information, what is stored in the transaction database **1310** is the routing code, in association with all of the IDs transmitted to the system in association with that particular routing code. Once this transaction database **1310** has been updated, as described hereinabove, the transactions can be transferred back to the subscriber at node **312** with the detailed profile information from the profile database **1308**.

The profile information can be transmitted back to the subscriber or manufacturer at the node **312** in realtime or non-realtime. A decision block **1512** is provided for this, which determines if the delivery is realtime. If realtime, the program will flow along a "Y" path to a function block **1514** wherein the information will be immediately forwarded to the manufacturer or subscriber. The program will then flow to a function block **1516** wherein the billing for that particular manufacturer or subscriber will be updated in the billing database **1316**. The program will then flow into an End block **1518**. If it was non-realtime, the program moves along the "N" path to a function block **1520** wherein it is set for a later delivery and it is accrued in the transaction database **1310**. In any event, the transaction database **1310** will accrue all information associated with a particular routing code.

With a realtime transaction, it is possible for a manufacturer to place an advertisement in a magazine or to place a product on a shelf at a particular time. The manufacturer can thereafter monitor the times when either the advertisements are or the products are purchased. Of course, they must be scanned into a computer which will provide some delay.

15

However, the manufacturer can gain a very current view of how a product is moving. For example, if a cola manufacturer were to provide a promotional advertisement on, for example, television, indicating that a new cola was going to be placed on the shelf and that the first 1000 purchasers, for example, scanning their code into the network would receive some benefit, such as a chance to win a trip to some famous resort in Florida or some other incentive, the manufacturer would have a very good idea as to how well the advertisement was received. Further, the advertiser would know where the receptive markets were. If this advertiser, for example, had placed the television advertisement in ten cities and received overwhelming response from one city, but very poor response from another city, he would then have some inclination to believe that either the one poor-response city was not a good market or that the advertising medium he had chosen was very poor. Since the advertiser can obtain a relatively instant response and also content with that response as to the demographics of the responder, very important information can be obtained in a relatively short time.

It should be noted that the disclosed embodiment is not limited to a single source PC 302, but may encompass a large number of source computers connected over a global communication network. Additionally, the embodiment is not limited to a single ARS 308 or a single advertiser server 312, but may include a plurality of ARS and advertiser systems, indicated by the addition of ARS 314 and advertiser server A 316, respectively. It should also be noted that this embodiment is not limited only to global communication networks, but also may be used with LAN, WAN, and peer-to-peer configurations.

It should also be noted that the disclosed embodiment is not limited to a personal computer, but is also applicable to, for example, a Network Computer ("NetPC"), a scaled-down version of the PC, or any system which accommodates user interaction and interfaces to information resources.

One typical application of the above noted technique is for providing a triggering event during a program, such as a sport event. In a first example, this may be generated by an advertiser. One could imagine that, due to the cost of advertisements in a high profile sports program, there is a desire to utilize this time wisely. If, for example, an advertiser contracted for 15 seconds worth of advertising time, they could insert within their program a tone containing the routing information. This routing information can then be output to the user's PC 302 which will cause the user's PC 302 to, via the network, obtain information from a remote location typically controlled by the advertiser. This could be in the form of an advertisement of a length longer than that contracted for. Further, this could be an interactive type of advertisement. An important aspect to the type of interaction between the actual broadcast program with the embedded routing information and the manufacturer's site is the fact that there is provided information as to the user's PC 302 and a profile of the user themselves. Therefore, an advertiser can actually gain realtime information as to the number of individuals that are watching their particular advertisement and also information as to the background of those individuals, profile information, etc. This can be a very valuable asset to an advertiser.

In another example, the producer of the program, whether it be an on-air program, a program embedded in a video tape, CD-ROM, DVD, or a cassette, can allow the user to automatically access additional information that is not displayed on the screen. For example, in a sporting event, various statistics can be provided to the user from a remote location,

16

merely by the viewer watching the program. When these statistics are provided, the advertiser can be provided with profile information and background information regarding the user. This can be important when, for example, the user may record a sports program. If the manufacturer sees that this program routing code is being output from some device at a time later than the actual broadcast itself, this allows the advertisers to actually see that their program is still being used and also what type of individual is using it. Alternatively, the broadcaster could determine the same and actually bill the advertiser an additional sum for a later broadcast. This is all due to the fact that the routing information automatically, through a PC and a network, will provide an indication to the advertiser the time at which the actual information was broadcast.

The different type of medium that can be utilized with the above embodiment are such things as advertisements, which are discussed hereinabove, contests, games, news programs, education, coupon promotional programs, demonstration media (demos), and photographs, all of which can be broadcast on a private site or a public site. This all will provide the ability to allow realtime interface with the network and the remote location for obtaining the routed information and also allow for realtime billing and accounting.

Referring now to FIG. 16, there is illustrated a general block diagram of a disclosed embodiment. A bar code scanning input device 1600 is provided by a input device distributor to customers and is associated with that distributor via a input device ID stored therein. The input device 1600 is either sold or freely distributed to customers for use with their personal computing systems. Since more and more products are being sold using bar codes, it can be appreciated that a user having the input device 1600 can scan bar codes of a multitude of products in order to obtain more information. Information about these products can be made immediately available to the user from the manufacturer for presentation by the user's computer 302. Beyond simply displaying information about the product in which the user is interested, the input device distributor may include additional advertising information for display to the user such as information about other promotions or products provided or sold by the input device distributor. Similarly, advertisers may provide catalogs of advertisements or information in newspapers or periodicals where the user simply scans the bar code associated with the advertisement using the input device 1600 to obtain further information. There is provided a paper source 1602 having contained thereon an advertisement 1604 and an associated bar code 1606. (Note that the disclosed concept is not limited to scanning of bar codes 1606 from paper sources 1602, but is also operable to scan a bar code 1606 on the product itself. Also, the input device 1600 can be any type of device that will scan any type of image having information encoded therein.)

After obtaining the input device 1600 from the input device distributor, the user connects the input device 1600 to their PC 302. During a scanning operation, input device 1600 reads bar code data 1606 and the input device ID into a "wedge" interface 1608 for conversion into keyboard data, which keyboard data is passed therefrom into the keyboard input port of PC 302. The importance of the input device ID will be discussed in more detail hereinbelow.

The wedge interface 1608 is simply an interface box containing circuitry that accommodates inputs from both the scanning input device 1600 and a computer keyboard 1610. This merely allows the information scanned by the input device 1600 to be input into the PC 302. In the disclosed

17

embodiment, the wedge interface **1608** will convert any information. The data output from the input device **1600** is passed into the wedge interface **1608** for conversion into keyboard data which is readily recognizable by the PC **302**. Therefore, the input device **1600** is not required to be connected to a separate port on the PC **302**. This data is recognized as a sequence of keystrokes. However, the output of the input device **1600** can be input in any manner compatible with the PC **302**. When not receiving scanner data, the wedge interface **1608** simply acts as a pass-through device for keyboard data from the keyboard **1610**. In any case, the information is ultimately processed by a processor in the PC **302** and can be presented to the user on a display **1612**. The wedge interface **1608** is operable to provide a decoding function for the bar code **1606** and conversion thereof to keystroke input data.

In operation, the product code of a product is provided in the form of a bar code **1606**. This bar code **1606** is the "link" to a product. The disclosed embodiment is operable to connect that product information contained in the bar code **1606** with a web page of the manufacturer of that product by utilizing the bar code **1606** as the product "identifier." The program operating on the PC **302** provides routing information to the ARS **308** after launching the browser on the PC **302** and connecting to the ARS **308** over the GCN **306**, which ARS **308** then performs the necessary steps to cause the browser to connect to the manufacturer web site, while also providing for an accounting step, as will be described in more detail hereinbelow.

The bar code **1606** by itself is incompatible with any kind of network for the purposes of communication therewith. It is primarily provided for a retail-type setting. Therefore, the information contained in the bar code **1606**, by itself, does not allow for anything other than identification of a product, assuming that one has a database **1614** containing information as to a correlation between the product and the bar code **1606**.

The wedge interface **1608** is operable to decode the bar code **1606** to extract the encoded information therein, and append to that decoded bar code information relating to an ID for the input device **1600**. This information is then forwarded to the ARS **308** by the resident program in the PC **302**. This is facilitated by intermediate routing information stored in the program indicating to which node on the GCN **306** the scanned bar code information is to be sent, i.e., to the ARS **308**. It is important to note that the information in the bar code **1606** must be converted from its optical image to numerical values which are then ultimately input to the keyboard input port of PC **302** and converted into data compatible with communication software residing on the PC **302** (in this case, HTML language for insertion into a browser program). When the scanned information is input to the PC **302**, the resident program launches the browser program and then assembles a communication packet comprised of the URL of the ARS **308**, the input device ID and the user ID. If another type of communications program were utilized, then it would have to be converted into language compatible with that program. Of course, a user could actually key in the information on the bar code **102** and then append the appropriate intermediate routing information thereafter. As will be described hereinbelow, the intermediate routing information appended thereto is the URL of the ARS **308** disposed on the GCN **306**.

As part of the configuration for using the input device **1600**, the PC **302** hosts input device software which is operable to interpret data transmitted from the input device **1600**, and to create a message packet having the scanned

18

product information and input device ID, routing information, and a user ID which identifies the user location of the input device **1600**. The input device software loads at boot-up of the PC **302** and runs in the background. In response to receiving a scanned bar code **1606**, the wedge interface **1608** outputs a keystroke code (e.g., ALT-F10) to bring the input device program into the foreground for interaction by the operating system. The input device program then inserts the necessary information into the browser program. The message packet is then transmitted to interface **304** across the global communication network **306** to the ARS **308**. The ARS **308** interrogates the message packet and performs a lookup function using the ARS database **310**. If a match is found between particular parameters of the message packet, a return message packet is sent back to the PC **302** for processing.

The input device program running on PC **302** functions to partition the browser window displayed to the user into several individual areas. This is for the purpose of preparing to present to the user selected information in each of the individual areas (also called "framing"). The selected information comprises the product information which the user requested by scanning the bar code **1606** using the input device **1600**, information about the input device distributor which establishes the identity of the company associated with that particular input device **1600**, and at least one or more other frames which may be advertisements related to other products that the input device distributor sells. Note that the advertisements displayed by the input device distributor may be related to the product of interest or totally unrelated. For example, if a user scans the bar code **1606** of a soda from Company A, the input device distributor may generate an advertisement of a new soft drink being marketed by Company A, that it sells. On the other hand, the input device distributor may also structure the display of information to the user such that a user requesting product information of a Product X may get the requested information of Product X along with advertisements for a competing item Product Y. Essentially, the input device distributor is free to generate any advertisement to the user in response to the user requesting product information.

The return message packet transmitted from the ARS **308** to the PC **302** is then transmitted back across the GCN **306** to the advertiser server **312**. The advertiser server **312** restructures the message packet and appends the particular product information for transmission back to the PC **302**. Upon receiving the particular advertiser information from advertiser server **312**, the PC **302** then retransmits a message to the input device distributor site **1616** and E-commerce site **1618** to obtain the information that needs to be framed in the browser window displayed to the user.

Therefore, the input device **1600** is associated with the input device distributor by way of a input device ID such that scanning a product bar code **1606** in order to obtain information about that particular product generates one or more responses from one or more remote sites disposed on the GCN **306**. Stored in the input device **1600** is the input device ID which establishes its relationship to the input device distributor. Proprietary input device software running on the PC **302** operates to decode scanned bar code information and the input device ID received from the input device **1600** and wedge interface **1608**, and also provides a unique user ID for establishing the location of the user of the input device **1600**. The input device software also assembles message packets and works in conjunction with the on-board communication software (e.g., a browser) to automatically route the message packets across the GCN **306** such that the

19

one or more remote sites disposed on the GCN 306 return information to be framed for presentation to the user.

Referring now to FIG. 17, there is illustrated a conversion circuit of the wedge interface. A microcontroller 1700 provides conversion of the data from the input device 1600 and controls interfacing of the keyboard 1610 and input device 1600 with the PC 302. The microcontroller 1700 has contained therein a memory 1702 or it can have external memory. There are provided a plurality of input device interfaces 1704 to the input device 1600, a plurality of PC interfaces 1706 to the PC 302, and plurality of keyboard interfaces 1708 to the keyboard 1610. In general, the input device interfaces 1704 comprise a serial data line, a ground line, and a power line. Similarly, the keyboard interfaces 1708 comprise a serial data line, a ground line, a clock line, and a power line. The PC 302 provides a clock line, a power line, a serial data, and a ground line for input to the microcontroller 1700. The microcontroller 1700 is operable to receive signals from the keyboard 1610 and transfer the signals to the PC 302 as keyboard signals. Operation with the keyboard 1610 is essentially a "pass-through" procedure. Data output from the keyboard 1610 is already in keyboard format, and therefore requires no conversion by the wedge interface 1608. With respect to the input device 1600, the serial data is not compatible with a keyboard 1610 and, therefore, it must be converted into a keyboard format in order to allow input thereof to the keyboard input of the PC 302.

The microcontroller 1700 performs this function after decoding this bar code information, and conversion of this bar code information into an appropriate stream of data which is comprised of the bar code information and the appended URL. This appended URL will be pre-stored in the memory 1702 and is programmable at the time of manufacture. It is noted that the memory 1702 is illustrated as being contained within the microcontroller 1702 to provide a single chip solution. However, this could be external memory that is accessible by the microcontroller 1702. Therefore, the microcontroller 1700 provides an interface between the input device 1600 and the keyboard 1610 to the PC 302 which allows the input device 1600 to receive coded information and convert it to keyboard strokes or, alternatively, to merely pass-through the keystrokes from the keyboard 1610. Therefore, the user need not install any type of plug-in circuit board into the motherboard of the PC 302 in order to provide an interface to the input device 1600; rather, the user need only utilize the already available keyboard port in order to input the appropriate data into the system.

In this particular disclosed embodiment, the microcontroller 1700 comprises a PIC 16C73 microcontroller by Microchip Technologies™. The PIC 16C73 device is a low cost CMOS 8-bit microcontroller with an integrated analog-to-digital converter. The PIC16C73 device, as illustrated in the disclosed embodiment, has 192 bytes of RAM and 4k×4 of EPROM memory. The microcontroller 1700 can accommodate asynchronous or synchronous inputs from input devices connected to it. In this disclosed embodiment, communication to the keyboard 1610 is synchronous while it is asynchronous when communicating with input device 1600.

It should be noted that, although in this particular embodiment bar code information of the bar code 1606 is input into the keyboard input port of the PC 302, disclosed methods may also be advantageously utilized with high speed port architectures such as Universal Serial Bus ("USB") and IEEE 1394.

20

Bar codes are structured to be read in either direction. Timing considerations need to be addressed because of the variety of individuals scanning the bar code introduce a wide variety of scan rates. Bar codes use bars of varying widths. The presence of a black bar generates a positive pulse, and the absence of a black bar generates no pulse. Each character of a conventional bar code has associated therewith seven pulses or bars. Depending on the width of the bars, the time between pulses varies. In this disclosed embodiment, the interface circuitry 1608 performs a "running" calculation of the scan time based upon the rising edge of the pulses commencing with the leader or header information. The minimum and maximum scans times are calculated continuously in software with the interface 1608 during the scanning process to ensure a successful scan by the user.

Referring now to FIG. 18, there is illustrated a sample message packet transmitted from the user's PC 302 to the ARS 308. The message packet 1800 comprises a number of bits of information including the bar code information 1802 obtained from the user scanning the bar code 1606 with the input device 1600; the input device ID 1804 which is embedded in a memory in the input device 1600 and identifies it with a particular input device distributor; and a user ID 1806 which is derived from the software running on the PC 302 and which identifies uniquely with the user location. Note that the message packet includes other necessary information for the proper transmission for point to point.

Referring now to FIG. 19, there is illustrated a more detailed block diagram of the routing of the message packets in order to present the framed information to the user. As is mentioned hereinabove, when the user scans a bar code 1606 using the input device 1600, a input device program running on the user PC 302 is operable to interpret the information output by the input device 1600 and generate a message packet for transmission over the GCN 306. The input device program assembles the message packet such that it is directed to the ARS 308 disposed on the GCN 306. The message packet contains several pieces of information including the input device ID 1804 which links it to the input device distributor, the user ID 1806 which identifies the particular user using the input device 1600, and bar code information 1802 describing a particular product of interest to the user. This message from the PC 302 is transmitted over a path 1900 to the ARS 308 where the ARS database 310 is accessed to cross reference the ID information 1804 and bar code information 1802 to a particular advertiser and input device distributor. The ARS 308 returns a message packet over a path 1902 to the user PC 302 which contains routing information as to the location of various other sites disposed on the GCN 306, for example, the advertiser server 312 and input device distributor site 1616.

It can be appreciated that other information can also be provided by the ARS 308 which more closely targets the particular user of the input device 1600. For example, if it is known that a particular input device 1600 is sold in a certain geographic area, this information can be useful in targeting the particular user with certain advertising information relevant to that geographic area. In any case, the information returned from the ARS 308 over path 1902 provides enough information for the input device program running on the user PC 302 to identify a number of other sites disposed on the GCN 306. The user PC 302 then processes the return message packet and routes another message packet over a path 1904 to the advertiser server 312. The advertiser server 312 then returns product information of the particular product in which the user was interested back to the user PC 302.

21

over a path **1906**. Similarly, the user PC **302** routes information (e.g., the URL of the input device distributor site and the user profile) to the input device distributor site **1616** over a path **1908** in order to obtain information back over a path **1910** for framing any banners which identify the input device distributor. Additionally, the user PC **302** forwards a message packet to the E-commerce site **1618** over a path **1912** in order to return information regarding any particular advertisements the input device distributor wants to display to the user. The advertisements are returned to the PC **302** over a path **1914**.

Referring now to FIG. **20**, there is illustrated a block diagram of a browser window according to the disclosed embodiment. The browser window **2000** is partitioned into a plurality of areas for framing specific information. A bar code area **2002** displays that product information in which the user was interested; an input device-specific area **2004** displays information about the input device distributor; and an E-commerce area **2006** displays advertising information that the input device distributor selects for display according to this particular user and input device **1600**. As mentioned hereinabove, a program operable to process scanned bar code information with the unique input device **1600** develops the browser window by partitioning it into specific areas for the framing of information. Therefore, information returned from the E-commerce site **1608** is passed through the GCN **306** to the particular E-commerce frame **2006**. Similarly, information about the particular product of interest is returned from the advertiser site **312** across the GCN **306** to the particular bar code specific area **2002**. Information placed in the input device specific area **2004** is information about the input device distributor which is returned from the input device distributor site **1616** across GCN **306**.

Referring now to FIG. **21**, there is illustrated a structure of information contained in the ARS database. The ARS database **310** contains a variety of information required to properly interrogate and assemble packets for obtaining information from the various sites disposed on the GCN **306**. The ARS database **310** has a database structure **2100** which contains addresses for the web sites containing the product information requested by the user when scanning the bar code **1606** with the input device **1600**. Under a PRODUCT heading **2102** are listed the particular bar codes and associated routing information for addressing the respective server location. For example, the ARS server **308** may contain any number of advertisers having unique URL addresses associated therewith. Therefore, the bar code **1606** of a particular product is associated with a unique URL address which routes any request for information of that product to that particular advertiser's site. Also part of the ARS database structure **2000** is a heading of INPUT DEVICE under which is the input device ID **1804** and the distributor associated with that input device ID **1804**.

It can be appreciated that there may be a number of distributors using the disclosed architecture such that each distributor has an ID embedded in the input device **1600** which uniquely identifies that input device with the particular distributor. Therefore, the unique input device ID **1804** needs to be listed with the respective distributors of that input device **1600** in order to process the information that needs to be framed and displayed to that particular user. Another heading under the ARS database structure **2100** is a user heading **2106** which contains profile information associated with that particular user ID **1806**. As mentioned hereinabove, the user ID **1806** is obtained via the input device software running on the PC **302** and upon installation or subsequent configuration may request that the user input

22

certain profile information which may be used to target that particular user with products and services which identify with that user profile. The ARS database structure **2100** also contains an E-commerce heading **2108** which contains information related to the bar code **1606** and an advertisement that may be triggered by the request for that information. For example, any bar code **1606** associated with a paper source **1602** can be associated with the specific information in the ARS database **310**. A user wishing to obtain information about a specific soft drink may, in fact, trigger an advertising response of a competitor product. Similarly, the user interested in information about that particular soft drink may also trigger information which is relevant to that particular product or a product which may normally be served in conjunction with that soft drink. Furthermore, if the user profile indicates that this individual has significant interest in finance or insurance, the request for information regarding this particular bar coded product may trigger advertisement from an E-commerce server **1618** related to information about finance and insurance. It should be noted that the information described as contained within the ARS database structure **2100** is not limited to what has been described, but may comprise any number of pieces of information used to present desired information to the computer display of the user.

Referring now to FIG. **22**, there is illustrated a flowchart of the process of receiving information from the user's perspective, and according to the disclosed embodiment. The input device software running on the user's PC **302** runs in the background until activated by output from the input device **1600**. Therefore, flow moves to a decision block **2200** where if a scanned input does not occur, flow moves out the "N" path and loops back to the input of decision block **2200**. On the other hand, if scanned input information is received, flow moves out the "Y" path to a function block **2202** where the input device software assembles a message packet containing the bar code information, the input device ID **1804** and the ARS **308** URL address. Additionally, the browser is launched in which this information is placed for transmission to the ARS **308**. Flow then moves to a function block **2204** where the browser is partitioned into any number of areas in which information is displayed when obtained from the input device distributor site **1616**, the E-commerce site **1618**, and the advertiser server **312**. It should be known that although three frames are shown in the particular window **2000** of this embodiment, the number of frames displayed in the window **2000** is limited only by the available real estate of the window **2000** area itself.

After the input device software partitions the browser window into one or more frames in preparation of receipt of return information, flow moves to a decision block **2206** where the computer waits for information to be returned from the various sites disposed on the GCN **306**. If information is not returned, flow moves out the "N" path and simply loops back to the input to continue monitoring for receipt of the information. If information has been received, flow moves out the "Y" path to a function block **2208** where routing information for each frame (or partitioned area of the window **2000**) is inserted into one or more packets for transmission to the various sites. The various sites then return the requested information back to the PC **302**, as indicated in function block **2210**. Flow is then to a function block **2212** where the proprietary software working in conjunction with the hosted browser places the returned information into the respective frames of the window. The user, viewing the display at PC **302**, then perceives a variety of information, one of which is the particular product

23

information which he or she requested, in addition to input device distributor information, and possibly other advertisements based upon the user's profile.

Referring now to FIG. 23, there is illustrated a flowchart of the process according to the ARS. The ARS 308 is operable to decode and process messages received from the GCN 306. Therefore, flow is to a decision block 2300 where, if bar code information is not received, flow is out the "N" path with loop-back to its input. If bar code information has been received, flow is to a function block 2302 where a matching process occurs to link the bar-coded product information to its respective manufacturer. The ARS database 310 also associates the URL address of the manufacturer's server. When a match is found, the ARS 308 begins to assemble a message packet of information for transmission back to the PC 302, as indicated in function block 2304. The message packet contains the product information and the URL address of the manufacturer's website. Flow then moves to a decision block 2306 where the input device ID 1804 is compared with the list of input device IDs issued by the particular input device distributor. If the input device ID 1804 is validated, flow moves out the "Y" path to a function block 2308 where the message packet is appended with the input device ID 1804 and distributor routing address. Flow then moves to a decision block 2310 where the ARS 308 determines if any E-commerce information is to be associated with a particular input device ID 1804. If so, flow is out the "Y" path to a function block 2312 where the message packet is appended with the E-commerce routing string. The E-commerce routing string provides addressing for the E-commerce server 1618. Flow then moves to a function block 2314 where all message packets are returned back to the PC 302 for processing.

Referring back to decision block 2306, if the input device ID 1804 is determined to be invalid, flow moves out the "N" path and jumps forward to the input of decision block 2314, since the lack of a input device ID 1804 interrupts the link to any advertising provided by the E-commerce server 1618. At this point, the only information provided is the link to the advertiser server 312 for return of product information. Referring now to decision block 2310, if no E-commerce information is available, flow moves out the "N" path and jumps forward to the input of function block 2314 where the message packet back to the PC 302 contains only the URL of the advertiser server 312, the bar code information, the distributor server 1616 address and input device ID 1804 information.

Referring now to FIG. 24, there is illustrated a flowchart of the process performed at the E-commerce site. The E-commerce server 1618 receives the message packet from the user PC 302, as indicated in function block 2400, and decodes the packet to perform a match with the bar coded information. Moving on to a decision block 2402, if the match is unsuccessful, flow is out the "N" path to a function block 2404 where the match is rejected. A message may be returned to indicate that a problem occurred and the user may need to re-scan the product bar code 1606. If a successful match occurs, flow moves out the "Y" path to a function block 2406 where the input device ID 1804 is matched with the bar code product information. The bar coded information may be distributed to customers over a large geographic area. However, the input device 1606 may be coded for certain geographic areas. For example, a input device 1600 having an XXX ID may be restricted for sale in the Southwestern United States while a input device 1600 having a YYY ID may be sold only in the Northeast. In this way, geographic areas may be targeted with advertising

24

more appealing to that particular area. Advertising returned to the user PC 302 may be focused further by obtaining a user profile when the software or input device 1600 are installed. In this way, advertising may be focused based upon the user profile. Therefore, flow moves to a function block 2408 to lookup the E-commerce action based upon the input device ID 1804 and the bar code information. Flow moves to a function block 2410 to assemble all the information into a packet for return to the user PC 302. The product information and/or user profile information may be returned. Flow is then to a function block 2412 where the message packet is transmitted.

Referring now to FIG. 25, there is illustrated an optical reader which can be used for scanning an optical code, for example a bar code, and delivering signals indicative of the optical code to a computer. Reader 2500 typically includes an outer shell 2502 enclosing the working components and shaped for convenient manual grasping by the user. During operation, the front end 2504 of the reader 2500 is brought into contact with (or very close proximity to) a surface 2506 bearing the optical code to be read, for example barcode 2508. The reading operation begins with the reader 2500 positioned at a starting position (shown in phantom and denoted by reference numeral 2510) to one side of the barcode 2508. The reader 2500 is then moved across the barcode 2508 as indicated by arrow 2512 to a final position (shown in phantom and denoted by reference numeral 2514) on the opposite side. Typically, the reader 2500 must be moved across the barcode 2508 at a substantially constant speed to ensure accurate reading of the symbol. Once the optical symbol has been scanned by the optical reader 2500, internal circuitry produces electronic output signals indicative of the symbol. These electronic output signals are provided to a computer (not shown), typically by means of a wired control cord 2516. Alternately, the output signals may be sent from the reader 2500 to the computer using other known transmission technologies, for example using a wireless radio frequency (RF) link or a wireless infrared (IR) link.

Referring now to FIGS. 26 and 27, there are illustrated external views of optical reader 2500 according to an embodiment of the invention. Typically, the outer shell 2502 of the reader 2500 will be constructed from multiple pieces to allow simple assembly of the internal components. For example, the illustrated embodiment includes an upper shell 2702 and a lower shell 2704 which form a hollow interior cavity within which the internal components are mounted. To provide for easier gripping and to prevent the device from rolling across flat surfaces, the upper shell 2702 may have a generally semi-circular cross section and the lower shell 2704 may have a generally flat cross section. A scanning portal 2706 is provided at the front end 2504 of reader 2500 to allow the interior components to project and collect radiant energy during the scanning operation. The scanning portal 2706 is typically covered by a protective window 2708 which is transparent to the radiant energy wavelength used for scanning. Projection and/or collection lenses may be visible behind the window 2708. For example, in FIG. 27, a collection lens 2710 and a projection lens 2712 are visible through the window 2708.

To assist the user in maintaining the proper orientation of the reader 2500 during the scanning operation (i.e., with the front end 2504 substantially flat against the surface 2506 bearing the optical symbol, the front end 2504 may be adapted to form a substantially flat bearing surface 2602 surrounding the scanning portal 2708. The bearing surface 2602 is preferably substantially perpendicular to the axis

25

2604 of the collection portion of the optical system. To reduce the likelihood that the scanning window **2708** will be scratched during the scanning process, it may be inset slightly behind the plane of the bearing surface **2602**. The window **2708** may be further protected by the provision of pads **2606** on external shell **2502** which project slightly ahead of the bearing surface **2602**.

The external shell **2502** of the reader **2500** may be contoured to provide a comfortable grasp for the user and/or to have an attractive or distinctive shape. For example, the upper shell **2702** of the reader **2500** is smoothly contoured to provide a "streamlined" appearance in accordance with a common style used on other computer related devices such as a computer mouse, a track ball, etc. In other embodiments, however, the exterior shell may be contoured to provide a more distinctive appearance. The exterior surface of the outer shell **2502** further provides an area **2607** for the placement of identifying or advertising indicia **2608** (shown in phantom). Such indicia, if present, may be formed by printing or painting directly on the exterior surface of the reader **2500**, by the application of discrete labels, and/or by molding letters, designs or other indicia directly into the surface of the reader by means of injection molding or a similar process.

Referring now to FIGS. **33-35**, there is illustrated an alternative embodiment of the invention. Optical reader **3300** has an exterior shell **3302** contoured to resemble an animal, in this case, a stylized cat. It will be readily appreciated that, except for the recontoured shell **3302**, the features described for the previous embodiment are present in substantially identical form in this embodiment, including the scanning portal **2706**, window **2708**, bearing surface **2602** and pads **2606**. In addition, identifying or advertising indicia **2608** may be placed on the stylized shell of reader **3300** in the same fashion as on the previous embodiment. It will further be apparent that the external shell of the reader can be contoured to resemble other animals, e.g., dogs, birds, reptiles, fish, etc. or other objects including automobiles, trucks, trains, aircraft, etc. without departing from the scope of the current invention.

Referring now to FIG. **28**, there is illustrated a general block diagram showing the function of an optical reader in accordance with embodiments of the current invention. A radiant energy source **2802** is provided for generating a radiant energy which will be used for illuminating a target region containing the barcode or other symbol to be scanned. The radiant energy, denoted by arrow **2804**, is transmitted from the source **2802** into an optical system **2806**. The radiant energy is typically light in the visible wavelength, however light of infrared (IR) wavelength or other forms of radiant energy may be used. The optical system **2606**, which will be described in further detail below, directs the radiant energy (now denoted by arrow **2807**) into a target region **2808** adjacent to the reader. The radiant energy directed into the target region **2808** illuminates a barcode **2810** present therein and causes an image, denoted by arrow **2812**, of the barcode to be reflected back into another portion of the optical system **2806**. The reflected image of the barcode passes through the optical system **2806** where it is processed to increase its contrast and decrease its luminance. After processing, the image, denoted now by arrow **2814**, is directed by the optical system **2806** onto a photodetector **2816**, which produces output electrical signals indicative of the radiant energy incident thereon. The output electrical signals, denoted by arrow **2818**, are routed to a decoder circuit **2820**, which utilizes electronic circuitry to decode the output electrical signals to provide an indication of the

26

information contained in the barcode **2810**. The information, denoted by reference numeral **2822**, is then transmitted to an external computer **2824** for further use or processing.

Typically, the decoded information **2822** is transmitted to the external computer **2824** in accordance with a known data interface format. Suitable data interface formats for transmission of the barcode information from the decoder circuit **2820** of the reader to an external computer **2824** include an output signal which emulates computer keyboard keystrokes such as those in accordance with the PS/2 keyboard interface standard or the AT keyboard interface standard. Alternately, the output signals may be formatted in accordance with other known data interface or communication standards, including the Universal Serial Bus (USB) standard, the RS-232 standard, the RS-423 standard, the IEEE 1394 (FIREWIRE) standard, the Integrated Drive Electronics (IDE) interface standard, the Enhanced Integrated Drive Electronics (EIDE) interface standard, the Asynchronous Transfer Mode (ATM) transmission standard, the Fiber Distributed Data Interface (FDDI) interface standard, the 8-Bit Industry Standard Architecture (ISA) bus standard, the 16-bit Industry Standard Architecture (ISA) bus standard, the VL-Bus bus standard, the Peripheral Component Interconnect (PCI) bus standard, the Personal Computer Memory Card International Association (PCMCIA) bus standard, the Centronics Parallel Port (CPP) standard, the Enhanced Parallel Port (EPP) standard, the Extended Capabilities Port (ECP) standard, the Small Computer System Interface (SCSI) interface standard, and network architecture standards including Ethernet and Token Ring network standards.

It is desirable to provide an optical reader which is economical to produce, therefore reducing the number of components and simplifying the design and construction of the remaining components are important features of the current invention. Referring now to FIG. **29**, there is illustrated the optical reader **2500** with the upper shell removed to show the interior components. A printed circuit board (PCB) **2902** is provided for physical mounting and electrical interconnection of the necessary electronic components comprising the decoder circuit and output signal interface circuit. These components include a microprocessor **2904**, memory (not shown), interface circuit **2906**, timing crystal **2908** and signal amplifiers **2910**. Note that for clarity of illustration, the individual circuit lines and many smaller components such as resistors which appear on the actual PCB **2902** are not illustrated in FIG. **29**. The PCB **2902** may be mounted to the lower shell **2704** of the reader by means of locating pins **2912** molded into the shell and protruding through corresponding holes in the PCB. These holes can further receive screws (not shown) for securing the upper shell **2702** to the lower shell **2704** during final assembly. The portion of the PCB **2902** mounting amplifiers **2910** is preferably enclosed in shielding material **2914** to prevent stray electrical signals from creating noise in the amplifier circuitry. The control cord **2516** connects the reader **2500** to the external computer **2824**, entering the shell and passing through strain relief fitting **2916** for connecting to the PCB **2902** with electrical connector **2918**.

The optical system **2806** may be mounted to the front end of the PCB **2902** and further secured to the lower shell **2704** with locating pins **2920** and/or clips **2922** as needed. The radiant energy source **2802** is typically mounted to the PCB **2902** and electrically connected thereto to receive electrical power. The radiant energy source **2802** produces light or other radiant energy which is delivered into the optical system **2806**. In one embodiment, the radiant energy source **2802** is a light emitting diode (LED), however it will be

apparent that a laser or other radiant energy source could be used. The optical system **2806** comprises a projection portion **2924** for directing the radiant energy along a projection path extending from the radiant energy source **2802** to the target region **2926**. The optical system **2806** further includes a collection portion **2928** for collecting the radiant energy reflected from a symbol (e.g., a barcode) when the symbol occupies the target region **2926** and directing the collected radiant energy along a collection path extending from the target region to the photodetector **2816**. The collection path of the optical system **2608** is typically enclosed by a light shield **2930** to prevent unwanted radiant energy from entering the optical system and being reflected or scattered into the photodetector **2816**.

Referring now to FIG. **30**, there is illustrated an enlarged view of the optical system **2608** showing its constituent components. In FIG. **30**, the top of the light shield **2930** has been removed for clarity of illustration, but the walls **3002** of the light shield are present on either side of the collection axis **2604**. In this embodiment, the radiant energy source **2802** is mounted on a forward extension **3004** of the PCB **2902**. At least a portion of the radiant energy emitted by the source **2802**, which is typically visible—or IR—wavelength light, enters the projection portion **2924** of the optical system. In the embodiment shown, the projection portion includes a guideway **3006** which directs the radiant energy (denoted by rays **3008**) from the source **2802** to the target region **2926**. In one embodiment, the guideway **3006** comprises a transparent prism which directs the radiant energy **3008** by reflection from the guideway sides **3010** and by refraction at the guideway ends **3012**, **3013**. It will be apparent, however that other embodiments may utilize a mirror or fiber optics as the guideway **3006**. Alternatively, other embodiments may directly illuminate the target region **2926** from the source **2802** without the use of a guideway. A guideway lens **2712** may be used at the upstream end **3013** of the guideway **3006** to increase the amount of radiant energy collected from the source **2802** for delivery to the target region **2926**.

The radiant energy **3008** delivered to the target region **2926** illuminates any barcode **2508** present, causing the energy to be scattered from the surface of the barcode as illustrated. At least a portion of the energy scattered from the barcode **2508** is reflected into the collection lens **2710**, forming a reflected image of the barcode. This image is directed along the collection axis **2604** of the optical system downstream toward the photodetector **2816**. As the barcode **2508** moves through the target region **2926**, the reflected image of the alternating light and dark (i.e., more reflective and less reflective) bars forming the symbol will be directed across the photodetector **2816**, causing the output electrical signals to vary correspondingly. Given output electronic signals having sufficient signal-to-noise ratio, decoding circuits of known design can amplify and decode the output electrical signals from a photodetector and identify the corresponding barcode. However, prior to the current invention, photodetectors providing signals having sufficient signal-to-noise ratio were not available at a sufficiently low manufacturing cost. Of particular challenge is obtaining a high signal-to-noise ratio electrical signal from a photodetector without utilizing a multi-stage photo amplifier. Further, it is preferred that the system utilize as few optical elements as possible.

Referring still to FIG. **30**, the photodetector **2816** of the current embodiment is mounted on the top surface **3014** of a base **3016** and electrically connected to the PCB **2902** with leads **3018**. The photodetector **2816** may be a device

selected from the group of known light-sensitive devices including photo-diodes, photo-transistors, photo-resistors, photomultiplier tubes, and Charge Coupled Devices (CCD). Alternately, the photodetector **2816** may be another type of device for producing electrical signals corresponding to light incident thereupon. In a preferred embodiment, the photodetector **2816** is a photo-diode which provides a desirable combination of light-sensitivity and low cost.

Disposed upstream on the collection path from the photodetector **2816** is a pinhole aperture **3020**. Preferably, there are no intervening or refractive or diffractive elements between the pinhole aperture **3020** and the photodetector **2816**, as their presence will increase the cost of the device. A pinhole aperture is a well known optical element which provides a well defined, virtually undistorted image of objects across a wide angular field (i.e., good depth of focus) and over a large range of distances (i.e., good depth of field). A pinhole aperture does not focus the energy passing there-through, but rather increases the contrast of the image, although at the same time decreasing its luminance. Raising the contrast of the image passed to the photodetector **2816** increases the signal-to-noise ratio of the resulting electrical output. The lower luminance of the image merely reduces the overall output signal strength and can be easily overcome by electronic amplification if the signal-to-noise ratio of the signal is high. Thus, by positioning the pinhole aperture **3020** upstream of the photodetector **2816** in the current invention, the image contrast of the barcode image is increased such that an inexpensive single stage photodetector can provide an electrical signal having sufficient signal-to-noise ratio to allow decoding of the barcode without encountering excessive signal noise during electronic amplification.

The collection lens **2710** is disposed upstream on the collection path (i.e., toward the barcode which is the source of the image) from the pinhole aperture **3020**. Preferably, collection lens **2710** is a magnifying lens, i.e., refracting the light rays passing therethrough to create an image which has increased dimensions compared to the actual bar code. The magnifying lens illustrated in FIG. **30** is a single element double convex lens. In another embodiment, a single element plano-convex lens may be used. In still further embodiments, other single element or multi element magnifying lenses can be used for collection lens **2710**. Preferably, there are no intervening refractive or diffractive elements between the pinhole aperture **3020** and the collection lens **2710**, as their presence will increase the cost of the device.

The refracted light rays **3009** leaving the collection lens **2710** form an image of the bar code which is dimensionally magnified as it moves toward the pinhole aperture **3020**, thereby increasing the apparent width of the bars when their image is received at the pinhole aperture. The portion of the image passing through the pinhole aperture **3020** and reaching the photodetector **2816** will likewise be dimensionally magnified. Thus, the optical system **2806** of the current embodiment, combining dimensional image magnification (provided by the collection lens **2710**) and contrast enhancement (provided by the pinhole aperture **3020**) effectively acts to pre-amplify the optical signal reaching the photodetector **2816** such that the electrical output signals **2818** will have sufficient signal-to-noise ratio for amplification and decoding without requiring a multi stage electronic photo amplifier which would be more expensive to manufacture. Described another way, the optical system according to one embodiment of the current invention provides increased resolution (i.e., the ability to distinguish between two lines or points in a symbol) as follows: The bar code **2508** to be

read has a minimum unit width denoted by W, for example, the minimum width of a bar in the bar code. The light rays **3009** of the image are refracted by the collection lens **2710** such that the minimum unit width of the bar code is dimensionally magnified, for example, from W to $2\times W$ (i.e., a factor of $2\times$) as it moves from the target plane **2506** to the pinhole aperture plane **3024**. The pinhole aperture **3020** is selected to have a diameter, for example $0.5\times W$, which is smaller than the magnified minimum unit width. Thus, only a sample (denoted by reference numeral **3028**) of the image rays may pass through the aperture **3020** to the photodetector **2816** lying in the photodetector plane **3026**. This results in the photodetector **2816** seeing (i.e., having in its field of view), at most, either a portion of a single feature (bar or space) or portions of one bar and one adjacent space. The photodetector never sees portions of three adjacent features at the same time. This arrangement results in a very high signal-to-noise ratio being produced by the photodetector **2816**. In one embodiment of the current invention, the optical system **2806** provides at the photodetector plane **3026** an image of the symbol **2508** at the target plane **2506** which is dimensionally magnified within the range of about $0.5\times$ to about $5\times$. In another embodiment, the optical system **2806** provides at the photodetector plane an image of the symbol at the target plane which is magnified within the range of about $1.5\times$ to about $2.5\times$. In yet another embodiment, the optical system **2806** provides at the photodetector plane an image of the symbol at the target plane which is dimensionally magnified within the range of $1.9\times$ to about $2.1\times$.

Referring still to FIG. 30, a protective window **2708** may be provided along the collection path upstream from the magnifying lens **2710**. The protective window **2708** has parallel surfaces which are disposed substantially perpendicular to the collection path **2604** and thus do not substantially refract or diffract light rays passing therethrough. In the embodiment illustrated, the protective window **2708** is molded as an integral portion of the component which also comprises the projection guideway **3006** and guideway lens **2712**. In one embodiment of the current invention, the collection portion **2928** of the optical system **2806** consists of only the protective window **2708**, the magnifying collection lens **2710** and the pinhole aperture **3020** arranged in that order between the target symbol **2508** and the photodetector **2816**. Such an embodiment provides a functional optical system having very low production costs.

Referring now to FIGS. 31 and 32, there is illustrated a discrete detector unit **3102** which may be used in an embodiment of the invention. The detector unit **3102** comprises the photodetector **2816** and the pinhole aperture **3020** packaged together in a discrete unit. Such packaging decreases production costs by reducing the assembly's part count and by reducing the number of components which must be assembled.

As best seen in FIG. 32, the detector unit **3102** includes a base **3016** having a top surface **3014** upon which the actual photodetector **2816** is mounted. Note that the photodetector **2816** may be a separate electronic component which has been mounted to the base **3016** or alternately, it may be a device formed as an integral part of the base substrate. A cap **3104** is mounted to the base **3016**. The cap **3104** has a top portion **3106** which is spaced apart from the top surface **3014** of the base **3016** to define an interior cavity **3202** containing the photodetector **2816**. The cap **3104** has a single pinhole **3020** formed therethrough at a predetermined distance **3108** from the photodetector **2816**. Except for the pinhole aperture **3020**, the cap **3104** is preferably light-tight.

In one embodiment of the invention, the cap **3014** of the detector unit **3102** is a cylindrical metallic canister having a flat upper portion **3106**. Using a metallic canister for the cap **3014** has two advantages: first, it provides a rugged container which protects the photodetector from damage during transportation, handling and assembly; and second, the metallic material allows a pinhole aperture **3020** having high dimensional accuracy to be formed by drilling, punching or otherwise machining a hole through the metallic surface. In addition, cylindrical metallic canisters suitable for use as cap **3014** are readily available at very low costs in the electronic industry, having been used for many years as protective caps for transistors and other semiconductor devices. To provide for a convenient sized optical reader, one embodiment of the current invention utilizes a detector unit **3102** having a cap **3104** with a diameter **3204** within the range of about 3 millimeters to about 20 millimeters. Another embodiment of the current invention utilizes a detector unit **3102** having a cap **3104** with a diameter **3204** within the range of about 4 millimeters to about 8 millimeters. Yet another reader according to the current invention utilizes a cap for the detector unit **3102** having a diameter **3204** within the range of about 5.5 millimeters to about 6.5 millimeters.

The predetermined distance **3108** between the pinhole aperture plane **3024** and the photodetector plane **3026** will affect the overall magnification of the image (or portion of the image) received at the photodetector **2816**. In one embodiment of the current invention, the predetermined distance **3108** is within the range of about 1 millimeter to about 10 millimeters. In another embodiment of the current invention, the predetermined distance **3108** is within the range of about 3 millimeters to about 7 millimeters. In yet another embodiment, the predetermined distance **3108** between the photodetector **2816** and the pinhole aperture **3020** is within the range of about 4.5 millimeters to about 6 millimeters.

Referring now to FIG. 36, there is illustrated a flowchart of a method of reading a bar code in accordance with another aspect of the current invention. The method starts in block **3602** and proceeds to the first function block **3604** wherein the target region is illuminated with a radiant energy generated by a radiant energy source which is directed from the source to the target region. Next, flow continues to function block **3606** wherein the bar code or other symbol is moved through the target area. Flow next proceeds to block **3608** which represents transmitting an image of the illuminated bar code through an optical system along a collection path extending from the target region to a photodetector. The step of transmitting includes a first sub-step **3610** wherein the reflected image of the bar code is dimensionally magnified with an optical element which is disposed along the collection path between the target region and the photodetector. Preferably, the optical element used for dimensional magnification is a magnifying lens, either a double convex lens or a plano-convex lens. Further, it should be noted that sub-step **3610** is preferred but not required.

The step **3608** of transmitting an image of the illuminated bar code further comprises a second sub-step **3612** which is increasing the contrast of the reflected image and decreasing the luminance of the image by passing it through an optical element disposed along the collection path between the target region and the photodetector. Note that when sub-step **3610** is performed, the optical element for magnifying the image is disposed between the bar code and the optical element which increases the contrast of the reflected image. In an embodiment of the invention, the optical element which increases the contrast of the reflected image is a

31

passive device, i.e., it requires no electrical energy or other external power. In another embodiment, the optical element which increases the contrast of the image is combined in a discrete package with the photodetector. In yet another embodiment, the optical element which increases the contrast of the reflected image is a pinhole aperture. The pinhole aperture may be formed through the body of a discrete package enclosing the photodetector or the pinhole aperture may be a separate element included in the optical system.

Flow now continues to function block **3614** wherein the reflected image of the bar code is received by the photodetector. Flow then continues to function block **3616** wherein the photodetector generates output electrical signals indicative of the radiant energy received. Flow then proceeds to function block **3618** wherein the output electrical signals produced by the detector are decoded to provide an indication of the information contained in the bar code. The method of reading the bar code is now complete as indicated by the flow proceeding to the "End" block **3620**.

Referring now to FIG. **37**, there is illustrated a diagrammatic view of an optical reader in accordance with another aspect of the invention. Externally, the optical reader of this embodiment may be substantially similar in construction to the optical readers **2500** or **3300** previously described. However, the optical reader **3700** is adapted for reading bar codes (or other such optical indicia encoding information therein) having one or more ultraviolet-wavelength-responsive properties. Two examples of ultraviolet-wavelength-responsive properties are the property of reflecting ultraviolet wavelengths and the property of fluorescing upon exposure to ultraviolet wavelengths. It will further be appreciated that fluorescence is the property of emitting electromagnetic radiation (e.g., visible light) resulting from and occurring only during the absorption of radiation from another source (e.g., ultraviolet light).

The optical reader **3700** includes an ultraviolet light source **3702**, an optical system **3704**, a photodetector **3706** and a decoder circuit **3708**. The ultraviolet light source **3702** generates light having a wavelength which is shorter than the wavelength for visible light and longer than the wavelength for X-rays. The ultraviolet light source **3702** may be any device capable of producing electromagnetic radiation having the desired wavelength, including lamps, bulbs, tubes, lasers and other devices known in the art.

Referring now to FIG. **38**, there is illustrated a partial cut-away view of the front end of one embodiment of optical reader **3700**. Ultraviolet lamp **3702** comprises a gas-filled glass tube **3804** having cathode **3806** and anode **3808** electrodes. A voltage impressed across the electrodes **3806**, **3808** causes electrons leaving the cathode to bombard the gas, resulting in the emission of ultraviolet light **3714**. In a preferred embodiment, the gas within the tube **3804** is mercury vapor. When a mercury vapor lamp or other such device is used for the ultraviolet light source **3702**, the optical reader **3700** may further include a high voltage power supply **3730** and/or a ballast circuit **3810**. The ballast circuit **3810** may be used to provide the necessary starting voltage and/or for stabilizing the current supplied to the mercury vapor lamp **3702** or other ultraviolet light source. Conventional designs for both a high voltage power supply and for a ballast circuit are known in the art and will not be described in detail.

The optical system **3704** of optical reader **3700** includes a projection portion **3710** and a collection portion **3712**. The projection portion **3710** directs the ultraviolet light (denoted by arrow **3714**) received from the ultraviolet light source **3702** along a projection path (denoted by arrow **3716**)

32

extending from the ultraviolet light source to a target region **3718**. The collection portion **3712** of the optical system **3704** collects light (denoted by arrow **3720**) from a bar code **3722** when the bar code occupies the target region **3718** and directs the collected light along a collection path (denoted by arrow **3724**) extending from the target region to the photodetector **3706**.

The photodetector **3706** generates output electrical signals (denoted by arrow **3726**) indicative of the light incident thereon having a wavelength within a predetermined range of wavelengths. In other words, the photodetector **3706** is responsive (i.e., generates output signals) only to light having a wavelength within a preselected range and "ignores" light having other wavelengths. The photodetector **3706** may be a photodiode, phototransistor, photoresistor or charged coupled device. In one embodiment, the photodetector **3706** is responsive to light having a predetermined range of wavelengths between visible light and X-rays, i.e., in the ultraviolet spectrum. Such an embodiment may be used to read a bar code **3722** having the ultraviolet-wavelength-responsive property of reflecting ultraviolet wavelengths. In other words, illuminating the bar code **3722** with ultraviolet light will cause a light-producing response, namely, ultraviolet light **3716** will be reflected from the bar code into the collection portion **3712**. Of course, the bars and spaces of the bar code **3722** must have different reflectivity in the ultraviolet wavelengths, however, the light **3720** from the bar code maintains its ultraviolet character.

In another embodiment, the photodetector **3706** is responsive to visible light, i.e., the predetermined range of wavelengths is within the spectrum of visible light. This embodiment may be used to read bar codes **3722** having the ultraviolet-wavelength-responsive property of fluorescing with visible light when illuminated with ultraviolet wavelength light. Inks which fluoresce in the visible spectrum under ultraviolet illumination are well known in the art, e.g., inks used for making so-called "black light" posters, and any of these inks can be used for making bar codes to be read by this embodiment. Further, some ultraviolet fluorescent inks are transparent and non-fluorescing to visible light, thus allowing a bar code **3722** to be provided which is invisible to human sight under normal lighting conditions. Such invisible bar codes could be used where a normal (i.e., human visible) bar code is undesirable, either for appearance or for security reasons.

Referring now to FIG. **39**, there is illustrated a diagrammatic view of the collection portion **3712** of the optical system **3704** in accordance with yet another embodiment. This embodiment may be used to read bar codes **3722** which are reflective (not fluorescent) in ultraviolet wavelengths by using a photodetector **3706** which is responsive to light in the visible spectrum. In this embodiment, the collection portion **3712** of the optical system **3704** is adapted to receive light **3720** having a first wavelength from the bar code **3722** and deliver light **3724** having a second wavelength to the photodetector **3706**. This conversion between the first wavelength of the received light **3720** and the second wavelength of the delivered light **3724** may be accomplished by providing in the collection portion **3712** a fluorescent target member **3902** disposed so as to absorb at least a portion of the received light (i.e., the light absorbed by the target member having the first wavelength) and emitting in response thereto light **3724** having a second wavelength. The emitted light **3724** is directed toward the photodetector **3706** for further processing. In the embodiment illustrated in FIG. **39**, a mirror or prism **3904** is used to direct the incoming light **3720** onto the target member **3902** where it

is absorbed and then re-emitted at the second wavelength, with at least a portion being directed towards the photodetector 3706. The target member 3902 may be constructed from, or coated with, known fluorescent materials which emit visible light upon illumination with ultraviolet light.

A decoder circuit 3708 receives the output electrical signals 3726 from the photodetector 3706. The decoder circuit 3708 produces, in response to the received signals 3726, electrical signals (denoted by arrow 3728) which are indicative of the information encoded in the bar code 3722. Decoder circuits for decoding electrical signals indicative of a bar code pattern are known in the art and will not be described in detail.

Referring now to FIG. 40, there is illustrated an output circuit which may be included in optical reader 3700. The output circuit 3731 receives electrical signals 3728 indicative of the information encoded in the bar code 3722 from the decoder circuit 3708 and transmits output signals (denoted by arrow 3732) indicative of the information encoded in the bar code from the optical reader. In one embodiment, the output circuit 3731 includes a modulator 4002 receiving the electrical signals 3728 indicative of information encoded in the bar code from the decoder 3708. The modulator 4002 combines the signal 3728 with a carrier signal 4003 from an oscillator 4004 to produce a modulated output signal 4006 indicative of information encoded in the bar code. The modulated signal 4006 is then passed to a transmitter circuit 4008 for amplifying the modulated signal as necessary and transmitting the final signal 3732 from the optical reader 3700. In one embodiment, the transmitter circuit 4008 transmits output signals 3732 using radio frequency (RF) wavelengths. In this case, as illustrated in FIG. 40, an antenna 4010 is operably connected to the transmitter circuit 4008 for sending the output signals 3732 from the optical reader. In another embodiment, the transmitter 4008 transmits output signals 3732 using infrared (IR) wavelengths. In this case, the transmitter 4008 will output to an infrared emitter (not shown) rather than to an antenna.

In yet another embodiment, the output circuit 3731 utilizes a hard-wired connection for outputting signals 3732 indicative of the information encoded in the bar code. In one such embodiment, the output circuit 3731 produces an output signal 3732 which is an electrical signal which emulates keyboard keystrokes and is directed to the keyboard port of a computer (not shown). In other embodiments, electrical outputs in accordance with other data transfer standards may be used.

Referring now to FIGS. 41 and 42, there are illustrated external views of an optical reader in accordance with another aspect of the invention. The optical reader 4100 of this embodiment has dual functionality, i.e., it may be used for accessing a remote location on a network in either of two distinct ways. First, the optical reader 4100 may be used to access a remote location on a network by optically scanning an encoded indicia (e.g., a bar code) with an optical scanning system. The optical scanning system provides signals indicative of the information encoded in the scanned indicia to an associated computer disposed on a network. The associated computer then proceeds to use the information from the encoded indicia to access a remote location on the network (typically, by first accessing a second computer on the network, e.g., ARS 308) as previously described and illustrated herein (e.g., FIGS. 3, 4a-4e, 16, 18-24). Second, the optical reader 4100 may be used to access a particular remote location on the network (the "dedicated address") by pressing a dedicated button 4102 on the optical reader. The dedicated button 4102 activates circuitry (described in detail

below) within the optical reader 4100 for providing signals indicative of information corresponding to the particular remote location. This information does not originate from the user optically scanning an encoded indicia. These signals are provided to the associated computer, which then proceeds to use the information corresponding to the particular remote location to access the remote location on the network without requiring scanning of any optical indicia.

Externally, the optical reader 4100 of this embodiment is similar in many respects to the optical reader 2500 previously described, having an outer shell 2502 with upper and lower shell portions 2702, 2704 and a scanning portal 2706 with protective window 2708 disposed at the front end 2504. In an alternative embodiment (not shown), the optical reader 4100 may be fitted with a stylized outer shell 3302 as previously described and illustrated for optical reader 3300. The dedicated button 4102 may be disposed at any convenient place on the outer shell 2502 which allows the button to be pressed by the user (denoted by arrow 4202).

Referring now to FIG. 43, there is illustrated a general block diagram of the components of the optical reader 4100. The optical reader 4100 includes an optical scanning system 4302, a dedicated address memory system 4304, and an output circuit 4306. The optical scanning system 4302 scans an encoded indicia 4308 (e.g., a bar code) and provides output signals which are indicative of the information encoded in the scanned indicia. The dedicated address memory system 4304 provides output signals which are indicative of information corresponding to a particular remote location when the dedicated button 4102 is pressed. The output circuit 4306 receives the output signals from both the optical scanning system 4302 and the dedicated address memory system 4304 and transmits them from the optical reader 4100 to an associated device, typically a nearby computer. The output circuit 4306 may utilize a hard-wired connection and/or a wireless connection (e.g., RF or IR wavelengths) to send the signals to the associated device as previously described herein.

In some embodiments, the optical scanning system 4302 may be constructed in accordance with those of the optical readers 2500 or 3700 as previously described herein and illustrated (e.g., FIGS. 28-32 and 37-39). In alternative embodiments, the optical scanning system 4302 may be constructed in accordance with known optical scanning systems. In the embodiment illustrated in FIG. 43, the optical scanning system 4302 includes a radiant energy source 4310 for generating a radiant energy (denoted by arrow 4312) for illuminating a target region 4314. The radiant energy source 4310 may be any of the sources previously described, for example, devices producing light having wavelengths in the visible, infrared (IR), or ultraviolet (UV) portions of the spectrum. A photodetector 4316 is provided for generating output electrical signals indicative of the radiant energy incident thereon. An optical system 4318 is provided including a projection portion 4320 for directing the radiant energy 4312 along a projection path extending from the radiant energy source 4310 to the target region 4314, and a collection portion 4322 for collecting the radiant energy (denoted by arrow 4324) from the encoded symbol 4308 when the encoded symbol occupies the target region. The collected radiant energy is directed by the collection portion 4322 along a collection path extending from the target region 4314 to the photodetector 4316. A photodetector 4316 produces electrical signals (denoted by arrow 4328) indicative of the energy incident thereon. A decoder circuit 4326 is provided which receives photodetector signals 4328, decodes the pattern of the signal in

35

accordance with known processes, and produces decoded output signals (denoted by arrow **4330**) indicative of information encoded in the scanned symbol **4308**. The decoded output signals **4330** are routed to the output circuit **4306** to be sent to the associated device. An output circuit signal (denoted by arrow **4332**) resulting from the optical scanning of encoded indicia by the user is termed a "scan code".

Referring now to FIG. **44**, there is illustrated a sample scan code sent from the output circuit **4306** of the optical reader **4100** to the associated device. The scan code **4402** comprises a number of fields of information including a header field **4404** indicative of message start, a subject field **4406** indicative of information that was encoded in the scanned indicia **4308**, and a stop field **4408** indicative of message end. The subject field contents **4406** may be any type of information indicative of the information that was encoded in the scanned indicia **4308**. For example, when the scanned indicia **4308** is a bar code on a consumer product, the subject field **4406** may contain all or part of a number assigned to the consumer product (e.g., a Universal Product Code number) which was encoded in the scanned indicia. In other cases, the subject field **4406** may contain numeric or alphanumeric characters encoded in a proprietary bar code. The header field **4404** and stop field **4408** are typically added by the output circuit **4306** to the subject information which is supplied by the decoder **4326**. The scan code **4402** may further include a type identification field **4410** indicative of the type (i.e., format) of encoded indicia that was scanned (e.g., UPC, ISBN, ISSN, etc.). The type identification of an indicia is typically determined by the decoder **4326** during the decoding process. Further, the scan code **4402** may include an optical reader identification field **4412** indicative of the serial number of the optical reader used. This serial number may, for example, be stored in a memory **4434** accessible by the output circuit **4306**.

Referring again to FIG. **43**, the dedicated address memory system **4304** comprises a processor **4336**, an electronic memory **4338** operably connected to the processor, and an electrical switch **4340** operably connected to the processor. In the embodiment illustrated, the processor **4336** is a separate device from the decoder **4326** of the optical scanning system **4302**. However, in another embodiment, the processor **4336** and the decoder circuitry **4326** may be portions of a common device or circuitry. The memory **4338** includes a memory location **4342** storing information corresponding to the particular remote location (i.e., the dedicated address) on the network. The dedicated address information stored in the memory location **4342** does not originate from the optical scanning of an encoded indicia by the user. Typically, the memory **4338** is pre-programmed by the manufacturer or distributor to contain the desired dedicated address information. In one embodiment, the dedicated address information cannot be changed by the user, e.g., where memory **4338** is a non-erasable read-only memory (ROM). In another embodiment, the memory **4338** is re-programmable, however, the dedicated address information is only changed in response to receiving signals from an attached computer.

The electrical switch **4340** is electrically connected to the processor **4336** and mechanically connected to the dedicated button **4102** such that pressing the button will provide an electrical signal to the processor. It will be appreciated that the dedicated button **4102** and button-activated switch **4340** may be replaced with a toggle switch, slide switch, touch switch circuit or other equivalent elements allowing the user to provide a two-state (i.e., ON/OFF) signal to the processor **4336**.

36

In response to activation of the electrical switch **4340**, the processor **4336** accesses the electronic memory **4338** and retrieves the dedicated address information corresponding to a particular remote location (i.e., the dedicated address) from the memory location **4342**. It is important to note that the dedicated address information may be any type of information which can be associated with a particular remote location on the network. In one embodiment, the dedicated address information may be an actual network address (e.g., a URL) of the remote location. In another embodiment, the dedicated address information may be a unique code number assigned by the manufacturer or distributor of the optical reader and correlated to the desired remote location in a database (e.g., the ARS database **310**). In yet another embodiment, the dedicated address information may be a pre-existing code number assigned to an article of commerce in accordance with an extrinsic standard (e.g., a Universal Product Code number assigned to a consumer product), which number is correlated to the desired remote location in a database (e.g., the ARS database **310**). The processor uses the dedicated address information to produce processor output signals (denoted by arrow **4344**) indicative of the dedicated address information. The processor output signals **4344** are sent to the output circuit **4306** for transmission to the associated device. An output circuit signal **4332** resulting from activation of the dedicated address memory system by the user is termed a "dedicated code".

Referring now to FIG. **45** there is illustrated a sample dedicated code sent from the output circuit **4306** of the optical reader **4100** to the associated device. The dedicated code **4502** comprises a number of fields of information including a header field **4504** indicative of message start, a subject field **4506** indicative of the dedicated address information retrieved from the memory **4338** (i.e., corresponding to the particular remote location), and a stop field **4508** indicative of message end. The header field **4504** and stop field **4508** are typically added by the output circuit **4306** as previously described. In a preferred embodiment, the dedicated code **4502** has a format which is identical to the format for the scan code **4402**. Thus, even though the dedicated code **4502** does not result from scanning an encoded indicia by the user, the dedicated code may further include a type identification field **4510**. In such cases, the contents of the type identification field **4510** will be information retrieved from the dedicated memory **4338**. If desired, the type identification field **4510** may contain information indicating that the subject information **4506** results from activation of the dedicated address memory system **4304**. However, it is also possible to provide information in memory **4338** such that the type identification field **4510** in a dedicated code **4502** simulates (i.e., is indistinguishable from) a type identification field **4410** in a scan code **4402** resulting from the scanning of encoded indicia. Further, the dedicated code **4502** may include an optical reader identification field **4512** indicative of the serial number of the optical reader used as previously described for field **4412**.

It will thus be apparent, that the optical reader **4100** may be configured to operate such that the associated computer or device receiving a signal **4332** from the optical reader **4100** will be incapable of distinguishing whether the signal is a scan code **4402** (resulting from actually scanning an encoded indicia) or a dedicated code **4502** (resulting from pressing the dedicated button). Such a configuration allows an optical reader **4100** incorporating the dedicated address memory system **4304** to be fully compatible with associated devices (e.g., computers), software applications (e.g., browsers), and network systems (e.g., servers, including ARS **308**,

37

and databases, including ARS database 310) designed for use with optical readers not having the dedicated address memory system.

Referring now to FIG. 46, there is illustrated a diagrammatic view of a system for accessing a remote location on a network using the optical reader 4100. The system includes a first computer 302 disposed (by means of network interface 304) on a network 306, which may be a global communication network such as the Internet. The optical reader 4100 is operably connected to the first computer 302. As previously discussed, this connection between the optical reader 4100 and the attached device may be hard-wired (as in the illustrated embodiment) or wireless. A second computer 308 (e.g., the ARS server) is also disposed on the network 306. A database 310 (e.g., ARS database) may be operably connected to the second computer 308. A third computer 312 (e.g., an advertiser's server) is disposed on the network 306 at a remote site. This system is similar to systems previously described and illustrated herein (e.g., FIGS. 3 and 16).

The process of connecting to the remote site on the network using the optical reader 4100 is similar in most respects to processes previously described and illustrated herein. However, in the current process, the signal provided by the optical reader 4100 to the associated device may be either a scan code 4402 (in response to actually scanning an encoded indicia 4308 with the optical scanning system 4302) or a dedicated code 4502 (in response to activating the dedicated address memory system 4304 by pushing dedicated button 4102). One of the scan code 4402 and the dedicated code 4502 is transmitted from optical reader 4100 to the first computer 302. The first computer 302, in response to receiving the code 4402 or 4502, accesses the second computer 308. Typically, this accessing will involve sending a packet of information (denoted by reference numeral 4602) including at least a portion of the code 4402 or 4502 across the network 306 from the first computer 302 to the second computer 308. A lookup operation is performed at the second computer 308 to match the scan code 4402 or the dedicated code 4502 received from the optical reader 4100 with a routing information for a remote location on the network. Typically this lookup operation is performed by accessing (denoted by reference numeral 4603) a computer database 310 including a plurality of codes and a plurality of routing information for remote locations on the network. In the database 310, each of the plurality of routing information is associated with at least one of the plurality of codes. The routing information corresponding to the code (4402 or 4502) received from the optical reader 4100 is then retrieved from the database 310 by second computer 308. The routing information (denoted by reference numeral 4604) is returned from the second computer 308 to the first computer 302. The routing information is then used by the first computer 302 to access (denoted by reference numeral 4606) the third computer 312 at the remote location on the network. Typically, after locating the third computer 312 at the remote location, information (denoted by reference numeral 4608) will be returned from the third computer to the first computer 302 for presentation to the user.

It is contemplated that the manufacturer of the optical reader 4100 will pre-program the dedicated address memory system 4304 with information corresponding to a network location sponsored by, or otherwise affiliated with, the manufacturer (e.g., a web site for the manufacturer, for the distributor of the reader, or for a paid advertiser). Users of the optical reader 4100 will thus always be able to access the

38

dedicated location simply by pressing the dedicated button 4102, no scanning of an indicia is required.

Although the preferred embodiment has been described in detail, it should be understood that various changes, substitutions and alterations can be made therein without departing from the spirit and scope of the invention as defined by the appended claims.

What is claimed is:

1. A method of enabling a user to access a remote location on a network using an optical reader, comprising the steps of:

transmitting one of a scan code and a dedicated code from an optical reader to a first computer disposed on the network, the optical reader having an optical scanning system for scanning an encoded indicia, and a dedicated code system, including the steps of:

the optical scanning system, in response to the user scanning the encoded indicia therewith, sending to the first computer the scan code indicative of information encoded in the scanned encoded indicia; or the dedicated code system, in response to the user completing an activation sequence, sending to the first computer the dedicated code indicative of information relating to a particular remote location on the network, the information not originating from the scanning of an encoded indicia or related to the encoded indicia, the dedicated code having no routing information contained therein;

accessing, in response to the first computer receiving the one of the scan code or the dedicated code from the optical reader, a second computer disposed on the network;

performing a lookup operation at the second computer to match the one of the scan code or the dedicated code received from the optical reader with routing information for a remote location on the network;

returning the routing information from the second computer to the first computer; and

accessing the remote location on the network in accordance with the routing information returned from the second computer.

2. A method in accordance with claim 1, wherein the dedicated code system further comprises:

a processor;

an electronic memory operably connected to the processor and including a memory location storing the information relating to the particular remote location on the network; and

an electrical switch operably connected to the processor; whereby, in response to activation of the electrical switch, the processor accesses the electronic memory, retrieves the information relating to the particular remote location from the memory location, and produces the dedicated code indicative of the information relating to the particular remote location.

3. A method in accordance with claim 2, wherein the information relating to the particular remote location in the electronic memory cannot be changed by the user.

4. A method in accordance with claim 2, wherein the electrical switch is operably connected to a dedicated button accessible from the exterior of the optical reader.

5. A method in accordance with claim 4, wherein the activation sequence includes pressing the dedicated button to activate the electrical switch.

6. A method in accordance with claim 1, wherein the second computer is connected to a computer database including a plurality of codes and a plurality of routing

39

information for remote locations on the network, and associating each of the plurality of routing information for remote locations on the network with at least one of the plurality of codes.

7. A method in accordance with claim 6, wherein one of the plurality of codes in the computer database is the dedicated code. 5

8. A method in accordance with claim 1, wherein the step of accessing a second computer further comprises:

launching a software application on the first computer; 10
incorporating the one of the scan code and the dedicated code received from the optical reader into a message packet using the software application; and
transmitting the message packet to the second computer. 15

9. A method in accordance with claim 8, wherein the message packet includes information identifying the optical reader.

10. A method in accordance with claim 8, wherein the message packet includes information identifying the user.

11. A method in accordance with claim 1, wherein the step of accessing the remote location on the network further comprises the steps of: 20

locating information on a third computer at the remote location; and

returning the information from the third computer to the first computer for presentation to the user. 25

12. A method in accordance with claim 1, wherein the network is a global communication network.

13. A method in accordance with claim 1, wherein the dedicated code has a data format substantially identical to a scan code resulting from the scanning of an encoded indicia. 30

14. A method of enabling a user to access a remote location on a network using an optical reader, comprising the steps of:

pressing a dedicated button accessible on an exterior surface of the optical reader, the optical reader operable for scanning an encoded indicia and sending decoded indicia information therefrom; 35

transmitting, in response to the pressing of the dedicated button, a dedicated code indicative of information stored in a memory location of a memory associated with the optical reader from the optical reader to a first computer disposed on the network, the information stored in the memory location not associated with or originating from the step of scanning of the encoded indicia by the user and having no routing information contained therein; 40 45

accessing, in response to the first computer receiving either the dedicated code or the dedicated indicia from the optical reader, a second computer disposed on the network; 50

performing a lookup operation at the second computer to match the received one of either the dedicated code or the decoded indicia received from the optical reader with routing information stored at the second computer for a remote location on the network; 55

40

returning the routing information from the second computer to the first computer; and

accessing the remote location on the network in accordance with the routing information returned from the second computer.

15. The method in accordance with claim 14, wherein the step of accessing the remote location on the network further comprises the steps of:

locating information on a third computer at the remote location; and

returning the information from the third computer to the first computer for presentation to the user.

16. A method of enabling a user to access a remote location on a network using an optical reader, comprising the steps of:

transmitting either of a scan code or a predetermined code from an optical reader to a first computer disposed on the network, the optical reader having an optical scanning system for scanning an encoded indicia to extract therefrom a scan code, and a fixed code system for enabling access to the predetermined code, including the steps of:

the optical scanning system, in response to the user scanning the encoded indicia therewith, sending to the first computer the scan code indicative of information encoded in the scanned encoded indicia; or
the fixed code system, in response to the user completing an activation sequence, sending to the first computer the predetermined code indicative of information relating to a particular remote location on the network, the information not originating from the scanning of an encoded indicia or directly related to the encoded indicia, the predetermined code having no routing information contained therein;

accessing, in response to the first computer receiving the one of the scan code or the dedicated code from the optical reader, a relational database of routing information to various remote locations on the network each having a corresponding matching relationship to one of either one of a plurality of scan codes or a one of a plurality of predetermined codes;

performing a lookup operation at the relational database to match the one of the scan codes or the predetermined code received from the optical reader with corresponding routing information for a corresponding remote location on the network;

returning the routing information from the relational database to the first computer; and

accessing the remote location on the network in accordance with the routing information returned from the relational database.

* * * * *