

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
15 October 2009 (15.10.2009)

(10) International Publication Number
WO 2009/126607 A2

(51) International Patent Classification:

B01D 53/047 (2006.01) *B01D 53/62* (2006.01)
C01B 3/56 (2006.01) *C01B 31/20* (2006.01)

(21) International Application Number:

PCT/US2009/039744

(22) International Filing Date:

7 April 2009 (07.04.2009)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/123,259 6 April 2008 (06.04.2008) US

(71) Applicant (for all designated States except US): IN-NOSEPRA LLC [US/US]; 15 Moray Ave, Bridgewater, NJ 08807 (US).

(71) Applicant and

(72) Inventor: JAIN, Ravi [IN/US]; 15 Moray Ave, Bridgewater, NJ 08807 (US).

(74) Agent: TANKHA, Ashok; 36 Greenleigh Drive, Sewell, NJ 08080 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,

HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

Published:

— without international search report and to be republished upon receipt of that report (Rule 48.2(g))

— with information concerning request for restoration of the right of priority in respect of one or more priority claims; the decision of the receiving Office regarding the request for restoration is pending and will be published separately once available (Rules 26bis.3 and 48.2(j))

(54) Title: CARBON DIOXIDE RECOVERY

(57) Abstract: Disclosed herein is a method and system for separating carbon dioxide (CO₂) from a CO₂ containing gas stream containing water vapor and additional impurities, for example, nitrogen, oxygen, sulfur oxides, nitrogen oxides, and mercury. The CO₂ is captured by subjecting the CO₂ gas feed stream to a temperature swing adsorption step. The temperature swing adsorption step comprises an adsorption step for producing a substantially dry carbon dioxide-depleted stream, and an adsorbent regeneration step comprising heating the adsorbent bed to produce a substantially water vapor-free carbon dioxide stream. Moisture from the gas stream containing CO₂ is optionally removed by pressure swing adsorption, temperature swing adsorption, membrane separation, or absorption prior to CO₂ capture.



WO 2009/126607 A2

CARBON DIOXIDE RECOVERY

CROSS REFERENCE TO RELATED APPLICATIONS

- 5 1. This application claims the benefit of provisional patent application number 61/123,259 titled "Process For Carbon Dioxide Recovery", filed on April 07, 2008 in the United States Patent and Trademark Office.
- 10 2. The following patent application is incorporated herein in its entirety: Non-provisional patent application number 12/419,513 titled "Carbon Dioxide Recovery", filed on 07 April, 2009 in the United States Patent and Trademark Office.

BACKGROUND

15

The method and system disclosed herein relates to capturing carbon dioxide (CO₂) from combustion sources such as flue gas of a power plant and making the CO₂ available for sequestration or other uses.

20

Emissions of greenhouse gases such as CO₂, if left unchecked, may potentially affect climatic conditions. Conversion of fossil fuels such as coal and natural gas to energy is a source of greenhouse gas emissions. Emissions of the greenhouse gases can be reduced by various means such as increase in efficiency of the combustion process and use of renewable energy such as wind and solar but the reduction in the emission of the greenhouse gases required to stabilize the greenhouse gas levels cannot be achieved without capturing a substantial part of the greenhouse gases at the source of the greenhouse gas emissions during either the pre-combustion process or the post-combustion process. Post-combustion capture of CO₂ from the flue gas of a power plant or other streams such as the flue gas from a refinery involves use of a solvent, typically

25 greenhouse gases required to stabilize the greenhouse gas levels cannot be achieved without capturing a substantial part of the greenhouse gases at the source of the greenhouse gas emissions during either the pre-combustion process or the post-combustion process. Post-combustion capture of CO₂ from the flue gas of a power plant or other streams such as the flue gas from a refinery involves use of a solvent, typically

30 an amine, which is regenerated using a part of the steam generated during the combustion process. Pre-combustion capture of CO₂ involves chemical reaction of the fuel with air or

oxygen and then with steam to produce a mixture of carbon dioxide and hydrogen. The carbon dioxide is removed from this stream through a CO₂ capture process and hydrogen may be used as a fuel for power generation. If oxygen is used for combustion, a flue gas containing mainly carbon dioxide is produced which can be easily separated for
5 sequestration.

The post-combustion capture of CO₂ results in 9%-11% reduction in absolute efficiency for power generation and about 28-30% reduction in relative efficiency for a pulverized coal power plant as discussed by Ciferno (Ciferno, J., "A Feasibility Study of
10 Carbon Dioxide Capture from an Existing Coal-Fired Power Plant," paper presented at the Sixth Annual Conference on Carbon Capture and Sequestration, Pittsburgh, PA, May 2007.). A May 2007 NETL report (Carbon Sequestration Technology Roadmap and Program Plan - 2007, U.S. DOE National Energy Technology Laboratory (NETL), May 2007.) shows a 60-100% increase in cost of power generation for existing power plants
15 taking into account capital and operating costs for CO₂ separation and sequestration. Net power output from the power plant is also decreased by 30% or more. Means to significantly decrease the power and capital penalty associated with the post-combustion CO₂ capture are sought. For the post-combustion capture, the Department Of Energy (DOE) has a goal of less than 35% increase in power cost for 90% CO₂ capture.

20

Most studies dealing with the post-combustion CO₂ capture use amine or ammonia-based absorption processes for the removal of carbon dioxide from the flue gas. The absorption-based processes have drawbacks such as the significant capital requirements. The best amine based absorbents such as the hindered amines and amine
25 blends have an energy requirement in the range of 750-900 Kcal/kg (1,350-1,620 Btu/lb) of the CO₂ captured. Furthermore, amine-based processes require the use of specialty steel equipment and the associated capital investment because of the corrosive nature of amine and ammonia solutions in the presence of acidic gases and oxygen. This equipment represents a significant capital cost.

30

In contrast to the amine-based systems, the heats of adsorption of CO₂ on various

zeolite and carbon based adsorbents range between 140-240 kcal/kg or 252-432 Btu/lb (Valenzuela, D.P. and A.L Myers, "Adsorption Equilibrium Data Handbook," Prentice Hall, Englewood Cliffs, NJ, 1989.) which is about a fifth of the heat of absorption for the amine-based systems. There is an unmet need for practical adsorption systems that can
5 take advantage of low heats of adsorption while providing high carbon dioxide yield and high recovery.

Temperature swing adsorption systems have been used extensively for applications such as air drying, natural gas drying, and water and CO₂ removal prior to
10 cryogenic distillation of air. These systems typically remove less than 2% of impurities and the regeneration outlet stream containing the impurities is not of high purity. Also the typical temperature swing adsorption processes have adsorption times of the order of 4-12 hours. For feed CO₂ concentrations between 10-12% in the flue gas, these adsorption times would require extremely large adsorption beds. For example, assuming a working
15 capacity of 12 weight% (difference in capacity between the adsorption and the regeneration steps), an adsorbent density of about 660 kgs/m³ and an adsorption time of 4 hours, a plant processing 1000 tons/day of CO₂ in the feed would require about 8,000 m³ (5.3 million kilograms) of the adsorbent, a size that makes the systems not practical for capturing carbon dioxide from combustion sources.

20

The method and system disclosed herein provides a solution for the efficient capture of CO₂ using a process based on a temperature and pressure swing adsorption cycles.

25 SUMMARY OF THE INVENTION

This summary is provided to introduce a selection of concepts in a simplified form that are further described in the detailed description of the invention. This summary is not intended to identify key or essential inventive concepts of the claimed subject
30 matter, nor is it intended for determining the scope of the claimed subject matter.

The method and system disclosed herein addresses the above stated need for separating carbon dioxide (CO₂) from a gas stream containing water vapor and additional impurities. The method and system disclosed herein captures CO₂ using a process based on a temperature and pressure swing adsorption cycles. The gas is a flue gas from a coal-fired power plant, a natural gas fired power plant, or a refinery.

High purity CO₂, i.e., CO₂ containing no more than about 10 percent by volume of impurities, is produced by subjecting a CO₂ gas stream to a temperature swing adsorption step. The temperature swing adsorption step comprises an adsorption step for producing a substantially dry CO₂-depleted stream, and an adsorbent regeneration step comprising heating the adsorbent bed to produce a substantially water vapor-free CO₂ stream. Temperature in the temperature swing adsorption step during the adsorbent regeneration step is increased to about 80°C to 300°C. Duration of the temperature swing adsorption step is in a range of about 2 minutes to 60 minutes.

15

The adsorption is generally carried out in the gaseous phase at temperatures between 10°C and 80°C and at pressures in the range of about 1.07 to 40.0 bar absolute. The CO₂ concentration is in a range of about 3% to 60% by volume.

20

The impurities that are preferably removed from the CO₂ containing gas stream are selected from the group comprising, for example, nitrogen, oxygen, hydrocarbons, nitrogen oxides, sulfur oxides, mercury, and argon. The adsorption is conducted in a bed comprising an adsorbent material, which preferentially adsorbs or reacts with CO₂ in the gas stream.

25

In an embodiment, the impurities comprising, for example, moisture, hydrocarbons, nitrogen oxides, sulfur oxides, and mercury are removed prior to CO₂ adsorption. The moisture removal is performed using, for example, pressure swing adsorption, temperature swing adsorption, membrane separation, and absorption.

30

Duration of the pressure swing adsorption process is in a range of about 4 minutes to about 60 minutes and duration of the temperature swing adsorption process is in a range

of about 1 hour to 12.0 hours. The moisture content in the moisture removal step is reduced to a dew point of -40°C or below. Adsorbents, for example, activated carbon, carbon molecular sieves, zeolites such as 4A, 5A, 13X, NaY and CaX, metallorganic framework compounds, natural zeolites, modified natural and synthetic zeolites, modified
5 activated carbon, pillared clays, etc. are used for CO_2 adsorption. The CO_2 -depleted stream from the CO_2 adsorption section is used for the regeneration of the moisture adsorption system.

In another embodiment, the feed containing moisture is sent directly to the CO_2
10 adsorption system wherein CO_2 from the feed is removed by activated carbon or by chemical reaction with sodium and potassium carbonates, amines or ionic liquids supported on a microporous support.

In both embodiments, the material containing CO_2 is regenerated by direct or
15 indirect heat transfer to produce a high purity CO_2 stream. Further CO_2 removal is performed by bed evacuation after heating. The CO_2 produced is further purified by a membrane process, a distillation process, an adsorption process, or a getter process to remove impurities comprising, for example, nitrogen, oxygen, argon, nitrogen oxides, sulfur oxides, and moisture. Part of the purified CO_2 can be used as a rinse in the CO_2
20 separation system. The method and system disclosed is effective for the removal of about 80% or higher amounts by volume of impurities from the CO_2 stream.

BRIEF DESCRIPTION OF THE DRAWINGS

25 The foregoing summary, as well as the following detailed description of the invention, is better understood when read in conjunction with the appended drawings. For the purpose of illustrating the invention, exemplary constructions of the invention are shown in the drawings. However, the invention is not limited to the specific methods and instrumentalities disclosed herein.

30

FIG. 1 illustrates an overall schematic of the carbon dioxide (CO₂) separation system for recovering high purity CO₂ from a feed stream containing CO₂.

FIGS. 2A-2D exemplarily illustrate various configurations of the CO₂ separation system wherein moisture is optionally removed in a first separation unit followed by the capture of CO₂ by chemical reaction or adsorption in a second separation unit.

FIG. 3 exemplarily illustrates the configuration of a moisture adsorption system wherein the moisture and additional impurities, for example, hydrocarbons, sulfur oxides or nitrogen oxides, and mercury are removed by a combination of pressure and temperature swing adsorption.

FIG. 4 exemplarily illustrates the configuration of the CO₂ separation system wherein CO₂ is removed from the feed stream by adsorption or chemical reaction and is recovered by heating directly or indirectly by steam, hot water or a dry stream recovered from the CO₂ separation system.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 illustrates an overall schematic of the carbon dioxide (CO₂) separation system **80** for recovering high purity CO₂ from a feed stream containing CO₂. The CO₂ is generated in a process **5** which could be a combustion process or another process that generates CO₂. If process **5** is a combustion process, an oxygen-enriched stream **10** can be optionally used during the combustion to improve combustion efficiency and to increase the concentration of CO₂ resulting from combustion. Using the heat-generated in process **5**, steam can be generated as stream **15**. A part of stream **15** can be taken as stream **20** and used in the CO₂ separation system **80** described later. The remaining part of stream **15** is taken off as stream **25** and can be used for other purposes, for example, for power generation or for the production of synthesis gas in unit **30**. Stream **35**, the low pressure stream or hot water in unit **30**, can be used in the CO₂ separation system **80** or can be sent to unit **5** for generating steam. A portion of electrical power generated in unit

30 can be sent to the CO₂ separation system **80** via line **45**. The remaining electrical power can be supplied to the end users such as the industrial and the residential customers through line **50**. The CO₂ containing stream such as the flue gas leaves process **5** as stream **55**.

5

After removing particulates, the stream **55** can be optionally sent to a feed conditioning unit **60** to remove impurities such as the oxides of nitrogen and sulfur, and mercury. The pressure of stream **55** containing residual sulfur and nitrogen oxides, mercury, nitrogen, oxygen and argon as the main impurities can be raised, if needed, by a fan or a blower **65** after unit **60**. If the CO₂ containing stream is from a chemical plant or a refinery or from a pre-combustion process, the CO₂ containing stream may contain additional impurities, for example, hydrogen, hydrocarbons, and carbon monoxide. For a coal or a natural gas fired power plant, the pressure of the flue gas will typically be raised to about between 1.07 bara to 1.34 bara. For the CO₂ stream generated in chemical or industrial processes, the pressure of the stream may be higher than 1.07-1.34 bara and may not have to be raised. In a gasification process where the fuel is gasified with air or oxygen, the pressure of the stream containing CO₂ may be several atmospheres and would not have to be raised. In the oxy-combustion process the flue gas may be recycled to the combustion system to increase the concentration of CO₂. After the removal of nitrogen oxides, sulfur oxides and mercury, and compression, the CO₂-containing stream is typically cooled to between near ambient temperature and 60°C prior to CO₂ capture. The flue gas cooling unit is not shown in FIG. 1. Many power plants have systems for the removal of particulates, nitrogen oxides, and sulfur oxides. The systems may include selective catalytic reduction (SCR) for nitrogen oxides, electrostatic precipitators for the particulates, and wet scrubbers for sulfur oxides. Removal of particulates, nitrogen oxides, and sulfur oxides may not be necessary if stream **55** comes from a process such as partial oxidation or reforming.

The stream containing CO₂ leaves unit **65** as stream **70** and enters the CO₂ separation system **80**. The CO₂ separation system **80** contains at least one bed with a material that removes CO₂ from the feed stream by adsorption or chemical reaction. The

30

pressure of the bed ranges from about 1.07 bar absolute to about 40 bar absolute.

Depending on the material used for CO₂ capture, the CO₂ separation system **80** may contain additional units for the removal of other components in the feed stream such as moisture, residual sulfur oxides, nitrogen oxides, and mercury. If a material such as
5 activated carbon, or potassium carbonate, an amine or an ionic liquid on a microporous support is used for CO₂ removal, the moisture in the feed stream **70** may not have to be removed and the CO₂-depleted stream **85** exiting the CO₂ separation system **80** would contain most of the moisture contained in stream **70**. In this case, stream **85** can be vented. However, if a material such as a zeolite is used for CO₂ capture by adsorption, the
10 moisture from the feed stream **70** would have to be removed prior to CO₂ adsorption and the CO₂-depleted stream **85** would be relatively dry. In this case, a part or all of stream **85**, stream **95**, can be used for regenerating the moisture adsorption system **79**.

The CO₂ captured in the CO₂ separation system **80** is recovered by desorbing the
15 CO₂. The energy for CO₂ desorption can be provided by stream **20**, stream **35** or electricity represented by stream **45**. Other external sources of heat and electricity can also be used for regenerating the material in the CO₂ separation system **80**. The adsorbent or reactant can be contacted directly by steam or condensate if the material is able to handle it. The material in the CO₂ separation system **80** can also be regenerated by dry
20 CO₂ depleted stream **85** which is heated with steam, hot water or electricity. If the adsorbent material is not water tolerant, the adsorbent bed would have to be heated indirectly by steam or hot water. Typically, the regeneration of the moisture adsorption material and the CO₂ adsorption material in the CO₂ separation system **80** would be done in parallel to ensure that the CO₂ leaving the CO₂ separation system **80** is dry. In addition
25 to heat, a vacuum pump may be used to remove CO₂ from the CO₂ separation system **80**. The stream used for regeneration is depicted as stream **90** in FIG. 1. More than 80% of the impurities are typically removed in the CO₂ separation section.

The desorbed CO₂ exits the CO₂ separation system **80** via line **105** and is sent to a
30 CO₂ purification system **125**. An optional vacuum pump **110** may be used to facilitate the recovery of CO₂ from the CO₂ separation system **80**. Part of the CO₂ product enters the

vacuum pump **110** as stream **100** and joins stream **105** after exiting the vacuum pump **110**. The stream **105** and the stream exiting the vacuum pump **110** are combined to form the CO₂ product stream which enters the CO₂ purification system **125** as stream **120**. The purity of the CO₂ product stream **120** produced during regeneration is dependent on the feed CO₂ concentration but would typically be higher than 90%. This stream **120** can be optionally compressed to pressures between 1.1 bara and 200 bara prior to purification. The CO₂ purification system **125** can be, for example, a distillation system, a membrane system, a pressure or temperature swing adsorption system or a getter system to remove small amounts of impurities such as nitrogen, oxygen, nitrogen oxides and sulfur oxides from CO₂. Also, if the CO₂ stream exiting the CO₂ separation system **80** is wet, the moisture is also removed. Purified CO₂ leaves as stream **130** from the CO₂ purification system **125**. Stream **135**, which is a small part of stream **120**, stream **115**, or stream **130**, may be used to purge the inerts in the CO₂ separation system **80**. This stream **135** enters the CO₂ separation system **80** as stream **145**. The purified CO₂ product exits the CO₂ purification system **125** as stream **140** and is available for food or beverage applications, industrial applications, enhanced oil or gas recovery, and sequestration. The CO₂ product stream **140** may have to be compressed, liquefied or both prior to some of these applications.

FIGS. **2A-2D** exemplarily illustrate various configurations of the CO₂ separation system **80** wherein moisture is optionally removed in a first separation unit followed by the capture of CO₂ by chemical reaction or adsorption in a second separation unit.

In FIG. **2A**, a wet CO₂ stream **70** is passed through a bed of material that adsorbs or reacts with CO₂ in the presence of moisture. The adsorption or chemical reaction system contains at least two beds at least one of which is removing CO₂ from the feed stream while at least one of which is undergoing regeneration at any given time. As disclosed later in relation to FIG. **4**, additional beds may be used for other steps such as cooling, pressurization, rinse, and evacuation. The rinse step can be performed using a relatively pure CO₂ stream **145**. As illustrated in FIG. **1**, the CO₂ product stream exits the CO₂ separation system **80** as stream **105** and as an additional optional stream **100**.

In FIG. 2B, wet CO₂ stream 70 is passed through a membrane dryer 71 where the moisture from the feed stream is removed. The dry feed stream 72 is sent to the adsorption or reaction bed 81 wherein the CO₂ from the feed is removed and a dry CO₂-depleted stream 85 exits the CO₂ separation system 80. While CO₂ is being adsorbed at least one other bed 81 is undergoing regeneration using stream 90. As in the case of FIG. 2A, additional beds may be used for other steps such as cooling, pressurization, rinse, and evacuation. Part or all of stream 85 is taken as stream 95 and is used to purge the permeated moisture in the membrane dryer 71. The moisture laden stream exits the membrane dryer 71 as stream 73. An optional vacuum pump 74 may be used to increase the driving force across the membrane and to facilitate the moisture removal, and the moisture-laden stream exits the vacuum pump 74 as stream 75.

In FIG. 2C, wet CO₂ stream 70 is passed through an absorption system 76 wherein the moisture from the feed stream is removed by an absorbent such as ethylene glycol. The beds used for moisture removal would normally contain dumped or structured packing for mass transfer between the feed and the absorbent phases and streams would typically flow in the countercurrent direction. The dry feed stream 72 exiting the absorption system 76 is sent to CO₂ adsorption beds 81 wherein the CO₂ from feed is removed and a dry CO₂-depleted stream 85 exits the CO₂ separation system 80. While CO₂ is being adsorbed at least one other bed 81 is undergoing regeneration using stream 90. Additional beds may be used for other steps such as cooling, pressurization, rinse and evacuation. Part or all of CO₂-depleted stream, stream 85, is taken as stream 95, heated in a heat exchanger or heater 96, and passed through the absorption system 76 as stream 97 to regenerate the moisture loaded solvent stream 77. The solvent loaded with moisture can also be regenerated by countercurrent heat exchange in a heat exchanger (not shown) with steam. The regenerated solvent stream 78 is sent to the absorption system 76 for moisture removal. The stream 95 can be heated by heat exchange with steam or condensate, or the stream 95 may be heated directly using the electrical energy. The moisture loaded stream exits the absorption system 76 as stream 75.

In FIG. 2D wet CO₂ stream 70 is passed through a moisture adsorption system 79 where the moisture from the feed stream is removed by an adsorbent such as activated alumina, silica gel or a molecular sieve. The dry feed stream 72 exiting the moisture adsorption system 79 is sent to the CO₂ adsorption beds 81 where the CO₂ from feed is removed and a dry CO₂-depleted stream 85 exits the CO₂ separation system 80. While CO₂ is being removed in one or more CO₂ adsorption beds 81, at least one other CO₂ adsorption bed 81 is undergoing regeneration using stream 90. Additional beds may be used for other steps such as cooling, pressurization, rinse, and evacuation. Part or all of stream 85 is taken as stream 95, optionally heated in a heat exchanger or heater 96, and is used to regenerate the moisture adsorption beds in the moisture adsorption system 79. If stream 95 is heated prior to regeneration of the moisture adsorption beds, the stream 95 can be heated by heat exchange with steam or hot water. The stream 95 can also be heated directly using electrical energy. The moisture loaded stream exits the moisture adsorption system 79 as stream 73. An optional vacuum pump 74 can be used to provide additional driving force for the moisture removal and the water loaded stream then exits the vacuum pump 74 as stream 75.

The moisture adsorption system 79 would typically contain multiple moisture adsorption beds for the removal of moisture as well as other impurities such as the heavy hydrocarbons that can hinder the adsorption of CO₂ in the CO₂ adsorption beds 81. Moisture adsorption beds in the moisture adsorption system 79 can also be designed to remove some of the sulfur oxides, nitrogen oxides and mercury impurities in the feed. For moisture removal, the moisture adsorption beds in the moisture adsorption system 79 would normally be operated in a pressure swing, temperature swing, or a vacuum swing mode. For pressure or vacuum swing adsorption, the heat of water adsorption would be retained during adsorption and stream 95 at reduced pressure would desorb the moisture. While it is possible to remove moisture by pressure swing adsorption alone, it may be necessary to use the temperature swing adsorption for desorption of other impurities such as the heavy hydrocarbons, sulfur oxides, nitrogen oxides and mercury. This can be done in a cycle comprising three or more beds and is described next.

FIG. 3 exemplarily illustrates the configuration of the moisture adsorption system **79** wherein the moisture and additional impurities, for example, hydrocarbons, sulfur oxides or nitrogen oxides, and mercury are removed by a combination of pressure and temperature swing adsorption. A three-bed pressure and temperature swing adsorption system for the removal of moisture and other impurities is illustrated in FIG. 3; however, the moisture and trace-impurities removal process is not limited to a three-bed system. If the removal of impurities such as sulfur oxides and hydrocarbons is not needed, two beds operating in pressure swing adsorption (PSA), vacuum swing adsorption (VSA), or temperature swing adsorption (TSA) mode can be used. Also, when the system operates in PSA and TSA or VSA and TSA mode, more than two beds can be used for PSA or VSA operation and more than one bed can be used for the TSA operation. The number of moisture adsorption beds in the moisture adsorption system **79** is not critical to the operation of this process. In the system of FIG. 3, the wet feed enters the moisture adsorption system **79** as stream **70** through valves **200**, **210** and **220**, respectively. These valves **200**, **210** and **220** control flow of feed gas into vessels **230**, **235** and **240** respectively. Vessels **230**, **235** and **240** each have first adsorbent layers **230a**, **235a** and **240a** respectively which comprise adsorbents such as activated alumina, silica gel or a molecular sieve such as 3A, 4A, 5A and 13X zeolites for moisture removal. Positioned in vessels **230**, **235** and **240** above layers **230a**, **235a** and **240a** are optional layers **230b**, **235b** and **240b**, respectively, which comprise adsorbent(s) selective for hydrocarbons, nitrogen and sulfur oxides, and mercury. Adsorbents such as activated carbon, zeolites such as 13X, and impregnated aluminas can be used for adsorbing these impurities. Modified activated carbons and silicates can be used for the removal of mercury impurities. The adsorbents in vessels **230**, **235** and **240** are chosen to minimize the adsorption of CO₂ so as to maximize the recovery of CO₂ in the CO₂ adsorption beds **81**. The preferred adsorbents for moisture removal are 3A and 4A zeolites, activated alumina, silica gel, and mixtures of activated alumina and zeolites 3A and 4A.

The outlet ends of vessels **230**, **235**, and **240** are connected to discharge lines with valves **245**, **260**, and **275**, respectively. Depending on the bed undergoing adsorption, dry CO₂-containing stream exits the moisture adsorption system **79** through one of these

valves **245** as stream **72** and is sent to the CO₂ separation system **80**. The purge stream **95** from the CO₂ separation system **80** is used to regenerate the moisture adsorption beds. For the PSA or VSA mode of regeneration, the purge gas **95** enters through valve **290** and then one of the valves **250**, **265**, and **280** and exits the moisture adsorption system **79** via corresponding valves **205**, **215**, and **225** as stream **73**. If an optional vacuum pump **74** is used then the purge gas **95** exits the moisture adsorption system **79** as stream **75**. For the TSA mode of regeneration, the purge gas **95** is heated in the heater or heat exchanger **96** and enters the vessels **230**, **235** and **240** through one of the open valves **255**, **270**, and **285** and exits the moisture adsorption system **79** via corresponding valves **205**, **215**, and **225**. If a vacuum pump **74** is not used the purge gas **95** exits the moisture adsorption system **79** as stream **73**. If a vacuum pump **74** is used the purge gas **95** exits the moisture adsorption system **79** as stream **75**. In normal operation, regeneration of one of the vessels by PSA or VSA and another vessel by TSA is contemplated.

The various layers are preferably contained in single vessels, as shown in the drawing, although each layer may be contained in separate vessels, if desired. The duration of each complete cycle of the PSA stage is, at most, several minutes (mins) typically 4-60 minutes, while the duration of the thermal regeneration is generally about 1-12 hours; accordingly, during any single phase of the process, the two vessels in the PSA or VSA mode will undergo many PSA or VSA cycles while the third vessel undergoes a single thermal regeneration step. For purposes of illustration, it will be assumed that the PSA or VSA process is carried out with pressurization to super atmospheric pressure during the adsorption step and reduction of pressure to atmospheric pressure or below during the bed regeneration step. The pressure in the vessel undergoing thermal regeneration is at or near atmospheric pressure.

The process described below comprises three phases; a first phase, in which vessels **230** and **235** are initially operating in an alternating PSA or VSA cycle and the adsorbent in vessel **240** is undergoing thermal regeneration; a second phase, in which vessels **235** and **240** are operating in an alternating PSA or VSA cycle while the adsorbent in vessel **230** undergoes thermal regeneration; and a third phase, in which

vessels **230** and **240** are operating in an alternating PSA or VSA cycle, while the adsorbent in vessel **235** undergoes thermal regeneration.

At the start of stage 1 of the first phase of the process, one of the vessels **230** or **235**, for example vessel **230** is in the adsorption mode and the other vessel is in the regeneration mode. With vessel **230** starting in the adsorption mode, wet feed **70** enters the bed through open valve **200** and exits the bed through open valve **245**. Prior to start of adsorption, vessel **230** is pressurized to the adsorption pressure through valve **200**. As the feed **70** passes through vessel **230** substantially all of water vapor, hydrocarbons, sulfur oxides, and mercury and some of the nitrogen oxides are removed. The dew point of the gas stream exiting the moisture adsorption system **79** would normally be below -40°C and more preferably below -60°C . For regeneration of bed **235**, part of the purge gas **95** enters through open valves **290** and **265** and picks up moisture from the adsorbent bed **235** and exits through valve **215**. Although not necessary, the purge gas may be heated prior to its use in the PSA or VSA process. The remainder of the purge gas entering the moisture adsorption system **79** is heated in heater or heat exchanger **96** and then flows through the layers **240a** and **240b** in vessel **240**. As the heated purge gas passes through the layers **240a** and **240b** in vessel **240**, the purge gas desorbs the residual moisture, hydrocarbons, nitrogen and sulfur oxides, and mercury from different layers that have gradually built up in this vessel **240** over the previous PSA or VSA stages carried out in this vessel. The regeneration gas, together with the desorbed impurities leaves vessel **240** through open valve **225**. After a certain time based on the moisture concentration in stream **72** and the retention of the heat front in the bed, typically 4 to 60 minutes, vessel **230** starts undergoing regeneration while vessel **235** starts removing moisture and other impurities. Vessels **230** and **235** continue under PSA or VSA operation for a period of several hours or days, typically 8 to 96 hours, while vessel **240** is thermally regenerated during part of this time. The temperatures for thermal regeneration typically range between 100°C and 300°C but can be higher or lower depending on the material. The impurities such as nitrogen and sulfur oxides removed during the thermal regeneration may be sent to the existing nitrogen and sulfur removal systems for further reduction of these impurities.

As the PSA or VSA cycle proceeds in vessels **230** and **235**, various impurities such as sulfur oxides and mercury which are more strongly adsorbed than water vapor accumulate in these vessels as they are not removed during the purge step of the pressure swing or the vacuum swing adsorption. When the buildup of these components in one or more layers reaches the point where it threatens to adversely affect the efficiency of the gas purification process, the first phase of the process is terminated and the second phase is started.

During the second phase of the process vessels **235** and **240** are in alternating PSA or VSA service and the adsorbents in vessel **230** undergo thermal regeneration. At the start of stage 1 of this phase of the process, one of the vessels **235** or **240**, for example vessel **235** is in the adsorption mode and the other vessel is in the regeneration mode. With vessel **235** starting in the adsorption mode, wet feed **70** enters the bed through open valve **210** and exits the bed through open valve **260** and is purified in the process. Prior to start of adsorption, vessel **235** is pressurized to the adsorption pressure through valve **210**. For regeneration of bed **240**, part of the purge gas **95** enters through open valves **290**, and **280**, picks up moisture from the adsorbent bed **240** and exits through open valve **225**. The remainder of the purge gas entering the moisture adsorption system **79** is heated in a heater or heat exchanger **96** and then flows through the layers **230a** and **230b** in vessel **230** and desorbs the residual moisture, hydrocarbons, nitrogen and sulfur oxides and mercury from different layers that have gradually built up in this vessel **230** over the previous PSA or VSA stages carried out in this vessel **230**. The regeneration gas, together with the desorbed impurities leaves vessel **230** through open valve **205**. After a certain time based on moisture concentration in stream **72** and retention of the heat front in the vessel, vessel **235** starts undergoing regeneration while vessel **240** starts removing moisture and other impurities. Vessels **235** and **240** continue under alternating PSA or VSA operation for a period of several hours or days while vessel **230** is thermally regenerated during part of this time.

As the PSA or VSA cycle proceeds in vessels **235** and **240**, various impurities

which are more strongly adsorbed than water vapor buildup in vessels **235**, and **240**. When the buildup of these components in one or more layers reaches the point where it threatens to adversely affect the efficiency of the gas purification process, the second phase of the process is terminated and the third phase is started.

5

During the third phase of the process vessels **230** and **240** are in PSA or VSA service and the adsorbent in vessel **235** undergoes thermal regeneration. Operation of the third phase is similar to the operation of the first and the second phases. After all the three phases are completed the process starts again with phase one and all three phases are repeated in a cyclic manner.

10

Like the PSA or VSA beds, the CO₂ adsorption or reaction beds (beds A to E in FIG. 4) also undergo a cyclic process to provide continuous operation and also to maximize CO₂ recovery. These beds contain one or more materials that have a significant selectivity for CO₂ over other major components of the flue gas, namely oxygen, nitrogen and argon. Some of the materials that can be used to capture CO₂ from the flue gas comprise, for example, activated carbon, carbon molecular sieves, zeolites such as 4A, 5A, 13X, NaY and CaX, metallorganic framework compounds, natural zeolites, modified natural and synthetic zeolites, modified activated carbon, pillared clays and reactive sorbents such as sodium and potassium carbonates, amines or ionic liquids supported on a microporous support.

15

20

Various beds in the CO₂ capture section illustrated in FIG. 4 would typically undergo the steps of adsorption, equalization, rinse with CO₂ product, heating, heating with evacuation, cooling and re-pressurization. Depending on the material and the process conditions different combinations of the steps can be used to maximize the CO₂ recovery. Also in some of the cycles some of the steps such as bed cooling can be eliminated. During the operation of the CO₂ adsorption beds **81**, any sulfur oxide impurities in the feed to the CO₂ capture section are likely to be removed as most adsorbents have a higher affinity for sulfur oxides than CO₂. Since most adsorbents have a higher affinity for CO₂ over nitrogen oxides, most of the nitrogen oxide impurities in

30

the feed to this section would pass through into the CO₂-depleted stream **85** leaving the CO₂ separation system **80**. For CO₂ removal by the chemical reaction, such as with supported carbonates or amines, some of the nitrogen and sulfur oxides may also be removed by chemical reaction.

5

FIG. **4** exemplarily illustrates the configuration of the CO₂ separation system **80** wherein CO₂ is removed from the feed stream by adsorption or chemical reaction and is recovered by heating directly or indirectly by steam, hot water or a dry stream recovered from the CO₂ separation system **80**. A five-bed CO₂ capture process is illustrated
10 schematically in FIG. **4**. The CO₂ feed step and the CO₂ production steps are continuous in this cycle. While the CO₂ capture is illustrated using a five-bed process the CO₂ capture process is not limited to five beds. The process can use less than five beds or more than five beds though a minimum of two beds are required to carry out CO₂ capture and production at the same time. As illustrated in FIG. **4** at any given time, one bed is
15 removing CO₂ from feed using adsorption or reaction, another bed is undergoing equalization and pressurization steps, a third bed is producing CO₂ while being heated, a fourth bed is producing CO₂ during heating and evacuation steps and the fifth bed is undergoing the steps of CO₂ rinse and equalization. Other cycles similar to this can be used omitting the steps such as the CO₂ rinse and adding steps such as bed cooling after
20 the heating steps. The equalization can be done from the bottom, from the top or from both top and the bottom. Pressurization can also be done from the bottom using the feed or from the top using the CO₂-depleted stream.

Each individual step of the CO₂ capture process is likely to be of the order of 2-60
25 minutes to maximize the productivity of the process. A typical cycle using the five-bed configuration of FIG. **4** is given in Table I.

The feed to adsorbers A to E is typically at a temperature between about 10 and 80°C and at pressures between about 1.07 bara and 40 bara, and at a temperature in the
30 range of about 20°C and 60°C. For the CO₂ capture from the flue gas of a power plant or a refinery, the pressures will be in the range of about 1.07 and 1.34 bara. The

regeneration temperatures are in the range of about 80°C and 300°C and more typically in the range of about 80°C-150°C. The concentration of CO₂ in the feed gas is about 3% for a natural gas fired power plant, about 12% for a coal-fired power plant and up to 60% of CO₂ for various chemical processes. Prior to the initial start of CO₂ separation, the
5 beds in adsorbers A to E may be heated to temperatures higher than 300°C to remove any residual moisture contained therein. High temperature regeneration may also be performed to remove impurities built up during normal operation.

The operation of various valves is illustrated using steps 1 and 2 of Table I. In
10 both steps 1 and 2 for bed A, feed gas **72** enters the bed through open valve **302**, CO₂ is captured in the bed and the CO₂-depleted stream exits the bed as stream **85** through the open valve **312**. During step 1, beds B and E undergo pressure equalization through open valves **340** and **430**. During step 2, bed B is pressurized using bed A through open valves **320** and **350**. During both steps 1 and 2, bed C is regenerated by heating under vacuum
15 and valves **366** is open. The high purity CO₂ product leaves as stream **100** prior to entering the vacuum pump **110**. During both steps 1 and 2, bed D is regenerated by heating, valves **398** and **408** are open and product CO₂ leaves as stream **105**. During step 2, bed E is rinsed with product CO₂ stream **145** which enters the bed through open valve **424** and exits through open valve **434**. Operation of various valves during steps 3 to 10 is
20 similar to operation during steps 1 and 2. Once all the steps are completed, the cycle is repeated continuously starting at step 1.

TABLE I
Typical Cycle Sequence for the CO₂ Capture Process

Step	Bed A	Bed B	Bed C	Bed D	Bed E	Time, mins
1	Adsorption/ reaction	Equalization with Bed E	Heating with evacuation	Heating	Equalization with Bed B	2.0
2	Adsorption/ reaction	Pressurization	Heating with evacuation	Heating	CO ₂ rinse	2.0
3	Equalization with Bed C	Adsorption/ reaction	Equalization with Bed A	Heating with evacuation	Heating	2.0
4	CO ₂ rinse	Adsorption/ reaction	Pressurization	Heating with evacuation	Heating	2.0
5	Heating	Equalization with Bed D	Adsorption/ reaction	Equalization with Bed B	Heating with evacuation	2.0
6	Heating	CO ₂ rinse	Adsorption/ reaction	Pressurization	Heating with evacuation	2.0
7	Heating with evacuation	Heating	Equalization with Bed E	Adsorption/ reaction	Equalization with Bed C	2.0
8	Heating with evacuation	Heating	CO ₂ rinse	Adsorption/ reaction	Pressurization	2.0
9	Equalization with Bed D	Heating with evacuation	Heating	Equalization with Bed A	Adsorption/ reaction	2.0
10	Pressurization	Heating with evacuation	Heating	CO ₂ rinse	Adsorption/ reaction	2.0
					Total	20.0 minutes

As shown in Table I, various steps in the CO₂ capture and regeneration process are significantly faster than in a typical temperature swing adsorption process where these steps are of the order of hours. For adsorbents and reactants that are moisture tolerant, fast heating can be accomplished by directly heating the beds with steam though this will have to be followed by a purge to remove steam, and then the beds will have to be cooled. For adsorbents or reactants that are not moisture-tolerant such as zeolites, direct heating with steam is not an option and heating with a dry gas will be too slow. For these cases, the beds may have to be heated indirectly. One such configuration is the shell and tube configuration wherein the adsorbents or reactants are contained in small diameter tubes and the heating medium flows on the shell side during the regeneration part of the cycle. Regeneration temperatures of about 80°C -300°C can be obtained using steam or hot water as the heating medium. A heated liquid or vapor stream utilizing the electricity generated in the power plant can also be used for regeneration. An alternative configuration includes the adsorbent material on the shell side and the heating or the cooling fluid on the tube side. Another configuration that allows indirect heating is a plate and frame configuration wherein adsorbents are contained in alternate parallel passages and the heated fluid flows in alternate parallel passages. Steam or a heated fluid may be used as the heating medium. For the shell and tube configuration and the plate and frame configurations, cold fluid can be used during the CO₂ removal step to remove the heat of adsorption or chemical reaction. Cold fluid can also be used for the bed cooling steps. For retrofit applications it might be easier to use the hot water or low pressure steam as the regeneration medium as this minimizes the disruption to the steam cycle of the power plant and would be easy to retrofit. In addition to the vertical beds both the horizontal and the radial beds can be used for carrying out the cycle. Also, if needed, either the shell and tube configuration or the plate and frame configuration can be used for heat exchange with horizontal or the radial beds.

The CO₂ generated during the heating and the evacuation parts of the cycle would typically have a purity of higher than 90%. This stream is compressed and sent to a CO₂ purification plant as discussed earlier. If a membrane is used for CO₂ purification, a small portion of the CO₂ stream is allowed to permeate the membrane to produce a higher

purity CO₂ stream which is used as the rinse stream in the CO₂ separation system **80**. The rest of the stream may be further compressed and used for enhanced oil recovery, industrial applications or for CO₂ sequestration. If a getter process is used for CO₂ purification impurities such as oxygen and sulfur dioxide are removed by reaction with the getter and the purified CO₂ stream may be further compressed and used in various applications. If a distillation process is used for CO₂ purification, CO₂ is produced as the bottoms product and the non-condensibles are removed as the overheads of the distillation column. Part of the CO₂ produced by distillation may be used to provide the purge in the CO₂ capture section; the rest is pumped to a higher pressure and used for various applications such as enhanced oil recovery or sequestration. The non-condensibles stream may be further purified by a membrane or an adsorption process to recover additional amounts of CO₂.

Example 1:

15

Commercially available 5A zeolite of 8x12 mesh size (about 1.5 mm) was obtained from Aldrich Corporation and loaded in two 18 mm diameter adsorbent beds. The total weight of adsorbent was about 500 grams (gms). A feed stream containing about 12.5% CO₂ with the balance being nitrogen, to simulate flue gas from a coal-fired power plant, was passed through these beds at a flow rate of 11 standard liters/min and at a pressure of 1.34 bara. The standard conditions refer to 21.1°C and 1 bara. The adsorbing bed was cooled with a jacket containing a water/glycol mixture at 30°C. The regenerating bed was heated with a jacket containing water / glycol mixture at 100°C. The concentrations in the CO₂-depleted stream and in the CO₂ product were analyzed using an infrared CO₂ analyzer. The cycle for this process is shown in Table II. After heating, the beds were evacuated to a pressure of about 0.25 bara during the evacuation steps. For these process conditions, an average CO₂ purity of 99.8% and an average CO₂ recovery of 85.8% were obtained.

30

Table II. Two Bed CO₂ Capture Process Cycle

Step #	Bed A	Bed B	Step Time
			Mins
1	Adsorption	Heating with evacuation	8.0
2	Equalization	Equalization	1.0
3	Rinse	Idle	1.0
4	Heating	Idle	7.0
5	Heating	Pressurization	1.0
6	Heating with evacuation	Adsorption	8.0
7	Equalization	Equalization	1.0
8	Idle	Rinse	1.0
9	Idle	Heating	7.0
10	Pressurization	Heating	1.0

Example 2:

The process of Example 1 was run at different adsorption temperatures. Other process conditions, namely the feed pressure, feed CO₂ concentration, and the adsorbent material were the same as in Example 1. Again, the concentrations in the CO₂-depleted stream and in the CO₂ product stream were analyzed using an infrared CO₂ analyzer. The process cycle of Table II was used. For a feed temperature of 20°C, an average CO₂ purity of 99.0% and an average CO₂ recovery of 88% were obtained. For a feed temperature of 40°C, an average CO₂ purity of 99.2% and an average CO₂ recovery of 84% were obtained.

Example 3:

The process of Example 1 was run with a commercially available 13X zeolite of 8x12 mesh size (1.5 mm) obtained from the Aldrich Corporation. The feed pressure, and the feed CO₂ concentration were the same as in Example 1 and the process cycle of Table II was used. Again, the concentrations in the CO₂-depleted stream and in the CO₂ product stream were analyzed using an infrared CO₂ analyzer. For a feed temperature of 20°C, an average CO₂ purity of 98.5% and an average CO₂ recovery of 87% were obtained. For a feed temperature of 30°C, an average CO₂ purity of 98.5% and an average CO₂ recovery of 78% were obtained.

Example 4:

The beds containing 5A as in Example 1 were used (total weight of about 500
5 gms) with a feed stream containing about 3.4% CO₂ with the balance being nitrogen, to
simulate the flue gas from a natural gas fired power plant. The feed was passed through
these beds at a total flow rate of 17 standard liters/min. The adsorbing bed was cooled
with a jacket containing a water/glycol mixture at 20°C. The process cycle in Table II
was used. The regenerating bed was heated with a jacket containing water/glycol mixture
10 at 100°C. The concentrations in the CO₂-depleted stream and in the CO₂ product were
analyzed using an infrared CO₂ analyzer. For these process conditions, an average CO₂
purity of 91% and an average CO₂ recovery of 86% were obtained. The results of this
example indicate that the process of this invention can provide reasonable purities and
recoveries for streams containing very low levels of carbon dioxide such as that from a
15 natural gas fired power plant.

Comparative Example 1:

The 5A zeolite of Example 1 was used to obtain the results for a vacuum swing
20 adsorption process without any thermal regeneration. The feed comprised 12.8% CO₂ at
1.34 bara and 30°C. The beds were evacuated to a pressure of 0.25 bara during the
regeneration step. Both the adsorption and the regeneration steps were carried out at
30°C. The process cycle comprised adsorption, equalization, rinse with pure CO₂,
evacuation, equalization and pressurization steps.

25

For a feed flow of 5.5 standard liters per min and an adsorption time of 4 minutes,
an equalization time of 0.5 minutes, a rinse time of 1.0 minutes, an evacuation time of 4.0
minutes, and a pressurization time of 0.5 minutes, an average CO₂ purity of 81.6% and an
average CO₂ recovery of 25.4% were obtained. The reduction of feed flow to 2.2
30 standard liters per minutes decreased the average purity to 53% and the average recovery
to 26%. For a feed flow of 5.5 standard liters per minute and a faster cycle (2 minute

adsorption, 0.25 minute equalization, 0.5 minute rinse, 2 minute evacuation and 0.25 minute pressurization) an average purity of 59.4% and an average recovery of 43.9% were obtained.

5 Comparison of the results of this example with Example 1 indicates that the performance both in terms of CO₂ recovery and CO₂ purity is significantly worse without thermal regeneration of the beds.

Example 5:

10

Commercially available F-200 activated alumina from Alcoa (1.5 mm size) was loaded in the beds of Example 1. The total weight of the adsorbent was about 300 gms. A feed stream saturated with water at 25°C and containing about 12.5% CO₂ with the balance being nitrogen was passed through these beds at a total flow rate of 10 standard
15 liters/min and at a pressure of 1.34 bara. The cycle comprised an adsorption time of 5 minutes, a purge time of 4.5 minutes, and a pressurization and depressurization time of 0.25 minutes each and was designed to retain most of the heat of water adsorption in the beds. The dry product exiting the adsorbing bed was used for purge after reducing the pressure to about atmospheric. The dew point of the product stream exiting the beds was
20 monitored continuously and the product moisture concentration remained below 1 parts per million (ppm) during a period of five days.

This example illustrates that under certain conditions the feed stream to the CO₂ separation can be dried to very low moisture levels to improve the CO₂ recovery in the
25 CO₂ separation section. The purge gas in a process wherein the moisture is removed prior to CO₂ adsorption would be the CO₂-depleted stream from the CO₂ adsorption section.

The results of these Examples suggest that the process disclosed herein can be used for recovering CO₂ from various process streams at high purity and recovery.
30 Estimates of the energy consumption for this process indicate that the energy required to capture CO₂ for this process is about half the energy required for the amine-based CO₂

capture process.

The method and system disclosed herein for the capture of CO₂ offers a number of advantages. The process can be used both for retrofit applications as well as for the new
5 plants. Modifications required to the power plant for retrofit applications are significantly smaller than those needed for amine-based CO₂ capture. The process is applicable to both coal-fired and natural-gas fired power plants. The process is also applicable to other streams such as the refinery and chemical process streams containing carbon dioxide. Unlike absorption processes where nitrogen and sulfur oxides (NO_x and SO_x) in the feed
10 can react with the solvent irreversibly and require removal to below about 10 ppm levels, the NO_x and SO_x in the feed do not affect the adsorbent adversely. Oxygen in the feed has no effect on the adsorbents unlike absorption-based processes where oxygen degrades the amine solvent. The process provides dry CO₂ product eliminating the drying step prior to CO₂ compression and liquefaction, and the power and capital costs associated
15 with it.

Although the system and methods herein are described with reference to specific examples, the scope of the invention is not limited thereto. For example, the feed gas containing CO₂ can come from other processes such as a natural gas fired power plant or
20 from a coal gasification plant.

The foregoing examples have been provided merely for the purpose of explanation and are in no way to be construed as limiting of the present method and system disclosed herein. While the invention has been described with reference to various
25 embodiments, it is understood that the words, which have been used herein, are words of description and illustration, rather than words of limitation. Further, although the invention has been described herein with reference to particular means, materials and embodiments, the invention is not intended to be limited to the particulars disclosed herein; rather, the invention extends to all functionally equivalent structures, methods and
30 uses, such as are within the scope of the appended claims. Those skilled in the art, having the benefit of the teachings of this specification, may effect numerous modifications

thereto and changes may be made without departing from the scope and spirit of the invention in its aspects.

1 CLAIMS

2
3 I claim:4
5 1. A method for separating carbon dioxide from a gas stream containing water vapor
6 and additional impurities comprising performing the following steps one or more
7 times:8
9 subjecting said gas stream to a first moisture removal step, wherein substantially
10 all of the moisture from gas in the gas stream is removed using a process selected
11 from a group comprising pressure swing adsorption, temperature swing
12 adsorption, membrane separation, and absorption; and13
14 subjecting the substantially water vapor-free gas to a second temperature swing
15 adsorption step, wherein said second temperature swing adsorption step is
16 conducted in a bed comprising an adsorbent, wherein the second temperature
17 swing adsorption step comprises an adsorption step for producing a substantially
18 dry carbon dioxide-depleted stream, and an adsorbent regeneration step
19 comprising heating said adsorbent bed to produce a substantially water vapor-free
20 carbon dioxide stream.21
22 2. The method of claim 1, wherein pressure of the gas stream is in a range of about 1.07
23 to about 40 bar absolute, the carbon dioxide concentration is in a range of about 3%
24 to 60% by volume, and gas temperature is in a range of about 10°C to 80°C.25
26 3. The method of claim 1, wherein duration of said pressure swing adsorption process in
27 said first moisture removal step is in a range of about 4 minutes to about 60 minutes
28 and duration of said temperature swing adsorption process during the first moisture
29 removal step is in a range of about 1 hour to 12.0 hours.30
31 4. The method of claim 1, wherein temperature in the second temperature swing

- 1 adsorption step during said adsorbent regeneration step is increased to about 80°C to
2 300°C.
3
- 4 5. The method of claim 1, wherein duration of the second temperature swing adsorption
5 step is in a range of about 2 minutes to 60 minutes.
6
- 7 6. The method of claim 1, wherein said gas is a flue gas from one of a coal-fired power
8 plant, a natural gas fired power plant, and a refinery.
9
- 10 7. The method of claim 1, wherein adsorbent used in said first moisture removal step is
11 selected from a group comprising activated alumina, silica gel, and a molecular sieve
12 comprising 3A, 4A, 5A and 13X zeolites.
13
- 14 8. The method of claim 1, wherein moisture content in said first moisture removal step
15 is reduced to a dew point of -40°C or below.
16
- 17 9. The method of claim 1, wherein said adsorbent used in the second temperature swing
18 adsorption step is selected from activated carbon, carbon molecular sieves, 4A, 5A,
19 13X, NaY and CaX zeolites, metallorganic framework compounds, natural zeolites,
20 modified natural and synthetic zeolites, modified activated carbon, and pillared clays.
21
- 22 10. The method of claim 1, wherein purity of said substantially water vapor-free carbon
23 dioxide stream produced in the second temperature swing adsorption step is 90% or
24 higher.
25
- 26 11. The method of claim 1, wherein the substantially dry carbon dioxide-depleted stream
27 from the second temperature swing adsorption step is used for one of regenerating the
28 adsorbents or absorbents in said first moisture removal step, and for providing a
29 driving force for a membrane drying step.
30
- 31 12. The method of claim 1, wherein said adsorbent regeneration step comprises heating

- 1 the adsorbent bed directly with a gas stream or indirectly using steam or a hot fluid in
2 a heat exchanger configuration.
3
- 4 13. The method of claim 12, further comprising bed evacuation after bed heating to
5 recover additional amounts of carbon dioxide.
6
- 7 14. The method of claim 1, wherein the second temperature swing adsorption step further
8 comprises the steps of bed equalization, bed pressurization, bed depressurization, and
9 bed cooling.
10
- 11 15. The method of claim 1, wherein impurities in the feed to the second temperature
12 swing adsorption step comprise hydrocarbons, oxygen, nitrogen, argon, and nitrogen
13 oxides.
14
- 15 16. The method of claim 1, wherein said additional impurities selected from the group
16 comprising hydrocarbons, nitrogen oxides, sulfur oxides, and mercury are removed
17 from the gas stream in said first moisture removal step.
18
- 19 17. The method of claim 1, wherein adsorbents used for removal of hydrocarbons,
20 nitrogen oxides, sulfur oxides, and mercury are selected from activated carbon, 13X
21 zeolites, impregnated aluminas, modified activated carbons, and silicates.
22
- 23 18. The method of claim 1, wherein said moisture and additional impurities removal
24 process comprises a system comprising a first adsorption section, a second adsorption
25 section, and a third adsorption section arranged in parallel, each of said first
26 adsorption section, said second adsorption section, and said third adsorption section
27 comprising a first zone containing a moisture removal adsorbent and a second zone
28 containing one or more adsorbents for the removal of impurities selected from
29 hydrocarbons, nitrogen oxides, sulfur oxides, and mercury, comprising performing
30 the following steps one or more times:
31

1 subjecting said gas to a cyclic pressure swing adsorption process comprising
2 alternating adsorption steps and adsorbent regeneration steps in the first
3 adsorption section and the second adsorption section, thereby removing
4 substantially all of the water vapor from the gas, while desorbing water vapor and
5 other impurities from said adsorbents in said first zone and said second zone of
6 said third adsorption section by heating the adsorbents;

7
8 subjecting said gas to a cyclic pressure swing adsorption process comprising
9 alternating adsorption steps and adsorbent regeneration steps in the first
10 adsorption section and the third adsorption section, thereby removing
11 substantially all of the water vapor from the gas, while desorbing water vapor and
12 other impurities from the adsorbents in the first zone and the second zone of the
13 second adsorption section by heating the adsorbents; and

14
15 subjecting said gas to a cyclic pressure swing adsorption process comprising
16 alternating adsorption steps and adsorbent regeneration steps in the second
17 adsorption section and the third adsorption section, thereby removing
18 substantially all of the water vapor from said gas, while desorbing water vapor
19 and other impurities from the adsorbents in the first zone and the second zone of
20 the first adsorption section by heating the adsorbents.

21
22 19. The method of claim 18, wherein the adsorbent heating step is carried out at a
23 temperature in a range of about 80°C-300°C.

24
25 20. The method of claim 1, wherein the gas stream containing water vapor and additional
26 impurities is sent directly to the second temperature swing adsorption step without
27 first removing the moisture and additional impurities, wherein the second temperature
28 swing adsorption step comprises an adsorption step to produce a carbon dioxide-
29 depleted stream, and an adsorbent regeneration step comprising heating the adsorbent
30 bed to produce a substantially pure carbon dioxide stream.

31

- 1 21. The method of claim 20, wherein the adsorbent for the second temperature swing
2 adsorption step is selected from activated carbon, or a carbonate, an amine or an ionic
3 liquid on a microporous support.
4
- 5 22. The method of claim 1, wherein the carbon dioxide stream is further purified by one
6 of a membrane process, a distillation process, an adsorption process, and a getter
7 process to remove impurities comprising nitrogen, oxygen, argon, nitrogen oxides,
8 sulfur oxides, and moisture.
9
- 10 23. The method of claim 22, wherein said purified carbon dioxide is used for providing
11 high purity rinse in a carbon dioxide separation system.




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3




FIG. 4