



(51) International Patent Classification:
A61F 2/24 (2006.01)

(21) International Application Number:

PCT/US2020/016636

(22) International Filing Date:

04 February 2020 (04.02.2020)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/805,125 13 February 2019 (13.02.2019) US

(71) Applicant: **EDWARDS LIFESCIENCES CORPORATION** [US/US]; One Edwards Way, Irvine, CA 92614 (US).

(72) Inventors: **NIR, Noam**; Caesarea Business Park, 8 Haeshel Street, 30889 Caesarea (IL). **SHERMAN, Elena**; Caesarea Business Park, 8 Haeshel Street, 30889 Caesarea

(IL). **BUKIN, Michael**; Caesarea Business Park, 8 Haeshel Street, 30889 Caesarea (IL). **SAAR, Tomer**; Caesarea Business Park, 8 Haeshel Street, 30889 Caesarea (IL).

(74) Agent: **GERMAN, Joel, B.** et al.; Edwards Lifesciences, One Edwards Way, Irvine, CA 92614 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

(54) Title: HEART VALVE FRAME DESIGN WITH NON-UNIFORM STRUTS




FIG. 31

(57) Abstract: An implantable prosthetic valve assembly, according to one embodiment, comprises a frame assembly including a plurality of struts and a prosthetic valve secured inside the frame assembly by sutures. The sutures are inward of the outermost surface of an outer periphery of the frame assembly. In certain embodiments the struts contain recesses in which sutures can be disposed. In other embodiments, the struts can have holes through them which the sutures pass through. The implantable prosthetic valve assembly can also be collapsed within a catheter such that an outermost surface of a periphery of the frame assembly touches the catheter but the sutures are spaced apart from the catheter or are flush with the outer surface of the frame.



GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

HEART VALVE FRAME DESIGN WITH NON-UNIFORM STRUTS

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims the benefit of U.S. Provisional Application 62/805,125 filed on February 13, 2019, which is incorporated by reference herein in its entirety.

FIELD

[0002] The present disclosure relates to implantable devices and, more particularly, to valve prosthetics for implantation into the circulatory system, such as native heart valve annuluses.

BACKGROUND

[0003] The human heart can suffer from various valvular diseases. These valvular diseases can result in significant malfunctioning of the heart and ultimately require replacement of the native valve with an artificial valve. There are a number of known artificial valves and a number of known methods of implanting these artificial valves in humans.

[0004] Various surgical techniques can be used to repair a diseased or damaged valve. In a valve replacement operation, the damaged leaflets are excised and the annulus sculpted to receive a replacement valve. Due to aortic stenosis and other heart valve diseases, thousands of patients undergo surgery each year wherein the defective native heart valve is replaced by a prosthetic valve, either bioprosthetic or mechanical. Another less drastic method for treating defective valves is through repair or reconstruction, which is typically used on minimally calcified valves.

[0005] When a valve is replaced, surgical implantation of a prosthetic valve typically requires an open-chest surgery during which the heart is stopped and patient placed on cardiopulmonary bypass (a "heart-lung machine"). In one common surgical procedure, the diseased native valve leaflets are excised and a prosthetic valve is sutured to the surrounding tissue at the valve annulus. By some estimates, more than 50% of the subjects suffering from aortic stenosis who are more than 80 years old cannot be operated on for aortic valve replacement.

[0006] Because of the drawbacks associated with conventional open-heart surgery, percutaneous and minimally-invasive surgical approaches are garnering intense attention. In one transvascular technique, a prosthetic valve is configured to be implanted in a much less invasive

procedure by way of catheterization. For instance, U.S. Pat. Nos. 7,993,394, 5,411,522, 6,730,118, and 9,393,110, which are incorporated herein by reference, describe collapsible transcatheter heart valves that can be percutaneously introduced in a compressed state from a catheter and expanded at the desired position by balloon inflation or by utilization of a self-expanding frame or stent.

[0007] An important design parameter of a transcatheter heart valve is the diameter of the compressed, folded, or crimped profile. The diameter of the crimped profile is important because it directly influences the physician's ability to advance the valve through the femoral artery or vein. More particularly, a smaller profile allows for treatment of a wider population of patients.

[0008] Some transcatheter heart valve assemblies include a prosthetic valve secured to a collapsible stent or frame assembly by sewing or stitching the soft components to the stent or frame. Suture material is most often used, but any suitable means for attaching the prosthetic valve to the collapsible stent or frame assembly can be used. U.S. Pat. Nos. 7,993,394 and 9,393,110 describe embodiments of transcatheter heart valve assemblies in which prosthetic heart valves are secured to a plurality of axial (i.e. vertical) and angled, circumferential struts and/or nodes by sutures that loop around the struts and/or nodes and through the prosthetic valve.

SUMMARY

[0009] An implantable prosthetic cardiac valve assembly including non-uniform struts and/or nodes is disclosed.

[0010] In certain disclosed embodiments, the prosthetic cardiac valve assembly comprises a collapsible and expandable frame or stent and a prosthetic valve secured within the collapsible and expandable frame or stent. The collapsible and expandable frame or stent can be formed of non-uniform struts. In certain embodiments, the collapsible and expandable frame or stent is formed of non-uniform struts and commissure attachment windows that attach to commissures of the prosthetic valve. In certain embodiments, the collapsible and expandable frame or stent is formed of non-uniform struts and attachment posts that attach to commissures of the

prosthetic valve. In certain embodiments, the collapsible and expandable frame or stent assembly is formed of nitinol or preferably a nickel-cobalt alloy.

[0011] In some embodiments, the prosthetic heart valve has valve components of a Sapien 3 valve, made by Edwards Lifesciences. The disclosed invention can be used with this type or any other suitable type of valve.

[0012] In certain embodiments, the valve has a plurality of non-uniform struts that extend from a first end of the valve assembly to a second end. Some of the struts can extend straight from the first end (i.e. axially) and some of the struts can be angled or extend perpendicular to the axial direction. The struts can be multiple pieces or can be formed as one integral piece. The struts can have a rectangular cross-section, a rounded cross-section, a regularly shaped cross-section, an irregularly shaped cross-section, or a cross-section that changes shape along the length of the strut. The struts can be formed of braided or crimped wires. The struts can meet at junctions called nodes.

[0013] The plurality of non-uniform struts and/or nodes can have depressions of the same or different shapes along their length. Sutures disposed in these depressions are inward of an outermost surface of the prosthetic cardiac valve frame formed by the non-uniform struts. As such, the recessed sutures do not touch the inner surface of a catheter when the prosthetic cardiac valve assembly is collapsed within the catheter. Or, the sutures can be flush with the outermost surface of the prosthetic valve frame.

[0014] The plurality of non-uniform struts and/or nodes can have passages along their length. Sutures disposed through these passages are inward of an outermost surface of a periphery of the prosthetic cardiac frame such that sutures do not touch the inner surface of a catheter.

[0015] In certain embodiments, areas between holes in optional attachment posts are recessed such that sutures disposed through these holes are inward of an outermost surface of the prosthetic cardiac valve frame.

[0016] In a representative embodiment, an implantable prosthetic device can comprise a radially expandable and compressible frame comprising a plurality of interconnected struts, each strut having a first end, a second end, and a length extending from the first end to the

second end. Each strut can comprise a plurality of recesses disposed on one or more longitudinal edges of the strut and extending into a width of the strut.

[0017] In some embodiments, the recesses are configured to retain one or more sutures and prevent the one or more sutures from sliding along the length of the strut. In some embodiments, each recess can extend radially through a thickness of the strut.

[0018] In some embodiments, each strut comprises a plurality of linear segments that are laterally offset from each other in a direction perpendicular to the lengths of the struts, and each linear segment comprises a plurality of recesses. In some embodiments, each linear segment can comprise an identical pattern of recesses.

[0019] In some embodiments, each linear segment can comprise at least first and second recesses, the first recess being located on a first longitudinal edge of the strut and the second recess being located on a second longitudinal edge of the strut. In some embodiments, the first and second recesses can be offset from one another along the length of the strut such that when the frame is in an expanded configuration the first and second recesses are aligned with one another across a width of the strut.

[0020] In some embodiments, the recesses can have a rounded triangular shape.

[0021] In some embodiments, the recesses can be configured to retain a suture in a whip stitch configuration. In other embodiments, the recesses can be configured to retain a suture in a knot configuration comprising one or more knots. In some embodiments, the plurality of recesses are disposed continuously along each longitudinal edge forming a sinusoidal curve.

[0022] In a representative embodiment, a prosthetic valve can comprise a radially expandable and compressible frame, and a skirt mounted to the frame via one or more sutures. The frame can comprise a plurality of interconnected struts, each strut having a first end, a second end, and a length extending from the first end to the second end. Each strut can comprise a plurality of recesses disposed on one or more longitudinal edges of the strut and extending into a width of the strut. The recesses can retain the one or more sutures and prevent the one or more sutures from sliding along the length of the strut.

[0023] In some embodiments, each recess can extend radially through a thickness of the strut. In some embodiments, each strut can comprise a plurality of linear segments that are laterally offset from each other in a direction perpendicular to the lengths of the struts and each linear segment can comprise a plurality of recesses.

[0024] In some embodiments, the recesses can have a rounded triangular shape.

[0025] In some embodiments, the one or more sutures can comprise a whip stitch configuration. In some embodiments, when in the whip stitch configuration, a suture of the one or more sutures can extend through the skirt, around a strut of the plurality of struts, and back through the skirt.

[0026] In other embodiments, the one or more sutures can comprise a knot configuration including one or more knots. In some embodiments, each of the one or more knots is positioned at a center of a width of the strut. In some embodiments, the one or more knots are positioned on a radially inner surface of the strut.

[0027] These features and others of the described embodiments will be more readily apparent from the following detailed description, which proceeds with reference to the accompanying figures.

BRIEF DESCRIPTION OF THE DRAWINGS

[0028] FIG. 1 is a perspective view of an embodiment of a prior art valve assembly;

[0029] FIG. 2 is a perspective view of an embodiment of a prior art valve assembly;

[0030] FIG. 2A is a perspective view of an embodiment of a prior art valve assembly;

[0031] FIG. 3 is a magnified, cut-away view of the prior art valve assembly illustrated by FIG. 1;

[0032] FIG. 3A is an embodiment of a prior art valve;

[0033] FIG. 4 is a magnified, cut-away view of an embodiment of a heart valve assembly having non-uniform struts with recesses;

[0034] FIG. 5 is a side view of an embodiment of a non-uniform strut with a rounded, continuous, helical recess;

[0035] FIG. 6 is a cross-sectional view taken along the plane indicated by lines 6-6 in FIG. 5;

[0036] FIG. 7 is a cross-sectional view taken along the plane indicated by line 7-7 of FIG. 4;

[0037] FIG. 8 is a cross-sectional view of an embodiment of a non-uniform strut that is similar to the embodiment illustrated by FIG. 7 where the strut has a recess that is rounded;

[0038] FIG. 9 is a cross-sectional view of an embodiment of a non-uniform strut that is similar to the embodiment illustrated by FIG. 7 where the non-uniform strut has inner and outer recesses;

[0039] FIG. 10 is a cross-sectional view taken along the plane indicated by line 10-10 of FIG. 4;

[0040] FIG. 11 is a side view of an embodiment of a non-uniform, circular cross-sectioned, strut with a plurality of recesses that each follow the circumference of the strut;

[0041] FIG. 12 is a cross-sectional view taken along the plane indicated by line 12-12;

[0042] FIG. 13 is a cross-sectional view taken along the plane indicated by line 13-13;

[0043] FIG. 14 is a side view of an embodiment of a non-uniform, circular cross-sectioned strut formed of braided wires, with a plurality of recesses that each follow the circumference of the strut;

[0044] FIG. 15 is a cross-sectional view taken along the plane indicated by line 15-15 showing individual wires loosely packed;

[0045] FIG. 16 is a cross-sectional view taken along the plane indicated by line 16-16 showing individual wires tightly packed;

[0046] FIG. 17 is a cross-sectional view of an embodiment of an expanded cardiac valve assembly including a schematic representation of a valve and non-uniform struts;

[0047] FIG. 18 is a cross-sectional view of the valve assembly of FIG. 17 collapsed in a catheter;

[0048] FIG. 19 is a side view of an embodiment of a circular cross-sectioned strut with a plurality of holes that pass through the non-uniform strut;

[0049] FIG. 20 is a cross-sectional view taken along the plane indicated by line 20-20 in FIG. 19;

[0050] FIG. 21 is a cross-sectional view taken along the plane indicated by line 21-21 in FIG. 19;

[0051] FIG. 22 is a side view of an embodiment of a hollow, circular cross-sectioned strut, with a plurality of holes that pass through the strut;

[0052] FIG. 23 is a cross-sectional view taken along the plane indicated by line 23-23 in FIG. 22;

[0053] FIG. 24 is a cross-sectional view taken along the plane indicated by line 24-24 in FIG. 22;

[0054] FIG. 25 is a cross-sectional view of an embodiment of an expanded cardiac valve assembly including a schematic representation of a valve and struts with holes; and

[0055] FIG. 26 is a cross-sectional view of the valve of FIG. 25 collapsed in a catheter.

[0056] FIG. 27A is a side elevational view of an embodiment of a prosthetic valve.

[0057] FIG. 27B is a side elevational view of an embodiment of a prosthetic valve showing the inner skirt and leaflets.

[0058] FIG. 28 is a partial side view of an embodiment of a strut for a frame of a prosthetic valve.

[0059] FIG. 29 is a partial perspective view of an embodiment of a frame that can be used in a prosthetic valve.

[0060] FIG. 30 is a partial side view of an embodiment of a strut for a frame of a prosthetic valve.

[0061] FIG. 31 is a partial perspective view of an embodiment of a frame that can be used in a prosthetic valve.

[0062] FIG. 32 is a partial side view of an embodiment of a strut for a frame of a prosthetic valve.

[0063] FIG. 33 is a partial side view of an embodiment of a strut for a frame of a prosthetic valve.

[0064] FIG. 34 is a partial side view of an embodiment of a strut for a frame of a prosthetic valve.

[0065] FIG. 35 is a partial side view of an embodiment of a strut for a frame of a prosthetic valve.

[0066] FIG. 36 is a partial side view of an embodiment of a strut for a frame of a prosthetic valve coupled to a skirt.

[0067] FIG. 37 is a partial side view of the strut of FIG. 36, shown from the opposite side.

[0068] FIG. 38 is a partial side view of an embodiment of a strut for a frame of a prosthetic valve.

DETAILED DESCRIPTION

[0069] As used herein, the singular forms "a," "an," and "the" refer to one or more than one, unless the context clearly dictates otherwise.

[0070] As used herein, the term "includes" means "comprises." For example, a device that includes or comprises A and B contains A and B but can optionally contain C or other components other than A and B. A device that includes or comprises A or B can contain A or B or A and B, and optionally one or more other components such as C.

[0071] Referring to FIGS. 1, 2A, and 4, the present application relates to implantable prosthetic devices 10 with frames 12 that are configured to inwardly offset sutures 17 used to attach valve components to the frame 12. The term "suture," as used in this application, includes, but is not limited to, polymer materials (e.g., Ethibond sutures), thread, strand, fiber, wire, other windable materials, organic and inorganic materials, or any other material that is acceptable for medical applications and is suitable for joining together the materials used in the various embodiments of the valve assembly.

[0072] The frame 12 can take a wide variety of different forms. While the present application primarily illustrates heart valves as examples, the frame 12 can be the frame of a stent, a docking station, etc. The sutures 17 can attach a wide variety of different structures to the frame 12. For

example, the sutures 17 can attach valve components, covering material, valves, etc. to the frame 12. As shown in FIG. 4, the inward offsetting of the sutures 17 minimizes contact or interaction between the sutures and the valve delivery and/or recapture system and can slightly decrease the overall profile of a crimped valve. In one exemplary embodiment, an outermost surface of the suture can be flush or substantially flush with an outermost surface of the valve frame. Suture damage or breakage due to abrasion or fraying is reduced, and the possibility of damage to the delivery or recapture system (including to the tip of an expandable sheath or tip of a delivery cylinder) from the sutures is also reduced. The pushing force or resistance on the valve as it is passed through the delivery or recapture system is also reduced by minimizing the suture exposure on the outer diameter of the frame, and by minimizing the interaction between the sutures and the delivery or recapture system. This also results in lower maximum stress or strain on a valve assembly during crimping or expansion in delivery, recapture, and fully deployed conditions.

[0073] The concepts described in this application can be used with a wide variety of different valve assemblies. Three of the many valve assemblies that can use the concepts disclosed by the present application are disclosed by U.S. Pat. No. 7,993,394 (see FIGS. 1, 2, and 3), U.S. Pat. No. 9,393,110 (see FIGS. 2A and 3A), and U.S. Publication No. 2018/0153689 (see FIG. 27A) which is incorporated by reference herein in its entirety.

[0074] Referring to FIGS. 1, 2, and 2A, the prosthetic valve 10 disclosed by U.S. Pat. Nos. 7,993,394 and 9,393,110 each comprise a frame, or stent, 12, a leaflet structure 14 supported by the frame, and skirt 16. The valves 10 are typically implanted in the annulus of the native aortic valve but also can be adapted to be implanted in other native valves of the heart or in various other ducts or orifices of the body.

[0075] Each of the valves 10 has a "first" end 80 and a "second" end 82. In the context of the present application, the terms "first" and "second" are used interchangeably with the terms "inflow" and "outflow", respectively. Thus, for example, in the embodiments illustrated in FIGS. 1, 2, and 2A, the first end 80 of the valve is its inflow end and the second end 82 of the valve is its outflow end.

[0076] The valves 10 are configured to be radially collapsible to a collapsed or crimped state for introduction into the body on a delivery catheter and radially expandable to an expanded state for implanting the valve at a desired location in the body (e.g., the native aortic valve). The frames 12 can be made of an expandable material that permits crimping of the valve to a smaller profile for delivery and expansion of the valve using an expansion device such as a balloon. Mechanically expandable frames are also contemplated, such as the frame 301 shown in FIG. 27A. Exemplary plastically-expandable materials that can be used to form the frame are described below.

[0077] Alternatively, valves 10 can be a so-called self-expanding valve wherein the frame is made of a self-expanding material such as Nitinol. A self-expanding valve can be crimped to a smaller profile and held in the crimped state with a restraining device such as a sheath covering the valve. When the valve is positioned at or near the target site, the restraining device is removed to allow the valve to self-expand to its expanded, functional size.

[0078] In the examples of FIGS. 1, 2, 2A and 3A, the frame 12 is an annular, stent-like structure comprising a plurality of vertical and angled struts 40. In this application, the term strut encompasses vertical struts, angled struts, attachment posts, commissure windows, and any similar structures described by U.S. Pat. Nos. 7,993,394 and 9,393,110, and U.S. Pub. No. 2018/0153689. A strut may be any elongated member or portion of the frame 12. In the illustrated examples, the struts are connected together at nodes or connecting portions 32. The frames 12 can have one or more multiple rows that can be made up of angled and vertical struts. Additional details of the frames illustrated by FIGS. 1, 2, 2A, 3A, and 27 can be found in U.S. Pat. Nos. 7,993,394 and 9,393,110, and U.S. Pub. No. 2018/0153689.

[0079] Prosthetic valves 10 can have leafed-valve configurations. The valves 10 can be formed from pieces of flexible, pliant material connected to each other at seams (also referred to as commissure tabs) to form collapsible prosthetic valve leaflets 60. The valves 10 can be connected to their respective frames, 12, at the seams using, for example, sutures 17 and/or flexible connectors 34 (see FIG. 2A). Alternatively, the valves 10 can be a mechanical type valve, rather than a leafed type valve.

[0080] The valves 10 can be made from biological matter, such as natural tissue, pericardial tissue (e.g., bovine, porcine or equine pericardium), a harvested natural valve, or other biological tissue. Alternatively, the valves 10 can be made from biocompatible, synthetic materials (e.g., biocompatible polymers), which are well known in the art. The valves 10 can be shaped to fit the contours of the frames 12 so as to match the frame assemblies in diameter. Flow through the valves 10 proceeds in a direction from first end 80 to second end 82.

[0081] Leaflets 60 can be secured to one another at their adjacent sides to form commissures 84 of the leaflet structure (the edges where the leaflets come together). For example, as shown in FIG. 3, commissures 84 of the leaflet structure 14 can be secured to struts 40 using sutures. Sutures 17 can also be used to attach skirt material 16 to the frame. In another example, as shown in FIG. 2A, commissures 84 of the leaflet structure 14 can be aligned with commissure window portion 33 (of FIG. 3A) or other attachment areas in the frame and secured thereto using flexible connectors 34 (shown in FIG. 2A).

[0082] FIG. 3 further illustrates an implantable prosthetic valve 10 in a magnified, cut-away view wherein the skirt 16 has been removed, but the sutures 17 used to attach the skirt material 16 and the leaflets 60 to the frame 12 remain. FIG. 3 also illustrates how sutures 17 can be wrapped around the struts 40 of frame assembly 12. Sutures 17 can pass through portions of leaflet assembly 14 and/or skirt 16 to secure them to the frame. Sutures 17 secure commissures 84 to vertical struts by looping through spaced apart attachment holes. Additional details of the construction of the valves shown in FIGS. 1, 2, and 2A can be found in U.S. Pat. Nos. 7,993,394 and 9,393,110.

[0083] Suitable materials that can be used to form a frame include, without limitation, stainless steel, nickel based alloy (e.g., a nickel-cobalt-chromium alloy), and polymers, or combinations thereof. In particular embodiments, frames 12 can be made of a nickel-cobalt-chromium-molybdenum alloy, such as MP35NTM (tradename of SPS Technologies), which is equivalent to UNS R30035 (covered by ASTM F562-02). MP35NTM/UNS R30035 comprises 35% nickel, 35% cobalt, 20% chromium, and 10% molybdenum by weight.

[0084] Referring again to FIGS. 1, 2, and 2A, the inner skirt 16 can comprise a tough, tear resistant material such as PET, although various other synthetic or natural materials can be used.

The main functions of the inner skirt 16 are to assist in securing the leaflet structure 14 to the frame 12 and to assist in forming a good seal between the valve and the native annulus by blocking the flow of blood through the open cells of the frame 12 below the lower edge of the leaflets.

[0085] Referring now to FIG. 4, in one exemplary embodiment non-uniform struts 40 allow attachment sutures 17 to secure a prosthetic cardiac valve 10 and/or skirt 16 to a collapsible and expandable frame 12 or stent such that the sutures 17 are recessed away from the inner surface or inner diameter of a catheter when the prosthetic valve assembly is collapsed and inserted into a catheter for delivery to the site of implantation. Or, the sutures 17 can be flush with an outer surface of the frame 12. The prosthetic cardiac valve assembly can incorporate different valve and frame structures than those described above in FIGS. 1, 2, 2A, 3 3A, and 27A in addition to the inventive features described below. In some embodiments, the inventive concepts can be applied to a Sapien 3 valve, made by Edwards Lifesciences. The disclosed invention can be used with any other catheter implanted device, including any other valve, stent, docking station, or frame-like structure.

[0086] FIG. 4 illustrates one embodiment of a prosthetic cardiac valve assembly 30 that has a plurality of axially extending and angled struts 40 and nodes 32. The struts 40 extend from first end 80 to second end 82 and form a periphery of the prosthetic cardiac valve assembly 30. The illustrated periphery is cylindrical in shape, but other shapes can be formed. For example, the periphery of the frame can be oval shaped, kidney shaped, or shaped to approximate the shape of a valve annulus, such as the mitral valve annulus, the pulmonary valve annulus, or the tricuspid valve annulus. The periphery formed by the struts 40 has a radially outermost surface 41 and a plurality of recesses 42 and/or recesses 43. In this application, the radial direction is perpendicular to a direction of travel from the first end 80 to the second end 82. An object that is “radially inward” is closer to the center of the valve than an object that is “radially outward.” In FIG. 4, recesses 42 and 43 are radially inward of the outermost surface of the periphery 41 such that sutures 17 can secure valve 10 to frame assembly 12 without extending radially beyond the outermost surface of the periphery 41. In one exemplary embodiment, when prosthetic valve assembly 30 is collapsed and inserted in a catheter for delivery, sutures 17 do not touch the inner

surface of the catheter. In another exemplary embodiment, the sutures are flush with the outermost surface of the periphery 41.

[0087] Recesses in struts also allow for faster and more accurate placement of securing sutures 17 in either manual or automated production/assembly (e.g., easier to count the appropriate number of sutures, space sutures along a frame strut, or appropriately control suture tension). Additionally, sutures 17 in recesses are less likely to change position relative to the frame assembly either in the frame assembly because attrition and frictional forces are minimized (with recessed struts, frictional forces are not the only force securing the sutures in place and accordingly need not be as high in magnitude).

[0088] In certain embodiments, the cross-sections of struts 40, described above with reference to FIG. 4, are not rectangular, but rounded, circular, having a polygonal shape, having an irregular shape, or having a shape that changes along the length of the strut. The cross-sections of the struts can also remain the same shape, but change size along the length of the strut or going from the first end 80 to the second end 82 of the prosthetic cardiac valve assembly.

[0089] Additionally, while recesses 42 in FIG. 4 are shown evenly spaced, recesses in other embodiments can be irregularly spaced or spaced differently for different struts. Struts 40 and nodes 32 can be made thicker in non-recessed cross-section to accommodate recesses. Recesses can generally be placed in thicker struts or nodes to ensure structural integrity of the strut or node.

[0090] Referring to FIG. 7, a cross-section of a recess 42 taken along line 7-7 in FIG. 4 shows a rectangular recess with square corners 71 (FIG. 7). In other embodiments recesses can be rounded, semi-circular, angular, polygonal, irregular in shape, or have a changing cross-section, and can have a variety of corner shapes. Examples of embodiments with recesses having different cross-sections are described below with reference to FIGS. 6-9.

[0091] Recesses 42 are depressions in the radially outermost surface of the periphery 41 of strut 40 as seen in FIG. 4. In still further embodiments, recesses can be depressions in any surface of a non-uniform strut. Such recesses can form a helical and continuous depression along the strut's surface, depressions in a radially inward surface of a strut, multiple depressions on

multiple sides of a strut, continuous depressions around the circumference or perimeter of a strut, or other configurations.

[0092] FIGS. 5 and 6 show an embodiment of a strut 40 with a circular cross-section and a recess 42 that is helical. For example, the strut illustrated by FIG. 5 has a non-recessed portion 51. In this embodiment, the outermost surface of the valve periphery is a line along the non-recessed portion of the strut 40 that is furthest from the center of the cardiac valve assembly. The recess 42 with a helical path is radially inward of non-recessed portion 51, such that a securing suture 17 in recess 40 would be radially inward of non-recessed portion 51. A suture 17 in the recess 42 with a helical shape is radially inward of the outermost surface of the periphery of the valve assembly. While the helical embodiment is illustrated in FIGS. 5 and 6 as a regular, continuous helical recess, the helical recesses can be interrupted or irregular in shape and spacing.

[0093] FIG. 6 shows a cross-section of the non-uniform strut 40 taken along a plane indicated by lines 6-6. The illustrated recess 42 is a rounded recess with non-rounded corners. This recess in alternate embodiments could have differently shaped cross-sections with different corner configurations, such as rounded and/or chamfered corners.

[0094] FIG. 8 is a cross-sectional view that is similar to the view of FIG. 7. FIG. 8 illustrates that the strut 40 can have a recess that is rounded, with rounded corners. The recess is in an outermost surface of a periphery 41 of the frame 12. FIG. 9 is a cross-sectional view that is similar to the view of FIG. 7. FIG. 9 illustrates that the strut 40 can have recesses at both the inner surface 91 and the outer surface 41 such as any of the shaped illustrated by FIGS. 7-9. In the FIG. 9 embodiment, the strut has recesses 42 that are rounded with rounded corners 81. The recess 42 can extend around the circumference of the strut or two discrete recesses can be formed on opposite sides of the strut. Surface 91 is the radially innermost surface of the strut.

[0095] FIG. 10 is a cross-sectional view of an embodiment of a strut 40 that is vertical and a suture 17 taken along the plane indicated by line 10-10 in FIG. 4. In the example illustrated by FIGS. 4 and 10, the recess 43 extends between two holes 110 that the suture 17 passes through. The recess 43 is illustrated as rectangular with square corners 102. However, the recess can have any shape. As shown in FIG. 10, recess 40 allows the suture 17, that extends between the holes

and is disposed in recess 43, to be inward or flush with the radially outermost surface of the periphery 41. Thus suture 17 would not touch (or would touch with minimal force) the inner surface of a catheter.

[0096] FIGS. 11-13 show side and cross-sectional views of an embodiment of a strut 40 that is non-uniform, circular cross-sectioned, and integrally formed. The strut has a plurality of recesses 42 that each follow the circumference of the strut. Recesses following the circumference or perimeter of a strut can further ease placing of sutures 17. FIG. 12 is a cross-sectional view of a non-recessed portion 112 of strut 40 taken along the plane indicated by line 12-12 in FIG. 11. FIG. 13 is a cross-sectional view of a recessed portion 111 of the strut 40 taken along the plane indicated by line 13-13 in FIG. 11. The diameter of the cross-section of the non-recessed portion 112 is notably larger than the diameter of the cross-section of the recessed portion 111, such that a suture 17 in a recess 42 of strut 40 would be radially inward of or flush with the outermost surfaces of the non-recessed portions 112.

[0097] Struts as described herein can be formed of any of the materials described above as suitable for formation of the frame assembly (desirably a nickel-cobalt based alloy or a Nitinol material). In certain embodiments disclosed here, each strut is integrally formed of one piece. In other embodiments, struts can be formed of multiple pieces or can be formed of multiple wires, such as braided or otherwise bundled wires.

[0098] FIGS. 14-16 are side and cross-sectional views of an embodiment of a strut 40 having a non-uniform, circular cross-section, said strut 40 formed of wires 143. The wires 143 may be braided or otherwise bundled. The struts 40 have a plurality of recesses 141 that each follow the circumference of the strut. FIG. 15 is a cross-sectional view of a non-recessed portion 142 of the strut 40 taken along the plane indicated by line 15-15 in FIG. 14. In FIG. 15, individual wires 143 are loosely packed to form a wider diameter. FIG. 16 is a cross-sectional view of a recessed portion 141 of the strut 40 taken along the plane indicated by line 16-16 in FIG. 14. In FIG. 16, individual wires 143 are more tightly packed to form a narrower diameter. The diameter of the cross-section of non-recessed portion 142 is notably larger than the diameter of the cross-section of recessed portion 141 such that a suture 17 in a recessed portion 141 of strut 40 would be radially inward of or at least flush with the outermost surfaces of the non-recessed portions 142.

[0099] Alternatively, an embodiment of a strut can be formed using braided wires, wherein the changing diameter of the wires forms the recessed and non-recessed portions of the strut instead of the relative tightness of packing/braiding. At portions of such a strut, wires would have wider diameters, naturally forming non-recessed portions of the strut, and at other portions of such a strut, the same wires would have narrower diameters, naturally forming recessed portions of the strut. In further embodiments, combinations of wire diameters and tightness of wire packing/braiding can be used to create recessed and non-recessed portions.

[0100] FIG. 17 is a schematic cross-sectional view of an embodiment of an expanded cardiac valve assembly 170. The valve assembly 170 includes a valve 174 (schematically illustrated), non-uniform struts 40 that form a frame assembly, and sutures 17. The struts have recessed portions 171 and non-recessed portions 172. Sutures 17 secure the valve 174 to struts 40. FIG. 18 illustrates the valve assembly 170 in collapsed form within a catheter 180. An inner surface 181 of the catheter 180 is flush with the outermost surface of the periphery formed by struts 40. Sutures 17 secure the valve 174 to the struts 40 without touching the inner surface 181 of catheter 180 as the sutures 17 are disposed in the recesses 42.

[0101] In still further embodiments described herein, struts 40 (angled and axially extending) and nodes 32 making up a frame assembly can contain holes through which sutures 17 can pass to secure a valve or other structure to the frame assembly. FIG. 19 shows a side view of an embodiment of a strut 40 having a circular cross-section and a plurality of holes 191 that pass through the strut 40. Sutures 17 can pass through holes 191 to secure a valve to strut 40 such that sutures 17 are inward from radially outermost surface 194 of strut 40 (i.e. the axes of the holes are generally parallel to the outer surface of the frame formed from the struts 40, rather than being generally perpendicular to the outer surface of the frame). FIG. 20 is a cross-sectional view of a portion of the strut 40 without any holes, taken along the plane indicated by line 20-20 in FIG. 19. This cross-section is solid, without any empty space, but can be hollow or have another non-solid configuration. FIG. 21 is a cross-sectional view of a portion of the strut 40 with a hole, taken along the plane indicated by line 21-21 in FIG. 19. Arrow B indicates the circumferential direction in the plane of the cross-section in FIG. 21 (i.e. around the circumference of an overall cardiac valve assembly). Holes 191 pass directly through strut 40,

entirely in the circumferential direction, from first hole opening 192 to second hole opening 193. As such, the sutures 17 are spaced apart from the outer circumference of the frame.

[0102] In alternative embodiments, struts can contain holes that do not strictly follow the circumferential direction. A hole can have a first hole opening that is substantially in line with the circumferential direction and then a second hole opening that is angularly displaced from the first, either to be more in line with the radial direction, or to be directed more at the first end 80 or second end 82 of the cardiac valve assembly, or a combination of the two. Holes can form angular or rounded turns mid-strut, or can form straight lines from a first hole opening to a second hole opening through a strut. In still further embodiments, holes are not spaced evenly along struts as they are with holes 191 in strut 40. In all embodiments of prosthetic cardiac valve assemblies including holes, holes are oriented such that sutures 17 disposed through the holes to secure a valve or skirt 16 to the struts 40 are inward of the radially outermost surface of the periphery of the frame formed by the struts.

[0103] In further embodiments of the present prosthetic cardiac valve, non-uniform struts and/or nodes making up a frame assembly can be hollow. Hollow, non-uniform struts can have recesses, holes, or both features. FIG. 22 shows a side view of an embodiment of a strut 40 having a hollow, circular cross-section with a plurality of holes 221 that pass through the strut 40. Sutures 17 can pass through the holes 221 to secure a valve and/or skirt 16 to strut 40 such that sutures 17 are inward from radially outermost surface 224 of strut 40 (i.e. the axes of the holes are generally parallel to the outer surface of the frame formed from the struts 40, rather than being generally perpendicular to the outer surface of the frame). FIG. 23 is a cross-sectional view of a portion of the hollow strut 40 taken along the plane indicated by line 23-23 where there are no holes. A passage 225 extends through the strut. FIG. 24 is a cross-sectional view of a portion of the strut 40 taken with a hole 221, along the plane indicated by line 24-24. Arrow B indicates the circumferential direction in the plane of the cross-section in FIG. 24 (with respect to an overall cardiac valve assembly). Holes 221 pass directly through strut 40, entirely in the circumferential direction, from first hole opening 222 to second hole opening 223. As such, the sutures are spaced apart from the outer circumference.

[0104] FIG. 25 is a cross-sectional view of an embodiment of an expanded cardiac valve assembly 250 including a valve 254 that is schematically illustrated, struts 40 that form a frame,

and sutures 17. The struts 40 have holes 251 that pass through the struts 40 in a generally circumferential direction. Sutures 17 secure the valve 254 to struts 40. FIG. 26 illustrates valve assembly 250 in a collapsed form within a catheter 180. An inner surface 181 of the catheter 180 is flush and in contact with the radially outermost surface of the periphery formed by struts 40. The sutures 17 secure the valve 254 to struts 40 without touching the inner surface 181 of the catheter 180, as sutures 17 are disposed through the holes 251.

[0105] Referring now to FIGS. 27-38, the concepts described above can be used with the prosthetic valve disclosed in U.S. Pub. No. 2018/0153689 (see FIG. 27A). FIG. 27A illustrates one embodiment of a prosthetic cardiac valve 300 having a frame 301 formed from a plurality of interconnected lattice struts 303 arranged in a lattice-type pattern. The lattice struts 303 are shown as positioned diagonally, or offset at an angle relative to, and radially offset from, the longitudinal axis of the prosthetic valve 300. In some embodiments, as shown in FIG. 27B, the prosthetic valve 300 can include an inner skirt 330 sutured to the frame 301, as described in further detail below. The leaflets 60 can be sutured to the skirt 330 along a suture line 332.

[0106] Referring again to FIG. 27A, the lattice struts 303 can be pivotably coupled to one another. In the illustrated embodiment, for example, the end portions of the struts 303 forming the apices 304 at the outflow end 305 and at the inflow end 307 of the frame 301 can have a respective opening (not shown). The struts 303 can be formed with apertures 306 (see FIG. 28) spaced apart along their lengths between the opposite ends of the struts. Respective hinges 308 can be formed at the locations where struts 303 overlap each other between the ends of the frame via fasteners 310, which can comprise rivets or pins that extend through the apertures 306.

[0107] Each lattice strut 303 can have an offset, or zig-zag, pattern defined by a plurality of offset linear portions or segments 312. The linear segments 312 in the illustrated embodiment are arranged end-to-end relative to each other with adjacent ends interconnected to each other by intermediate segments 314. The strut 303 can have enlarged end portions 316 that form the apices 304 at the inflow and outflow ends of the frame. Each linear segment 312 is slightly laterally offset from an adjacent linear segment 312 in a direction perpendicular to the overall length of the strut 303 to provide the zig-zag pattern to the strut. Each of the intermediate

segments 314 and end portions 316 can have a respective aperture 306 at its geometric center for receiving a fastener 310.

[0108] Referring now to FIG. 28, the linear segments 312 can include at least substantially flat or linear opposing longitudinal edges 312a, 312b extending between curved or rounded edges 318 of the intermediate segments 314. In alternative embodiments, the edges 318 of the intermediate segments 314 can be substantially flat or linear edges that extend at an angle between respective ends of the edges 312a, 312b of the linear segments 312.

[0109] The width W1 of each linear segment 312 is defined as the distance measured between the opposing edges 312a, 312b of a segment. Each longitudinal edge 312a can be laterally offset from an adjacent longitudinal edge 312a of an adjacent linear segment 312, and each longitudinal edge 312b is laterally offset from an adjacent longitudinal edge 312b of an adjacent linear segment 312. The width W2 of each intermediate segment 314 and end portion 316 can be greater than the width W1 of the linear segments 312. Further details of the struts can be found, for example, in U.S. Pub. No. 2018/0153689.

[0110] FIGS. 28-38 show an embodiment of a strut 303 having linear segments 312 with a rectangular cross-section. As shown in FIGS. 28-38, each strut 303 can comprise a plurality of recesses 320 formed in the longitudinal edges 312a, 312b. The recesses 320 can be configured to prevent the one or more sutures 322 coupling the valve assembly to the frame 301 from sliding along the length of the strut 303. The recesses 320 can be positioned in any location along the length of the strut 303. In some embodiments, each linear segment 312 can comprise a plurality of recesses 320.

[0111] In some embodiments, each strut 303 of the frame 301 can comprise a plurality of recesses. In other embodiments, only one or more selected struts 303 of the frame 301 include recesses.

[0112] As mentioned previously, recesses can be depressions in any surface of a strut. Each recess 320 can be a depression extending into the width W1 of the strut 303. Each recess 320 can extend radially through the entire thickness of the strut 303 (wherein the thickness of a strut is measured between the radial inner and outer surfaces of the strut along a line perpendicular to the width W1). In the illustrated embodiments, the recesses have a rounded

triangular shape, however, in other embodiments the recesses can have any shape, for example, square, rectangular, circular, T-shaped, L-shaped, J-shaped, etc. In some embodiments, the recesses can be irregular in shape. The recesses can have non-rounded, rounded, and/or chamfered corners. The illustrated embodiments show all recesses 320 having the same shape, however, in other embodiments the recesses can have differing shapes within the same strut or within the same linear segment.

[0113] While in the illustrated embodiments, recesses 320 are shown in the same pattern on each linear segment 312, in other embodiments, each linear segment 312 can comprise a different pattern of recesses 320. In some embodiments, the linear segments 312 can have alternating patterns of recesses.

[0114] Referring now to FIG. 28, in a particular embodiment, each linear segment 312 can comprise four recesses 320. The recesses 320 can be oriented as opposing pairs 320a, 320b and 320c, 320d, wherein one recess of each pair is located on each longitudinal edge 312a, 312b of the linear segment 312. The opposing pairs, for example, recess 320a and recess 320b, can be slightly offset from one another along the length of the strut 303 such that the opposing pairs can become aligned with one another along a circumference of the frame when frame 301 is in its radially expanded configuration and the struts 303 are positioned diagonally. In other embodiments, the opposing pairs can be arranged such that they align with one another across the width of the strut. In the illustrated embodiment, each opposing pair of recesses is positioned adjacent a respective intermediate segment 314. For example, recesses 320a and 320b can be positioned adjacent intermediate segment 314a, and recesses 320c and 320d can be positioned adjacent intermediate segment 314b.

[0115] Referring to FIG. 30, in another particular embodiment, each linear segment 312 can comprise four recesses 320 oriented as opposing pairs 320a, 320b and 320c, 320d wherein one recess of each pair is located on each longitudinal edge 312a, 312b of the linear segment 312. As shown, the opposing pairs can be positioned substantially in the center of the length of the linear segment 312 such that the opposing pairs are closer to one another than to the intermediate segments 314.

[0116] As shown in FIGS. 32-33, in some embodiments, each strut comprises recesses positioned to retain sutures 322 that can be tied in a “whip stitch” configuration. For example, each linear segment 312 can comprise two or more recesses positioned to receive a suture being tied in a whip stitch. A whip stitch is a continuous, running stitch. In some embodiments, a whip stitch can extend through one or more leaflets (not shown) and/or a skirt (not shown), around one or more struts 303, and back through the one or more leaflets and/or the skirt in the same direction. The whip stitch can be repeated as necessary along the length of the strut.

[0117] In some embodiments (see e.g., FIG. 32), each linear segment 312 can comprise two recesses 320a, 320b positioned on opposite longitudinal edges 312a, 312b, respectively, of the linear segment 312. In the illustrated embodiment, recess 320a is positioned adjacent to intermediate segment 314a on longitudinal edge 312b, and recess 320b is positioned adjacent to intermediate segment 314b on longitudinal edge 312a. In other embodiments, the recesses 320 can be positioned in any location along the linear segment and on either longitudinal edge.

[0118] In some embodiments, as shown in FIG. 32, the suture can be tied such that it forms an X over one or more of the intermediate segments 314.

[0119] Referring now to FIG. 33, in some embodiments, each linear segment 312 can comprise three opposing parts of recesses positioned along the length of the linear segment. The recesses 320 can be evenly spaced along the length of the segment 312, with each recess being linearly offset from its corresponding pair. In such embodiments, a suture 322 tied in a whip stitch can be retained within the recesses 320. For example, along a single linear segment 312, a suture 322 moving in a whip stitch can pass through one or more leaflets (not shown) and/or a skirt (not shown), be retained by recess 320b, extend across the width W1 of the strut, be retained by recess 320a, pass through the one or more leaflets and/or the skirt, be retained by recess 320d, extend across the width W1 of the strut, be retained by recess 320c, pass through the one or more leaflets and/or the skirt, be retained by recess 320f, extend across the width W1 of the strut, and be retained by recess 320e.

[0120] In other embodiments, as shown in FIGS. 34 and 36-37, each strut 303 can comprise recesses 320 configured to retain sutures 322 tied in a “knot” configuration. Sutures tied in a

knot configuration can include one or more knots. As shown in FIG. 34, in some embodiments, each linear segment 312 can be configured to retain a knot 324. In other embodiments, each linear segment can comprise recesses configured to retain two or more knots. In some embodiments, the strut can be configured such that alternating linear segments can be configured to retain a knot.

[0121] In some embodiments, the recesses can be positioned such that each knot is located in the center of the width of the linear segment 312. In this way, the knots can be aligned with the intermediate segments 314 such that an imaginary line can pass through the aperture 306 of each intermediate segment 314 and each knot 324 along the length of the strut 303. The knots 324 can therefore form an “anchoring path” along the length of the strut. This allows the leaflets 60 to be attached along the anchoring path, thereby mitigating the potential of a ‘zig-zag’ leaflet shape, which can affect valve performance. In some embodiments, the knot can be located on the radially inner surface of the strut. In other embodiments, the knot can be located on the radially outer surface of the strut.

[0122] In still other embodiments, as shown in FIG. 35, a plurality of recesses 320 can be positioned continuously along each longitudinal edge 312a, 312b of each linear segment 312. For example, the recesses 320 can be positioned such that the recesses 320 form a sinusoidal curve along each longitudinal edge 312a, 312b of the linear segment 312. In the illustrated embodiment, for ease of illustration, recesses are only shown on one segment 312, however, each linear segment can a plurality of recesses positioned continuously along each longitudinal edge. In such embodiments, the suture 322 does not need to be positioned within the recess during the suturing procedure, as the suture will naturally “fall” (e.g., be drawn into) the recess as the suture is tightened.

[0123] FIGS. 36-38 show an inner skirt 330 sutured to a strut 303 with a suture 322. In particular embodiments (e.g., the embodiment of FIG. 27B), the leaflets 60 are not directly sutured to the struts 303 of the frame and instead can be separately sutured to the skirt 330. In this manner, the leaflets 60 are mounted within and connected to the frame via the inner skirt 330. In other embodiments, the leaflets 60 can be connected to the struts 303 of the frame by sutures 322, which are threaded through the skirt 330 as shown and through the leaflets 60.

[0124] The above described configurations can help increase the durability of a prosthetic valve by mitigating sliding of sutures along the longitudinal edges of the struts. The recesses can additionally reduce quality assurance time, as it is easier for an operator to see that the sutures have been tied in a selected configuration.

[0125] Having illustrated and described the principles of the illustrated embodiments, it will be apparent that the embodiments can be modified in arrangement and detail without departing from such principles.

[0126] Further, although the prosthetic valve assemblies of this disclosure are shown generally circular in cross section, these prosthetic valve assemblies can have a D-shape, an oval shape, a kidney shape, the shape of any native heart valve, or any other shape suitable for fitting the contours of the relevant, replaced, native valve.

[0127] For purposes of this description, certain aspects, advantages, and novel features of the embodiments of this disclosure are described herein. The disclosed methods, apparatus, and systems should not be construed as being limiting in any way. Instead, the present disclosure is directed toward all novel and nonobvious features and aspects of the various disclosed embodiments, alone and in various combinations and sub-combinations with one another. The methods, apparatus, and systems are not limited to any specific aspect or feature or combination thereof, nor do the disclosed embodiments require that any one or more specific advantages be present or problems be solved.

[0128] Although the operations of some of the disclosed embodiments are described in a particular, sequential order for convenient presentation, it should be understood that this manner of description encompasses rearrangement, unless a particular ordering is required by specific language set forth below. For example, operations described sequentially can in some cases be rearranged or performed concurrently. Moreover, for the sake of simplicity, the attached figures may not show the various ways in which the disclosed methods can be used in conjunction with other methods. Additionally, the description sometimes uses terms like “provide” or “achieve” to describe the disclosed methods. These terms are high-level abstractions of the actual operations that are performed. The actual operations that correspond to these terms can vary

depending on the particular implementation and are readily discernible by one of ordinary skill in the art.

[0129] In view of the many possible embodiments, it will be recognized that the illustrated embodiments include only examples of the invention and should not be taken as a limitation on the scope of the invention. Rather, the invention is defined by the following claims. We therefore claim as the invention all such embodiments that come within the scope of these claims.

We claim:

1. An implantable prosthetic device, comprising:
a radially expandable and compressible frame comprising a plurality of interconnected struts, each strut having a first end, a second end, and a length extending from the first end to the second end;
wherein each strut comprises a plurality of recesses disposed on one or more longitudinal edges of the strut and extending into a width of the strut.
2. The prosthetic device of claim 1, further comprising one or more sutures extending through the recesses, wherein the recesses retain the one or more sutures and prevent the one or more sutures from sliding along the length of the struts.
3. The prosthetic device of claim 1 or claim 2, wherein each recess extends radially through a thickness of the strut.
4. The prosthetic device of any of claims 1-3, wherein each strut comprises a plurality of linear segments that are laterally offset from each other in a direction perpendicular to the lengths of the struts, wherein each linear segment comprises a plurality of recesses.
5. The prosthetic device of claim 4, wherein each linear segment comprises an identical pattern of recesses.
6. The prosthetic device of any of claims 1-5, wherein the recesses have a rounded triangular shape.
7. The prosthetic device of any of claims 1-5, wherein the recesses have a rectangular shape.
8. The prosthetic device of any of claims 1-5, wherein the recesses are J-shaped.

9. The prosthetic device of any of claims 4-8, wherein each linear segment comprises at least first and second recesses, the first recess being located on a first longitudinal edge of the strut and the second recess being located on a second longitudinal edge of the strut.

10. The prosthetic device of claim 9, wherein the first and second recesses are offset from one another along the length of the strut such that when the frame is in an expanded configuration the first and second recesses are aligned with one another across a width of the strut.

11. The prosthetic device of any of claims 4-10, wherein each linear segment comprises four or more recesses configured as two or more sets of opposing pairs.

12. The prosthetic device of claim 11, wherein each recess in an opposing pair can be slightly offset from the other along the length of the strut so that they are aligned with one another along the circumference of the valve when the valve is expanded.

13. The prosthetic device of claims 4-12, wherein each linear segment is coupled to one or more adjacent linear segments via one or more intermediate segments.

14. The prosthetic device of claim 13, wherein each intermediate segment can comprise an opposing pair of recesses, and wherein a first recess of the opposing pair is disposed on a first linear segment and a second recess of the opposing pair is disposed on a second linear segment.

15. The prosthetic device of claim 2, wherein the one or more sutures form whip stitches extending through the recesses and around the struts.

16. The prosthetic device of claim 15, wherein the prosthetic device comprises one or more leaflets, and wherein in the whip stitches extend through one or more leaflets in a first direction, around a respective strut, and back through the one or more leaflets in the first direction.

17. The prosthetic device of claim 2, wherein one or more knots formed in the one or more sutures are retained in selected ones of the recesses.

18. The prosthetic device of claim 17, wherein the one or more knots are disposed on a radially inner surface of a corresponding strut.

19. The prosthetic device of any of claims 17-18, wherein the one or more knots form an anchoring path along the length of the corresponding strut, and wherein a cusp edge of a respective leaflet is coupled to the anchoring path.

20. The prosthetic device of claim 2, wherein the one or more sutures are tied in an X-shape over one or more of the intermediate segments.

21. The prosthetic device of any of claims 1-20, wherein the plurality of recesses are disposed continuously along each longitudinal edge forming a sinusoidal curve.

22. A prosthetic valve, comprising:
a radially expandable and compressible frame comprising a plurality of interconnected struts, each strut having a first end, a second end, and a length extending from the first end to the second end, each strut further comprising a plurality of recesses disposed on one or more longitudinal edges of the strut and extending into a width of the strut;
a skirt mounted to the frame via one or more sutures; and
wherein the recesses retain the one or more sutures and prevent the one or more sutures from sliding along the length of the strut.

23. The prosthetic valve of claim 22, wherein each recess extends radially through a thickness of the strut.

24. The prosthetic valve of claim 22 or claim 23, wherein each strut comprises a plurality of linear segments that are laterally offset from each other in a direction perpendicular to the lengths of the struts and each linear segment comprises a plurality of recesses.

25. The prosthetic valve of claim 24, wherein each linear segment comprises an identical pattern of recesses.

26. The prosthetic valve of any of claims 22-25, wherein the recesses have a rounded triangular shape.

27. The prosthetic valve of any of claims 22-24, wherein the recesses have a rectangular shape.

28. The prosthetic valve of any of claims 22-24, wherein the recesses are J-shaped.

29. The prosthetic valve of any of claims 24-29, wherein each linear segment comprises at least first and second recesses, the first recess being located on a first longitudinal edge of the strut and the second recess being located on a second longitudinal edge of the strut.

30. The prosthetic valve of claim 30, wherein the first and second recesses are offset from one another along the length of the strut such that when the frame is in an expanded configuration the first and second recesses are aligned with one another across a width of the strut.

31. The prosthetic valve of any of claims 24-30, wherein each linear segment has a substantially rectangular shape in cross-section.

32. The prosthetic valve of any of claims 22-31, wherein the one or more sutures comprise a whip stitch configuration.

33. The prosthetic valve of claim 32, wherein when in the whip stitch configuration a suture of the one or more sutures extends through the skirt, around a strut of the plurality of struts, and back through the skirt.

34. The prosthetic valve of any of claims 22-33, wherein the one or more sutures comprise a knot configuration including one or more knots.

35. The prosthetic valve of claim 34, wherein each of the one or more knots is positioned at a center of a width of the strut.

36. The prosthetic valve of 34, wherein the one or more knots are positioned on a radially inner surface of the strut.

37. The prosthetic valve of any of claims 35-36, wherein the one or more knots form an anchoring path along the length of the corresponding strut, and wherein a cusp edge of a respective leaflet is coupled to the anchoring path.

38. An implantable prosthetic device, comprising:
a radially expandable and compressible frame comprising a plurality of interconnected struts, each strut having a first end, a second end, and a length extending from the first end to the second end;

wherein each strut comprises a plurality of first recesses disposed on one or more longitudinal edges of the strut and extending into a width of the strut; and

wherein each strut comprises a plurality of second recesses disposed on at least one of a radially outer surface and a radially inner surface of the strut and extending into a thickness of the strut.

39. The prosthetic device of claim 38, wherein each strut has a substantially rectangular shape in cross-section.

40. The prosthetic device of any of claims 38-39, wherein each first recess has a rounded triangular shape.

41. The prosthetic device of any of claims 38-40, wherein each second recess has a rectangular shape.

42. The prosthetic device of any of claims 38-41, wherein each strut comprises a plurality of linear segments that are laterally offset from each other in a direction perpendicular to the lengths of the struts, wherein each linear segment comprises a plurality of first and second recesses.

43. The prosthetic valve of claim 42, wherein each linear segment comprises an identical pattern of first recesses.

44. The prosthetic valve of any of claims 38-43, wherein the first recesses are configured as opposing pairs.

45. A prosthetic valve, comprising:
a radially expandable and compressible frame comprising a plurality of interconnected struts, each strut having a first end, a second end, and a length extending from the first end to the second end, each strut further comprising a plurality of recesses disposed on one or more longitudinal edges of the strut and extending into a width of the strut;
a valvular structure secured within the frame by one or more sutures; and

wherein the recesses retain the one or more sutures and prevent the one or more sutures from sliding along the length of the strut.

46. The prosthetic valve of claim 45, wherein one or more struts can comprise holes extending circumferentially through the strut.

47. The prosthetic device of any of claims 45-46, wherein each strut comprises a plurality of linear segments that are laterally offset from each other in a direction perpendicular to the lengths of the struts, wherein each linear segment comprises a plurality of recesses.

48. The prosthetic device of any of claims 45-47, wherein the recesses have a rounded triangular shape.

49. The prosthetic device of any of claims 45-47, wherein the recesses have a rectangular shape.

50. The prosthetic device of any of claims 47-49, wherein each linear segment comprises at least first and second recesses, the first recess being located on a first longitudinal edge of the strut and the second recess being located on a second longitudinal edge of the strut.

51. A prosthetic valve, comprising:
a radially expandable and compressible frame comprising a plurality of interconnected struts, each strut having a first end, a second end, a length extending from the first end to the second end, and first and second longitudinal edges extending along the length;

a valvular structure secured within the frame by sutures that are positioned circumferentially inward of the longitudinal edges.

52. The prosthetic valve of claim 50, wherein each suture is additionally positioned radially inwardly of an outermost surface of the periphery of the frame.
53. The prosthetic valve of any of claims 51-52, wherein each strut is hollow.
54. The prosthetic valve of any of claims 51-53, wherein each strut comprises a plurality of linear segments that are laterally offset from each other in a direction perpendicular to the lengths of the struts, wherein each linear segment comprises a plurality of recesses disposed in one or more longitudinal edges of the linear segment.
55. The prosthetic valve of claim 54, wherein each linear segment comprises at least first and second recesses, the first recess being located on a first longitudinal edge of the strut and the second recess being located on a second longitudinal edge of the strut.
56. The prosthetic valve of any of claims 51-55, wherein the sutures form whip stitches extending around the struts and disposed in one or more recesses in one or more longitudinal edges of the struts.
57. The prosthetic valve of claim 56, wherein the valvular structure comprises one or more leaflets, and wherein in the whip stitches extend through one or more leaflets in a first direction, around a respective strut, and back through the one or more leaflets in the first direction.
58. The prosthetic valve of claim 54, wherein one or more knots formed in the sutures are retained in selected ones of the recesses.
59. The prosthetic valve of claim 58, wherein the valvular structure comprises one or more leaflets, and wherein the one or more knots form an anchoring path along the length of the corresponding strut, and wherein a cusp edge of a respective leaflet is coupled to the anchoring path.




FIG. 1
(PRIOR ART)




FIG. 2
(PRIOR ART)




FIG. 2A
(PRIOR ART)




FIG. 3
(PRIOR ART)




FIG. 3A
(PRIOR ART)




FIG. 4

6/21




FIG. 6




FIG. 5

7/21




FIG. 7




FIG. 8




FIG. 9

8/21




FIG. 10

9/21




FIG. 11




FIG. 12



FIG. 13




FIG. 14




FIG. 15




FIG. 16

11/21




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27A




FIG. 27B

17/21




FIG. 28




FIG. 29

18/21




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 38




FIG. 37




FIG. 36

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2020/016636

A. CLASSIFICATION OF SUBJECT MATTER
INV. A61F2/24
ADD.
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED
Minimum documentation searched (classification system followed by classification symbols)
A61F
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2016/175095 A1 (DIENNO DUSTIN V [US] ET AL) 23 June 2016 (2016-06-23) paragraph [0121] - paragraph [0180]; figures 11-23 -----	1-59
X	US 2008/178459 A1 (BARR A; BARR A P ET AL.) 31 July 2008 (2008-07-31) paragraph [0032] - paragraph [0036]; figures 1A-4B -----	1-59
X	US 2017/065410 A1 (STRAUBINGER HELMUT [DE] ET AL) 9 March 2017 (2017-03-09) paragraph [0198] - paragraph [0244]; figures 5d, 6a-g -----	1-59
A	WO 2018/136959 A1 (CEPHEA VALVE TECH INC [US]) 26 July 2018 (2018-07-26) paragraph [00115]; figure 27Q -----	1-59

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

16 April 2020

Date of mailing of the international search report

24/04/2020

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Varone, Anna

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No PCT/US2020/016636

Patent document cited in search report	Publication date	Patent family member(s)	Publication date	
US 2016175095	A1	23-06-2016	AU 2015364334 A1	01-06-2017
			AU 2019200712 A1	21-02-2019
			CA 2967866 A1	23-06-2016
			CN 107106294 A	29-08-2017
			CN 109758266 A	17-05-2019
			CR 20170313 A	29-08-2017
			EP 3232989 A1	25-10-2017
			JP 6616418 B2	04-12-2019
			JP 2017538518 A	28-12-2017
			JP 2019069166 A	09-05-2019
			US 2016175095 A1	23-06-2016
			US 2016175096 A1	23-06-2016
			US 2018110619 A1	26-04-2018
US 2018206987 A1	26-07-2018			
US 2008178459	A1	31-07-2008	AU 2008211193 A1	07-08-2008
			EP 2107895 A1	14-10-2009
			JP 2010516393 A	20-05-2010
			US 2008178459 A1	31-07-2008
			WO 2008094504 A1	07-08-2008
US 2017065410	A1	09-03-2017	BR 112012021347 A2	24-09-2019
			US 2016331525 A1	17-11-2016
			US 2017049563 A1	23-02-2017
			US 2017065410 A1	09-03-2017
			US 2019224007 A1	25-07-2019
			WO 2011104269 A1	01-09-2011
WO 2018136959	A1	26-07-2018	CA 3051272 A1	26-07-2018
			CN 110621260 A	27-12-2019
			CR 20190381 A	27-09-2019
			EP 3570779 A1	27-11-2019
			JP 2020505980 A	27-02-2020
			US 2018296341 A1	18-10-2018
			US 2019328525 A1	31-10-2019
			WO 2018136959 A1	26-07-2018