

(12) **United States Patent**  
**Ichikawa et al.**

(10) **Patent No.:** **US 10,964,929 B2**  
(45) **Date of Patent:** **Mar. 30, 2021**

(54) **STRUCTURE OF CONNECTION AMONG  
CIRCUIT BODY, BUS BAR AND  
ELECTRONIC ELEMENT**

(71) Applicant: **YAZAKI CORPORATION**, Tokyo  
(JP)

(72) Inventors: **Yoshiaki Ichikawa**, Shizuoka (JP);  
**Kimitoshi Makino**, Shizuoka (JP);  
**Makoto Kobayashi**, Shizuoka (JP);  
**Tomoji Yasuda**, Shizuoka (JP);  
**Masahiro Takamatsu**, Shizuoka (JP)

(73) Assignee: **YAZAKI CORPORATION**, Tokyo  
(JP)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 26 days.

(21) Appl. No.: **16/506,356**

(22) Filed: **Jul. 9, 2019**

(65) **Prior Publication Data**  
US 2020/0020917 A1 Jan. 16, 2020

(30) **Foreign Application Priority Data**  
Jul. 10, 2018 (JP) ..... JP2018-130912  
Jul. 31, 2018 (JP) ..... JP2018-144234

(51) **Int. Cl.**  
**H01M 2/02** (2006.01)  
**H01B 1/20** (2006.01)  
**H05K 1/02** (2006.01)  
**H01M 2/20** (2006.01)  
**H02B 1/20** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **H01M 2/206** (2013.01); **H01M 2/0247**  
(2013.01); **H02B 1/20** (2013.01); **H05K**  
**1/0277** (2013.01)

(58) **Field of Classification Search**  
CPC .. H01M 2/202; H01M 10/4257; H01M 2/266;  
H05K 1/0278  
See application file for complete search history.

(56) **References Cited**  
**U.S. PATENT DOCUMENTS**  
6,172,867 B1 \* 1/2001 Satou ..... G06F 1/1616  
312/223.1  
2002/0141746 A1 \* 10/2002 Manabe ..... G03B 13/18  
396/89

(Continued)

**FOREIGN PATENT DOCUMENTS**


JP 2002-93995 A 3/2002  
JP 2010-257775 A 11/2010

(Continued)

*Primary Examiner* — Imran Akram  
(74) *Attorney, Agent, or Firm* — Kenealy Vaidya LLP

(57) **ABSTRACT**  
A structure of connection among a circuit body, a bus bar and an electronic element includes a circuit body configured by a flexible board on which a wiring pattern is provided, a bus bar attached to a mounting surface of the circuit body, and an electronic element attached to the mounting surface so as to connect the bus bar and the wiring pattern. The bus bar has a fixed portion extending along the mounting surface. The fixed portion is fixed to the mounting surface so that a restricted area which restricts deformation of the mounting surface is formed in a periphery of the fixed portion. The electronic element is arranged in the restricted area and is fixed to the mounting surface.

**5 Claims, 24 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

2003/0137813 A1\* 7/2003 Onizuka ..... H05K 7/026  
361/777  
2010/0271223 A1 10/2010 Ohkura et al.  
2011/0159336 A1\* 6/2011 Ohkura ..... H01M 2/1077  
429/99  
2012/0161677 A1\* 6/2012 Kunimitsu ..... H01M 2/1077  
318/139  
2013/0000957 A1\* 1/2013 Ikeda ..... H01M 2/204  
174/254  
2013/0308282 A1\* 11/2013 Shin ..... H05K 7/14  
361/749  
2014/0370343 A1 12/2014 Nomoto et al.  
2016/0372796 A1\* 12/2016 Nishihara ..... H01M 2/202  
2017/0194721 A1\* 7/2017 Fan ..... H01R 12/52  
2018/0088179 A1\* 3/2018 Ota ..... H01R 12/592  
2018/0130989 A1\* 5/2018 Saito ..... H01M 2/206  
2018/0335060 A1\* 11/2018 Miyashiro ..... B23K 26/28  
2019/0027731 A1 1/2019 Zeng et al.  
2019/0181418 A1 6/2019 Son et al.

FOREIGN PATENT DOCUMENTS

JP 2013-143281 A 7/2013  
JP 2014-220128 A 11/2014

\* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG.5A




FIG.5B




FIG.5C




FIG. 6




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C




FIG.9A




FIG.9B




FIG. 10




FIG.11A




FIG.11B




FIG.12A




FIG.12B




FIG.12C




FIG.13A




FIG.13B




FIG.14A

FIG.14B




FIG. 15




FIG.16A




FIG.16B




FIG.17




FIG.18A




FIG.18B




FIG.19




FIG. 20A




FIG. 20B




FIG.21A




FIG.21B




FIG.21C




FIG.22




FIG.23A




FIG.23B




FIG. 24A





FIG. 24B



## STRUCTURE OF CONNECTION AMONG CIRCUIT BODY, BUS BAR AND ELECTRONIC ELEMENT

### CROSS REFERENCE TO RELATED APPLICATIONS

This application is based on Japanese Patent Application (No. 2018-130912) filed on Jul. 10, 2018 and Japanese Patent Application (No. 2018-144234) filed on Jul. 31, 2018 and, the contents of which are incorporated herein by reference.

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention relates to a structure of connection among a circuit body, a bus bar and an electronic element.

#### 2. Description of the Related Art

Conventionally, a flexible board (FPC: Flexible Printed Circuits) where a wiring pattern is provided has been used as wiring that connects between various electronic devices (for example, see JP-A-2002-093995). The flexible board typically has a structure where a thin-film conductive layer constituting a wiring pattern of a predetermined form (that is, a circuit) is sandwiched between insulating films, and in particular, is characterized by being capable of flexible deformation such as curving while maintaining electric characteristics.

### TECHNICAL FIELD

The present invention relates to a structure of connection among a circuit body, a bus bar and an electronic element, and a bus bar module using the connection structure.

### BACKGROUND ART

Conventionally, a flexible board (FPC: Flexible Printed Circuits) where a wiring pattern is provided has been used as wiring that connects between various electronic devices (for example, see JP-A-2002-093995). The flexible board typically has a structure where a thin-film conductive layer constituting a wiring pattern of a predetermined form (that is, a circuit) is sandwiched between insulating films, and in particular, is characterized by being capable of flexible deformation such as curving while maintaining electric characteristics.

When an electronic element is directly mounted on a flexible board, normally, a reinforcing plate that is more difficult to become deformed than the constituent material (for example, a polyimide film) of the flexible board is provided on the mounting area of the electronic element in order that separation of the portion of connection between the wiring pattern and the electronic element (for example, a soldered portion) or the like does not occur due to a deformation of the flexible board. However, the provision of the reinforcing plate is undesirable from the viewpoint of reduction in the size of the flexible board, reduction in the number of parts and the like. Accordingly, it is desired to suppress deformation of the flexible board in the mounting area of the electronic element without the use of a reinforcing plate.

## SUMMARY OF THE INVENTION

The present invention is made in view of the above-mentioned circumstances, and an object thereof is to provide a structure of connection between a circuit body, a bus bar and an electronic element capable of suppressing deformation of the flexible board in the mounting area of the electronic element.

To attain the above-mentioned object, a structure of connection among a circuit body, a bus bar and an electronic element according to the present invention and a bus bar module according to the present invention are characterized by the following [1] to [5]:

[1] The structure of connection among a circuit body, a bus bar and an electronic element, the connection structure being provided with:

a circuit body configured by a flexible board on which a wiring pattern is provided;

a bus bar attached to a mounting surface of the circuit body; and

an electronic element attached to the mounting surface so as to connect the bus bar and the wiring pattern,

wherein the bus bar has a fixed portion extending along the mounting surface;

wherein the fixed portion is fixed to the mounting surface so that a restricted area which restricts deformation of the mounting surface is formed in a periphery of the fixed portion; and

wherein the electronic element is arranged in the restricted area and is fixed to the mounting surface.

[2] In the connection structure according to the above [1], the fixed portion of the bus bar has a first portion extending in a direction along the mounting surface and a pair of second portions extending in a direction intersecting with the first portion and along the mounting surface; and the first portion and the pair of second portions are fixed to the mounting surface so that the restricted area is formed in a part sandwiched between the pair of second portions.

[3] In the connection structure according to the above [1] or [2],

the electronic element is attached to the mounting surface so as to connect the fixed portion and the wiring pattern.

[4] In the connection structure according to any one of the above [1] to [3],

the fixed portion is higher than the electronic element in a thickness direction of the circuit body; and

the connection structure further being provided with: a sealing member that is arranged in the restricted area formed by the fixed portion and covers the electronic element so as to isolate the electronic element from an outside.

[5] A bus bar module attached to a battery assembly where a plurality of single cells are laminated, the bus bar module being provided with:

a circuit body configured by a flexible board on which a wiring pattern is provided;

a bus bar configured to be connected to an electrode of each of the single cells; and

a holder configured to hold the bus bar and being stretchable and shrinkable in the first direction, wherein the circuit body includes:

a belt-like main line that extends in the first direction;

a belt-like branch line that extends from the main line so as to branch from the main line, a part of the branch line extending in the first direction and including a folded portion having a shape folded back around an axis intersecting with the first direction;

a connection portion provided in a position closer to a distal end of the branch line than the folded portion and configured to be connected to the bus bar; and

an electronic element attached to a mounting surface of the connection portion so as to connect the bus bar and the wiring pattern,

wherein at the connection portion, the circuit body, the bus bar and the electronic element are connected by the connection structure according to any one of the above [1] to [4].

According to the connection structure of the structure of the above [1], the bus bar originally used for electric connection with an external device or the like is used, and the restricted area where deformation of the circuit body is regulated is formed within the mounting surface of the circuit body. For example, if a fixed portion of a form surrounding a specific area is fixed to the mounting surface, the circuit body in the restricted area is in a stretched condition by being supported by the fixed portion. Consequently, even if an external force reaches the circuit body, the circuit body in the restricted area surrounded by the fixed portion is kept in a flat condition and cannot be easily deformed. And the electric element is mounted in the restricted area where deformation is regulated as described above. Thereby, deformation of the circuit body in the mounting area of the electronic element can be regulated without the use of an attached member such as a conventionally used reinforcing plate. In other words, deformation of the flexible board in the mounting area of the electronic element can be appropriately suppressed while reduction in the size of the flexible board and reduction in the number of parts are attained. The above-mentioned "deformation" is a concept including various deformation modes that can affect the condition of attachment of the electronic element to the mounting surface such as curving and flexion of the circuit body in the thickness direction of the circuit body, twisting of the circuit body and bending of the circuit body.

According to the connection structure of the structure of the above [2], by the first portion and the pair of second portions, the fixed portion can be structured that has, for example, a form surrounding a specific area from three sides so that one side is open (as an example, a substantial U shape). At this time, if the electronic element is mounted in the area sandwiched between the pair of second portions, not only separation of the electronic element or the like can be suppressed by regulating deformation of the circuit body but also the wiring pattern connecting with the electronic element can be easily provided through the part having no fixed portion and being open. That is, the connection structure of the present structure can provide a fixed portion of a form excellent in practicality.

According to the connection structure of the structure of the above [3], the fixed portion of the bus bar can be used as the point of contact between the bus bar and the electronic element. Therefore, contribution to reduction in the size and reduction in the cost of the connection structure can be made more than in a case where the point of contact between the bus bar and the electronic element is provided in another portion different from the fixed portion.

According to the connection structure of the structure of the above [4], by the sealing member covering the electronic element (for example, a potting material), the waterproofing property of, for example, the electronic element and the point of contact between the electronic element and the bus bar can be enhanced. Further, if the sealing member is fixed in a state of adhering to the mounting surface, an external force is restrained from reaching the point of contact

between the electronic element and the bus bar by the sealing member, so that deformation of the circuit body is further solidly suppressed. From this point of view, it is preferable that the sealing member be provided so as to fill the entire part of the area formed by the fixed portion of the bus bar.

According to the bus bar module of the structure of the above [5], the folded portion is configured so that the connection portion and the main line are along surfaces different in the thickness direction of the main line. For this reason, when the bus bar module is assembled to the battery assembly, the lower surface of the main line is situated away from the upper surfaces of the single cells. Therefore, for example, it is unnecessary to provide a protecting member or the like for protecting the circuit body between the main line of the circuit body and the upper surfaces of the single cells, so that contribution can be made to reduction in height, reduction in the number of parts, simplification of the manufacturing process and the like of the bus bar module. At this time, if the main line and the branch line have a strength of a degree that can maintain the condition where the main line of the circuit body is away from the upper surfaces of the single cells, the circuit body is self-standing. Moreover, a support member for maintaining such a condition may be used as required. That is, the circuit body may be configured so as to be self-standing to maintain the above-mentioned condition, or may be configured so as to maintain the above-mentioned condition by using a different member or the like.

Further, according to the bus bar module of the above-described structure, the bus bar originally used for electric connection with the single cells is used, and the area where deformation of the circuit body is regulated is formed within the mounting surface of the connection portion. For example, if a bus bar of a form surrounding a specific area is fixed to the mounting surface (specifically, the fixed portion), the circuit body in the area is in a stretched condition by being supported by the fixed portion. Consequently, even if an external force reaches the circuit body, the circuit body in the area surrounded by the fixed portion is kept in a flat condition and cannot be easily deformed. And the electric element is mounted in the area where deformation is regulated as described above. Thereby, deformation of the circuit body in the mounting area of the electronic element can be regulated without the use of an attached member such as a conventionally used reinforcing plate.

As described above, the bus bar module of the present structure is excellent in the assemblability to the battery assembly and the conformability to the deformation of the battery assembly and the manufacturing variations compared with general bus bar modules. Further, the bus bar module of the present structure is capable of appropriately suppressing the deformation of the flexible board in the mounting area of the electronic element while reducing the size and the number of parts of the flexible board particularly at the portion of connection with the bus bar.

According to the present invention, a structure of connection among a circuit body, a bus bar and an electronic element capable of suppressing the deformation of a flexible board in a mounting area of the electronic element, and a bus bar module can be provided.

The present invention has been briefly described above. Further, details of the present invention will be further clarified by reading through the mode for carrying out the

invention (hereinafter, referred to as “embodiment”) described below with reference to the attached drawings.

#### BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is an overall perspective view of a bus bar module according to the present embodiment.

FIG. 2 is a perspective view of a battery assembly to which the bus bar module to which the present invention is applied is assembled.

FIG. 3 is a perspective view where an end portion of a circuit body is enlarged.

FIG. 4 is a perspective view showing the structure of a main line, first branch portions and second branch portions constituting the circuit body.

FIG. 5A is a perspective view showing a condition where the second branch portion is bent in an S shape as a whole, FIG. 5B is a perspective view showing a shape into which the second branch portion is deformed when the bus bar relatively moves rearward, and FIG. 5C is a perspective view of a condition where the bus bar relative moves forward so that the second branch portion stretches.

FIG. 6 is a perspective view showing a part of the holder.

FIG. 7 is a perspective view of an accommodation space in a bus bar accommodating portion.

FIGS. 8A to 8C are perspective views showing modifications of a folded portion of the second branch portion constituting the circuit body; FIG. 8A shows a case where the folded portion is Z-shaped as a whole, FIG. 8B shows a case where the folded portion is C-shaped as a whole, and FIG. 8C shows a case where the folded portion is O-shaped as a whole.

FIG. 9A is a perspective view showing a modification of the first branch portion, and FIG. 9B is a perspective view showing a modification of a position of branch of the main line and the branch line.

FIG. 10 is a perspective view where the periphery of the position of contact between a connection piece of the bus bar and a connection portion of the second branch portion is enlarged.

FIG. 11A is a top view of the periphery of the connection position shown in FIG. 10, and FIG. 11B is an A-A cross-sectional view of FIG. 11A.

FIG. 12A is a view, corresponding to FIG. 11A, of the bus bar module according to a modification of the present embodiment, FIG. 12B is a view, corresponding to FIG. 11A, of the bus bar module according to another modification of the present embodiment, and FIG. 12C is a view, corresponding to FIG. 11A, of the bus bar module according to still another modification of the present embodiment.

FIG. 13A is a perspective view where the periphery of the position of connection between the connection piece of the bus bar and the connection portion of the second branch portion on the bus bar module according to another modification of the present embodiment is enlarged, and FIG. 13B is a B-B cross-sectional view of FIG. 13A.

FIG. 14A is a cross-sectional view corresponding to an upper side metal layer on a part of the circuit body, and FIG. 14B is a cross-sectional view corresponding to a lower side metal layer on part of the circuit body.

FIG. 15 is a cross-sectional view where the periphery of one branch portion on the circuit body shown in FIG. 14A is enlarged.

FIG. 16A is a cross-sectional view corresponding to the upper side metal layer in the periphery of the front end portion of the circuit body, and FIG. 16B is a cross-sectional

view corresponding to the lower side metal layer in the periphery of the front end portion of the circuit body.

FIG. 17 is a cross-sectional view corresponding to FIG. 16B at the front end portion of the circuit body according to another modification of the present embodiment.

FIG. 18A is a perspective view showing a manner in which a cover is attached to the holder of the bus bar module, and FIG. 18B is a perspective view showing the condition where the cover is attached to the holder of the bus bar module.

FIG. 19 is a side view for explaining the position of engagement between the holder and the cover.

FIG. 20A is a perspective view of a cover in the assembled condition, and FIG. 20B is an exploded perspective view of the cover.

FIG. 21A is an upper view of the cover in the assembled condition, FIG. 21B is a cross-sectional view corresponding to the C-C cross section of FIG. 21A on the cover in the most stretched condition, and FIG. 21C is a cross-sectional view corresponding to the C-C cross section of FIG. 21A in the most shrunken condition.

FIG. 22 is a perspective view showing the condition where a protector attached to the circuit body exposed from the cover is fixed to the cover.

FIG. 23A is an upper view of the protector attached to the circuit body exposed from the cover, and FIG. 23B is a lower view of the protector attached to the circuit body exposed from the cover.

FIG. 24A is a schematic view for explaining a manner in which a connector provided on the front end portion of the circuit body moves forward under the condition where the protector is fixed to the cover, and FIG. 24B is a schematic view for explaining a manner in which the connector provided on the front end portion of the circuit body moves rearward under the condition where the protector is fixed to the cover.

#### DETAILED DESCRIPTION OF THE EXEMPLARY EMBODIMENTS

##### Embodiment

Hereinafter, referring to the drawings, a bus bar module 10 using a structure of connection among a circuit body, a bus bar and an electronic element according to an embodiment of the present invention will be described. The bus bar module 10 according to the present embodiment is used in such a manner as to be assembled to a battery assembly (a battery module where a plurality of single cells are disposed so as to be assembled) as a driving power source mounted on, for example, an electric car and a hybrid car. (Structure of the Battery Assembly)

First, a battery assembly 1 to which the bus bar module 10 of the present embodiment is attached will be described. As shown in FIG. 2, the battery assembly 1 is formed by linearly connecting a plurality of single cells 2. The single cells 2 each have a positive electrode 4 and a negative electrode 5 provided so as to project on the top portion of a battery body (body) 3 formed in a rectangular shape. The positive electrode 4 and the negative electrode 5 are disposed away from each other on an electrode surface 6 of the battery body 3, and are each provided so as to substantially project vertically upward from the electrode surface 6 in a cylindrical shape.

In the battery assembly 1, the single cells 2 are arranged so as to be assembled in a predetermined direction (assembled direction) in such a manner that the positive elec-

trodes 4 and the negative electrodes 5 of the adjoining single cells 2 alternate with each other. In this battery assembly 1, for example, the positive electrode 4 of one of the single cells 2 corresponding to both ends of the series-connected single cells 2 is the total positive electrode, whereas the negative electrode 5 of the other of the single cells 2 is the total negative electrode.

(General Structure of the Bus Bar Module)

Next, the bus bar module of the present embodiment will be described. As shown in FIG. 1, the bus bar module 10 has: a circuit body 20 formed of a flexible board (FPC) and to which bus bars 25 (see FIG. 3) connected to the positive electrodes 4 and the negative electrodes 5 of the single cells 2 are attached; and a holder (wire routing member) 30 for accommodating and holding the circuit body 20 and for the attachment to the battery assembly 1.

As shown in FIGS. 1 and 3, the circuit body 20 has a belt-like main line 21 disposed in the assembled direction on the single cells 2 and where a plurality of wiring patterns (details will be described later) are provided. To an end portion of the main line 21, a connector 212 is attached through a voltage detection line 211 pulled out from the main line 21. The connector 212 is connectable to a later-described voltage detector 60 (see FIG. 22).

On the side portions of the main line 21 in the length direction (in the present example, substantially coinciding with the "assembled direction" of the battery assembly 1), belt-like first branch portions 22 extending in a direction intersecting with the length direction and thickness direction of the main line 21 (outside of the main line 21 in the width direction) are provided, and at the leading end of each first branch portion 22, a belt-like second branch portion 23 extending in a direction parallel to the assembled direction of the battery bodies 3 is provided. The main line 21, the first branch portions 22 and the second branch portions 23 are formed of an FPC. Therefore, the main line 21, the first branch portions 22 and the second branch portions 23 are flexibly deformable particularly in a direction orthogonal to the surface of each.

As shown in FIGS. 4 and 5A, the second branch portions 23 each have a folded portion 231 folded back around axes L1 and L2 (in other words, around axes extending in the width direction of the second branch portion 23) intersecting with the assembled direction of the battery assembly 1 (in the present example, substantially coinciding with the extension direction of the second branch portion 23). In the present example, the second branch portions 23 are each bent in an S shape (including an inverted S shape) as a whole by a first folded portion 231A folded back with respect to the axis L1 and a second folded portion 231B folded back with respect to the axis L2. For this reason, the second branch portion 23 is movable in the length direction of the main line 21 (the assembled direction of the battery assembly 1) and stretchable and shrinkable also in the vertical direction.

The first branch portion 22 is provided so as to be flush with the main line 21 outside the main line 21, and the second branch portion 23 is connected to the first branch portion 22. For this reason, the second branch portion 23 is provided outside the main line 21 in the width direction, and is provided so as to be S-shaped downward under the condition where the relative positions of the battery assembly 1 and the circuit body 20 do not change (see FIG. 5A). For this reason, the bus bar 25 is situated below the plane of the main line 21 outside the main line 21 in the width direction.

Moreover, on the end portion of the second branch portion 23 opposite to the first branch portion 22, a leading end

portion 232 having a surface substantially parallel to the main line 21 is provided, and to the upper surface of the leading end portion 232, a connection portion 24 is attached. The lower surface of the connection portion 24 is provided parallel to the lower surface of the main line 21 in a different height position, and the lower surfaces are away from each other. The upper surface of the connection portion 24 is connected to the bus bar 25 connecting the positive electrode 4 and the negative electrode 5 of the adjoining single cells 2 in the battery assembly 1. Thereby, the second branch portion 23 is connected to the electrodes of each single cell 2 through the connection portion 24 and the bus bar 25, so that the voltage detection line 211 is connected to the electrodes.

As shown in FIGS. 3 and 5A to 5C, the bus bar 25 has: a bus bar body 251 which is a plate-like member formed of a conductor (for example, made of copper) and is rectangular as a whole; and a connection piece 252 projecting from the bus bar body 251 toward the main line 21. The bus bar body 251 is provided with two electrode holes 253 through which the positive electrode 4 and the negative electrode 5 of the adjoining single cells 2 are passed. At the end portion on the side of the main line 21 and the end portion on the opposite side on the bus bar body 251, positioning concave portions 254 are provided so as to correspond to intervals between the two electrode holes 253. Moreover, to the lower surface of the connection piece 252 of the bus bar body 251, the connection portion 24 of the second branch portion 23 is connected. A concrete form of the connection between the connection piece 252 of the bus bar 25 and the connection portion 24 of the second branch portion 23 will be described later.

A bus bar 25A provided on each end of the main line 21 in the length direction is connected to the total positive electrode or the total negative electrode, and is provided with one electrode hole 253 through which the total positive electrode or the total negative electrode is passed. To the bus bar 25A, a power cable (not shown) that derives power from the battery assembly 1 is connected. The internal structure of the main line 21, the first branch portions 22 and the second branch portions 23 constituting the circuit body 20 will be described later.

(Structure of the Holder)

As shown in FIG. 6, the holder 30 is formed of, for example, resin, and has, in a central portion in the width direction, a main line accommodating portion 31 extending in the assembled direction of the single cells 2 and accommodating and holding the main line 21. The main line accommodating portion 31 is provided with main line support members 311 at predetermined intervals in the length direction of the main line 21 that it accommodates, and the main line 21 is routed on the main line support members 311. When the main line 21, the first branch portions 22 and the second branch portions 23 have a strength of a degree capable of maintaining a condition where the circuit body 20 of the present example is self-standing without the support by the main line support members 311, it is unnecessary to provide the main line support members 311. However, even in this case, the main line support members 311 may be provided in order to deliver an auxiliary support function when the circuit body 20 cannot maintain the self-standing condition for some reason. As described above, the circuit body 20 may be configured so as to maintain the above-mentioned condition by using the main line support members 311 or may be configured so as to be self-standing without the use of the main line support members 311.

On each outer side of the main line accommodating portion **31** in the width direction, a bus bar accommodating portion **32** accommodating the bus bar **25** is provided. In the bus bar accommodating portion **32**, a plurality of accommodation spaces **33** accommodating the bus bars **25** are provided in the assembled direction of the single cells **2**. As shown also in FIG. 7, the adjoining accommodating spaces **33** are separated by partitions **34** to prevent contact between the adjoining bus bars **25**. On each end portion of the main line **21** in the length direction, an accommodation space **33A** accommodating the bus bar **25A** connected with the power cable (not shown) is provided, and a power cable accommodating portion **36** is provided continuously with the accommodation space **33A**.

As shown in FIG. 7, the accommodation space **33** is a rectangular space that is open at the top and partitioned by an outer wall **331** on the outside and an inner wall **332** on the inside in the width direction, and a pair of partitions **34** on both sides in the assembled direction. One side of each partition **34** in the assembled direction (left side in FIG. 7) is connected to the outer wall **331** and the inner wall **332** through a stretching and shrinking portion **35**. Consequently, the accommodation space **33** is stretchable and shrinkable in the assembled direction.

The lower end portion of the outer wall **331** and the lower end portion of the inner wall **332** are coupled by a coupling plate **333**. On the lower end portion of the outer wall **331** and the lower end portion of the inner wall **332**, engagement claws **334** are provided on both sides with the coupling plate **333** in between. This enables the bus bar **25** to be held between the coupling plate **333** and the engagement claws **334**. Moreover, on the inner side surface of the outer wall **331** and the inner side surface of the inner wall **332**, projections **338** are provided so as to project inward in a central portion in the assembled direction. These projections **338** are fitted in the positioning concave portions **254** of the bus bar **25** (see FIG. 5A) to position the bus bar **25**.

The inner wall **332** is provided with a cut part **336**, and in correspondence with the cut part **336**, a support plate **337** is provided so as to project inward. Thereby, the connection piece **252** of the bus bar **25** accommodated in the accommodation space **33** is supported by the support plate **337**.

Moreover, on each side of the coupling plate **333** in the coupling direction, a space **335** is provided. Consequently, the positive electrode **4** and the negative electrode **5** of the single cell **2** can be exposed to the inside of the accommodation space **33** from the space **335**, so that they can be connected to the electrode holes **253** of the bus bar **25** accommodated in the accommodation space **33**. Instead of the coupling plate **333**, a bottom plate may be provided where cut parts or holes corresponding to the positive electrode **4** and the negative electrode **5** of the single cell **2** are provided.

As shown in FIG. 1, the holder **30** accommodates and holds a part of the circuit body **20** situated on the rear of a position a predetermined length behind the front end of the main line **21** to which the connector **212** is attached (in other words, of the circuit body **20**, a part within a range where at least the position of branch of the main line **21** and the first branch portion **22** is present). In other words, the part of a predetermined length from the front end of the main line **21** to which the connector **212** is attached (hereinafter, referred to as "exposed part **213**") is not accommodated in the holder **30** but exposed from the holder **30**.

(Operation of the Bus Bar Module)

Next, the operation of the bus bar module **10** will be described. FIG. 5A shows a condition where the second

branch line is bent in an S shape as a whole, FIG. 5B shows a condition where the second branch line slightly stretches rearward, and FIG. 5C shows a condition where the second branch line stretches forward.

As described above, the main line **21** is routed on the main line support members **311** of the holder **30**, and movable upward and in the length direction. Moreover, the bus bar **25** is fixed to the inside of the accommodation space **33** of the holder **30**, and the accommodation space **33** is movable in the length direction of the main line **21**. The main line **21** and the bus bar **25** are connected through the second branch portion **23** bent in an S shape (see FIG. 5A).

Even if the relative positions of the battery assembly **1** and the circuit body **20** are changed, for example, due to a deformation of the battery assembly **1** under this condition and this changes the relative positions of the main line **21** and the bus bars **25**, the changes (shifts) of the relative positions can be absorbed by the bending and stretching of the second branch portions **23**. Likewise, even if the size of the battery assembly **1** in the assembled direction differs among the manufactured battery assemblies **1** due to the assembly tolerances of a plurality of single cells **2**, the manufacturing variations can be absorbed by the bending and stretching of the second branch portions **23**.

More specifically, FIG. 5B shows a case where the bus bar **25** is slightly shifted rearward (rightward in FIG. 5B) with respect to the main line **21**. In this case, the S shape of the folded portion **231** of the second branch portion **23** is deformed to thereby allow the shift of the bus bar **25**. Moreover, FIG. 5C shows a case where the bus bar **25** is largely shifted forward (leftward in FIG. 5C) with respect to the main line **21**. In this case, the S shape of the folded portion **231** of the second branch portion **23** stretches to allow the shift of the bus bar **25**. Although not shown, when the main line **21** moves upward or downward to change the position relative to the bus bar **25**, the S shape of the folded portion **231** stretches in the vertical direction to thereby allow the change of the relative position.

In the above-described embodiment, a case is described where the folded portions **231** of the second branch portions **23** are bent in an S shape (including an inverted S shape) as a whole. In addition, as shown in FIG. 8A, the folded portions **231** may be folded in a Z shape (including an inverted Z shape) as a whole. Moreover, as shown in FIG. 8B, the folded portions **231** may be formed in a C shape (including an inverted C shape) as a whole. Further, as shown in FIG. 8C, the folded portions **231** may be formed in an O shape as a whole. As in the example shown in FIG. 8C, the branch lines **22** and **23** may be configured so that the lower surface of the main line **21** and the lower surfaces of the connection portions **24** are flush with each other as required.

Moreover, for example, in the above-described embodiment, a case is described where the first branch portions **22** extend on the same plane as the main line **21**; however, as shown in FIG. 9A, the first branch portions **22** may be provided in a direction intersecting with the lower surface of the main line **21** (for example, a downward direction orthogonal to the main line **21** in FIG. 9A). Further, for example, in the above-described embodiment, a case is described where the first branch portions **22** branch from side portions of the main line **21**, as shown in FIG. 9B, an opening **29** may be provided in a central area different from the side portions of the main line **21** so that the first branch portions **22** branch from the central area of the main line **21**.

11

(Internal Structure of the Main Line and the Branch Lines Constituting the Circuit Body)

Next, referring to FIGS. 11B, 14A, 14B and 17, the internal structure of the main line 21, the first branch portions 22 and the second branch portions 23 constituting the circuit body 20 will be described.

As described above, the main line 21, the first branch portions 22 and the second branch portions 23 constituting the circuit body 20 are formed of an FPC. As shown in FIG. 11B, (the FPC constituting) the circuit body 20 is formed of a resin layer 201, and an upper side metal layer 203a and a lower side metal layer 203b so as to be sandwiched in the resin layer 201. Typically, the resin layer 201 is made of polyimide, and the upper side metal layer 203a and the lower side metal layer 203b are made of copper (Cu). As described later, in the present embodiment, a conventionally required reinforcing plate for suppressing a deformation, such as curving and the like of the circuit body 20 can be omitted by supporting the circuit body 20 with the bus bars 25. In actuality, the circuit body 20 is provided with an adhesive layer (not shown) that tightly fixes these layers together. However, for convenience of explanation, the illustration of the adhesive layer is omitted in FIG. 11B.

The upper side metal layer 203a situated on the upper side (obverse side) of the center of the resin layer 201 in the thickness direction and the lower side metal layer 203b situated on the lower side (reverse side) of the center of the resin layer 201 in the thickness direction are embedded inside the resin layer 201. The upper side metal layer 203a and the lower side metal layer 203b are separated from each other in the thickness direction of the resin layer 201, and the resin layer 201 is interposed therebetween. That is, the upper side metal layer 203a and the lower side metal layer 203b are insulated from each other.

As shown in FIGS. 14A and 16A, the upper side metal layer 203a forms upper side wiring patterns 204a as part of the above-mentioned plurality of wiring patterns, upper side dummy patterns 205a independent of the upper side wiring patterns 204a and the above-described connection portions 24 independent of the upper side wiring patterns 204a.

As shown in FIGS. 14B and 16B, the lower side metal layer 203b forms lower side wiring patterns 204b as the remaining part of the above-mentioned plurality of wiring patterns and lower side dummy patterns 205b independent of the lower side wiring patterns 204b. The corresponding upper side wiring patterns 204a and lower side wiring patterns 204b are interconnected so as to be electrically continuous with each other in the thickness direction of the circuit body 20 through corresponding via holes 206 (see FIGS. 14A, 14B, 16A and 16B).

As shown in FIGS. 14A, 14B, 16A and 16B, regarding the first and second branch portions 22 and 23, on one side in the width direction (the right side in FIGS. 14A and 14B), of the plurality of first branch portions 22 and second branch portions 23 provided on both sides of the main line 21 in the width direction, the corresponding upper side wiring patterns 204a continuously extend from the neighborhood of the tail end portions of the second branch portions 23 by way of the first and second branch portions 22 and 23 and the main line 21 over to the connector 212 connected to the front end portion of the circuit body 20, whereby the first and second branch portions 22 and 23 and the connector 212 are connected so as to be electrically continuous.

On the other hand, regarding the first and second branch portions 22 and 23, on the other side in the width direction (the left side in FIGS. 14A and 14B), of the first and second branch portions 22 and 23, first, as shown in FIG. 14A, the

12

corresponding upper side wiring patterns 204a extend from the neighborhood of the tail end portions of the second branch portions 23 by way of the first and second branch portions 22 and 23 up to the via holes 206 in the neighborhood of the first branch portions 22 on the main line 21. And as shown in FIG. 14B, from the via holes 206, the corresponding lower side wiring patterns 204b extend up to the via holes 206 (see FIG. 16B) in the neighborhood of the connector 212 on the main line 21. Further, as shown in FIG. 16A, from the via holes 206, the corresponding upper side wiring patterns 204a extend up to the connector 212, whereby the first and second branch portions 22 and 23 and the connector 212 are connected so as to be electrical continuous. That is, at the portion of connection with the connector 212 on the main line 21, the upper side wiring patterns 204a corresponding to all the first and second branch portions 22 and 23 provided on both sides in the width direction are connected to the connector 212 (see FIG. 16B), and no lower side wiring patterns 204b connected to the connector 212 are present (see FIG. 16B).

By bringing the upper side wiring patterns 204a and the lower side wiring patterns 204b together to the connector 212 by using both the upper side metal layer 203a and the lower side metal layer 203b as described above, a plurality of wirings extending from a plurality of bus bars 25 can be connected to the connector 212 while being rearranged in the order corresponding to the order of arrangement of the single cells 2 (see FIG. 2). That is, the wiring patterns can be arranged in the order of potentials.

As shown in FIGS. 14A, 14B, 16A and 16B, the upper side dummy patterns 205a and the lower side dummy patterns 205b are formed, mainly, in the nearly entire area except the area occupied by the upper side wiring patterns 204a and the lower side wiring patterns 204b in the part of the main line 21 accommodated in the holder 30 (that is, the part except the exposed part 213). The upper side dummy patterns 205a and the upper side wiring patterns 204a, and the lower side dummy patterns 205b and the lower side wiring patterns 204b are disposed away from each other so as not to be electrically continuous. These upper side dummy patterns 205a and lower side dummy patterns 205b are provided mainly in order that the stiffness of the part of the main line 21 accommodated in the holder 30 (that is, the part except the exposed part 213) is higher than that of the first and second branch portions 22 and 23.

Further, as shown in FIG. 16B, the lower side dummy patterns 205b (hereinafter, referred to particularly as “connector connection portion dummy patterns 207”) are formed in a predetermined area in the length direction and substantially over the entire area in the width direction at the portion of connection between the main line 21 and the connector 212. In other words, the connector connection portion dummy patterns 207 are provided so as to be multilayered with respect to the upper side wiring patterns 204a connected to the connector 212.

Since a multiplicity of upper side wiring patterns 204a are densely connected to the connector 212 as described above, the points of contact between the terminals incorporated in the connector 212 and the upper side wiring patterns 204a are also dense. For this reason, the heat caused by the contact resistance at each point of contact concentrates in a small space in the connector 212. It is desirable to release this heat to the outside of the connector 212. In this regard, since the connector connection portion dummy patterns 207 made of a metal are high in thermal conductivity, the heat inside the connector 212 can be released to the outside through the connector connection portion dummy patterns 207. There-

13

fore, by providing the connector connection portion dummy patterns 207, the performance of heat release from the connector 212 can be made higher than in a mode where no connector connection portion dummy patterns 207 are provided. In addition, since the stiffness of the main line 21 at the portion of connection with the connector 212 can be made higher by providing the connector connection portion dummy patterns 207 than in the mode where no connector connection portion dummy patterns 207 are provided, for example, separation of the point of contact between the terminals and the upper side wiring patterns 204a due to the deformation, for example, a curving of the main line 21 can be suppressed.

In the example shown in FIG. 16B, an edge portion 207a on the rear side (the side opposite to the side connected to the connector 212) on the connector connection portion dummy pattern 207 is linear in shape. This makes the manufacture of the connector connection portion dummy patterns 207 comparatively easy. On the contrary, as shown in FIG. 17, the edge portion 207a may be corrugated in shape. With this, the occurrence of stress concentration inside the connector connection portion dummy patterns 207 when the main line 21 of the circuit body 20 is deformed can be avoided as much as possible.

Next, as shown in FIG. 14A, the connection portion 24 is formed on the tail end portion of each of the second branch portions 23 on all the first and second branch portions 22 and 23 provided on both sides of the main line 21 in the width direction. As shown in FIG. 15, the connection portion 24 is disposed so as to be separate from a tail end portion 26 of the upper side wiring pattern 204a on the second branch portion 23. As described later, the bus bar 25 is connected to the connection portion 24 and a chip fuse 50 is disposed so as to bridge between the tail end portion 26 and the connection portion 24 (see FIG. 10, etc.), whereby the bus bar 25 and the connector 212 are connected so as to be electrically continuous.

As shown in FIG. 15, a thin portion 27 where the width (that is, the cross-sectional area) of the wiring pattern is relatively small is formed on the upper side wiring pattern 204a on the second branch portion 23. Thereby, even if excessive current flows at a specific wiring pattern for various reasons and the chip fuse 50 does not function, the thin portion 27 corresponding to the wiring pattern melts more preferentially than the remaining part of the upper side wiring pattern 204a because of the Joule heat caused by the excessive current. Thus, the remaining part of the upper side wiring pattern 204a (particularly, the part where the upper side wiring patterns 204a are dense on the main line 21) melts, so that adverse effects on the peripheral wirings and the like can be suppressed. Since the molten thin portion 27 is trapped in the resin layer 201, scattering around of the metal forming the thin portion 27 can be suppressed.

(Concrete Form of Connection Between the Connection Piece of the Bus Bar and the Connection Portion of the Branch Line)

Next, referring to FIGS. 10, 11A and 11B, a concrete form of connection between the connection piece 252 of the bus bar 25 and the connection portion 24 of the second branch portion 23 will be described.

As shown in FIGS. 10, 11A and 11B, in the area, corresponding to the connection portion 24 and the tail end portion 26, on the upper surface of the leading end portion 232 of the second branch portion 23, the resin layer 201 (see FIG. 11B) constituting the circuit body 20 is removed. As a result, on the upper surface of the leading end portion 232,

14

the substantially U-shaped connection portion 24 and the rectangular tail end portion 26 are exposed so as to be open at the top.

The connection piece 252 of the bus bar 25 is formed of a first portion 252a extending from the bus bar body 251 toward the inside in the width direction (the side of the main line 21) and a pair of second portions 252b and 252c extending rearward from the leading end portion and the base portion of the first portion 252a. As a result, the connection piece 252 has a substantial U shape that is open to the rear corresponding to the shape of the exposed connection portion 24.

The connection piece 252 (which has the first portion 252a and the second portions 252b and 252c) is fixed to the upper surface of the exposed connection portion 24 over the entire area so that the substantial U shapes thereof coincide with each other. In this example, such fixing is made by using solder H. As a result, the connection portion 24 and the bus bar 25 are connected so as to be electrically continuous, and by using the stiffness of the connection piece 252, an area (deformation restricted area) R where the deformation such as the curving of the second branch portion 23 is restricted is formed in a rectangular part sandwiched by the pair of second portions 252b and 252c.

In this deformation restricted area R, the chip fuse 50 is attached so as to bridge between the tail end portion 26 and the connection portion 24. Specifically, one of the electrodes on both end portions of the chip fuse 50 is fixed to the exposed connection portion 24, and the other thereof is fixed to the exposed tail end portion 26. In this example, such fixing is made by using solder H. As a result, the connection portion 24 (consequently, the bus bar 25) and the tail end portion 26 (consequently, the connector 212) are connected so as to be electrically continuous.

As described above, the deformation restricted area R is formed by the connection piece 252 of the bus bar 25, and the chip fuse 50 is mounted in this area. Thereby, curving of the second branch portion 23 in the mounting area of the chip fuse 50 can be suppressed without the provision of a reinforcing plate or the like.

As shown in FIG. 12A, the connection piece 252 may have an L shape where the second portion 252c is omitted from the mode shown in FIG. 11A. Moreover, as shown in FIG. 12B, the connection piece 252 may have a rectangular shape where a third portion 252d coupling the leading ends of the pair of second portions 252b and 252c is further provided in the mode shown in FIG. 11A. Further, as shown in FIG. 12C, the connection piece 252 may be formed of two first portions 252a and 252e from the bus bar body 251. In any of the modes, since the chip fuse 50 is attached within the deformation restricted area R using the stiffness of the connection piece 252, a deformation of the second branch portion 23 in the mounting area of the chip fuse 50 can be suppressed.

Further, as shown in FIGS. 13A and 13B, a potting member 28 may be provided so as to cover the chip fuse 50 so that it is separated from the outside in the deformation restricted area R formed by the connection piece 252 by using the structure such that the height of the connection piece 252 (which has the first portion 252a and the second portions 252b and 252c) is larger than the height of the chip fuse 50 (see FIG. 11B).

As described above, by the potting member 28 covering the chip fuse 50, the waterproofing property of the chip fuse 50 and the electric contacts around the chip fuse 50 can be enhanced. Further, by the potting member 28 solidifying in a state of being in intimate contact with the surface of the

leading end portion **232**, a deformation of the second branch portion **23** can be further suppressed by using the stiffness of the potting member **28**. It is desirable that the potting member **28** be provided so as to fill the entire deformation restricted area **R** formed by the connection piece **252** of the bus bar **25**.

(Cover Assembled to the Holder)

Next, referring to FIGS. **18A** and **18B** to **21A** to **21C**, a cover **40** assembled to the holder **30** will be described. As shown in FIGS. **18A** and **18B**, the cover **40** made of resin is assembled to the holder **30** accommodating the circuit body **20** from above so as to cover the circuit body **20** in order to protect the circuit body **20**. Under the condition where the cover **40** is assembled to the holder **30**, the exposed part **213** of the circuit body **20** is exposed to the outside from the space covered with the holder **30** and the cover **40** (see FIG. **18B**).

As described above, the holder **30** is stretchable and shrinkable in the front-rear direction (the assembled direction of the battery assembly **1**). For this reason, it is desirable that the cover **40** be also configured so as to be stretchable and shrinkable in the front-rear direction. In this regard, the cover **40** is formed of two portions arranged in the front-rear direction (that is, a front side portion **41** and a rear side portion **42**), and the front side portion **41** and the rear side portion **42** are coupled so as to be movable relatively to each other in the front-rear direction. Hereinafter, concrete structures of the front side portion **41** and the rear side portion **42** will be described.

As shown in FIGS. **20A** and **20B**, the front side portion **41** is substantially formed of a rectangular plate form top plate portion **411** and a pair of side plate portions **412** hanging down from both sides of the top plate portion **411** in the width direction. The rear side portion **42** is also substantially formed of a rectangular plate form top plate portion **421** and a pair of side plate portions **422** hanging from both sides of the top plate portion **421** in the width direction.

As shown in FIG. **19**, the side plate portions **412** of the front side portion **41** and the side plate portions **422** of the rear side portion **42** are provided with a plurality of engagement portions **43** so as to correspond to engagement portions **37** provided in a plurality of positions in the front-rear direction on both side walls of the holder **30** (see FIGS. **1** and **6**). The corresponding engagement portions **37** of the holder **30** and engagement portions **43** of the cover **40** engage with each other, whereby the cover **40** (=the front side portion **41** and the rear side portion **42**) is assembled to the holder **30**.

As shown in FIGS. **20A** and **20B**, on the top plate portion **411** of the front side portion **41**, an engagement hole (through hole) **413** is formed in a central portion in the width direction in the neighborhood of the rear end portion (the portion to be coupled to the rear side portion **42**). Moreover, on the rear end portion of the top plate portion **411**, a first coupling plate portion **414** is formed in a position slightly lower than the top plate portion **411** in a central portion in the width direction, and on both sides of the first coupling plate portion **414** in the width direction, a pair of second coupling plate portions **415** that are flush with the top plate portion **411** are formed.

On the top plate portion **421** of the rear side portion **42**, a tongue-shaped piece **423** is formed that projects forward from a central portion of the front end portion (the portion to be coupled to the front side portion **41**) in the width direction. On a central portion of the upper surface of the tongue-shaped piece **423**, a projection **423a** projecting upward is formed. Moreover, on the front end portion of the

top plate portion **421**, a first coupling plate portion **424** that is flush with the top plate portion **421** is formed in a central portion in the width direction, and on both sides of the first coupling plate portion **424** in the width direction, a pair of second coupling plate portions **425** are formed in positions slightly lower than the top plate portion **421**.

Under a condition where the front side portion **41** and the rear side portion **42** are coupled together, as shown in FIGS. **20A** and **21A**, the tongue-shaped piece **423** of the rear side portion **42** enters the vertical gap between the top plate portion **411** and the first coupling plate portion **414** of the front side portion **41**, and the projection **423a** of the tongue-shaped piece **423** is situated inside the engagement hole **413**. Moreover, the first coupling plate portion **414** enters below the first coupling plate portion **424** and the pair of second coupling plate portions **415** enters above the pair of second coupling plate portions **425**, whereby the first coupling plate portion **414** and the first coupling plate portion **424** partially overlap with each other, and the pair of second coupling plate portions **415** and the pair of second coupling plate portions **425** partially overlap with each other.

Under a condition where the front side portion **41** and the rear side portion **42** are coupled together, the front side portion **41** and the rear side portion **42** are stretchable in the front-rear direction until the projection **423a** abuts on the rear side end of the engagement hole **413** as shown in FIG. **21B**, and are shrinkable in the front-rear direction until a leading end portion **423b** of the tongue-shaped piece **423** abuts on a stopper wall **417** provided on the lower surface of the top plate portion **411** of the front side portion **41** as shown in FIG. **21C**.

Thus, the cover **40** formed of the front side portion **41** and the rear side portion **42** coupled together is configured so as to be stretchable and shrinkable. As a consequence, the cover **40** also stretches and shrinks as the holder **30** stretches and shrinks, so that the circuit body **20** and the bus bars **25** can be protected from the outside while the assemblability to the battery assembly **1** and the conformability to the manufacturing variations are improved.

Further, in whichever position in the stretchable and shrinkable range the front side portion **41** and the rear side portion **42** are situated, the first coupling plate portion **414** and the first coupling plate portion **424** partially overlap with each other, and the pair of second coupling plate portions **415** and the pair of second coupling plate portions **425** partially overlap with each other. That is, in whichever position in the stretchable and shrinkable range the front side portion **41** and the rear side portion **42** are situated, the portion of coupling of the front side portion **41** and the rear side portion **42** is closed so that the inside and outside of the cover **40** do not communicate with each other. As a consequence, even if the cover **40** stretches or shrinks, the condition where the circuit body **20** and the bus bars **25** are protected from the outside can be maintained.

Further, since the cover **40** is configured so as to be stretchable and shrinkable, the degree of absorbing the manufacturing variations and the like at the engagement portions **37** of the holder **30** and the engagement portions **43** of the cover **40** can be made lower than that in a mode where the cover **40** cannot stretch or shrink. As a result, the engagement portions **37** of the holder **30** and the engagement portions **43** of the cover **40** can be made small.

(Protector Fixed to the Cover)

Next, referring to FIGS. **22** to **24A** and **24B**, a protector **70** fixed to the cover **40** will be described. The protector **70**

made of resin is provided on the exposed part **213** of the circuit body **20** in order to protect the exposed part **213** of the circuit body **20**.

As shown in FIGS. **23A** and **23B**, the protector **70** is formed of a first accommodation portion **71**, a second accommodation portion **72** and a coupling portion **73**. The first accommodation portion **71** has a rectangular plate shape. Using engagement portions **71a** on both sides in the width direction, the first accommodation portion **71** is assembled from above to be fixed to a front end portion **38** of the holder **30** accommodating the circuit body **20**, so as to cover the base portion of the exposed part **213** of the circuit body **20**. Thereby, the base portion of the exposed part **213** of the circuit body **20** is accommodated so as to be slidable in the length direction by the first accommodation portion **71** and the front end portion **38** of the holder **30**.

The second accommodation portion **72** is formed of a rectangular plate form upper side portion **72a** and lower side portion **72b**. The upper side portion **72a** and the lower side portion **72b** are assembled to each other so as to sandwich a central portion of the exposed part **213** of the circuit body **20** in the length direction by the upper side portion **72a** and the lower side portion **72b** by using engagement portions **72c** on both sides in the width direction. Thereby, the central portion of the exposed part **213** of the circuit body **20** is accommodated so as to be slidable in the length direction by the second accommodation portion **72** formed of the upper side portion **72a** and the lower side portion **72b**.

The coupling portion **73** is formed of a plurality of (in this example, three) bendable belts that couple the first accommodation portion **71** and the upper side portion **72a** of the second accommodation portion **72**.

As shown in FIG. **22**, the connector **212** situated at the leading end of the exposed part **213** is connected to a connector connection portion **61** of the voltage detector **60** disposed on the upper surface of the cover **40** under a condition where the exposed part **213** of the circuit body **20** is folded back from the base portion thereof toward the upper surface of the cover **40**. Under this condition, the coupling portion **73** of the protector **70** is curved, and the second accommodation portion **72** is fixed to the upper surface of the cover **40** by engaging engagement portions **72d** on both sides thereof in the width direction (see also FIGS. **23A** and **23B**) with engagement portions **416** of the cover **40** (see also FIGS. **20A** and **20B**, etc.).

As shown in FIGS. **24A** and **24B**, by sliding the circuit body **20** with respect to the second accommodation portion **72**, the circuit body **20** can be deformed in a direction away from the coupling portion **73** also under a condition where the coupling portion **73** is curved and the second accommodation portion **72** is fixed to the upper surface of the cover **40**. That is, the deformation of the circuit body **20** is not prevented. For this reason, not only the connector **212** is movable in the front-rear direction relatively to the cover **40** but also handling of the circuit body **20** can be made easy. (Main Effects of the Present Embodiment)

According to the bus bar module **10** according to the present embodiment, the circuit body **20** formed of a flexible board has the main line **21** that can be disposed on the upper part of the single cells **2**, the first branch portions **22** extending outward from the side portions of the main line **21**, and the second branch portions **23** connecting with the first branch portions **22** and extending parallel to the assembled direction of the single cells **2**. The second branch portion **23** is provided with the folded portion **231** folded

around the axis L intersecting in the assembled direction (in the width direction). For this reason, when the single cells **2** repetitively stretch and shrink in the thickness direction (assembled direction) and when the positions of the single cells **2** differ among the manufactured battery assemblies **1** due to the assembly tolerances of the single cells **2**, the folded portions **231** of the second branch portions **23** bend and stretch, so that the bus bars **25** are movable in the thickness direction of the single cells **2**.

As described above, the bus bar module **10** is capable of easily handling the stretch and shrinkage and the manufacturing variations of the battery assembly **1** substantially by the deformation of only the first and second branch lines **22** and **23** without the need for any deformation of the main line **21** of the circuit body **20**. Moreover, even when a multiplicity of circuit structures are contained, the flexible board is typically easy to become deformed flexibly with a far smaller force than normal electric wires used for the above-described conventional bus bar module. For this reason, the assemblability to the battery assembly **1** is significantly improved. Therefore, the bus bar module **10** is excellent in the assemblability to the battery assembly **1** and the conformability to the deformation and the manufacturing variations of the battery assembly **1**.

Further, in the bus bar module **10** according to the present embodiment, the folded portions **231** are provided in such a manner that the lower surfaces of the connection portions **24** of the second branch portions **23** are along a surface different from the lower surface of the main line **21**. Therefore, contact between the single cells **2** and the main line **21** can be suppressed without the provision of a projecting plate or the like on the upper surfaces of the single cells **2**. Therefore, contribution can be made to reduction in height, reduction in the number of parts, simplification of the manufacturing process and the like of the bus bar module **10**.

Further, in the bus bar module **10** according to the present embodiment, the second branch portions **23** are formed in an S shape provided with the first folded portion **231A** and the second folded portion **231B**. For this reason, even if the relative positions of the bus bars **25** change in any direction in the length direction of the main line **21**, the change can be followed, and return to the initial position is made possible.

Further, in the bus bar module **10** according to the present embodiment, the area where deformation such as curving or the like of the second branch portion **23** is regulated is formed by the bus bar **25**, and the chip fuse **50** is mounted in this area. Thereby, the deformation of the flexible board in the mounting area of the chip fuse **50** can be suppressed without the provision of a conventionally used reinforcing plate or the like.

The present invention is not limited to the above-described embodiments, and various modifications may be adopted within the scope of the present invention. For example, the present invention is not limited to the above-described embodiment, and modifications, improvements and the like are possible as appropriate. Besides, the materials, shapes, dimensions, numbers, disposition positions and the like of the elements of the above-described embodiment are arbitrary as long as the present invention is attained, and are not limited.

Now, features of the above-described embodiment of the structure of connection among the circuit body, the bus bar and the electronic, and the bus bar module **10** according to the present invention is briefly summarized and listed in the following [1] to [5]:

[1] A structure of connection among a circuit body, a bus bar and an electronic element, the connection structure being provided with:

a circuit body (**20**) configured by a flexible board on which a wiring pattern (**204a**, **204b**) is provided;

a bus bar (**25**) attached to a mounting surface of the circuit body (**20**); and

an electronic element (**50**) attached to the mounting surface so as to connect the bus bar (**25**) and the wiring pattern (**204a**),

wherein the bus bar (**25**) has a fixed portion (**252**) extending along the mounting surface;

wherein the fixed portion (**252**) is fixed to the mounting surface so that a restricted area which restricts deformation of the mounting surface is formed in a periphery of the fixed portion (**252**); and

wherein the electronic element (**50**) is arranged in the restricted area and is fixed to the mounting surface.

[2] In the connection structure according to the above [1], the fixed portion (**25**) of the bus bar has a first portion (**252a**) extending in a direction along the mounting surface and a pair of second portions (**252b**, **252c**) extending in a direction intersecting with the first portion (**252a**) and along the mounting surface; and

the first portion (**252a**) and the pair of second portions (**252b**, **252c**) are fixed to the mounting surface so that the restricted area is formed in a part sandwiched between the pair of second portions (**252b**, **252c**).

[3] In the connection structure according to the above [1] or [2],

the electronic element (**50**) is attached to the mounting surface so as to connect the fixed portion (**25**) and the wiring pattern (**204a**).

[4] In the connection structure according to any one of the above [1] to [3],

the fixed portion (**25**) is higher than the electronic element (**50**) in a thickness direction of the circuit body (**20**); and the connection structure further being provided with:

a sealing member (**28**) that is arranged in the restricted area formed by the fixed portion (**252**) and covers the electronic element (**50**) so as to isolate the electronic element (**50**) from an outside.

[5] The bus bar module (**10**) configured to be attached to the battery assembly (**1**) having a plurality of single cells (**2**) which are assembled to each other along a first direction (an assembled direction), the bus bar module (**10**) being provided with:

a circuit body (**20**) configured by a flexible board on which a wiring pattern is provided;

a bus bar (**25**) configured to be connected to an electrode of each of the single cells; and

a holder (**30**) configured to hold the bus bar and being stretchable and shrinkable in the first direction,

wherein the circuit body (**20**) includes:

a belt-like main line (**21**) that extends in the first direction;

a belt-like branch line (**22**, **23**) that extends from the main line so as to branch from the main line, a part (**23**) of the branch line (**22**, **23**) extending in the first direction and including the folded portion (**231**) having a shape folded back around the axis (**L1**, **L2**) intersecting with the first direction; and

a connection portion (**24**) provided in a position closer to a distal end of the branch line than the folded portion and configured to be connected to the bus bar;

5 a connection portion (**24**) provided in a position closer to a distal end of the branch line than the folded portion and configured to be connected to the bus bar; and

an electronic element (**50**) attached to a mounting surface of the connection portion so as to connect the bus bar and the wiring pattern,

10 wherein at the connection portion (**24**), the circuit body, the bus bar and the electronic element are connected by the connection structure according to any one of the above [1] to [4].

15 What is claimed is:

1. A structure of connection among a circuit body, a bus bar and an electronic element, the connection structure comprising:

a circuit body configured by a flexible board on which a wiring pattern is provided;

a bus bar attached to a mounting surface of the circuit body; and

an electronic element attached to the mounting surface so as to connect the bus bar and the wiring pattern,

wherein the bus bar has a fixed portion projecting from a bus bar body and extending along the mounting surface;

wherein the fixed portion is fixed to the mounting surface so that a restricted area which restricts deformation of the mounting surface is formed in a periphery of the fixed portion;

wherein the electronic element is arranged in the restricted area and is fixed to the mounting surface;

wherein the fixed portion of the bus bar has a first portion extending in a direction along the mounting surface and a pair of second portions protruding from the first portion and extending in a direction intersecting with the first portion and along the mounting surface; and wherein the first portion and the pair of second portions are fixed to the mounting surface so that the restricted area is formed in a part sandwiched between the pair of second portions.

2. The connection structure according to claim 1, wherein the electronic element is attached to the mounting surface so as to connect the fixed portion and the wiring pattern.

3. The connection structure according to claim 1, wherein the fixed portion is higher than the electronic element in a thickness direction of the circuit body; and the connection structure further comprising:

a sealing member that is arranged in the restricted area formed by the fixed portion and covers the electronic element so as to isolate the electronic element from an outside.

4. The connection structure according to claim 1, wherein the first portion and the pair of second portion form an L shape around the restricted area.

5. The connection structure according to claim 1, wherein the fixed portion of the bus bar has a third portion extending in the direction intersecting with the pair of second portions; and

wherein the pair of second portions is disposed between the first portion and the third portion to form a rectangular shape around the restricted area.