

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(10) International Publication Number

WO 2015/022122 A1

(43) International Publication Date
19 February 2015 (19.02.2015)

WIPO | PCT

(51) International Patent Classification:
H04N 7/15 (2006.01) **H04L 12/18** (2006.01)

(21) International Application Number:
PCT/EP2014/064865

(22) International Filing Date:
10 July 2014 (10.07.2014)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
13306152.3 15 August 2013 (15.08.2013) EP

(71) Applicant: **ALCATEL LUCENT** [FR/FR]; 148/152 route de la Reine, F-92100 Boulogne-Billancourt (FR).

(72) Inventors: **ABOU-CHAKRA, Rabih**; Alcatel-Lucent Enterprise, 32, Avenue Kleber, F-92707 Colombes (FR). **BLETTERIE, Philippe**; Alcatel-Lucent Enterprise, 32, Avenue Kleber, F-92707 Colombes (FR).

(74) Agent: **HERIAS, Philippe**; Alcatel-Lucent International, 148/152 Route de la Reine, F-92100 Boulogne-Billancourt (FR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: A METHOD FOR GENERATING AN IMMERSIVE VIDEO OF A PLURALITY OF PERSONS




FIG.1

(57) Abstract: A method for interfacing a plurality of videoconferencing client devices the method comprising, in a computer server (5) connected to a client devices : - receiving a first client video stream (7) from the video routing client (4); - tagging a video image of the first client video stream received from the video routing client; - sending, through a bidirectional communication channel (14), the first client video stream (21) to a mixing client (2); - receiving, through the bidirectional communication channel with the mixing client, a mixed video stream (15) from said mixing client; - detecting in the mixed video stream received from the mixing client a video image portion which is different from the tagged video image of the first client video stream; - extracting the detected video image portion from the mixed video stream; - generating a second client video stream (23) from the extracted video image portion; - sending the second client video stream to the video routing client.

WO 2015/022122 A1

A method for generating an immersive video of a plurality of persons**Field of the invention**

The invention relates to a method of video processing in a multi-participant video-conferencing system.

5

Background

Along with the increase of bandwidth capabilities in communication systems, video communication systems have become increasingly popular in both business 10 and residential applications. Indeed, in the case of geographically distributed team collaboration, these systems avoid the travelling of the team collaborators and increase flexibility.

Videoconferencing technologies use video and audio communication to allow a plurality of people to communicate at a same time, for instance for meeting 15 activities. Furthermore, besides the audio and visual transmission of meeting activities, videoconferencing technologies can be used to share documents and display information.

Each participant in a videoconference is filmed by a camera which generates a video stream representing the participant in his/her own environment. To create a 20 video conference, two different technologies are generally used.

In a Video mixing based conference, all incoming video streams from N participants are combined by a Multiparty Conference Unit (MCU) in one mixed video stream. The mixed video stream includes the video streams of all the participants joined together. The mixed video stream is sent to the N participants.

25 As opposed to video mixing, video routing technology consists in having each participant send his own video stream to all other parties, which simultaneously decode up to 4 or 5 of them. Each video client device has thus to support receiving and decoding multiple flows.

30

Summary

In an embodiment, the invention provides a method for interfacing a plurality of videoconferencing client devices comprising a video routing client and a video mixing

client, wherein said mixing client comprises a Multiparty Conference Unit able to receive a plurality of client video streams and to generate a mixed video stream by mixing said plurality of client video streams, the method comprising, in a computer server connected to the client devices :

- 5 - receiving a first client video stream from the video routing client ;
- tagging a video image of the first client video stream received from the video routing client ;
- sending, through a bidirectional communication channel, the tagged first client video stream to the mixing client ;
- 10 - receiving, through the bidirectional communication channel with the mixing client, a mixed video stream from said mixing client ;
- detecting in the mixed video stream received from the mixing client a video image portion which is different from a tagged video image of the tagged first client video stream ;
- 15 - extracting the detected video image portion from the mixed video stream ;
- generating a second client video stream from the extracted video image portion ;
- sending the second client video stream to the video routing client.

20 According to embodiments, such method may comprise one or more of the features below.

In an embodiment, the method further including the steps of

- 25 - receiving additional information data, wherein the additional information data is included in the first client video stream ;
- tagging the additional information data received from the video routing client ;
- sending the tagged additional information data to the mixing client ;
- detecting in the mixed video stream received from the mixing client additional information data which is different from the tagged additional information data ;
- 30 - extracting the metadata detected in the mixed video stream ;
- sending the extracted metadata in the second client video stream to the video routing client or to the video routing clients.

In an embodiment, the method further including the steps of :

- Detecting that the video image portion that is different from the tagged client video image comprises a plurality of disjoint portions ;
- generating a plurality of second client video streams, each second client video stream corresponding to a different one of the disjoint portions ;
- sending the plurality of second client video streams to the video routing client.

In an embodiment, the client video stream received from the video routing client is carried on a bidirectional communication channel carrying a plurality of video streams in both directions.

In an embodiment, the tagging step includes a step of adding a frame around the video image of the first client video stream received from the video routing client.

15 In an embodiment, the tagging step includes a step of adding a transparent layer on the video stream received from the video routing client.

In an embodiment, the method further comprises the steps of :

- receiving a plurality of first client video stream from a plurality of video routing clients ;
- tagging each first client video stream received from the plurality of video routing clients ;
- sending, through a plurality of bidirectional communication channels, each tagged first client video stream to the mixing client ;
- 25 detecting in the mixed video stream received from the mixing client the video image portion which is different from each of the plurality of tagged first client video streams.

In an embodiment, the method further includes the steps of :

- 30 receiving a plurality of additional information data from a plurality of first video routing client ;
- tagging the plurality of additional information data received from the plurality of first video routing client.

In an embodiment, the invention also provides a video processing server for interfacing a plurality of videoconferencing clients devices comprising a video routing client and a video mixing client, wherein said mixing client comprises a Multiparty Conference Unit able to receive a plurality of client video streams to generate a mixed video stream by mixing said plurality of client video streams, the video processing sever including :

- a router able to
 - o receive a first client video stream from a video routing client device,
 - o Send to the video routing client a second client video stream generated from a video image portion extracted from mixed video stream received from the mixing client ;
- a tagging agent block able to mark the first client video stream received from the video routing clients,
- a communication block able to
 - o send, in a bidirectional communication channels carrying the tagged first client video stream to the mixing client, and to
 - o receive a mixed video stream generated by the mixing client including tagged first client video stream sent to said mixing client;
- a tag detector block able to
 - o detect a video image portion of the mixed video stream received from the mixing client which is different from the tagged first client video stream,
 - o extract the detected image portion in the mixed video stream received from the mixing client.

25

In other embodiments, the first client video stream from the video routing client and the second video stream sent to the video routing client are carried on a bidirectional communication channel established between the server and the video routing client.

30

In an embodiment, the invention also provides a computer program comprising computer-executable instructions that perform the above-mentioned method when executed, and a computer that comprises said computer program.

The invention originates from the observation that, despite of an installed base market dominated by mixing compatible video systems, a significant part of them embedding an up to four ports MCU, multiparty video conferencing is shifting 5 from mixing to video routing technology. An idea on which the invention is based is to include such a video mixing based system in routed multiparty video sessions, in which multiple video flows, sometimes including a presentation sharing data, are exchanged among all parties.

10 **Brief description of the drawings**

These and other aspects of the invention will be apparent from and elucidated with reference to the embodiments described hereinafter, by way of example, with reference to the drawings.

15 - Figure 1 illustrates functionally an embodiment of a video conferencing system architecture in the case wherein three video routing clients are participating in a video conference with a mixing client comprising an integrated capture device.

- Figure 2 is a diagram representing the steps performed by a server in a system of figure 1.

20 - Figure 3A is a schematically representation of an image of a mixed video stream generated by the mixing client of figure 1.

- Figure 3B is a schematically representation of an image of a mixed video stream generated by a mixing client having two different capture devices directly connected to the MCU ;

25 **Detailed description of the embodiments**

Figure 1 illustrates an embodiment of a video conferencing system architecture in the case wherein four persons are participating in a video conference.

30 In figure 1, a mixing participant 1 uses a mixing client device 2. Three video routing participants 3 use each one a video routing client device 4. Mixing client device 2 and video routing client devices are connected to a Mixing Compatible

Video Routing Server 5 (MCVRS). Each client device may be for instance a personal computer, a mobile phone, a tablet or any other device. The participants, and their respective client devices, are located in different places and have a video conference together.

5

Each video routing client device 4 has a capture device 6. The capture device 6 is, for instance, a camera 6 which captures a video stream 7 of its routing participant 3 in his/her own environment. Each video routing client device 4 has a communication port able to establish a bidirectional communication channel 8 with 10 the MCVRS 5. Such a communication channel 8, established between the video routing client device 4 and the MCVRS 5, is able to carry a plurality of video streams in both directions. In use, the video routing client device 4 sends its captured video stream 7 to the MCVRS 5 and receives video streams corresponding to the video streams captured by other participants. Video routing client device 4 is able to mix its 15 own captured video stream and received video streams carried on the communication channels 8 in a mixed video stream. An image of such mixed video stream includes the simultaneous images of all the video streams joined together (see figure 2).

The mixing client 2 comprises a capture device 9, an encoder block 10, a 20 decoder block 11 and an embedded MCU 12. The capture device 9 is, for instance, a camera 9 which captures a video stream 13 of the mixing participant 1 in his/her environment. The encoder block 10 encodes the captured video stream 13 and transmits it to the MCU 12.

The MCU 12 has a plurality of communication ports. Each port of the MCU 25 12 permits to establish a communication channel 14 between the mixing client device 2 and the MCVRS 5. Each communication channel 14 established between the MCU 12 and the MCVRS 5 is a bidirectional channel able to carry one video stream, and optionally a further data stream, in both directions. The MCU 12 mixes the video stream captured by the capture device 9 of the mixing client device 2 and the 30 received video streams carried on the communication channels 14 into a mixed video stream 15. An image of such a mixed video stream 15 includes the simultaneous images of all the video streams used to generate the mixed video stream 15 joined together. The mixed video stream 15 is sent to the decoder block 11. The mixed

video stream 15 is also sent in the established communication channel 14 to the MCVRS 5.

5 The decoder block 11 decodes the mixed video stream 15. The decoded video stream is displayed on a display device of the mixing client device 2, for instance a computer screen or a TV.

If the mixing client device 2 were merely connected to a video routing client 4 device, the video routing client device 4 would send to the mixing client device 2 its captured video stream, then the mixing client device 2 would include the video stream received from the video routing client device 4 in a mixed video stream and the 10 mixing client device 2 would send back the mixed video stream to the video routing client device 4. The video routing client device 4 would then generate a mixed video stream including its own captured video stream and the mixed video stream received from the mixing client device 2. Such a mixed video stream generated by the video 15 routing client device 4 would include the video routing client device captured video stream two times, once from its own captured video stream and once from the mixed video stream from the mixing client device 2.

To avoid this in the video conferencing system represented in figure 1, the MCVRS 5 includes a router 16, a tagging block 17, a tag detection block 18 and a communication agent block 19.

20 The router 16 has a plurality of ports able to establish bidirectional communication channels 8 with the video routing client devices 4. Each established bidirectional communication channel 8 established can carry a plurality of video streams in both directions. In fact, router 16 receives a respective video stream, and optionally data, from each video routing client device 4 and sends it back to all other 25 video routing client devices 4. The router 16 also sends the video streams received from every video routing client 4 to the tagging agent block 17.

The tagging agent block 17 performs the tagging of the video images. Tagging can be any marking technology, and can range from sophisticated transparent technology, to simple addition of a signed/specific frame around each 30 image of the video stream. When the incoming video stream includes additional information data 20, e.g. documents to be shared by the participants, the additional data 20 is also tagged. The tagging agent block 17 sends each tagged video stream to the communication agent block 19.

The communication agent block 19 establishes as many communication channels 14 as needed with the MCU 12 embedded in the mixing client device 2, i.e. one bidirectional channel 14 per video routing client device 4, with a maximum depending on the MCU 12 capability. Each communication channel 14 between the 5 communication agent block 19 and the MCU 12 carries one video stream, and optionally a further data stream, in both directions. The communication agent block 19 sends the tagged video streams 21, and optionally tagged additional information data 22, to the MCU 12. The tagged video streams 21 sent by the communication agent block 19 to the MCU 12 are the ones received from the tagging agent block 10 17. The Communication agent block 19 receives from the MCU 12 the mixed video stream 15 generated by the MCU 12. The communication agent block 19 transmits mixed video stream 15 to the Tag detector block 18.

The tag detector block 18 is able to detect which parts of each image in the mixed video stream correspond to images previously tagged by the tagging agent 15 block 17. The Tag detector block 18 receives the mixed video stream 15 from the communication agent block 19. Tag detector block 18 detects the tagged areas in each image of the mixed video stream 15. Once tagged areas have been identified in an image of the mixed video stream 15, the tag agent block 18 cuts-out the non-tagged areas from the image of the mixed video stream 15. The cut-out portion or 20 portions is used to generate a new image corresponding to an image captured by the capture device 9 included in the mixing device 2. An extracted video stream 23 is generated with the cut-out portion or portions of the mixed video stream 15. Said extracted video stream 23 is sent back to the communication agent block 19.

The tag detector block 18 generates a video stream corresponding to each 25 disjoined portion of the mixed video stream 15 which has not been tagged by the tagging agent block 17. If the tag detector block 18 detects only one non-tagged area in the images of the mixed video stream 15, the tag detector block generates only one extracted video stream 23. If the tag detector block 18 detects a plurality of disjoined non-tagged areas in the images of the mixed video stream 15, the tag 30 detector block 18 generates one extracted video stream 23 for each detected non-tagged portion of the image.

Figure 2 is a diagram representing the steps performed during a video conference in a system of figure 1.

In this system, a first video routing participant 3A has a personal computer 4A as video routing client device 4, a second video routing participant 3B has a smartphone 4B as video routing client device 4 and a third video routing participant 3C has a tablet 4C as video routing client device 4 (see figure 1).

5 As explained above, each video routing client device 4 generates (steps 24A, 24B and 24C) a captured video stream 7 representing its participant in his/her own environment. Each video routing device 4 establishes a bidirectional communication channel 8 with the router 16 of the MCVRS 5 (steps 25A, 25B and 25C). The captured video stream 7 of each video routing client 4 device is send (step 26A, 26B
10 and 26C) to the router 16 via the established communication channel 8. The router 16 sends (step 27) each captured video stream 7 from the video routing devices 4 to the other video routing client devices 4 and to the tagging agent block 17. Typically, as shown in figure 1, a first captured video stream 7A from the first video routing client 4A is sent to the second video routing client device 4B, to the third client device
15 4C and to the tagging agent block 17. A second captured video stream 7B, from the second video routing client device 4B and including data 20, is sent to the first client video routing device 7A, to the third video routing client device 4C and to the tagging agent block 17. A third captured video stream from the third video routing client device 4C is sent to the first video routing client device 4A, to the second video
20 routing client device 4B and to the tagging agent block 17.

Each captured video stream 7 is tagged by the tagging agent block 17 (step 28). As the capture video stream 7B of the second video routing client device includes additional information data 20, the tagging agent block 17 tags also said additional information data 20. The tagging agent block 17 adds a red frame 29 (see figures
25 3A and 3B) around each image of the captured video streams 7. The tagging agent block 17 sends the tagged video streams 21, including tagged additional information data 22, to the communication agent block 19 (step 30). As the MCU 12 in the mixing client device 2 supports communication channels 14 carrying only one video stream, and optionally a further data stream, in both direction, the communication agent block 19 establishes a bidirectional communication channel 14 with the MCU 12 for each tagged video stream 21 (step 31). As shown in figure 1, a first communication channel 14A carries a first tagged video stream 21A, a second communication channel 14B carries a second tagged video stream 21B including

tagged additional information data 22 And a third communication channel 14C carries a third tagged video stream 21C.

The MCU 12 generates the mixed video stream 15 with the tagged video streams 21 and its own captured video stream 13 (step 32). The mixed video stream 5 15 includes the three tagged video streams 21 and the captured video stream 13 from the mixing client device 2 joined together. A display device of the mixing device 2 displays the mixed video stream 15. The MCU 12 sends the mixed video stream 15 on the three already established bidirectional communication channels 14 (step 33).

The communication agent block 19 receives the mixed video stream 15. The 10 communication agent block 19 transmits the mixed video stream 15 to the tag detector block 18 (step 34).

The tag detector block 18 analyses each image of the mixed video streams 15. More specifically, the tag detector block 18 analyses each image of the mixed 15 video stream 15 to detect each portions of the image which comprises a tag as added by the tagging agent block 17 (step 35). During this step, the tagging agent detects all portions which are surrounded by a red frame. The images of the three tagged video stream 21 and the tagged additional information data 22 are detected by the tag detector block 18. Then, the tag detector block 18 cuts-out portion of the images which have not been detected as tagged by the tagging agent block 17 (step 20 36). As an image of the mixed video stream 15 includes three tagged images and tagged additional information data 22 joined together, only one portion of such image is cut-out as having not been tagged by the tagging agent block 17. Such cut-out image corresponds to an image of the captured video stream 13 from the mixing client device 2. The tag detector block 18 generates the extracted video stream 23 25 with the cut-out images of the mixed video stream 15 (step 37). The tag detector block sends said extracted video stream 23 to the communication agent block 19 which transmits it to the tagging agent block 17. The tagging agent block 17 then transmits to the router 16 the extracted video stream 23. The router 16 uses the established communication channels 8 to send the extracted video stream 23 to each 30 video routing client 4 (step 38).

Each video routing client generates a mixed video stream 40 with the captured video stream from its own capture device 2 (step 39), the capture video streams from the other video routing client devices and the extracted video stream 23

of the mixed video stream 15. A mixed video stream 40 generated by each video routing client device 4 (see figure 1) is similar to the mixed video stream 15 generated by the mixing client, each one representing all the participants 1 and 3 joined in a same mixed video stream 15 or 40.

5 Figures 3A is an image from a mixed video stream including tagged portions during a conference using the system of figure 1.

An image 41 from a mixed video stream as represented in figure 3A includes a first tagged image portion 42A representing a first video routing participant 3A, a second tagged image portion 42B representing a second video routing participant 10 3B, a third image portion 42C representing a third video routing participant 3C and a fourth portion 42D representing the tagged additional information data 22. The image 41 also includes a mixing portion 43 representing mixing participant 1.

During its analyses, the tag detector block 18 detects the red frame 29 around the tagged portions 42. As these tagged portions 42 have been detected, the 15 tag detector block 18 cuts-out the non-tagged portion of the image. Typically, the tag detector block 18 cuts-out the mixing portion 43. The tag detector block 18 extracts an image corresponding to the mixing portion 43 and integrates the extracted image to an extracted video stream representing the mixing participant.

Figures 3B is an image from a mixed video stream including tagged portions 20 and disjoint non-tagged portions during a conference.

An image 44 from a mixed video stream as represented in figure 3B includes a first tagged image portion 45A representing a first video routing participant and a second tagged image portion 45B representing a second video routing participant and a tagged additional information portion 45C. The image 44 also includes a first 25 mixing portion 46A and a second mixing portion 46B, each one representing a respectively a first and a second mixing participant.

During its analyses, the tag detector block 18 detects the tagged portions 45. As these tagged portions 45 have been detected, the tag detector block 18 cuts-out the non-tagged portions 46 of the image 44. Typically, the tag detector block 18 30 cuts-out the first mixing portion 46A and the second mixing portion 46B. The tag detector block 18 detects that these two non-tagged portions are disjoint in the image 44, the first mixing portion 46A being separated from the second mixing portion 46B by the first video routing portion 45B. As two disjoint portions of the image are

detected as being not tagged, the tag detector block 18 generates two different images corresponding respectively to the first mixing portion 46A and to the second mixing portion 46B. These two images are integrated to two different extracted video streams 23, each one representing respectively the first and the second mixing participant.

In an embodiment, the mixed video stream 15 generated by the mixing client 2 includes additional information data which is not tagged, e.g which is not included in a captured video stream from a video routing client device. Such additional information data is detected by the tag detector block 18 as being non-tagged and then cut-out and inserted in the extracted video stream.

To tag an item in a video stream, marks may be inserted in one image or in each image or in every N images of the video stream. In an embodiment, the mark used by the tagging agent block is a red frame added around the first image of a video stream. When the tag detector block detects in the first image of a video stream such a red frame, the tag detector considers that the tagged portion in the first image is also a tagged portion in the following images. In another embodiment, only one image every N images, with for instance N=10, of a video stream is tagged, each tagged portion being defined for the tagged image of a video stream and the N following images.

The invention is not limited to the described embodiments. The appended claims are to be construed as embodying all modification and alternative constructions that may be occurred to one skilled in the art, which fairly fall within the basic teaching here, set forth. The use of the verb "to comprise" or "to include" and its conjugations does not exclude the presence of elements or steps other than those stated in a claim. Furthermore, the use of the article "a" or "an" preceding an element or step does not exclude the presence of a plurality of such elements or steps. The invention may be implemented by means of hardware as well as software. The same item of hardware may represent several "means".

CLAIMS

1. A method for interfacing a plurality of videoconferencing client devices comprising a video routing client (4) and a video mixing client (2), wherein
5 said mixing client comprises a Multiparty Conference Unit (12) able to receive a plurality of client video streams (20) and to generate a mixed video stream (15) by mixing said plurality of client video streams the method comprising, in a computer server connected to the client devices :

- receiving a first client video stream (7) from the video routing client ;
- 10 - tagging a video image of the first client video stream received from the video routing client,
- sending, through a bidirectional communication channel (14), the first client video stream (21) to the mixing client,
- receiving, through the bidirectional communication channel with the mixing
15 client, a mixed video stream (15) from said mixing client,
- detecting in the mixed video stream received from the mixing client a video image portion which is different from the tagged video image of the first client video stream,
- extracting the detected video image portion from the mixed video stream,
- 20 - generating a second client video stream (23) from the extracted video image portion;
- sending the second client video stream to the video routing client.

2. A method according to claim anyone of claims 1 or 2, the method further including the steps of

- 25 - receiving additional information data (20), wherein the additional information data is included in the first client video stream ;
- tagging the additional information data received from the video routing client ;
- sending the tagged additional information data (22) to the mixing client,
- detecting in the mixed video stream received from the mixing client additional
30 information data which is different from the tagged additional information data,
- extracting the additional information data detected in the mixed video stream,
- sending the extracted additional information data in the second client video stream to the video routing client or to the video routing clients.

3. A method according to any one of claims 1 to 2, the method further including the steps of :

- Detecting that the video image portion that is different from the tagged client video image comprises a plurality of disjoint portions (29, 30);
- 5 - generating a plurality of second client video streams, each second client video stream corresponding to a different one of the disjoint portions;
- sending the plurality of second client video streams to the video routing client.

4. A method according to anyone of claims 1 to 3, wherein the client video stream received from the video routing client is carried on a bidirectional 10 communication channel (8) carrying a plurality of video streams in both directions.

5. A method according to anyone of claims 1 to 4, wherein the tagging step includes a step of adding a frame (24) around the video image of the first client video stream received from the video routing client.

6. A method according to anyone of claims 1 to 4, wherein the 15 tagging step includes a step of adding a transparent layer on the video stream received from the video routing client.

7. A method according to anyone of claims 1 to 6, wherein the method further comprises the steps of :

- receiving a plurality of first client video streams (7A, 7B, 7C) from a plurality of 20 video routing clients (4A, 4B, 4C);
- tagging each first client video stream received from the plurality of video routing clients ;
- sending, through a plurality of bidirectional communication channels, each tagged first client video stream (20A, 20B, 20C) to the mixing client,
- 25 - detecting in the mixed video stream received from the mixing client the video image portion which is different from each of the plurality of tagged first client video streams.


8. A method according to claim 7, wherein the method further includes the steps of :

- 30 - receiving a plurality of additional information data from a plurality of first video routing client ;
- tagging the plurality of additional information data received from the plurality of first video routing client ;

9. A video processing server for interfacing a plurality of videoconferencing clients devices comprising a video routing client and a video mixing client, wherein said mixing client comprises a Multiparty Conference Unit able to receive a plurality of client video streams to generate a mixed video stream by 5 mixing said plurality of client video streams, the video processing sever including :

- a router (16) able to
 - o receive a first client video stream from the video routing client device,
 - o Send to the video routing client a second client video stream generated from a video image portion extracted from a mixed video stream received 10 from the mixing client ;
- a tagging agent block (17) able to mark the first client video stream received from the video routing client,
- a communication block (19) able to
 - o send in a bidirectional communication channel the tagged first client video 15 stream to the mixing client, and to
 - o receive a mixed video stream generated by the mixing client including tagged first client video stream sent to said mixing client;
- a tag detector block (18) able to
 - o detect a video image portion of the mixed video stream received from the 20 mixing client which is different from the tagged first client video stream, and
 - o extract the detected image portion in the mixed video stream received from the mixing client.

10. The Video processing server according to claim 9, wherein the first 25 client video stream from the video routing client and the second client video stream sent to the video routing client are carried on a bidirectional communication channel established between the server and the video routing client.






FIG.2

3/3

-41-




FIG. 3A

-44-




FIG. 3B

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2014/064865

A. CLASSIFICATION OF SUBJECT MATTER
INV. H04N7/15 H04L12/18
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
H04N H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2006/244819 A1 (PUN THOMAS [US] ET AL) 2 November 2006 (2006-11-02) abstract paragraph [0026] - paragraph [0029]; figure 2 ----- EP 2 288 104 A1 (AVAYA INC [US]) 23 February 2011 (2011-02-23) paragraph [0041] - paragraph [0047]; figures 1-3 ----- US 2006/215765 A1 (HWANG CHERNG-DAW [US] ET AL) 28 September 2006 (2006-09-28) paragraph [0002] - paragraph [0005]; figures 1-4 paragraph [0034] - paragraph [0036]; figure 5 -----	1-10 1,9 1,9



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
30 September 2014	13/10/2014
Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3046	Authorized officer Beaudoin, Olivier

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2014/064865

Patent document cited in search report	Publication date	Patent family member(s)			Publication date
US 2006244819	A1 02-11-2006	US 2006244819	A1	02-11-2006	
		US 2010189178	A1	29-07-2010	
		US 2012287227	A1	15-11-2012	
-----	-----	-----	-----	-----	-----
EP 2288104	A1 23-02-2011	EP 2288104	A1	23-02-2011	
		US 2011043600	A1	24-02-2011	
-----	-----	-----	-----	-----	-----
US 2006215765	A1 28-09-2006	CN 101147400	A	19-03-2008	
		GB 2439265	A	19-12-2007	
		US 2006215765	A1	28-09-2006	
		WO 2006104556	A2	05-10-2006	
-----	-----	-----	-----	-----	-----