



(86) Date de dépôt PCT/PCT Filing Date: 2014/07/18

(87) Date publication PCT/PCT Publication Date: 2015/01/22

(45) Date de délivrance/Issue Date: 2021/07/13

(85) Entrée phase nationale/National Entry: 2016/01/06

(86) N° demande PCT/PCT Application No.: US 2014/047182

(87) N° publication PCT/PCT Publication No.: 2015/010011

(30) Priorité/Priority: 2013/07/19 (US61/856,200)

(51) Cl.Int./Int.Cl. *C09K 8/34* (2006.01),
C09K 8/565 (2006.01), *C09K 8/64* (2006.01),
E21B 33/138 (2006.01), *E21B 43/04* (2006.01),
E21B 43/267 (2006.01)



(72) Inventeurs/Inventors:
FERNANDEZ, JORGE M., US;
JONES, CHRISTIAN W., US

(73) Propriétaire/Owner:
SASOL PERFORMANCE CHEMICALS GMBH, DE

(74) Agent: FINLAYSON & SINGLEHURST

(54) Titre : COMPOSITION S'UTILISANT DANS LA MISE EN OEUVRE D'OPERATIONS DE FOND DANS DES PUITES
DE PETROLE ET DE GAZ

(54) Title: COMPOSITION FOR USE IN CONDUCTING DOWNHOLE OPERATIONS IN OIL AND GAS WELLS



(57) Abrégé/Abstract:

A composition for viscosifying a nonaqueous base liquid. The composition has glycerin carbonate and optionally an alkoxyated alcohol having the formula: wherein R is a linear or branched alkyl from 2 to 18 carbon atoms, or an aromatic radical having the structure: where R₁ is a branched or linear alkyl having from 2 to 18 carbon atoms R₂ is H or CH₃ R₃ is H or CH₃ a is from 0 to 12 and b is from 1 to 12. The base liquid having greater than 20% naphthenics and about 10% to about 35% isoparaffins.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(10) International Publication Number
WO 2015/010011 A1

(43) International Publication Date
22 January 2015 (22.01.2015)

(51) International Patent Classification:

E21B 43/16 (2006.01) *C09K 8/502* (2006.01)
E21B 33/13 (2006.01) *C09K 8/035* (2006.01)

(21) International Application Number:

PCT/US2014/047182

(22) International Filing Date:

18 July 2014 (18.07.2014)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/856,200 19 July 2013 (19.07.2013) US

(71) Applicant (for all designated States except US): **SASOL OLEFINS & SURFACTANTS GMBH** [DE/DE]; 1 Ankelmannsplatz, 20537 Hamburg (DE).

(72) Inventors; and

(71) Applicants (for US only): **FERNANDEZ, Jorge, M.** [US/US]; 2417 Luke St., Lake Charles, LA 70605 (US). **JONES, Christian, W.** [US/US]; 101 Marilyn Drive, Sulphur, LA 70663 (US).

(74) Agent: **WERNER, Erin, J.**; Bushman & Associates, P.C., 1001 West Loop South, Suite 810, Houston, TX 77027 (US).



(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: COMPOSITION FOR USE IN CONDUCTING DOWNHOLE OPERATIONS IN OIL AND GAS WELLS



(57) Abstract: A composition for viscosifying a nonaqueous base liquid. The composition has glycerin carbonate and optionally an alkoxyated alcohol having the formula: wherein R is a linear or branched alkyl from 2 to 18 carbon atoms, or an aromatic radical having the structure: where R₁ is a branched or linear alkyl having from 2 to 18 carbon atoms R₂ is H or CH₃ R₃ is H or CH₃ a is from 0 to 12 and b is from 1 to 12. The base liquid having greater than 20% naphthenics and about 10% to about 35% isoparaffins.

COMPOSITION FOR USE IN CONDUCTING DOWNHOLE OPERATIONS IN OIL AND GAS WELLS

5

FIELD OF THE INVENTION

10

The present invention relates to the viscosification of non-aqueous fluids and more particularly to the viscosification of wellbore fluids. In particular, the invention relates to activators for use in exfoliating organophilic clays used in various applications, e.g., wellbore fluids.

BACKGROUND OF THE INVENTION

15

20

Organophilic clays are widely used as rheological control agents in a wide variety of solvent systems. In particular, organophilic clays have found wide usage in wellbore fluids, used in operations related to the development, completion and production of natural hydrocarbon reservoirs. Typical operations include drilling, fracturing subterranean formations, modifying the permeability of subterranean formations, logging operations, sand control, packer fluids, etc. In particular, in deep well drilling, the use of organophilic clays in oil-based muds have certain advantages despite their considerably higher initial cost. The advantages of oil-based fluids are apparent in water-sensitive formations, e.g.,

swelling shale, insoluble salt formations, and at high temperatures. These fluids are used for drill stem lubrication, particularly in drilling curved or deviated wells, for corrosion protection and they have the further advantage of being reusable.

One of the primary functions of organophilic clays in oil-based wellbore
5 fluids, as well as other non-aqueous based fluids (i.e glycol ethers), is to act as
viscosifiers. However, it is well known that for organophilic clays to swell in or
viscosify a non-aqueous wellbore fluid it is usually necessary to use small
amounts of polar molecules as activators. Typical activators for use with clay-
type thixotropic viscosifying agent such as organophilic clays include water,
10 ethanol, methanol, glycols, sodium silicate, sodium fluoride, magnesium silico
fluoride, calcium carbonate, polar aprotic compounds, etc. An especially
preferred and widely used activator is propylene carbonate.

SUMMARY OF THE INVENTION

In one aspect, the present invention provides an exfoliating agent for use in non-aqueous fluids, particularly non-aqueous wellbore fluids.

5 In another aspect, the present invention provides a viscosifying package for use in non-aqueous fluids.


In still another aspect, the present invention provides a wellbore fluid comprised of a non-aqueous fluid, e.g., a hydrocarbon base fluid, an organophilic clay and an exfoliating agent.

10 In still a further aspect, the present invention provides a wellbore fluid comprised of a hydrocarbon based fluid having a significant content of naphthenics and/or branched hydrocarbons, an organophilic clay, and an exfoliating agent.


In a broad aspect, the present invention pertains to an exfoliating agent for viscosifying a nonaqueous base fluid, the non-aqueous base fluid comprising an organophilic clay, wherein the exfoliating agent comprises:

glycerin carbonate;

15 an alkoxyated alcohol having the general formula:



wherein R is a linear or branched alkyl from 2 to 18 carbon atoms or an aromatic radical having the structure:



20 wherein R₁ is a branched or linear alkyl having from 2 to 18 carbon atoms,

R₂ is H or CH₃,


R₃ is H or CH₃,

a is from 0 to 12,


and b is from 1 to 12.

25

In a still further aspect, the present invention provides a wellbore fluid comprising:
 a hydrocarbon base oil;
 an organophilic clay;
 an exfoliating agent comprising:
 glycerin carbonate; and
 an alkoxyated alcohol having the general formula:



wherein R is a linear or branched alkyl from 2 to 18 carbon atoms or an aromatic radical having the structure:



wherein R₁ is a branched or linear alkyl having from 2 to 18 carbon atoms,
 R₂ is H or CH₃,
 R₃ is H or CH₃,
 a is from 0 to 12,
 and b is from 1 to 12.

In a yet further aspect, the present invention embodies a method of treating a wellbore comprising introducing into the wellbore the composition of claim 1 and an additive comprising at least one of emulsifiers, wetting agents, viscosifiers, weighting agents, fluid loss control agents, proppants, and particulate agents for forming gravel packs.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a graph showing the viscosity of various exfoliating agents in diesel.

FIG. 2 is a graph showing the viscosity of various exfoliating agents in ODC-15.

FIG. 3 is a graph showing the viscosity of various exfoliating agents in LPA.

FIG. 4 is a graph showing the viscosity of various exfoliating agents in LPA-142.

FIG. 5 is a graph showing the viscosity of various exfoliating agents in LPA-170.

FIG. 6 is a graph showing the viscosity of various exfoliating agents in SPA-210.

FIG. 7 is a graph showing the viscosity of various exfoliating agents in HF-1000.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The term “wellbore fluid” or similar terms refers to any fluid which is used in any phase of the exploration, drilling or production of oil and gas from subterranean formations.

- 5 The compositions of the present invention, as will be seen below, can employ a base oil including pure hydrocarbon mixtures as well as a hydrocarbon in admixture with oxygenated compounds. In general, the base oil useful in the compositions of the present inventions comprise base oils with a significant content of naphthenic and/or highly branched paraffins. As a general rule, the
- 10 base oil can contain from about 20% to about 99% or greater naphthenics, isoparaffins, or a mixture thereof. In particular, the base oil having this composition will contain from about C8 to about C30. In Table 1 below, there are shown non-limiting examples of the wide variety of base oils which can be employed in the composition of the present invention.

15

Table 1

	LPA	LPA-142	LPA-170	LPA-210	Diesel	HF-1000	ODC-15
Linear	--	--	--	--	41.3 ¹	20.9	--
Isoparaffins (mol %)	25	21	28	30		14	25
Olefins	--	--	--	--	--	24.89	--
Napthenics (mono-cyclic) (mol %)	62	64	60	69	22.1 ²	30	47
Decalins (bi-cyclic) (mol %)	13	15	12	1	11.9 ³	--	10
Aromatics	--	--	--	--	24.7	--	15
Oxygenates	--	--	--	--	--	3.84	--
Carbon chain range	C10-C16	C-11-C12	C12-C14	C14-C16	C10-C20	C12-C22	

¹ Depends on specific diesel

² Also contains 2.3% tricyclic

³ Alcohols, esters

As can be seen from the above Table 1, the base oil can comprise liquid hydrocarbon having from about 10% to about 35% isoparaffins, from about 30% to about 73% naphthenics, and having a carbon chain length of from about C8 to about C30. As can also be seen from Table 1, some of the base oils can include significant amounts of linear paraffins while others can contain small amounts of oxygenates such as alcohols, esters, or the like. As should be further apparent from Table 1, some of the base oils can contain olefins while others, e.g., diesel, can contain significant amounts of aromatics. Table 1 demonstrates that the compositions of the present invention can employ, with advantage, a wide variety of base oils, all of which have significant hydrocarbon oil content, albeit that other compounds can be present in certain cases.


The organophilic clays that may be used in the compositions of the present invention include any clay in which the inorganic cations associated with the clay have been displaced by organic cations such as quarternary ammonium cations. Suitable organophilic clays include the reaction products of smectite-type, hectorite clays, or other clays and organic cations, i.e., quaternary ammonium cations (sometimes referred to as organophilic clay gellants); smectite clays; kaolin clays; and the like. The preferred organophilic clays used as a thixotropic viscosifying agent, in accordance with one aspect of the present invention, is a smectite-type clay that is selected from the group consisting of bentonite, hectorite, montmorillonite, nontronite, biedellite, saponite, stevensite, and mixtures thereof, most preferably bentonite or hectorite. The preferred

quaternary ammonium cations, in the event that the clay used is the reaction product of a clay and a quaternary ammonium compound, are selected from the group consisting of methyl trihydrogenated tallow ammonium, dimethyl dehydrogenated tallow ammonium, dimethyl benzyl hydrogenated tallow ammonium, methyl benzyl dehydrogenated tallow ammonium, and mixtures thereof. Exemplary organoclays and clay gellants suitable for use with the compositions described herein are set forth in the following U.S. patents, all of which may be referred to for details: U.S. Pat. No. 2,531,427; U.S. Pat. No. 2,966,506; U.S. Pat. No. 4,105,578; and U.S. Pat. No. 4,208,218.


10 Exemplary, commercially available organophilic clays suitable for use with the compositions described herein are CLAYTONETM. IMG 400 ClaytoneTM ER, ClaytoneTM EM, and ClaytoneTM II, available from Southern Clay Products, Inc., Gonzalez, Tex., U.S.A., or Bentone 34, Bentone 150 and BENTONETM. 38 Organoclay (a commercial hectorite-based product, available from a number of

15 suppliers).

The exfoliating agents of the present invention in general comprise glycerin carbonate in admixture with certain alkoxylated alcohols. The alkoxylated alcohols useful in the present invention will have the general formula:



20 wherein R is a linear or branched alkyl from 2 to 18 carbon atoms, or an aromatic radical having the structure:



where R₁ is a branched or linear alkyl having from 2 to 18 carbon atoms

R₂ is H or CH₃

R₃ is H or CH₃

- 5 a is from 0 to 12
and b is from 1 to 12.

The exfoliating agent of the present invention will generally comprise from about 10 % to about 100 % glycerin carbonate and from about 0% to about 90%
10 alkoxyated alcohol where all amounts are by weight based on the combined weight of the glycerin carbonate and the alkoxyated alcohol. It will be understood though that different exfoliating agents have different effectiveness in different base oils. Therefore the composition of the exfoliating agent should be tailored to fit the base oil in question.

- 15 The exfoliating agent may be incorporated into the wellbore fluid in any number of ways, whether by separate or previous addition to the base oil and/or clay, or by admixture with base oil, clay, and other components at the time of preparation of the wellbore fluid. In certain cases a "pill" comprised of exfoliating agent and organophilic clay, alone or together with other components, can be
20 employed, the pill being injected into the wellbore at a desired time.

The alkoxyated alcohol used in the examples which follow are ethoxylated alcohols sold by Sasol North America, Inc. under the trade name NOVEL[®]. As is

well known to those skilled in the art, the ethoxylated alcohols are formed by reacting various alcohols with ethylene oxide under suitable reaction conditions. The resulting ethoxylated alcohol thus has an alkyl chain residue from the alcohol and the desired number of ethoxy groups. By way of example, an ethoxylated alcohol designated as NOVEL[®] 1012-9 means that the ethoxylated alcohol has an alkyl chain length with an average carbon number of 10-12 and 9 ethoxy groups. An ethoxylated alcohol designated as NOVEL[®] 23E9 will contain an alkyl chain of 12-13 carbon atoms with 9 ethoxy groups.

In general, the compositions of the present invention will contain from about 95% to about 98% base oil, from about 1% to about 5% organophilic clay and from about 0.005% to about 1% exfoliating agent, where all amounts are in weight % based on the total composition.

To more fully illustrate the present invention, the following non-limiting examples are presented.

15

EXAMPLE 1

Three grams of Claytone[®] II organophilic clay was dispersed in 100 mL of diesel containing 1 mL of the exfoliating agent. The exfoliating agents are shown in Table 2 below. The exfoliating agents shown in Table 2 are used in Examples 2-7 as well.

20

Table 2

Exfoliating agent	Content		
Agent 1	0% glycerin carbonate (GC)	50% NOVEL [®] 1012-9	50% NOVEL [®] 23E9
Agent 2	33.33% glycerin carbonate (GC)	33.33% NOVEL [®] 1012-9	33.33% NOVEL [®] 23E9
Agent 3	60% glycerin	20% NOVEL [®]	20% NOVEL [®]

	carbonate (GC)	1012-9	23E9
Agent 4	70% glycerin carbonate (GC)	15% NOVEL [®] 1012-9	15% NOVEL [®] 23E9
Agent 5	80% glycerin carbonate (GC)	10% NOVEL [®] 1012-9	10% NOVEL [®] 23E9
Agent 6	100% glycerin carbonate (GC)	---	---

The mixture was mixed for three minutes and then sheared at medium-high (3) for one minute on a TURRAX high shear mixer. The samples were aged overnight for 16 hours at room temperature. The samples were then
5 rehomogenized for 30 seconds and tested on a Grace 3600 Viscometer. The results are shown in Figure 1 and indicate that the highest viscosity was achieved using 100% glycerin carbonate.

Example 2

The experiment of Example 1 was repeated, but the base oil used was
10 ODC-15. The results are shown in Fig. 2 and indicate that the highest viscosity was achieved using 80% glycerin carbonate and 20% alkoxylated alcohols.

Example 3

The experiment of Example 1 was repeated, but the base oil used was
LPA. The results are shown in Fig. 3 and indicate that the highest viscosity was
15 achieved using 80% glycerin carbonate and 20% alkoxylated alcohols.

Example 4

The experiment of Example 1 was repeated, but the base oil used was
LPA-142. The results are shown in Fig. 4 and indicate that the highest viscosity
was achieved using 70% glycerin carbonate and 30% alkoxylated alcohols.

20

Example 5

The experiment of Example 1 was repeated, but the base oil used was LPA-170. The results are shown in Fig. 5 and indicate that the highest viscosity was achieved using 70% glycerin carbonate and 30% alkoxylated alcohols.

Example 6

5 The experiment of Example 1 was repeated, but the base oil used was LPA-210. The results are shown in Fig. 6 and indicate that the highest viscosity was achieved using 80% glycerin carbonate and 20% alkoxylated alcohols.

Example 7

The experiment of Example 1 was repeated, but the base oil used was
10 HF-1000. The results are shown in Fig. 7 and indicate that the highest viscosity was achieved using 80% glycerin carbonate and 20% alkoxylated alcohols.

A summary of Examples 1-7 is shown in Table 3 below.

Table 3

Solvent	Carbon Number	Carbon Range	Exfoliating Agent	Reference Viscosity @ 0.017 1/sec shear rate (cP)
Diesel	17	10-24	Agent 6 (100% glycerin carbonate)	311,300
ODC-15	13	10-16	Agent 5 (80% Glycerin carbonate)	164,500
LPA	13	10-16	Agent 5 (80% Glycerin carbonate)	41,100
LPA-142	11	10-12	Agent 4 (70% Glycerin carbonate)	105,700
LPA-170	13	12-14	Agent 4 (70% Glycerin carbonate)	88,100
LPA-210	15	14-16	Agent 5 (80% Glycerin carbonate)	176,200
HF-1000	14	12-16	Agent 5 (80% Glycerin carbonate)	111,600

15 As can be seen from the data in Table 3, the exfoliating agents of the present invention display a remarkable ability with most of the base oils to increase the viscosity of the compositions.

Comparative Example 8

To more fully demonstrate the efficacy of the exfoliating agents of the present invention, the procedure of Example 1 was followed using four of the base oils shown in Table 1. As noted above, one of the most widely used exfoliating agents used with oil based drilling fluids containing organophilic clays is propylene carbonate. By comparing the data in Table 3 above and Table 4 below, it can readily be seen that the exfoliating agent of the present invention is clearly superior to propylene carbonate at exfoliating the organophilic clay.

Table 4

Solvent	Carbon Number	Carbon Range	Exfoliating Agent	Reference Viscosity @ 0.017 1/sec shear rate (cP)
Diesel	17	10-24	100% Propylene carbonate	0.0
ODC-15	13	10-16	100% Propylene carbonate	11,748
LPA-170	13	12-14	100% Propylene carbonate	0
HF-1000	14	12-16	100% Propylene carbonate	0

One of the advantages of the present invention is the fact that in the composition of the exfoliating agent and clay, water need not be present. As is well known, water in addition to reacting with the organophilic clay, may also interact with other additives such as guar gum, Xanthan gum, etc. Nonetheless, it is to be understood that in certain cases the addition of a small amount of water as a co-activator can further enhance the suspending characteristics of the resulting organophilic clay suspension medium. When used, water will generally be present in the composition in an amount from about 30 wt% to about 50 wt% based on the organophilic clay.

While in the above description, reference is made to the use of the exfoliating agents of the present invention in conjunction with organophilic clays

used in wellbore fluids, it will be understood that the invention is not so limited. As well known to those skilled in the art, activated, organophilic clays are well known for their gelling and viscosity increasing ability in organic liquids of many types. Thus, in addition to wellbore fluids, e.g., drilling fluids, they find wide usage
5 in paints, greases, and fiberglass resins. They may also be used in cosmetics, inks, and polishes.

It will be recognized that, when used as a wellbore fluid, the composition of the present invention may contain certain ingredients tailored to the specific use of the wellbore fluid. Thus, for example if the wellbore fluid was a sealing
10 composition for sealing off subterranean zones, water soluble clays, cross-linking agents, dispersing agents, cements, fillers and the like can also be employed. In the case of viscosity well treatment fluid compositions suitable for use in managed pressure drilling (MPD), the composition can also include emulsifiers, wetting agents, fluid loss control additives and weighing materials. Still further,
15 as is well known, completion fluids are generally comprised of clear brines containing such material as ammonium chloride, sodium chloride, sodium bromide, etc. The compositions of the present invention could be used to improve dispersion of additives of the resulting completion fluids so that the suspended particles remain suspended for longer periods of time or at higher
20 temperatures before being introduced into completion fluids. Fracturing fluids according to the present invention in addition to the viscosifying package can include, proppants, certain polymeric materials and other ingredients. Methods of employing various wellbore fluids for certain purposes are well known to those

skilled in the art and are also contemplated by the present invention. In general the wellbore fluids of the present invention can comprise an additive selected from the group consisting of emulsifiers, wetting agents, viscosifiers, weighting agents, fluid loss control agents, proppants, and particulate agents for forming
5 gravel packs.


Although specific embodiments of the invention have been described herein in some detail, this has been done solely for the purposes of explaining the various aspects of the invention, and is not intended to limit the scope of the invention as defined in the claims which follow. Those skilled in the art will
10 understand that the embodiment shown and described is exemplary, and various other substitutions, alterations and modifications, including but not limited to those design alternatives specifically discussed herein, may be made in the practice of the invention without departing from its scope.

WHAT IS CLAIMED IS:


1. An exfoliating agent for viscosifying a nonaqueous base fluid, the non-aqueous base fluid comprising an organophilic clay, wherein the exfoliating agent comprises:

glycerin carbonate;

an alkoxyated alcohol having the general formula:



wherein R is a linear or branched alkyl from 2 to 18 carbon atoms or an aromatic radical having the structure:



wherein R₁ is a branched or linear alkyl having from 2 to 18 carbon atoms,

R₂ is H or CH₃,

R₃ is H or CH₃,

a is from 0 to 12,

and b is from 1 to 12.

2. The exfoliating agent of claim 1, wherein said glycerin carbonate is present in an amount of 10 wt% and above and said alkoxyated alcohol is present in an amount of up to 90 wt% based on the total exfoliating agent.

3. The exfoliating agent of claim 1, wherein said glycerin carbonate is present in an amount of 80 wt% and said alkoxyated alcohol is present in an amount of 20 wt% based on the total exfoliating agent.

4. The exfoliating agent of claim 1, wherein said glycerin carbonate is present in an amount of 70 wt% and said alkoxyated alcohol is present in an amount of 30 wt% based on the total exfoliating agent.

5. The exfoliating agent of claim 1, wherein said glycerin carbonate is present in an amount of 60 wt% and said alkoxyated alcohol is present in an amount of 40 wt% based on the total exfoliating agent.

6. The exfoliating agent of claim 1, wherein said organophilic clay is a smectite-type clay selected from the group consisting of bentonite, hectorite, montmorillonite, nontronite, biedellite, saponite, stevensite, and mixtures thereof.

7. A wellbore fluid comprising:


a hydrocarbon base oil;

an organophilic clay;


an exfoliating agent comprising:

glycerin carbonate; and

an alkoxyated alcohol having the general formula:



wherein R is a linear or branched alkyl from 2 to 18 carbon atoms or an aromatic radical having the structure:



wherein R₁ is a branched or linear alkyl having from 2 to 18 carbon atoms,

R₂ is H or CH₃,

R₃ is H or CH₃,

a is from 0 to 12,

and b is from 1 to 12.

8. The wellbore fluid of claim 7, wherein said base oil comprises greater than 20% naphthenics.

9. The wellbore fluid of claim 7, wherein said base oil comprises from 10% to 35% isoparaffins.

10. The wellbore fluid of claim 7, wherein said glycerin carbonate is present in an amount of 10 wt% and above and said alkoxylated alcohol is present in an amount of up to 90 wt% based on the total exfoliating agent.

11. The wellbore fluid of claim 7, wherein said glycerin carbonate is present in an amount of 80 wt% and said alkoxylated alcohol is present in an amount of 20 wt% based on the total exfoliating agent.

12. The wellbore fluid of claim 7, wherein said glycerin carbonate is present in an amount of 70 wt% and said alkoxylated alcohol is present in an amount of 30 wt% based on the total exfoliating agent.

13. The wellbore fluid of claim 7, wherein said glycerin carbonate is present in an amount of 60 wt% and said alkoxylated alcohol is present in an amount of 40 wt% based on the total exfoliating agent.

14. The wellbore fluid of claim 7, wherein said organophilic clay is a smectite-type clay selected from the group consisting of bentonite, hectorite, montmorillonite, nontronite, biedellite, saponite, stevensite, and mixtures thereof.

15. The wellbore fluid of claim 7, wherein said organophilic clay is present in an amount of from 1 wt% to 5 wt% and said exfoliating agent is present in an amount of from 0.005 wt% to 1 wt% based on the total composition.

16. The wellbore fluid of claim 7, further comprising:
water in an amount of 30 to 50 wt% based on said organophilic clay.

17. The wellbore fluid of claim 7, further comprising:
an additive comprising at least one of emulsifiers, wetting agents, viscosifiers, weighting agents, fluid loss control agents, proppants, and particulate agents for forming gravel packs.

18. A method of treating a wellbore comprising:
introducing into the wellbore the composition of claim 1 and an additive comprising at least one of emulsifiers, wetting agents, viscosifiers, weighting agents, fluid loss control agents, proppants, and particulate agents for forming gravel packs.

19. The method of claim 18, wherein said treating comprises drilling a well.

20. The method of claim 18, wherein said treating comprises fracturing a well.

21. The method of claim 18, wherein said treating comprises forming a gravel pack.




Fig. 1




Fig. 2





Fig. 3






Fig. 5




Fig. 6




Fig. 7

