



US 20160054833A1

(19) **United States**
(12) **Patent Application Publication**
Ciesla et al.

(10) **Pub. No.: US 2016/0054833 A1**
(43) **Pub. Date: Feb. 25, 2016**

(54) **USER INTERFACE SYSTEM**

(71) Applicant: **Tactus Technology, Inc.**, Fremont, CA (US)
(72) Inventors: **Craig Michael Ciesla**, Fremont, CA (US); **Micah B. Yairi**, Fremont, CA (US); **Nathaniel Mark Saal**, Fremont, CA (US)

(21) Appl. No.: **14/927,859**

(22) Filed: **Oct. 30, 2015**

application No. 12/975,337 is a continuation-in-part of application No. 12/319,334, filed on Jan. 5, 2009, now Pat. No. 8,154,527.

(60) Provisional application No. 61/288,826, filed on Dec. 21, 2009.

Publication Classification


(51) **Int. Cl.**
G06F 3/044 (2006.01)
G06F 3/041 (2006.01)
(52) **U.S. Cl.**
CPC **G06F 3/044** (2013.01); **G06F 3/0414** (2013.01); **G06F 3/0416** (2013.01); **G06F 2203/04105** (2013.01)


Related U.S. Application Data

(63) Continuation of application No. 14/514,134, filed on Oct. 14, 2014, now Pat. No. 9,207,795, which is a continuation of application No. 12/975,337, filed on Dec. 21, 2010, now Pat. No. 8,922,503, which is a continuation-in-part of application No. 12/497,622, filed on Jul. 3, 2009, now Pat. No. 8,179,375, which is a continuation-in-part of application No. 11/969,848, filed on Jan. 4, 2008, now Pat. No. 8,547,339, said

(57) **ABSTRACT**

Disclosed is a user interface system that includes a sheet that defines a surface and at least partially defines a fluid vessel arranged underneath the surface, a volume of fluid within the fluid vessel, a displacement device that influences the volume of the fluid within the fluid vessel to expand and contract at least a portion of the fluid vessel, thereby deforming a particular region of the surface, and a sensor system that is configured to receive a user input on the surface with a first sensitivity and configured to receive a user input substantially proximal to the particular region of the surface at with second sensitivity higher than the first sensitivity.





130 FIG. 1A




FIG. 1B

FIG. 2A




FIG. 2B





FIG. 2C






FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7




FIG. 8A















FIG. 8B








FIG. 15A




FIG. 15B




FIG. 15C

USER INTERFACE SYSTEM

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is continuation of prior application Ser. No. 14/514,132, filed 14 Oct. 2014, which is a continuation of prior application Ser. No. 12/975,337 filed on 21 Dec. 2010, which is a continuation in part of prior application Ser. No. 12/497,622 filed on 3 Jul. 2009, now issued as U.S. Pat. No. 8,179,375, which is a continuation in part of prior application Ser. No. 11/969,848, filed on 4 Jan. 2008, now issued as U.S. Pat. No. 8,547,339, and application Ser. No. 12/975,337 is a continuation in part of prior application Ser. No. 12/319,334, filed on 5 Jan. 2009, now issued as U.S. Pat. No. 8,154,527, and claims the benefit of U.S. Provisional Application No. 61/288,826, filed on 21 Dec. 2009, all of which are incorporated in their entirety by this reference.

TECHNICAL FIELD

[0002] This invention relates generally to touch sensitive user interfaces, and more specifically to an improvement of the user interface of U.S. application Ser. No. 12/497,622.

BRIEF DESCRIPTION OF THE FIGURES

[0003] FIGS. 1*a* and 1*b* are a top view of the user interface system of a preferred embodiments and a cross-sectional view illustrating the operation of a button array in accordance to the preferred embodiments, respectively.

[0004] FIGS. 2*a*, 2*b*, and 2*c* are cross-sectional views of the retracted, extended, and user input modes of the preferred embodiments, respectively.

[0005] FIG. 3 is a cross-sectional view of the sheet, the cavity, the sensor, and the display of the preferred embodiments.

[0006] FIGS. 4*a*, 4*b*, and 4*c* are cross-sectional views of the sheet split into a layer portion and a substrate portion.

[0007] FIGS. 5*a* and 5*b* are cross-sectional views of the sheet, the cavity, the sensor, and a displacement device that modifies the existing fluid in the cavity, with the cavity in a retracted volume setting and an expanded volume setting, respectively.

[0008] FIG. 6 is a schematic view of the sheet, the cavity, the sensor, and a displacement device of a first example that displaces additional fluid into the cavity.

[0009] FIG. 7 is a schematic view of the sheet, the cavity, the sensor, and a displacement device of a second example that displaces additional fluid into the cavity.

[0010] FIGS. 8*a* and 8*b* are schematic views of the sheet, the cavity, the sensor, and a displacement device of a third example that displaces additional fluid into and out of the cavity, with the cavity in a retracted volume setting and an expanded volume setting, respectively.

[0011] FIGS. 9*a*, 9*b*, 10*a*, 10*b*, 11*a*, 11*b*, 12*a*, and 12*b* are top and side views of a button deformation, a slider deformation, a slider ring deformation, a guide deformation, and a pointing stick deformation, respectively.

[0012] FIG. 13 is a variation of the sensor as described in U.S. application Ser. No. 12/497,622.

[0013] FIGS. 14*a* and 14*b* are schematic views of the first and second variations of the first preferred embodiment.

[0014] FIGS. 15*a*, 15*b*, and 15*c* are schematic views of the second preferred embodiment, user input locations with

respect to the second preferred embodiment, and the method for determination of input locations in the second preferred embodiment, respectively.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0015] The following description of the preferred embodiments of the invention is not intended to limit the invention to these preferred embodiments, but rather to enable any person skilled in the art to make and use this invention.

[0016] As shown in FIGS. 1 and 2, the user interface system 100 of the preferred embodiments includes a sheet 102 that defines a surface 115 and a fluid vessel 127, a volume of a fluid 112 contained within the fluid vessel 127, a displacement device 130 that modifies the volume of the fluid 112 to expand at least a portion of the fluid vessel 127 (thereby outwardly deforming a particular region 113 of the surface 115), and a capacitive sensor system 140 that receives a user input on the surface 115 at a first sensitivity and receives a user input substantially proximal to the particular region of the surface at a second sensitivity higher than the first sensitivity. As shown in FIG. 3, the user interface system may also include a processor 160 that functions to detect the user input and/or to evaluate the user input received by the capacitive sensor system 140. The processor 160 is preferably coupled to the capacitive sensor system 140 to receive signals from the capacitive sensor system 140. The processor 160 may also be coupled to the displacement device 130 to send signals to the displacement device 130. As shown in FIG. 3, the user interface system 100 may also include a display 150 coupled to the sheet 102 and adapted to output images to the user. In this variation, the processor 160 may also be coupled to the display 150 to control the display 150. The capacitive sensor system 140 may also be located in between the sheet 102 and the display 150 and may alternatively include a plurality of sensor components that are located in various locations within the user interface system 100. However, any other suitable arrangement of the components of the system 100 may be used. As shown in FIGS. 1*b* and 2, the fluid vessel 127 is preferably a cavity 125 and the displacement device 130 preferably influences the volume of fluid within the cavity 125 to expand and retract the cavity 125. The fluid vessel 127 may alternatively be a channel 138 or a combination of a channel 138 and a cavity 125, as shown in FIG. 4*a*. The fluid vessel 127 may also include a second cavity 125*b* that contains a volume of fluid 112 and the displacement device 130 preferably also influences the volume of the fluid within the second cavity 125*b* to expand and retract the second cavity 125*b*, thereby deforming a second particular region 113 of the surface 115. The displacement device 130 preferably influences the volume of fluid 112 within the second cavity 125*b* independently of the cavity 125, but may alternatively influence the volumes of fluid 112 within both cavity and second cavity 125 and 125*b* substantially concurrently. Alternatively, the user interface enhancement system 100 may include a second displacement device 130 that functions to influence the volume of fluid 112 within the second cavity 125*b* to expand and retract the second cavity 125*b*, thereby deforming a second particular region 113 of the surface. The second cavity 125*b* is preferably similar or identical to the cavity 125, but may alternatively be any other suitable type of cavity.

[0017] The user interface system 100 of the preferred embodiments has been specifically designed to be used as the user interface for an electronic device, more preferably in an

electronic device that features an adaptive user interface. The electronic device, which may or may not include a display, may be an automotive console, a desktop computer, a laptop computer, a tablet computer, a television, a radio, any suitable appliance, a desk phone, a mobile phone, a PDA, a personal navigation device, a personal media player, a camera, a watch, a remote, a mouse, a trackpad, or a keyboard. The user interface system 100 may, however, be used as the user interface for any suitable device that interfaces with a user in a tactile and/or visual manner. As shown in FIG. 2, the surface 115 of the user interface system 100 preferably remains flat until a tactile guidance is to be provided at the location of the particular region 113. The surface 115 of the user interface system 100 may also be deformed when a user input is required. At that time, the displacement device 130 may increase the volume of the fluid within the fluid vessel 127 (or at the cavity 125) to deform and/or expand the particular region 113 outward, preferably forming a button-like shape. With the button-like shape, the user will have tactile guidance when navigating for the expanded particular region 113 and will have tactile feedback when applying force onto the particular region 113 to provide input. The capacitive sensor system 140 preferably senses a user input that inwardly deforms the particular region 113, but may alternatively a user input that inwardly deforms any other suitable region along the surface 115 and/or any other user input that does not inwardly deform the surface 115. However, any other arrangement of the user interface system 100 suitable to providing tactile guidance and/or detecting user input may be used.

[0018] As shown in FIG. 3, the user interface system 100 may be display 150 that displays an image. As described above, the volume of fluid 112 and/or the capacitive sensor system 140 preferably cooperates with the sheet 102 to transmit an image through the sheet 102 without substantial obstruction. Alternatively, the volume of fluid 112 may cooperate with the sheet 102 to transmit an image through the sheet 102 without substantial obstruction only when the fluid vessel 127 is in a particular state, for example, when the fluid vessel 127 is in the retracted state or when the fluid vessel is in the expanded state. Because the deformation of the particular region 113 functions to provide tactile guidance to the user, the user may not need the visual cues from the image to operate the user interface when tactile guidance is present. However, the volume of fluid 112 and the sheet 102 may cooperate to transmit an image through the sheet 102 without substantial obstruction in any other suitable arrangement. Obstruction to image transmission may be defined as any manipulation of the image that provides a visual interruption of the image in reaching the user. Obstruction may include blocking a substantial portion of the image, substantially dimming the image, and/or substantially distorting the image unintelligibly. Manipulations to an image that are preferably not considered obstruction to image transmission may include distortion of the image while allowing the image to be substantially visually intelligible, substantially uniformly tinting the image, and/or substantially uniformly enlarging the image. In a first variation, to decrease distortion of the image, the volume of fluid 112 and the sheet 102 preferably cooperate to allow the light from the display to reach the user's eyes at substantially the same angle from the sheet 102 as directly from the display 150 such that an image from the display is seen through the sheet 102 as it would be seen directly from the display. In a second variation, the volume of

fluid 112 and sheet 102 may function to substantially uniformly refract light from the display to maintain substantially the same relative proportions between different regions of the image as seen by the user. For example, the volume of fluid 112 and the sheet 102 may cooperatively function to substantially magnify the image from the display of the device 10 thus increasing the size of the image as seen by the user uniformly or increasing the size of one portion of the image more than another portion. In a third variation, the volume of fluid 112 and sheet 102 may cooperate to refract light from different portions of the image differently (i.e., "warp" the image) to increase the magnification of certain portions of the image. For example, the fluid 112 and the sheet 102 may cooperate to provide a fish-eye type magnification to the image to substantially increase visibility of certain portions of the image. In the first, second, and third variations, the volume of fluid 112 and sheet 102 are preferably each of substantially the same index of refraction to maintain substantially one refraction angle of the light from the display as the light transmits through the sheet 102. Alternatively, the index of refraction of the volume of fluid 112 and the sheet 102 may be substantially different but the fluid 112 and sheet 102 preferably cooperate to decrease detection of the different refraction angles by the user. For example, the volume of fluid 112 may occupy a substantially small percentage of the thickness and/or width of the sheet 102 such that the change in refraction angle in the fluid 112 is substantially undetectable by the user. In a second example, the walls of the channel 138 and/or cavity 125 may be arranged to compensate for differences in the index of refraction between the fluid 112 and the sheet 102, for example, by positioning the walls at a particular angle relative to the sheet 102. Both the sheet 102 and the fluid 112 are preferably substantially transparent to decrease changes in the color and/or intensity of the image. Similarly, the sheet 102 and fluid 112 preferably both include substantially similar light absorptive properties, birefringence properties, and/or chromaticity properties. However, any other suitable translucency, transparency level, absorptive, refraction, and/or any other suitable light transmission properties may be used for the sheet 102 and fluid 112. Similarly, any other suitable method may be used to decrease obstruction to the transmission of an image.

1. The Sheet

[0019] As shown in FIGS. 1 and 2, the sheet 102 of the preferred embodiment functions to provide the surface 115 that interfaces with a user in a tactile manner and to at least partially define a fluid vessel 127. As described above, the fluid vessel 127 is preferably a cavity 125 (as shown in FIGS. 1b and 2), but may alternatively be a channel 138 or a combination of a cavity 125 and a channel 138 (as shown in FIG. 4a). The surface 115 is preferably continuous, such that when swiping a finger across the surface 115 a user would not feel any interruptions or seams. Alternatively, the surface 115 may include features that facilitate the user in distinguishing one region from another. The surface 115 is also preferably planar. The surface 115 is preferably arranged in a flat plane, but may alternatively be arranged in a curved plane or on a first plane and then wrapped around to a second plane substantially perpendicular to the first plane, or any other suitable arrangement. The surface 115 may alternatively include lumps, bumps, depressions, textures, or may be a surface of any other suitable type or geometry. The surface 115 also functions to deform upon an expansion of the cavity 125, and

to preferably “relax” or “un-deform” back to a normal planar state upon retraction of the cavity 125. In a first version, the sheet 102 contains a first portion that is elastic and a second portion that is relatively inelastic. In a second version, sheet 102 is relatively more elastic in a first portion and relatively less elastic in a second portion and is deformed by the expanded cavity 125 in the relatively more elastic portion. In the first and second version, the first portion and the second portion may be located across the length and width of the sheet 102. Alternatively, the first portion and the second portion may be located along the thickness of the sheet 102. In a third version, the sheet 102 is generally uniformly elastic. In fourth version, the sheet 102 includes or is made of a smart material, for example, a shape memory alloy such as Nickel Titanium (commonly referred to as “Nitinol”), that has a selective and/or variable elasticity or a shape memory polymer that may be activated, for example, by ultra violet light or any other suitable type of activation, to have selective and/or variable elasticity. The sheet 102 is preferably optically transparent, but may alternatively be translucent or opaque. In addition to the transparency, the sheet 102 preferably has the following properties: a high transmission, a low haze, a wide viewing angle, a minimal amount of back reflectance upon the display (if the display is included with the user interface system 100), minimal or low glare in ambient and/or daylight condition, scratch resistant, chemical resistant, stain resistant, relatively smooth (not tacky) to the touch, no out-gassing, and/or relatively low degradation rate when exposed to ultra-violet light. The material may also include properties that change during the usage of the device, for example, in the variation that utilizes shape memory polymer, usage of the device in an environment that includes a wavelength or wavelengths of light that may change the properties of the shape memory polymer desirably. For example, certain parts of the material may change elasticity when exposed to UV light. In a second example, the material may change shape. In this example, the volume of fluid 112 within the fluid vessel 127 preferably substantially conforms to the changed shape of the material. This may allow for light to transmit through the fluid 112 and the material without substantial obstruction. However, any other suitable dynamic physical property may be used. This change in the properties may be temporary, in particular, once the wavelength of light is no longer present, the material preferably reverts back to the original state. Alternatively, the change may be permanent. In this variation, the change is preferably reversible, for example, the material may revert back to the original state when exposed to another wavelength of light. In the variation wherein the sheet 102 is placed over a display, the sheet 102 may also function to decrease reflection and/or refraction of light emitting from the display. However, the sheet 102 may include any other suitable material property.

[0020] The sheet 102 is preferably made from a suitable elastic material, including polymers and silicone-based and urethane elastomers such as poly-dimethylsiloxane (PDMS) or RTV Silicone (e.g., Momentive RTV Silicone 615). The sheet 102 may also include coatings to provide properties such as smoothness (for example, low coefficient of friction), hydrophobic and oleophobic characteristics, scratch resistance, scratch concealing, and/or resistance to debris retention. The sheet 102 may also include coatings to provide desired optical properties, such as anti-reflection and antiglare. Coatings may be applied on the surface 115, but may alternatively be applied on any other suitable surface of the

sheet 102. In the version wherein the sheet 102 includes a first portion that is elastic and a second portion that is relatively inelastic, the inelastic portion is preferably made from a material including polymers or glass, for example, elastomers, silicone-based organic polymers such as poly-dimethylsiloxane (PDMS), thermoset plastics such as polymethyl methacrylate (PMMA), and photocurable solvent resistant elastomers such as perfluoropolyethers. The sheet 102 may, however, be made of any suitable material that provides the surface 115 that deforms and defines a fluid vessel 127.

[0021] The sheet 102 may be manufactured using well-known techniques for micro-fluid arrays to create one or more cavities and/or micro channels. The sheet 102 may be constructed using multiple layers from the same material or from different suitable materials, for example, the sheet 102 may include a layer portion 110 of one material that defines the surface 115 and a substrate portion 120 of a second material (as shown in FIGS. 4a and 4c). As shown in FIGS. 4a and 4b, the substrate portion 120 preferably defines a fluid outlet 116 that allows fluid to flow between the channel 138 and the cavity 125 to deform and un-deform a particular region of the surface 113. The fluid outlet 116 may be formed into the substrate portion 120, for example, the fluid outlet 116 may be a series of bores that are formed into the substrate in between the channel 138 and the cavity 125 as shown in FIGS. 4a and 4b or an open orifice between the cavity 125 and the channel 138 as shown in FIG. 4c, but may alternatively be a property of the material, for example, the substrate portion 120 may include a porous material that includes a series of interconnected cavities that allow fluid to flow through the substrate portion 120. The substrate portion 120 may define any suitable number of fluid outlets 116 that are of any suitable size and shape. The substrate portion 120 may also include a fluid outlet layer that defines the fluid outlets 116 that is separate from substrate portion 120 and arranged in between the substrate portion 120 and layer portion 110. However, any other suitable arrangement of the fluid outlets 116 may be used. As shown in FIG. 4b, the portion of the substrate portion 120 (or fluid outlet layer) that includes the fluid outlets 116 may also function to provide a support for the layer portion no to substantially prevent the layer portion no from substantially depressing into the channel 138 when force is applied over the particular region 113. However, the substrate portion 120 may be arranged in any other suitable manner and may provide support for the layer portion 110 in any other suitable way.

[0022] The layer portion 110 is preferably attached to the substrate portion 120 (or fluid outlet layer) at an attachment point 117 that at least partially defines the size and/or shape of the particular region 113. In other words, the attachment point 117 functions to define a border between a deformable particular region of the surface 113 and the rest of the surface 115 and the size of the particular region 113 is substantially independent of the size of the cavity 124 and/or the channel 138. The attachment point 117 may be a series of continuous points that define an edge, but may alternatively be a series of non-continuous points. The attachment point 117 may be formed using, for example, adhesive, chemical bonding, surface activation, welding, or any other suitable attachment material and/or method. The method and material used to form the attachment point 117 is preferably of a similar optical property as the layer portion 110 and the substrate portion 120, but may alternatively be of any other optical property. Other portions of the layer portion no and substrate portion

120 not corresponding to a particular region of the surface **113** may also be adhered using similar or identical materials and methods to the attachment point **117**. Alternatively, the layer portion **110** and substrate portion **120** may be left unattached in other portions not corresponding to a particular region of the surface **113**. However, the sheet **102** may be arranged in any other suitable manner.

2. The Displacement Device

[0023] The displacement device **130** of the preferred embodiment functions to influence the volume of the fluid **112** to deform at least a portion of the fluid vessel **127** from the retracted volume setting to the extended volume setting and, ultimately, deforming a particular region **113** of the surface **115**. The displacement device **130** preferably functions to expand at least a portion of the fluid vessel **127**, but may alternatively function to contract at least a portion or any other suitable manipulation of at least a portion of the fluid vessel **127**. The displacement device **130** preferably modifies the volume of the fluid **112** by (1) modifying the volume of the existing fluid in the fluid vessel **127**, or (2) adding and removing fluid to and from the fluid vessel **127**. The displacement device **130** may, however, influence the volume of the fluid **112** by any suitable device or method. Modifying the volume of the existing fluid in the fluid vessel **127** may have an advantage of lesser complexity, while adding and removing fluid to and from the fluid vessel **127** may have an advantage of maintaining the deformation of the surface **115** without the need for additional energy (if valves or other lockable mechanisms are used). When used with a mobile phone device, the displacement device **130** preferably increases the volume of the fluid **112** within the fluid vessel **127** by approximately 0.003-0.1 ml. When used with this or other applications, however, the volume of the fluid may be increased (or possibly decreased) by any suitable amount. The variations of the displacement device **130** described below refer to modifying the volume of the fluid to expand the cavity **125**, but may be applied to any other suitable portion of the fluid vessel **127**.

[0024] Modifying the existing fluid in the cavity **125** may be accomplished in several ways. In a first example, as shown in FIGS. **5a** and **5b**, the fluid may be an expandable fluid and the displacement device **130** may include a heating element that heats the expandable fluid, thereby expanding the volume of the existing fluid in the cavity **125** (according to the ideal gas law, $PV=nRT$). The heating element, which may be located within, adjacent the cavity **125**, or any other location suitable to providing heat to the fluid, is preferably a resistive heater (made of a material such as TaN or Nichrome). In a second example, the fluid may include an expandable substance, such as plastic expandable microspheres. In a third example, the fluid may include paraffin. While these are three examples, the displacement device **130** can be any other suitable device or method that ultimately expands the cavity **125** from the retracted volume setting to the extended volume setting by modifying the existing fluid in the cavity **125**.

[0025] Adding and removing fluid to and from the cavity **125** may also be accomplished in several ways. In a first example, as shown in FIG. **6**, the displacement device **130** includes a reservoir **132** to hold additional fluid and a pump **134** to displace fluid from the reservoir **132** to the cavity **125**. The reservoir **132** is preferably remote from the cavity **125** (and connected by a channel **138** or other suitable device), but may alternatively be located adjacent the cavity **125** and connected directly to the cavity **125**. A portion of the channel

138 is preferably a micro-fluidic channel (having cross-section dimensions in the range of 1 micrometer to 1000 micrometers), but depending on the size and costs constraints of the user interface system **100**, the channel **138** may have any suitable dimensions. The pump **134** is preferably a micro-pump (such as pump #MDP2205 from ThinXXS Microtechnology AG of Zweibrucken, Germany or pump #mp5 from Bartels Mikrotechnik GmbH of Dortmund, Germany), but may be any suitable device to pump fluid from one location to another. The pump **134** is preferably located at a distance from the cavity **125**, and is preferably connected to the cavity **125** by a channel **138**. To extend the cavity **125** from a retracted volume setting to the extended volume setting, the pump **134** displaces fluid from a reservoir **132**, through the channel **138**, and into the cavity **125**. To retract the cavity **125** from the extended volume setting to the retracted volume setting, the pump **134** preferably “vents” or pumps in a reverse direction from the cavity **125** to the reservoir **132**. In a second example, as shown in FIG. **7**, the displacement device **130** includes a reservoir **132** to hold additional fluid, a first pump **134** to displace fluid from the reservoir **132** to the cavity **125**, a second pump **136** to displace fluid from the cavity **125** to the reservoir **132**, a first valve located between the first pump **134** and the cavity **125**, and a second valve located between the cavity **125** and the second pump **136**. To extend the cavity **125** from the retracted volume setting to the extended volume setting, the first valve is opened, the second valve is closed, and the first pump **134** displaces fluid from the reservoir **132**, through the channel **138**, and into the cavity **125**. To retract the cavity **125** from the extended position to the retracted position, the first valve is closed, the second valve is opened, and the second pump **136** displaces fluid from the cavity **125**, through the channel **138**, and into the reservoir **132**. In other respects, the second example is similar to the first example above. The user interface system **100** may omit the second pump **136** and simply retract the cavity **125** from the extended volume setting to the retracted volume setting by opening the second valve and allowing the cavity **125** to vent or “drain” into the reservoir **132** (potentially assisted by the elasticity of the sheet **102** returning to an un-deformed state). In a third example, as shown in FIGS. **8a** and **8b**, the displacement device **130** includes an actuator, such as a linear actuator, that displaces fluid into and out of the cavity **125**. To extend the cavity **125** from a retracted volume setting to the extended volume setting, as shown in FIG. **8a**, the linear actuator displaces fluid through the channel **138** and into the cavity **125**. To retract the cavity **125** from the extended volume setting to the retracted volume setting, as shown in FIG. **8b**, the linear actuator draws fluid in a reverse direction from the cavity **125** to the reservoir **132**. In other respects, the third example is similar to the second example above. While these are three examples, the displacement device **130** can be any other suitable device or method that ultimately expands the cavity **125** from the retracted volume setting to the extended volume setting by adding and removing fluid to and from the cavity **125**.

[0026] Although the cause of the deformation of a particular region **113** of the surface **115** has been described as a modification of the volume of the fluid in the cavity **125**, it is possible to describe the cause of the deformation as an increase in the pressure below the surface **115** relative to the pressure above the surface **115**. When used with a mobile phone device, an increase of approximately 0.1-10.0 psi between the pressure below the sheet **102** relative to the

pressure above the sheet **102**, is preferably enough to deform a particular region **113** of the surface **115**. When used with this or other applications, however, the modification of the pressure may be increased (or possibly decreased) by any suitable amount.

3. The Deformation of the Surface

[0027] As shown in FIG. 2, The fluid vessel **127** of the preferred embodiment functions to hold a volume of fluid **112** and to have at least two volumetric settings: a retracted volume setting (as shown in FIG. 2a for the variation of the fluid vessel **127** that includes a cavity **125**) and an expanded volume setting (shown in FIG. 2b for the variation of the fluid vessel **127** that includes a cavity **125**). Alternatively, there may be a plurality of volume settings or a dynamic range of volume settings. The fluid **112** is preferably a substantially incompressible fluid, but may alternatively be a compressible fluid. The fluid **112** is preferably a liquid (such as water, glycerin, or ethylene glycol), but may alternatively be a gas (such as air, nitrogen, or argon) or any other substance (such as a gel or aerogel) that expands the cavity **125** and deforms the surface **115**. The fluid **112** may also function to direct selected wavelengths of light, such as UV light, to desired portions of the sheet **102**, due to wavelength specific refractive index changes. In the extended volume setting, the cavity **125** deforms the particular region **113** of the surface **115** above the plane of the other regions of the surface **115**. When used with a mobile phone device, the cavity **125** preferably has a diameter of 2-10 mm. When used with this or other applications, however, the cavity **125** may have any suitable dimension.

[0028] The shape of the deformation of the particular region **113** is preferably one that is felt by a user through their finger and preferably acts as (1) a button that can be pressed by the user (as shown in FIG. 9), (2) a slider that can be pressed by the user in one location along the slider or that can be swept in a sliding motion along the slider (such as the “click wheel” of the Apple iPod (second generation)) (as shown in FIGS. 10 and 11), and/or (3) a pointing stick that can be pressed by the user from multiple directions and/or locations along the surface whereby the user is provided with tactile feedback that distinguishes a first directional touch from a second directional touch and/or a touch in a first location from a touch in a second location (such as the pointing stick trademarked by IBM as the TRACKPOINT and by Synaptics as the TOUCHSTYK (which are both informally known as the “nipple”)) (as shown in FIG. 12). The deformation may, however, act as any other suitable device or method that provides suitable tactile guidance and feedback. In the variation including a display **150**, the shape of the deformation of the particular region **113** also preferably functions to minimize the optical distortion of the image underneath the deformed particular region **113**.

4. The Capacitive Sensor System

[0029] In the preferred embodiments of the present invention, a capacitive sensor system **140** preferably receives a user input on the surface **115**. However, as mentioned in U.S. application Ser. No. 12/497,622, the sensor **140** may be a resistive sensor and/or any other suitable type of sensor to sense the presence of a user input at the particular region **113**. Alternatively, the capacitive sensor system **140** may also receive a user input substantially adjacent to the surface **115**,

for example, in the variation of the user interface that is applied to a mobile phone with a main surface **115** and a side surface substantially perpendicular to the main surface **115**, the capacitive sensor system **140** may function to detect a user input on the side surface. As shown in FIG. 14, the capacitive sensor system **140** is arranged into an array of the type described as the second variation of the array in U.S. application Ser. No. 12/497,622 for a plurality of cavities **125**. Also as described in U.S. application Ser. No. 12/497,622, the presence of a user input is preferably detected by detection of a change in the electric field and/or capacitance between a first conductor and a second conductor that both correspond to a particular region **113**. The capacitive sensor system **140** of the preferred embodiments functions to detect the presence of a user input at locations of the surface **115** that do not include a particular region as well as a user input at the particular region **113**. The capacitive sensor system **140** of the preferred embodiments preferably functions to detect the presence of a user input that deforms the surface **115** and/or a user input that does not deform the surface **115**. Because the sensor **140** is preferably a capacitive sensor that utilizes electric fields for user input detection, the capacitive sensor system **140** preferably also accommodates to capacitance changes that result from expansion and retraction of the cavities **125** (for example, the increased height of fluid in the cavity **125** may affect the capacitance and/or the increased volume of fluid within the cavity **125** may affect the capacitance) and detects user input in both the expanded and retracted states of the cavities **125**.

[0030] Because the deformed particular region **113** preferably functions as a guide for a user input substantially proximal to the particular region **113**, the capacitive sensor system **140** preferably detects a user input substantially proximal to the particular region **113** at a higher sensitivity than other regions of the surface **115** the increase the accuracy of detecting a user input that is provided substantially proximal to the deformed particular region **113**. The capacitive sensor system **140** of the second sensitivity may be of a higher location detection sensitivity than the first sensitivity, for example, the detection of the X-Y location of the user input relative to the surface **115** is more accurately determined (e.g., with a lower margin of error) or the distinction between two user inputs that are provide substantially close to each other may be higher in the second sensitivity than the first sensitivity, but may alternatively be of a higher detection sensitivity than the first sensitivity, for example, the presence of a user input is more accurately detected. Alternatively, the second sensitivity detects attributes of the deformed particular region at a higher accuracy than the first sensitivity, for example, the second sensitivity may detect the height of the deformed particular region **113**, the speed of inward deformation of the deformed particular region **113** by the user, and/or the degree of inward deformation of the deformed particular region **113** by the user at a higher sensitivity than the first sensitivity. However, the second sensitivity may be higher than the first sensitivity in detecting any other suitable characteristic of the user input, for example, magnitude of the force of the input and/or the rate of the force applied of the input. As shown in FIGS. 14a, 14b, and 15, the capacitive sensor system **140** of the preferred embodiments preferably includes a first sensor portion **140a** that detects user input anywhere along the surface **115** at a first sensitivity and a second sensor portion **140b** that detects a user input substantially proximal to the particular regions **113** at a second sensitivity. In a first preferred

embodiment, the first and second sensor portions of the capacitive sensor system 140 are substantially independent of each other and a second preferred embodiment, the second sensor portion increases the sensitivity of the first sensor portion to the second sensitivity substantially proximal to the particular region 113 of the surface.

[0031] In the preferred embodiments, the processor 160 may function to prioritize a user input detected substantially proximal to the particular region 113. For example, the processor 160 may include a first mode that evaluates a user input provided substantially proximal to the particular region 113 at substantially the same weight as a user input provided on another region of the surface substantially concurrently and a second mode that evaluates a user input provided substantially proximal to the particular region 113 over one that is provided on another region of the surface substantially concurrently. The second mode may be particularly useful when the displacement device 130 influences the volume of fluid 112 to deform the particular region 113 of the surface. Because the particular region 113 preferably functions as a guide for a user input that may be provided substantially proximal to the particular region 113, when the particular region 113 is deformed, a user input provided substantially proximal to the particular region 113 may be more likely to be the desired input of the user while another input received at another region of the surface 113 substantially concurrently may be an unintentional input. The processor 160 may also function to activate the second sensitivity of the capacitive sensor system 160. The increased sensitivity of the second sensor portion 140b may increase energy consumption of the user interface system 100. To decrease the energy consumption of the user interface system 100, the processor 160 may function to active the second sensor portion 140b only when the increased second sensitivity is desired, for example, when a particular region 113 is deformed. Alternatively, because the detection of a characteristic of the user input in the second sensitivity may increase the amount of computing power used by the processor 160, the processor 160 may function to detect a user input at the second sensitivity only when the second sensitivity is desired, for example, when the particular region 113 is deformed. However, any other suitable type of control of the first and second sensor portions 140a and 140b may be used.

[0032] In the first preferred embodiment, as shown in FIGS. 15a and 15b, the user interface system includes a first sensor portion 140a that includes at least one horizontal conductor 244 and at least one vertical conductor 242 and functions to detect user input anywhere along the surface 115 and a second sensor portion 140b that includes a set of first conductors 246 and a set of second conductors 248 and functions to detect user input only at the particular regions 113. In this first preferred embodiment, the processor 160 functions to determine which of the first and second sensing systems 140a and 140b to be used for detection of user input at any one time. For example, the first sensor portion 140a may be the default sensing system until an application of the device activates the expansion of the cavities 125 and deforms the particular regions 113. Once the expansion of the cavities 125 is activated, the second sensor portion 140b is then used to provide substantially more accurate details of user input (for example, speed of user input, direction of user input, pressure of user input, or the amount of inward deformation of the particular region 113) at the particular regions 113. Once the cavities 125 are retracted, the user interface system preferably returns

to utilizing the first sensor portion 140a. Alternatively, both the first sensor portion 140a and the second sensor portion 140b may be used concurrently when the expansion of the cavities 125 is activated to allow for increased accuracy in the details of the user input at the particular regions 113 as well as detection of user input at locations away from the portion of the surface 115 that includes the particular regions 113. The user interface system of the first preferred embodiment may include a first driver chip that cooperates with the first sensor portion 140a and a second driver chip that cooperates with the second system 140b, but may alternatively include one driver chip that drives both the first and second sensing systems 140a and 140b. However, any other suitable arrangement of the driver chips and the processor 160 may be used.

[0033] As shown in FIGS. 15a and 15b, the first sensor portion 140a may be of a type that is known in the art and the second sensor portion 140b is preferably one that has been described in U.S. application Ser. No. 12/497,622. For example, as shown in FIG. 15a, the first sensor portion 140a may include vertical conductors 242 and 243 substantially at the left and right edges of the surface 115 and horizontal conductors 244 and 246 substantially at the top and bottom edges of the surface 115. An electric field is provided by a vertical conductor 242 and a horizontal conductor 244 that is detected by the other vertical conductor 243 and the other horizontal conductor 246. An example of electric field generation may be by transmitting a current through the vertical conductor 242 and the horizontal conductor 244 that creates an electric field that is detected by the by the other vertical conductor 243 and the other horizontal conductor 246. However, any other suitable method of generating an electric field may be used. The presence of a finger may cause disruptions and/or fluctuations in the electric field that are detected and the location of the finger may be triangulated from the electric field that is felt by the electric field receivers vertical conductor 243 and horizontal conductor 246. Alternatively, an electric field may be provided only by the horizontal conductors 244 and 246 or only by the vertical conductors 242 and 243. However, any other suitable arrangement of providing detectable electric fields may be used. In a second example, as shown in FIG. 14b, the method known in the art of projected capacitance may be used to detect user input. The first sensor portion 140a of this variation preferably includes a grid of vertical conductors 242 and horizontal conductors 244 where the location of electric field fluctuations due to a finger or any other suitable body part or object is more accurately detected, allowing advanced touch sensing applications such as multi-finger touch. In a third example, the first sensor portion 140a may also sense the presence and the location of the user input by using surface capacitance where the sheet 102 may include a layer of conductive material to which a voltage is applied. The conductive layer is preferably transparent and/or index matched with the rest of the sheet 102 and preferably is located away from the surface 115. When the finger of the user comes into contact with the surface 115, the proximity of the finger with the conductive layer creates a change in the capacitance and the resulting change capacitance at various static locations along the surface 115 is measured to triangulate the location of the finger of the user. The conductors of the first sensor portion 140a may be arranged diagonally, in a cross pattern, or any other suitable orientation. The conductors of the first sensor portion 140a may also be of any other suitable shape (for example, the conductors may resemble a sine wave), size, or geometry. However, any other suitable

capacitive touch system known in the art may be used for the first sensor portion **140a** and the second sensor portion **140b**.

[0034] As described in U.S. application Ser. No. 12/497,622, the second sensor portion **140b** may include a first and second conductor at a particular region **113** and the distance between the first and second conductor changes when a user provides an input at the particular region to detect and receive a user input. The distance between first and second conductor at the particular region **113** preferably decreases as a user input is provided at the particular region **113** (for example, one that inwardly deforms the particular region **113**), but may alternatively increase. The first and second conductor may alternatively come into contact to substantially detect a user input substantially proximal to the particular region **113**. Because the second sensor portion **140b** includes conductors that are configured to detect a user input at the particular region **113**, the sensitivity for detection of a user input, determining the location of the user input, and/or detecting any other suitable characteristic of the user input may be increased. However, any other suitable arrangement of conductors may be used for the second sensor portion **140b** to provide the higher second sensitivity to a user input provided substantially proximal to the particular region **113**.

[0035] The second preferred embodiment, as shown in FIGS. **15a** and **15b**, preferably includes a sensing system that allows for the detection of both user inputs at a particular region **113** and anywhere along the surface **115** at the second and first sensitivities, respectively, without the need of an additional sensor system (for example, a first sensor system to detect the presence and/or properties of user inputs at a particular region **113** and a second sensor system to detect the presence and/or properties of user inputs elsewhere along the surface **115**). The sensor **140** of the second preferred embodiment preferably utilizes one driver chip that cooperates to detect both user inputs at a particular region **113** and anywhere else along the surface **115**. In a first variation of the second preferred embodiment, the sensor **140** preferably includes a first sensing portion **140a** that includes elongated vertical conductors **242** (shown as **242a** and **242b**), and non-array horizontal conductor **244** with a first sensitivity to a user input and a second sensing portion **140b** that includes horizontal array conductors **246** (three horizontal array conductors **246a**, **246b**, and **246c** are shown, but may be any other suitable number), vertical array conductors **248** (three vertical array conductors **248a**, **248b**, and **248c** are shown, but may be any other suitable number), that increases the sensitivity to the second sensitivity substantially proximal to the particular region **113** of the surface. The horizontal and vertical array conductors **246** and **248** of the second sensor portion **140b** are preferably of the type of conductor **142** and **144**, respectively, as described in U.S. application Ser. No. 12/497,622. The elongated vertical conductors **242** of the first sensor portion **140a** are preferably of the same conductor type as the vertical array conductors **248** and extend through a column of cavities **125** to a portion of the surface **115** that does not include a particular region **113**. In the substantially rectangular surface **115** as shown in FIGS. **15a** and **15b**, one elongated vertical conductor **242** preferably corresponds to the left most column of cavities **125** and a second elongated vertical conductor **242** preferably corresponds to the right most column of cavities **125** and both preferably extend from the bottom corners of the rectangle to the upper corners of the rectangle, preferably forming a bracket around a substantially large portion of the surface **115**. The non-array horizontal

conductor **244** is preferably of the same conductor type as the horizontal array conductors **246** and is preferably located at a portion of the surface that does not include a particular region **113**. In the substantially rectangular surface **115** as shown in FIGS. **15a** and **15b**, the non-array horizontal conductor **244** preferably extends from the two side corners of the rectangle, preferably cooperating with the horizontal array conductor **246c** corresponding with the bottom most row of cavities **125** to form a bracket around a substantially large portion of the surface **115**. In other words, the elongated vertical conductors **242**, the non-array horizontal conductor **243**, and the horizontal array conductor **246c** corresponding to the bottom most row of the cavities **125** may resemble the conductors of the first example of the first sensor portion **140a** of the first preferred embodiment. Alternatively, an additional non-array horizontal conductor **244** may be used instead of the horizontal array conductor **246** corresponding to the bottom most row of the cavities **125** to form a bracket around a substantially large portion of the surface **115**. Alternatively, the elongated vertical conductors **242** and non-array horizontal conductor **244** may be arranged diagonally, in a cross pattern, or any other suitable orientation. The elongated vertical conductors **242** and non-array horizontal conductor **244** may also be of any other suitable shape (for example, the conductors may resemble a sine wave), size, or geometry. For example, the portion of the elongated vertical conductor **242** that corresponds to a particular region **113** may be of the same conductor type and/or geometry as the vertical array conductors **248** while a second portion of the elongated vertical conductor **242** that corresponds to a portion of the surface **115** that does not include a particular region **113** may be of a different conductor type and/or geometry. However, any other suitable material or arrangement of the horizontal and vertical array conductors **246** and **248**, elongated vertical conductor **242**, and non-array horizontal conductor **244** may be used.

[0036] Though the sensing system of the second preferred embodiment is described in the substantially rectangular surface **115** as shown in the FIGURES, the sensing system may be accommodated to any other suitable geometry of the surface **115** (for example, circular or octagonal) and may also be accommodated to any suitable type of surface plane (for example, substantially flat or curved). Additionally, the particular regions **113** may be arranged in any suitable pattern. The particular regions **113** may also occupy a substantial portion of the surface **115**. The sensing system of this variation may utilize a second horizontal array conductor **246** to function as the non-array horizontal conductor **244**. However, any other suitable arrangement of the sensing system may be used.

[0037] Similar to the first example of the first sensor portion **140a** of the first preferred embodiment, an electric field is provided by a conductor (for example, by means of a current through the conductor) and the electric field is detected by a second conductor such that disruptions and/or fluctuations caused by the presence of a finger in the electric field may also be detected. The second conductor may function to scan across the plurality of electric fields at a plurality of combinations of conductor pairs to detect a user input. Alternatively, the second conductor may act as a conductor that is connected to ground and cooperates with the first conductor to create an electric field that may be disrupted by the presence of a finger. In the second preferred embodiment, because a user input at the particular region **113** and the portions of the surface **115** that do not include a particular region **113** are preferably

detected simultaneously, the user interface system preferably also functions to discern between a user input at a particular region 113 and a user input at a portion of the surface 115 that does not include a particular region 113. This may be achieved using one of several variations of the capacitive sensor system 140.

[0038] In a first variation of the second preferred embodiment, currents are transmitted through each of the vertical array conductors 248 and the elongated vertical conductors 242 and the horizontal array conductors 246 and the non-array horizontal conductor 244 each function to detect the change in the electric fields generated by the vertical conductors 248 and 242. The electric signal that is transmitted through each of the vertical array conductors 248 is preferably at a first frequency and the electric signal that is transmitted through the elongated vertical conductors 242 is preferably at a second frequency, where the first and second frequencies are substantially different. In particular, the first and second frequencies are preferably not harmonics of each other and the frequency offset between the first and second frequencies is preferably not of the frequency of the electrical grid (for example, 60 hertz in North America) or some other frequency that is commonly present in electronic devices (for example, the refresh frequency in a liquid crystal display or LCD) to decrease interference. As a result, of the different frequencies transmitted through conductors that correspond to both the particular regions 113 and the portions of the surface 115 that do not include particular regions 113 and through conductors that correspond only to the particular regions 113, the electric field conductors may discern a user input at the particular region 113 from a user input elsewhere on the surface 115. An example of a method of discerning such user input is: 1. Detect the presence of a disruption in the electric field and/or capacitance of the first frequency, 2. Detect the presence of a disruption in the electric field and/or capacitance of the second frequency, 3. Compare the magnitude of the disruption of the electric field and/or capacitance in the two frequencies, and 4. Determine the location of the disruption relative to the particular region 113. This method is preferably carried out by a processor 160 through software and digital signal processing, but may alternatively be carried out through electrical circuitry, such as an FPGA. As shown in FIG. 15b, the user interface system preferably discerns between a user input at the particular region 113 (input A), at a portion of the surface 115 that does not include a particular region 113 but is in relative proximity to an elongated vertical conductor 242 (Input B), at a particular region 113 that is relatively central to the portion of the surface 115 that includes a group of particular regions 113 (Input C), at a portion of substantially central to a portion of the surface 115 that does not include a particular region 113 (Input D), and at a portion of the surface 115 that includes a particular region 113 but not at a particular region 113 (Input E). However, the user interface system preferably also functions to discern between any other suitable locations of user inputs. To save power and processing, the electric field of the second frequency may be employed only when the cavities 125 are in the expanded state. When the cavities 125 are retracted, the elongated vertical conductors 242a and 242b, the horizontal array conductor 246c and the non-array horizontal 244 may be employed using an electric field of the first frequency to determine the location of a user input while other conductors are inactive.

[0039] It is well known in the art that the human body acts as a dielectric and increases the capacitance between two conductors when placed within the electric field that between the conductors. The closer a part of the human body (for example, the finger of the user) is placed to a conductor, the overall larger the change in the capacitance between the conductors. The processor 160 may function to utilize this property of electric fields and capacitance to determine the location and the type of user input that is detected, as shown in FIG. 15c. When the user provides an Input A at the particular region 113, because of the proximity of the input to both elongated vertical conductor 242a and vertical array conductor 248a, the change in the electric field of the first frequency as received by horizontal array conductor 246a is substantially large and the change in the electric field of the second frequency as received by the horizontal array conductor 246a is also substantially large. Because both changes are substantially large, the user interface system may infer that the input is the portion of the surface 115 that includes a particular region 113 and will preferably primarily detecting changes in the electric field of the second frequency. To determine that the user input is located at the particular region 113, the change in the electric fields of the first and second frequency as felt by horizontal array conductors 246b and 246c may also be used to triangulate the location of the user input. Alternatively, the elongated vertical conductor 242a may come into contact with the horizontal array conductor 246a at the particular region 113 and provide a second signal to indicate that the user input is at the particular region 113. However, any other suitable method to determine that the user input is located at the particular region 113 may be used.

[0040] When the user provides an Input B, because of the proximity of the input to the elongated vertical conductor 242a and relative substantial distance from vertical array conductors 248a, b, and c, the change in the electric field of the first frequency is larger than the change in the electric field of the second frequency as received by any of the horizontal array conductors 246a, b, and c relative to an Input A or an Input C. The user interface system may determine that the user input is located at the portion of the surface 115 that does not include a particular region 113 and will preferably primarily detect changes in the electric field of the first frequency through use of the non-array horizontal conductor 244, elongated vertical conductors 242a and b, and horizontal array conductor 246c. The location of the Input B may be determined using methods known in the art for triangulating the location of a user input using the four conductors, for example, comparing the change in the electric field of the first frequency as received by the non-array horizontal conductor 244 and the horizontal array conductor 248c. The same methods may be applied to determining an Input D that is substantially central to the portion of the surface 115 that does not include a particular region 113.

[0041] When the user provides an Input C, similarly to when the user provides an Input A, the change in the electric field of the second frequency as felt by horizontal array conductor 246a is substantially large. However, the change in the electric field of the first frequency as felt by the horizontal array conductor 246a is smaller than in the case of Input A. The user interface system may infer that the use input is at the portion of the surface 115 that includes the particular regions, but is located at a location substantially far from the elongated vertical conductors 242a and b and will preferably switch to detecting only changes in the electric field of the second

frequency. To determine the location of the user input **113**, similar to the case of Input A, the change in the electric fields of the first and second frequency as felt by horizontal array conductors **246b** and **c** may also be used to triangulate the location of the user input. Alternatively, the vertical array conductor **248b** may come into contact with the horizontal array conductor **246a** at the particular region **113** and provide a second signal to indicate that the user input is at the particular region **113**. However, any other suitable method to determine that the user input is located at the particular region **113** may be used.

[0042] When the user provides an Input E, similarly to the case of Input C, the change in the electric field of the first frequency as felt by the horizontal array conductor **246a** is substantially small while the change in the electric field of the second frequency as felt by horizontal array conductor **246a** is substantially large and the user interface system preferably infers that the user input is located at a portion of the surface **115** that includes a particular region **113**. To determine the location of the Input E, the change in the electric fields of the first and/or second frequency as felt by horizontal array conductors **246b** and **c** may also be used to triangulate the location of the user input. For example, if the change in the electric field of the second frequency as felt by the horizontal array conductor **246a** is substantially equal than as felt by the horizontal array conductor **246b**, then the user interface system may infer that the user input is located in between a particular region **113** that corresponds to the horizontal array conductor **246a** and a particular region **113** that corresponds to the horizontal array conductor **246b**. Alternatively, in the variation of the user interface system where the vertical conductor and the horizontal conductor of a particular region **113** come into contact when a user input is provided at the particular region **113**, the absence of contact while a substantially large change in the electric field is detected may be used to determine that the user input is in close proximity to a particular region **113**. However, any other suitable method to determine the location of the Input E may be used.

[0043] Alternatively, the processor **160** may determine the location of the of the user input and, when the user input is detected to be at a particular region **113**, the processor **160** may primarily detect changes in the electric field of the second frequency. To determine that the user input is located at the particular region **113**, the change in the electric fields of the first and second frequency as detected by the sensing system may be used to triangulate the location of the user input. The processor **160** may function to evaluate the changes in the electric fields of the first and second frequencies independently to determine the location of the user input, but may alternatively evaluate changes in the electric fields of the first and second frequencies together, which may achieve a more accurate determination of user input location. Alternatively, the elongated vertical conductor **242a** may come into contact with the horizontal array conductor **246a** at the particular region **113** and provide a second signal to indicate that the user input is at the particular region **113**. However, any other suitable method to determine that the user input is located at the particular region **113** may be used.

[0044] In a second variation of the second preferred embodiment, the second sensor portion **140b** may include a first and second conductor at a particular region **113**, as described in U.S. application Ser. No. 12/497,622. As described above in the first preferred embodiment, the distance between the first and second conductor changes when a

user provides an input at the particular region to detect and receive a user input. The distance between first and second conductor at the particular region **113** preferably decreases as a user input is provided at the particular region **113** (for example, one that inwardly deforms the particular region **113**), but may alternatively increase. The first and second conductor may alternatively come into contact to substantially acutely detect a user input substantially proximal to the particular region **113**. The first and second conductor may alternatively come into contact to substantially acutely detect a user input substantially proximal to the particular region **113**. Because the second sensor portion **140b** includes conductors that are configured to detect a user input at the particular region **113**, the sensitivity for detection of a user input, determining the location of the user input, and/or detecting any other suitable characteristic of the user input may be increased. However, any other suitable arrangement of conductors may be used for the second sensor portion **140b** to provide the higher second sensitivity to a user input provided substantially proximal to the particular region **113**.

[0045] In a third variation of the second preferred embodiment, the sensor system may substantially similar or identical to that of the first sensor portion **140a** of the first preferred embodiment. In this variation, the sensor system functions to determine the location of the user input. However, because the sensor system as described in U.S. application Ser. No. 12/497,622 is not used, substantially more accurate details of user input (for example, speed of user input, direction of user input, pressure of user input, or the amount of inward deformation of the particular region **113**) may not be detected.

[0046] The sensor **140** of the preferred embodiments is preferably one of the variations and arrangements described above, but may alternatively be any other suitable variation or arrangement. For example, a current of a unique frequency may be transmitted through each electric field emitting conductor (elongated vertical conductors **242** and vertical array conductors **248**), resulting in a plurality of electric fields that are each of a different frequency, which may facilitate in determining the location of the user input. In a second example, the horizontal array conductors **246** and the non-array horizontal conductor **244** as the electric field emitters and the vertical array conductors **248** and the elongated vertical conductors **242** may function as the electric field receivers. In a third example, user inputs located at a particular region **113** may be detected by the a horizontal array conductor coming into contact with a vertical array conductor (or elongated vertical conductor) while user input located at a portion of the surface **115** that does not include a particular region **113** may be detected from disruptions in the electric field. However, any other suitable method that allows for user inputs both located at a portion of the surface **115** that includes a particular region **115** and at a portion of the surface **115** that does not include a particular region **115** to be detected simultaneously may be used. The sensor **140** may also function to detect the occurrence of multiple user inputs (commonly known as “multi-touch”), in various combinations: multiple user inputs, each at a different particular region **113**, each at various locations on the surface **115** that do not include a particular region **113**, or a combination of inputs at both the particular regions **113** and at locations on the surface **115** that do not include a particular region **113**.

[0047] In the user interface system **100** of the preferred embodiments, the fluid **112** may affect the electromagnetic fields that are generated within the sensor system **140**, for

example, the fluid itself may be conductive, the fluid may include suspensions or dispersions of particles with relevant electrical and optical properties, or the any other suitable type of fluid. For example, the fluid **112** may function as an electrical conductor or an electrical insulator that manipulates an electromagnetic field that passes through the fluid **112**. In this variation, the fluid **112** may be directed within the sheet **102** to provide desired manipulations of an electromagnetic field, for example, to increase the sensitivity of the sensor system **140** at particular portions and/or to decrease the sensitivity of the sensor system at another portion. Alternatively, the processor **160** may be configured to recognize the affect that the fluid **112** may have on the electromagnetic fields of the sensor **140** and to adjust the method of detecting a user touch when effects from the fluid **112** are detected. However, any other suitable use and/or accommodation to the effects of the fluid **112** on the electromagnetic fields of the sensor system **140** may be used.

[0048] As a person skilled in the art will recognize from the previous detailed description and from the figures and claims,

modifications and changes can be made to the preferred embodiments of the invention without departing from the scope of this invention defined in the following claims.

We claim:

1. A user interface system, comprising:
 - a sheet that defines a surface and at least partially defines a fluid vessel arranged underneath the surface;
 - a volume of fluid within the fluid vessel;
 - a displacement device that influences the volume of the fluid within the fluid vessel to expand and contract at least a portion of the fluid vessel, thereby deforming a particular region of the surface; and
 - a sensor system configured to receive a user input on the surface with a first sensitivity and configured to receive a user input substantially proximal to the particular region of the surface at with second sensitivity higher than the first sensitivity.

* * * * *