

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
20 January 2005 (20.01.2005)

PCT

(10) International Publication Number
WO 2005/005537 A1

- (51) International Patent Classification⁷: **C08L 27/06**, C08K 5/06, C09D 127/06
- (21) International Application Number: PCT/EP2004/051421
- (22) International Filing Date: 8 July 2004 (08.07.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 103 31 520.9 11 July 2003 (11.07.2003) DE
- (71) Applicant (for all designated States except US): **HUNTS-MAN ADVANCED MATERIALS (SWITZERLAND) GMBH** [CH/CH]; Klybeckstrasse 200, CH-4057 Basel (CH).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **KRUSE, Alfred** [DE/DE]; Hinter Holtein, 44227 Dortmund (DE). **BROLL, Christa** [DE/DE]; Brechenstrasse 8, 44575 Castrop-Rauxel (DE). **VOLLE, Jörg** [DE/DE]; Luisenstrasse 37a, 59379 Selm-Bork (DE).
- (74) Agents: **MAUÉ, Paul Georg** et al.; Solvias AG, Patents, WKL-402.3.04, Klybeckstrasse 191, CH-4002 Basel (CH).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
- with international search report
 - before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



WO 2005/005537 A1

(54) Title: ADHESION PROMOTERS FOR PLASTISOLS

(57) Abstract: The invention relates to adhesion promoters for plastisols based on polyaminoamides, characterized in that the adhesion promoter comprises not only a polyaminoamide but also at least 10% by weight, and at most 60% by weight, based on the total amount of adhesion promoter, of ethyldiglycol (ethyl Carbitol), and to a process for the production of coatings and adhesive bonds for materials, and also to plastisols in which these adhesion promoters are used concomitantly.

Adhesion promoters for plastisols

The invention relates to adhesion promoters based on polyaminoamides, comprising ethyldiglycol, and also to the use of these adhesion promoters for improving adhesion of PVC plastisols.

Plastisols are widely used for protecting metallic surfaces from corrosion. In particular in the automotive sector, plastisols are used for the waterproofing, bonding and sealing of seams and joints, and for protecting external surfaces, such as underbodies and sills.

These applications mostly use plastisols based on PVC polymers or on PVC copolymers. These plastisols are composed of fine polymer particles which have been dispersed in a non-volatile plasticizer. At room temperature, the polymer particles are insoluble in the liquid phase. At a higher temperature (gelling temperature), the polymer particles dissolve in the plasticizer. On cooling, the homogeneous solution hardens to give a flexible or rigid coating. The main methods used to apply these coatings to the materials to be protected are brushing, rolling or spraying.

The formulation of plasticized polyvinyl chloride coating compositions (plastisols), and their preparation and use is extensively described in: Krekeler / Wick, Kunststoff-Handbuch [Plastics Handbook] (1963), Volume II, Part 1, pp. 396 ff.

A significant criterion for the quality of plastisols applied in this way is their adhesion to the coated material. Relatively low adhesion of the protective layer increases the risk of penetration of aggressive fluids. For example, water can migrate under the coating and corrode the metal. This becomes increasingly possible as the adhesion of the protective film to the metal becomes lower. To increase the adhesion of these coatings, therefore, industry adds adhesion-improving additives to the plasticized polyvinyl chloride. The function of the adhesion promoters is to bring about lasting adhesion to the surfaces of commonly encountered materials, such as non-degreased untreated steel, galvanised metal sheet or tin-coated metal sheet, electrocoated metal sheet, etc.

There are previously-developed adhesion promoters for PVC plastisols. Examples of these adhesion promoters are polyamines, epoxy resins, capped isocyanates, organofunctional

- 2 -

silanes, and esters of acrylic or methacrylic acid.

In most cases, the adhesion promoters used comprise polyaminoamides containing imidazoline groups. These give good adhesion to the substrate, even if the concentrations in the plastisol are relatively small. These polyaminoamides are prepared from what are known as polymerized fatty acids and an excess of polyethylene polyamines, by polycondensation. The expression polymerized fatty acids encompasses polymerized fatty acids prepared from unsaturated, naturally occurring or synthetic, monobasic, aliphatic acids having from 12 to 22 carbon atoms, preferably 18 carbon atoms. The fatty acids may be polymerized by a well-known process, for example as in DE 25 06 211 A1. These adhesion promoters are described by way of example in DE 26 54 871 A1 and in DE 32 01 265 A1. DE 44 00 509 A1 describes plastisol compositions in which the addition of secondary adhesion promoters in the form of trihydric or higher-functionality aliphatic alcohols and/or alkanolamines, in addition to the conventional adhesion promoters based on polyaminoamides, to PVC plastisols improves their adhesion properties, in particular on sheets coated by a cathaphoretic process. In the experimental section of that specification, glycerol is used as secondary adhesion promoter. However, these secondary adhesion promoters have to be added in addition to the primary polyaminoamide adhesion promoters, the amount of which incorporated into the plastisol is usually about 1% by weight (based on the total amount of plastisol). The viscosity of the polyaminoamides used is moreover generally very high, and incorporation into the plastisol is therefore rendered difficult.

In order to lower the viscosity and thus provide good processability of the adhesion promoter, e.g. for the mixing of the adhesion promoter into the plastisol, and also to lower the price of these adhesion promoters, the adhesion promoters, which are generally of very high viscosity, are often formulated with plasticizers. However, plasticizers have an adverse effect on the adhesion of the PVC plastisol to the substrate in most cases. Plasticizers often used are phthalic esters, e.g. dibutyl phthalate, dioctyl phthalate or dinonyl phthalate. One adverse effect which has been observed is their low effectiveness in diluting the adhesion promoter. Relatively high amounts of these phthalates have to be used if sufficient processability is to be provided.

However, larger amounts of these plasticizers have an adverse effect on adhesion to the substrate. In addition, dialkyl phthalates used as plasticizers in adhesion promoters bring about a rise in viscosity of the adhesion promoter over the course of time, this being

- 3 -

explicable via cleavage of the ester and reaction with the free amine groups in the polyaminoamide/imidazoline. The usefulness of these adhesion promoters is therefore subject to a time limit, because after some time incompatibility arises, and finally gelling occurs. In addition, the toxicological risks posed by the dialkyl phthalates class of product have recently caused their use to be criticized. DE 694 02 959 T2 claims a process for the preparation of specific polyamide resins which, according to Claim 9, comprise dioctyl phthalate, benzyl alcohol, and diisopropyl naphthalene as plasticizers. EP 0 658 574 A1 describes the use of amidoamines, imidoamines and ester amines based on

- a) copolymers of monounsaturated carboxylic acids and ethylenically unsaturated compounds and
- b) polyamines as adhesion promoters, likewise using the abovementioned compounds as plasticizers. However, as the proportion in the adhesion promoter rises, the use of these plasticizers again leads to impairment of adhesion of the plastisol to the substrate.

Finally, EP 0 263 053 A2 describes plastisol compositions comprising a polyaminoamide adhesion promoter and a primary plasticizer, characterized in that a non-ionic secondary plasticizer in the form of solvents is added to the adhesion promoter and the primary plasticizer, and this composition composed of adhesion promoter and of plasticizers is separately mixed before it is also added to the PVC polymer and additives. The solvents used, mention being made of diethylene glycol monoethyl ether (ethyldiglycol) inter alia, are added at from 10 to 70 parts by weight per 100 parts by weight of PVC polymer.

It is an object of the present invention to provide an additive which is intended for polyaminoamide-based adhesion promoters in PVC plastisols and which is compatible with the polyaminoamide, has good effectiveness in diluting the adhesion promoter, and is stable with respect to viscosity, and, finally, has minimum effect on the adhesion of the PVC plastisols to the substrate.

According to the invention, this object is achieved by using adhesion promoters based on polyaminoamides which comprise not only a polyaminoamide but also ethyldiglycol (ethyl Carbitol). The proportion of ethyldiglycol in the polyaminoamide-based adhesion promoter should be at least 10% by weight and at most 60% by weight, preferably from 25 to 55% by weight, particularly preferably from 40 to 50% by weight.

The polyaminoamides used concomitantly according to the invention are obtainable from

- 4 -

polymerized fatty acids and, where appropriate, mono- and/or dicarboxylic acids and amine compounds, in particular polyalkylene polyamines via polycondensation, as described below.

The term polymerized fatty acids encompasses polymerized fatty acids which are prepared from unsaturated, natural or synthetic, monobasic, aliphatic acids having from 12 to 22 carbon atoms, preferably 18 carbon atoms. The fatty acids may be polymerized by a well-known process (see, for example, processes in DE 25 06 211 A1).

Polymerized fatty acids whose use is preferred are the commercially available products whose composition is approximately as follows: monomeric acids: from 0.1 to 10%, dimeric acids: from 50 to 98%, trimeric and higher acids: from 1 to 70%.

Dicarboxylic acids which may be used: aliphatic and/or cycloaliphatic, straight-chain or branched acids which have not more than 20 carbon atoms, e.g.: oxalic acid, malonic acid, succinic acid, glutaric acid, adipic acid, pimelic acid, suberic acid, azelaic acid, sebacic acid, trimethyladipic acid, maleic acid and fumaric acid, hexahydrophthalic acid, tetrahydrophthalic acid; or aromatic dicarboxylic acids, e.g. phthalic acid, isophthalic acid, terephthalic acid.

It is preferable to use aliphatic and/or aromatic dicarboxylic acids.

The dicarboxylic acids may be used individually or in a mixture.

These dicarboxylic acids are preferably used in a mixture with the polymerized fatty acids described above. Small amounts of tricarboxylic acids, e.g. trimesic acid, may also be added.

For the condensation process it is preferable to use from 0.5 to 1.0 equivalent of the polymerized fatty acid, from 0.0 to 0.5 equivalent of the dicarboxylic acid, and from 0.2 to 1 mol of polyalkylene polyamine, the total of the equivalents of the polymerized fatty acid and of the dicarboxylic acid here being 1 equivalent.

Preferred polyalkylene polyamines for preparing the polyaminoamides are polyethylene polyamines. Particular preference is given here to polyethylene polyamines having 4 or more nitrogen atoms in the molecule.

- 5 -

The polyaminoamides can be prepared via condensation of the amine compounds with the acid compounds at temperatures up to 280°C. Imidazoline groups also form here. The imidazoline groups form at relatively high temperatures of from about 160 to 280°C via intramolecular cyclization with elimination of water from the amide groups. Adhesion promoters of this type are commercially available from Huntsman with the trade mark Euretek.

Surprisingly, ethyldiglycol has no adverse effect on the adhesion of the PVC plastisol to the substrate, even in these very large amounts of from 40 to 50% by weight in the adhesion promoter. It would have been expected that the adhesion of the PVC plastisols to the substrate would fall off as the amount of additive in the adhesion promoter rises, because the proportion of the adhesion promoter itself becomes smaller. However, even when the proportion of ethyldiglycol in the adhesion promoter is 50%, there is no, or at least hardly any, effect on the adhesion of the PVC plastisol to the substrate. The viscosity of the adhesion promoters is low, and the adhesion promoter is stable in terms of viscosity.

This invention therefore provides adhesion promoters for PVC plastisols, characterized in that they comprise not only a polyaminoamide but also ethyldiglycol, the amount of ethyldiglycol present in the adhesion promoter, based on the total amount of adhesion promoter, being at least 10% by weight and at most 60% by weight, preferably from 25 to 55% by weight, particularly preferably from 40 to 50% by weight.

The invention also provides a process for the production of coatings and adhesive bonds for materials by applying plastisols based on fine-particle polyvinyl chloride or, respectively, vinyl chloride copolymers, which comprise conventional fillers, additives, plasticizers and adhesion promoters, characterized in that use is made of adhesion promoters which comprise not only a polyaminoamide but also ethyldiglycol in amounts, based on the total amount of adhesion promoter, of at least 10% by weight and at most 60% by weight, preferably from 25 to 55% by weight, particularly preferably from 40 to 50% by weight.

The adhesion promoters according to the invention are added in proportions of from 0.3 to 5% by weight, preferably from 0.5 to 2% by weight, particularly preferably 1% by weight, based on the weight of the plastisol. The proportion of ethyldiglycol in the entire plastisol is thus about 0.03-3%, preferably about 0.5%. After addition of the adhesion promoters of the

- 6 -

invention, the plastisol composition is homogenized, and the plastisols thus prepared are stoved on the material at temperatures of 90°C or above, preferably at from 120°C to 160°C.

The invention also provides plastisols for the production of coatings on materials, comprising fine-particle polyvinyl chloride or, respectively, vinyl chloride copolymers, conventional plasticizers, fillers, additives and adhesion promoters, characterized in that an adhesion promoter of the invention is present.

- 7 -

Examples

In examples 2 to 4 below, the polyaminoamide adhesion promoter Euretek 563 from example 1 is heated with stirring to about 100°C and the appropriate additives are added, and the mixture is then homogenized.

Example 1 (comparative example):

Euretek[®] 563 (commercial adhesion promoter based on a polyaminoamide from the company Vantico AG).

Example 2 (comparative example): 60% Euretek 563; 40% of dioctyl phthalate.

Example 3 : 60% Euretek 563; 40% of ethyldiglycol.

Example 4 (comparative example): 80% Euretek 563; 20% of glycerol.

Preparation of plastisols:

1% of the abovementioned polyaminoamide of examples 1 to 4, based on the entire mixture, is added as adhesion promoter to a plastisol composed of: 35% of diisononyl phthalate; 25% of paste PVC (e.g. Solvic[®] 347 MB); 16.0% of coated chalk (Socal[®] 312); 16.5% of naturally occurring chalk (Juraperle); 2.0% of CaO; 0.2% of ZnO and 4.3% of Exsol[®] 80.

Of course, the adhesion promoters may also be added to conventional plastisol formulations other than those given above in order to obtain the self-adhesive plastisols of the invention.

The adhesion achievable using the plastisols of the invention is determined manually. For this, use is made of Cathoguard 400 CEC sheets from the company BASF. Dimensions of adherends 25 x 100 mm.

Method:

A spatula is used to apply a strip of the PVC plastisol, about 1.5 cm in width and about 5 cm in length, to the CEC strip, and a doctor is used to spread the plastisol to give a test strip of width 1.5 cm with a thickness of 1.5 mm. The test specimen is placed in the temperature-controlled drying cabinet and stoved at 140°C for 30 minutes. After stoving, the test specimen is removed from the drying cabinet. After cooling (for at least 2 hours), the adhesion test can be carried out. For this, a knife is used to make an incision to a width of

about 0.5 cm in both sides of the test strip. The test strip is then tested manually for peelability.

The following classification system is used for assessment:

—	No adhesion at all
O	Strip can easily be peeled; slight film of plastisol remaining on the CEC layer
⊕	Strip difficult to peel; slight film of plastisol remaining on the CEC layer
+	Strip difficult to peel and breaks on peeling; significant film of plastisol remaining on the CEC layer
++	Strip cannot be peeled

The results of the measurements are listed in table 1 below.

Table 1:

Example	Viscosity ^{*)} at 25°C [mPa•s]	Viscosity at 75°C [mPa•s]	Manual Adhesion	Viscosity at 75°C [mPa•s] after storage 30 days/50°C	Appearance after storage 30 days/50°C
1	n.m. ^{*)}	16500	++	16600	clear
2	22300	1300	+	6000	cloudy/ incompatible
3	4300	300	++	305	clear
4	n.m. ^{*)}	12000	⊕	12600	clear

^{*)} not measurable at 25°C (viscosity too high). ^{**)} The viscosities were measured using a VT 550 Haake rotary viscosimeter in accordance with the manufacturer's instructions.

Interpretation of results:

As can be seen from the table, the adhesion promoter of the invention (example 3) has very low viscosity and is therefore easy to process. In contrast with comparative example 2, the adhesion promoter of the invention is storage-stable, even after storage at relatively high temperatures, and consequently remains available for use by the user after a prolonged storage time. Surprisingly, use of the inventive adhesion promoters with 40% content of ethyldiglycol, based on the total amount, gives excellent adhesion of the plastisols to the substrate (example 3). Use of the adhesion promoter from comparative examples 2, and in

- 9 -

particular 4, gives adhesion which is in some cases markedly reduced. The adhesion of the plastisols to the substrates would also have been expected to fall when ethyldiglycol is used in the adhesion promoter, as the proportion of ethyldiglycol rises. Surprisingly, adhesion to the substrate is not reduced and remains good. This result was not foreseeable.

- 10 -

Patent Claims

- 1) Adhesion promoter for plastisols, characterized in that the adhesion promoter comprises not only a polyaminoamide but also at least 10% by weight, and at most 60% by weight, based on the total amount of adhesion promoter, of ethyldiglycol (ethyl Carbitol).
- 2) Adhesion promoter according to Claim 1, characterized in that the proportion of ethyldiglycol is from 25 to 55% by weight, preferably from 40 to 50% by weight.
- 3) Plastisol composition, comprising fine-particle polyvinyl chloride or, respectively, vinyl chloride copolymers, and conventional plasticizers, fillers, additives and adhesion promoters, characterized in that it comprises an adhesion promoter according to either of Claims 1 and 2.
- 4) Plastisol composition according to Claim 3, characterized in that the adhesion promoter is added in proportions of from 0.3 to 5% by weight, based on the weight of the plastisol.
- 5) Plastisol composition according to Claim 4, characterized in that the adhesion promoter is added in proportions of from 0.5 to 2% by weight, preferably 1% by weight, based on the weight of the plastisol.
- 6) Process for producing coatings and adhesive bonds for materials, characterized in that use is made of a plastisol composition according to any of Claims 3 to 5.
- 7) Process according to Claim 6, characterized in that the adhesion promoter is added to the plastisol composition, and the mixture is homogenized, and the plastisols thus prepared are stoved on the material at temperatures greater than or equal to 90°C, preferably from 120°C to 160°C.

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP2004/051421

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C08L27/06 C08K5/06 C09D127/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C08L C08K C09D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 263 053 A (SHEREX CHEM) 6 April 1988 (1988-04-06) page 3, line 21 - line 26 page 3, line 49 - line 54 examples; tables 10,12,15 claims 1,2,5,8	1-3,6
A	EP 0 171 850 A (CHEM PLAST SPA) 19 February 1986 (1986-02-19) the whole document claims 1,9	1,6

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

° Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

18 November 2004

Date of mailing of the international search report

25/11/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Engel, S

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP2004/051421

Patent document cited in search report		Publication date	Patent family member(s)	Publication date			
EP 0263053	A	06-04-1988	US 4851464 A	25-07-1989			
			AT 89021 T	15-05-1993			
			AU 595907 B2	12-04-1990			
			AU 7620487 A	10-03-1988			
			CA 1323131 C	12-10-1993			
			DE 3785719 D1	09-06-1993			
			EP 0263053 A2	06-04-1988			
			JP 63068652 A	28-03-1988			
			KR 9601976 B1	08-02-1996			
			US 4824700 A	25-04-1989			
			ZA 8705626 A	09-02-1988			
			EP 0171850	A	19-02-1986	IT 1180214 B	23-09-1987
						AT 68007 T	15-10-1991
DE 3584277 D1	07-11-1991						
EP 0171850 A1	19-02-1986						
ES 8802431 A1	16-09-1988						
JP 2025678 C	26-02-1996						
JP 6021265 B	23-03-1994						
JP 61053347 A	17-03-1986						
US 4717746 A	05-01-1988						