



(51) International Patent Classification:
A61C 7/08 (2006.01) *B33Y 10/00* (2015.01)

(21) International Application Number:
PCT/IB2016/000970

(22) International Filing Date:
7 July 2016 (07.07.2016)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
62/189,380 7 July 2015 (07.07.2015) US
15/201,958 5 July 2016 (05.07.2016) US

(71) Applicant: **ALIGN TECHNOLOGY, INC.** [US/US];
2560 Orchard Parkway, San Jose, CA 95131 (US).

(72) Inventors: **CHEN, Yan**; 10461 Pineville Ave., Cupertino, CA 95014 (US). **LI, Chunhua**; 19688 Vicksburg Drive, Cupertino, CA 95014 (US). **KAZA, Srinivas**; 120 Gough Street, #15F, San Francisco, CA 94109 (US). **CRAMER, Neil, Brian**; Boulder, CO (US). **BERARD, Mary, Catherine**; Longmont, CO (US).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,

[Continued on next page]

(54) Title: DENTAL MATERIALS USING THERMOSET POLYMERS




Fig. 1A

(57) Abstract: Provided herein are crosslinked polymers useful in orthodontic appliances and light polymerizable liquid compositions and formulations useful for making crosslinked polymers. Also provided are methods of making an orthodontic appliance comprising a cross-linked polymer formed by a direct fabrication technique.





SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,

DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT,
LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE,
SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

DENTAL MATERIALS USING THERMOSET POLYMERS

This application claims the benefit of U. S. Provisional Application No. 62/189,380, filed July 7, 2015 which is hereby incorporated by reference in its entirety.

BACKGROUND

Orthodontic procedures typically involve repositioning a patient's teeth to a desired arrangement in order to correct malocclusions and/or improve aesthetics. To achieve these objectives, orthodontic appliances such as braces, retainers, shell aligners, and the like can be applied to the patient's teeth by an orthodontic practitioner. The appliance is configured to exert force on one or more teeth in order to effect desired tooth movements. The application of force can be periodically adjusted by the practitioner (e.g., by altering the appliance or using different types of appliances) in order to incrementally reposition the teeth to a desired arrangement.

Fig. 1A illustrates an exemplary orthodontic appliance **106** and jaw **104** including a patient's teeth, as presented in US Patent Application Publication 2015/0004553, the disclosure of which is incorporated herein by reference in its entirety. Fig. 1B illustrates orthodontic appliance cross-section **112** as taken along line **1B-1B** of Fig. 1A, while Fig. 1C illustrates orthodontic appliance cross-section **118** as taken along line **1C-1C** of Fig. 1A. The orthodontic appliance **106** may be designed to fit over a number of teeth present in an upper or lower jaw. As illustrated, the orthodontic appliance has a U-shaped cross-section to form one or more cavities for placement of a patient's teeth therein.

BRIEF SUMMARY

Provided herein are crosslinked polymers useful in orthodontic appliances and light polymerizable liquid compositions and formulations useful for making crosslinked polymers. Also provided are methods of making an orthodontic appliance comprising a cross-linked polymer formed by a direct fabrication technique. Direct fabrication can provide various advantages compared to other

technique. Direct fabrication can provide various advantages compared to other manufacturing approaches. For instance, in contrast to indirect fabrication, direct fabrication permits production of an appliance without utilizing any molds or templates for shaping the appliance, thus reducing the number of manufacturing steps involved and improving the resolution and accuracy of the final appliance geometry. Additionally, direct fabrication permits precise control over the three-dimensional geometry of the appliance, such as the appliance thickness.

In many embodiments, direct fabrication is used to produce appliance geometries that would be difficult to create using alternative manufacturing techniques, such as appliances with very small or fine features, complex geometric shapes, undercuts, interproximal structures, shells with variable thicknesses, or internal structures (e.g., for improving strength with reduced weight and material usage). For instance, in many embodiments, the direct fabrication approaches herein permit fabrication of an orthodontic appliance with feature sizes of less than or equal to about 5 μm , or within a range from about 5 μm to about 50 μm , or within a range from about 20 μm to about 50 μm . The direct fabrication techniques described herein can be used to produce appliances with substantially isotropic material properties, e.g., substantially the same or similar strengths along all directions. In some embodiments, the direct fabrication approaches herein permit production of an orthodontic appliance with a strength that varies by no more than about 25%, about 20%, about 15%, about 10%, about 5%, about 1%, or about 0.5% along all directions. Additionally, the direct fabrication approaches herein can be used to produce orthodontic appliances at a faster speed compared to other manufacturing techniques. In some embodiments, the direct fabrication approaches herein allow for production of an orthodontic appliance in a time interval less than or equal to about 1 hour, about 30 minutes, about 25 minutes, about 20 minutes, about 15 minutes, about 10 minutes, about 5 minutes, about 4 minutes, about 3 minutes, about 2 minutes, about 1 minutes, or about 30 seconds. Such manufacturing speeds allow for rapid “chair-side” production of customized appliances, e.g., during a routine appointment or checkup.

Orthodontic appliances using the materials and method described herein include, but are not limited to, braces, retainers and shell aligners. The appliances can have different materials/formulation, shapes, and/or size/thickness from one area to another area with different force design in mind using multiple materials

5 formulations. In embodiments, a multi-material direct fabrication method can involve forming an object from multiple materials in a plurality of sequential manufacturing steps. For instance, a first portion of the object (e.g., an interior layer) can be formed from a first material in accordance with any of the direct fabrication methods described herein, then a second portion of the object (e.g., an exterior layer) can be

10 formed from a second material in accordance with methods herein, and so on, until the entirety of the object has been formed. In further embodiments, a multi-tip extrusion apparatus can be used to selectively dispense multiple types of materials from distinct material supply sources in order to fabricate an object from a plurality of different materials. Such methods are described in U.S. Patent No. 6,749,414, the

15 disclosure of which is incorporated herein by reference in its entirety.

In embodiments, the orthodontic appliance is a tooth position adjustment dental appliance having cavities shaped to receive and resiliently reposition teeth from a first arrangement to a second arrangement. For example, a dental appliance

20 can include a shell formed of cross-linked polymer materials and having a number of cavities to receive one or more teeth. In some embodiments, the shell is formed of thermoset polymer materials. In one or more apparatus embodiments, the dental appliance is an aligner (e.g., shell) having a number of cavities to receive one or more teeth. In embodiments, the aligner is one of a series of aligners corresponding

25 to intermediate steps of an orthodontic treatment where the number of cavities are arranged to reposition the one or more teeth from a first configuration to a successive configuration, and the aligner is fabricated from material that is irreversibly cured to irreversibly link molecules into a rigid three dimensional structure. A dental

30 appliance (e.g., a dental positioning appliance such as an aligner, a tray for delivery of chemicals in proximity to the teeth or gums, etc.) can include a number of cavities for receiving one or more corresponding teeth. In various embodiments, the cavities

can correspond to one, or multiple, teeth, implants, and/or other features of a patient's jaw.

5 In embodiments, the crosslinked polymer comprises crosslinks formed by covalent interactions. In further embodiments, the crosslinked polymer also comprises crosslinks formed by non-covalent interactions. In embodiments, the crosslinked polymer is a thermoset polymer. In embodiments, the crosslinked polymer forms a crosslinked network.

10 In embodiments, the crosslinked polymer is selected from the group consisting of polyurethanes, (meth)acrylates, epoxies and copolymers thereof. As used herein, (meth)acrylate is shorthand for acrylate and/or methacrylate and a polyurethane polymer or oligomer includes at least one urethane linkage, also known as a carbamate linkage. In a further embodiment, the crosslinked polymer is an
15 epoxy acrylate, a modified epoxy acrylate, epoxy methacrylate or a urethane acrylate. In embodiments, the crosslinked polymer is a copolymer. In embodiments, the crosslinked polymer is biocompatible. In different embodiments, the crosslinked polymer is transparent, translucent or opaque. Transparent crosslinked polymers may be clear or tinted to achieve various colors. In some
20 embodiments the crosslinked polymer is characterized by a transmittance equal to or greater than 80% for light having a wavelength in the visible region.

In an aspect the crosslinked polymer has a tensile strength at yield of greater than 4000 psi (27.6 MPa) or from 20 MPa to 55 MPa. In embodiments, the tensile
25 modulus is greater than 150,000 psi (1034 MPa) or from 800 MPa to 2000 MPa. In further embodiments, the elongation at yield is greater than 4%, greater than 4% and less than or equal to 25%, or greater than 4% and less than or equal to 10%. In additional embodiments, the elongation at break is greater than 30%, greater than 40%, greater than 40% and less than or equal to 250% or greater than 40% and less
30 than or equal to 80%. Tensile and elongation properties may be measured per ASTM D 638--14. The water absorption may be less than one percent. In an embodiment, the glass transition temperature is greater than 90 °C and the deflection

temperature is greater than 90 °C. In further embodiments, the glass transition temperature is from 38 °C to 90 °C or from 40 °C to less than 90 °C. In embodiments, the amount of stress relaxation at 37°C at 24 hours and 100% relative humidity is such that the remaining load is greater than 80% of the initial load, greater than 50% of the initial load, greater than 25% of the initial load or greater than 10% of the initial load. In embodiments, the amount of stress relaxation at 37°C at 14 days and 100% relative humidity is such that the remaining load is greater than 50% of the initial load, greater than 25% of the initial load or greater than 10% of the initial load. In further embodiments, the stress relaxation at 37°C at 24 hours and 100% relative humidity is such that the remaining load is greater than 80% of the initial load (stress relaxation less than 20%) and at 14 days at 100% relative humidity the remaining load is greater than 50% of the initial load (stress relaxation less than 50%). In embodiments, the dimensional stability of the crosslinked polymer is such an orthodontic appliance including the crosslinked polymer meets dimensional specifications when placed in an oral environment, thereby maintaining fit of the appliance for the patient. In embodiments, the crosslinked polymer is used to form a shell of a tooth positioning aligner; the shell may span the entire arch.

In some aspects, a crosslinked polymer is provided having a tensile modulus, a tensile strength at yield, an elongation at yield and an elongation at break as described above. In some embodiments, a crosslinked polymer is provided having a tensile modulus from 800 MPa to 2000 MPa, a tensile strength at yield of 20 MPa to 55 MPa, an elongation at yield greater than 4% and an elongation at break greater than 30%.

In an aspect, the crosslinked polymers provided herein are formed by polymerization of a light polymerizable liquid composition or formulation comprising at least two polymerizable components. In a further aspect, the light polymerizable liquid composition comprises three polymerizable components. In embodiments, the light polymerizable liquid composition further comprises a photoinitiator. In further embodiments, the light polymerizable liquid composition

further comprises a radical stabilizer, an inhibitor, a filler or a combination thereof. Suitable fillers include soluble filler and inorganic fillers.

In an aspect, a polymerizable component comprises at least one
5 polymerizable group. Polymerizable groups include, but are not limited to, vinyl groups, ally groups, acrylate groups, methacrylate groups, acrylamide groups, epoxy groups and oxetanyl groups. As used herein, when a polymerizable component is stated to be a monomer or oligomer, a plurality of monomer or oligomer molecules of the specified type is intended to be included. A polymerizable component, such
10 as a monomer or oligomer, may be characterized by the polymerizable groups of the monomer, by other functional groups of the monomer, or a combination thereof. As used herein, vinyl monomers or oligomers are monomers or oligomers including a vinyl group and include, but are not limited to, monomers or oligomers having acrylate, methacrylate or acrylamide groups. In some embodiments, vinyl monomers
15 or oligomers not including meth (acrylate) groups are characterized as non-(meth) acrylate monomers or oligomers.

In embodiments, the formulation comprises at least one urethane (meth) acrylate prepolymer, monomer or oligomer. For example, the urethane (meth)acrylate prepolymer, monomer or oligomer is selected from the group
20 consisting of Exothane 108, Exothane 10, isophorone urethane dimethacrylate (IPDI-UDMA), CN991, CN9782, CN3211, CN9782, CN9009, PU3201NT and combinations thereof. In some embodiments, the urethane (meth)acrylate prepolymer, monomer or oligomer is an aliphatic urethane dimethacrylate. In other embodiments, the (meth)acrylate prepolymer, monomer or oligomer is an aliphatic
25 urethane diacrylate. In further embodiments, the urethane (meth) acrylate prepolymer or oligomer has a viscosity of from 100,000 centipoise (cP) to 1,000,000 cP as measured at 25°C, from 10,000 cP to 50,000 cP as measured at 60°C, from 10,000 centipoise (cP) to 50,000 cP as measured at 25°C or from 500 cP to 50,000 cP as measured at 60°C.

30

In additional embodiments, the formulation further comprises at least one vinyl monomer. For example, suitable vinyl monomers are selected from the group

consisting of SR833S, SR368D, β -carboxyethylacrylate (CEA), and 1-vinyl-2-pyrrolidinone (NVP), M1130 (trimethyl cyclohexyl acrylate TMCHA), M151 (tetrahydrofurfuryl methacrylate, THFMA), isobornyl acrylate (IBOA), isobornyl methacrylate (IBOMA) and combinations thereof. In a further embodiment, the vinyl monomer is 1,3,5-Triallyl-1,3,5-triazine-2,4,6(1*H*,3*H*,5*H*)-trione (TATATO). TATATO may be used in combination with a thiol monomer. Exothane 108, Exothane 10, IPDI-UDMA or UDMA-IPDI (Esstech, Inc., identified as Isophorone Urethane dimethacrylate) are available from Esstech, Inc. (Essington, PA). CN991, CN9782 and CN3211, SR833S (also identified as 833 S, Tricyclodecane dimethanol diacrylate), SR368D (also identified as SR 368 D, Tris (2-hydroxy ethyl) isocyanurate triacrylate), CN9782, CN9009 and CN3211 are available from Sartomer (Exton, PA). PU3201NT, M1130, M151, IBOA, and IBOMA are available from Miwon (Anyang, South Korea). See also Table 3.

15 In embodiments, the vinyl monomer is a (meth)acrylate monomer which does not include a urethane linkage. Exemplary (meth)acrylate monomers which do not include a urethane linkage have a viscosity from 1 to 400 cP at 25 °C. In embodiments, the number of (meth)acrylate functional groups is from 1 to 3.

In additional embodiments, the vinyl monomer does not include a urethane linkage or (meth)acrylate functional groups. Exemplary vinyl monomers which do not include a urethane linkage or (meth)acrylate functional groups include vinyl functional groups or allyl functional groups. In embodiments, such vinyl monomers have a viscosity from 1 to 200 cP at 25 °C. In embodiment, the number of vinyl or allyl functional groups is from 1 to 3.

25

In a further aspect the formulation includes two polymerizable components. In some embodiments, the crosslinked polymer comprises a first repeating unit derived from a urethane (meth)acrylate oligomer and a second repeating unit derived from a vinyl or thiol monomer wherein at least one of the urethane (meth)acrylate oligomer, the vinyl monomer and the thiol monomer comprises at least two polymerizable groups. In an embodiment, amount of the first component is from 15-40 wt% and the amount of the second component is from 15 to 75 wt%.

In some embodiments, the crosslinked polymer comprises a first repeating unit derived from a urethane (meth)acrylate oligomer and a second repeating unit derived from a vinyl or thiol monomer wherein at least one of the urethane (meth)acrylate oligomer, the vinyl monomer and the thiol monomer comprises at least two polymerizable groups. The urethane (meth)acrylate oligomer and the vinyl or thiol monomer are as described herein. In some embodiments, the amount of the first repeating unit is from 25 to 50 wt% and the amount of the second repeating unit is from 50 to 75 wt%, with the total amount of the first repeating unit and the second repeating unit being greater than or equal to 70 wt%.

In an aspect, the formulations contain three polymerizable components. The first component may be regarded as a base component. In embodiments, the first component is a monomer or oligomer. In embodiments the first component is selected from the group of consisting of acrylates, methacrylates, vinyl esters, polyurethane with acrylate end groups and polyurethane with epoxy end groups. As examples, the first component comprises a functional group selected from polyurethane, acrylate, methacrylate, vinyl ester, epoxy, oxetanyl and combinations thereof. In further embodiments, the first component comprises a functional group selected from polyurethane, acrylate, epoxy, and combinations thereof. Some biocompatible monomers include tetraethylene glycol diacrylate (E4-A), diisopropyl acrylamide (DPA), diisobutylacrylamide (DBA), 2-(2-ethoxy-ethoxy) ethyl acrylate, trimethylolpropanetriacrylate (TTA) and urethanedimethacrylate (UDMA).

In embodiments, the first component is a urethane (meth)acrylate monomer or oligomer. In embodiments the urethane portion of the monomer or oligomer may be aliphatic or aromatic. In embodiments, the number of (meth)acrylate groups in the monomer is 1, 2 or 3. In further embodiments, the urethane (meth)acrylate monomer or oligomer is selected from the group consisting of a dimethacrylate urethane oligomer, an isophorone urethane dimethacrylate oligomer, a urethane diacrylate oligomer and a urethane triacrylate oligomer. As examples, suitable urethane (meth)acrylate monomers and oligomers are selected from the group

consisting of Exothane 108, Exothane 10, IPDI-UDMA, CN991, CN9782, CN9782, CN3211, CN9009, PU3201NT and combinations thereof. In embodiments, the first component is selected from the group consisting of Exothane 108, Exothane 10, IPDI-UDMA or UDMA-IPDI (identified as Isophorone Urethane dimethacrylate),
5 CN991, CN9782, CN9009, PU3201NT and CN3211. In some embodiments, the viscosity of the first component is greater than the viscosity of the other monomer or oligomer components in the formulation.

In some embodiments, the second component may be regarded as a reactive
10 diluent. In embodiments, the second component comprises a functional group selected from polyurethane, acrylate, methacrylate, vinyl ester, epoxy, and combinations thereof. As examples, the second component is an acrylate, epoxy or urethane based diluent. In some embodiments, the second component is a vinyl monomer or a thiol monomer. As examples, the second component is selected from
15 the group consisting of diacrylate monomers, triacrylate monomers, acyclic diacrylate monomers, cyclic diacrylate monomers, methacrylate monomers, vinyl ester monomers, polyurethane monomers with acrylate end groups and polyurethane monomers with epoxy end groups. In further embodiments, the third component is a vinyl monomer which does not include a urethane group. Such vinyl monomers
20 include (meth)acrylate monomers and vinyl monomers which do not include (meth)acrylate groups. As examples, the second component is selected from 1-vinyl-2-pyrrolidinone (NVP), CEA (β -carboxyethylacrylate), trimethyl cyclohexyl acrylate (M1130), isobornyl acrylate (IBOA), Isobornyl methacrylate (IBOMA), tetrahydrofurfuryl methacrylate (M151) and one of PETMP and TATATO (see Table
25 4). In some embodiments, the viscosity of the reactive diluent component(s) (e.g. the second component) is less than the viscosity of other monomer or oligomer components in the formulation (e.g. the first and the third components).

In some embodiments, the third component may be regarded as a modifier.
30 In embodiments, the third component is a vinyl monomer or a thiol monomer. In further embodiments, the third component is a urethane (meth)acrylate monomer or oligomer. In embodiments the urethane portion of the monomer or oligomer may be

aliphatic or aromatic. In an embodiment, the number of (meth)acrylate groups in the monomer is 1 or 2. In further embodiments, the third component is a vinyl monomer which does not include a urethane group. Such monomers include (meth)acrylate monomers. In an embodiment in which the formulation includes a thiol-ene system, the second component is one of a vinyl monomer or a thiol and the third component is the other of a vinyl monomer or a thiol. For example, when the second component is one of PETMP and TATATO, the third component is the other of PETMP and TATATO. As examples, the third component is selected from SR833S, SR368D, CN9782, CN3211, tris(2-hydroxy ethyl)isocyanurate triacrylate (M370), tricyclodecane dimethanol diacrylate (TCDDA), PE210, tripropylene glycol diacrylate (TPGDA), PU340, ME2110 and NVP (see Tables 3 and 4). In some embodiments, the viscosity of the modifier component(s) (e.g. the second component) is less than the viscosity of the first component in the formulation.

In embodiments of a formulation including three polymerizable components, the amount of the first repeating unit is from 15-40 wt%, the amount of the second repeating unit is from 15 to 75 wt% and the amount of the third repeating unit is from 2 to 60 wt%. In a further embodiment, the total amount of the first repeating unit, the second repeating unit and the third repeating unit is greater than or equal to 70 wt%. 80 wt% or 90 wt%. In further embodiments the amount of the first repeating unit is from 20-35 wt%, the amount of the second repeating unit is from 20 to 70 wt% and the amount of the third repeating unit is from 2 to 45 wt%, 2 to 20 wt%, 15 to 45 wt% or 20 to 40 wt%. In yet a further embodiment, the total amount of the first repeating unit, the second repeating unit and the third repeating unit being greater than or equal to 70 wt%. 80 wt% or 90 wt%.

An exemplary formulation comprising three polymerizable components includes a urethane (meth)acrylate monomer or oligomer and two vinyl monomers, each of which does not include a urethane group. In some embodiments, one of the vinyl monomers is an acrylate monomer. An exemplary formulation includes a urethane (meth) acrylate prepolymer, a non-urethane acrylate monomer and a non-acrylate vinyl monomer. Another exemplary formulation includes a urethane (meth)acrylate prepolymer and two non-urethane acrylate monomers. Another

exemplary formulation with three polymerizable components includes two different urethane (methacrylate) monomers or oligomers and a vinyl monomer which does not include a urethane group. Another exemplary formulation with three polymerizable components includes two different urethane (methacrylate) monomers or oligomers and a vinyl monomer which does not include a urethane group or an acrylate group. A further exemplary formulation includes a urethane (methacrylate) monomer or oligomer, a thiol monomer and a vinyl monomer, wherein neither the thiol monomer nor the vinyl monomer includes a urethane group.

10 In an aspect, the crosslinked polymer comprises a first repeating unit derived from a first urethane (meth) acrylate oligomer, a second repeating unit derived from a first vinyl or thiol monomer not including a urethane linkage and a third repeating unit derived from a second urethane (meth) acrylate oligomer or a second vinyl or thiol monomer not including a urethane linkage, wherein at least one of the urethane (meth) acrylate oligomer(s) and the vinyl or thiol monomer(s) comprises at least two polymerizable groups. In some embodiments, the amount of the first repeating unit is from 15-40 wt%, the amount of the second repeating unit is from 15 to 75 wt% and the amount of the third repeating unit is from 2-60 wt%, with the total amount of the first repeating unit, the second repeating unit and the third repeating unit being greater than or equal to 70 wt%.

Photoinitiators suitable for use in the polymerizable liquid compositions of the invention include, but are not limited to photoinitiators activated by UV or visible light. In embodiments, the photoinitiator is activated by long-wavelength UV light or UVA (wavelength approximately 320 to 400 nm). Photo-initiators activated by long wavelength UV light include, but are not limited to, 2, 4, 6-trimethylbenzoylphenyl phosphinate (Irgacure ®TPO-L), acylgermanes, a bimolecular system of camphorquinone (CQ) and N, N-dimethylaminobenzoic acid ethyl ester (DMAB), bisacylphosphine oxides (Irgacure 819) and hydroxyalkylphenones (Irgacure 2959) and 1,5-diphenyl-1,4-diyn-3-one (Diinone). Camphorquinone (CQ), N, N-dimethylaminobenzoic acid ethyl ester (DMAB) bisacylphosphine oxides (Irgacure 819), hydroxyalkylphenones (Irgacure 2959) and

1,5-diphenyl-1,4-diyn-3-one (Diinone) are biocompatible. In some embodiments, the formulation includes from 0.1 wt% to 3 wt% photoinitiator. In further embodiments, the formulation does not include a second type of initiator other than a photoinitiator.

5

In an aspect, the viscosity of the polymerizable liquid composition is suitable for use with a direct or additive manufacturing process. In embodiments, the viscosity of the polymerizable liquid composition is less than 4000 cP, less than 2000 cP, less than 700 cP, from greater than or equal to 500 cP to less than 4000 cP, from
10 greater than or equal to 500 cP to less than 2000 cP, from greater than or equal to 200 cP to less than 4000 cP or from greater than or equal to 200 cP to less than 2000 cP. The viscosity may be measured at the process temperature. The process temperature can be adjustable from room temperature (~25 °C) to higher temperature such as 80 °C or higher in order to achieve the desired process viscosity and speed.

15

In an aspect, the crosslinked polymer is formed via a direct or additive manufacturing process. Direct or additive manufacturing processes may also be termed 3D printing. Suitable manufacturing processes include, but are not limited to, stereolithography (SLA), micro-stereolithography (μ SLA), DLP projection, 2PP (two
20 photon polymerization), continuous liquid interface production and material jetting. In embodiments, the direct fabrication methods described herein build up the object geometry in a layer-by-layer fashion, with successive layers being formed in discrete build steps. In particular embodiments, an at least partially crosslinked polymer is formed by sequential formation of polymer layers on a surface of a build plate,
25 wherein at least that surface of the build plate is immersed in a vat or reservoir of a formulation comprising polymerizable components. In embodiments the polymer is formed by exposure of the formulation to light of suitable wavelengths and intensity to activate the photoinitiator in the formulation and cause photopolymerization of polymerizable components in the formulation. The build plate is typically moved
30 with respect to the vat or reservoir (e.g., along the vertical or Z-direction) during the irradiation phase. In some embodiments, the build plate is moved away from the free surface of the formulation (e.g. moved deeper into the vat) as irradiation progresses.

In other embodiments, the build plate is moved away from the base of the vat as irradiation progresses.

Alternatively or in combination, direct fabrication methods that allow for
5 continuous or nearly continuous build-up of an object geometry can be used, referred
to herein as “continuous direct fabrication.” Various types of continuous direct
fabrication methods can be used. As an example, in embodiments, the crosslinked
polymers herein are fabricated using “continuous liquid interphase printing,” in
10 which an object is continuously built up from a reservoir of photopolymerizable resin
by forming a gradient of partially cured resin between the building surface of the
object and a polymerization-inhibited “dead zone.” In many embodiments, a semi-
permeable membrane is used to control transport of a photopolymerization inhibitor
(e.g., oxygen) into the dead zone in order to form the polymerization gradient. In an
15 embodiment, the oxygen concentration is greater near the base of the reservoir than
at the surface of the build plate and the build plate is moved away from the base of
the reservoir during irradiation. Continuous liquid interphase printing can achieve
fabrication speeds about 25 times to about 100 times faster than other direct
fabrication methods, and speeds about 1000 times faster can be achieved with the
incorporation of cooling systems. Continuous liquid interphase printing is described
20 in U.S. Patent Publication Nos. 2015/0097315, 2015/0097316, and 2015/0102532,
the disclosures of each of which are incorporated herein by reference in their
entirety.

The crosslinked polymer may undergo post processing following direct
25 fabrication. In some embodiments, the crosslinked polymer may be subjected to
chemical extraction to remove small molecule contents (e.g. uncured or
unpolymerized monomers and/or oligomers, photoinitiators and other components).
In embodiments, a single solution or multiple solutions are used for chemical
extraction. As an example, multiple solutions used for extraction differ in the nature
30 and/or concentration of the solution components. The processes can also include a
dual curing system in order to achieve a high level of curing of the final parts. In
embodiments, an initial level of crosslinking is achieved during the deposition of the

part and a further crosslinking is achieved by additional exposure to light (“post-curing”). In a further embodiment, the first step is to be achieved with slower reaction with mixing catalysts or fast reaction by light source: the second step will be completed with a gamma source e-beam, or heat for a continuous process. In
5 embodiments, the light source provides UV light.

In some embodiments, methods of making an orthodontic appliance comprising a cross-linked polymer comprise the steps of:

providing a light polymerizable liquid composition comprising:

- 10 a first polymerizable component, wherein the first polymerizable component is selected from the group consisting of an acrylate monomer or oligomer, a methacrylate monomer or oligomer, a vinyl ester monomer or oligomer, an acrylamide monomer or oligomer; a thiol monomer or oligomer, urethane monomer or oligomer, an epoxy monomer or oligomer and a oxetane monomer or oligomer;
- 15 a second polymerizable component, wherein the second polymerizable component is a vinyl monomer or oligomer, thiol monomer or oligomer, a urethane monomer or oligomer and an epoxy monomer or oligomer; and
- a photoinitiator;
- 20 wherein at least one of the first and second polymerizable components comprises at least two polymerizable groups; and

fabricating the cross-linked polymer by a direct fabrication technique.

The liquid polymerizable liquid compositions or formulations are as described elsewhere herein. Similarly, suitable fabrication techniques are described herein.

- 25 The various embodiments of the orthodontic appliances presented herein can be fabricated in a wide variety of ways. In some embodiments, the orthodontic appliances herein (or portions thereof) can be produced using direct fabrication, such as additive manufacturing techniques (also referred to herein as “3D printing”) or subtractive manufacturing techniques (e.g., milling). In some embodiments,
- 30 direct fabrication involves forming an object (e.g., an orthodontic appliance or a portion thereof) without using a physical template (e.g., mold, mask etc.) to define the object geometry. Additive manufacturing techniques can be categorized as

follows: (1) vat photopolymerization (e.g., stereolithography), in which an object is constructed layer by layer from a vat of liquid photopolymer resin; (2) material jetting, in which material is jetted onto a build platform using either a continuous or drop on demand (DOD) approach; (3) binder jetting, in which alternating layers of a build material (e.g., a powder-based material) and a binding material (e.g., a liquid binder) are deposited by a print head; (4) fused deposition modeling (FDM), in which material is drawn through a nozzle, heated, and deposited layer by layer; (5) powder bed fusion, including but not limited to direct metal laser sintering (DMLS), electron beam melting (EBM), selective heat sintering (SHS), selective laser melting (SLM), and selective laser sintering (SLS); (6) sheet lamination, including but not limited to laminated object manufacturing (LOM) and ultrasonic additive manufacturing (UAM); and (7) directed energy deposition, including but not limited to laser engineering net shaping, directed light fabrication, direct metal deposition, and 3D laser cladding. For example, stereolithography can be used to directly fabricate one or more of the appliances herein. In some embodiments, stereolithography involves selective polymerization of a photosensitive resin (e.g., a photopolymer) according to a desired cross-sectional shape using light (e.g., ultraviolet light). The object geometry can be built up in a layer-by-layer fashion by sequentially polymerizing a plurality of object cross-sections. As another example, the appliances herein can be directly fabricated using selective laser sintering. In some embodiments, selective laser sintering involves using a laser beam to selectively melt and fuse a layer of powdered material according to a desired cross-sectional shape in order to build up the object geometry. As yet another example, the appliances herein can be directly fabricated by fused deposition modeling. In some embodiments, fused deposition modeling involves melting and selectively depositing a thin filament of thermoplastic polymer in a layer-by-layer manner in order to form an object. In yet another example, material jetting can be used to directly fabricate the appliances herein. In some embodiments, material jetting involves jetting or extruding one or more materials onto a build surface in order to form successive layers of the object geometry.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1A illustrates an exemplary dental appliance **106** and jaw **104** including a patient's teeth.

- 5 Fig. 1B illustrates dental appliance cross-section **112** as taken along line **1B-1B** of Fig. 1A, while

Fig. 1C illustrates dental appliance cross-section **118** as taken along line **1C-1C** of Fig. 1A.

10

DETAILED DESCRIPTION

As used herein, the term “polymer” refers to a molecule composed of repeating structural units connected by covalent chemical bonds often characterized by a substantial number of repeating units (e.g., equal to or greater than 10 repeating units and often equal to or greater than 50 repeating units and often equal to or greater than 100 repeating units) and a high molecular weight (e.g. greater than or equal to 50,000 Da). Polymers are commonly the polymerization product of one or more monomer precursors. The term polymer includes homopolymers, or polymers consisting essentially of a single repeating monomer subunit. The term polymer also includes copolymers which are formed when two or more different types of monomers are linked in the same polymer. Copolymers may comprise two or more monomer subunits, and include random, block, alternating, segmented, grafted, tapered and other copolymers.

- 25 An “oligomer” refers to a molecule composed of repeating structural units connected by covalent chemical bonds often characterized by a number of repeating units less than that of a polymer (e.g., equal to or less than 10 repeating units) and a lower molecular weights (e.g. less than or equal to 50,000 Da) than polymers. Oligomers may be the polymerization product of one or more monomer precursors.
- 30 In an embodiment, an oligomer or a monomer cannot be considered a polymer in its own right.

A “prepolymer” refers to a polymer or oligomer the molecules of which are capable of entering, through reactive groups, into further polymerization. Routes to forming polyurethane polymers include polymerization of diol and diisocyanate monomers and polymerization of prepolymers including urethane linkages. In
5 embodiments, the polyurethane prepolymer is oligomeric. In other embodiments, the polyurethane prepolymers include acrylate or methacrylate endgroups.

Oligomers and polymer mixtures can be characterized and differentiated from other mixtures of oligomers and polymers by measurements of molecular weight and
10 molecular weight distributions. The following definitions of molecular weight can be applied for such characterization (see: L.H. Sperling, Introduction to Physical Polymer Science, 2nd Ed., Wiley New York (1992).) The average Molecular Weight (M) is the Average Number of Repeating Units n (or dp_n) $\times$ the molecular weight or molar mass (M_i) of the repeating unit. The number-average molecular weight (M_n)
15 is the arithmetic mean, representing the total weight of the molecules present divided by the total number of molecules. Molecular weight may also be measured by the weight-average molecular weight (M_w) and the z-average molecular weight M_z ,

In embodiments, one or more monomers or oligomers in the light
20 polymerizable liquid composition contains one or more vinyl functional groups, which contain one or more carbon-carbon double bonds. The vinyl functional groups in the system may be provided by, for example, allyl ethers, vinyl ethers, norbornenes, acrylates, methacrylates, acrylamides or other monomers containing vinyl groups. In embodiments, the vinyl monomer or oligomer has at least one vinyl
25 functional group, at least two vinyl functional groups, at least three vinyl functional groups or at least four vinyl functional groups or from 2 to 4 thiol functional groups. In some embodiments, the vinyl monomer or oligomer may further comprise a hydroxyl group. In other embodiments, the vinyl monomer or oligomer does not comprise a hydroxyl group.

30

In embodiments, one of the monomers or oligomers in the light polymerizable liquid composition includes a thiol monomer or oligomer. As used

herein, a thiol monomer or oligomer containing one or more thiol functional groups, which terminate with –SH. Monomers or oligomers containing thiol functional groups may be combined with monomers or oligomers comprising at least one aliphatic carbon-carbon double bond or at least one aliphatic carbon-carbon triple bond. In embodiments, the thiol monomer or oligomer has at least two thiol functional groups, at least three thiol functional groups or at least four thiol functional groups or from 2 to 4 thiol functional groups. In different embodiments, a thiol-ene system has about 1-90% of its functional groups as thiol functional groups or 2%-65 % thiol functional groups. The balance of the functional groups (35% to 98%) of the functional groups may be vinyl functional groups.

In embodiments, the light polymerizable composition further includes a filler material. Soluble filler materials include, but are not limited to poly(vinyl alcohol), poly(vinyl butyral-co-vinyl alcohol-co-vinyl acetate), polycaprolactone, poly (methyl methacrylate), polycaprolactone-block-polytetrahydrofuran block-polycaprolactone, poly(vinyl chloride) or cellulose acetate butyrate, which may be used to tune the viscosity. Inorganic fillers include, but are not limited to hydroxyapatite, fumed silica, colloidal silica, glass powders and β -tricalciumphosphate, which may be used to improve the mechanical properties of the polymer.

20

Photoinitiators that are useful in the invention include those that can be activated with light and initiate polymerization of the polymerizable components of the formulation. In embodiments, the photoinitiator is a radical photoinitiator or a cationic initiator. In a further embodiment, the photoinitiator is a Type I photoinitiator which undergoes a unimolecular bond cleavage to generate free radicals. In an additional embodiment the photoinitiator is a Type II photoinitiator which undergoes a bimolecular reaction to generate free radicals. Common Type I photoinitiators include, but are not limited to benzoin ethers, benzil ketals, α -dialkoxy-acetophenones, α -hydroxy-alkyl phenones and acyl-phosphine oxides. Common Type II photoinitiators include benzophenones/amines and thioxanthenes/amines. Cationic initiators include aryldiazonium, diaryliodonium, and triarylsulfonium salts.

30

Photopolymerization occurs when suitable formulations are exposed to light of sufficient power and of a wavelength capable of initiating polymerization. The wavelengths and power of light useful to initiate polymerization depends on the initiator used. Light as used herein includes any wavelength and power capable of initiating polymerization. Preferred wavelengths of light include ultraviolet (UV) or visible. UV light sources include UVA (wavelength about 400nm to about 320 nm), UVB (about 320 nm to about 290 nm) or UVC (about 290 nm to about 100 nm). Any suitable source may be used, including laser sources. The source may be broadband or narrowband, or a combination. The light source may provide continuous or pulsed light during the process. Both the length of time the system is exposed to UV light and the intensity of the UV light can be varied to determine the ideal reaction conditions.

Additive manufacturing includes a variety of technologies which fabricate three-dimensional objects directly from digital models through an additive process. In some aspects, successive layers of material are deposited and “cured in place.” A variety of techniques are known to the art for additive manufacturing, including selective laser sintering (SLS), fused deposition modeling (FDM) and jetting or extrusion. In many embodiments, selective laser sintering involves using a laser beam to selectively melt and fuse a layer of powdered material according to a desired cross-sectional shape in order to build up the object geometry. In many embodiments, fused deposition modeling involves melting and selectively depositing a thin filament of thermoplastic polymer in a layer-by-layer manner in order to form an object. In yet another example, 3D printing can be used to fabricate the appliances herein. In many embodiments, 3D printing involves jetting or extruding one or more materials onto a build surface in order to form successive layers of the object geometry.

Photopolymers may be fabricated by “vat” processes in which light is used to selectively cure a vat or reservoir of the photopolymer. Each layer of photopolymer may be selectively exposed to light in a single exposure or by scanning a beam of

light across the layer. Specific techniques include sterolithography (SLA), Digital Light Processing (DLP) and two photon-induced photopolymerization (TPIP).

Continuous direct fabrication methods for photopolymers have also been reported. For example, a direct fabrication process can achieve continuous build-up of an object geometry by continuous movement of the build platform (e.g., along the vertical or Z-direction) during the irradiation phase, such that the hardening depth of the irradiated photopolymer is controlled by the movement speed. Accordingly, continuous polymerization of material on the build surface can be achieved. Such methods are described in U.S. Patent No. 7,892,474, the disclosure of which is incorporated herein by reference in its entirety. In yet another example, a continuous direct fabrication method utilizes a “heliolithography” approach in which the liquid photopolymer is cured with focused radiation while the build platform is continuously rotated and raised. Accordingly, the object geometry can be continuously built up along a spiral build path. Such methods are described in U.S. Patent Publication No. 2014/0265034, the disclosure of which is incorporated herein by reference in its entirety. Continuous liquid interface production of 3D objects has also been reported (J. Tumbleston et al., Science, 2015, 347 (6228), pp 1349-1352) hereby incorporated by reference in its entirety for description of the process. Another example of continuous direct fabrication method can involve extruding a composite material composed of a curable liquid material surrounding a solid strand. The composite material can be extruded along a continuous three-dimensional path in order to form the object. Such methods are described in U.S. Patent Publication No. 2014/0061974, the disclosure of which is incorporated herein by reference in its entirety.

“Biocompatible” refers to a material that does not elicit an immunological rejection or detrimental effect, referred herein as an adverse immune response, when it is disposed within an *in-vivo* biological environment. For example, in embodiments a biological marker indicative of an immune response changes less than 10%, or less than 20%, or less than 25%, or less than 40%, or less than 50% from a baseline value when a human or animal is exposed to or in contact with the

biocompatible material. Alternatively, immune response may be determined histologically, wherein localized immune response is assessed by visually assessing markers, including immune cells or markers that are involved in the immune response pathway, in and adjacent to the material. In an aspect, a biocompatible material or device does not observably change immune response as determined histologically. In some embodiments, the invention provides biocompatible devices configured for long-term use, such as on the order of weeks to months, without invoking an adverse immune response. Biological effects may be initially evaluated by measurement of cytotoxicity, sensitization, irritation and intracutaneous reactivity, acute systemic toxicity, pyrogenicity, subacute/subchronic toxicity and/or implantation. Biological tests for supplemental evaluation include testing for chronic toxicity.

“Bioinert” refers to a material that does not elicit an immune response from a human or animal when it is disposed within an *in-vivo* biological environment. For example, a biological marker indicative of an immune response remains substantially constant (plus or minus 5% of a baseline value) when a human or animal is exposed to or in contact with the bioinert material. In some embodiments, the invention provides bioinert devices.

20

In embodiments, the crosslinked polymers are characterized by a tensile stress-strain curve that displays a yield point after which the test specimen continues to elongate, but there is no increase in load. Such yield point behavior typically occurs “near” the glass transition temperature, where the material is between the glassy and rubbery regimes and may be characterized as having viscoelastic behavior. In embodiments, viscoelastic behavior is observed in the temperature range 20 °C to 40 °C. The yield stress is determined at the yield point. In some embodiments, the yield point follows an elastic region in which the slope of the stress-strain curve is constant or nearly constant. In embodiments, the modulus is determined from the initial slope of the stress-strain curve or as the secant modulus at 1% strain (e.g. when there is no linear portion of the stress-strain curve). The elongation at yield is determined from the strain at the yield point. When the yield

point occurs at a maximum in the stress, the ultimate tensile strength is less than the yield strength. For a tensile test specimen, the strain is defined by $\ln(l/l_0)$, which may be approximated by $(l-l_0)/l_0$ at small strains (e.g. less than approximately 10%) and the elongation is l/l_0 , where l is the gauge length after some deformation has occurred and l_0 is the initial gauge length. The mechanical properties can depend on the temperature at which they are measured. The test temperature may be below the expected use temperature for a dental appliance such as 35°C to 40°C, In embodiments, the test temperature is $23 \pm 2^\circ\text{C}$

10 In embodiments, the stress relaxation can be measured by monitoring the time-dependent stress resulting from a steady strain. The extent of stress relaxation can also depend on the temperature. In embodiments, the test temperature is $37 \pm 2^\circ\text{C}$

The dynamic viscosity of a fluid indicates its resistance to shearing flows. The SI unit for dynamic viscosity is the Poiseuille ($\text{Pa} \cdot \text{s}$). Dynamic viscosity is commonly given in units of centipoise, where 1 centipoise (cP) is equivalent to 1 mPa $\cdot$ s. Kinematic viscosity is the ratio of the dynamic viscosity to the density of the fluid; the SI unit is m^2/s . Devices for measuring viscosity include viscometers and rheometers.

20

Examples of devices that may be made by direct fabrication include, but are not limited to, those described in the following US Provisional Applications filed July 7, 2015: "MULTI-MATERIAL ALIGNERS", USSN 62/189,259 (attorney docket number 22773-852.101); "DIRECT FABRICATION OF ALIGNERS WITH INTERPROXIMAL FORCE COUPLING", USSN 62/189,263 (attorney docket number 22773-855.101); "DIRECT FABRICATION OF ORTHODONTIC APPLIANCES WITH VARIABLE PROPERTIES", USSN 62/189 291 (attorney docket number 22773-856.101); "DIRECT FABRICATION OF ALIGNERS FOR ARCH EXPANSION", USSN 62/189,271 (attorney docket number 22773-857.101); "DIRECT FABRICATION OF ATTACHMENT TEMPLATES WITH ADHESIVE", USSN 62/189,282 (attorney docket number 22773-858.101); "DIRECT FABRICATION CROSS-LINKING FOR PALATE EXPANSION AND

OTHER APPLICATIONS”, USSN 62/189,301 (attorney docket number 22773-859.101); “SYSTEMS, APPARATUSES AND METHODS FOR DENTAL APPLIANCES WITH INTEGRALLY FORMED FEATURES”, USSN 62/189,312 (attorney docket number 22773-860.101); “DIRECT FABRICATION OF POWER
5 ARMS”, USSN 62/189,317 (attorney docket number 22773-861.101); “SYSTEMS, APPARATUSES AND METHODS FOR DRUG DELIVERY FROM DENTAL APPLIANCES WITH INTEGRALLY FORMED RESERVOIRS”, USSN 62/189,303 (attorney docket number 22773-862.101) and “DENTAL APPLIANCE HAVING ORNAMENTAL DESIGN”, USSN 62/189,318 (attorney docket number
10 ALGNP006P2), each of which is hereby incorporated by reference in its entirety.

STATEMENTS REGARDING INCORPORATION BY REFERENCE AND VARIATIONS

All references cited throughout this application, for example patent
15 documents including issued or granted patents or equivalents; patent application publications; and non-patent literature documents or other source material; are hereby incorporated by reference herein in their entireties, as though individually incorporated by reference, to the extent each reference is at least partially not inconsistent with the disclosure in this application (for example, a reference that is
20 partially inconsistent is incorporated by reference except for the partially inconsistent portion of the reference).

The terms and expressions which have been employed herein are used as terms of description and not of limitation, and there is no intention in the use of such
25 terms and expressions of excluding any equivalents of the features shown and described or portions thereof, but it is recognized that various modifications are possible within the scope of the invention claimed. Thus, it should be understood that although the present invention has been specifically disclosed by preferred embodiments, exemplary embodiments and optional features, modification and
30 variation of the concepts herein disclosed may be resorted to by those skilled in the art, and that such modifications and variations are considered to be within the scope of this invention as defined by the appended claims. The specific embodiments

provided herein are examples of useful embodiments of the present invention and it will be apparent to one skilled in the art that the present invention may be carried out using a large number of variations of the devices, device components, methods steps set forth in the present description. As will be obvious to one of skill in the art, 5 methods and devices useful for the present methods can include a large number of optional composition and processing elements and steps.

When a group of substituents is disclosed herein, it is understood that all individual members of that group and all subgroups, including any isomers, 10 enantiomers, and diastereomers of the group members, are disclosed separately. When a Markush group or other grouping is used herein, all individual members of the group and all combinations and subcombinations possible of the group are intended to be individually included in the disclosure. When a compound is described herein such that a particular isomer, enantiomer or diastereomer of the 15 compound is not specified, for example, in a formula or in a chemical name, that description is intended to include each isomers and enantiomer of the compound described individual or in any combination. Additionally, unless otherwise specified, all isotopic variants of compounds disclosed herein are intended to be encompassed by the disclosure. For example, it will be understood that any one or more hydrogens 20 in a molecule disclosed can be replaced with deuterium or tritium. Isotopic variants of a molecule are generally useful as standards in assays for the molecule and in chemical and biological research related to the molecule or its use. Methods for making such isotopic variants are known in the art. Specific names of compounds are intended to be exemplary, as it is known that one of ordinary skill in the art can 25 name the same compounds differently.

It must be noted that as used herein and in the appended claims, the singular forms "a", "an", and "the" include plural reference unless the context clearly dictates otherwise. Thus, for example, reference to "a cell" includes a plurality of such cells 30 and equivalents thereof known to those skilled in the art, and so forth. As well, the terms "a" (or "an"), "one or more" and "at least one" can be used interchangeably herein. It is also to be noted that the terms "comprising", "including", and "having"

can be used interchangeably. The expression "of any of claims XX-YY" (wherein XX and YY refer to claim numbers) is intended to provide a multiple dependent claim in the alternative form, and in some embodiments is interchangeable with the expression "as in any one of claims XX-YY."

5

Unless defined otherwise, all technical and scientific terms used herein have the same meanings as commonly understood by one of ordinary skill in the art to which this invention belongs. Although any methods and materials similar or equivalent to those described herein can be used in the practice or testing of the present invention, the preferred methods and materials are now described. Nothing herein is to be construed as an admission that the invention is not entitled to antedate such disclosure by virtue of prior invention.

Every formulation or combination of components described or exemplified herein can be used to practice the invention, unless otherwise stated.

Whenever a range is given in the specification, for example, a temperature range, a time range, or a composition or concentration range, all intermediate ranges and subranges, as well as all individual values included in the ranges given are intended to be included in the disclosure. As used herein, ranges specifically include the values provided as endpoint values of the range. For example, a range of 1 to 100 specifically includes the end point values of 1 and 100. It will be understood that any subranges or individual values in a range or subrange that are included in the description herein can be excluded from the claims herein.

25

As used herein, "comprising" is synonymous with "including," "containing," or "characterized by," and is inclusive or open-ended and does not exclude additional, unrecited elements or method steps. As used herein, "consisting of" excludes any element, step, or ingredient not specified in the claim element. As used herein, "consisting essentially of" does not exclude materials or steps that do not materially affect the basic and novel characteristics of the claim. In each instance herein any of the terms "comprising", "consisting essentially of" and "consisting of"

30

may be replaced with either of the other two terms. The invention illustratively described herein suitably may be practiced in the absence of any element or elements, limitation or limitations which is not specifically disclosed herein.

One of ordinary skill in the art will appreciate that starting materials,
5 biological materials, reagents, synthetic methods, purification methods, analytical methods, assay methods, and biological methods other than those specifically exemplified can be employed in the practice of the invention without resort to undue experimentation. All art-known functional equivalents, of any such materials and methods are intended to be included in this invention. The terms and expressions
10 which have been employed are used as terms of description and not of limitation, and there is no intention that in the use of such terms and expressions of excluding any equivalents of the features shown and described or portions thereof, but it is recognized that various modifications are possible within the scope of the invention claimed. Thus, it should be understood that although the present invention has been
15 specifically disclosed by preferred embodiments and optional features, modification and variation of the concepts herein disclosed may be resorted to by those skilled in the art, and that such modifications and variations are considered to be within the scope of this invention as defined by the appended claims.

20 **STATEMENTS REGARDING CHEMICAL COMPOUNDS AND NOMENCLATURE**

As used herein, the term “group” may refer to a functional group of a chemical compound. Groups of the present compounds refer to an atom or a collection of atoms that are a part of the compound. Groups of the present invention
25 may be attached to other atoms of the compound via one or more covalent bonds. Groups may also be characterized with respect to their valence state. The present invention includes groups characterized as monovalent, divalent, trivalent, etc. valence states.

30 As used herein, the term “substituted” refers to a compound wherein a hydrogen is replaced by another functional group.

Alkyl groups include straight-chain, branched and cyclic alkyl groups. Alkyl groups include those having from 1 to 30 carbon atoms. Alkyl groups include small alkyl groups having 1 to 3 carbon atoms. Alkyl groups include medium length alkyl groups having from 4-10 carbon atoms. Alkyl groups include long alkyl groups having more than 10 carbon atoms, particularly those having 10-30 carbon atoms. The term cycloalkyl specifically refers to an alkyl group having a ring structure such as ring structure comprising 3-30 carbon atoms, optionally 3-20 carbon atoms and optionally 3 – 10 carbon atoms, including an alkyl group having one or more rings. Cycloalkyl groups include those having a 3-, 4-, 5-, 6-, 7-, 8-, 9- or 10- member carbon ring(s) and particularly those having a 3-, 4-, 5-, 6-, 7- or 8- member ring(s). The carbon rings in cycloalkyl groups can also carry alkyl groups. Cycloalkyl groups can include bicyclic and tricycloalkyl groups. Alkyl groups are optionally substituted. Substituted alkyl groups include among others those which are substituted with aryl groups, which in turn can be optionally substituted. Specific alkyl groups include methyl, ethyl, n-propyl, iso-propyl, cyclopropyl, n-butyl, s-butyl, t-butyl, cyclobutyl, n-pentyl, branched-pentyl, cyclopentyl, n-hexyl, branched hexyl, and cyclohexyl groups, all of which are optionally substituted. Substituted alkyl groups include fully halogenated or semihalogenated alkyl groups, such as alkyl groups having one or more hydrogens replaced with one or more fluorine atoms, chlorine atoms, bromine atoms and/or iodine atoms. Substituted alkyl groups include fully fluorinated or semifluorinated alkyl groups, such as alkyl groups having one or more hydrogens replaced with one or more fluorine atoms. An alkoxy group is an alkyl group that has been modified by linkage to oxygen and can be represented by the formula R-O and can also be referred to as an alkyl ether group. Examples of alkoxy groups include, but are not limited to, methoxy, ethoxy, propoxy, butoxy and heptoxy. Alkoxy groups include substituted alkoxy groups wherein the alkyl portion of the groups is substituted as provided herein in connection with the description of alkyl groups. As used herein MeO- refers to CH₃O-.

Alkenyl groups include straight-chain, branched and cyclic alkenyl groups. Alkenyl groups include those having 1, 2 or more double bonds and those in which two or more of the double bonds are conjugated double bonds. Alkenyl groups

include those having from 2 to 20 carbon atoms. Alkenyl groups include small alkenyl groups having 2 to 3 carbon atoms. Alkenyl groups include medium length alkenyl groups having from 4-10 carbon atoms. Alkenyl groups include long alkenyl groups having more than 10 carbon atoms, particularly those having 10-20 carbon atoms. Cycloalkenyl groups include those in which a double bond is in the ring or in an alkenyl group attached to a ring. The term cycloalkenyl specifically refers to an alkenyl group having a ring structure, including an alkenyl group having a 3-, 4-, 5-, 6-, 7-, 8-, 9- or 10- member carbon ring(s) and particularly those having a 3-, 4-, 5-, 6-, 7- or 8- member ring(s). The carbon rings in cycloalkenyl groups can also carry alkyl groups. Cycloalkenyl groups can include bicyclic and tricyclic alkenyl groups. Alkenyl groups are optionally substituted. Substituted alkenyl groups include among others those that are substituted with alkyl or aryl groups, which groups in turn can be optionally substituted. Specific alkenyl groups include ethenyl, prop-1-enyl, prop-2-enyl, cycloprop-1-enyl, but-1-enyl, but-2-enyl, cyclobut-1-enyl, cyclobut-2-enyl, pent-1-enyl, pent-2-enyl, branched pentenyl, cyclopent-1-enyl, hex-1-enyl, branched hexenyl, cyclohexenyl, all of which are optionally substituted. Substituted alkenyl groups include fully halogenated or semihalogenated alkenyl groups, such as alkenyl groups having one or more hydrogens replaced with one or more fluorine atoms, chlorine atoms, bromine atoms and/or iodine atoms. Substituted alkenyl groups include fully fluorinated or semifluorinated alkenyl groups, such as alkenyl groups having one or more hydrogen atoms replaced with one or more fluorine atoms.

Aryl groups include groups having one or more 5-, 6-, 7- or 8- member aromatic rings, including heterocyclic aromatic rings. The term heteroaryl specifically refers to aryl groups having at least one 5-, 6-, 7- or 8- member heterocyclic aromatic rings. Aryl groups can contain one or more fused aromatic rings, including one or more fused heteroaromatic rings, and/or a combination of one or more aromatic rings and one or more nonaromatic rings that may be fused or linked via covalent bonds. Heterocyclic aromatic rings can include one or more N, O, or S atoms in the ring. Heterocyclic aromatic rings can include those with one, two or three N atoms, those with one or two O atoms, and those with one or two S atoms, or combinations of one or two or three N, O or S atoms. Aryl groups are optionally

substituted. Substituted aryl groups include among others those that are substituted with alkyl or alkenyl groups, which groups in turn can be optionally substituted. Specific aryl groups include phenyl, biphenyl groups, pyrrolidinyl, imidazolidinyl, tetrahydrofuryl, tetrahydrothienyl, furyl, thienyl, pyridyl, quinolyl, isoquinolyl, pyridazinyl, pyrazinyl, indolyl, imidazolyl, oxazolyl, thiazolyl, pyrazolyl, pyridinyl, benzoxadiazolyl, benzothiadiazolyl, and naphthyl groups, all of which are optionally substituted. Substituted aryl groups include fully halogenated or semihalogenated aryl groups, such as aryl groups having one or more hydrogens replaced with one or more fluorine atoms, chlorine atoms, bromine atoms and/or iodine atoms. Substituted aryl groups include fully fluorinated or semifluorinated aryl groups, such as aryl groups having one or more hydrogens replaced with one or more fluorine atoms. Aryl groups include, but are not limited to, aromatic group-containing or heterocyclic aromatic group-containing groups corresponding to any one of the following: benzene, naphthalene, naphthoquinone, diphenylmethane, fluorene, anthracene, anthraquinone, phenanthrene, tetracene, tetracenedione, pyridine, quinoline, isoquinoline, indoles, isoindole, pyrrole, imidazole, oxazole, thiazole, pyrazole, pyrazine, pyrimidine, purine, benzimidazole, furans, benzofuran, dibenzofuran, carbazole, acridine, acridone, phenanthridine, thiophene, benzothiophene, dibenzothiophene, xanthene, xanthone, flavone, coumarin, azulene or anthracycline. As used herein, a group corresponding to the groups listed above expressly includes an aromatic or heterocyclic aromatic group, including monovalent, divalent and polyvalent groups, of the aromatic and heterocyclic aromatic groups listed herein provided in a covalently bonded configuration in the compounds of the invention at any suitable point of attachment. In embodiments, aryl groups contain between 5 and 30 carbon atoms. In embodiments, aryl groups contain one aromatic or heteroaromatic six-member ring and one or more additional five- or six-member aromatic or heteroaromatic ring. In embodiments, aryl groups contain between five and eighteen carbon atoms in the rings. Aryl groups optionally have one or more aromatic rings or heterocyclic aromatic rings having one or more electron donating groups, electron withdrawing groups and/or targeting ligands provided as substituents.

Arylalkyl groups are alkyl groups substituted with one or more aryl groups wherein the alkyl groups optionally carry additional substituents and the aryl groups are optionally substituted. Specific alkylaryl groups are phenyl-substituted alkyl groups, e.g., phenylmethyl groups. Alkylaryl groups are alternatively described as
5 aryl groups substituted with one or more alkyl groups wherein the alkyl groups optionally carry additional substituents and the aryl groups are optionally substituted. Specific alkylaryl groups are alkyl-substituted phenyl groups such as methylphenyl. Substituted arylalkyl groups include fully halogenated or semihalogenated arylalkyl groups, such as arylalkyl groups having one or more alkyl and/or aryl groups having
10 one or more hydrogens replaced with one or more fluorine atoms, chlorine atoms, bromine atoms and/or iodine atoms.

As used herein, the terms “alkylene” and “alkylene group” are used synonymously and refer to a divalent group derived from an alkyl group as defined
15 herein. The invention includes compounds having one or more alkylene groups. Alkylene groups in some compounds function as attaching and/or spacer groups. Compounds of the invention may have substituted and/or unsubstituted C₁-C₂₀ alkylene, C₁-C₁₀ alkylene and C₁-C₅ alkylene groups.

20 As used herein, the terms “cycloalkylene” and “cycloalkylene group” are used synonymously and refer to a divalent group derived from a cycloalkyl group as defined herein. The invention includes compounds having one or more cycloalkylene groups. Cycloalkyl groups in some compounds function as attaching and/or spacer groups. Compounds of the invention may have substituted and/or unsubstituted C₃-
25 C₂₀ cycloalkylene, C₃-C₁₀ cycloalkylene and C₃-C₅ cycloalkylene groups.

As used herein, the terms “arylene” and “arylene group” are used synonymously and refer to a divalent group derived from an aryl group as defined herein. The invention includes compounds having one or more arylene groups. In
30 some embodiments, an arylene is a divalent group derived from an aryl group by removal of hydrogen atoms from two intra-ring carbon atoms of an aromatic ring of the aryl group. Arylene groups in some compounds function as attaching and/or

spacer groups. Arylene groups in some compounds function as chromophore, fluorophore, aromatic antenna, dye and/or imaging groups. Compounds of the invention include substituted and/or unsubstituted C₃-C₃₀ arylene, C₃-C₂₀ arylene, C₃-C₁₀ arylene and C₁-C₅ arylene groups.

5

As used herein, the terms “heteroarylene” and “heteroarylene group” are used synonymously and refer to a divalent group derived from a heteroaryl group as defined herein. The invention includes compounds having one or more heteroarylene groups. In some embodiments, a heteroarylene is a divalent group derived from a heteroaryl group by removal of hydrogen atoms from two intra-ring carbon atoms or intra-ring nitrogen atoms of a heteroaromatic or aromatic ring of the heteroaryl group. Heteroarylene groups in some compounds function as attaching and/or spacer groups. Heteroarylene groups in some compounds function as chromophore, aromatic antenna, fluorophore, dye and/or imaging groups. Compounds of the invention include substituted and/or unsubstituted C₃-C₃₀ heteroarylene, C₃-C₂₀ heteroarylene, C₁-C₁₀ heteroarylene and C₃-C₅ heteroarylene groups.

As used herein, the terms “alkenylene” and “alkenylene group” are used synonymously and refer to a divalent group derived from an alkenyl group as defined herein. The invention includes compounds having one or more alkenylene groups. Alkenylene groups in some compounds function as attaching and/or spacer groups. Compounds of the invention include substituted and/or unsubstituted C₂-C₂₀ alkenylene, C₂-C₁₀ alkenylene and C₂-C₅ alkenylene groups.

As used herein, the terms “cylcoalkenylene” and “cylcoalkenylene group” are used synonymously and refer to a divalent group derived from a cylcoalkenyl group as defined herein. The invention includes compounds having one or more cylcoalkenylene groups. Cycloalkenylene groups in some compounds function as attaching and/or spacer groups. Compounds of the invention include substituted and/or unsubstituted C₃-C₂₀ cylcoalkenylene, C₃-C₁₀ cylcoalkenylene and C₃-C₅ cylcoalkenylene groups.

As used herein, the terms “alkynylene” and “alkynylene group” are used synonymously and refer to a divalent group derived from an alkynyl group as defined herein. The invention includes compounds having one or more alkynylene groups. Alkynylene groups in some compounds function as attaching and/or spacer groups.

- 5 Compounds of the invention include substituted and/or unsubstituted C₂-C₂₀ alkynylene, C₂-C₁₀ alkynylene and C₂-C₅ alkynylene groups.

As used herein, the term “halo” refers to a halogen group such as a fluoro (-F), chloro (-Cl), bromo (-Br) or iodo (-I)

10

The term “heterocyclic” refers to ring structures containing at least one other kind of atom, in addition to carbon, in the ring. Examples of such heteroatoms include nitrogen, oxygen and sulfur. Heterocyclic rings include heterocyclic alicyclic rings and heterocyclic aromatic rings. Examples of heterocyclic rings include, but are not limited to, pyrrolidinyl, piperidyl, imidazolidinyl, tetrahydrofuryl, tetrahydrothienyl, furyl, thienyl, pyridyl, quinolyl, isoquinolyl, pyridazinyl, pyrazinyl, indolyl, imidazolyl, oxazolyl, thiazolyl, pyrazolyl, pyridinyl, benzoxadiazolyl, benzothiadiazolyl, triazolyl and tetrazolyl groups. Atoms of heterocyclic rings can be bonded to a wide range of other atoms and functional groups, for example, provided as substituents.

20

The term “carbocyclic” refers to ring structures containing only carbon atoms in the ring. Carbon atoms of carbocyclic rings can be bonded to a wide range of other atoms and functional groups, for example, provided as substituents.

25

The term “alicyclic ring” refers to a ring, or plurality of fused rings, that is not an aromatic ring. Alicyclic rings include both carbocyclic and heterocyclic rings.

The term “aromatic ring” refers to a ring, or a plurality of fused rings, that includes at least one aromatic ring group. The term aromatic ring includes aromatic rings comprising carbon, hydrogen and heteroatoms. Aromatic ring includes

30

carbocyclic and heterocyclic aromatic rings. Aromatic rings are components of aryl groups.

5 The term "fused ring" or "fused ring structure" refers to a plurality of alicyclic and/or aromatic rings provided in a fused ring configuration, such as fused rings that share at least two intra ring carbon atoms and/or heteroatoms.

As used herein, the term "alkoxyalkyl" refers to a substituent of the formula alkyl-O-alkyl.

10

As used herein, the term "polyhydroxyalkyl" refers to a substituent having from 2 to 12 carbon atoms and from 2 to 5 hydroxyl groups, such as the 2,3-dihydroxypropyl, 2,3,4-trihydroxybutyl or 2,3,4,5-tetrahydroxypentyl residue.

15 As used herein, the term "polyalkoxyalkyl" refers to a substituent of the formula alkyl-(alkoxy)_n-alkoxy wherein n is an integer from 1 to 10, preferably 1 to 4, and more preferably for some embodiments 1 to 3.

20 As to any of the groups described herein that contain one or more substituents, it is understood that such groups do not contain any substitution or substitution patterns which are sterically impractical and/or synthetically non-feasible. In addition, the compounds of this invention include all stereochemical isomers arising from the substitution of these compounds. Optional substitution of alkyl groups includes substitution with one or more alkenyl groups, aryl groups or
25 both, wherein the alkenyl groups or aryl groups are optionally substituted. Optional substitution of alkenyl groups includes substitution with one or more alkyl groups, aryl groups, or both, wherein the alkyl groups or aryl groups are optionally substituted. Optional substitution of aryl groups includes substitution of the aryl ring with one or more alkyl groups, alkenyl groups, or both, wherein the alkyl groups or
30 alkenyl groups are optionally substituted.

Optional substituents for any alkyl, alkenyl and aryl group includes substitution with one or more of the following substituents, among others:

halogen, including fluorine, chlorine, bromine or iodine;

pseudohalides, including $-\text{CN}$, $-\text{OCN}$ (cyanate), $-\text{NCO}$ (isocyanate), $-\text{SCN}$ (thiocyanate) and $-\text{NCS}$ (isothiocyanate);

$-\text{COOR}$, where R is a hydrogen or an alkyl group or an aryl group and more specifically where R is a methyl, ethyl, propyl, butyl, or phenyl group all of which groups are optionally substituted;

$-\text{COR}$, where R is a hydrogen or an alkyl group or an aryl group and more specifically where R is a methyl, ethyl, propyl, butyl, or phenyl group all of which groups are optionally substituted;

$-\text{CON}(\text{R})_2$, where each R, independently of each other R, is a hydrogen or an alkyl group or an aryl group and more specifically where R is a methyl, ethyl, propyl, butyl, or phenyl group all of which groups are optionally substituted; and where R and R can form a ring which can contain one or more double bonds and can contain one or more additional carbon atoms;

$-\text{OCON}(\text{R})_2$, where each R, independently of each other R, is a hydrogen or an alkyl group or an aryl group and more specifically where R is a methyl, ethyl, propyl, butyl, or phenyl group all of which groups are optionally substituted; and where R and R can form a ring which can contain one or more double bonds and can contain one or more additional carbon atoms;

$-\text{N}(\text{R})_2$, where each R, independently of each other R, is a hydrogen, or an alkyl group, or an acyl group or an aryl group and more specifically where R is a methyl, ethyl, propyl, butyl, phenyl or acetyl group, all of which are optionally substituted; and where R and R can form a ring that can contain one or more double bonds and can contain one or more additional carbon atoms;

$-\text{SR}$, where R is hydrogen or an alkyl group or an aryl group and more specifically where R is hydrogen, methyl, ethyl, propyl, butyl, or a phenyl group, which are optionally substituted;

$-\text{SO}_2\text{R}$, or $-\text{SOR}$, where R is an alkyl group or an aryl group and more specifically where R is a methyl, ethyl, propyl, butyl, or phenyl group, all of which are optionally substituted;

–OCOOR, where R is an alkyl group or an aryl group;

–SO₂N(R)₂, where each R, independently of each other R, is a hydrogen, or an alkyl group, or an aryl group all of which are optionally substituted and wherein R and R can form a ring that can contain one or more double bonds and can contain one or more additional carbon atoms;

–OR, where R is H, an alkyl group, an aryl group, or an acyl group all of which are optionally substituted. In a particular example R can be an acyl yielding –OCOR'', wherein R'' is a hydrogen or an alkyl group or an aryl group and more specifically where R'' is methyl, ethyl, propyl, butyl, or phenyl groups all of which groups are optionally substituted.

Specific substituted alkyl groups include haloalkyl groups, particularly trihalomethyl groups and specifically trifluoromethyl groups. Specific substituted aryl groups include mono-, di-, tri-, tetra- and pentahalo-substituted phenyl groups; mono-, di-, tri-, tetra-, penta-, hexa-, and hepta-halo-substituted naphthalene groups; 3- or 4-halo-substituted phenyl groups, 3- or 4-alkyl-substituted phenyl groups, 3- or 4-alkoxy-substituted phenyl groups, 3- or 4-RCO-substituted phenyl, 5- or 6-halo-substituted naphthalene groups. More specifically, substituted aryl groups include acetylphenyl groups, particularly 4-acetylphenyl groups; fluorophenyl groups, particularly 3-fluorophenyl and 4-fluorophenyl groups; chlorophenyl groups, particularly 3-chlorophenyl and 4-chlorophenyl groups; methylphenyl groups, particularly 4-methylphenyl groups; and methoxyphenyl groups, particularly 4-methoxyphenyl groups.

As to any of the above groups that contain one or more substituents, it is understood that such groups do not contain any substitution or substitution patterns which are sterically impractical and/or synthetically non-feasible. In addition, the compounds of this invention include all stereochemical isomers arising from the substitution of these compounds.

The invention may be further understood by the following non-limiting examples.

EXAMPLE 1: Properties for Selected Formulations and Testing Methods

Table 1 gives exemplary formulations which were measured as having a modulus in the range 800 MPa to 2000 MPa, a tensile strength of 20 MPa to 55 mPa,

an elongation at yield greater than 4% and a elongation @ break greater than 40% (composition ratios by weight):

Table 1:

Formulation	Composition
Exo10/CEA/NVP	30/50/20
Exo10/PETMP:TATATO	30/70 (2:1.1)
Exo10/CEA/NVP	20/70/10
CN3211/CEA/NVP	20/60/20

- 5 Table 2 gives exemplary formulations which were measured as having a modulus in the range 800 MPa to 2000 MPa, a tensile strength of 20 MPa to 55 mPa, an elongation at yield greater than 4% and a elongation @ break from 30% to 40% (composition ratios by weight): :

Table 2:

Formulation	Composition
Exo108/NVP/CEA	33/33/33
Exo108/CEA/SR833S	30/50/20
CN991/NVP/CEA	20/40/40
CN991/NVP/CN9782	30/60/10
Exo108/IBOA/NVP	20/20/60
CN3211/CEA/IPDI-UDMA	20/60/20
CN3211/CEA/SR833S	20/60/20

10

Protocols

The mixing protocol was as follows. All of the formulations were mixed with a Flacktek SpeedmixerTM (1.5 minutes at 2700 rpm) and contained 0.5 wt% TPO-L as the photoinitiator.

- 15 The curing protocol was as follows. The samples were cured into dog bone molds, 1 mm thickness, 6 mm width and 12 or 35 mm length. Samples were cured

with a 395 nm LED light at an intensity of 10 mW/cm^2 for 45 seconds or with a 385 nm Heraeus NobleCure light at an intensity of 80 mW/cm^2 for 15 seconds.

The tensile properties protocol was as follows. Tensile properties were
5 measured with a TestResources Materials Testing System. The crosshead speed was 2.5 mm/min. The dog bones were 35 mm long for assessment of mechanical properties for Tables 1 and 2.

Table 3: Acrylate Monomers and Oligomers

Product Code	Chemical Name/Classification	Viscosity (cP)
SR 833S	Tricyclodecane dimethanol diacrylate	130 @ 25C
SR 368D	Tris (2-hydroxy ethyl) isocyanurate triacrylate	330 @ 25C
SR 368	Tris (2-hydroxy ethyl) isocyanurate triacrylate	
CN 991	Aliphatic urethane diacrylate oligomer	600 @60C
CN 9782	Aromatic urethane diacrylate oligomer	42000@ 60C
CN 3211	Aliphatic urethane acrylate oligomer	27500 @ 25C
CN 9009	Urethane acrylate	
PU 3201NT	Aliphatic trifunctional methacrylate	15,000 @ 25C
PE210	Bisphenol A Epoxy Acrylate	5,000 @ 60C
TPGDA	Tripropylene glycol diacrylate	15 – 20 @ 25C
PU340	Aliphatic trifunctional acrylate	70,000 @ 25C
ME 2110	Modified epoxy acrylate	4,000 @ 65C
Exo10	Dimethacrylate urethane	816000 @ 25C
Exo 108	Dimethacrylate urethane	176000 @ 25C
IPDI-UDMA	Isophorone Urethane Dimethacrylate	
UDMA	Urethane dimethacrylate	

Table 4: Additional Monomers

Product Code	Chemical Name/Classification	Viscosity (cP)
IBOA	Isobornyl acrylate	7 @ 25C
IBOMA	Isobornyl Methacrylate	
M1130	Trimethyl cyclohexyl acrylate	1 – 10 @ 25C
M151	Tetrahydrofurfuryl methacrylate	10 @ 25C
NVP	1-vinyl-2-pyrrolidinone	2 @ 20C
SR833S	Tricyclodecane dimethanol diacrylate	130 @ 25C
TATATO	1,3,5-Triallyl-1,3,5-triazine-2,4,6(1 <i>H</i> ,3 <i>H</i> ,5 <i>H</i>)-trione	
PETMP	Pentaerythritol tetrakis(3-mercaptopropionate)	
CEA	β -carboxyethylacrylate	73 @ 25C

5

EXAMPLE 2: 3D Printing

For 3D printing, samples were formulated with 0.1 or 0.08 wt% UV blocker (OB+, Mayzo, Suwanee, GA) and 2 or 0.5 wt% photoinitiator. An Auto Desk Ember 3D printer (DLP SLA) was utilized with a 405 nm LED projector and build plate with dimensions of 64 mm by 40 mm. The layer thickness was 25 μ m and the exposure time was 4 seconds/layer. After printing, the parts were rinsed with methanol and post cured with the 385 nm Heraeus NobleCure light for 30 minutes.

CLAIMS

1. A crosslinked polymer for use in an orthodontic appliance, the crosslinked polymer having a tensile modulus from 800 MPa to 2000 MPa, a tensile strength at yield of 20 MPa to 55 MPa, an elongation at yield greater than 4% and an elongation at break greater than 30%.
2. The crosslinked polymer of claim 1, wherein the elongation at yield is less than or equal to 25%.
3. The crosslinked polymer of claim 1, wherein the elongation at break is greater than 40%.
4. The crosslinked polymer of any one of claims 1-3, wherein the elongation at break is less than or equal to 250%.
5. The crosslinked polymer of any one of claims 1-4, wherein said crosslinked polymer is transparent, translucent or opaque.
6. The crosslinked polymer of any one of claims 1-4, wherein said crosslinked polymer is characterized by a transmittance equal to or greater than 80% for light having a wavelength in the visible region.
7. The crosslinked polymer of any one of claims 1-6, wherein at 37°C and 100% relative humidity the remaining load is greater than 10% of the initial load at 24 hours.
8. The crosslinked polymer of any one of claims 1-7, wherein at 37°C and 100% relative humidity the remaining load is greater than 80% of the initial load at 24 hours.

9. The crosslinked polymer of any one of claims 1-8, wherein the crosslinked polymer forms a crosslinked network.
10. The crosslinked polymer of any one of claims 1-9, wherein the crosslinked polymer is biocompatible.
11. The crosslinked polymer of any one of claims 1-10, wherein the crosslinked polymer is selected from the group consisting of polyurethanes, (meth)acrylates, epoxies and copolymers thereof.
12. The crosslinked polymer of any one of claims 1-10, wherein the crosslinked polymer comprises a first repeating unit derived from a urethane (meth)acrylate oligomer and a second repeating unit derived from a vinyl or thiol monomer wherein at least one of the urethane (meth)acrylate oligomer, the vinyl monomer and the thiol monomer comprises at least two polymerizable groups.
13. The crosslinked polymer of claim 12, wherein the amount of the first repeating unit is from 25 to 50 wt% and the amount of the second repeating unit is from 50 to 75 wt%, with the total amount of the first repeating unit and the second repeating unit being greater than or equal to 70 wt%.
14. The crosslinked polymer of claim 12, wherein the urethane (meth)acrylate oligomer is selected from the group consisting of a urethane dimethacrylate oligomer, an isophorone urethane dimethacrylate oligomer, a urethane diacrylate oligomer and a urethane triacrylate oligomer.
15. The crosslinked polymer of claim 12, wherein the first repeating unit is derived from Exothane 108, Exothane 10, IPDI-UDMA, CN991, CN9782, CN3211, CN9009 or PU3201NT.

16. The crosslinked polymer of any one of claims 12-15, wherein the second repeating unit is derived from an acrylate monomer.
17. The crosslinked polymer of any one of claims 1-10, wherein the crosslinked polymer comprises a first repeating unit derived from a first urethane (meth) acrylate oligomer, a second repeating unit derived from a first vinyl or thiol monomer not including a urethane linkage and a third repeating unit derived from a second urethane (meth) acrylate oligomer or a second vinyl or thiol monomer not including a urethane linkage, wherein at least one of the urethane (meth) acrylate oligomer(s) and the vinyl or thiol monomer(s) comprises at least two polymerizable groups.
18. The crosslinked polymer of claim 17, wherein the amount of the first repeating unit is from 15-40 wt%, the amount of the second repeating unit is from 15 to 75 wt% and the amount of the third repeating unit is from 2-60 wt%, with the total amount of the first repeating unit, the second repeating unit and the third repeating unit being greater than or equal to 70 wt%.
19. The crosslinked polymer of claim 17 or claim 18, wherein the first repeating unit is derived from a urethane dimethacrylate oligomer, an isophorone urethane dimethacrylate oligomer, a urethane diacrylate oligomer or a urethane triacrylate oligomer.
20. The crosslinked polymer of claim 17 or claim 18, wherein the first repeating unit is derived from Exothane 108, Exothane 10, IPDI-UDMA, CN991, CN9782, CN3211, CN9009 or PU3201NT.
21. The crosslinked polymer of any one of claims 17-20, wherein the second repeating unit is derived from a vinyl monomer not including a urethane linkage.

22. The crosslinked polymer of any one of claims 17-20, wherein the second repeating unit is derived from 1-vinyl-2-pyrrolidinone (NVP), β -carboxyethylacrylate (CEA), trimethyl cyclohexyl acrylate (TMCHA), tetrahydrofurfuryl methacrylate (THFMA), isobornyl acrylate (IBOA) or isobornyl methacrylate (IBOMA).
23. The crosslinked polymer of any one of claims 17-22, wherein the third repeating unit is derived from a urethane (meth) acrylate oligomer or a vinyl monomer not including a urethane linkage.
24. The crosslinked polymer of any one of claims 17-22, wherein the third repeating unit is derived from SR833S, SR368D, CN9782, CN3211, tris(2-hydroxy Ethyl)isocyanurate triacrylate (M370), tricyclodecane dimethanol diacrylate (TCDDA), PE210, tripropylene glycol diacrylate (TPGDA), PU340, ME2110 or NVP.
25. The crosslinked polymer of any one of claims 17-22, wherein the third repeating unit is derived from a thiol monomer.
26. A light polymerizable liquid composition comprising
a first polymerizable component, wherein the first polymerizable component is a urethane (meth)acrylate oligomer;
a second polymerizable component, wherein the second polymerizable component is a vinyl or thiol monomer; and
a photoinitiator
wherein at least one of the first or second polymerizable component comprises at least two polymerizable groups.
27. The light polymerizable liquid composition of claim 26, wherein the viscosity of the solution is less than 4000 cP at 25°C.

28. The light polymerizable liquid composition of any one of claims 26-27, wherein the amount of the first polymerizable component is from 25 to 50 wt% and the amount of second polymerizable component is from 50 to 75 wt%, with the total amount of the first polymerizable component and the second polymerizable component being greater than or equal to 70 wt%.
29. The light polymerizable liquid composition of any one of claims 26 -28, wherein the first polymerizable component is selected from the group consisting of a urethane dimethacrylate oligomer, an isophorone urethane dimethacrylate oligomer, a urethane diacrylate oligomer and a urethane triacrylate oligomer.
30. The light polymerizable liquid composition of any one of claims 26-28, wherein the first polymerizable component is selected from the group consisting of Exothane 108, Exothane 10, IPDI-UDMA , CN991, CN9782, CN3211, CN9009 and PU3201NT.
31. The light polymerizable liquid composition of any one of claims 26-30, wherein the second polymerizable component is an acrylate monomer.
32. A light polymerizable liquid composition according to claim 26 comprising a first polymerizable component, wherein the first polymerizable component is a first urethane (meth)acrylate oligomer;
a second polymerizable component, wherein the second polymerizable component is a first vinyl or thiol monomer not including a urethane linkage;
a third polymerizable component, wherein the third polymerizable component is a second urethane (meth)acrylate oligomer or a second vinyl or thiol monomer not including a urethane linkage; and
a photoinitiator
wherein at least one of the first, second or third polymerizable components comprises at least two polymerizable groups.

33. The light polymerizable liquid composition of claim 32, wherein the viscosity of the solution is less than 700 cP at 25°C.
34. The light polymerizable liquid composition of any one of claims 32-33, wherein the amount of the first component is from 15-40 wt%, the amount of the second component is from 15 to 75 wt% and the amount of the third component is from 2 to 45 wt%, with the total amount of the first, second and third components being greater than or equal to 70 wt%.
35. The light polymerizable liquid composition of any one of claims 32-34, wherein the first polymerizable component is a urethane dimethacrylate oligomer, an isophorone urethane dimethacrylate oligomer a urethane diacrylate oligomer or a urethane triacrylate oligomer.
36. The light polymerizable liquid composition of any one of claims 32-34, wherein the first polymerizable component is selected from the group consisting of Exothane 108, Exothane 10, IPDI-UDMA , CN991, CN9782, CN3211, CN9009 or PU3201NT.
37. The light polymerizable liquid composition of any one of claims 32-36, wherein the second polymerizable component is a vinyl monomer not including a urethane linkage.
38. The light polymerizable liquid composition of any one of claims 32-36, wherein the second polymerizable component is selected from the group consisting of 1-vinyl-2-pyrrolidinone (NVP), β -carboxyethylacrylate(CEA), trimethyl cyclohexyl acrylate (TMCHA), tetrahydrofurfuryl methacrylate (THFMA) isobornyl acrylate (IBOA) and isobornyl methacrylate (IBOMA).

39. The light polymerizable liquid composition of any one of claims 32-38, wherein the third polymerizable component is a urethane (meth)acrylate oligomer or a vinyl monomer not including a urethane linkage.
40. The light polymerizable liquid composition of any one of claims 32-38, wherein the third polymerizable component is selected from the group consisting of SR833S, SR368D, CN9782, CN3211, tris(2-hydroxy ethyl)isocyanurate triacrylate (M370), tricyclodecane dimethanol diacrylate (TCDDA), PE210, , tripropylene glycol diacrylate (TPGDA), PU340, ME2110 and NVP.
41. The light polymerizable liquid composition of any one of claims 32-38, wherein the third polymerizable component is a thiol monomer.
42. A method of making an orthodontic appliance comprising a cross-linked polymer, the method comprising: providing a light polymerizable liquid composition comprising:
- a first polymerizable component , wherein the first polymerizable component is selected from the group consisting of an acrylate monomer or oligomer, a methacrylate monomer or oligomer, a vinyl ester monomer or oligomer, an acrylamide monomer or oligomer; a thiol monomer or oligomer, urethane monomer or oligomer, an epoxy monomer or oligomer and a oxetane monomer or oligomer;
 - a second polymerizable component, wherein the second polymerizable component is a vinyl monomer or oligomer, thiol monomer or oligomer, a urethane monomer or oligomer and an epoxy monomer or oligomer ; and
 - a photoinitiator;
- wherein at least one of the first and second polymerizable components comprises at least two polymerizable groups; and fabricating the cross-linked polymer by a direct fabrication technique.


43. The method of claim 42, wherein said first polymerizable component is selected from the group consisting of: an acrylate, a methacrylate, a vinyl ester, a polyurethane including at least one acrylate end group and a polyurethane including at least one epoxy end group.
44. The method of claim 42, wherein said first polymerizable component is selected from the group consisting of: tetraethylene glycol diacrylate (E4-A), diisopropyl acrylamide (DPA), diisobutylacrylamide (DBA), 2-(2-ethoxy-ethoxy) ethyl acrylate, trimethylolpropanetriacrylate (TTA) and urethanedimethacrylate (UDMA).
45. The method of claim 42 wherein the first polymerizable component is a urethane dimethacrylate oligomer, an isophorone urethane dimethacrylate oligomer a urethane diacrylate oligomer or a urethane triacrylate oligomer.
46. The method of claim 42, wherein the first polymerizable component is selected from the group consisting of Exothane 108, Exothane 10, IPDI-UDMA , CN991, CN9782, CN3211, CN9009 and PU3201NT.
47. The method of any one of claims 42-46, wherein the second polymerizable component is a vinyl monomer.
48. The method of any one of claims 42-46, wherein said second polymerizable component is selected from the group of consisting of: diacrylate, triacrylate, acyclic diacrylate , cyclic diacrylate, methacrylate, vinyl ester, polyurethane including at least one acrylate end group and polyurethane including at least one epoxy end group.
49. The method of any one of claims 42-46, wherein the second polymerizable component is selected from the group consisting of 1-vinyl-2-pyrrolidinone (NVP), β -carboxyethylacrylate (CEA), trimethyl cyclohexyl acrylate

(TMCHA), tetrahydrofurfuryl methacrylate (THFMA) isobornyl acrylate (IBOA) and isobornyl methacrylate (IBOMA).

50. The method of any one of claims 42-49, wherein the amount of the first polymerizable component is from 15-40 wt% and the amount of the second component is from 15 to 75 wt%.
51. The method of any one of claims 42-50, wherein said light polymerizable liquid composition further comprises a third polymerizable component, wherein the third polymerizable component is a urethane (meth)acrylate oligomer or a vinyl or thiol monomer not including a urethane linkage.
52. The method of claim 51, wherein the third polymerizable component is selected from the group consisting of SR833S, SR368D, CN9782, CN3211, tris(2-hydroxy ethyl)isocyanurate triacrylate (M370), tricyclodecane dimethanol diacrylate (TCDDA), PE210, tripropylene glycol diacrylate (TPGDA), PU340, ME2110 and NVP.
53. The method of any one of claims 51-52, wherein the amount of the first component is from 15-40 wt%, the amount of the second component is from 15 to 75 wt% and the amount of the third component is from 2 to 60 wt%, with the total amount of the first, second and third components being greater than or equal to 70 wt%.
54. The method of any one of claims 42-53, wherein said light polymerizable liquid composition further comprises a radical stabilizer, inhibitor, filler, reactive diluent, cross-linker or any combination of these.
55. The method of any one of claims 42-54, wherein said light polymerizable liquid composition has a viscosity less than 4000 cP at 25°C.

56. The method of any one of claims 42-55, wherein the liquid polymerizable composition is exposed to light in said direct fabrication technique.
57. The method of any one of claims 42-56, wherein the direct fabrication technique is selected from the group consisting of:
a stereolithographic (SLA) technique;
a digital light processing (DLP) technique;
a continuous liquid interface production technique;
a micro- stereolithographic (μ -SLA) technique;
a two photon polymerization technique; and
a material jetting technique.
58. The method of any one of claims 42-57, further comprising an additional curing step following direct fabrication of the crosslinked polymer.
59. The method of any one of claims 42-58, further comprising a step of extracting non-polymerized components from the crosslinked polymer.
60. The method of any one of claims 52-59, in which the light polymerizable liquid is according to any one of claims 26-41.
61. The method of any one of claims 52-60, in which the cross-linked polymer is according to any one of claims 1 to 25.
62. Use of the light polymerizable liquid according to any one of claims 26-31 to produce a cross-linked polymer according to claim 12.
63. Use of the light polymerizable liquid according to any one of claims 32-41 to produce a cross-linked polymer according to claim 17.

64. An orthodontic appliance comprising, consisting of or consisting essentially of a cross linked polymer according to any one of claims 1 to 25.
65. An orthodontic appliance according to claim 64, which is a brace, a retainer or a shell aligner.

*Fig. 1A*




Fig. 1B




Fig. 1C

INTERNATIONAL SEARCH REPORT

International application No
PCT/IB2016/000970

A. CLASSIFICATION OF SUBJECT MATTER
INV. A61C7/08 B33Y10/00
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61C B33Y

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EP0-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2006/078688 A1 (DESIMONE JOSEPH M [US] ET AL) 13 April 2006 (2006-04-13) paragraphs [0001], [0016], [0021], [0030]	1-11, 64, 65
X	US 2012/231232 A1 (XU PINGYONG [US] ET AL) 13 September 2012 (2012-09-13) paragraphs [0002], [0013], [0014], [0032] - [0038], [0045] - [0050]; example 1	26, 29-32, 34, 35, 37-40, 42, 47-54, 56, 57, 60, 62, 63

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

28 September 2016

Date of mailing of the international search report

05/10/2016

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Plehiens, Mark

INTERNATIONAL SEARCH REPORT

International application No
PCT/IB2016/000970

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2003/003172 A1 (STANGE FRANK [DE] ET AL) 2 January 2003 (2003-01-02) paragraphs [0079], [0080] -----	26, 32, 37

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/IB2016/000970

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2006078688 A1	13-04-2006	US 2006078688 A1	13-04-2006
		US 2010065976 A1	18-03-2010
		US 2011062609 A1	17-03-2011
		WO 2006044012 A1	27-04-2006

US 2012231232 A1	13-09-2012	CN 103547630 A	29-01-2014
		EP 2683774 A1	15-01-2014
		EP 2774954 A1	10-09-2014
		US 2012231232 A1	13-09-2012
		WO 2012121884 A1	13-09-2012

US 2003003172 A1	02-01-2003	CA 2378419 A1	22-09-2002
		DE 10114243 A1	02-10-2002
		EP 1243230 A2	25-09-2002
		JP 2002315760 A	29-10-2002
		US 2003003172 A1	02-01-2003
		US 2005131098 A1	16-06-2005
