



US010966708B2

(12) **United States Patent**  
**Kostrzewski**

(10) **Patent No.:** **US 10,966,708 B2**

(45) **Date of Patent:** **\*Apr. 6, 2021**

(54) **STITCHING END EFFECTOR**

(71) Applicant: **Covidien LP**, Mansfield, MA (US)

(72) Inventor: **Stanislaw Kostrzewski**, Newtown, CT (US)

(73) Assignee: **Covidien LP**, Mansfield, MA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 178 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/279,096**

(22) Filed: **Feb. 19, 2019**

(65) **Prior Publication Data**

US 2019/0175167 A1 Jun. 13, 2019

**Related U.S. Application Data**

(63) Continuation of application No. 15/271,831, filed on Sep. 21, 2016, now Pat. No. 10,245,024, which is a (Continued)

(51) **Int. Cl.**

**A61B 17/04** (2006.01)

**A61B 17/00** (2006.01)

**A61B 17/06** (2006.01)

(52) **U.S. Cl.**

CPC .... **A61B 17/0469** (2013.01); **A61B 17/00234** (2013.01); **A61B 17/0491** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC . A61B 17/04; A61B 17/0469; A61B 17/0482; A61B 17/0491; A61B 2017/0472; A61B 2017/0496

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,822,330 A 9/1931 Ainslie

2,327,353 A 8/1943 Karle

(Continued)

FOREIGN PATENT DOCUMENTS

DE 4423881 C1 10/1995

EP 0592244 A2 4/1994

(Continued)

OTHER PUBLICATIONS

European Search Report dated Oct. 7, 2015, issued in European Application No. 15167797.

(Continued)


*Primary Examiner* — Ryan J. Severson

(57)

**ABSTRACT**

A stitching assembly includes upper and lower cradles, upper and lower needles, and first and second sutures supported by the upper and lower needles, respectively. The cradles move along a curved path in relation to the carriages between advanced and retracted positions. When each cradle is moved from the retracted position towards the advanced position, a stitch loop is formed when the respective needle is retracted. This process is repeated alternating between the first and second cradles with the upper and lower needles passing through the previous stitch loop formed by the other needle before passing through the tissue.

**20 Claims, 22 Drawing Sheets**



<b>Related U.S. Application Data</b>						
	continuation of application No. 14/507,900, filed on Oct. 7, 2014, now Pat. No. 9,468,434.					
(60)	Provisional application No. 62/006,922, filed on Jun. 3, 2014.					
(52)	<b>U.S. Cl.</b> CPC ..... <i>A61B 2017/0472</i> (2013.01); <i>A61B 2017/0608</i> (2013.01)					
(56)	<b>References Cited</b>					
	U.S. PATENT DOCUMENTS					
	3,073,311 A	1/1963	Tibbs et al.	5,674,230 A	10/1997	Tovey et al.
	3,123,077 A	3/1964	Alcamo	5,681,331 A	10/1997	de la Torre et al.
	4,236,470 A	12/1980	Stenson	5,690,652 A	11/1997	Wurster et al.
	4,417,532 A	11/1983	Yasukata	5,690,653 A	11/1997	Richardson et al.
	4,890,615 A	1/1990	Caspari et al.	5,700,272 A	12/1997	Gordon et al.
	4,923,461 A	5/1990	Caspari et al.	5,702,408 A	12/1997	Wales et al.
	4,935,027 A	6/1990	Yoon	5,715,942 A	2/1998	Li et al.
	5,037,433 A	8/1991	Wilk et al.	5,728,107 A	3/1998	Zlock et al.
	5,042,707 A	8/1991	Taheri	5,728,109 A	3/1998	Schulze et al.
	5,080,663 A	1/1992	Mills et al.	5,728,113 A	3/1998	Sherts
	5,100,421 A	3/1992	Christoudias	5,730,747 A	3/1998	Ek et al.
	5,100,430 A	3/1992	Avellanet et al.	5,741,277 A	4/1998	Gordon et al.
	5,209,747 A	5/1993	Knoepfler	5,746,751 A	5/1998	Sherts
	5,271,543 A	12/1993	Grant et al.	5,749,898 A	5/1998	Schulze et al.
	5,300,082 A	4/1994	Sharpe et al.	5,752,973 A	5/1998	Kieturakis
	5,308,353 A	5/1994	Beurrier	5,755,729 A	5/1998	de la Torre et al.
	5,314,445 A	5/1994	Heidmueller nee Degwitz et al.	5,759,188 A	6/1998	Yoon
	5,330,502 A	7/1994	Hassler et al.	5,766,196 A	6/1998	Griffiths
	5,336,229 A	8/1994	Noda	5,779,646 A	7/1998	Koblish et al.
	5,350,391 A	9/1994	Iacovelli	5,792,153 A	8/1998	Swain et al.
	5,358,498 A	10/1994	Shave	5,792,165 A	8/1998	Klieman et al.
	5,364,408 A	11/1994	Gordon	5,797,537 A	8/1998	Oberlin et al.
	5,374,275 A	12/1994	Bradley et al.	5,797,927 A	8/1998	Yoon
	5,374,277 A	12/1994	Hassler	5,797,928 A	8/1998	Kogasaka
	5,387,221 A	2/1995	Bisgaard	5,814,054 A	9/1998	Kortenbach et al.
	5,389,103 A	2/1995	Melzer et al.	5,814,069 A	9/1998	Schulze et al.
	5,391,176 A	2/1995	de la Torre	5,817,119 A	10/1998	Klieman et al.
	5,403,342 A	4/1995	Tovey et al.	5,827,323 A	10/1998	Klieman et al.
	5,405,352 A	4/1995	Weston	5,843,126 A	12/1998	Jameel
	5,439,478 A	8/1995	Palmer	5,860,990 A	1/1999	Nobles et al.
	5,454,823 A	10/1995	Richardson et al.	5,865,836 A	2/1999	Miller
	5,454,827 A	10/1995	Aust et al.	5,871,488 A	2/1999	Tovey et al.
	5,458,609 A	10/1995	Gordon et al.	5,876,412 A	3/1999	Piraka
	5,462,560 A	10/1995	Stevens	5,893,592 A	4/1999	Schulze et al.
	5,472,446 A	12/1995	de la Torre	5,897,563 A	4/1999	Yoon et al.
	5,478,344 A	12/1995	Stone et al.	5,906,630 A	5/1999	Anderhub et al.
	5,480,406 A	1/1996	Nolan et al.	5,908,428 A	6/1999	Scirica et al.
	5,496,334 A	3/1996	Klundt et al.	5,911,727 A	6/1999	Taylor
	5,527,323 A	6/1996	Jervis et al.	5,928,136 A	7/1999	Barry
	5,540,703 A	7/1996	Barker, Jr. et al.	5,931,855 A	8/1999	Buncke
	5,540,704 A	7/1996	Gordon et al.	5,938,668 A	8/1999	Scirica et al.
	5,540,706 A	7/1996	Aust et al.	5,941,430 A	8/1999	Kuwabara
	5,549,617 A	8/1996	Green et al.	5,947,982 A	9/1999	Duran
	5,549,637 A	8/1996	Crainich	5,947,983 A	9/1999	Solar et al.
	5,562,686 A	10/1996	Sauer et al.	5,954,731 A	9/1999	Yoon
	5,564,615 A	10/1996	Bishop et al.	5,954,733 A	9/1999	Yoon
	5,571,090 A	11/1996	Sherts	5,957,937 A	9/1999	Yoon
	5,573,286 A	11/1996	Rogozinski	5,980,538 A	11/1999	Fuchs et al.
	5,575,799 A	11/1996	Bolanos et al.	5,984,932 A	11/1999	Yoon
	5,575,800 A	11/1996	Gordon	5,993,466 A	11/1999	Yoon
	5,582,617 A	12/1996	Klieman et al.	5,993,467 A	11/1999	Yoon
	5,591,181 A	1/1997	Stone et al.	5,997,565 A	12/1999	Inoue
	5,601,224 A	2/1997	Bishop et al.	6,004,332 A	12/1999	Yoon et al.
	5,620,415 A	4/1997	Lucey et al.	6,017,358 A	1/2000	Yoon et al.
	5,628,756 A	5/1997	Barker, Jr. et al.	6,027,522 A	2/2000	Palmer
	5,630,825 A	5/1997	de la Torre et al.	6,051,006 A	4/2000	Shluzas et al.
	5,632,751 A	5/1997	Piraka	6,071,289 A	6/2000	Stefanchik et al.
	5,643,293 A	7/1997	Kogasaka et al.	6,077,287 A	6/2000	Taylor et al.
	5,643,294 A	7/1997	Tovey et al.	6,080,180 A	6/2000	Yoon et al.
	5,662,664 A	9/1997	Gordon et al.	6,086,601 A	7/2000	Yoon
	5,662,666 A	9/1997	Onuki et al.	6,119,913 A	9/2000	Adams et al.
	5,674,229 A	10/1997	Tovey et al.	6,126,665 A	10/2000	Yoon
				6,126,666 A	10/2000	Trapp et al.
				6,139,563 A	10/2000	Cosgrove, III et al.
				6,143,005 A	11/2000	Yoon et al.
				6,171,316 B1	1/2001	Kovac et al.
				6,206,893 B1	3/2001	Klein et al.
				6,214,028 B1	4/2001	Yoon et al.
				6,223,100 B1	4/2001	Green
				6,224,614 B1	5/2001	Yoon
				6,261,307 B1	7/2001	Yoon et al.
				6,277,132 B1	8/2001	Brhel
				6,319,262 B1	11/2001	Bates et al.
				6,332,889 B1	12/2001	Sancoff et al.
				6,346,111 B1	2/2002	Gordon et al.
				6,358,259 B1	3/2002	Swain et al.
				6,494,888 B1	12/2002	Laufer et al.
				6,506,196 B1	1/2003	Laufer
				6,517,539 B1	2/2003	Smith et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,533,795 B1	3/2003	Tran et al.	7,837,696 B2	11/2010	Modesitt et al.
6,533,796 B1	3/2003	Sauer et al.	7,842,047 B2	11/2010	Modesitt et al.
6,562,052 B2	5/2003	Nobles et al.	7,842,048 B2	11/2010	Ma
6,569,105 B1	5/2003	Kortenbach et al.	7,846,170 B2	12/2010	Modesitt et al.
6,582,450 B2	6/2003	Ouchi	7,850,701 B2	12/2010	Modesitt et al.
6,596,015 B1	7/2003	Pitt et al.	7,883,517 B2	2/2011	Pantages et al.
6,599,310 B2	7/2003	Leung et al.	7,883,519 B2	2/2011	Oren et al.
6,638,287 B2	10/2003	Danitz	7,887,554 B2	2/2011	Stokes et al.
6,663,639 B1	12/2003	Laufer et al.	7,935,128 B2	5/2011	Rioux et al.
6,663,641 B1	12/2003	Kovac et al.	7,947,052 B2	5/2011	Baxter, III et al.
6,666,854 B1	12/2003	Lange	7,947,053 B2	5/2011	McKay et al.
6,676,676 B2	1/2004	Danitz et al.	7,951,157 B2	5/2011	Gambale
6,719,764 B1	4/2004	Gellman et al.	7,967,832 B2	6/2011	Chu
6,719,765 B2	4/2004	Bonutti	7,967,842 B2	6/2011	Bakos
6,743,239 B1	6/2004	Kuehn et al.	7,972,344 B2	7/2011	Murray et al.
6,743,240 B2	6/2004	Smith et al.	7,976,552 B2	7/2011	Suzuki
6,755,843 B2	6/2004	Chung et al.	8,197,510 B2	6/2012	Nobles
6,773,441 B1	8/2004	Laufer et al.	8,292,903 B2	10/2012	Dreyfus et al.
6,786,913 B1	9/2004	Sancoff et al.	8,348,962 B2	1/2013	Nobles et al.
6,821,285 B2	11/2004	Laufer et al.	8,747,424 B2	6/2014	Taylor et al.
6,835,200 B2	12/2004	Laufer et al.	9,468,434 B2	10/2016	Kostrzewski
6,889,116 B2	5/2005	Jinno	2001/0023352 A1	9/2001	Gordon et al.
6,911,034 B2	6/2005	Nobles et al.	2002/0010480 A1	1/2002	Sancoff et al.
6,936,054 B2	8/2005	Chu	2002/0045908 A1	4/2002	Nobles et al.
6,936,061 B2	8/2005	Sasaki	2002/0049453 A1	4/2002	Nobles et al.
6,955,643 B2	10/2005	Gellman et al.	2002/0065526 A1	5/2002	Oren et al.
6,972,017 B2	12/2005	Smith et al.	2002/0072702 A1	6/2002	Quay
6,981,628 B2	1/2006	Wales	2002/0128666 A1	9/2002	Sancoff et al.
6,991,635 B2	1/2006	Takamoto et al.	2002/0173800 A1	11/2002	Dreyfuss et al.
6,997,931 B2	2/2006	Sauer et al.	2002/0198542 A1	12/2002	Yamamoto et al.
6,997,932 B2	2/2006	Dreyfuss et al.	2003/0009195 A1	1/2003	Field
7,011,668 B2	3/2006	Sancoff et al.	2003/0014077 A1	1/2003	Leung et al.
7,033,370 B2	4/2006	Gordon et al.	2003/0045891 A1	3/2003	Yamamoto et al.
7,037,315 B2	5/2006	Sancoff et al.	2003/0105475 A1	6/2003	Sancoff et al.
7,041,111 B2	5/2006	Chu	2003/0105476 A1	6/2003	Sancoff et al.
7,052,489 B2	5/2006	Griego et al.	2003/0114863 A1	6/2003	Field
RE39,152 E	6/2006	Aust et al.	2003/0116670 A1	6/2003	Gentry
7,060,077 B2	6/2006	Gordon et al.	2003/0171761 A1	9/2003	Sancoff et al.
7,063,710 B2	6/2006	Takamoto et al.	2003/0233104 A1	12/2003	Gellman et al.
7,063,715 B2	6/2006	Onuki et al.	2003/0233107 A1	12/2003	Gellman et al.
7,090,686 B2	8/2006	Nobles et al.	2003/0233108 A1	12/2003	Gellman et al.
7,107,124 B2	9/2006	Green	2004/0006352 A1	1/2004	Nobles et al.
7,153,314 B2	12/2006	Laufer et al.	2004/0010245 A1	1/2004	Cerier et al.
7,191,900 B2	3/2007	Opie et al.	2004/0059350 A1	3/2004	Gordon et al.
7,192,437 B2	3/2007	Shalaby	2004/0060410 A1	4/2004	Leung et al.
7,211,093 B2	5/2007	Sauer et al.	2004/0068272 A1	4/2004	Sauer et al.
7,218,972 B2	5/2007	Rodriguez	2004/0087976 A1	5/2004	DeVries et al.
7,232,448 B2	6/2007	Battles et al.	2004/0088003 A1	5/2004	Leung et al.
7,244,260 B2	7/2007	Koseki	2004/0092963 A1	5/2004	Moll et al.
7,248,944 B2	7/2007	Green	2004/0092967 A1	5/2004	Sancoff et al.
7,468,068 B2	12/2008	Kolster	2004/0181243 A1	9/2004	Chu et al.
7,601,164 B2	10/2009	Wu	2004/0193186 A1	9/2004	Kortenbach et al.
7,645,284 B2	1/2010	Burbank et al.	2004/0199184 A1	10/2004	Topper et al.
7,666,194 B2	2/2010	Field et al.	2004/0254605 A1*	12/2004	DiFrancesco
7,691,112 B2	4/2010	Chanduszko et al.	2005/0043747 A1	2/2005	Field et al.
7,704,261 B2	4/2010	Sakamoto et al.	2005/0085832 A1	4/2005	Sancoff et al.
7,708,747 B2	5/2010	Bjerkén	2005/0096694 A1	5/2005	Lee
7,722,630 B1	5/2010	Stone et al.	2005/0126876 A1	6/2005	Simmons
7,731,726 B2	6/2010	Belhe et al.	2005/0165419 A1	7/2005	Sauer et al.
7,736,372 B2	6/2010	Reydel et al.	2005/0228407 A1	10/2005	Nobles et al.
7,758,597 B1	7/2010	Tran et al.	2005/0256533 A1	11/2005	Roth et al.
7,758,598 B2	7/2010	Conlon et al.	2006/0025817 A1	2/2006	Ortiz et al.
7,766,925 B2	8/2010	Stokes et al.	2006/0036232 A1	2/2006	Primavera et al.
7,771,438 B2	8/2010	Dreyfuss et al.	2006/0052801 A1	3/2006	Dreyfuss et al.
7,776,059 B2	8/2010	Craig	2006/0069396 A1	3/2006	Meade et al.
7,776,066 B2	8/2010	Onuki et al.	2006/0111209 A1	5/2006	Hinman et al.
7,780,701 B1	8/2010	Meridew et al.	2006/0235304 A1	10/2006	Harhen et al.
7,784,612 B2	8/2010	Kanda et al.	2006/0253126 A1	11/2006	Bjerkén et al.
7,798,325 B2	9/2010	Wizemann et al.	2006/0282091 A1	12/2006	Shelton et al.
7,814,630 B2	10/2010	Price et al.	2006/0282093 A1	12/2006	Shelton et al.
7,815,654 B2	10/2010	Chu	2007/0005110 A1	1/2007	Collier et al.
7,815,659 B2	10/2010	Conlon et al.	2007/0043385 A1	2/2007	Nobles et al.
7,828,812 B2	11/2010	Stokes et al.	2007/0276413 A1	11/2007	Nobles
7,833,235 B2	11/2010	Chu	2008/0071296 A1	3/2008	Klundert et al.
7,833,237 B2	11/2010	Sauer	2008/0188868 A1	8/2008	Weitzner et al.
			2008/0312688 A1	12/2008	Nawrocki et al.
			2009/0312773 A1	12/2009	Cabrera et al.
			2010/0268256 A1	10/2010	Dreyfuss et al.

A61B 17/0625  
606/205

(56)

**References Cited**

U.S. PATENT DOCUMENTS

2012/0283754	A1	11/2012	Murillo et al.
2012/0310220	A1	12/2012	Malkowski et al.
2013/0030450	A1	1/2013	Dreyfuss et al.
2013/0317525	A1	11/2013	Wingardner, Iii et al.
2014/0296880	A1	10/2014	Heneveld
2014/0350576	A1	11/2014	Patel et al.
2015/0327850	A1	11/2015	Kostrzewski
2015/0342599	A1	12/2015	Kostrzewski

FOREIGN PATENT DOCUMENTS


EP	0647431	A2	4/1995
EP	1481628	A1	12/2004
EP	1915957	A2	4/2008
EP	1915966	A1	4/2008
EP	2044890	A1	4/2009
EP	2133028	A2	12/2009
EP	2329773	A1	6/2011
EP	2586382	A2	5/2013
EP	2606834	A2	6/2013
WO	8705122	A1	8/1987
WO	9727807	A1	8/1997

WO	9811814	A2	3/1998
WO	9811829	A1	3/1998
WO	9853745	A1	12/1998
WO	9915090	A1	4/1999
WO	9918859	A1	4/1999
WO	0067834	A1	11/2000
WO	0174254	A1	10/2001
WO	0234147	A1	5/2002
WO	03017850	A2	3/2003
WO	2006061868	A1	6/2006
WO	2008042423	A2	4/2008
WO	2008045333	A2	4/2008

OTHER PUBLICATIONS

Zeiss, Carl, "Universal S 3B Stand", Sep. 15, 2006, XP055216369, [http://www.ophtalword.decosmoshop/pix/a/media/28072015/Zeiss\\_S3\\_Floor\\_Stand\\_User\\_Manual.pdf](http://www.ophtalword.decosmoshop/pix/a/media/28072015/Zeiss_S3_Floor_Stand_User_Manual.pdf).  
 U.S. Appl. No. 14/279,928, filed May 16, 2014, inventor: Stanislaw Kostrzewski.  
 European Search Report dated Sep. 3, 2015, issued in EP Application No. 15170195.

\* cited by examiner



**FIG. 1**




FIG. 2

FIG. 3







FIG. 4




**FIG. 5**




**FIG. 7**



**FIG. 6**



**FIG. 8**



**FIG. 9**







FIG. 10





**FIG. 14**




FIG. 15




FIG. 16







FIG. 17




**FIG. 18**




**FIG. 19**




**FIG. 20**




**FIG. 21**



**FIG. 22**




**FIG. 23**




**FIG. 24**


**FIG. 25**



**FIG. 26**



**FIG. 27**



**FIG. 28**




FIG. 29




FIG. 31

FIG. 30






FIG. 32


FIG. 33




**FIG. 34**




**FIG. 35**



**FIG. 36**



**FIG. 37**



**FIG. 38**

**STITCHING END EFFECTOR****CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 15/271,831, filed Sep. 21, 2016, which is a continuation of U.S. patent application Ser. No. 14/507,900, filed Oct. 7, 2014, now U.S. Pat. No. 9,468,434, which claims the benefit of and priority to U.S. Provisional Patent Application Ser. No. 62/006,922, filed Jun. 3, 2014. The entire disclosure of each of the above applications is incorporated by reference herein.

**BACKGROUND****1. Technical Field**

The present disclosure relates to surgical instruments, specifically, surgical instruments with a stitching end effector for forming stitches.

**2. Background of the Invention**

As medical and hospital costs continue to increase, surgeons are constantly striving to develop advanced surgical techniques. Advances in the surgical field are often related to the development of operative techniques which involve less invasive surgical procedures which reduce overall patient trauma. In this manner, the length of hospital stays and thus, medical costs can be significantly reduced.

One of the truly great advances to reduce the invasiveness of surgical procedures is endoscopic surgery. Endoscopic surgery involves surgery through body walls for example, viewing and/or operating on the ovaries, uterus, gall bladder, bowels, kidneys, appendix, etc. There are many common endoscopic surgical procedures, including arthroscopy, laparoscopy (pelviscopy), gastroscopy and laryngobronchoscopy, just to name a few. Typically, trocars are utilized for creating incisions through which the endoscopic surgery is performed. Trocar tubes or cannula devices are extended into and left in place in the abdominal wall to provide access for endoscopic surgical tools. A camera or endoscope is inserted through a trocar tube to permit the visual inspection and magnification of the body cavity. The surgeon can then perform diagnostic and therapeutic procedures at the surgical site with the aid of specialized instrumentation, such as, forceps, cutters, applicators, and the like which are designed to fit through additional cannulas.

In many surgical procedures, it is often necessary to suture body organs or tissue. Traditionally, suturing was accomplished by hand using a needle attached to a suture material. This procedure required open access to the tissue to be sutured. Upon the advent of endoscopic surgical procedures, endoscopic suturing instruments have been developed. The development of endoscopic suturing instruments is especially challenging because of the small openings through which the suturing of body organs or tissues must be accomplished.

**SUMMARY**

In an aspect of the present disclosure, a stitching assembly includes an upper cradle, an upper carriage, an upper needle, and a first suture. The upper carriage is configured to support the upper cradle for movement along a curved path between an advanced position and a retracted position relative to the

upper carriage. The upper needle is supported by and extends distally from the upper cradle. The first suture is supported by the upper needle. The upper cradle and the upper carriage are configured to draw the first suture through tissue when the upper cradle is moved towards the advanced position and are configured to form a first stitch loop in the first suture when the upper cradle is moved from the advanced position towards the retracted position. In addition, the stitching assembly includes a lower cradle, a lower carriage, a lower needle, and a second suture. The lower carriage is configured to support the lower cradle for movement along a curved path between an advanced position and a retracted position relative to the lower carriage. The lower needle is supported by and extends distally from the lower cradle. The second suture is supported by the lower needle. The lower cradle and the lower carriage are configured to draw the first suture through tissue and the first stitch loop when the lower cradle is moved towards the advanced position and are configured to form a second stitch loop in the second suture when the lower cradle is moved from the advanced position towards the retracted position.

In aspects, the upper needle includes an outer surface and a distal end and the upper carriage includes an upper plow that is positioned adjacent the distal end of the upper needle. The upper plow of the upper carriage and the outer surface of the upper needle being configured to capture a portion of the first suture therebetween as the upper cradle is moved towards the advanced position. In addition, the lower needle includes an outer surface and a distal end and the lower carriage includes a lower plow that is positioned adjacent the distal end of the lower needle. The lower plow of the lower carriage and the outer surface of the lower needle being configured to capture a portion of the second suture therebetween as the lower cradle is moved towards the advanced position.

In some aspects, the upper carriage has a sidewall that defines a cam slot and the upper cradle includes a sidewall including a cam. The cam of the upper cradle is received within the cam slot of the upper carriage. The upper needle may be a curved needle. The cam slot of the upper carriage may be a curved cam slot defining the curved path of the upper cradle. A curvature of the curved path of the upper cradle may correspond to a curvature of the curved upper needle.

In another aspect of the present disclosure, a stitching loading unit includes an inner housing, a jaw member assembly, and a stitching assembly. The inner housing having proximal and distal ends. The jaw member assembly is positioned at the distal end of the inner housing and includes first and second jaw members. The first and second jaw members are moveable relative to one another between open and clamped positions. Each of the first and second jaw members define a longitudinal needle slot positioned parallel to the longitudinal axis of the jaw member. The stitching assembly may be any of the stitching assemblies disclosed herein.

In aspects, the stitching loading unit includes a suture storage and delivery assembly having a suture tension, a first suture recess, a second suture recess, a groove, a conduit, a portion of the first suture, and a portion of the second suture. The first suture recess is defined by and along a length of the inner housing, the first suture recess is positioned proximal to the suture tensioner. The second suture recess is defined by and along a length of the inner housing proximal to the first suture recess. The groove is defined in the inner housing through the first suture recess and into the second suture recess. The conduit is disposed within the groove. The

portion of the first suture is wound around the inner housing in the first suture recess, passes through the suture tensioner, and through the upper needle. The portion of the second suture is wound around the inner housing in the second suture recess, passes through the conduit, passes through the suture tensioner, and passes through the lower needle.

In some aspects, the stitching loading unit includes a drive bar assembly that is disposed within the inner housing. The drive bar assembly includes an upper carriage drive bar, an upper cradle drive bar, a lower carriage drive bar, and a lower cradle drive bar. The upper carriage drive bar includes a distal end that is connected to the upper carriage to move the upper carriage within the upper jaw member. The upper cradle drive bar includes a distal end that is operatively associated with the upper cradle to move the upper cradle between the retracted and advanced positions. The lower carriage drive bar includes a distal end that is connected to the lower carriage to move the lower carriage within the lower jaw member. The lower cradle drive bar includes a distal end that is operatively associated with the lower cradle to move the lower cradle between the retracted and advanced positions. A proximal end of the upper cradle drive bar may be disposed over the upper carriage drive bar distal to a proximal end of the upper carriage drive bar such that the upper cradle is advanced with the upper carriage. A proximal end of the lower cradle drive bar may be disposed over the lower carriage drive bar distal to a proximal end of the lower carriage drive bar such that the lower cradle is advanced with the lower carriage.

In particular aspects, the distal end of the upper cradle drive bar includes a cradle finger that is operatively associated with the upper cradle. In embodiments, the cradle drive finger is flexible. A distal end of the cradle drive finger may be fixed to a surface of the upper cradle such that when the cradle is in the advanced position, the cradle drive finger forms a curve with a surface of the upper cradle. In other embodiments, the cradle drive finger is substantially rigid. The cradle drive finger may include a toothed rack and a surface of the upper cradle may include a pinion. The toothed rack engages the pinion to move the cradle between the retracted and advanced positions.

In certain aspects, the stitching loading unit includes an extension rod assembly disposed within the inner housing. The extension rod assembly including an upper carriage extension rod, an upper cradle extension rod, a lower carriage extension rod, and a lower cradle extension rod. The upper carriage extension rod includes a distal end that is operatively associated with the upper carriage drive bar to longitudinally translate the upper carriage drive bar. The upper cradle extension rod includes a distal end that is operatively associated with the upper cradle drive bar to longitudinally translate the upper cradle drive bar. The lower carriage extension rod includes a distal end that is operatively associated with the lower carriage drive bar to longitudinally translate the lower carriage drive bar. The lower cradle extension rod includes a distal end that is operatively associated with the lower cradle drive bar to longitudinally translate the lower cradle drive bar.

In aspects, the stitching loading unit includes including an I-beam, and a knife defined by the I-beam. The I-beam is positioned within and is longitudinally translatable within a knife slot. The knife slot is defined about the longitudinal axis of each of the first and second jaw members. The knife slot extends from the proximal end of each of the first and second jaw members and towards a distal end of each of the first and second jaw members. The drive bar assembly may include a knife drive bar that has a proximal end connected

to the upper carriage drive bar. A distal end of the knife drive bar is operatively associated with the I-beam to advance the I-beam with the upper carriage drive bar. The first and second jaw members each define a beam groove in an outer surface of the jaw member. The I-beam may include upper and lower flanges integrally formed on upper and lower surfaces thereof. The upper and lower flanges may be received within the beam grooves of the upper and lower jaw member to urge the jaw members towards the clamped position as the I-beam is advanced through the knife slot.

In some aspects, the stitching loading unit includes an articulation assembly having an articulation joint, an articulation pivot, an articulation rod, and an articulation pin. The articulation joint is positioned between a proximal end of the jaw member assembly and a distal end of the inner housing. The articulation pivot passes through the articulation joint. The articulation pivot is orthogonal to and passes through the longitudinal axis of the first and second jaw members when the jaw members are in the clamped position. The articulation rod is disposed within the inner housing and includes a proximal end. The articulation pin passes through the proximal end of the articulation rod and the articulation joint. The articulation pin is parallel to the articulation pivot. The articulation joint is offset from the articulation pivot such that when the articulation rod is longitudinally translated, the jaw member assembly articulates relative to the outer tube about the articulation pivot.

In still another aspect of the present disclosure, a surgical instrument for suturing tissue includes a handle and a stitching loading unit. The stitching loading unit is operatively associated with the handle. The stitching loading unit may be any of the stitching loading units disclosed herein.

In aspects, the handle includes a drive shaft for manipulating the stitching loading unit. The surgical instrument may include an adaptor having proximal and distal ends. The proximal end of the adaptor engages the handle and the distal end of the adaptor receives a connector of the stitching loading unit. The connector is configured to manipulate the stitching assembly of the stitching loading unit. The adaptor is configured to convert rotation of drive shafts of the handle to longitudinal translation to longitudinal translation of the stitching assembly of the stitching loading unit.

In still yet another aspect of the present disclosure, a stitching assembly includes a first jaw member, a second jaw member, a first needle, a first suture, a second needle, and a second suture. The first jaw member has proximal and distal ends and the second jaw member has proximal and distal ends. The first needle is moveable in a stepwise manner between the proximal and distal ends of the first jaw member. The first needle is moveable between a retracted position, where the first needle is disposed within the first jaw member, and an advanced position, where the first needle is extended towards the second jaw member from the first jaw member. The first suture is associated with the first needle. The second needle is moveable in a stepwise manner between the proximal and distal ends of the second jaw member. The second needle is moveable between a retracted position, where the second needle is disposed within the second jaw member, and an advanced position, where the second needle is extended towards the first jaw member from the second jaw member. The second suture is associated with the second needle. In addition, the stitching assembly includes first and second drive bars. The first drive bar is configured at each step of movement of the first needle to move the first needle from the retracted position to the advanced position and to return the first needle to the retracted position. This movement of the first needle forms

5

a suture loop in the first suture through tissue and adjacent the second jaw member. The second drive bar is configured to at each step of movement of the second needle to move the second needle from the retracted position to the advanced position and to return the second needle to the retracted position. This movement of the second needle forms a suture loop in the second suture through tissue and adjacent the first jaw member.

Further, to the extent consistent, any of the aspects described herein may be used in conjunction with any or all of the other aspects described herein.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Various aspects of the present disclosure are described herein below with reference to the drawings, wherein:

FIG. 1 is a front perspective view of an embodiment of a surgical instrument in accordance with the present disclosure including a stitching end effector;

FIG. 2 is a rear perspective view of the stitching end effector of FIG. 1 with the jaws in an open position;

FIG. 3 is a front perspective view of the stitching end effector of FIG. 2 with the jaws in an open position;

FIG. 4 is an exploded view of the stitching end effector of FIG. 2;

FIG. 5 is an enlarged view of the indicated area of detail of FIG. 4;

FIG. 6 is an enlarged view of the indicated area of detail of FIG. 5;

FIG. 7 is an enlarged view of the indicated area of detail of FIG. 5;

FIG. 8 is a front perspective of the drive bar assembly and the stitching assembly of FIG. 5;

FIG. 9 is a cross-sectional view taken along section line "9-9" of FIG. 8;

FIG. 10 is an exploded view of the drive bar assembly illustrated in FIG. 5

FIG. 11 is a top perspective view of the upper carriage extension bar of the drive bar assembly engaged with the upper carriage drive bars of the drive bar assembly;

FIG. 12 is an enlarged view of indicated area of detail of FIG. 11;

FIG. 13 is an enlarged view of indicated area of detail of FIG. 2;

FIG. 14 is a cross-sectional view taken along section line "14-14" of FIG. 2;

FIG. 15 is an exploded perspective view of the knife assembly;

FIG. 16 is a top view of the stitching end effector of FIG. 2 in a non-articulated configuration;

FIG. 17 is a top view of the stitching end effector shown in FIG. 16 in an articulated configuration with a longitudinal axis of the jaw assembly of the end effector defining an angle in relation to a longitudinal axis of the outer tube;

FIG. 18 is an enlarged view of the indicated area of detail of FIG. 10 illustrating the cradle and the carriage of FIG. 10 with the cradle in a retracted configuration;

FIG. 19 is a perspective view of the cradle of FIG. 18 with the carriage removed;

FIG. 20 is an exploded view of the carriage and the cradle of FIG. 18;

FIG. 21 is a perspective view of the cradle and the carriage of FIG. 18 with the cradle in an advanced configuration;

FIG. 22 is a perspective view of the cradle of FIG. 21 with the carriage removed;

6

FIG. 23 is perspective view of another embodiment of a cradle drive finger in accordance with the present disclosure including a rack and pinion with the cradle in a retracted configuration;

FIG. 24 is a perspective view of the cradle drive finger of FIG. 23 with the cradle in an advanced configuration;

FIG. 25 is a front perspective view of the stitching end effector of FIG. 2 with the upper jaw and the outer tube removed;

FIG. 26 is an enlarged view of the indicated area of detail of FIG. 25 with the cradles in the retracted configuration and the needles within the needle slots of the lower jaw;

FIG. 27 is an enlarged view of the indicated area of detail of FIG. 4 of the suture tensioner;

FIG. 28 is a view of the cradles of FIG. 26 in an advanced configuration with the needles extending from the needles slots of the lower jaw;

FIG. 29 is a cross-sectional view of the stitching end effector taken along section line "29-29" of FIG. 16;

FIG. 30 is a cross-sectional view of the stitching end effector of taken along section line "30-30" of FIG. 16;

FIG. 31 is an enlarged view of the indicated area of detail of FIG. 30;

FIG. 32 is a cross-sectional view of the stitching end effector illustrating the drive bar assembly advanced to a clamped position;

FIG. 33 is an enlarged view of the indicated area of detail of FIG. 32;

FIG. 34-38 are a progression of longitudinal side cross-sectional views of the stitching end effector forming first, second, and third stitch loops as the drive bar assembly is manipulated in accordance with the present disclosure.

#### DETAILED DESCRIPTION

Embodiments of the present disclosure are now described in detail with reference to the drawings in which like reference numerals designate identical or corresponding elements in each of the several views. As used herein, the term "clinician" refers to a doctor, a nurse, or any other user, operator, or care provider and may include support personnel. Throughout this description, the term "proximal" refers to the portion of the device or component thereof that is closest to the clinician and the term "distal" refers to the portion of the device or component thereof that is farthest from the clinician.

Referring now to FIG. 1, an exemplary embodiment of a surgical instrument 1 is provided in accordance with present disclosure and includes a handle 10, a stitching adaptor 20, and a stitching loading unit 30. The stitching loading unit 30 is configured to provide a line of stitches along the length of a jaw assembly as will be discussed in detail below. The handle 10 is a powered handle with one or more drive shafts (not shown) that rotate independently of one another. An exemplary embodiment of such a powered handle is disclosed in commonly owned and co-pending U.S. patent application Ser. No. 13/484,975 filed May 31, 2012, and now published as U.S. Patent Publication No. 2012/0253329 on Oct. 4, 2012, the contents of which are incorporated herein by reference in its entirety. It is also contemplated that the handle 10 may be a manually driven handle with one or more output shafts.

The stitching adaptor 20 converts rotary motion of the drive shafts of the handle 10 into linear motion of selected drive bars to manipulate the stitching loading unit 30 as detailed below. The stitching adaptor 20 may include one or more gear trains (not shown) and one or more cams to

convert the rotary motion of the drive shafts of the handle 10 into linear motion of the drive bars. An exemplary embodiment of such a stitching adaptor 20 is disclosed in commonly owned and co-pending U.S. patent application Ser. No. 14/279,928, filed May 16, 2014, now published as U.S. Patent Publication No. 2015/0327850, the contents of which are incorporated herein by reference in its entirety.

With reference to FIGS. 2-4, the stitching loading unit 30 includes an outer tube 32, a jaw assembly 34, and an inner housing 62. A proximal end of the stitching loading unit 30 forms a connector 33 that engages the stitching adaptor 20 to secure the stitching loading unit 30 to the stitching adaptor 20.

The jaw assembly 34 includes a first or upper jaw member 36 and a second or lower jaw member 38. The upper and lower jaw members 36, 38 are moveable relative to one another between an open configuration (FIG. 3) and a closed or clamped configuration (FIG. 32). The upper jaw member 36 defines a longitudinal knife slot 96a disposed along a longitudinal axis of the upper jaw member 36. The lower jaw member 38 defines a longitudinal knife slot 96b disposed along a longitudinal axis of the lower jaw member 38. Each of the knife slots 96a, 96b extends through an inner or tissue contacting surface of a respective one of the jaw members 36, 38 and an outer surface of a respective one of the jaw members 36, 38. Each of the knife slots 96a, 96b extends along the longitudinal axis of a respective one of the jaw members 36, 38 from a proximal end thereof to a point adjacent a distal end of the respective jaw member 36, 38. The outer surface of each of the jaw members 36, 38 defines a longitudinal beam groove 98 for receiving an upper or lower flange 97 of an I-beam 94 (FIG. 33) as detailed below. The beam grooves 98 are disposed about the knife slots 96a, 96b and extend from the proximal end of each of the jaw members 36, 38 to the distal end of the knife slots 96a, 96b.

Each of the jaw members 36, 38 further defines longitudinal needle slots 39. The needle slots 39 are disposed in pairs on opposite sides of the knife slots 96a, 96b. The needle slots 39 of the lower jaw member 38 oppose the needle slots (not shown) of the upper jaw member 36. The distal end of each of the jaw members 36, 38 includes a blunt tip 37 and angled guide surface 37a which are configured to atraumatically contact and guide tissue between the jaw members 36, 38.

The inner housing 62 is generally cylindrical and is disposed within the outer tube 32. The inner housing 62 may include an upper segment 62a and a lower segment 62b which are secured together using known fastening techniques (e.g., welding, gluing, etc.). The inner housing 62 slidably receives a drive bar assembly 40 and an extension rod assembly 70.

Referring to FIGS. 5-14, the drive bar assembly 40 includes upper carriage drive bars 41 (FIG. 7), upper cradle drive bars 42 (FIG. 7), lower carriage drive bars 43 (FIG. 10), and lower cradle drive bars 44 (FIG. 10). A stitching assembly 80 (FIG. 6) is supported on a distal end of the drive bar assembly 80 and includes upper carriages 44, upper cradles 45, lower carriages 46, and lower cradles 47. Each of the drive bars 41-44 translate longitudinally in a stepwise manner (i.e., in a series of distinct steps) within the inner housing 62 to actuate the upper carriages 44, upper cradles 45, lower carriages 46, and lower cradles 47 as detailed below.

Each carriage drive bar 41, 43 is positioned adjacent to and flanked by one of the cradle drive bars 42, 44 (FIGS. 9 and 10). A distal end of each of the upper carriage drive bars 41 is connected, either rigidly or releasably, to one of the

upper carriages 45 such that longitudinal translation of a drive bar 41 effects longitudinal translation of the upper carriage 45 (FIG. 7). Similarly, a distal end of each of the lower carriage drive bars 43 is connected to one of the lower carriages 47 such that longitudinal translation of a drive bar 41 effects longitudinal translation of the lower carriage 47. In embodiments, the distal end of each of the upper carriage drive bars 41 is integrally formed with one of the upper carriages 45 and the distal end of each of the lower carriage drive bars 43 is integrally formed with one of the lower carriages 47. The carriage drive bars 41, 43 may be connected to corresponding carriages 45, 47 in a rigid or releasable manner, for example integrally formed, snap fit, through glue, welding, molding, or via any variety of fasteners, or any other technique known to those of skill in the art.

The proximal ends 41a of the upper carriage drive bars 41 are connected to one another and the proximal ends 42a of each of the upper cradle drive bars 42 are connected to one another (e.g., by welding or gluing) (FIG. 7). Similarly, the proximal ends 43a (FIG. 14) of each of the lower carriage drive bars 43 are connected to one another and the proximal ends 44a (FIG. 14) of each of the lower cradle drive bars 44 are connected to one another. The proximal ends 41a, 42a, 43a, 44a may be connected to corresponding proximal ends 41a, 42a, 43a, 44a in a rigid or releasable manner, for example integrally formed, snap fit, through glue, welding, molding, or via any variety of fasteners, or any other technique known to those of skill in the art.

The proximal ends 42a of the upper cradle drive bars 42 are positioned distal to the proximal ends 41a of the upper carriage drive bars 41 such that when the upper carriage drive bars 41 are advanced, the proximal ends 41a of the upper carriage drive bars 41 engage the proximal ends 42a of the upper cradle drive bars 42 to advance the upper cradle drive bars 42. Similarly, the proximal ends 44a of the lower cradle drive bars 44 are positioned distal to the proximal ends 43a of the lower carriage drive bars 43 such that when the lower carriage drive bars 43 are advanced, the proximal ends 43a of the lower carriage drive bars 43 engage the proximal ends 44a of the lower cradle drive bars 44 to advance the lower cradle drive bars 44. As shown in FIG. 7, the proximal ends 42a of the upper cradle drive bars 42 may be positioned over the upper carriage drive bars 41. Similarly, the proximal ends 44a of the lower cradle drive bars 44 may be positioned over the lower carriage drive bars 43.

As shown in FIGS. 8 and 9, the upper carriage drive bars 41 are connected to the knife drive member 95 such that longitudinal translation of the upper carriage drive bars 41 effects longitudinal translation of the knife drive member 95. Alternatively, it is contemplated that the lower carriage drive bars 43 may be connected to the knife drive member 95 such that longitudinal translation of the lower carriage drive bars 43 effects longitudinal translation of member 95. The carriage drive bars 41, 43 may be connected to the knife drive member 95 in a rigid or releasable manner, for example integrally formed, snap fit, through glue, welding, molding, or via any variety of fasteners, or any other technique known to those of skill in the art.

The proximal ends 41a of the upper carriage drive bars 41 are connected to an upper carriage drive arm 41b and the proximal ends 42a of the upper cradle drive bars 42 are connected to an upper cradle drive arm 42b (FIG. 9). For example, the upper carriage drive arm 41b may be integrally formed with a proximal end 41a of one of the upper carriage drive bars 41 and the upper cradle drive arm 42b may be integrally formed with the proximal end 42a of one of the

upper cradle drive arms **42b**. Alternatively, the upper drive arms **41b**, **42b** may be welded or glued to a respective one of the upper drive bars **41**, **42**. Similarly, the proximal ends **43a** of the lower carriage drive bars **43** are connected to a lower carriage drive arm **43b** and the proximal ends **44a** of the lower cradle drive bars **44** are connected to a lower cradle drive arm **44b** (FIG. 14). The proximal ends **41a**, **42a**, **43a**, **44a** of the drive bars **41**, **42**, **43**, **44** may be connected to corresponding drive arms **41b**, **42b**, **43b**, **44b** in a rigid or releasable manner, for example integrally formed, snap fit, through glue, welding, molding, or via any variety of fasteners, or any other technique known to those of skill in the art.

With particular reference to FIGS. 10-14, the extension rod assembly **70** includes an upper carriage extension rod **72**, an upper cradle extension rod **74**, a lower carriage extension rod **76**, and a lower cradle extension rod **78**. The distal portion of each of the extension rods **72**, **74**, **76**, **78** is engagable with includes an engagement mechanism, such as notch **72a**, **74a**, **76a**, **78a**, configured to engage a respective one of the drive arms **41b**, **42b**, **43b**, **44b** such that movement, for example longitudinal translation, of the extension rods **72**, **74**, **76**, **78** effects movement, for example longitudinal translation, of each of the drive bars **41**, **42**, **43**, **44**, respectively. For example, as shown in FIG. 12, the notch **72a** in the distal portion of the upper cradle extension rod **72** engages the upper carriage drive arm **41a** to axially fix upper cradle extension rod **72** to the upper carriage drive bar **41**. The proximal end of each of the extension rods **72**, **74**, **76**, **78** includes an extension wing **72b**, **74b**, **76b**, **78b** (FIG. 10) positioned proximal to the proximal end of the outer tube **32** of loading unit **30** (FIG. 1) adjacent the connector **33**. The connector **33** is configured to engage the adaptor **20** such that the adaptor **20** can manipulate the extension wings **72b**, **74b**, **76b**, **78b** to operate the loading unit **30**. It is contemplated that the connector **33** may engage a handle or robotic controller which is configured to manipulate the extension wings **72b**, **74b**, **76b**, **78b** to operate the loading unit **30**.

When the extension rod assembly **70** is assembled within the loading unit **30**, the extension rods **72**, **74**, **76**, **78** are slidably disposed within the inner housing **62** of the loading unit **30**. The extension wings or tabs **72b**, **74b**, **76b**, **78b** of the carriage extension rods **72**, **74**, **76**, **78** extend beyond the outer surface of the inner housing **62** (FIG. 13) to facilitate engagement by the adaptor **20** or other controller. It is also contemplated that the loading unit **30** may engage with the adaptor **20** in any manner known to those of skill in the art. For example, the loading unit **30** may engage with the adaptor **20** by a bayonet-type connection, a J-hook type connection, a screw type connection, a spring-detent connection, or any combination thereof. Examples of such connections are disclosed in U.S. patent application Ser. No. 14/279,928, filed May 16, 2014, and U.S. Pat. No. 7,308,998, the contents of each are incorporated herein by reference in its entirety.

Referring also to FIG. 15, the knife assembly **90** includes an I-beam **94** and a knife drive member **95**. The I-beam **94** has a vertical strut **97a** defining a knife **92**, and upper and lower flanges **97** interconnected by the vertical strut **97a**. The knife drive member **95** is coupled to a proximal portion of the I-beam **94** to advance and retract the I-beam **94** as detailed below. As detailed above, the knife drive member **95** is connected to the upper carriage drive bars **41** such that the knife drive member **95** is moved, such as advanced and retracted, in response to movement, such as advancement and retraction, of the upper carriage drive bars **41**.

Referring to FIGS. 16 and 17, the stitching loading unit **30** includes an articulation assembly **50** that includes an articulation member **52**, a mounting member **53**, an articulation pivot **54**, and an articulation pin **56**. The articulation assembly **50** is configured to articulate the jaw assembly **34** about an axis perpendicular to a longitudinal axis of the loading unit **30** between a non-articulated configuration (FIG. 16) and an articulated configuration (FIG. 17). The articulation member **52** is slidably disposed within the inner housing **62** and outer tube **32**. An articulation bar arm **52a** is positioned at the proximal end of the articulation member **52** and is engaged by the adaptor **20** to facilitate longitudinal translation of the articulation member **52** upon actuation of the adaptor **20**. The distal end of the articulation member **52** includes an opening **52b** (FIG. 4) that receives the articulation pin **56** (FIG. 2). The articulation pin **56** passes through the opening **52b** into the mounting member **53**. The mounting member **53** is secured to the proximal end of the jaw assembly **34** and is pivotally connected to the inner housing **62** by the articulation pivot **54**. As the articulation member **52** is advanced within the inner housing **62**, the articulation pin **56**, which is offset from the longitudinal axis of the jaw member assembly **34** and articulation pivot **54**, pivots mounting member **53** to articulate the jaw assembly **34** (FIG. 28). It is understood that as the articulation member **52** is retracted, the articulation pin **56** will pivot the mounting member **53** in the opposite direction to pivot the jaw assembly **34** in the opposite direction. Each of the carriage drive bars **41**, **43**, the cradle drive bars **42**, **44**, and the knife drive member **95** is flexible to facilitate actuation of the loading unit **30** when the jaw assembly **34** is articulated.

Referring now to FIGS. 18-22, operation of the stitching assembly **80** is described in accordance with the present disclosure with an exemplary upper cradle **46** and an exemplary upper carriage **45**. As illustrated, an upper carriage drive bar **41** is connected to the upper carriage **45** and an upper cradle drive bar **42** is connected to the upper cradle **46**.

Each upper carriage **45** includes a pair of distally located, spaced sidewalls **45a**. Each of the sidewalls **45a** defines an at least partially curved or arced cam slot **82**. The upper cradle **46** includes curved or arced cams **83** which protrude from each side of the upper cradle **46**. The upper cradle **46** defines suture passages **63** (FIG. 20) which extend through the upper cradle **46**. A hollow curved or arced needle **81** is secured to the upper cradle **46** adjacent each suture passage **63** such that a suture **61** (FIG. 2) may pass through the suture passage **63** and out a distal end of the needle **81** as detailed below. The arc of the cam slot **82** is substantially similar to the arc of the needles **81**. Each cam **83** of the upper cradle **46** is received within a respective cam slot **82**. A distal end of the upper carriage **45** defines plows **49**. One plow **49** is aligned with a distal end of each of the needles **81**. As shown, each cradle **46** may support a pair of needles **81** with a pair of sutures **61** associated with each pair of needles **81** as detailed below.

The distal end of the upper cradle drive bar **42** includes a cradle drive finger **84** which is operatively associated with the upper cradle **46**. The cradle drive finger **84** translates the upper cradle **46** between a retracted configuration (FIGS. 18 and 19) and an advanced configuration (FIGS. 21 and 22). As shown in FIG. 19, the distal end of the cradle drive finger **84** is secured to an upper surface of the upper cradle **46**. As the cradle drive bar **42** is advanced to advance the cradle drive finger **84** the cam **83** of the cradle **46** is advanced through the arced cam slot **82**. To accommodate the movement of the cradle **46**, a portion of the cradle drive finger **84** is curved or flexible to bend as the upper cradle **46** moves

11

through a curved or arched path defined by the arced cam slot **82**. When the upper cradle **46** is advanced distally towards the advanced configuration, the cams **83** of the upper cradle **46** translate within the cam slots **82** of the upper carriage **45** to advance the needles **81** along an arced path. As the needles **81** are advanced in relation to the upper carriage **45** which is held stationary as the upper cradle **46** is advanced, the body of each needle **81** tracks the distal end of the needle **81** such that the body of the needle **81** passes through a hole in tissue created by the distal end of the needle **81**. When the needles **81** are retracted in response to retraction of the cradle drive bar **42**, the body of each needle **81** passes back through the hole in the tissue such that the distal end of the needle **81** is withdrawn from the tissue. It will be understood, that the lower carriages **47** and lower cradles **48** are manipulated in a similar manner to the upper carriage **45** and the upper cradle **46** described above.

FIGS. **23** and **24** illustrate another embodiment of the presently disclosed cradle drive bar **42'** and cradle **46**. As illustrated the cradle drive bar **41'** includes a cradle drive finger **84'** having a toothed rack **85'**. The cradle **46'** supports a pinion **86'** which meshes with the toothed rack **85'**. The cradle drive finger **84'** is substantially rigid such that as the cradle drive finger **84'** is longitudinally translated as a portion of the toothed rack **85'** remains engaged with the pinion **86'** of the cradle **46'** to transition the cradle **46'** between the retracted and advanced configurations. It is noted that the cradle **46'** is supported by the carriage **45**.

With reference to FIGS. **4** and **25-28**, the stitching loading unit **30** includes a suture storage and delivery assembly **60** disposed generally between the outer tube **32** and inner housing **62**. The suture storage and delivery assembly **60** includes sutures **61** and a suture tensioner **68**. The inner housing **62** defines suture recesses **64** which are separated by annular rings **64a**. Portions of sutures **61** are wound around the inner housing **62** within the suture recesses **64**. The sutures **61** associated with each pair of needles **81** of a respective cradle **46**, **48** are stored in pairs in each suture recess **64**. The inner housing **62** also defines conduit grooves **66** (FIG. **4**) which extend between the suture tensioner **68** and each of the suture recesses **64**. A conduit **65** is disposed within each of the conduit grooves **66**. A length of the sutures **61** is wound around the inner housing **62** within a suture recess **64**, along the conduits **65** and through the suture tensioner **68**. The suture tensioner **68** includes tensioning fingers **68a** (FIG. **27**) that engage the sutures **61** to prevent lengths of sutures **61** from inadvertently being drawn through the suture tensioner **68**. In addition, the suture tensioner **68** permits stitch loops to be formed as detailed below. The sutures **61** are fed from the suture tensioner **68**, through the suture passages **63** of cradle **46**, **48**, and through needles **81**. The conduits **65** prevent interference between the portion of the sutures **61** wound about the inner housing **62** and the portion of the suture **61** extending through the conduit grooves **65**.

When the cradles (e.g., lower cradle **48**) are in the retracted position (FIG. **26**), the needles **81** associated with the cradle are recessed within the needle slots **39** of a respective jaw member (e.g., lower jaw member **38**) beneath a tissue engaging surface **100** of a respective jaw member **36**, **38**. The sutures **61** extend from the distal end of each needle **81** with a portion positioned along an outer surface of the needles **81**. When the needles **81** are advanced from the retracted position to the advanced position (FIG. **25**), the needles **81** extend from the needle slots **39** across the tissue engaging surface **100** of the respective jaw member **36**, **38** (e.g., lower jaw member **38**). As the needles **81** are moved

12

from the retracted position toward the advanced position, a portion of the suture **61** is trapped between the outer surface of the needle **81** and the plow **49** such that as the needle **81** moves an additional portion of sutures **61** are drawn through the suture tensioner **68**. Then, as the needles **81** are returned back to the retracted position within the needle slots **39**, a loop is formed from a portion of the sutures **61** as detailed below.

Referring to FIGS. **29-38**, the operation of the stitching loading unit **30** is detailed in accordance with the present disclosure. In a fully retracted position of the drive bar assembly **40** (FIGS. **29-31**) the upper and lower jaws **36**, **38** are in an open configuration, the upper and lower cradles **46**, **48** are in the retracted position, and the I-beam **94** is in its proximal-most position. The proximal end of the beam grooves **98** include ramps **99** (FIG. **31**). In the proximal-most position of the I-beam **94**, the flanges **97** of the I-beam **94** are positioned proximal to the ramps **99** of the beam grooves **98**. One of the upper and lower jaw members **36**, **38** may include a shield **31** (FIG. **29**) to prevent premature engagement of tissue with the knife **92**.

With tissue (not shown) positioned between the upper and lower jaw members **36**, **38**, the upper carriage drive bars **41** (FIG. **11**) can be longitudinally advanced within the jaw assembly **34** to advance the knife drive member **95**. As discussed above, the upper carriage drive bars **41** are engaged with the upper cradle drive bars **42** such that when the upper carriage drive bars **41** are advanced the upper cradle drive bars **42** are also advanced. As the knife drive member **95** is advanced, the knife drive member **95** advances the I-beam **94** to advance the flanges **97** along the beam grooves **98** of the upper and lower jaw members **36**, **38** as shown in FIGS. **32** and **33**. As the flanges **97** advance into the beam grooves **98**, the flanges **97** of the I-beam **94** engage ramps **99** to cam the jaw members **36**, **38** to the clamped configuration.

After the upper and lower jaw members **36**, **38** are in the clamped configuration, the drive bar assembly **40** (FIG. **10**) can be advanced further to translate the carriages **45**, **47** and the cradles **46**, **48** through the jaw assembly to create stitches with the sutures **61** in tissue clamped between the jaw members **36**, **38**. The carriages **45**, **47** and cradles **46**, **48** advance through the jaw assembly in a stepped manner. For example, the carriage **45** and the cradle **46** are advanced together (a first step) to a first suture location. Next, the cradle **46** is advanced and retracted relative to the carriage **45** to move a needle **81** through tissue to apply a suture loop to tissue. Then the carriage **45** and the cradle **46** are advanced together to a second suture location as detailed below. This process is repeated to form suture loops along the length of the jaw assembly **34**.

Referring to FIG. **34**, the upper carriage **45** is advanced, which also advances the upper cradle **46**, to a position within the jaw assembly **34**. Next, with the upper carriage **45** longitudinally fixed, the upper cradle **46** is advanced to extend needle **81a** from the needle slot **39a** of the upper jaw member **36**, through tissue clamped within the jaw assembly **34**, and into the needle slot **39b** of the lower jaw member **38**. The suture **61a**, which passes through needle **81a**, is pinched between the plow **49a** and the outer surface of needle **81a** as the needle **81a** is moved such that a length of suture **61a** is drawn through the suture tensioner (FIG. **27**). As the needle **81** returns to its retracted position, the length of suture **61a** forms a first stitch loop **161** (FIG. **35**) on the lower side of the tissue clamped within the jaw assembly **34** and adjacent the lower jaw member **38**. It is contemplated that a portion

of the first stitch loop **161** may be disposed within the needle slot **39b** of the lower jaw member **38**.

With reference to FIG. **35**, when the first stitch loop **161** is formed, the upper cradle **46** is returned to the retracted position within the needle slot **39a** of the upper jaw member **36** leaving the first stitch loop **161** on the lower side of tissue clamped within the jaw assembly **34** and adjacent the lower jaw member **38**. Next, the lower carriage **47** and the lower cradle **48** are advanced to locate the distal end of the needle **81b** of the lower cradle **48** in a position to pass through the first stitch loop **161**.

Referring to FIG. **36**, with the lower carriage **47** longitudinally fixed, the lower cradle **48** is advanced to extend the needle **81b** from the needle slot **39b** of the lower jaw member **38**, through the first stitch loop **161**, through tissue clamped within the jaw assembly, and into the needle slot **39a** of the upper jaw member **36**. The suture **61b**, which passes through needle **81b**, is also pinched between the plow **49b** and the outer surface of the needle **81b** as the needle **81b** is extended to draw a length of suture **61b** through the suture tensioner (FIG. **27**). The length of suture **61b** forms a second stitch loop **162** on the upper side of tissue clamped within the jaw assembly **34** distal to the first stitch loop **161** and adjacent the upper jaw member **36**.

With reference to FIG. **37**, when the second stitch loop **162** is formed, the lower cradle **48** is returned to the retracted position within the lower jaw member **38** leaving the second stitch loop **162** on the upper side of tissue clamped within the jaw assembly **34** adjacent the upper jaw member **36**. The upper carriage **45** is advanced within the jaw assembly **34** (a second step) to also advance the upper cradle **46** to locate the distal end of needle **81a** of the upper cradle **46** in a position to pass through the second stitch loop **162**. As the upper carriage **45** is advanced, the knife **92** is advanced to sever tissue clamped within the jaw assembly **34**. It will be appreciated that to reduce bleeding, the knife **92** trails the newly formed stitch loops (e.g., stitch loops **161**, **162**) by at least one stitch loop.

Referring to FIG. **38**, with the upper carriage **45** longitudinally fixed, the upper cradle **46** is advanced to extend needle **81a** from the needle slot **39a** of the upper jaw member **36**, through the second stitch loop **162**, through tissue clamped within the jaw assembly **34**, and into the needle slot **39b** of the lower jaw member **38**. As discussed above, the suture **61a** is pinched between the plow **49a** and the outer surface of needle **81a** as the needle **81a** is extended to tension the first stitch loop **161** on the second stitch loop **162** and to draw an additional length of suture **61a** through the suture tensioner **68** (FIG. **27**). The additional length of the suture **61a** forms a third stitch loop **163** on the lower side of tissue clamped within the jaw assembly **34**. The tensioned stitch loops form stitches.

This process is repeated to form additional stitches until the carriages **45**, **47** reach the end of the jaw members **36**, **38** or until a desired portion of tissue is stitched and cut (e.g., a body lumen is sutured and dissected). To open the jaw members **36**, **38**, the drive bar assembly **40** is returned to the fully retracted position to withdraw the flanges **97** of the I-beam **94** from the beam grooves **98** releasing the jaw members **36**, **38** from the clamped configuration. The suture tensioner **68** maintains tension in the sutures **61** to continuously stitch an additional portion of tissue clamped within the jaw assembly **34**. When the desired portion of tissue is stitched and cut, the excess of sutures **61a**, **61b** is trimmed.

If additional tissue stitching and cutting is required, the jaw assembly **34** is advanced over additional tissue and the process is repeated until the desired portion of tissue is stitched and cut.

It is contemplated that stitching loading unit **30** may define openings in the outer tube **32** proximal to the suture tensioner **68** permitting lengths of the sutures **61** to be stored external to the stitching loading unit **30**. It will be understood that storing lengths of the sutures **61** external to the stitching loading unit **30** may permit the stitching loading unit **30** to be used indefinitely.

Although the jaw members **36**, **38** of the jaw assembly **34** are illustrated as being substantially linear, it is contemplated that jaw members **36**, **38** of jaw assembly **34** may be curved along a length thereof. An exemplary embodiment of such a curved jaw assembly is disclosed in commonly owned U.S. Pat. No. 7,988,028, the contents of which are incorporated herein by reference in its entirety.

While several embodiments of the disclosure have been shown in the drawings, it is not intended that the disclosure be limited thereto, as it is intended that the disclosure be as broad in scope as the art will allow and that the specification be read likewise. Any combination of the above embodiments is also envisioned and is within the scope of the appended claims. Therefore, the above description should not be construed as limiting, but merely as exemplifications of particular embodiments. Those skilled in the art will envision other modifications within the scope and spirit of the claims appended hereto.

What is claimed is:

1. An end effector comprising:

a jaw assembly including a first jaw and a second jaw, the first and second jaws movable relative to one another between open and clamped configurations;

a first needle movable along the first jaw;

a first suture supported by the first needle;

a second needle movable along the second jaw; and

a second suture supported by the second needle, the first needle configured to move along a first curved path between an advanced position and a retracted position, the first needle configured to draw the first suture through tissue and towards the second needle when the first needle moves towards the advanced position, the second needle configured to move along a second curved path between an advanced position and a retracted position, the second needle configured to draw the second suture through tissue and towards the first needle when the second needle moves towards its advanced position.

2. The end effector according to claim 1, wherein the first needle is configured to form a first stitch loop in the first suture when the first needle is moved from its advanced position towards its retracted position.

3. The end effector according to claim 1, wherein the first needle is configured to move distally and towards the second needle as the first needle moves towards its advanced position.

4. The end effector according to claim 1, further comprising a first cradle, the first needle supported by and extending distally from the first cradle.

5. The end effector according to claim 4, further comprising a first carriage moveably supporting the first cradle such that the first cradle moves along the first curved path to move the first needle between its advanced position and its retracted position relative to the first carriage.

6. The end effector according to claim 1, wherein the first needle is curved.

## 15

7. The end effector according to claim 6, wherein the first curved path has a curvature that corresponds to a curvature of the first needle.

8. An end effector comprising:

- a first needle;
- a first suture supported by the first needle;
- a second needle; and
- a second suture supported by the second needle, the first needle configured to move along a first curved path between an advanced position and a retracted position, the first needle configured to draw the first suture through tissue and towards the second needle when the first needle moves towards the advanced position, the second needle configured to move along a second curved path between an advanced position and a retracted position, the second needle configured to draw the second suture through tissue and towards the first needle when the second needle moves towards its advanced position;

wherein the first needle is configured to form a first stitch loop in the first suture when the first needle is moved from its advanced position towards its retracted position and the second needle is configured to draw the second suture through the first stitch loop as the second needle moves towards its advanced position.

9. The end effector according to claim 8, wherein the second needle is configured to form a second stitch loop in the second suture when the second needle is moved from its advanced position towards its retracted position.

10. A loading unit comprising:

- an inner housing having proximal and distal portions;
- a first jaw member supported by the distal portion of the inner housing and defining a first needle slot, the first needle slot extending in a direction parallel to a longitudinal axis of the first jaw member;
- a second jaw member supported by the distal portion of the inner housing and defining a second needle slot, the second needle slot extending in a direction parallel to a longitudinal axis of the second jaw member, the first and second jaw members moveable relative to one another between an open position and a clamped position;
- a first needle movable along the first jaw member between retracted and advanced positions, the first needle also configured to move along a first curved path between an advanced position and a retracted position; and
- a first suture supported by the first needle, the first needle configured to draw the first suture from the first needle slot, through tissue, and towards the second needle slot when the first needle moves towards the advanced position.

11. The loading unit according to claim 10, further comprising:

- a second needle configured to move along a second curved path between an advanced position and a retracted position; and
- a second suture supported by the second needle, the second needle configured to draw the second suture from the second needle slot, through tissue, and towards the first needle slot when the second needle moves towards its advanced position.

12. The loading unit according to claim 11, wherein the first needle is configured to form a first stitch loop in the first suture when the first needle is moved from its advanced position towards its retracted position.

## 16

13. The loading unit according to claim 10, further comprising a suture storage and delivery assembly including:

- a suture tensioner;
- a first suture recess defined by and along a length of the inner housing proximal to the suture tensioner;
- a second suture recess defined by and along a length of the inner housing proximal to the first suture recess;
- a groove defined in the inner housing through the first suture recess and into the second suture recess;
- a conduit disposed within the groove; and
- a portion of the first suture being configured to wind around the inner housing in the first suture recess, pass through the suture tensioner, and pass through the first needle.

14. The loading unit according to claim 10, further comprising:

- a first cradle supporting the first needle, the first needle extending distally from the first cradle; and
- a first carriage moveably supporting the first cradle, the first cradle moveable along the first curved path relative to the first carriage as the first needle moves between its advanced and retracted positions.

15. The loading unit according to claim 14, further comprising a drive bar assembly disposed within the inner housing, the drive bar assembly having:

- a first carriage drive bar including a distal portion connected to the first carriage to move the first carriage within the first jaw member; and
- a first cradle drive bar including a distal portion operatively associated with the first cradle to advance and retract the first cradle relative to the first carriage to move the first needle between its advanced and retracted positions.

16. The loading unit according to claim 14, wherein a proximal portion of the first cradle drive bar is disposed over the first carriage drive bar distal to a proximal end of the first carriage drive bar such that the first cradle is advanced with the first carriage.

17. The loading unit according to claim 10, further comprising a knife assembly, the knife assembly including: an I-beam positioned within and longitudinally translatable within a knife slot, the knife slot defined about the longitudinal axis of each of the first and second jaw members, the knife slot extending from a proximal portion of each of the first and second jaw members towards a distal end of each of the first and second jaw members; and

- a knife defined by the I-beam.

18. A loading unit comprising:

- an inner housing having proximal and distal portions;
- a first jaw member supported by the distal portion of the inner housing and defining a first needle slot, the first needle slot extending in a direction parallel to a longitudinal axis of the first jaw member;
- a second jaw member supported by the distal portion of the inner housing and defining a second needle slot, the second needle slot extending in a direction parallel to a longitudinal axis of the second jaw member, the first and second jaw members moveable relative to one another between an open position and a clamped position;
- a first needle configured to move along a first curved path between an advanced position and a retracted position;
- a first suture supported by the first needle, the first needle configured to draw the first suture from the first needle

17

slot, through tissue, and towards the second needle slot when the first needle moves towards the advanced position;

a second needle configured to move along a second curved path between an advanced position and a retracted position;

a second suture supported by the second needle, the second needle configured to draw the second suture from the second needle slot, through tissue, and towards the first needle slot when the second needle moves towards its advanced position; and

wherein the first needle is configured to form a first stitch loop in the first suture when the first needle is moved from its advanced position towards its retracted position and the second needle is configured to draw the second suture through the first stitch loop as the second needle moves towards its advanced position.

19. A stitching assembly comprising:

- a first jaw member;
- a second jaw member;

18

a first needle moveable in a first direction in a stepwise manner distally through the first jaw member, the first needle being moveable from a retracted position in which the first needle is disposed within the first jaw member to an advanced position in which the first needle is extended from the first jaw member towards the second jaw member;

a first suture associated with the first needle;

a first drive bar configured to, at each step of movement of the first needle, move the first needle in a second direction along a curved path from the retracted position to the advanced position and to return the first needle to the retracted position.

20. The stitching assembly according to claim 19, wherein the first needle is configured to form a first suture loop in the first suture adjacent the second jaw member when the first needle is moved from the advanced position to the retracted position.

\* \* \* \* \*