

(12) **United States Patent**
Daraskavich et al.

(10) **Patent No.:** **US 10,071,291 B2**
(45) **Date of Patent:** **Sep. 11, 2018**

- (54) **GOLF IRONS WITH SEALED UNDERCUT**
(71) Applicant: **NIKE, Inc.**, Beaverton, OR (US)
(72) Inventors: **Matt Daraskavich**, Grapevine, TX (US); **Brian J. Kammerer**, Fort Worth, TX (US); **Michael Pinto**, Fort Worth, TX (US)
(73) Assignee: **Karsten Manufacturing Corporation**, Phoenix, AZ (US)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/708,709**
(22) Filed: **May 11, 2015**

(65) **Prior Publication Data**
US 2016/0332044 A1 Nov. 17, 2016

- (51) **Int. Cl.**
A63B 53/04 (2015.01)
A63B 60/54 (2015.01)
(52) **U.S. Cl.**
CPC **A63B 53/0475** (2013.01); **A63B 60/54** (2015.10); **A63B 2053/0408** (2013.01)
(58) **Field of Classification Search**
CPC **A63B 53/04**; **A63B 53/0475**
USPC **473/350**
See application file for complete search history.

- (56) **References Cited**
U.S. PATENT DOCUMENTS
2,846,228 A * 8/1958 Reach **A63B 53/04**
473/332
4,340,230 A * 7/1982 Churchward **A63B 53/04**
473/339

4,355,808 A *	10/1982	Jernigan	A63B 53/04 264/129
4,645,207 A	2/1987	Teramoto et al.	
4,824,110 A	4/1989	Kobayashi	
4,883,274 A *	11/1989	Hsien	A63B 53/04 473/335
D320,056 S	9/1991	Antonious	
5,048,835 A *	9/1991	Gorman	A63B 53/04 473/350
5,074,563 A *	12/1991	Gorman	A63B 53/04 473/350
5,082,278 A *	1/1992	Hsien	A63B 53/04 473/242
D327,308 S	6/1992	Antonious	
5,290,032 A	3/1994	Fenton et al.	
5,290,036 A *	3/1994	Fenton	A63B 53/04 273/DIG. 8
5,328,184 A	7/1994	Antonious	
5,447,311 A	9/1995	Viollaz et al.	
5,492,327 A *	2/1996	Biafore, Jr.	A63B 53/04 473/332
5,586,947 A *	12/1996	Hutin	A63B 53/04 473/324
5,588,923 A *	12/1996	Schmidt	A63B 53/04 473/324
5,816,936 A *	10/1998	Aizawa	A63B 53/04 473/335


(Continued)

Primary Examiner — William Pierce

(57) **ABSTRACT**



A golf club head includes a body, a first polymeric insert, and a second polymeric insert. The body includes a face, a sole, and a rear wall that collectively define an undercut volume. The first polymeric insert is provided within the undercut volume to define a sealed cavity within the undercut volume; and, the second polymeric insert is secured to the body and defines an open cavity extending from the rear wall toward the face.

20 Claims, 3 Drawing Sheets



(56)		References Cited						
U.S. PATENT DOCUMENTS				8,366,566	B1 *	2/2013	Rollinson	A63B 53/0475
								473/332
				8,403,771	B1 *	3/2013	Rice	A63B 53/04
								473/328
5,899,815	A *	5/1999	Helou	A63D 3/00	8,475,293	B2	7/2013	Morin et al.
				273/269	8,480,507	B2	7/2013	Finn et al.
5,967,903	A *	10/1999	Cheng	A63B 53/04	8,512,164	B2	8/2013	Ines et al.
				473/342	8,517,863	B2	8/2013	Wahl et al.
6,017,278	A *	1/2000	Benko	A63D 5/04	8,535,176	B2	9/2013	Bazzel et al.
				340/323 B	8,758,159	B2	6/2014	Morin et al.
6,027,415	A *	2/2000	Takeda	A63B 53/04	8,777,776	B2	7/2014	Wahl et al.
				473/291	8,814,725	B2	8/2014	Wahl et al.
6,030,295	A	2/2000	Takeda		8,834,292	B2 *	9/2014	Tsuji
6,048,272	A *	4/2000	Tsuji	A63D 5/04				
				463/25	8,911,301	B1 *	12/2014	Allen
D428,632	S	7/2000	Besnard et al.					
6,086,485	A *	7/2000	Hamada	A63B 53/04	8,911,302	B1 *	12/2014	Ivanova
				473/329				
6,093,112	A *	7/2000	Peters	A63B 53/00	8,920,258	B2	12/2014	Dolezel et al.
				473/291	8,920,261	B2	12/2014	Taylor et al.
6,183,376	B1	2/2001	Peters et al.		8,932,150	B2	1/2015	Ines et al.
6,193,614	B1 *	2/2001	Sasamoto	A63B 53/04	2002/0042307	A1 *	4/2002	Deshmukh
				473/329				
D438,925	S	3/2001	Adams et al.		2002/0098910	A1 *	7/2002	Gilbert
6,358,158	B2	3/2002	Peters et al.					
6,368,231	B1 *	4/2002	Chen	A63B 53/04	2004/0092331	A1 *	5/2004	Best
				473/329				
6,482,104	B1 *	11/2002	Gilbert	A63B 53/04	2006/0234805	A1 *	10/2006	Gilbert
				473/287				
D473,606	S	4/2003	Mickelson et al.		2007/0178988	A1 *	8/2007	Tavares
6,554,719	B2	4/2003	Peters et al.					
6,592,469	B2 *	7/2003	Gilbert	A63B 53/04	2007/0293343	A1	12/2007	Lai et al.
				473/291	2008/0020861	A1 *	1/2008	Adams
D487,127	S	2/2004	Madore					
6,811,496	B2 *	11/2004	Wahl	A63B 53/047	2008/0058119	A1 *	3/2008	Soracco
				473/334				
6,830,519	B2	12/2004	Reed et al.		2008/0102982	A1 *	5/2008	Wahl
6,863,625	B2	3/2005	Reyes et al.					
6,942,580	B2	9/2005	Hou et al.		2010/0029406	A1 *	2/2010	Stites
6,981,924	B2	1/2006	Deshmukh					
7,004,853	B2	2/2006	Deshmukh		2011/0207551	A1 *	8/2011	Breier
7,022,031	B2	4/2006	Nishio					
7,025,693	B2	4/2006	Sugimoto		2012/0157222	A1 *	6/2012	Kii
7,112,148	B2	9/2006	Deshmukh					
7,137,903	B2	11/2006	Best et al.		2012/0289360	A1	11/2012	Breier et al.
7,147,571	B2	12/2006	Best et al.		2013/0017903	A1 *	1/2013	Takechi
7,186,188	B2 *	3/2007	Gilbert	A63B 53/047				
				473/290				
7,192,361	B2	3/2007	Gilbert et al.		2013/0017904	A1	1/2013	Woolley et al.
7,192,362	B2 *	3/2007	Gilbert	A63B 53/047	2013/0252754	A1	9/2013	Bazzel et al.
				473/291	2013/0281227	A1 *	10/2013	Roach
7,232,377	B2	6/2007	Gilbert et al.					
7,273,418	B2	9/2007	Gilbert et al.		2013/0331201	A1 *	12/2013	Wahl
7,371,190	B2	5/2008	Gilbert et al.					
D571,421	S	6/2008	Clausen et al.		2013/0344988	A1 *	12/2013	Hettinger
7,485,049	B2	2/2009	Gilbert et al.					
7,614,962	B1 *	11/2009	Clausen	A63B 53/047	2013/0344989	A1 *	12/2013	Hebreo
				473/291				
7,621,822	B2 *	11/2009	Roach	A63B 53/047	2014/0073447	A1 *	3/2014	Golden
				473/329				
7,662,050	B2	2/2010	Gilbert et al.		2014/0206469	A1	7/2014	Girard et al.
7,686,704	B2	3/2010	Gilbert et al.		2014/0248977	A1	9/2014	Morin et al.
7,789,771	B2 *	9/2010	Park	A63B 53/0475	2014/0302944	A1	10/2014	Roach et al.
				473/332	2014/0364248	A1	12/2014	Wahl et al.
7,803,062	B2 *	9/2010	Gilbert	A63B 53/047	2015/0217364	A1 *	8/2015	Zimmerman
				473/290				
7,942,760	B2	5/2011	Best et al.					
8,033,927	B2	10/2011	Gilbert et al.		2015/0328506	A1 *	11/2015	Morales
8,088,025	B2	1/2012	Wahl et al.					
8,182,359	B2	5/2012	Gilbert et al.		2016/0144248	A1 *	5/2016	Chen
8,197,354	B2	6/2012	Gilbert et al.					
8,202,174	B2	6/2012	Breier et al.		2016/0184669	A1 *	6/2016	Deshmukh
8,235,833	B2	8/2012	Best et al.					
8,298,095	B2	10/2012	Gilbert et al.		2017/0028270	A1 *	2/2017	Westrum
8,328,663	B2	12/2012	Wahl et al.					
8,353,785	B2	1/2013	Ines et al.					

* cited by examiner






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

GOLF IRONS WITH SEALED UNDERCUT

TECHNICAL FIELD

The present invention relates generally to an iron-type 5
golf club head with a sealed undercut.

BACKGROUND

A golf club may generally include a club head disposed on 10
the end of an elongate shaft. During play, the club head may be swung into contact with a stationary ball located on the ground in an effort to project the ball in an intended direction and with a desired vertical trajectory.

Many design parameters must be considered when forming 15
a golf club head. For example, the design must provide enough structural resilience to withstand repeated impact forces between the club and the ball, as well as between the club and the ground. The club head must conform to size requirements set by different rule setting associations, and 20
the face of the club must not have a coefficient of restitution above a predefined maximum (measured according to applicable standards). Assuming that certain predefined design constraints are satisfied, a club head design for a particular loft can be quantified by the magnitude and location of the 25
center of gravity, as well as the head's moment of inertia about the center of gravity and/or the shaft.

The club's moment of inertia relates to the club's resistance to rotation (particularly during an off-center hit), and is often perceived as the club's measure of "forgiveness." In 30
typical club designs, high moments of inertia are desired to reduce the club's tendency to push or fade a ball. Achieving a high moment of inertia generally involves moving mass as close to the perimeter of the club as possible (to maximize the moment of inertia about the center of gravity), and as close to the toe as possible (to maximize the moment of inertia about the shaft). In iron-type golf club heads, this desire for increased moments of inertia have given rise to designs such as the cavity-back club head and the hollow club head. 35

While the moment of inertia affects the forgiveness of a club head, the location of the center of gravity behind the club face (and above the sole) generally affects the trajectory of a shot for a given face loft angle. A center of gravity that is positioned as far rearward (away from the face) and as low 45
(close to the sole) as possible typically results in a ball flight that has a higher trajectory than a club head with a center of gravity placed more forward and/or higher.

While a high moment of inertia is obtained by increasing the perimeter weighting of the club head or by moving mass 50
toward the toe, an increase in the total mass/swing weight of the club head (i.e., the magnitude of the center of gravity) has a strong, negative effect on club head speed and hitting distance. Said another way, to maximize club head speed (and hitting distance), a lower total mass is desired; however a lower total mass generally reduces the club head's moment of inertia (and forgiveness). 55

In the tension between swing speed (mass) and forgiveness (moment of inertia), it may be desirable to place varying amounts of mass in specific locations throughout the 60
club head to tailor a club's performance to a particular golfer or ability level. In this manner, the total club head mass may generally be categorized into two categories: structural mass and discretionary mass.

Structural mass generally refers to the mass of the materials that are required to provide the club head with the structural resilience needed to withstand repeated impacts. 65

Structural mass is highly design-dependent, and provides a designer with a relatively low amount of control over specific mass distribution. On the other hand, discretionary mass is any additional mass that may be added to the club head design for the sole purpose of customizing the performance and/or forgiveness of the club. In an ideal club design, the amount of structural mass would be minimized (without sacrificing resiliency) to provide a designer with a greater ability to customize club performance, while maintaining a traditional or desired swing weight.

Specifically as to iron designs, discretionary mass is typically placed as far from the shaft as possible (i.e., toward the toe portion), as far from the face as possible (i.e., to the rear of the head), and as low as possible. This tends to provide a club head having a high moment of inertia (forgiveness) and a generally higher launch angle.

SUMMARY

A golf club head includes a body, a first polymeric insert, and a second polymeric insert. The body includes a face, a sole, and a rear wall that collectively define an undercut volume. The first polymeric insert is provided within the undercut volume to define a sealed cavity within the undercut volume; and, the second polymeric insert is secured to the body and defines an open cavity extending from the rear wall toward the face. 20

In one configuration, the first polymeric insert is operative to restrict fluid access to the undercut volume. The first polymeric insert may be in compression between the face and the rear wall and may be adhered about its perimeter to the face and rear wall. 25

The normal projection of the open cavity onto the face defines a first area, and the normal projection of the undercut volume onto the face defines a second area. In one configuration these areas do not overlap, and may be in a ratio of from about 0.7:1 to about 1.3:1. Additionally, the projection of the sealed cavity onto the face may define a third area, and the ratio of the first area to the third area may be from about 0.9:1 to about 2.0:1. In one configuration, the first area is from about 800 mm² to about 1600 mm². 40

The above features and advantages and other features and advantages of the present technology are readily apparent from the following detailed description when taken in connection with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic perspective view of the face of an iron-type golf club head.

FIG. 2 is a schematic perspective view of the rear wall of an iron-type golf club head.

FIG. 3 is a schematic perspective view of the rear portion of a body of an iron-type golf club head.

FIG. 4 is a schematic cross-sectional view of the golf club head FIG. 2, taken along line 4-4.

FIG. 5 is a schematic perspective view of the body of an iron-type golf club head, including a sealed undercut volume.

FIG. 6 is a schematic perspective view of a polymeric insert.

FIG. 7 is a schematic view of the normal projection of a dual cavity structure onto the face of a golf club head.

DETAILED DESCRIPTION

Referring to the drawings, wherein like reference numerals are used to identify like or identical components in the

various views, FIGS. 1 and 2 schematically illustrate a golf club head 10 including a body 12 and a polymeric insert 14. In the illustrated embodiment, the body 12 includes a face 16, sole 18, topline 20, rear wall 22, and hosel 24.

The club face 16 is intended to contact the golf ball during a normal swing, and includes a plurality of parallel grooves 26 that are recessed into a hitting surface of the club face 16 in a generally concave manner. As is commonly understood, the club face 16 is angled (relative to a vertical plane) when the golf club is held in a neutral hitting position. This angle is generally referred to as the loft angle or slope of the club. Wood-type club heads (including hybrid woods) may most commonly have loft angles of from about 8.5 degrees to about 24 degrees, while iron-type club heads may most commonly have loft angles from about 17 degrees to about 64 degrees, though other loft angles are possible and have been commercially sold. A particular subset of iron-type club heads, referred to as “wedges,” generally have loft angles of from about 44 degrees to about 64 degrees. The present technology may be of particular importance to iron-type club heads, and more specifically to wedges.

The sole 18 may extend on an underside of the club head 10 such that the sole 18 contacts the ground or a horizontal ground plane when the golf club is held in a neutral hitting position. The sole 18 may extend from a toe portion 28 of the club head 10 to a heel portion 30 of the club head 10, and may be disposed between the club face 16 and the rear wall 22. In general, the sole 18 may transition into the face at a leading edge 32 and may transition into the rear wall at a trailing edge 34.

While the sole 18 may generally define the underside of the club head 10, the topline 20 may generally define the upper or top portion of the club head 10. The topline 20 provides structural support or reinforcement for the club face 16. In general, the sole 18 and topline 20 are disposed on opposing sides of both the club face 16 and the rear wall 22.

As shown in FIG. 3, in an effort to shift the center of mass closer to the sole 18, toe 28, and/or rear wall 22, the present design removes a portion of the rear wall 22 to define an opening 40 and removes material between the rear wall 22 and the face 16 to define an undercut volume 42. In the present design, the threshold of the undercut volume 42 is defined by one or more of the following: an imaginary surface that is normal to the club face 16 and in contact with an edge of the opening 40; an imaginary surface that is extrapolated from a threshold surface 44 of the opening 40 provided in the rear wall 22 to the face 16; or by a surface 46 of the polymeric insert 14 that extends between the rear wall 22 and the face 16.

As best illustrated in FIG. 4, the present club head 10 employs a dual-cavity design that is formed, in part by the first, exposed polymeric insert 14, as well as by a second, concealed polymeric insert 50. In this design, the first polymeric insert 14 is secured to the body 12 to define a first, open cavity 52. The open cavity 52 includes a concave recess that is open to the external environment and extends from the opening 40 provided in the rear wall 22 toward the face 16.

The second polymeric insert 50 is provided within the undercut volume 42 to form a second, sealed cavity 54. The sealed cavity 54 is an entirely enclosed portion of the undercut volume 42 and is defined between the second polymeric insert 50 and the body 12 (e.g., the face 16, the sole 18, and the rear wall 22).

In one embodiment, the first polymeric insert 14 is adhered to a rear surface 56 of the face 16, similar to a

medallion. In this design, where the insert 14 extends from the rear wall 22, the construction of the first polymeric insert 14 disguises/hides the existence of the undercut volume 42. To some consumers, this is an advantageous quality since the design allows the club to have performance benefits attributable to an undercut volume, without the undercut being outwardly visible.

If the design only consisted of the first polymeric insert 14 and the body 12, with the insert 14 only being secured to the face 16, any clearance between the insert 14 and the rear wall 22 may allow liquid to enter the undercut volume 42 where it might become temporarily trapped. If this occurred, for example, while cleaning the club just prior to a shot, the trapped fluid may be difficult to drain out, and may alter the swing weighting of the club head 10.

To overcome possible trapped fluid issues, the second polymeric insert 50 may be positioned at the threshold of the undercut volume 42 such that it is operative to restrict fluid access into the undercut volume 42. In one configuration, this sealing effect may occur by forming the insert 50 from a sufficiently elastic material and placing it in compression between the face 16 and the rear wall 22. For example, the second insert 50 may be formed from a polymer that has a hardness, measured on the Shore A scale, of from about 40 A to about 60 A. In another configuration, the sealing effect may occur by adhering the insert 50 to the body 12 around a perimeter of the insert 50.

The second polymeric insert 50 may further be operative to support the face 16 and rear wall 22. In this manner, the insert 50 may dampen vibrations following an impact and/or may stiffen the body 12 to increase one or more of the modal frequencies of the club head 10.

In one configuration, the second insert 50 may be maintained in position at the threshold of the undercut volume 42 by one or more retaining features provided in the body 12. Examples of potential retaining features may include posts, ledges, or sloped walls, where the feature is operative to restrain the insert 50 from entering the undercut volume 42 by more than a predefined distance. In the example provided in FIGS. 3 and 4, the retaining feature includes a ledge 60 that interferes with the insert's ability to enter the undercut volume 42 any more than shown (in FIG. 4). If the second insert 50 is adhered in place, it may likewise be adhered to the retaining feature.

FIG. 5 illustrates the second insert 50 installed within the body such that it is flush with the threshold of the undercut volume 42. Once installed, the first insert 14, (e.g., shown in FIG. 6) may be slid into place through the opening 40 and secured. Because the first insert 14 is exposed to the external environment and extends to the rear wall 22, it is desirably made from a polymer that is sufficiently hard and durable such that it can withstand minor impacts. For example, the first insert 14 may be formed from a polymeric material that has a hardness, measured on the Shore D scale, of from about 75 D to about 90 D, or more preferably from about 80 D to about 90 D.

The present design may include a sufficiently large hidden undercut volume 42 to cause a meaningful movement of the center of gravity of the club head 10. When viewed normal to the face 16, the undercut volume 42 and open cavity 52 may be similarly sized. More specifically, in one configuration such as shown in FIG. 7, a normal projection of the open cavity 52 onto the face 16 may define a first area 70, and the normal projection of the undercut volume 42 may define a second area 72 (i.e., where the second area 72 includes the projection 74 of the sealed cavity 54 and the projection 76 of the second polymeric insert 50). The ratio

of the first area **70** to the second area **72** may be from about 0.7:1 to about 1.3:1, or from about 0.8:1 to about 1.2:1, or even from about 0.9:1 to about 1.1:1. Additionally, the size of the first area **70** may be from about 800 mm² to about 1600 mm². In one embodiment, the areas **70**, **72** do not overlap.

While it may be possible to entirely fill the undercut volume **42** with polymer, the weight savings provided by a hollow, sealed cavity **54** may enable additional mass to be moved toward the toe **28**, sole **18**, and/or rear wall **22**. As such, the ratio of the first area **70** to the area of the projection **74** of the sealed cavity **54** may be from about 0.9:1 to about 2.0:1, or from about 1.1:1 to about 1.9:1. Such ratios may further benefit the design from a structural/acoustic perspective by causing the second polymeric insert **50** to extend across a central region of the face **16** and/or behind a designed impact zone.

Referring to FIG. **6**, the exposed first insert **14** may define the open cavity **52** and may have a varying width **80** around its perimeter (i.e., where width is measured normal to the face **16**, or to the surface **82** of the insert **14** that is intended to be positioned in contact with, or parallel to the face **16**). For example, the variable width **80** may be within the range of from about 2.5 mm to about 6.0 mm along an upper portion **84** that is intended to contact, or be directly adjacent to the topline **20**. Conversely, the variable width **80** may be within the range of from about 5.0 mm to about 20 mm along a lower portion **86** that is intended to contact, or be directly adjacent the second insert **50**. Regardless of the specific dimension, the variable width **80** should be sufficiently large to extend between the rear wall **22** and the face **16** such that the insert **14** appears to extend from the rear wall **22** and/or could be adhered to the rear wall **22** if so desired.

In one embodiment, the first polymeric insert **14** may be dimensioned such that it is in contact with the body **12** along some or all of the topline **20** and rear wall **22**. In such an embodiment, the strength and hardness of the first insert **14** may serve a further reinforcing purpose. Said another way, the first insert **14** may be operative to stiffen the body structure and raise one or more vibrational modes of the club head **10**. In this embodiment, design features of the insert **14**, such as a reinforcing feature **88** extending across the open cavity **52**, may contribute to the stiffening. As shown, the reinforcing feature **88** may be a channel, beam, bar, strut, or the like, and may extend across the cavity **52** between two non-adjacent portions of the insert **14**.

To accomplish a structural reinforcement, it is preferable to use a material that has a tensile strength of greater than about 200 MPa (according to ASTM D638), or more preferably greater than about 250 MPa. Additionally, for ease of molding, if the polymeric material of the insert **14** is filled, then it desirably has a resin content of greater than about 50%, or even greater than about 55% by weight. One such material may include, for example, a thermoplastic aliphatic or semi-aromatic polyamide that is filled with chopped fiber, such as chopped carbon fiber or chopped glass fiber. Other materials may include polyimides, polyamide-imides, polyetheretherketones (PEEK), polycarbonates, engineering polyurethanes, and/or other similar materials.

As noted above, the present design removes a substantial amount of structural weight between the rear wall **22** and the face **16**, and affords a club designer the ability to place the weight elsewhere in the club head **10** to maximize performance. Additionally, these goals are achieved while maintaining a particular aesthetic appearance that hides the presence of the undercut volume **42** via the use of comparatively light weight polymers.

“A,” “an,” “the,” “at least one,” and “one or more” are used interchangeably to indicate that at least one of the item is present; a plurality of such items may be present unless the context clearly indicates otherwise. All numerical values of parameters (e.g., of quantities or conditions) in this specification, including the appended claims, are to be understood as being modified in all instances by the term “about” whether or not “about” actually appears before the numerical value. “About” indicates that the stated numerical value allows some slight imprecision (with some approach to exactness in the value; about or reasonably close to the value; nearly). If the imprecision provided by “about” is not otherwise understood in the art with this ordinary meaning, then “about” as used herein indicates at least variations that may arise from ordinary methods of measuring and using such parameters. In addition, disclosure of ranges includes disclosure of all values and further divided ranges within the entire range. Each value within a range and the endpoints of a range are hereby all disclosed as separate embodiment. The terms “comprises,” “comprising,” “including,” and “having,” are inclusive and therefore specify the presence of stated items, but do not preclude the presence of other items. As used in this specification, the term “or” includes any and all combinations of one or more of the listed items. When the terms first, second, third, etc. are used to differentiate various items from each other, these designations are merely for convenience and do not limit the items.

The invention claimed is:

1. A cavity-back golf club head for an iron-type golf club, the golf club head comprising:
 - a club head body including a face, a sole adjoining the face, and a rear wall adjoining the sole, wherein the face, the sole, and the rear wall define an undercut volume, the rear wall including at an upper edge thereof a threshold surface defining an upper threshold of the undercut volume, and a sloped ledge adjoining the threshold surface and projecting at an obtuse angle from the threshold surface into the undercut volume;
 - a first polymeric insert interference fit between a rear surface of the face and the sloped ledge of the rear wall within the undercut volume to thereby define a fluidly sealed empty cavity within the undercut volume; and
 - a second polymeric insert secured to the club head body and including a concave recess defining an open cavity extending from the rear wall toward the face, wherein the first polymeric insert includes a top surface and a sloped surface projecting at an oblique angle from the top surface, the top surface of the first polymeric insert being seated against a bottom surface of the second polymeric insert, and the sloped surface being seated against the sloped ledge of the rear wall.
2. The golf club head of claim **1**, wherein the top surface of the first polymeric insert is flush with the bottom surface of the second polymeric insert.
3. The golf club head of claim **1**, wherein the first polymeric insert is in compression between the rear surface of the face and the sloped ledge of the rear wall.
4. The golf club head of claim **1**, wherein a normal projection of the open cavity onto the face defines a first area, and a normal projection of the undercut volume onto the face defines a second area, and wherein the first area and the second area do not overlap.
5. The golf club head of claim **4**, wherein a ratio of the first area to the second area is from about 0.7:1 to about 1.3:1.
6. The golf club head of claim **5**, wherein the normal projection of the undercut volume includes a normal pro-

jection of the sealed cavity onto the face that defines a third area, and wherein a ratio of the first area to the third area is from about 0.9:1 to about 2.0:1.

7. The golf club head of claim 4, wherein the first area is from about 800 mm² to about 1600 mm².

8. The golf club head of claim 1, wherein the second polymeric insert is adhered to the rear surface of the face.

9. The golf club head of claim 8, wherein the second polymeric insert is adhered only to the rear surface of the face.

10. The golf club head of claim 1, wherein the second polymeric insert is harder than the first polymeric insert.

11. The golf club head of claim 10, wherein the first polymeric insert has a hardness, measured on the Shore A scale, of from about 40 A to about 60 A.

12. The golf club head of claim 1, wherein the first polymeric insert is adhered to the sloped ledge of the rear wall.

13. The golf club head of claim 1, wherein the face is disposed at a loft angle of from about 44 degrees to about 64 degrees.

14. A golf club head comprising:

a club head body including a face, a sole, and a rear wall, wherein the face, the sole, and the rear wall define an undercut volume, the rear wall including a threshold surface at an upper threshold of the undercut volume, and a sloped ledge adjoined to and projecting at an obtuse angle from the threshold surface;

a first polymeric insert interference fit between a rear surface of the face and the sloped ledge of the rear wall within the undercut volume to thereby restrict fluid access to the undercut volume and to define a sealed hollow cavity within the undercut volume; and

a second polymeric insert secured to the rear surface of the face and extending to the rear wall, wherein the second polymeric insert includes a concave recess that defines an open cavity, the second polymeric insert trapping the first polymeric insert between the second polymeric insert and the sloped ledge of the rear wall, wherein the first polymeric insert includes a top surface seated against a bottom surface of the second polymeric

insert, and a sloped surface projecting at an oblique angle from the top surface and seated against the sloped ledge of the rear wall.

15. The golf club head of claim 14, wherein the first polymeric insert is in compression between the rear surface of the face and the sloped ledge of the rear wall.

16. The golf club head of claim 14, wherein the second polymeric insert includes a reinforcing feature extending across the open cavity.

17. The golf club head of claim 14, wherein the second polymeric insert is harder than the first polymeric insert.

18. The golf club head of claim 17, wherein the first polymeric insert has a hardness, measured on the Shore A scale, of from about 40 A to about 60 A.

19. The golf club head of claim 14, wherein the first polymeric insert is adhered to the ledge of the rear wall.

20. A club head for an iron-type golf club, the club head comprising:

a club head body including a face, a sole adjoining a bottom end of the face, a rear wall opposite the face and adjoining the sole, and a topline opposite the sole and adjoining a top end of the face, wherein the face, the sole, and the rear wall cooperatively define an undercut volume proximate the sole, the rear wall including at an upper edge thereof a threshold surface defining an upper threshold of the undercut volume, and a sloped ledge adjoined to and projecting at an obtuse angle from the threshold surface into the undercut volume;

a first insert interference fit between a rear surface of the face and the sloped ledge of the rear wall, the first insert fluidly sealing the undercut volume and defining an empty hollow cavity within the undercut volume; and a second insert attached to the club head body adjacent the topline and the face, the second insert defining an open cavity between the topline and the undercut volume,

wherein the first polymeric insert includes a top surface seated flush against a bottom surface of the second polymeric insert, and a sloped surface projecting at an oblique angle from the top surface and seated flush against the sloped ledge of the rear wall.

* * * * *