
W. C. FRAILEY. Chimney Cowl.

No. 80,618.

Patented Aug. 4, 1868.



N. PETERS, PHOTO-LITHOGRAPHER, WASHINGTON, D. C.

Anited States Patent Office.

WILLIAM C. FRAILEY, OF IRONTON, ASSIGNOR TO HIMSELF AND D. T. WOODROW, OF CINCINNATI, OHIO.

Letters Patent No. 80,618, dated August 4, 1868.

IMPROVEMENT IN CHIMNEY-COWLS.

The Schedule referred to in these Tetters Patent and making part of the same.

TO ALL WHOM IT MAY CONCERN:

Be it known that I, WILLIAM C. FRAILEY, of Ironton, Lawrence county, State of Ohio, have invented certain new and useful Improvements in Chimney-Caps; and I do hereby declare the following to be a full, clear, and exact description thereof, reference being had to the accompanying drawings, making part of this specification.

My invention consists in the construction of a chimney-cap of light, thin, slightly ornamental plates of cast iron, put together in sections, and adapted, when put together, to properly enclose the brick-work of the chimney and prevent displacement.

The accompanying drawing is a perspective view of a chimney and cap embodying my invention, the drawing being sectionized in parts to properly exhibit the necessary construction.

A is the chimney. B is the can proper having two havecared analyses

A is the chimney. B is the cap proper, having two hexagonal smoke-apertures. This cap is merely a plate of cast iron, having a deep flange, b, all round on the under side, and two slightly-projecting flanges, b', on the upper side, surrounding the smoke-apertures.

C C' are the pots or pipes of the cap, each composed of two half hexagon sides, c c' and c'' c''', and sur-

mounting caps d d'.

The sides c c' and c'' c''', when joined together, fit the flanges b', and are provided with perforated lugs, e, at the sides, and lugs f g, at top and bottom, for the accommodation of bolts and nuts h, by which the sides are secured together, and to the caps B and d d', as shown.

I claim herein as new, and of my invention-

The combination of the flanged base B b, sides c c', cap d, lugs e f g, and connecting-bolts h, all constructed and employed substantially as and for the purposes set forth.

In testimony of which invention, I hereunto set my hand.

Witnesses:

GEO. H. KNIGHT, JAMES H. LAYMAN. WILLIAM C. FRAILEY.