



US008152519B1

(12) **United States Patent**  
**Dumas**

(10) **Patent No.:** **US 8,152,519 B1**  
(45) **Date of Patent:** **Apr. 10, 2012**

(54) **ORTHODONTIC CONNECTOR ASSEMBLY  
AND A METHOD FOR TREATING TEETH**

(76) Inventor: **John Joseph Dumas**, Bloomfield Hills,  
MI (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 462 days.

(21) Appl. No.: **11/724,140**

(22) Filed: **Mar. 14, 2007**

(51) **Int. Cl.**  
**A61C 3/00** (2006.01)

(52) **U.S. Cl.** ..... **433/8; 433/10**

(58) **Field of Classification Search** ..... **433/8-16,**  
**433/24**

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,721,005 A *	3/1973	Cohen	433/16
3,959,880 A	6/1976	Andrews	
3,975,824 A	8/1976	Lee	
4,180,912 A	1/1980	Kesling	
4,427,381 A *	1/1984	Hall	433/14
4,496,317 A *	1/1985	Hulsey	433/10

4,496,318 A	1/1985	Connelly, Jr.	
4,525,143 A	6/1985	Adams	
4,585,413 A	4/1986	Wool	
4,957,438 A	9/1990	Bax	
5,356,288 A *	10/1994	Cohen	433/8
5,580,243 A	12/1996	Bloore	
6,726,474 B2	4/2004	Spencer	
7,722,354 B1	5/2010	Dumas	
2002/0058227 A1	5/2002	Townsend-hansen	
2004/0157184 A1	8/2004	Reising	
2005/0255422 A1	11/2005	Cordato	
2005/0277082 A1	12/2005	Christoff	
2006/0199137 A1	9/2006	Abels et al.	
2006/0269891 A1	11/2006	Miqui	

\* cited by examiner

*Primary Examiner* — Todd Manahan

*Assistant Examiner* — Yogesh Patel

(57) **ABSTRACT**

An orthodontic connector assembly **10** including a plurality of substantially identical connecting members, such as members **12**, **14** which include a movable but biased portion **20** which is adapted to selectively and removably receive a pocket portion **44** which is deployed on at least one bracket, such as bracket **40**. In an alternative embodiment, the members, such as member **12**, **14** each include a ridge, such as ridge **212**, which is selectively, removably, and frictionally placed within slot **236**.

**4 Claims, 9 Drawing Sheets**




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6





FIG. 7









FIG. 9







FIG. 10

FIG. 11



# ORTHODONTIC CONNECTOR ASSEMBLY AND A METHOD FOR TREATING TEETH

## GENERAL BACKGROUND

### 1. Field of the Invention

The present invention generally relates to an orthodontic connector assembly and to a method for treating teeth and more particularly, to an assembly which allows orthodontic brackets, even a plurality of dissimilar brackets, to be selectively and removably coupled to teeth in a manner which forms a method for effectively and therapeutically treating teeth.

### 2. Background of the Invention

Orthodontic brackets, often referred to as “braces”, are devices which are normally and selectively affixed to the teeth of an individual, by the use of cement or another type of bonding agent, and are adapted to selectively receive a wire which is formed and deployed in the brackets (e.g., in the mouth of a patient) in order to provide therapeutic force or pressure on the patient’s teeth. The combination of the brackets and the wire are often sometimes collectively referred to as a “retaining system” or an “orthodontic retaining system”.

While such prior and currently utilized retaining systems do allow therapeutic pressure to be applied to a patient’s teeth, they suffer from some drawbacks.

By way of example and without limitation, as the therapy is applied to the patient (i.e., over time) modifications may need to be made to the brackets or different brackets may be optimally needed. This “bracket modification” or “replacement” is complicated and time consuming because the currently utilized brackets must be forcibly removed from the patient’s teeth (e.g., removed from the cement or adhering agent), the teeth must be cleaned and “re-prepped” (an etching agent and a new application of an adhering agent must be deployed on the teeth), and the new or modified brackets must be deployed on the newly prepped teeth. The process is uncomfortable to the patient and is relatively costly due to the need for additional etching and adhesive material and the time needed to achieve the change or modification. Moreover, sometimes the deployed brackets become broken or are in need of repair and must be removed from the patient’s teeth to become serviced, thereby requiring the same sort of afore-described process and relatively the same sort of cost and discomfort.

Further, it may be therapeutically desirable to deploy different sorts or types of brackets upon the teeth of a patient within a relatively short amount of time due to the needs of the patient and such “rapid bracket deployment” undesirably and greatly increases the cost and discomfort to the patient. Further, different sorts of brackets may be used on a patient, within a certain time, just in order for a dentist to evaluate the efficacy of these deployed brackets on a certain patient and discover the bracket type which may provide optimal therapy on a particular patient (i.e., each patient may experience different amounts and types of therapy with a certain bracket). Non-limiting examples of orthodontic brackets are found within United States Patent Application Publication Numbers US2005/0255422 A1, US2002/0058227 A1, and US2004/0157184 A1 which are each fully and completely incorporated herein by reference, word for word and paragraph for paragraph.

There is therefore a need for a new and improved connector assembly which allows brackets and orthodontic retaining systems to be easily, quickly, and cost effectively deployed upon the teeth of a patient and it is one non-limiting object of the present invention to provide such an improved connector system.

## SUMMARY OF THE INVENTION

It is a first non-limiting object of the present invention to provide a new and novel orthodontic connector assembly which overcome some or all of the previously delineated disadvantages of prior connector systems.

It is a second non-limiting object of the present invention to provide a new and improved methodology for treating teeth which overcome some or all of the previously delineated disadvantages of prior and current strategies and methodologies.

According to a first non-limiting aspect of the present invention, an orthodontic connector assembly is provided and includes a plurality of substantially identical connector members which are each selectively and respectively adhered to unique teeth and each of which include a substantially identical connector portion, wherein each of the substantially identical connector portions cooperatively and removably receive a bracket.

According to a second non-limiting aspect of the present invention, an orthodontic connector assembly is provided and includes the combination of a plurality of substantially identical connector members which each include a first smooth surface which is respectively and selectively adhered to unique teeth and each of which further respectively include a second opposed surface which includes a ridge and wherein each of the ridges are substantially identical and have a certain first shape; and a plurality of brackets which include a first back surface having a slot having a complementary shape to each of said ridges and where each of said slots are adapted to receive a unique one of each of the ridges and wherein each of the plurality of brackets include dissimilar front wire reception portions.

According to a third non-limiting embodiment of the invention, a bracket is provided and includes a back surface which includes a slot and a front surface which includes a plurality of protuberances which cooperatively form a slot and a member which is pivotally coupled to the front surface and which includes a nub portion which extends from said front surface.

According to a fourth non-limiting aspect of the present invention, a method for therapeutically treating teeth is provided. Particularly, the method includes the steps of providing a plurality of substantially identical connector members, wherein each of the substantially identical connector members has a certain first shape which includes a central ridge; respectively fixing each of the plurality of substantially identical connector members onto a unique tooth in a manner which allows each of the central ridge to protrude from a respectively unique tooth; providing a plurality of dissimilar brackets, each of the brackets including a slot; causing the respective slot of each of said plurality of dissimilar brackets to be connected to a unique one of the central ridges.

These and other features, aspects, and advantages of the present invention will become apparent by a reading of the detailed description of the preferred embodiment of the invention, including the subjoined claims and by reference to the drawings.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a orthodontic connector assembly which is made in accordance with the teachings of the preferred embodiment of the invention.

FIG. 2 is a partial front view of a portion of a patient’s mouth showing a partial deployment of the orthodontic connector assembly which is shown in FIG. 1, upon certain teeth.

3

FIG. 3 is a partial front view of a patient's mouth into which the orthodontic connector assembly of the preferred embodiment of the invention is operatively deployed.

FIG. 4 is a perspective view of an orthodontic connector assembly which is made in accordance with the teachings of an alternate embodiment of the invention in unassembled combination with an orthodontic bracket made according to the invention.

FIG. 5 is a back view of the orthodontic bracket taken in the direction of arrow 5 of FIG. 4.

FIG. 6 is a front view of one of the teeth which are shown in FIG. 3 showing, in phantom, the manner in which a portion of the connector assembly, shown in FIG. 1, is attached to the tooth.

FIG. 7 is a front view of a bracket which is made in accordance with the teachings of the present invention.

FIG. 8 is a partial side sectional view of the bracket which is shown in FIG. 7 selectively deployed upon a connector member which is made in accordance with the teachings of an alternate embodiment of the invention, before therapeutic wire is received.

FIG. 9 is a view which is similar to that which is shown in FIG. 8, but including a therapeutic wire.

FIG. 10 is a partial side sectional view of a bracket which is made in accordance with the teachings of an alternate embodiment of the invention being selectively deployed upon a connector member which is made in accordance with the teachings of another alternate embodiment of the invention, before therapeutic wire is received.

FIG. 11 is a view which is similar to that which is shown in FIG. 10 but having therapeutic wire received it should be appreciated that the dark circles in FIGS. 1, 2, and 3 denote the use of a variable number of elements which respectively appear to the left and right of these respective circles.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT OF THE INVENTION

Referring now to FIGS. 1, 2, 3, and 6, there is shown an orthodontic connector assembly 10 which is made in accordance with the teachings of the preferred embodiment of the invention.

Particularly, the orthodontic connector assembly 10 includes a plurality of substantially identical connector members, such as members 12, 14, which may be constructed from metal, plastic or another composite material and which includes a first substantially flat back surface 16 and a second substantially flat front surface 18. The connector members, such as members 12, 14, are of a size and a shape which is smaller than the size and shape of a human tooth. Nothing in this description is meant to limit the members 12, 14 to any particular size and shape or to any particular material and, in various alternate embodiments of the invention, many connector members of different sizes and shapes may be provided.

The surface 18 includes a portion 20 which is hingedly coupled (e.g., by a hinge member 3 which is coupled to surface 18 and to member 20) to the surface 18 along the edge 22 and thus normally contacts (i.e., is biased against) surface 18 but may be selectively moved from this first surface contacting position to a second non-contacting position away from surfaces 18 and 16. In one non-limiting embodiment, hinge member 3 may space a spring or other device which allows portion 20 to be selectively and movably coupled to surface 18 but which causes portion 20 to be biased against surface 18. Portion 20 may be of substantially any desired shape. The surface 18 further includes a raised edge portion

4

30 upon which the far edge 32 of portion 20 overlays (e.g., the term "far edge", in this context, means the part of portion 20 farthest away from edge 22).

The connector assembly 10 further includes at least one bracket 40 having a generally flat back surface 42 upon which a pocket portion 44 is formed. A pocket portion 44 may comprise a generally "c-shape" member which is coupled to the surface 42 and which includes an opening 43 which extends through the entire pocket portion 44 and which lies between surface 42 and inner surface 5 of the portion 44. The at least one bracket 40 may have a front portion 41 of any desired size and shape therapeutic configuration and the pocket portion 44 is adapted to receive the portion 20, of a member 12, after it is raised off of the surface 18 that it normally is biased against by the edge 22 (e.g., the member 20 is selectively received within and extends through opening 43 in a manner which allows surface 41 to cover the portion 44 from view). The pocket portion 44 may be integrally formed with bracket 40 or attached to bracket 40 by adhesive or any other similar type of material.

The front portion 41 may be adapted to receive a wire or any other therapeutic member or element. After the pocket 44 receives the raised portion 20 (e.g., the portion 20 is inserted through opening 43 of the pocket portion 44) it is ensured that the bottom edge 50 of the pocket portion 44 is supported by edge 30 and then the raised portion 20 is allowed to be biased back toward surface 18 by the biasing member 22, thereby fixing the pocket portion 44 against the surface 18 and attaching the bracket 40 to the portion 12, as shown best in FIG. 6. The edge 30 cooperates with the edge 50 to further attach the bracket 40 to the member 12. It should be appreciated that bracket, such as bracket 70, which may be dissimilar to bracket 40, is made to have a substantially identical back surface 72 which is similar to back surface 41 (i.e., each dissimilar bracket is made to have a substantially similar back surface and thereby includes a substantially identical pocket 44). Thus, every bracket to be utilized as part of or in combination with the assembly 10 must, in the most preferred although non-limiting embodiment, include a back portion which is substantially similar to back portions 42, 72 (e.g., having a pocket portion 44) but which may have a respectively unique and therapeutic front portion (i.e., a portion which receives a wire). In this manner, the respective therapeutic front portion (e.g., portion 41) always outwardly extends from the front surface 7 of each tooth (e.g., the surface which is visible, in the manner which is shown, for example, in FIGS. 3 and 6. Thus, a first set of substantially identical brackets (one for each tooth to be treated) may be deployed, such that each bracket is deployed upon a unique tooth 9, 11 within the mouth of a patient (e.g., each of these brackets has a substantially identical front portion 41 and substantially identical back portion 42). A second set of brackets, each having a front portion which is dissimilar to the front portion of the first set of brackets, may replace the first set of brackets, if the need arises. Alternatively, dissimilar brackets (e.g., those having respectively different therapeutic front portions) may be concurrently utilized upon various teeth within the mouth of a patient if the need arises.

The connector assembly 10 may also include a quantity of cement or an adhesive 80 and some etching material or acid 82. In other non-limiting embodiments of the invention, the assembly 10 does not include the adhesive 80 or etching material 82 or any brackets, such as bracket 40.

As shown best in FIGS. 2 and 3, teeth, such as teeth 7, 9, which are to receive the substantially identical members, such as members 12, 14, are first etched with the material 82 and then the attaching material 80 is applied to the previously

5

etched teeth and then the respective surface **16** of each respective member **12**, **14** is placed onto a respectively unique tooth **7**, **9** (i.e., onto the previously deployed material **80**), until all of teeth **7,9** which are to be therapeutically manipulated have received a unique member **12**.

Brackets, such as bracket **40** may be easily applied and removed from each of the deployed members **12** (e.g., a bracket, such as bracket **40** is removed simply by moving the portion **20** away from the surface **18** and sliding the pocket **44** downwards in the direction **90**). In this manner, brackets, such as bracket **40**, may be easily applied and removed from teeth.

Thus, it should be appreciated that this forgoing invention describes a system and a technique by which dissimilar brackets are made to have a common back portion **42**, **72** which is adapted to selectively and removably receive a standardized member **12**, **14** which has been placed upon teeth. In this manner, dissimilar brackets (e.g., those with different therapeutic or "wire receiving" frontal portions **41**) may be easily placed upon and removed from teeth (e.g., front portion **20**). It should also be appreciated that the shape of portions **20** and pocket **44** may change as desired and that nothing in this description is meant to limit the shape of portion **20** in any manner.

Referring now to FIGS. **4-5**, there is shown a connector member **200** which is made in accordance with the teachings of an alternate embodiment of the invention and which includes a substantially flat base portion **202** having a flat back surface **204** which is adapted to be selectively attached to a tooth, such as tooth **206**, such as by use of attaching material **80**. The member **202** has a substantially flat front surface **210** having a protruding central ridge portion **212** which protrudes away from surfaces **210** and **204**, and from tooth **206** when the member **202** is selectively attached to the tooth **206** (e.g., by use of cement/glue).

The bracket, such as bracket **230**, has a therapeutic front portion **232**, which may be configured as desired and which is selectively adapted to receive wire, such as wire **353**, and a back portion **234** having a depression or slot **236** which is adapted to selectively and removably and fixedly receive the member **212** (e.g., the slot **236** selectively "slides onto" and frictionally engages and receives member **212**), thereby allowing the back surface **234** to be slidably, frictionally, selectively, and removably fixed onto member **212**. In this manner, each tooth, such as tooth **206**, may receive a connector member **200** and have the connector member **200** selectively adhered to it, thereby allowing a bracket, such as bracket **230**, to be connected to the member **200** and selectively removed from it (e.g., by having the member **230** selectively and forcibly "slide away" from the ridge **212**). The ridge **212** may be of any shape including a columnar shape and the shape of ridge **212** is "complimentary" to the shape of the slot **236** (e.g., the term "complimentary" means a ridge **212** is adapted to be selectively, slidably, removably and frictionally received within a slot **236** and to be later selectively and frictionally removed from the slot **236**).

In yet another non-limiting embodiment of the invention, the slot **236** may include at least one ridge **304**, which may be placed within and/or formed within the slot **236** and which is adapted to selectively engage edge **310** of ridge member **212** to prevent movement of deployed bracket **230** in the direction of arrow **320**. In this manner, the deployed bracket, such as bracket **230** may be adjusted to occupy a certain position along length **400** of a member **212** but will never move out of engagement with member **212** while traveling along direction **320**. Additionally, a relatively thin wire strap, such as strap **330**, may be deployed upon surface **210** and adapted to be placed around the interior slot portion **350** of the bracket **230**

6

after slot **236** receives ridge **212**, thereby further securing the bracket **230** to the member **210**. Therapeutic wire **353** may, of course, later be placed within slot **350** (i.e., after strap **330** is made to selectively occupy the slot **350**).

Referring now to FIGS. **7, 8** and **9**, there is shown a bracket **400** which is made in accordance with the teachings of the invention. Particularly, bracket **400** includes a front surface **402** and a back surface **404** which may be substantially similar to back surface or portion **234** which is shown in FIG. **5**.

Front surface **402** includes four substantially similar protuberances **406, 408, 410**, and **412** which cooperatively form a channel **414** in which member **416** resides. Particularly, member **416** is pivotally coupled to surface **402** by attachment pin **420** or a tack weld and has a width **440** which is substantially equal to the width of the channel **414** and member **416** has a nub or protuberance portion **442** which extends off of and away from the surface **402** and away from pin **420**. In one non-limiting embodiment of the invention, the nub portion **442** "curls" or projects away from surface **402** and toward surface **404**.

In operation, the bracket **400** may be attached to the member **212** in the manner which has been previously delineated (e.g., as the back surface **404** is placed onto the ridge member **212**, the nub **442** is made to forcibly pivot away from the surface **402** until the surface **404** is secured onto the member **212** at which time the nub **442** engages the surface **411** of the member **212** onto which it is deployed). Thus, in this embodiment, the bracket **400** is given additional "stability" (e.g. has a reduced likelihood of movement off of member **212**) due to the fact that nub **442** frictionally engages the surface **411** of the member **212**, when the bracket **400** is attached to member **210**, thereby preventing or substantially reducing the likelihood of movement of the bracket **400** from surface **210**. Further, wire **450** may be placed between the protuberances **406, 408, 410** and **412**, thereby further securing the bracket **400** to the surface **210** by preventing disengagement of member **416**. When it is desired to remove the bracket **400** from the member **212**, the wire **450** is removed, the member **416** is pivoted away from the surface **402** (i.e., shown in phantom in FIG. **9**), thereby causing nub **442** to be in a "non-contact" relationship with **411** portion of **212** and then the back surface of the bracket **400** is "slid away" from contact with ridge **212** in the direction of arrow **460**.

Referring now to FIGS. **10** and **11**, there is shown a bracket **500** which is made in accordance with the teachings of yet another alternate embodiment of the invention.

Particularly, bracket **500** has a front surface **502** which is substantially similar to front surface **402** (e.g., having four substantially similar protuberances **504** which are similar to each of the protuberances **406, 408, 410, 412**. However, bracket **500** includes a member **516** which is pivotally coupled, like member **416** to the front surface **502** and which includes a member **542** which, like member **442**, projects away from surface **502**. However, unlike member **416**, the member **516** additionally includes a projection **560** which projects away from the front surface **502**. Further, unlike member **212**, the member **550** includes equidistantly spaced slots, **562, 564, 568, 570, 572**, and **574**, each of which is adapted to selectively and frictionally and removably receive projection **560**. In this manner, the position of the bracket **500** along axis **600** may be selectively modified (e.g., by selecting which slot **562-574** which is to receive the projection **568**, the position of the bracket **500** along axis **600** may be selected).

When it is desired to remove the bracket **500** from the member **210**, the projection **560** is forcibly removed from whatever slot **566-574** it currently resides within, the member

7

**542** is moved away from the detent **700**, and the bracket **500** is slid off the member **210**. Nothing in this description limits the invention to any particular number or types of slots **562**, **564**, **568**, **570**, **572**, and **574** or to any particular number or type of members **560**.

It is to be understood that the various inventions are not limited to the exact construction or methodology which has been delineated anywhere in this description, but that various changes and modifications may be made without departing from the spirit and the scope of the inventions as are delineated in the following claims.

What is claimed is:

1. An orthodontic connector assembly comprising a flat base portion having a flat tooth contacting adhering back surface and a flat front surface, said flat front surface further having a central protruding ridge which has a length less than the length of said flat front surface, and having a certain shape, and which is disposed along a longitudinal axis of said flat front surface, said central protruding ridge having a top edge; said orthodontic connector assembly further comprising a bracket having a front portion with a wire reception slot and a back portion having a single slotted depression which has a shape which is complimentary to said certain shape of said central protruding ridge and wherein said single slotted depression having at least one ridge

8

which is disposed within said single slotted depression and which extends along the width of said single slotted depression; and

said central protruding ridge being selectively and movably disposed within said single slotted depression and wherein said top edge of said central protruding ridge engages said at least one ridge of said single slotted depression when said central protruding ridge is disposed within said single slotted depression, when said at least one ridge of said single slotted depression engages said top edge of said central protruding ridge, said central protruding ridge is secured within said single slotted depression, thereby coupling said first base portion to said bracket.

2. The orthodontic connector assembly of claim 1 wherein said certain shape of said central protruding ridge is a columnar shape.

3. The orthodontic connector assembly of claim 1 wherein said central protruding ridge is selectively movable within and along the length of said single slotted depression.

4. The orthodontic connector assembly of claim 3 wherein said certain shape of said central protruding ridge is a columnar shape.

\* \* \* \* \*