



US 20220121333A1

(19) **United States**(12) **Patent Application Publication**  
**Chauhan**(10) **Pub. No.: US 2022/0121333 A1**(43) **Pub. Date: Apr. 21, 2022**(54) **SYSTEMS AND METHODS FOR LIVE TILES FOR SAAS****Publication Classification**(71) Applicant: **Citrix Systems, Inc.**, Fort Lauderdale, FL (US)(72) Inventor: **Abhishek Chauhan**, Santa Clara, CA (US)(73) Assignee: **Citrix Systems, Inc.**, Fort Lauderdale, FL (US)(21) Appl. No.: **17/562,634**(22) Filed: **Dec. 27, 2021****Related U.S. Application Data**


(63) Continuation of application No. 16/188,166, filed on Nov. 12, 2018, now Pat. No. 11,226,727.

(51) **Int. Cl.****G06F 3/0483** (2006.01)**G06F 3/04817** (2006.01)**H04L 65/1063** (2006.01)(52) **U.S. Cl.**CPC ..... **G06F 3/0483** (2013.01); **G06F 3/04817**(2013.01); **H04L 67/42** (2013.01); **H04L****65/1063** (2013.01); **H04L 63/08** (2013.01)

(57)

**ABSTRACT**

Embodiments described include systems and methods for generating and displaying live tiles for network applications. A small icon or thumbnail-like visual, referred to generally as a “live tile” or “tile”, may be provided via a user interface to a user, with the tile displaying key relevant information from the application or network resource, without the user having to launch the complete application or manually access the resource. The contents of the live tile may be periodically and automatically updated, including performing authentication processes necessary to access the application or resource.






FIG. 1




FIG. 2





FIG. 3






FIG. 5




FIG. 6





FIG. 7








FIG. 9




FIG. 10






FIG. 12




FIG. 13




FIG. 14

## SYSTEMS AND METHODS FOR LIVE TILES FOR SAAS

### CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application is a continuation of and claims priority to and the benefit of U.S. patent application Ser. No. 16/188,166, titled “SYSTEMS AND METHODS FOR LIVE TILES FOR SAAS,” and filed on Nov. 12, 2018, the contents of all of which are hereby incorporated herein by reference in its entirety for all purposes.

### FIELD OF THE DISCLOSURE

[0002] The present application generally relates to management of applications, including but not limited to systems and methods for using an embedded browser to add watermarks.

### BACKGROUND

[0003] As the workforce of an enterprise becomes more mobile and work under various conditions, an individual can use one or more client devices, including personal devices, to access network resources such as web applications. Due to differences between the client devices and the manner in which network resources can be accessed, there are significant challenges to the enterprise in managing access to network resources and monitoring for potential misuse of resources.

[0004] In some implementations, a user may launch web applications or access network resources via a user interface, such as a menu system or set of selectable icons. This user interface may be inefficient and difficult to use, and provide limited information about the associated web application or network resource.

### BRIEF SUMMARY

[0005] A small icon or thumbnail-like visual, referred to generally as a “live tile” or “tile”, may be provided via a user interface to a user, with the tile displaying key relevant information from the application or network resource, without the user having to launch the complete application or manually access the resource. The contents of the live tile may be periodically and automatically updated, including performing authentication processes necessary to access the application or resource.

[0006] The present disclosure is directed towards systems and methods of an embedded browser. A client application executing on a client device can allow a user to access applications (apps) that are served from and/or hosted on one or more servers, such as web applications and software-as-a-service (SaaS) applications (hereafter sometimes generally referred to as network applications). A browser that is embedded or integrated with the client application can render to the user a network application that is accessed or requested via the client application, and can enable interactivity between the user and the network application. The browser is sometimes referred to as an embedded browser, and the client application with embedded browser (CEB) is sometimes referred to as a workspace application. The client application can establish a secure connection to the one or more servers to provide an application session for the user to access the network application using the client device and the embedded browser. The embedded browser can be

integrated with the client application to ensure that traffic related to the network application is routed through and/or processed in the client application, which can provide the client application with real-time visibility to the traffic (e.g., when decrypted through the client application), and user interactions and behavior. The embedded browser can provide a seamless experience to a user as the network application is requested via the user interface (shared by the client application and the embedded browser) and rendered through the embedded browser within the same user interface.

[0007] In one aspect, this disclosure is directed to a method for providing a dynamically updating user interface element associated with a network application. The method includes receiving, by a client application comprising an embedded browser executed by a client device, from an application server executing a network application, a selection of a portion of the network application. The method also includes generating, by the client application, a user interface element comprising the portion of the network application. The method also includes retrieving, by the client application from the application server, data associated with the portion of the network application. The method also includes displaying, by the embedded browser, the user interface element and the retrieved data associated with the portion of the network application.

[0008] In some implementations, the user interface element comprises an icon or thumbnail displaying the retrieved data associated with the portion of the network application. In some implementations, the method includes periodically retrieving, by the client application, updated data associated with the portion of the network application; and updating the display of the user interface element by the embedded browser with the retrieved updated data associated with the portion of the network application.

[0009] In some implementations, periodically retrieving updated data associated with the portion of the network application and updating the display of the user interface element is performed at a first periodic rate; and the method includes: displaying, by the embedded browser, a second user interface element and retrieved data associated with a portion of a second network application; periodically retrieving, by the client application, updated data associated with the portion of the second network application at a second periodic rate different from the first periodic rate; and updating the display of the second user interface element by the embedded browser with the retrieved updated data associated with the portion of the second network application.

[0010] In some implementations, the method includes receiving the selection of the portion of the network application, by a user via the embedded browser; and retrieving data, specific to the user, associated with the portion of the network application. In a further implementation, the method includes receiving the selection of the portion of the network application comprises by receiving authentication credentials of the user, by the client application; and retrieving data, specific to the user, associated with the portion of the network application by retrieving the data, by the client application from the application server, using the authentication credentials of the user.

[0011] In some implementations, generating the user interface element includes extracting a portion of a document-object-model (DOM) element of the network application



corresponding to the selection of the portion of the network application. In some implementations, the method includes detecting an interaction by a user with the user interface element, by the embedded browser; and responsive to detection of the interaction by the user, initiating, by the client application via the embedded browser, execution of the network application.

**[0012]** In some implementations, the method includes transmitting the user interface element to a second client device, a client application of the second client device retrieving the data associated with the portion of the network application from the application server and an embedded browser of the client application of the second client device displaying the user interface element and the retrieved data associated with the portion of the network application. In some implementations, the user interface element further comprises an identification of the network application.

**[0013]** In another aspect, the present disclosure is directed to a system for providing a dynamically updating user interface element associated with a network application. The system includes a client device executing a client application comprising an embedded browser in communication with an application server executing a network application. The client application is configured to: receive a selection of a portion of the network application; generate a user interface element comprising the portion of the network application; and retrieve, from the application server, data associated with the portion of the network application. The embedded browser is configured to display the user interface element and the retrieved data associated with the portion of the network application.

**[0014]** In some implementations, the user interface element comprises an icon or thumbnail displaying the retrieved data associated with the portion of the network application. In some implementations, the client application is further configured to periodically retrieve updated data associated with the portion of the network application; and the embedded browser is configured to update the display of the user interface element with the retrieved updated data associated with the portion of the network application. In a further implementation, the client application is further configured to: periodically retrieve updated data associated with the portion of the network application at a first periodic rate; and periodically retrieve updated data associated with a portion of a second network application at a second periodic rate different from the first periodic rate; and the embedded browser is further configured to: display the second user interface element and retrieved data associated with the portion of the second network application; and update the display of the second user interface element with the retrieved updated data associated with the portion of the second network application.

**[0015]** In some implementations, the client application is further configured to: receive the selection of the portion of the network application, by a user via the embedded browser; and retrieve data, specific to the user, associated with the portion of the network application. In a further implementation, the client application is further configured to: receive authentication credentials of the user responsive to selection of the portion of the network application; and retrieve the data, by the client application from the application server, using the authentication credentials of the user.

**[0016]** In some implementations, the client application is further configured to extract a portion of a document-object-

model (DOM) element of the network application corresponding to the selection of the portion of the network application. In some implementations, the embedded browser is further configured to detect an interaction by a user with the user interface element, by the embedded browser; and the client application is further configured to initiate, via the embedded browser, execution of the network application responsive to detection of the interaction by the user.

**[0017]** In some implementations, the client application is further configured to transmit the user interface element to a second client device, a client application of the second client device retrieving the data associated with the portion of the network application from the application server and an embedded browser of the client application of the second client device displaying the user interface element and the retrieved data associated with the portion of the network application. In some implementations, the user interface element further comprises an identification of the network application.

#### BRIEF DESCRIPTION OF THE FIGURES

**[0018]** The foregoing and other objects, aspects, features, and advantages of the present solution will become more apparent and better understood by referring to the following description taken in conjunction with the accompanying drawings, in which:

**[0019]** FIG. 1 is a block diagram of embodiments of a computing device;

**[0020]** FIG. 2 is a block diagram of an illustrative embodiment of cloud services for use in accessing resources;

**[0021]** FIG. 3 is a block diagram of an example embodiment of an enterprise mobility management system;

**[0022]** FIG. 4 is a block diagram of a system 400 of an embedded browser;

**[0023]** FIG. 5 is a block diagram of an example embodiment of a system for using a secure browser;

**[0024]** FIG. 6 is an example representation of an implementation for browser redirection using a secure browser plug-in;

**[0025]** FIG. 7 is a block diagram of an example embodiment of a system of using a secure browser;

**[0026]** FIG. 8 is a block diagram of an example embodiment of a system for using local embedded browser(s) and hosted secured browser(s);

**[0027]** FIG. 9 is an example process flow for using local embedded browser(s) and hosted secured browser(s);

**[0028]** FIG. 10 is an example embodiment of a system for managing user access to webpages;

**[0029]** FIG. 11 is an illustration of an example embodiment of live tiles for network applications;

**[0030]** FIG. 12 is a block diagram of an example embodiment of a system for providing and utilizing live tiles for network applications;

**[0031]** FIG. 13 is an illustration of one implementation of generation of live tiles for network applications; and

**[0032]** FIG. 14 is a flow chart of an implementation of a method for generating and providing live tiles for network applications.

**[0033]** The features and advantages of the present solution will become more apparent from the detailed description set forth below when taken in conjunction with the drawings, in which like reference characters identify corresponding ele-

ments throughout. In the drawings, like reference numbers generally indicate identical, functionally similar, and/or structurally similar elements.

#### DETAILED DESCRIPTION

**[0034]** For purposes of reading the description of the various embodiments below, the following descriptions of the sections of the specification and their respective contents may be helpful:

**[0035]** Section A describes a computing environment which may be useful for practicing embodiments described herein.

**[0036]** Section B describes systems and methods for an embedded browser.

**[0037]** Section C describes systems and methods for generating and providing live tiles for network applications.

#### A. Computing Environment

**[0038]** Prior to discussing the specifics of embodiments of the systems and methods detailed herein in Section B, it may be helpful to discuss the computing environments in which such embodiments may be deployed.

**[0039]** As shown in FIG. 1, computer **101** may include one or more processors **103**, volatile memory **122** (e.g., random access memory (RAM)), non-volatile memory **128** (e.g., one or more hard disk drives (HDDs) or other magnetic or optical storage media, one or more solid state drives (SSDs) such as a flash drive or other solid state storage media, one or more hybrid magnetic and solid state drives, and/or one or more virtual storage volumes, such as a cloud storage, or a combination of such physical storage volumes and virtual storage volumes or arrays thereof), user interface (UI) **123**, one or more communications interfaces **118**, and communication bus **150**. User interface **123** may include graphical user interface (GUI) **124** (e.g., a touchscreen, a display, etc.) and one or more input/output (I/O) devices **126** (e.g., a mouse, a keyboard, a microphone, one or more speakers, one or more cameras, one or more biometric scanners, one or more environmental sensors, one or more accelerometers, etc.). Non-volatile memory **128** stores operating system **115**, one or more applications **116**, and data **117** such that, for example, computer instructions of operating system **115** and/or applications **116** are executed by processor(s) **103** out of volatile memory **122**. In some embodiments, volatile memory **122** may include one or more types of RAM and/or a cache memory that may offer a faster response time than a main memory. Data may be entered using an input device of GUI **124** or received from I/O device(s) **126**. Various elements of computer **101** may communicate via one or more communication buses, shown as communication bus **150**.

**[0040]** Computer **101** as shown in FIG. 1 is shown merely as an example, as clients, servers, intermediary and other networking devices and may be implemented by any computing or processing environment and with any type of machine or set of machines that may have suitable hardware and/or software capable of operating as described herein. Processor(s) **103** may be implemented by one or more programmable processors to execute one or more executable instructions, such as a computer program, to perform the functions of the system. As used herein, the term “processor” describes circuitry that performs a function, an operation, or a sequence of operations. The function, operation, or

sequence of operations may be hard coded into the circuitry or soft coded by way of instructions held in a memory device and executed by the circuitry. A “processor” may perform the function, operation, or sequence of operations using digital values and/or using analog signals. In some embodiments, the “processor” can be embodied in one or more application specific integrated circuits (ASICs), microprocessors, digital signal processors (DSPs), graphics processing units (GPUs), microcontrollers, field programmable gate arrays (FPGAs), programmable logic arrays (PLAs), multi-core processors, or general-purpose computers with associated memory. The “processor” may be analog, digital or mixed-signal. In some embodiments, the “processor” may be one or more physical processors or one or more “virtual” (e.g., remotely located or “cloud”) processors. A processor including multiple processor cores and/or multiple processors multiple processors may provide functionality for parallel, simultaneous execution of instructions or for parallel, simultaneous execution of one instruction on more than one piece of data.

**[0041]** Communications interfaces **118** may include one or more interfaces to enable computer **101** to access a computer network such as a Local Area Network (LAN), a Wide Area Network (WAN), a Personal Area Network (PAN), or the Internet through a variety of wired and/or wireless or cellular connections.

**[0042]** In described embodiments, the computing device **101** may execute an application on behalf of a user of a client computing device. For example, the computing device **101** may execute a virtual machine, which provides an execution session within which applications execute on behalf of a user or a client computing device, such as a hosted desktop session. The computing device **101** may also execute a terminal services session to provide a hosted desktop environment. The computing device **101** may provide access to a computing environment including one or more of: one or more applications, one or more desktop applications, and one or more desktop sessions in which one or more applications may execute.

**[0043]** Additional details of the implementation and operation of network environment, computer **101** and client and server computers may be as described in U.S. Pat. No. 9,538,345, issued Jan. 3, 2017 to Citrix Systems, Inc. of Fort Lauderdale, Fla., the teachings of which are hereby incorporated herein by reference.

#### B. Systems and Methods for an Embedded Browser

**[0044]** The present disclosure is directed towards systems and methods of an embedded browser. A client application executing on a client device can allow a user to access applications (apps) that are served from and/or hosted on one or more servers, such as web applications and software-as-a-service (SaaS) applications (hereafter sometimes generally referred to as network applications). A browser that is embedded or integrated with the client application can render to the user a network application that is accessed or requested via the client application, and can enable interactivity between the user and the network application. The browser is sometimes referred to as an embedded browser, and the client application with embedded browser (CEB) is sometimes referred to as a workspace application. The client application can establish a secure connection to the one or more servers to provide an application session for the user to access the network application using the client device and

the embedded browser. The embedded browser can be integrated with the client application to ensure that traffic related to the network application is routed through and/or processed in the client application, which can provide the client application with real-time visibility to the traffic (e.g., when decrypted through the client application), and user interactions and behavior. The embedded browser can provide a seamless experience to a user as the network application is requested via the user interface (shared by the client application and the embedded browser) and rendered through the embedded browser within the same user interface.

**[0045]** The client application can terminate one end of a secured connection established with a server of a network application, such as a secure sockets layer (SSL) virtual private network (VPN) connection. The client application can receive encrypted traffic from the network application, and can decrypt the traffic before further processing (e.g., rendering by the embedded browser). The client application can monitor the received traffic (e.g., in encrypted packet form), and also have full visibility into the decrypted data stream and/or the SSL stack. This visibility can allow the client application to perform or facilitate policy-based management (e.g., including data loss prevention (DLP) capabilities), application control (e.g., to improve performance, service level), and collection and production of analytics. For instance, the local CEB can provide an information technology (IT) administrator with a controlled system for deploying web and SaaS applications through the CEB, and allow the IT administrator to set policies or configurations via the CEB for performing any of the foregoing activities.

**[0046]** Many web and SaaS delivered applications connect from web servers to generic browsers (e.g., Internet Explorer, Firefox, and so on) of users. Once authenticated, the entire session of such a network application is encrypted. However, in this scenario, an administrator may not have visibility, analytics, or control of the content entering the network application from the user's digital workspace, or the content leaving the network application and entering the user's digital workspace. Moreover, content of a network application viewed in a generic browser can be copied or downloaded (e.g., by a user or program) to potentially any arbitrary application or device, resulting in a possible breach in data security.

**[0047]** This present systems and methods can ensure that traffic associated with a network application is channeled through a CEB. By way of illustration, when a user accesses a SaaS web service with security assertion markup language (SAML) enabled for instance, the corresponding access request can be forwarded to a designated gateway service that determines, checks or verifies if the CEB was used to make the access request. Responsive to determining that a CEB was used to make the access request, the gateway service can perform or provide authentication and single-sign-on (SSO), and can allow the CEB to connect directly to the SaaS web service. Encryption (e.g., standard encryption) can be used for the application session between the CEB and the SaaS web service. When the content from the web service is unencrypted in the CEB to the viewed via the embedded browser, and/or when input is entered via the CEB, the CEB can provide added services on selective application-related information for control and analytics for instance. For example, an analytics agent or application

programming interface (API) can be embedded in the CEB to provide or perform the added services.

**[0048]** The CEB (sometimes referred to as workspace application or receiver) can interoperate with one or more gateway services, intermediaries and/or network servers (sometimes collectively referred to as cloud services or Citrix Cloud) to provide access to a network application. Features and elements of an environment related to the operation of an embodiment of cloud services are described below.

**[0049]** FIG. 2 illustrates an embodiment of cloud services for use in accessing resources including network applications. The cloud services can include an enterprise mobility technical architecture **200**, which can include an access gateway **260** in one illustrative embodiment. The architecture can be used in a bring-your-own-device (BYOD) environment for instance. The architecture can enable a user of a client device **202** (e.g., a mobile or other device) to both access enterprise or personal resources from a client device **202**, and use the client device **202** for personal use. The user may access such enterprise resources **204** or enterprise services **208** via a client application executing on the client device **202**. The user may access such enterprise resources **204** or enterprise services **208** using a client device **202** that is purchased by the user or a client device **202** that is provided by the enterprise to user. The user may utilize the client device **202** for business use only or for business and personal use. The client device may run an iOS operating system, and Android operating system, or the like. The enterprise may choose to implement policies to manage the client device **202**. The policies may be implanted through a firewall or gateway in such a way that the client device may be identified, secured or security verified, and provided selective or full access to the enterprise resources. The policies may be client device management policies, mobile application management policies, mobile data management policies, or some combination of client device, application, and data management policies. A client device **202** that is managed through the application of client device management policies may be referred to as an enrolled device. The client device management policies can be applied via the client application for instance.

**[0050]** In some embodiments, the operating system of the client device may be separated into a managed partition **210** and an unmanaged partition **212**. The managed partition **210** may have policies applied to it to secure the applications running on and data stored in the managed partition. The applications running on the managed partition may be secure applications. In other embodiments, all applications may execute in accordance with a set of one or more policy files received separate from the application, and which define one or more security parameters, features, resource restrictions, and/or other access controls that are enforced by the client device management system when that application is executing on the device. By operating in accordance with their respective policy file(s), each application may be allowed or restricted from communications with one or more other applications and/or resources, thereby creating a virtual partition. Thus, as used herein, a partition may refer to a physically partitioned portion of memory (physical partition), a logically partitioned portion of memory (logical partition), and/or a virtual partition created as a result of enforcement of one or more policies and/or policy files across multiple apps as described herein (virtual partition).

Stated differently, by enforcing policies on managed apps, those apps may be restricted to only be able to communicate with other managed apps and trusted enterprise resources, thereby creating a virtual partition that is not accessible by unmanaged apps and devices.

**[0051]** The secure applications may be email applications, web browsing applications, software-as-a-service (SaaS) access applications, Windows Application access applications, and the like. The client application can include a secure application launcher **218**. The secure applications may be secure native applications **214**, secure remote applications **222** executed by the secure application launcher **218**, virtualization applications **226** executed by the secure application launcher **218**, and the like. The secure native applications **214** may be wrapped by a secure application wrapper **220**. The secure application wrapper **220** may include integrated policies that are executed on the client device **202** when the secure native application is executed on the device. The secure application wrapper **220** may include meta-data that points the secure native application **214** running on the client device **202** to the resources hosted at the enterprise that the secure native application **214** may require to complete the task requested upon execution of the secure native application **214**. The secure remote applications **222** executed by a secure application launcher **218** may be executed within the secure application launcher application **218**. The virtualization applications **226** executed by a secure application launcher **218** may utilize resources on the client device **202**, at the enterprise resources **204**, and the like. The resources used on the client device **202** by the virtualization applications **226** executed by a secure application launcher **218** may include user interaction resources, processing resources, and the like. The user interaction resources may be used to collect and transmit keyboard input, mouse input, camera input, tactile input, audio input, visual input, gesture input, and the like. The processing resources may be used to present a user interface, process data received from the enterprise resources **204**, and the like. The resources used at the enterprise resources **204** by the virtualization applications **226** executed by a secure application launcher **218** may include user interface generation resources, processing resources, and the like. The user interface generation resources may be used to assemble a user interface, modify a user interface, refresh a user interface, and the like. The processing resources may be used to create information, read information, update information, delete information, and the like. For example, the virtualization application may record user interactions associated with a graphical user interface (GUI) and communicate them to a server application where the server application may use the user interaction data as an input to the application operating on the server. In this arrangement, an enterprise may elect to maintain the application on the server side as well as data, files, etc., associated with the application. While an enterprise may elect to “mobilize” some applications in accordance with the principles herein by securing them for deployment on the client device (e.g., via the client application), this arrangement may also be elected for certain applications. For example, while some applications may be secured for use on the client device, others might not be prepared or appropriate for deployment on the client device so the enterprise may elect to provide the mobile user access to the unprepared applications through virtualization techniques. As another example, the enterprise may have large

complex applications with large and complex data sets (e.g., material resource planning applications) where it would be very difficult, or otherwise undesirable, to customize the application for the client device so the enterprise may elect to provide access to the application through virtualization techniques. As yet another example, the enterprise may have an application that maintains highly secured data (e.g., human resources data, customer data, engineering data) that may be deemed by the enterprise as too sensitive for even the secured mobile environment so the enterprise may elect to use virtualization techniques to permit mobile access to such applications and data. An enterprise may elect to provide both fully secured and fully functional applications on the client device. The enterprise can use a client application, which can include a virtualization application, to allow access to applications that are deemed more properly operated on the server side. In an embodiment, the virtualization application may store some data, files, etc., on the mobile phone in one of the secure storage locations. An enterprise, for example, may elect to allow certain information to be stored on the phone while not permitting other information.

**[0052]** In connection with the virtualization application, as described herein, the client device may have a virtualization application that is designed to present GUIs and then record user interactions with the GUI. The virtualization application may communicate the user interactions to the server side to be used by the server side application as user interactions with the application. In response, the application on the server side may transmit back to the client device a new GUI. For example, the new GUI may be a static page, a dynamic page, an animation, or the like, thereby providing access to remotely located resources.

**[0053]** The secure applications may access data stored in a secure data container **228** in the managed partition **210** of the client device. The data secured in the secure data container may be accessed by the secure wrapped applications **214**, applications executed by a secure application launcher **222**, virtualization applications **226** executed by a secure application launcher **218**, and the like. The data stored in the secure data container **228** may include files, databases, and the like. The data stored in the secure data container **228** may include data restricted to a specific secure application **230**, shared among secure applications **232**, and the like. Data restricted to a secure application may include secure general data **234** and highly secure data **238**. Secure general data may use a strong form of encryption such as Advanced Encryption Standard (AES) 128-bit encryption or the like, while highly secure data **238** may use a very strong form of encryption such as AES 256-bit encryption. Data stored in the secure data container **228** may be deleted from the device upon receipt of a command from the device manager **224**. The secure applications may have a dual-mode option **240**. The dual mode option **240** may present the user with an option to operate the secured application in an unsecured or unmanaged mode. In an unsecured or unmanaged mode, the secure applications may access data stored in an unsecured data container **242** on the unmanaged partition **212** of the client device **202**. The data stored in an unsecured data container may be personal data **244**. The data stored in an unsecured data container **242** may also be accessed by unsecured applications **248** that are running on the unmanaged partition **212** of the client device **202**. The data stored in an unsecured data container **242** may remain

on the client device 202 when the data stored in the secure data container 228 is deleted from the client device 202. An enterprise may want to delete from the client device selected or all data, files, and/or applications owned, licensed or controlled by the enterprise (enterprise data) while leaving or otherwise preserving personal data, files, and/or applications owned, licensed or controlled by the user (personal data). This operation may be referred to as a selective wipe. With the enterprise and personal data arranged in accordance to the aspects described herein, an enterprise may perform a selective wipe.

[0054] The client device 202 may connect to enterprise resources 204 and enterprise services 208 at an enterprise, to the public Internet 248, and the like. The client device may connect to enterprise resources 204 and enterprise services 208 through virtual private network connections. The virtual private network connections, also referred to as microVPN or application-specific VPN, may be specific to particular applications (e.g., as illustrated by microVPNs 250), particular devices, particular secured areas on the client device (e.g., as illustrated by O/S VPN 252), and the like. For example, each of the wrapped applications in the secured area of the phone may access enterprise resources through an application specific VPN such that access to the VPN would be granted based on attributes associated with the application, possibly in conjunction with user or device attribute information. The virtual private network connections may carry Microsoft Exchange traffic, Microsoft Active Directory traffic, HyperText Transfer Protocol (HTTP) traffic, HyperText Transfer Protocol Secure (HTTPS) traffic, application management traffic, and the like. The virtual private network connections may support and enable single-sign-on authentication processes 254. The single-sign-on processes may allow a user to provide a single set of authentication credentials, which are then verified by an authentication service 258. The authentication service 258 may then grant to the user access to multiple enterprise resources 204, without requiring the user to provide authentication credentials to each individual enterprise resource 204.

[0055] The virtual private network connections may be established and managed by an access gateway 260. The access gateway 260 may include performance enhancement features that manage, accelerate, and improve the delivery of enterprise resources 204 to the client device 202. The access gateway may also re-route traffic from the client device 202 to the public Internet 248, enabling the client device 202 to access publicly available and unsecured applications that run on the public Internet 248. The client device may connect to the access gateway via a transport network 262. The transport network 262 may use one or more transport protocols and may be a wired network, wireless network, cloud network, local area network, metropolitan area network, wide area network, public network, private network, and the like.

[0056] The enterprise resources 204 may include email servers, file sharing servers, SaaS/Web applications, Web application servers, Windows application servers, and the like. Email servers may include Exchange servers, Lotus Notes servers, and the like. File sharing servers may include ShareFile servers, and the like. SaaS applications may include Salesforce, and the like. Windows application servers may include any application server that is built to provide applications that are intended to run on a local Windows

operating system, and the like. The enterprise resources 204 may be premise-based resources, cloud based resources, and the like. The enterprise resources 204 may be accessed by the client device 202 directly or through the access gateway 260. The enterprise resources 204 may be accessed by the client device 202 via a transport network 262. The transport network 262 may be a wired network, wireless network, cloud network, local area network, metropolitan area network, wide area network, public network, private network, and the like.

[0057] Cloud services can include an access gateway 260 and/or enterprise services 208. The enterprise services 208 may include authentication services 258, threat detection services 264, device manager services 224, file sharing services 268, policy manager services 270, social integration services 272, application controller services 274, and the like. Authentication services 258 may include user authentication services, device authentication services, application authentication services, data authentication services and the like. Authentication services 258 may use certificates. The certificates may be stored on the client device 202, by the enterprise resources 204, and the like. The certificates stored on the client device 202 may be stored in an encrypted location on the client device, the certificate may be temporarily stored on the client device 202 for use at the time of authentication, and the like. Threat detection services 264 may include intrusion detection services, unauthorized access attempt detection services, and the like. Unauthorized access attempt detection services may include unauthorized attempts to access devices, applications, data, and the like. Device management services 224 may include configuration, provisioning, security, support, monitoring, reporting, and decommissioning services. File sharing services 268 may include file management services, file storage services, file collaboration services, and the like. Policy manager services 270 may include device policy manager services, application policy manager services, data policy manager services, and the like. Social integration services 272 may include contact integration services, collaboration services, integration with social networks such as Facebook, Twitter, and LinkedIn, and the like. Application controller services 274 may include management services, provisioning services, deployment services, assignment services, revocation services, wrapping services, and the like.

[0058] The enterprise mobility technical architecture 200 may include an application store 278. The application store 278 may include unwrapped applications 280, pre-wrapped applications 282, and the like. Applications may be populated in the application store 278 from the application controller 274. The application store 278 may be accessed by the client device 202 through the access gateway 260, through the public Internet 248, or the like. The application store may be provided with an intuitive and easy to use User Interface.

[0059] A software development kit 284 may provide a user the capability to secure applications selected by the user by providing a secure wrapper around the application. An application that has been wrapped using the software development kit 284 may then be made available to the client device 202 by populating it in the application store 278 using the application controller 274.

[0060] The enterprise mobility technical architecture 200 may include a management and analytics capability. The management and analytics capability may provide informa-

tion related to how resources are used, how often resources are used, and the like. Resources may include devices, applications, data, and the like. How resources are used may include which devices download which applications, which applications access which data, and the like. How often resources are used may include how often an application has been downloaded, how many times a specific set of data has been accessed by an application, and the like.

[0061] FIG. 3 depicts an illustrative embodiment of an enterprise mobility management system 300. Some of the components of the mobility management system 200 described above with reference to FIG. 2 have been omitted for the sake of simplicity. The architecture of the system 300 depicted in FIG. 3 is similar in many respects to the architecture of the system 200 described above with reference to FIG. 2 and may include additional features not mentioned above.

[0062] In this case, the left hand side represents an enrolled client device 302 with a client agent 304, which interacts with gateway server 306 to access various enterprise resources 308 and services 309 such as Web or SaaS applications, Exchange, Sharepoint, public-key infrastructure (PKI) Resources, Kerberos Resources, Certificate Issuance service, as shown on the right hand side above. The gateway server 306 can include embodiments of features and functionalities of the cloud services, such as access gateway 260 and application controller functionality. Although not specifically shown, the client agent 304 may be part of, and/or interact with the client application which can operate as an enterprise application store (storefront) for the selection and/or downloading of network applications.

[0063] The client agent 304 can act as a UI (user interface) intermediary for Windows apps/desktops hosted in an Enterprise data center, which are accessed using the High-Definition User Experience (HDX) or Independent Computing Architecture (ICA) display remoting protocol. The client agent 304 can also support the installation and management of native applications on the client device 302, such as native iOS or Android applications. For example, the managed applications 310 (mail, browser, wrapped application) shown in the figure above are native applications that execute locally on the device. Client agent 304 and application management framework of this architecture act to provide policy driven management capabilities and features such as connectivity and SSO (single sign on) to enterprise resources/services 308. The client agent 304 handles primary user authentication to the enterprise, for instance to access gateway (AG) with SSO to other gateway server components. The client agent 304 obtains policies from gateway server 306 to control the behavior of the managed applications 310 on the client device 302.

[0064] The Secure interprocess communication (IPC) links 312 between the native applications 310 and client agent 304 represent a management channel, which allows client agent to supply policies to be enforced by the application management framework 314 “wrapping” each application. The IPC channel 312 also allows client agent 304 to supply credential and authentication information that enables connectivity and SSO to enterprise resources 308. Finally the IPC channel 312 allows the application management framework 314 to invoke user interface functions implemented by client agent 304, such as online and offline authentication.

[0065] Communications between the client agent 304 and gateway server 306 are essentially an extension of the management channel from the application management framework 314 wrapping each native managed application 310. The application management framework 314 requests policy information from client agent 304, which in turn requests it from gateway server 306. The application management framework 314 requests authentication, and client agent 304 logs into the gateway services part of gateway server 306 (also known as NetScaler access gateway). Client agent 304 may also call supporting services on gateway server 306, which may produce input material to derive encryption keys for the local data vaults 316, or provide client certificates which may enable direct authentication to PKI protected resources, as more fully explained below.

[0066] In more detail, the application management framework 314 “wraps” each managed application 310. This may be incorporated via an explicit build step, or via a post-build processing step. The application management framework 314 may “pair” with client agent 304 on first launch of an application 310 to initialize the Secure IPC channel and obtain the policy for that application. The application management framework 314 may enforce relevant portions of the policy that apply locally, such as the client agent login dependencies and some of the containment policies that restrict how local OS services may be used, or how they may interact with the application 310.

[0067] The application management framework 314 may use services provided by client agent 304 over the Secure IPC channel 312 to facilitate authentication and internal network access. Key management for the private and shared data vaults 316 (containers) may be also managed by appropriate interactions between the managed applications 310 and client agent 304. Vaults 316 may be available only after online authentication, or may be made available after offline authentication if allowed by policy. First use of vaults 316 may require online authentication, and offline access may be limited to at most the policy refresh period before online authentication is again required.

[0068] Network access to internal resources may occur directly from individual managed applications 310 through access gateway 306. The application management framework 314 is responsible for orchestrating the network access on behalf of each application 310. Client agent 304 may facilitate these network connections by providing suitable time limited secondary credentials obtained following online authentication. Multiple modes of network connection may be used, such as reverse web proxy connections and end-to-end VPN-style tunnels 318.

[0069] The Mail and Browser managed applications 310 can have special status and may make use of facilities that might not be generally available to arbitrary wrapped applications. For example, the Mail application may use a special background network access mechanism that allows it to access Exchange over an extended period of time without requiring a full AG logon. The Browser application may use multiple private data vaults to segregate different kinds of data.

[0070] This architecture can support the incorporation of various other security features. For example, gateway server 306 (including its gateway services) in some cases might not need to validate active directory (AD) passwords. It can be left to the discretion of an enterprise whether an AD password is used as an authentication factor for some users in

some situations. Different authentication methods may be used if a user is online or offline (i.e., connected or not connected to a network).

**[0071]** Step up authentication is a feature wherein gateway server **306** may identify managed native applications **310** that are allowed to have access to more sensitive data using strong authentication, and ensure that access to these applications is only permitted after performing appropriate authentication, even if this means a re-authentication is requested from the user after a prior weaker level of login.

**[0072]** Another security feature of this solution is the encryption of the data vaults **316** (containers) on the client device **302**. The vaults **316** may be encrypted so that all on-device data including clipboard/cache data, files, databases, and configurations are protected. For on-line vaults, the keys may be stored on the server (gateway server **306**), and for off-line vaults, a local copy of the keys may be protected by a user password or biometric validation. When data is stored locally on the device **302** in the secure container **316**, it is preferred that a minimum of AES 256 encryption algorithm be utilized.

**[0073]** Other secure container features may also be implemented. For example, a logging feature may be included, wherein all security events happening inside an application **310** are logged and reported to the backend. Data wiping may be supported, such as if the application **310** detects tampering, associated encryption keys may be written over with random data, leaving no hint on the file system that user data was destroyed. Screenshot protection is another feature, where an application may prevent any data from being stored in screenshots. For example, the key window's hidden property may be set to YES. This may cause whatever content is currently displayed on the screen to be hidden, resulting in a blank screenshot where any content would normally reside.

**[0074]** Local data transfer may be prevented, such as by preventing any data from being locally transferred outside the application container, e.g., by copying it or sending it to an external application. A keyboard cache feature may operate to disable the autocorrect functionality for sensitive text fields. SSL certificate validation may be operable so the application specifically validates the server SSL certificate instead of it being stored in the keychain. An encryption key generation feature may be used such that the key used to encrypt data on the device is generated using a passphrase or biometric data supplied by the user (if offline access is required). It may be XORed with another key randomly generated and stored on the server side if offline access is not required. Key Derivation functions may operate such that keys generated from the user password use KDFs (key derivation functions, notably Password-Based Key Derivation Function 2 (PBKDF2)) rather than creating a cryptographic hash of it. The latter makes a key susceptible to brute force or dictionary attacks.

**[0075]** Further, one or more initialization vectors may be used in encryption methods. An initialization vector might cause multiple copies of the same encrypted data to yield different cipher text output, preventing both replay and cryptanalytic attacks. This may also prevent an attacker from decrypting any data even with a stolen encryption key. Further, authentication then decryption may be used, wherein application data is decrypted only after the user has authenticated within the application. Another feature may relate to sensitive data in memory, which may be kept in

memory (and not in disk) only when it's needed. For example, login credentials may be wiped from memory after login, and encryption keys and other data inside objective-C instance variables are not stored, as they may be easily referenced. Instead, memory may be manually allocated for these.

**[0076]** An inactivity timeout may be implemented via the CEB, wherein after a policy-defined period of inactivity, a user session is terminated.

**[0077]** Data leakage from the application management framework **314** may be prevented in other ways. For example, when an application **310** is put in the background, the memory may be cleared after a predetermined (configurable) time period. When backgrounded, a snapshot may be taken of the last displayed screen of the application to fasten the foregrounding process. The screenshot may contain confidential data and hence should be cleared.

**[0078]** Another security feature relates to the use of an OTP (one time password) **320** without the use of an AD (active directory) **322** password for access to one or more applications. In some cases, some users do not know (or are not permitted to know) their AD password, so these users may authenticate using an OTP **320** such as by using a hardware OTP system like SecurID (OTPs may be provided by different vendors also, such as Entrust or Gemalto). In some cases, after a user authenticates with a user ID, a text is sent to the user with an OTP **320**. In some cases, this may be implemented only for online use, with a prompt being a single field.

**[0079]** An offline password may be implemented for offline authentication for those applications **310** for which offline use is permitted via enterprise policy. For example, an enterprise may want storefront to be accessed in this manner. In this case, the client agent **304** may require the user to set a custom offline password and the AD password is not used. Gateway server **306** may provide policies to control and enforce password standards with respect to the minimum length, character class composition, and age of passwords, such as described by the standard Windows Server password complexity requirements, although these requirements may be modified.

**[0080]** Another feature relates to the enablement of a client side certificate for certain applications **310** as secondary credentials (for the purpose of accessing PKI protected web resources via the application management framework micro VPN feature). For example, an application may utilize such a certificate. In this case, certificate-based authentication using ActiveSync protocol may be supported, wherein a certificate from the client agent **304** may be retrieved by gateway server **306** and used in a keychain. Each managed application may have one associated client certificate, identified by a label that is defined in gateway server **306**.

**[0081]** Gateway server **306** may interact with an Enterprise special purpose web service to support the issuance of client certificates to allow relevant managed applications to authenticate to internal PKI protected resources.

**[0082]** The client agent **304** and the application management framework **314** may be enhanced to support obtaining and using client certificates for authentication to internal PKI protected network resources. More than one certificate may be supported, such as to match various levels of security and/or separation requirements. The certificates may be used by the Mail and Browser managed applications, and ultimately by arbitrary wrapped applications (provided

those applications use web service style communication patterns where it is reasonable for the application management framework to mediate https requests).

**[0083]** Application management client certificate support on iOS may rely on importing a public-key cryptography standards (PKCS) **12** BLOB (Binary Large Object) into the iOS keychain in each managed application for each period of use. Application management framework client certificate support may use a HTTPS implementation with private in-memory key storage. The client certificate might never be present in the iOS keychain and might not be persisted except potentially in “online-only” data value that is strongly protected.

**[0084]** Mutual SSL or TLS may also be implemented to provide additional security by requiring that a client device **302** is authenticated to the enterprise, and vice versa. Virtual smart cards for authentication to gateway server **306** may also be implemented.

**[0085]** Both limited and full Kerberos support may be additional features. The full support feature relates to an ability to do full Kerberos login to Active Directory (AD) **322**, using an AD password or trusted client certificate, and obtain Kerberos service tickets to respond to HTTP Negotiate authentication challenges. The limited support feature relates to constrained delegation in Citrix Access Gateway Enterprise Edition (AGEE), where AGEE supports invoking Kerberos protocol transition so it can obtain and use Kerberos service tickets (subject to constrained delegation) in response to HTTP Negotiate authentication challenges. This mechanism works in reverse web proxy (aka corporate virtual private network (CVPN)) mode, and when http (but not https) connections are proxied in VPN and MicroVPN mode.

**[0086]** Another feature relates to application container locking and wiping, which may automatically occur upon jail-break or rooting detections, and occur as a pushed command from administration console, and may include a remote wipe functionality even when an application **310** is not running.

**[0087]** A multi-site architecture or configuration of enterprise application store and an application controller may be supported that allows users to be service from one of several different locations in case of failure.

**[0088]** In some cases, managed applications **310** may be allowed to access a certificate and private key via an API (example OpenSSL). Trusted managed applications **310** of an enterprise may be allowed to perform specific Public Key operations with an application’s client certificate and private key. Various use cases may be identified and treated accordingly, such as when an application behaves like a browser and no certificate access is used, when an application reads a certificate for “who am I,” when an application uses the certificate to build a secure session token, and when an application uses private keys for digital signing of important data (e.g., transaction log) or for temporary data encryption.

**[0089]** Referring now to FIG. 4, depicted is a block diagram of a system **400** of an embedded browser. In brief overview, the system **400** may include a client device **402** with a digital workspace for a user, a client application **404**, cloud services **408** operating on at least one network device **432**, and network applications **406** served from and/or hosted on one or more servers **430**. The client application **404** can for instance include at least one of: an embedded browser **410**, a networking agent **412**, a cloud services agent

**414**, a remote session agent **416**, or a secure container **418**. The cloud services **408** can for instance include at least one of: secure browser(s) **420**, an access gateway **422** (or CIS, e.g., for registering and/or authenticating the client application and/or user), or analytics services **424** (or CAS, e.g., for receiving information from the client application for analytics). The network applications **406** can include sanctioned applications **426** and non-sanctioned applications **428**.

**[0090]** Each of the above-mentioned elements or entities is implemented in hardware, or a combination of hardware and software, in one or more embodiments. Each component of the system **400** may be implemented using hardware or a combination of hardware or software detailed above in connection with FIG. 1. For instance, each of these elements or entities can include any application, program, library, script, task, service, process or any type and form of executable instructions executing on hardware of the client device **402**, the at least one network device **432** and/or the one or more servers **430**. The hardware includes circuitry such as one or more processors in one or more embodiments. For example, the at least one network device **432** and/or the one or more servers **430** can include any of the elements of a computing device described above in connection with at least FIG. 1 for instance.

**[0091]** The client device **402** can include any embodiment of a computing device described above in connection with at least FIG. 1 for instance. The client device **402** can include any user device such as a desktop computer, a laptop computer, a tablet device, a smart phone, or any other mobile or personal device. The client device **402** can include a digital workspace of a user, which can include file system(s), cache or memory (e.g., including electronic clipboard(s)), container(s), application(s) and/or other resources on the client device **402**. The digital workspace can include or extend to one or more networks accessible by the client device **402**, such as an intranet and the Internet, including file system(s) and/or other resources accessible via the one or more networks. A portion of the digital workspace can be secured via the use of the client application **404** with embedded browser **410** (CEB) for instance. The secure portion of the digital workspace can include for instance file system(s), cache or memory (e.g., including electronic clipboard(s)), application(s), container(s) and/or other resources allocated to the CEB, and/or allocated by the CEB to network application(s) **406** accessed via the CEB. The secure portion of the digital workspace can also include resources specified by the CEB (via one or more policies) for inclusion in the secure portion of the digital workspace (e.g., a particular local application can be specified via a policy to be allowed to receive data obtained from a network application).

**[0092]** The client application **404** can include one or more components, such as an embedded browser **410**, a networking agent **412**, a cloud services agent **414** (sometimes referred to as management agent), a remote session agent **416** (sometimes referred to as HDX engine), and/or a secure container **418** (sometimes referred to as secure cache container). One or more of the components can be installed as part of a software build or release of the client application **404** or CEB, or separately acquired or downloaded and installed/integrated into an existing installation of the client application **404** or CEB for instance. For instance, the client device may download or otherwise receive the client application **404** (or any component) from the network device(s)



**432.** In some embodiments, the client device may send a request for the client application **404** to the network device (s) **432**. For example, a user of the client device can initiate a request, download and/or installation of the client application. The network device(s) **432** in turn may send the client application to the client device. In some embodiments, the network device(s) **432** may send a setup or installation application for the client application to the client device. Upon receipt, the client device may install the client application onto a hard disk of the client device. In some embodiments, the client device may run the setup application to unpack or decompress a package of the client application. In some embodiments, the client application may be an extension (e.g., an add-on, an add-in, an applet or a plug-in) to another application (e.g., a networking agent **412**) installed on the client device. The client device may install the client application to interface or inter-operate with the pre-installed application. In some embodiments, the client application may be a standalone application. The client device may install the client application to execute as a separate process.

**[0093]** The embedded browser **410** can include elements and functionalities of a web browser application or engine. The embedded browser **410** can locally render network application(s) as a component or extension of the client application. For instance, the embedded browser **410** can render a SaaS/Web application inside the CEB which can provide the CEB with full visibility and control of the application session. The embedded browser can be embedded or incorporated into the client application via any means, such as direct integration (e.g., programming language or script insertion) into the executable code of the client application, or via plugin installation. For example, the embedded browser can include a Chromium based browser engine or other type of browser engine, that can be embedded into the client application, using the Chromium embedded framework (CEF) for instance. The embedded browser can include a HTML5-based layout graphical user interface (GUI). The embedded browser can provide HTML rendering and JavaScript support to a client application incorporating various programming languages. For example, elements of the embedded browser can bind to a client application incorporating C, C++, Delphi, Go, Java, .NET/Mono, Visual Basic 6.0, and/or Python.

**[0094]** In some embodiments, the embedded browser comprises a plug-in installed on the client application. For example, the plug-in can include one or more components. One such components can be an ActiveX control or Java control or any other type and/or form of executable instructions capable of loading into and executing in the client application. For example, the client application can load and run an Active X control of the embedded browser, such as in a memory space or context of the client application. In some embodiments, the embedded browser can be installed as an extension on the client application, and a user can choose to enable or disable the plugin or extension. The embedded browser (e.g., via the plugin or extension) can form or operate as a secured browser for securing, using and/or accessing resources within the secured portion of the digital workspace.

**[0095]** The embedded browser can incorporate code and functionalities beyond that available or possible in a standard or typical browser. For instance, the embedded browser can bind with or be assigned with a secured container **418**,

to define at least part of the secured portion of a user's digital workspace. The embedded browser can bind with or be assigned with a portion of the client device's cache to form a secured clipboard (e.g., local to the client device, or extendable to other devices), that can be at least part of the secured container **418**. The embedded browser can be integrated with the client application to ensure that traffic related to network applications is routed through and/or processed in the client application, which can provide the client application with real-time visibility to the traffic (e.g., when decrypted through the client application). This visibility to the traffic can allow the client application to perform or facilitate policy-based management (e.g., including data loss prevention (DLP) capabilities), application control, and collection and production of analytics.

**[0096]** In some embodiments, the embedded browser incorporates one or more other components of the client application **404**, such as the cloud services agent **414**, remote session agent **416** and/or secure container **418**. For instance, a user can use the cloud services agent **414** of the embedded browser to interoperate with the access gateway **422** (sometimes referred to as CIS) to access a network application. For example, the cloud services agent **414** can execute within the embedded browser, and can receive and transmit navigation commands from the embedded browser to a hosted network application. The cloud services agent can use a remote presentation protocol to display the output generated by the network application to the embedded browser. For example, the cloud services agent **414** can include a HTML5 web client that allows end users to access remote desktops and/or applications on the embedded browser.

**[0097]** The client application **404** and CEB operate on the application layer of the operational (OSI) stack of the client device. The client application **404** can include and/or execute one or more agents that interoperate with the cloud services **408**. The client application **404** can receive, obtain, retrieve or otherwise access various policies (e.g., an enterprise's custom, specified or internal policies or rules) and/or data (e.g., from an access gateway **422** and/or network device(s) of cloud services **408**, or other server(s), that may be managed by the enterprise). The client application can access the policies and/or data to control and/or manage a network application (e.g., a SaaS, web or remote-hosted application). Control and/or management of a network application can include control and/or management of various aspects of the network application, such as access control, session delivery, available features or functions, service level, traffic management and monitoring, and so on. The network application can be from a provider or vendor of the enterprise (e.g., salesforce.com, SAP, Microsoft Office **365**), from the enterprise itself, or from another entity (e.g., Dropbox or Gmail service).

**[0098]** For example, the cloud services agent **414** can provide policy driven management capabilities and features related to the use and/or access of network applications. For example, the cloud services agent **414** can include a policy engine to apply one or more policies (e.g., received from cloud services) to determine access control and/or connectivity to resources such as network applications. When a session is established between the client application and a server **430** providing a SaaS application for instance, the cloud services agent **414** can apply one or more policies to control traffic levels and/or traffic types (or other aspects) of

the session, for instance to manage a service level of the SaaS application. Additional aspects of the application traffic that can be controlled or managed can include encryption level and/or encryption type applied to the traffic, level of interactivity allowed for a user, limited access to certain features of the network application (e.g., print-screen, save, edit or copy functions), restrictions to use or transfer of data obtained from the network application, limit concurrent access to two or more network applications, limit access to certain file repositories or other resources, and so on.

[0099] The cloud services agent **414** can convey or feed information to analytics services **424** of the cloud services **408**, such as information about SaaS interaction events visible to the CEB. Such a configuration using the CEB can monitor or capture information for analytics without having an inline device or proxy located between the client device and the server(s) **430**, or using a SaaS API gateway 'out-of-band' approach. In some embodiments, the cloud services agent **414** does not execute within the embedded browser. In these embodiments, a user can similarly use the cloud services agent **414** to interoperate with the access gateway (or CIS) **422** to access a network application. For instance, the cloud services agent **414** can register and/or authenticate with the access gateway (or CIS) **422**, and can obtain a list of the network applications from the access gateway (or CIS) **422**. The cloud services agent **414** can include and/or operate as an application store (or storefront) for user selection and/or downloading of network applications. Upon logging in to access a network application, the cloud services agent **414** can intercept and transmit navigation commands from the embedded browser to the network application. The cloud services agent can use a remote presentation protocol to display the output generated by the network application to the embedded browser. For example, the cloud services agent **414** can include a HTML5 web client that allows end users to access remote desktops and/or applications on the embedded browser.

[0100] In some embodiments, the cloud services agent **414** provides single sign on (SSO) capability for the user and/or client device to access a plurality of network applications. The cloud services agent **414** can perform user authentication to access network applications as well as other network resources and services, by communicating with the access gateway **422** for instance. For example, the cloud services agent **414** can authenticate or register with the access gateway **422**, to access other components of the cloud services **408** and/or the network applications **406**. Responsive to the authentication or registration, the access gateway **422** can perform authentication and/or SSO for (or on behalf of) the user and/or client application, with the network applications.

[0101] The client application **404** can include a networking agent **412**. The networking agent **412** is sometimes referred to as a software-defined wide area network (SD-WAN) agent, mVPN agent, or microVPN agent. The networking agent **412** can establish or facilitate establishment of a network connection between the client application and one or more resources (e.g., server **430** serving a network application). The networking agent **412** can perform handshaking for a requested connection from the client application to access a network application, and can establish the requested connection (e.g., secure or encrypted connection). The networking agent **412** can connect to enterprise resources (including services) for instance via a virtual

private network (VPN). For example, the networking agent **412** can establish a secure socket layer (SSL) VPN between the client application and a server **430** providing the network application **406**. The VPN connections, sometimes referred to as microVPN or application-specific VPN, may be specific to particular network applications, particular devices, particular secured areas on the client device, and the like, for instance as discussed above in connection with FIG. 3. Such VPN connections can carry Microsoft Exchange traffic, Microsoft Active Directory traffic, HyperText Transfer Protocol (HTTP) traffic, HyperText Transfer Protocol Secure (HTTPS) traffic, as some examples.

[0102] The remote session agent **416** (sometimes referred to as HDX engine) can include features of the client agent **304** discussed above in connection with FIG. 2 for instance, to support display a remoting protocol (e.g., HDX or ICA). In some embodiments, the remote session agent **416** can establish a remote desktop session and/or remote application session in accordance to any variety of protocols, such as the Remote Desktop Protocol (RDP), Appliance Link Protocol (ALP), Remote Frame Buffer (RFB) Protocol, and ICA Protocol. For example, the remote session agent **416** can establish a remote application session for a user of the client device to access an enterprise network application. The remote session agent **416** can establish the remote application session within or over a secure connection (e.g., a VPN) established by the networking agent **412** for instance.

[0103] The client application or CEB can include or be associated with a secure container **418**. A secure container can include a logical or virtual delineation of one or more types of resources accessible within the client device and/or accessible by the client device. For example, the secure container **418** can refer to the entirety of the secured portion of the digital workspace, or particular aspect(s) of the secured portion. In some embodiments, the secure container **418** corresponds to a secure cache (e.g., electronic or virtual clipboard), and can dynamically incorporate a portion of a local cache of each client device of a user, and/or a cloud-based cache of the user, that is protected or secured (e.g., encrypted). The secure container can define a portion of file system(s), and/or delineate resources allocated to a CEB and/or to network applications accessed via the CEB. The secure container can include elements of the secure data container **228** discussed above in connection with FIG. 2 for example. The CEB can be configured (e.g., via policies) to limit, disallow or disable certain actions or activities on resources and/or data identified to be within a secure container. A secured container can be defined to specify that the resources and/or data within the secure container are to be monitored for misuse, abuse and/or exfiltration.

[0104] In certain embodiments, a secure container relates to or involves the use of a secure browser (e.g., embedded browser **410** or secure browser **420**) that implements various enterprise security features. Network applications (or web pages accessed by the secure browser) that are configured to run within the secure browser can effectively inherit the security mechanisms implemented by the secure browser. These network applications can be considered to be contained within the secure container. The use of such a secure browser can enable an enterprise to implement a content filtering policy in which, for example, employees are blocked from accessing certain web sites from their client

devices. The secure browser can be used, for example, to enable client device users to access a corporate intranet without the need for a VPN.

**[0105]** In some embodiments, a secure container can support various types of remedial actions for protecting enterprise resources. One such remedy is to lock the client device, or a secure container on the client device that stores data to be protected, such that the client device or secure container can only be unlocked with a valid code provided by an administrator for instance. In some embodiments, these and other types of remedies can be invoked automatically based on conditions detected on the client device (via the application of policies for instance), or can be remotely initiated by an administrator.

**[0106]** In some embodiments, a secure container can include a secure document container for documents. A document can comprise any computer-readable file including text, audio, video, and/or other types of information or media. A document can comprise any single one or combination of these media types. As explained herein, the secure container can help prevent the spread of enterprise information to different applications and components of the client device, as well as to other devices. The enterprise system (which can be partially or entirely within a cloud network) can transmit documents to various devices, which can be stored within the secure container. The secure container can prevent unauthorized applications and other components of the client device from accessing information within the secure container. For enterprises that allow users to use their own client devices for accessing, storing, and using enterprise data, providing secure container on the client devices helps to secure the enterprise data. For instance, providing secure containers on the client devices can centralize enterprise data in one location on each client device, and can facilitate selective or complete deletion of enterprise data from each client device when desired.

**[0107]** The secure container can include an application that implements a file system that stores documents and/or other types of files. The file system can comprise a portion of a computer-readable memory of the client device. The file system can be logically separated from other portions of the computer-readable memory of the client device. In this way, enterprise data can be stored in a secure container and private data can be stored in a separate portion of the computer-readable memory of the client device for instance. The secure container can allow the CEB, network applications accessed via the CEB, locally installed applications and/or other components of the client device to read from, write to, and/or delete information from the file system (if authorized to do so). Deleting data from the secure container can include deleting actual data stored in the secure container, deleting pointers to data stored in the secure container, deleting encryption keys used to decrypt data stored in the secure container, and the like. The secure container can be installed by, e.g., the client application, an administrator, or the client device manufacturer. The secure container can enable some or all of the enterprise data stored in the file system to be deleted without modifying private data stored on the client device outside of the secure container. The file system can facilitate selective or complete deletion of data from the file system. For example, an authorized component of the enterprise's system can delete data from the file system based on, e.g., encoded rules. In some

embodiments, the client application can delete the data from the file system, in response to receiving a deletion command from the enterprise's system.

**[0108]** The secure container can include an access manager that governs access to the file system by applications and other components of the client device. Access to the file system can be governed based on document access policies (e.g., encoded rules) maintained by the client application, in the documents and/or in the file system. A document access policy can limit access to the file system based on (1) which application or other component of the client device is requesting access, (2) which documents are being requested, (3) time or date, (4) geographical position of the client device, (5) whether the requesting application or other component provides a correct certificate or credentials, (6) whether the user of the client device provides correct credentials, (7) other conditions, or any combination thereof. A user's credentials can comprise, for example, a password, one or more answers to security questions (e.g., What is the mascot of your high school?), biometric information (e.g., fingerprint scan, eye-scan), and the like. Hence, by using the access manager, the secure container can be configured to be accessed only by applications that are authorized to access the secure container. As one example, the access manager can enable enterprise applications installed on the client device to access data stored in the secure container and to prevent non-enterprise applications from accessing the data stored in the secure container.

**[0109]** Temporal and geographic restrictions on document access may be useful. For example, an administrator may deploy a document access policy that restricts the availability of the documents (stored within the secure container) to a specified time window and/or a geographic zone (e.g., as determined by a GPS chip) within which the client device must reside in order to access the documents. Further, the document access policy can instruct the secure container or client application to delete the documents from the secure container or otherwise make them unavailable when the specified time period expires or if the client device is taken outside of the defined geographic zone.

**[0110]** Some documents can have access policies that forbid the document from being saved within the secure container. In such embodiments, the document can be available for viewing on the client device only when the user is logged in or authenticated via the cloud services for example.

**[0111]** The access manager can also be configured to enforce certain modes of connectivity between remote devices (e.g., an enterprise resource or other enterprise server) and the secure container. For example, the access manager can require that documents received by the secure container from a remote device and/or sent from the secure container to the remote device be transmitted through secured tunnels/connections, for example. The access manager can require that all documents transmitted to and from the secure container be encrypted. The client application or access manager can be configured to encrypt documents sent from the secure container and decrypt documents sent to the secure container. Documents in the secure container can also be stored in an encrypted form.

**[0112]** The secure container can be configured to prevent documents or data included within documents or the secure container from being used by unauthorized applications or components of the client device or other devices. For

instance, a client device application having authorization to access documents from the secure container can be programmed to prevent a user from copying a document's data and pasting it into another file or application interface, or locally saving the document or document data as a new file outside of the secure container. Similarly, the secure container can include a document viewer and/or editor that do not permit such copy/paste and local save operations. Moreover, the access manager can be configured to prevent such copy/paste and local save operations. Further, the secure container and applications programmed and authorized to access documents from the secure container can be configured to prevent users from attaching such documents to emails or other forms of communication.

**[0113]** One or more applications (e.g., applications installed on the client device, and/or network applications accessed via the CEB) can be programmed or controlled (e.g., via policy-based enforcement) to write enterprise-related data only into the secure container. For instance, an application's source code can be provided with the resource name of the secure container. Similarly, a remote application (e.g., executing on a device other than the client device) can be configured to send data or documents only to the secure container (as opposed to other components or memory locations of the client device). Storing data to the secure container can occur automatically, for example, under control of the application, the client application, and/or the secure browser. The client application can be programmed to encrypt or decrypt documents stored or to be stored within the secure container. In certain embodiments, the secure container can only be used by applications (on the client device or a remote device) that are programmed to identify and use the secure container, and which have authorization to do so.

**[0114]** The network applications **406** can include sanctioned network applications **426** and non-sanctioned network applications **428**. By way of a non-limiting example, sanctioned network applications **426** can include network applications from Workday, Salesforce, Office **365**, SAP, and so on, while non-sanctioned network applications **426** can include network applications from Dropbox, Gmail, and so on. For instance, FIG. 4 illustrates a case where sanctioned applications **426** are accessed via a CEB. In operation (1), a user instance of a client application **404**, that is installed on client device **402**, can register or authenticate with the access gateway **422** of cloud services **408**. For example, the user can authenticate the user to the client device and login to the client device **402**. The client application can automatically execute, or be activated by the user. In some embodiments, the user can sign in to the client application (e.g., by authenticating the user to the client application). In response to the login or sign-in, the client application can register or authenticate the user and/or the client application with the access gateway **422**.

**[0115]** In operation (2), in response to the registration or authentication, the access gateway **422** can identify or retrieve a list of enumerated network applications available or pre-assigned to the user, and can provide the list to the client application. For example, in response to the registration or authentication, the access gateway can identify the user and/or retrieve a user profile of the user. According to the identity and/or user profile, the access gateway can determine the list (e.g., retrieve a stored list of network applications matched with the user profile and/or the identity

of the user). The list can correspond to a list of network applications sanctioned for the user. The access gateway can send the list to the client application or embedded browser, which can be presented via the client application or embedded browser to the user (e.g., in a storefront user interface) for selection.

**[0116]** In operation (3), the user can initiate connection to a sanctioned network application (e.g., a SaaS application), by selecting from the list of network applications presented to the user. For example, the user can click on an icon or other representation of the sanctioned network application, displayed via the client application or embedded browser. This user action can trigger the CEB to transmit a connection or access request to a server that provisions the network application. The request can include a request to the server (e.g., SaaS provider) to communicate with the access gateway to authenticate the user. The server can send a request to the access gateway to authenticate the user for example.

**[0117]** In operation (4), the access gateway can perform SSO with the server, to authenticate the user. For example, in response to the server's request to authenticate the user, the access gateway can provide credentials of the user to the server(s) **430** for SSO, to access the selected network application and/or other sanctioned network applications. In operation (5), the user can log into the selected network application, based on the SSO (e.g., using the credentials). The client application (e.g., the networking agent **412** and/or the remote session agent **416**) can establish a secure connection and session with the server(s) **430** to access the selected network application. The CEB can decrypt application traffic received via the secure connection. The CEB can monitor traffic sent via the CEB and the secured connection to the servers **430**.

**[0118]** In operation (6), the client application can provide information to the analytics services **424** of cloud services **408**, for analytics processing. For example, the cloud services agent **414** of the client application **404** can monitor for or capture user interaction events with the selected network application. The cloud services agent **414** can convey the user interaction events to the analytics services **424**, to be processed to produce analytics.

**[0119]** FIG. 5 depicts an example embodiment of a system for using a secure browser. In brief overview, the system includes cloud services **408**, network applications **406** and client device **402**. In some embodiments, various elements of the system are similar to that described above for FIG. 4, but that the client application (with embedded browser) is not available in the client device **402**. A standard or typical browser may be available on the client device, from which a user can initiate a request to access a sanctioned network application for instance. A network application can be specified as being sanctioned or unsanctioned via policies that can be set by an administrator or automatically (e.g., via artificial intelligence).

**[0120]** For example, in operation (1), the user may log into the network application using the standard browser. For accessing a sanctioned network application, the user may access a predefined URL and/or corresponding webpage of a server that provisions the network application, via the standard browser, to initiate a request to access the network application. In some embodiments, the request can be forwarded to or intercepted by a designated gateway service (e.g., in a data path of the request). For example, the gateway service can reside on the client device (e.g., as an executable

program), or can reside on a network device **432** of the cloud services **408** for instance. In some embodiments, the access gateway can correspond to or include the gateway service. The gateway service can determine if the requested network application is a sanctioned network application. The gateway service can determine if a CEB initiated the request. The gateway service can detect or otherwise determine that the request is initiated from a source (e.g., initiated by the standard browser) in the client device other than a CEB. In some embodiments, there is no requirement for a designated gateway service to detect or determine if the request is initiated from a CEB, for example if the requested network application is sanctioned, that user is initiating the request via a standard browser, and/or that the predefined URL and/or corresponding webpage is accessed.

[0121] In operation (2), the server may authenticate the user via the access gateway of the cloud services **408**. The server may communicate with the access gateway to authenticate the user, in response to the request. For instance, the request can include an indication to the server to communicate with the access gateway to authenticate the user. In some embodiments, the server is pre-configured to communicate with the access gateway to authenticate the user, for requests to access a sanctioned network application. The server may send a request to the access gateway to authenticate the user. In response to the server's request to authenticate the user, the access gateway can provide credentials of the user to the server **430**.

[0122] In operation (3), the gateway service and/or the server can direct (or redirect) all traffic to a secure browser **420** which provides a secure browsing service. This may be in response to at least one of: a determination that the requested network application is a sanctioned network application, a determination that the request is initiated from a source other than a CEB, a determination that the requested network application is sanctioned, a determination that user is initiating the request via a standard browser, and/or a determination that the predefined URL and/or corresponding webpage is accessed.

[0123] The user's URL session can be redirected to the secure browser. For example, the server, gateway service and/or the access gateway can generate and/or send a URL redirect message to the standard browser, responsive to the determination. The secure browser plug-in of the standard browser can receive the URL redirect message, and can for example send a request to access the non-sanctioned network application, to the secure browser **420**. The secure browser **420** can direct the request to the server of the non-sanctioned network application. The URL redirect message can instruct the standard browser (and/or the secure browser plug-in) to direct traffic (e.g., destined for the network application) from the standard browser to the secure browser **420** hosted on a network device. This can provide clientless access and control via dynamic routing through a secure browser service. In some embodiments, a redirection of all traffic to the secure browser **420** is initiated or configured, prior to performing authentication of the user (e.g., using SSO) with the server.

[0124] In some embodiments, the gateway service can direct or request the server of the requested network application to communicate with the secure browser **420**. For example, the gateway service can direct the server and/or the secure browser to establish a secured connection between

the server and the secure browser, for establishing an application session for the network application.

[0125] In some embodiments, the secured browser **420** comprises a browser that is hosted on a network device **432** of the cloud services **408**. The secured browser **420** can include one or more features of the secured browser **420** described above in connection with at least FIG. 4 for instance. The hosted browser can include an embedded browser of a CEB that is hosted on the network device **432** instead of on the client device. The hosted browser can include an embedded browser of a hosted virtualized version of the CEB that is hosted on the network device **432**. Similar to the CEB installed on the client device, traffic is routed through the CEB hosted on the network device, which allows an administrator to have visibility of the traffic through the CEB and to remain in control for security policy control, analytics, and/or management of performance.

[0126] FIG. 6 illustrates an example implementation for browser redirection using a secure browser plug-in. In brief overview, the implementation includes a web browser **512** with a secure browser plug-in **516** operating on a client device, and a hosted web browser (or secure browser) **522** residing on a network device. The web browser **512** can correspond to a standard browser, instead of an embedded browser as discussed above in connection with FIG. 4 for example. The secure browser plug-in **516** can execute within a first network **510** and access a server **430** in a second network **530**. The first network **510** and the second network **530** are for illustration purposes and may be replaced with fewer or additional computer networks. A secure browser plug-in **516** can be installed on the standard browser **512**. The plug-in can include one or more components. One such component can include an ActiveX control or Java control or any other type and/or form of executable instructions capable of loading into and executing in the standard browser. For example, the standard browser can load and run an Active X control of the secure browser plug-in **516**, in a memory space or context of the standard browser. In some embodiments, the secure browser plug-in can be installed as an extension on the standard browser, and a user can choose to enable or disable the plugin or extension. The secure browser plug-in can communicate and/or operate with the secured browser **420** for securing, using and/or accessing resources within the secured portion of the digital workspace.

[0127] By using the secure browser plug-in **516** operating within the standard browser **512** network applications accessed via the standard browser **512** can be redirected to a hosted secure browser. For instance, the secure browser plug-in **516** can be implemented and/or designed to detect that a network application is being accessed via the standard browser, and can direct/redirect traffic from the client device associated with the network application, to the hosted secure browser. The hosted secure browser can direct traffic received from the network application, to the secure browser plug-in **516** and/or a client agent **514** for rendering and/or display for example. The client agent **514** can execute within the web browser **512** and/or the secure browser plug-in, and can include certain elements or features of the client application **404** discussed above in connection with at least FIG. 4 for example. For instance, the client agent **514** can include a remote session agent **416** for rendering the network application at the web browser **512**. In some embodiments, the network application is rendered at the hosted secure

browser, and the rendered data is conveyed or mirrored to the secure browser plug-in **516** and/or the client agent **514** for processing and/or display.

**[0128]** By way of an example, a user may be working remotely and may want to access a network application that is internal to a secure corporate network while the user is working on a computing device connected to an unsecure network. In this case, the user may be utilizing the standard browser **512** executing in the first network **510**, in which the first network **510** may comprise an unsecure network. The server **430** that the user wants to access may be on the second network **530**, in which the second network **530** comprises a secure corporate network for instance. The user might not be able to access the server **430** from the unsecure first network **510** by clicking on an internal uniform record locator (URL) for the secure website **532**. That is, the user may need to utilize a different URL (e.g., an external URL) while executing the standard browser **512** from the external unsecure network **510**. The external URL may be directed to or may address one or more hosted web browsers **522** configured to access server(s) **430** within the second network **530** (e.g., secure network). To maintain secure access, the secure browser plug-in **516** may redirect an internal URL to an external URL for a hosted secure browser.

**[0129]** The secure browser plug-in **516** may be able to implement network detection in order to identify whether or not to redirect internal URLs to external URLs. The standard browser **512** may receive a request comprising an internal URL for a website executing within the secure network. For example, the standard browser **512** may receive the request in response to a user entering a web address (e.g., for secure website **532**) in the standard browser. The secure browser plug-in **516** may redirect the user web browser application **512** from the internal URL to an external URL for a hosted web browser application. For example, the secure browser plug-in **516** may replace the internal URL with an external URL for the hosted web browser application **522** executing within the secure network **530**.

**[0130]** The secure browser plug-in **516** may allow the client agent **514** to be connected to the hosted web browser application **522**. The client agent **514** may comprise a plug-in component, such as an ActiveX control or Java control or any other type and/or form of executable instructions capable of loading into and executing in the standard browser **512**. For example, the client agent **514** may comprise an ActiveX control loaded and run by a standard browser **512**, such as in the memory space or context of the user web browser application **512**. The client agent **514** may be pre-configured to present the content of the hosted web browser application **522** within the user web browser application **512**.

**[0131]** The client agent **514** may connect to a server or the cloud/hosted web browser service **520** using a thin-client or remote-display protocol to present display output generated by the hosted web browser application **522** executing on the service **520**. The thin-client or remote-display protocol can be any one of the following non-exhaustive list of protocols: the Independent Computing Architecture (ICA) protocol developed by Citrix Systems, Inc. of Ft. Lauderdale, Fla.; or the Remote Desktop Protocol (RDP) manufactured by the Microsoft Corporation of Redmond, Wash.

**[0132]** The hosted web browser application **522** may navigate to the requested network application in full-screen mode, and can render the requested network application.

The client agent **514** may present the content or rendition of the network application on the web browser application **512** in a seamless and transparent manner such that it appears that the content is being displayed by the standard browser **512**, e.g., based on the content being displayed in full screen mode. In other words, the user may be given the impression that the web site content is displayed by the user web browser application **512** and not by the hosted web browser application **522**. The client agent **514** may transmit navigation commands generated by the user web browser application **512** to the hosted web browser application **522** using the thin-client or remote-display protocol. Changes to the display output of the hosted web browser application **522**, due to the navigation commands, may be reflected in the user web browser application **512** by the client agent **514**, giving the impression to the user that the navigation commands were executed by the user web browser application **512**.

**[0133]** Referring again to FIG. 5, and in operation (4), a new browser tab can open on the standard browser, to render or display the secure browser session. The new browser tab can be established or opened by the secure browser plug-in for instance. The secure browser plug-in and/or a client agent can receive data from the secure browser session, and can render the network application within the new browser tab as discussed above in connection with FIG. 6 for instance.

**[0134]** In operation (5), the secure browser can feed all user interaction events via the network application, back to analytics service for processing. The secure browser plug-in can monitor for and intercept any user interaction events directed to the rendition of the network application within the browser tab. Hence, a user can use a native (or standard) browser to access a network application while allowing visibility into the network application's traffic, via the inter-operation of cloud services and a secure browser (in the absence of the client application).

**[0135]** FIG. 7 depicts another example embodiment of a system of using a secure browser. In brief overview, the system includes cloud services **408**, network applications **406** and the client device **402**. In some embodiments, various elements of the system are similar to that described above for FIG. 5. A client application with embedded browser is not available in the client device **402**. A standard or typical (e.g., HTML5) browser is available on the client device, from which a user can initiate a request to access a non-sanctioned network application. A network application can be specified as being sanctioned or non-sanctioned via policies that can be set by an administrator or automatically (e.g., via artificial intelligence).

**[0136]** In operation (1), the user may attempt to log into a non-sanctioned network application using the standard browser. The user may attempt to access a webpage of a server that provisions the network application, and to initiate a request to access the network application. In some embodiments, the request can be forwarded to or intercepted by a designated gateway service (e.g., in a data path of the request). For example, the gateway service (sometimes referred to as SWG) can reside on the client device (e.g., as an executable program), or can reside on a network device **432** of the cloud services **408** for instance. The gateway service can detect or otherwise determine if the requested network application is a sanctioned network application. The gateway service can determine if a CEB initiated the request. The gateway service can detect or otherwise deter-

mine that the request is initiated from a source (e.g., initiated by the standard browser) in the client device other than a CEB.

**[0137]** In operation (2), the gateway service detects that the requested network application is a non-sanctioned network application. The gateway service can for instance extract information from the request (e.g., destination address, name of the requested network application), and compare the information against that from a database of sanctioned and/or non-sanctioned network applications. The gateway service can determine, based on the comparison, that the requested network application is a non-sanctioned network application.

**[0138]** In operation (3), responsive to the determination, the gateway service can block access to the requested network application, e.g., by blocking the request. The gateway service can generate and/or send a URL redirect message to the standard browser, responsive to the determination. The URL redirect message can be similar to a URL redirect message sent from the server to the standard browser in FIG. 5 in operation (3). A secure browser plug-in of the standard browser can receive the URL redirect message, and can for example send a request to access the non-sanctioned network application, to the secure browser 420. The secure browser 420 can direct the request to the server of the non-sanctioned network application.

**[0139]** The server of the non-sanctioned network application may authenticate the user via the access gateway of the cloud services 408, e.g., responsive to receiving the request from the secure browser. The server may communicate with the access gateway to authenticate the user, in response to the request. The server may send a request to the access gateway to authenticate the user. In response to the server's request to authenticate the user, the access gateway can provide credentials of the user to the server 430. Upon authentication, the secure browser (or a corresponding CEB) can establish a secured connection and an application session with the server.

**[0140]** In operation (4), a new browser tab can open on the standard browser, to render or display the secure browser's application session. The new browser tab can be established or opened by the secure browser plug-in for instance. The secure browser plug-in and/or a client agent can receive data from the secure browser session, and can render the network application within the new browser tab as discussed above in connection with FIGS. 5-6 for instance.

**[0141]** In operation (5), the secure browser can feed all user interaction events via the network application, back to analytics service for processing. The secure browser plug-in can monitor for and intercept any user interaction events directed to the rendition of the network application within the browser tab. Hence, a user can use a native (or standard) browser to access a network application while allowing visibility into the network application's traffic, via the inter-operation of cloud services and a secure browser (in the absence of the client application).

**[0142]** In some embodiments, in the absence or non-availability of a CEB on the client device, browser redirection is performed so that each requested network application is accessed via a corresponding hosted secure browser (or hosted CEB) for handling, instead of having all traffic redirected through a single hosted secure browser (or hosted CEB). Each dedicated secure browser can provide compartmentalization and improved security.

**[0143]** The use of a CEB, whether hosted or local to the client device, can allow for end-to-end visibility of application traffic for analytics, service level agreement (SLA), resource utilization, audit, and so on. In addition to such visibility, the CEB can be configured with policies for managing and controlling any of these as well as other aspects. For example, DLP features can be supported, to control "copy and paste" activities, download of files, sharing of files, and to implement watermarking for instance. As another example, the CEB can be configured with policies for managing and controlling access to local drives and/or device resources such as peripherals.

**[0144]** Referring now to FIG. 8, an example embodiment of a system for using local embedded browser(s) and hosted secured browser(s) is depicted. An environment is shown where different types of client devices 402A, 402B may be used (e.g., in a BYOD context), such that one may be locally equipped with a suitable CEB, and another client device may not have a suitable local CEB installed. In such an environment, systems described in FIGS. 4, 5 and 7 can be used to support each of the client devices based on the availability of a locally installed and suitable CEB.

**[0145]** FIG. 9 depicts an example process flow for using local embedded browser(s) and hosted secured browser(s). The process flow can be used in the environment described above in FIG. 8, to determine whether an embedded browser or a hosted secured browser should be used for each client device to access a network application. For example, in operation 901, a HTTP client can attempt to access a web service (e.g., server of a network application). In operation 903, the web service can redirect the HTTP client to a gateway service for authentication. In operation 905, the gateway service can determine if the HTTP client is a CEB. If so, in operation 909, the gateway service can determine if the CEB is a suitable CEB, e.g., capable of enforcing defined application policies. If so, in operation 911, the CEB is allowed access to the web service, and can enforce the defined policies.

**[0146]** If the gateway service determines that the HTTP client is not a CEB, the gateway service can cause a virtualized version of a CEB to be initialized and hosted on a remote server (e.g., a network device 432 of cloud services 408), in operation 907. In some embodiments, such a hosted CEB may already be available on a network device 432, and can be selected for use. For example in operation 911, the CEB is allowed access to the web service, and can enforce the defined policies.

**[0147]** If the gateway service determines that the HTTP client is a CEB, but that the CEB is not a suitable CEB, the gateway service can cause a virtualized version of a CEB to be initialized and hosted on a remote server (e.g., a network device 432 of cloud services 408), in operation 907. In some embodiments, such a hosted CEB may already be available on a network device 432, and can be selected for use. For example in operation 911, the CEB is allowed access to the web service, and can enforce the defined policies.

**[0148]** In some embodiments, if the user is requesting access to a web application located in a company data center, the gateway service (in cloud service or on premise) can allow access when the client application with CEB is detected. Otherwise, the request can be routed to a service with the hosted virtualized version of the CEB, and then access is authenticated and granted.

[0149] At operation 905 and/or operation 909 for instance, the decisions made on whether the HTTP client is a CEB and whether it is a suitable CEB may be determined by a number of factors. For example, to determine if the HTTP client is CEB, the gateway service may take into account factors, for example including at least one of: user Identity and strength of authentication, client Location, client IP Address, how trusted the user identity, client location, client IP are, jail-break status of the client device, status of anti-malware software, compliance to corporate policy of the client device, and/or remote attestation or other evidence of integrity of the client software.

[0150] To determine if the CEB is able to honor or support all defined application policies (which may vary by client version, client OS platform and other factors), the client device's software and gateway service may perform capability negotiation and/or exchange version information. In some embodiments, the gateway service can query or check a version number or identifier of the CEB to determine if the CEB is a suitable CEB to use.

[0151] Driving all the traffic through the CEB then allows additional control of content accessing SaaS and Web based systems. Data Loss Prevention (DLP) of SaaS and Web traffic can be applied through the CEB app with features including copy and paste control to other CEB access applications or IT managed devices. DLP can also be enforced by enabling content to be downloaded only to designated file servers or services under IT control.

[0152] Referring now to FIG. 10, depicted is an example embodiment of a system for managing user access to webpages. Some webpages (or websites) are known to be safe while others may be suspect. A user may access a webpage via a corresponding URL through a standard browser. For example, the user may click on a link corresponding to the URL, which may be included in an email being viewed using a mail application. An access gateway (SWG) may intercept an access request generated by the clicking of the link, and can determine if the corresponding URL is safe or suspect. If the URL is known to be safe, the access gateway can allow the request to proceed to the corresponding website or web server. If the URL is suspect, the access gateway can redirect the request to be handled via a hosted secure browser. The secure browser can request access for, and access the webpage (on behalf of the standard browser), and can allow the webpage information to be conveyed to the standard browser, similar to the handling of a network application via browser redirection as discussed in connection with at least FIGS. 7 and 5.

### C. Systems and Methods for Generating and Providing Live Tiles for Network Applications

[0153] The present disclosure is directed towards systems and methods for generating and providing live tiles for network applications. In some implementations, a user may launch web applications or access network resources via a user interface, such as a menu system or set of selectable icons. This user interface may be inefficient and difficult to use, and provide limited information about the associated web application or network resource. For example, to access a network application or resource, in many implementations, a user must launch the application, log in or otherwise provide authentication credentials,

[0154] Instead, a small icon or thumbnail-like visual, referred to generally as a "live tile" or "tile", may be

provided via a user interface to a user, with the tile displaying key relevant information from the application or network resource, without the user having to launch the complete application or manually access the resource. The contents of the live tile may be periodically and automatically updated, including performing authentication processes necessary to access the application or resource.

[0155] For example, FIG. 11 is an illustration of an example embodiment of live tiles for network applications and resources. Each live tile 1100 may include a portion of the corresponding application or resource, with live updated data. In some implementations, rather than a mere screenshot or similar representation, the live tile may comprise a portion of the application. For example, a network application may be presented as a dynamic web page with embedded data from various online resources. A portion of the network application may be extracted (e.g. extracting a portion of the source code of the page) and a tile generated comprising the extract portion. When the client application renders the live tile user interface, the portion of the application may be rendered normally, with embedded data retrieved and displayed. Thus, rather than a static thumbnail, the live tile will actually comprise a portion of the corresponding network application in a "live" online state.

[0156] The tile may be generated by an administrator, or may be created by a user. For example, in some implementations, a user may generate a tile via a document-object-model (DOM)-aware web-clipping interface. The user may select a portion of a network application and indicate to make a tile, and the client application may parse a DOM tree of the network application to identify the selected portion. The client application may integrate any inherited qualities or parameters (e.g. from parent nodes of the DOM tree) and may generate a self-contained stand-alone tile element that includes all of the required information to render the selected portion of the network application, including retrieving corresponding embedded data. The client application may identify the DOM sub-element corresponding to the live tile content as well as the containing page of the web application, and in some implementations, may also identify navigation required to reach the page (in cases where the page is not directly "deep-linkable" from a post-login landing page of the application).

[0157] The live tile may also be used as an application's launch icon: upon detecting an interaction with the live tile via the embedded browser, the client application may launch the corresponding network application (and perform any additional navigation steps to reach the corresponding page or view).

[0158] Because live tiles may represent a portion of an application, it is possible for many live tiles to be associated with a single application, albeit with different portions of the application.

[0159] In the example illustrated in FIG. 11, the tiles are shown in different sizes. In some implementations, tiles may be manually or dynamically resized. As discussed above, embedded data may be periodically retrieved to update the live tile. In some implementations, the rate at which data is updated may be proportional to the size of the tile. For example, a larger tile may be updated at more frequent intervals than a smaller tile. The user may manually resize the tiles to adjust the refresh rate, in some such implementations.



[0160] Live tiles may be displayed in a user interface that provides a “launchpad” or “dashboard” for multiple web applications, and thus the interface may include tiles from multiple applications on a single page. Live tiles may also be shared with other users and integrated into other users’ dashboards. In some implementations, live tiles may be associated with popularity scores or rankings generated by users of the tiles, and an interface may provide a list or set of live tiles with associated rankings or scores, allowing users to select from the most popular or best rated live tiles.

[0161] FIG. 12 is a block diagram of an example embodiment of a system for providing and utilizing live tiles for network applications. The system may include a client device 1200 in communication via a network 1210 with one or more application servers 1212 and/or one or more data servers 1214. Client device 1200 may execute a client application 1202, similar to client applications discussed above, that includes an embedded browser 1204 (e.g. similar to client application 404 and embedded browser 410) that can render information of a network application accessed via the client application 1200. The client application 1202 may be an instance of the client application 404 previously detailed herein. The client application 1202 with the embedded browser 1204 (CEB) can include any element of a CEB 410 as previously described herein.

[0162] Each of the above-mentioned elements or entities is implemented in hardware, or a combination of hardware and software, in one or more embodiments. Each component of the system may be implemented using hardware or a combination of hardware or software detailed above in connection with FIG. 1. For instance, each of these elements or entities can include any application, program, library, script, task, service, process or any type and form of executable instructions executing on hardware of a client device (e.g., the client applications 1202). The hardware includes circuitry such as one or more processors in one or more embodiments.

[0163] Client application 1202 may comprise a tile generator 1206. Tile generator 1206 may comprise an application, server, service, daemon, routine, or other executable logic for generating a live tile. In many implementations, tile generator 1206 may comprise functionality for parsing and/or extracting portions of a web application, such as by parsing a DOM tree to identify or generate a self-contained block corresponding to a selected portion of an application to be used for generating a live tile 1208. Self-contained blocks may comprise all of the executable code of the web application needed to generate the portion extracted for a live tile. In some implementations, a portion may be extracted and then modified to include other portions (e.g. from parent nodes). For example, a first DOM element may be extracted, and the portions of parent DOM elements extracted or copied into the first DOM element such that it includes all of the properties which it would inherit via the full DOM tree structure. For example, referring briefly to FIG. 13 illustrated is one implementation of generation of live tiles for network applications. As shown, a web application 1300 may be presented to a user or administrator, and the user or administrator may select a portion of the web application from which to generate a live tile (e.g. box in dashed line). The tile generator 1206 may extract a corresponding portion of the source code of the web application 1302 (e.g. box in dashed line), and may generate code for a live tile 1304 including the extracted portion. The tile

generator 1206 may also extract parameters or styles of parent elements of the DOM tree, and may iteratively search through the DOM tree for each parent element of the selected element or elements to identify such parameters or styles. The extracted styles and parameters may be added into the single-layer DOM tree of the live tile 1304. In other implementations, the live tile 1304 may have a more complex DOM tree. The live tile source may be rendered via the embedded browser as a live tile 1306 as shown.

[0164] Returning to FIG. 12, as discussed above, live tiles 1208 may comprise executable code for generating a portion of a web application and for accessing embedded data of the portion of the web application (including performing authentication routines, if necessary, such as providing a previously obtained authentication token to a server). Live tiles 1208 may be encoded in any suitable format, including HTML, Javascript, or other formats.

[0165] FIG. 14 is a flow chart of an implementation of a method for generating and providing live tiles for network applications. At step 1402, a client application comprising an embedded browser may access a network application. In some implementations, the client application and/or embedded browser may perform an authentication process, such as providing user or device credentials to an authentication server or application server, receiving an authentication token, etc. Once authenticated, the network application may be accessed and rendered via the embedded browser.

[0166] At step 1404, a user may select a portion of the network application from which to generate a live tile. In various implementations, the user may click and drag over a portion of the network application, highlight a portion, select a portion via a touch gesture, or otherwise indicate a portion of the network application from which to make a live tile. In some implementations, the entire network application may be the portion—i.e. a tile may be made from the entire network application rather than a subset.

[0167] At step 1406, the client application may generate the live tile from the selected portion. As discussed above, the client application may extract a portion of the network application corresponding to the selected portion, and may parse a DOM tree of the network application to extract parameters or styles from parent elements of the selected portion. The extracted portion and extracted parameters or styles may be aggregated, in many implementations into a single-tier tree, to generate executable code of the live tile. In some implementations in which the selected portion includes multiple tiers of the DOM tree, the tile generator may “flatten” the DOM tree into a single tier, or may generate a live tile including the multiple selected tiers (as well as incorporating styles or parameters from parent elements of the selected elements).

[0168] The tile may be rendered via the embedded browser of the client application. During rendering, at step 1408, the embedded browser may request and receive embedded data of the portion of the web application. Such requests and responses may be similar to those generated during normal execution of the web application: that is, requests for embedded data that would be generated during access of the web application via the embedded browser may be similarly generated by the embedded browser during rendering and display of the live tile, should such embedded data be within the selected portion of the web application.

[0169] As discussed above, live tiles may be periodically refreshed by the embedded browser and/or client applica-

tion. The time for expiration may be predetermined or set during creation of the live tile, or may be dynamically set by a user (e.g. by resizing the tile as discussed above). If time has expired, then the client application or embedded browser may attempt to refresh embedded data, e.g. by transmitting a request to an application server or data server for the corresponding data. The client application or embedded browser may utilize a previously received authentication token, if it has not expired. This may allow refreshing of user- or device-specific data. If access is not valid (e.g. if the token is unavailable or has expired), then at step 1410, the embedded browser or client application may re-authenticate with the server and receive a new authentication token. The authentication process may be performed automatically, in some implementations, using authentication credentials provided during generation of the live tile as discussed above. Once re-authenticated or if the token is valid, then at step 1412, the client application and/or embedded browser may transmit one or more requests for embedded data, and may update the display of the live tile.

**[0170]** Additionally, as discussed above, live tiles may serve as links to allow a user to launch the corresponding web application. If an interaction (e.g. click, selection, or other such interaction) is detected, then at step 1414, the embedded browser may access the web application. Accessing the web application may comprise instantiating a new window and requesting a launch page of the application. In some implementations, the web browser may automatically navigate to a portion of the web application corresponding to the tile. For example, in one implementation in which the tile displays a secondary page of the web application (e.g. a user calendar within a web mail application), the web browser may launch the web application in a new tab or new window, and then navigate to the corresponding secondary page, such that the user is immediately able to access the portion of the web application corresponding to the tile.

**[0171]** Thus, the present systems and methods describe implementations for providing and displaying live tiles for web applications corresponding to portions of the web applications, and displaying automatically-updated user- or device-specific data.

**[0172]** It should be understood that the systems described above may provide multiple ones of any or each of those components and these components may be provided on either a standalone machine or, in some embodiments, on multiple machines in a distributed system. The systems and methods described above may be implemented as a method, apparatus or article of manufacture using programming and/or engineering techniques to produce software, firmware, hardware, or any combination thereof. In addition, the systems and methods described above may be provided as one or more computer-readable programs embodied on or in one or more articles of manufacture. The term “article of manufacture” as used herein is intended to encompass code or logic accessible from and embedded in one or more computer-readable devices, firmware, programmable logic, memory devices (e.g., EEPROMs, ROMs, PROMs, RAMs, SRAMs, etc.), hardware (e.g., integrated circuit chip, Field Programmable Gate Array (FPGA), Application Specific Integrated Circuit (ASIC), etc.), electronic devices, a computer readable non-volatile storage unit (e.g., CD-ROM, USB Flash memory, hard disk drive, etc.). The article of manufacture may be accessible from a file server providing access to the computer-readable programs via a network

transmission line, wireless transmission media, signals propagating through space, radio waves, infrared signals, etc. The article of manufacture may be a flash memory card or a magnetic tape. The article of manufacture includes hardware logic as well as software or programmable code embedded in a computer readable medium that is executed by a processor. In general, the computer-readable programs may be implemented in any programming language, such as LISP, PERL, C, C++, C#, PROLOG, or in any byte code language such as JAVA. The software programs may be stored on or in one or more articles of manufacture as object code.

**[0173]** While various embodiments of the methods and systems have been described, these embodiments are illustrative and in no way limit the scope of the described methods or systems. Those having skill in the relevant art can effect changes to form and details of the described methods and systems without departing from the broadest scope of the described methods and systems. Thus, the scope of the methods and systems described herein should not be limited by any of the illustrative embodiments and should be defined in accordance with the accompanying claims and their equivalents.

We claim:

1. A method comprising:

generating, by a client device, a user interface element comprising executable code identified from a document-object-model element of an application hosted on a remote computing device;

displaying, by the client device, the user interface element with updated data associated with the application and retrieved from the remote computing device; and

causing, by the client device, a second device to display the user interface element with updated data associated with the application and retrieved from the remote computing device

2. The method of claim 1, further comprising receiving, by the client device, the document-object-model element of the application from the remote computing device.

3. The method of claim 2, further comprising receiving the document-object-model element of the application by a browser within a client application.

4. The method of claim 1, further comprising extracting, by the client device, the executable code from the document-object-model element.

5. The method of claim 1, further comprising retrieving, by the client device, the updated data from the remote computing device.

6. The method of claim 1, wherein the user interface element comprises a tile displaying the updated data.

7. The method of claim 1, further comprising updating the display of the updated data on one of the client device or the second device using data retrieved from the remote computing device on a periodic basis.

8. A client device comprising:

one or more processors, coupled to memory and configured to:

generate a user interface element comprising executable code identified from a document-object-model element of an application hosted on a remote computing device;

display, the user interface element with updated data associated with the application and retrieved from the remote computing device; and

cause a second device to display the user interface element with updated data associated with the application and retrieved from the remote computing device.

9. The client device of claim 8, wherein the one or more processors are further configured to receive the document-object-model element of the application from the remote computing device.

10. The client device of claim 9, further comprising a browser within a client application to receive the document-object-model element of the application.

11. The client device of claim 8, wherein the one or more processors are further configured to extract the executable code from the document-object-model element.

12. The client device of claim 8, wherein the one or more processors are further configured to retrieve the updated data from the remote computing device.

13. The client device of claim 8, wherein the user interface element comprises a tile displaying the updated data.

14. The client device of claim 8, wherein the display of the updated data on one of the client device or the second device is updated using data retrieved from the remote computing device on a periodic basis.

15. A non-transitory computer-readable medium storing instructions that, when executed by one or more processors, cause the one or more processors to:

generate a user interface element comprising executable code identified from a document-object-model element of an application hosted on a remote computing device;

display the user interface element with updated data associated with the application and retrieved from the remote computing device; and

cause a second device to display the user interface element with updated data associated with the application and retrieved from the remote computing device.

16. The non-transitory computer-readable medium of claim 15, further comprising instructions to configured to cause the one or more processors to receive, via a browser within a client application, the document-object-model element of the application from the remote computing device.

17. The non-transitory computer-readable medium of claim 15, further comprising instructions to configured to cause the one or more processors to extract the executable code from the document-object-model element.

18. The non-transitory computer-readable medium of claim 15, further comprising instructions to configured to cause the one or more processors to retrieve the updated data from the remote computing device.

19. The non-transitory computer-readable medium of claim 15, wherein the user interface element comprises a tile displaying the updated data.

20. The non-transitory computer-readable medium of claim 15, wherein the display of the updated data on one of the client device or the second device is updated using data retrieved from the remote computing device on a periodic basis.

\* \* \* \* \*