



(12) **DEMANDE DE BREVET CANADIEN  
CANADIAN PATENT APPLICATION**

(13) **A1**

(86) **Date de dépôt PCT/PCT Filing Date:** 2017/07/12  
(87) **Date publication PCT/PCT Publication Date:** 2018/01/18  
(85) **Entrée phase nationale/National Entry:** 2019/01/10  
(86) **N° demande PCT/PCT Application No.:** EP 2017/067585  
(87) **N° publication PCT/PCT Publication No.:** 2018/011286  
(30) **Priorités/Priorities:** 2016/07/13 (US62/361,805);  
2016/09/16 (EP16189213.8)

(51) **Cl.Int./Int.Cl. C12P 7/64** (2006.01),  
**A23D 7/00** (2006.01), **A23K 20/158** (2016.01),  
**A61K 31/20** (2006.01), **C11B 1/00** (2006.01),  
**C11B 3/00** (2006.01)  
(71) **Demandeurs/Applicants:**  
EVONIK DEGUSSA GMBH, DE;  
DSM IP ASSETS B.V., NL  
(72) **Inventeurs/Inventors:**  
BARZ, MANFRED, DE;  
BEISER, MARC, DE;  
BORCHERS, GEORG, DE;  
CHERINKO, STEPHEN ROBERT, US;  
DERNEDDE, MATHIAS, DE; ...

(54) **Titre : PROCÉDE DE SEPARATION DE LIPIDES A PARTIR D'UN LIPIDE LYSE CONTENANT DE LA BIOMASSE**  
(54) **Title: METHOD OF SEPARATING LIPIDS FROM A LYSED LIPIDS CONTAINING BIOMASS**

(57) **Abrégé/Abstract:**

The current invention relates to a method of separating polyunsaturated fatty acids containing lipids from a lipids containing biomass.

(72) **Inventeurs(suite)/Inventors(continued)**: DIEHL, MICHAEL, DE; DONG, XIAO DANIEL, US; HABERLAND, JURGEN, DE; JOHNSON, MICHAEL BENJAMIN, US; KERTIS, ROBERT CODY, US; LEBERT, JOCHEN, DE; LEININGER, NEIL FRANCIS, US; MATTHEWS, KIRT LYVELL, SR., US; PFEIFER, HOLGER, DE; RABE, CHRISTIAN, DE; RESOP, SHANNON ELIZABETH ETHIER, US; SHANK, GINGER MARIE, US; TARWADE, VINOD, US; TINSLEY, DAVID ALLEN, US; VERKOEIJEN, DANIEL, US

(74) **Agent**: ROBIC

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(10) International Publication Number  
**WO 2018/011286 A1**

(43) International Publication Date  
**18 January 2018 (18.01.2018)**

**(51) International Patent Classification:**

*C12P 7/64* (2006.01)      *C11B 1/00* (2006.01)  
*A23D 7/00* (2006.01)      *C11B 3/00* (2006.01)  
*A61K 31/20* (2006.01)      *A23K 20/158* (2016.01)

**(21) International Application Number:**

PCT/EP2017/067585

**(22) International Filing Date:**

12 July 2017 (12.07.2017)

**(25) Filing Language:**

English

**(26) Publication Language:**

English

**(30) Priority Data:**

62/361,805      13 July 2016 (13.07.2016)      US  
16189213.8      16 September 2016 (16.09.2016)      EP

**(71) Applicants:** **EVONIK DEGUSSA GMBH** [DE/DE]; Rellinghauser Straße 1-11, 45128 Essen (DE). **DSM IP ASSETS B.V.** [NL/NL]; Het Overloon 1, 6411 TE Heerlen (NL).

**(72) Inventors:** **BÄRZ, Manfred**; Franz-Schilling-Str. 41, 63579 Freigericht (DE). **BEISER, Marc**; Hellersberg 3, 63667 Nidda (DE). **BORCHERS, Georg**; Kurstraße 2, 61231 Bad Nauheim (DE). **CHERINKO, Stephen Robert**; 1678 Pringles Ferry Road, Georgetown, South Carolina 29440 (US). **DERNEDDE, Mathias**; Diebacher Str. 2a, 63486 Bruchköbel (DE). **DIEHL, Michael**; Ahrtalstraße 13, 60529 Frankfurt (DE). **DONG, Xiao Daniel**; 10710 Hillingdon Road, Woodstock, Maryland 21163 (US). **HABERLAND, Jürgen**; Dahlienstr. 26, 45721 Haltern am See (DE). **JOHNSON, Michael Benjamin**; 2536 E. Baltimore Street, Baltimore, Maryland 21224 (US). **KERTIS, Robert Cody**; 2353 Cale Yarborough Highway, Timmonsville, South Carolina 29161 (US). **LEBERT, Jochen**; Enzlinger Berg 9a, 63864 Glattbach (DE). **LEININGER, Neil Francis**; 208 Sandlewood Pointe, Winchester, Kentucky 40391 (US). **MATTHEWS, Kirt Lyvell**; 631 East Cheval Drive, Fort Mill, South Carolina 29708 (US). **PFEIFER, Holger**; Zitronenfalterweg 6, 63457 Hanau (DE). **RABE, Christian**; Vogelsbergstr. 14, 63762 Großostheim (DE). **RESOP, Shannon Elizabeth Ethier**; 18905 Olney Mill Road, Olney, Maryland 20832 (US). **SHANK, Ginger Marie**; 27 West Hickman Street, Winchester, Kentucky 40391 (US). **TARWADE, Vinod**; 8619 Enoch Pratt Drive, Ellicott City, Maryland 21043 (US). **TINSLEY, David Allen**; 437 Barroway Lane, Versailles, Kentucky 40383 (US). **VERKOEIJEN, Daniel**; 2504 Abbey Way, Florence, South Carolina 29501 (US).

**(74) Agent:** **IOANNIDIS, Johannes**; CI-IPM-PAT, Postcode 84/339, Rodenbacher Chaussee 4, 63457 Hanau (DE).

**(81) Designated States** (*unless otherwise indicated, for every*

*kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

**(84) Designated States** (*unless otherwise indicated, for every*

*kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

**Published:**

— *with international search report (Art. 21(3))*

**(54) Title:** METHOD OF SEPARATING LIPIDS FROM A LYSSED LIPIDS CONTAINING BIOMASS

**(57) Abstract:** The current invention relates to a method of separating polyunsaturated fatty acids containing lipids from a lipids containing biomass.

WO 2018/011286 A1

Method of separating lipids from a lysed lipids containing biomass

The current invention relates to a method of separating polyunsaturated fatty acids containing lipids from a lipids containing biomass.

5 PUFAs (polyunsaturated fatty acids) containing lipids are of high interest in the feed, food and pharmaceutical industry. Due to overfishing there is a high need for alternative sources for PUFAs containing lipids besides fish oil. It turned out that besides certain yeast and algal strains in particular microalgal cells like those of the order Thraustochytriales are a very good source for PUFAs containing lipids.

10 But with respect to microbial organisms and in particular cells of the order Thraustochytriales, which produce the PUFAs containing lipids, the isolation of the oil from the cells turned out as a particular problem. The most effective way of isolating the oil was the use of organic solvents like hexane. But the use of organic solvents leads to hazardous operating conditions, requires the use of expensive explosion-proof equipment and requires the implementation of an expensive solvent recovery process to avoid pollution of the environment.

15 In the attempt to avoid the use of organic solvents, as an effective alternative way for isolating the oil has turned out the salting-out of the oil with high amounts of sodium chloride. But the use of high amounts of sodium chloride leads to a delipidated biomass by-product which due to the high salt content cannot be utilized as a feed ingredient, so that the process is not very sustainable. Further, the high salt concentration leads to fast corrosion of the used steel equipment.

20 Thus, it was the object of the current invention to provide an effective method for isolating a lipid, in particular a PUFAs containing lipid, from lipids containing cells, in particular of the order Thraustochytriales, and simultaneously avoiding not only the need of organic solvents, but further avoid the need of high amounts of salts for realizing the effective isolation of the oil from the cells.

25 It was a further object of the current invention to provide a method for isolating a lipid, in particular a PUFAs containing lipid, from lipids containing cells, in particular of the order Thraustochytriales, and simultaneously providing a delipidated biomass which can be utilized in a commercial way, preferably in the agricultural field.

30 It turned out that an effective separation of the lipid from the cell debris containing aqueous phase can be realized, if the lysed cell mixture is incubated at a low alkaline pH and a temperature of not more than 100°C for a time period of at least 10 hours. By keeping the temperature below 100°C, it was possible to prohibit at least essentially saponification of the fatty acid esters.

Thus, a first subject of the current invention is a method of separating a polyunsaturated fatty acids (PUFAs) containing lipid from the debris of a biomass, comprising the following steps:

- 35 a) Providing a suspension of a biomass comprising cells which contain a PUFAs containing lipid;  
b) Lysing the cells of the biomass;

- c) Heating the suspension as obtained in step (b) to a temperature of of 80°C to 100°C, preferably 85°C to 95°C, more preferably about 90°C, while adjusting the pH to a value of 9.5 to 11.5, preferably 10.0 to 11.0, more preferably 10.3 to 10.7;
- d) Keeping the temperature and pH value in the ranges as depicted in (c) for at least 10 hours, preferably 15 to 40 hours, more preferably 20 to 36 hours.

The steps (c) and (d) lead to the separation of the oil containing light phase and the water, cell debris, salts and residual oil containing heavy phase, as obtained by lysing the cells of the biomass. This separation of the light and heavy phase is also called “de-emulsification” or “demulsification” in the context of this application.

- 10 The order of the measures in step (d) is of no importance. Adjusting of the temperature can be carried out before or after adjusting the pH value.

Preferably, in the steps (b), (c) and (d) of the method the suspension is continuously mixed by using a stirrer and/or an agitator. In the method steps (c) and/or (d) preferably low shear agitation and/or axial-flow agitation is applied, in particular as disclosed in WO 2015/095694. Impellers suitable for agitating prior and during steps (c) and/or (d) include in particular straight blade impellers, Rushton blade impellers, axial flow impellers, radial flow impellers, concave blade disc impellers, high-efficiency impellers, propellers, paddles, turbines and combinations thereof.

Lysing of the cells of the biomass can be carried out by methods as known to those skilled in the art, in particular enzymatically, mechanically, physically, or chemically, or by applying combinations thereof.

Depending on the time of exposure and/or the degree of force applied, a composition comprising only lysed cells or a composition comprising a mixture of cell debris and intact cells may be obtained. The term “lysed lipids containing biomass” insofar relates to a suspension which contains water, cell debris and oil as set free by the cells of the biomass, but beyond that may also comprise further components, in particular salts, intact cells, further contents of the lysed cells as well as components of a fermentation medium, in particular nutrients. In a preferred embodiment of the invention, only small amounts of intact cells, in particular less than 20 %, preferably less than 10 %, more preferably less than 5 % (relating to the total number of intact cells as present before lysing the cells of the biomass) are present in the lysed biomass after the step of lysing the cells.

30 Lysing of the cells may be realized for example by utilizing a French cell press, sonicator, homogenizer, microfluidizer, ball mill, rod mill, pebble mill, bead mill, high pressure grinding roll, vertical shaft impactor, industrial blender, high shear mixer, paddle mixer, and/or polytron homogenizer.

In a preferred embodiment of the invention lysing of the cells is carried out without applying high mechanical stress on the cells. According to the invention, the energy input onto the cells in the lysing step preferably amounts to not more than 50 kWh per tonne of suspension, in particular not more than 40, 30 or 20 kWh per tonne of suspension, especially preferably not more than 15, 10 or 5 kWh per tonne of suspension.

In a preferred embodiment of the invention, lysing of the cells comprises an enzymatic treatment of the cells by applying a cell-wall degrading enzyme.

According to the invention, the cell-wall degrading enzyme is preferably selected from proteases, cellulases (e.g., Cellustar CL (Dyadic), Fibrezyme G2000 (Dyadic), Celluclast (Novozymes), Fungamyl (Novozymes), Viscozyme L (Novozymes)), hemicellulases, chitinases, pectinases (e.g., Pectinex (Novozymes)), sucrases, maltases, lactases, alpha-glucosidases, beta-glucosidases, amylases (e.g., Alphastar Plus (Dyadic); Termamyl (Novozymes)), lysozymes, neuraminidases, galactosidases, alpha-mannosidases, glucuronidases, hyaluronidases, pullulanases, glucocerebrosidases, galactosylceramidases, acetylgalactosaminidases, fucosidases, hexosaminidases, iduronidases, maltases-glucoamylases, xylanases (e.g., Xylanase Plus (Dyadic), Pentopan (Novozymes)), beta-glucanases (e.g., Vinoflow Max (Novozymes), Brewzyme LP (Dyadic)), mannanases, and combinations thereof. The protease may be selected from serine proteases, threonine proteases, cysteine proteases, aspartate proteases, metalloproteases, glutamic acid proteases, alcalases (subtilisins), and combinations thereof. The chitinase may be a chitotriosidase. The pectinase may be selected from pectolyases, pectozymes, polygalacturonases, and combinations thereof.

The adequate pH for utilizing the enzyme depends on the pH optimum of the enzyme. The pH optimum of the enzyme is known to those skilled in the art or otherwise can be determined easily.

In a preferred embodiment of the invention, an enzyme with a pH optimum of between 6.5 and 8.5, preferably of between 7.0 and 8.0, in particular of about 7.5, is used, so that the pH applied in this step is from 6.5 to 8.5, in particular from 7.0 to 8.0, preferably from 7.3 to 7.7. A preferred enzyme which can be used in this pH range is an alcalase.

The enzyme is preferably added as a concentrated enzyme solution, preferably in an amount of 0.01 to 1.5 wt.-%, more preferably in an amount of 0.03 to 1.0 wt.-%, above all in an amount of 0.05 to 0.5 wt.-%, relating to the amount of concentrated enzyme solution as added in relation to the total amount of the suspension after addition of the concentrated enzyme solution.

In a very preferred embodiment of the invention, lysing of the cells is carried out as follows:

- a) Heating the suspension of (a) to a temperature of between 50°C and 70°C, preferably to a temperature of between 55°C and 65°C, and adding a cell wall-degrading enzyme to the fermentation broth, and adjusting an adequate pH value, if necessary, at which the enzyme is properly working;
- b) Keeping the temperature and pH in the ranges as depicted in (b) for at least one hour, preferably for at least two hours, more preferably for two to four hours.

In step (a), the enzyme can be added before or after heating up the suspension and/or before or after adjusting the pH. In the same way heating up of the suspension can be carried out before or after adjusting the pH. – But in a preferred embodiment, the enzyme is added after heating up of the

suspension and after adjusting the pH, if adjusting of the pH is necessary, at all. – In a very preferred embodiment all measures are carried out more or less simultaneously.

Preferably, in the steps (a) and (b) the suspension is continuously mixed by using a stirrer and/or an agitator.

- 5 In a further preferred embodiment of the invention, after lysing the cells of the biomass and before the demulsification step, the suspension is concentrated to a total dry matter content of 30 to 60 wt.-%, more preferably 35 to 55 wt.-%, in particular 40 to 50 wt.-%.

Concentration of the suspension is preferably carried out by evaporation of water at a temperature not higher than 100°C, preferably 70°C to 100°C, more preferably 80°C to 90°C, until a total dry matter  
10 content of 30 to 60 wt.-% more preferably 35 to 55 wt.-%, in particular 40 to 50 wt.-%, is reached.

Concentration of the suspension is preferably carried out in a forced circulation evaporator (for example available from GEA, Germany) to allow fast removal of the water.

In general, adjusting the pH value can be carried out according to the invention by using either bases or acids as known to those skilled in the art. Decreasing of the pH can be carried out in particular by  
15 using organic or inorganic acids like sulfuric acid, nitric acid, phosphoric acid, boric acid, hydrochloric acid, hydrobromic acid, perchloric acid, hypochlorous acid, chlorous acid, fluorosulfuric acid, hexafluorophosphoric acid, acetic acid, citric acid, formic acid, or combinations thereof. As a high content of chloride is desirably avoided, in a preferred embodiment of the invention no or only small amounts of hydrochloric acid are used in the process of the current invention. According to the  
20 invention, sulfuric acid is the preferred substance for decreasing the pH value. – Increasing of the pH can be carried out in particular by using organic or inorganic bases like hydroxides, in particular sodium hydroxide, lithium hydroxide, potassium hydroxide, and/or calcium hydroxide, carbonates, in particular sodium carbonate, potassium carbonate, or magnesium carbonate, and/or bicarbonates, in particular lithium bicarbonate, sodium bicarbonate, and/or potassium bicarbonate. – Due to easiness  
25 of handling, the acids and bases are preferably used in liquid form, in particular as concentrated solutions. Thus, caustic soda is the preferred substance for increasing the pH value.

The method according to the invention preferably comprises as a further step the harvesting of the PUFAs containing lipid from the demulsified composition as obtained in step (d).

The harvesting of the PUFAs containing lipid preferably comprises neutralization of the demulsified  
30 suspension and subsequent separation of the thus obtained oil containing light phase from the water, salts, cell debris and residual oil containing heavy phase.

Neutralization of the demulsified composition is preferably realized by adding an acid, preferably sulfuric acid, to adjust a pH value of 5.5 to 8.5, in particular 6.5 to 8.5, preferably 7.0 to 8.0. Before starting separation of the light phase from the heavy phase the thus obtained neutralized composition  
35 may be stirred at said pH value from several minutes up to several hours.

Separation of the oil containing light phase from the water, salts and cell debris containing heavy phase is preferably realized by mechanical means and preferably at a temperature of 60-90°C, more

preferably 70-80°C, and at a pH value of preferably 6-9, more preferably 7-8.5. "Mechanical means" refers in particular to filtration and centrifugation methods as known to those skilled in the art.

After separation of the oil containing light phase, the PUFAs containing oil thus obtained can further be worked up by applying methods as known to those skilled in the art, in particular refining, bleaching,  
5 deodorizing and/or winterizing.

A particular advantage of the method of the current invention is that it can be carried out without the use of any organic solvent, in particular without the use of any polar or non-polar organic solvent. Thus, in a preferred embodiment of the invention, no or only little amounts of organic solvents, in particular of polar or non-polar organic solvents, are used for isolating the PUFAs containing oil from  
10 the biomass. Typical organic solvents are hexane and ethanol.

In a preferred embodiment of the invention less than 2 wt.-% non-polar organic solvents are used, more preferably less than 1, 0.5 or 0.1 wt.-%. In a particularly preferred embodiment of the invention no non-polar organic solvent is used, at all. In a very preferred embodiment of the invention less than 2 wt.-% organic solvents are used, in general, particularly preferred less than 1, 0.5 or 0.1 wt.-%. In a  
15 particularly very preferred embodiment of the invention no organic solvents are used, at all, for isolating the PUFAs containing oil from the biomass. – This means in particular for this embodiment that the suspension as employed in the method according to the invention as well as all compositions as obtained by said single method steps preferably contain non-polar organic solvents, preferably organic solvents in general, in an amount of less than 2 wt.-%, more preferably less than 1 wt.-%, in  
20 particular less than 0.5 or 0.3 wt.-%, above all in an amount of less than 0.1 or 0.05 wt.-%.

A further advantage of the method of the current invention is that a very effective separation of the oil from the remaining biomass can be realized without the addition of sodium chloride, which is normally used for salting out the oil from the biomass. Preferably the method can be carried out without the addition of chloride salts, at all, above all without the addition of any salts for salting out the oil. But  
25 small amounts of chloride salts, in particular sodium chloride, might be present in the suspension due to the fermentation medium as used for growing of the biomass.

Thus, in a preferred embodiment of the current invention, no or only little amounts of sodium chloride are used for improving the oil isolation. In a preferred embodiment of the invention less than 1 wt.-% of sodium chloride, are used, more preferably less than 0.5 or 0.2 wt.-% of sodium chloride are used for  
30 isolating the oil from the biomass, above all less than 0.1 or 0.05 wt.-%, wherein the wt.-% relate to the total weight of the composition after addition of the sodium chloride. – This means in particular for this embodiment that the suspension as employed in the method according to the invention as well as all compositions as obtained by said single method steps preferably contain sodium chloride in an amount of less than 2 wt.-%, more preferably less than 1 wt.-%, in particular less than 0.5 or 0.3 wt.-%,  
35 %, above all in an amount of less than 0.1 or 0.05 wt.-%.

In a particularly preferred embodiment of the invention no or only little amounts of chloride salts are used for improving the oil isolation, at all. In this embodiment preferably less than 1 wt.-% of chloride salts, more preferably less than 0.5 or 0.2 wt.-% of chloride salts are used for isolating the oil from the

biomass, above all less than 0.1 or 0.05 wt.-%, wherein the wt.-% relate to the total weight of the composition after addition of the chloride salts. – This means in particular for this embodiment that the suspension as employed in the method according to the invention as well as all compositions as obtained by said single method steps preferably contain chloride, in particular chloride salts, in an amount of less than 2 wt.-%, more preferably less than 1 wt.-%, in particular less than 0.5 or 0.3 wt.-%, above all in an amount of less than 0.1 or 0.05 wt.-%.

In a very preferred embodiment of the invention no or only little amounts of salts are used for improving the oil isolation, in general. In this embodiment preferably less than 1 wt.-% of salts, more preferably less than 0.5 or 0.2 wt.-% of salts are used for isolating the oil from the biomass, above all less than 0.1 or 0.05 wt.-%, wherein the wt.-% relate to the total weight of the composition after addition of the salts. - This means in particular for this embodiment that the suspension as employed in the method according to the invention as well as all compositions as obtained by said single method steps preferably contain salts in general in an amount of less than 2 wt.-%, more preferably less than 1 wt.-%, in particular less than 0.5 or 0.3 wt.-%, above all in an amount of less than 0.1 or 0.05 wt.-%.

The methods of the current invention allow a very effective separation of the oil contained in the biomass from the cell-debris and other substances as contained in the fermentation broth. By using the methods of the current invention preferably more than 80 wt.-%, in particular more than 90 wt.-% of the oil contained in the biomass can be separated from the biomass and isolated.

It turned out that the oil as obtained by applying the method of the current invention has some advantageous characteristics over the PUFAs containing oils as disclosed in the state of the art so far. In particular it exhibits very low oxidation values, a low content of free fatty acids and impurities, a very low viscosity and a very high flash point.

Thus, a further subject of the current invention is an oil as obtained or as obtainable by a method according to the current invention.

A further subject of the current invention is therefore also a PUFAs containing oil exhibiting the following characteristics: a) a peroxide value of less than 0.5, preferably less than 0.3, in particular less than 0.15; b) an anisidine value of less than 15, preferably less than 10; c) preferably a content of free fatty acids of less than 1 wt.-%; d) preferably a content of moisture and impurities of less than 1 wt.-%, preferably less than 0.5 wt.-%; e) preferably a viscosity of less than 250 cps, more preferably of less than 200 cps, in particular of less than 160 cps; e) preferably a flash point of at least 350°C, more preferably of at least 400°C, in particular of at least 450°C; f) preferably a content of omega-3 fatty acids, in particular of DHA and EPA, of at least 35 wt.-%, preferably at least 40 or 45 wt.-%, above all at least 50 wt.-%; g) preferably DHA and EPA each in an amount of at least 8 wt.-%, preferably at least 10 wt.-%, above all at least 15 wt.-%; h) preferably an amount of organic solvents of less than 0.5 wt.-%, more preferably less than 0.1 wt.-%, in particular less than 0.05 wt.-%, above all less than 0.01 wt.-%; i) preferably an amount of chlorides of less than 0.1 wt.-%, more preferably less than 0.05 wt.-%, in particular less than 0.01 wt.-%; j) preferably a content of crude fat of more than 90 wt.-%.

The anisidine value (AV) is determined in accordance with AOCS Official Method Cd 18-90. The AV is a measure for secondary reaction products of the fatty acids, such as aldehydes and ketones, that occur during oxidation of the oil.

5 The peroxide value (PV) is determined in accordance with the AOCS Official Method CD 8-53. The PV is a measure for primary reaction products, such as peroxide and hydroperoxides, that occur during oxidation of the oil. – According to the invention the PV is measured in meq/kg.

10 The content of free fatty acids is determined in accordance with AOCS Official Method AOCS Ca 5a-40. The content of moisture is determined in accordance with AOCS Official Methods AOAC 930.15, 935.29. The content of insoluble impurities is determined in accordance with AOCS Official Method AOCS 3a-46. The amount of DHA and EPA is determined in accordance with AOCS Official Method AOCS Ce 1b-89. The amount of total fat is determined in accordance with AOCS Official Method AOCS 996.06. The amount of crude fat is determined in accordance with AOCS Official Methods AOAC 920.39, 954.02.

15 As the isolation of the oil is carried out by using no or only small amounts of solvents and by also using no or only small amounts of sodium chloride, the aqueous phase obtained as a by-product is preferably substantially free of organic solvents and sodium chloride, as well. Thus, the aqueous phase can be utilized in different ways, either directly after separation of the oil phase or after further work-up like concentrating and/or drying.

20 A further subject of the current invention is therefore a PUFAs containing aqueous suspension, containing a biomass, preferably a delipidated biomass, as obtained or as obtainable by a method according to the current invention. A further subject of the current invention is therefore also a concentrate or a dried product as obtained or obtainable by concentrating and/or drying this aqueous suspension. When concentrating the aqueous suspension, it is preferably dried until a total dry matter (TDM) content of 20 to 60 wt.-% is reached. – In the following the expression “aqueous suspension  
25 according to the invention” refers to the aqueous phase as obtained after separation of the oil phase as well as to any concentrated suspensions of this aqueous phase as obtained by concentrating of this aqueous phase. Drying is preferably carried out by solvent evaporation, as described further below.

30 A further subject of the current invention is therefore also a PUFAs containing aqueous suspension, containing a biomass, in particular cell debris of a delipidated biomass, characterized by a content of non-polar organic solvents of less than 1 wt.-%, preferably less than 0.5 or 0.2 wt.-%, more preferably less than 0.1 or 0.05 wt.-%, above all less than 0.01 wt.-%, and further characterized by a content of chloride ions of less than 1 wt.-%, preferably less than 0.5 or 0.2 wt.-%, more preferably less than 0.1 or 0.05 wt.-%.

35 A further subject of the current invention is therefore in particular also a PUFAs containing aqueous suspension, containing a biomass, in particular, cell debris of a delipidated biomass, characterized by a content of organic solvents of less than 1 wt.-%, preferably less than 0.5 or 0.2 wt.-%, more preferably less than 0.1 or 0.05 wt.-%, above all less than 0.01 wt.-%, and further characterized by a

content of chloride ions of less than 1 wt.-%, preferably less than 0.5 or 0.2 wt.-%, more preferably less than 0.1 or 0.05 wt.-%.

A preferred subject of the current invention is therefore also a PUFAs containing aqueous suspension, containing a Thraustochytrid biomass, in particular cell debris of a delipidated Thraustochytrid  
5 biomass, characterized by a content of non-polar organic solvents of less than 1 wt.-%, preferably less than 0.5 or 0.2 wt.-%, more preferably less than 0.1 or 0.05 wt.-%, above all less than 0.01 wt.-%, and further characterized by a content of chloride ions of less than 1 wt.-%, preferably less than 0.5 or 0.2 wt.-%, more preferably less than 0.1 or 0.05 wt.-%.

A particularly preferred subject of the current invention is therefore also a PUFAs containing aqueous  
10 suspension, containing a Thraustochytrid biomass, in particular, cell debris of a delipidated Thraustochytrid biomass, characterized by a content of organic solvents of less than 1 wt.-%, preferably less than 0.5 or 0.2 wt.-%, more preferably less than 0.1 or 0.05 wt.-%, above all less than 0.01 wt.-%, and further characterized by a content of chloride ions of less than 1 wt.-%, preferably less than 0.5 or 0.2 wt.-%, more preferably less than 0.1 or 0.05 wt.-%.

15 The aqueous suspensions of the invention as described before preferably exhibit a total dry matter (TDM) content of 20 to 60 wt.-%, in particular of 25 to 55 wt.-%, more preferably of 30 to 50 wt.-%, as such concentrated suspensions turned out as particularly suitable for the applications of the invention as described below.

“Chloride” according to the invention refers to the amount of detectable chlorine. The amount of  
20 chlorine as present can be determined for example by elemental analysis according to DIN EN ISO 11885. The chlorine is present in the form of salts which are called “chlorides”. The content of chloride as mentioned according to the invention – also called “chloride ions” - only refers to the amount of detectable chlorine, not to the amount of the complete chloride salt, which comprises besides the chloride ion also a cationic counterion.

25 In a particularly preferred embodiment of the current invention the water, salts, residual oil and cell debris containing aqueous phase, which is obtained as by-product in the oil harvesting step as described before, is converted into a dried biomass by drying the biomass to a total dry matter content of more than 90 wt.-%.

Thus, a further subject of the current invention is also a PUFAs containing biomass, in particular a  
30 delipidated PUFAs containing biomass, characterized by a content of non-polar organic solvents of less than 2 wt.-%, preferably less than 1, 0.5 or 0.2 wt.-%, more preferably less than 0.1, 0.05 or 0.02 wt.-% and further characterized by a content of chloride ions of less than 2 wt.-%, preferably less than 1, 0.5 or 0.2 wt.-%, more preferably less than 0.1 or 0.05 wt.-%.

Thus, a further subject of the current invention is also a PUFAs containing biomass, in particular a  
35 delipidated PUFAs containing biomass, characterized by a content of organic solvents of less than 2 wt.-%, preferably less than 1, 0.5 or 0.2 wt.-%, more preferably less than 0.1, 0.05 or 0.02 wt.-% and further characterized by a content of chloride ions of less than 2 wt.-%, preferably less than 1, 0.5 or 0.2 wt.-%, more preferably less than 0.1 or 0.05 wt.-%.

Thus, a preferred subject of the current invention is also a PUFAs containing Thraustocyhtrid biomass, in particular a delipidated Thraustochytrid biomass, characterized by a content of non-polar organic solvents of less than 2 wt.-%, preferably less than 1, 0.5 or 0.2 wt.-%, more preferably less than 0.1, 0.05 or 0.02 wt.-% and further characterized by a content of chloride ions of less than 2 wt.-%, preferably less than 1, 0.5 or 0.2 wt.-%, more preferably less than 0.1 or 0.05 wt.-%.

Thus, a particularly preferred subject of the current invention is also a PUFAs containing Thraustochytrid biomass, in particular a delipidated Thraustochytrid biomass, characterized by a content of organic solvents of less than 2 wt.-%, preferably less than 1, 0.5 or 0.2 wt.-%, more preferably less than 0.1, 0.05 or 0.02 wt.-% and further characterized by a content of chloride ions of less than 2 wt.-%, preferably less than 1, 0.5 or 0.2 wt.-%, more preferably less than 0.1 or 0.05 wt.-%.

As preferably the preparation is carried out without the use of non-polar organic solvents, preferably without the use of any organic solvents, at all, and without the use of sodium chloride, preferably without the use of chloride salts, at all, the resulting biomass is preferably free of any non-polar organic solvents, preferably free of any organic solvents, in general, and further essentially free of any chloride ions, at all, wherein "essentially free" means that it contains chloride ions in an amount of less than 0.1 wt.-%, in particular in an amount of less than 0.05 wt.-%.

The biomass according to the invention exhibits preferably a moisture content of not more than 10 wt.-%, preferably not more than 5 wt.-%.

The biomass thus obtained preferably comprises lipids (crude fat) in an amount of about 3 to 14 wt.-%, in particular about 4 to about 14 wt.-%, preferably in an amount of about 4.5 to about 12 wt.-%, more preferably in an amount of about 5 to about 10 wt.-%. Further, the lipid preferably comprises at least one PUFA selected from DHA and EPA, more preferably a mixture of DHA and EPA, wherein the ratio of DHA to EPA is preferably between 3:2 to 4:1 and wherein the amount of DHA is preferably from 30 to 50 wt.-% of the total amount of lipids contained and the amount of EPA is preferably from 10 to 20 wt.-% of the total amount of lipids contained. Accordingly, also the aqueous suspensions as described before are preferably characterized by being convertible by drying into a biomass with such a crude fat content and/or EPA content and/or DHA content by drying the aqueous suspension to a moisture content of not more than 10 wt.-%, preferably not more than 5 wt.-%.

The biomass preferably further comprises amino acids in an amount of 15 to 25 wt.-%, more preferably in an amount of 17 to 23 wt.-%, and exhibits preferably a crude protein content of 25 to 35 wt.-%. Accordingly, also the aqueous suspensions as described before are preferably characterized by being convertible by drying into a biomass with such an amino acid and/or crude protein content by drying the aqueous suspension to a moisture content of not more than 10 wt.-%, preferably not more than 5 wt.-%.

The biomass preferably further exhibits a crude fiber content of less than 5 wt.-%, preferably less than 2 wt.-%, more preferably of about 0 wt.-%. Accordingly, also the aqueous suspensions as described before are preferably characterized by being convertible by drying into a biomass with such a crude

fiber content by drying the aqueous suspension to a moisture content of not more than 10 wt.-%, preferably not more than 5 wt.-%.

The dried biomass is preferably a delipidated biomass, that means a biomass, of which the major part of the lipids have been removed, preferably by a process as disclosed in this application. As the  
5 separation of oil from the biomass is very effectively, the remaining oil in the biomass is preferably less than 20 wt.-%, preferably less than 15 wt.-%, more preferably less than 10 wt.-%, of the oil as originally contained in the biomass. But as the oil cannot be removed completely by such a process, a substantial amount of oil is still contained also in the delipidated biomass according to the invention. That means that the term "delipidated biomass" according to the invention refers to a lysed biomass,  
10 from which the major part of oil has been removed, preferably by a process or method as disclosed in this application, but which still contains a substantial part of lipids, in particular of PUFAs containing lipids, wherein the amount of lipids in the dried delipidated biomass is preferably from 3-14 wt.-%, in particular 4-14 wt.-%, preferably from 4.5-12 wt.-%, more preferably from 5-10 wt.-%. Thus, the "delipidated biomass" according to the invention might also be called a "partially delipidated biomass"  
15 or a "substantially delipidated biomass".

Thus, a further subject of the current invention is a method of obtaining a biomass which is substantially free of non-polar organic solvents, preferably free of organic solvents, in general, and which is further substantially free of sodium chloride, preferably free of chloride salts, in general, comprising the method steps as mentioned before.

20 Conversion of the water, salts, remaining oil and cell debris containing heavy phase, which is obtained as by-product in the oil harvesting step, into a dried biomass by drying the biomass to a total dry matter content of more than 90 wt.-%, can be carried out in different ways.

In a very preferred way, the transformation is carried out by concentration of the heavy phase to a dry matter content of 30-50 wt.-%, preferably 35-45 wt.-%, and subsequent spray granulation of the  
25 biomass by means of fluidized bed granulation. By doing that, in a very efficient way, a biomass with advantageous features can be obtained. Spray granulation by means of fluidized bed granulation is disclosed in more detail in EP13176661.0.

The biomass as obtained in that way has some further advantageous characteristics as follows: it has a good flowability (preferably at least grade 4), a low dust value (preferably free of dust), a high bulk  
30 density of preferably more than 500 kg/m<sup>3</sup>, and/or a high energy value of at least 3500 kcal/kg, preferably of about 3800 to 4200 kcal/kg.

Concentration of the heavy phase to a dry matter content of 30-50 wt.-% is preferably carried out by solvent evaporation, in particular vacuum evaporation, and/or by using a rotary evaporator, a thin-film evaporator or a falling-film evaporator. A useful alternative to solvent evaporation is reverse osmosis.

35 For determining the flowability of the granular biomass conical glass efflux vessels with different size outflow openings are used (Klein: Seifen, Öle, Fette, Wachse 94, 12 (1968)). The glass vessels exhibit a height of 70 mm, a maximal inner diameter of 36 mm, a maximal outer diameter of 40 mm and circular apertures at the conical end of the glass vessels with diameters as follows: 2.5; 5; 8; 12; 18

mm. The glass vessels are completely filled with the granular biomass and subsequently fixed in a rack with the aperture directed downwards. Preferably, the aperture of the glass vessels is opened by removing a covering located on the aperture after having fixed the glass vessels on the rack.

5 The flowability is determined as follows: If the granular material can flow out of the vessel with the smallest diameter (2.5 mm) without stagnation, then the flowability is determined as 1; if it can flow out of the vessel with diameter of 5 mm without stagnation, then the flowability is determined as 2; and so on. A flowability of 6 means that the granular material can not flow out of the vessel with the broadest diameter (18 mm), at all, or it can flow out of this vessel only with stagnation. – Thus, a flowability of 4 means that the granular material can flow out of the vessel with a diameter of 12 mm without  
10 stagnation.

“Dust-free” according to the invention is understood to mean a powder which contains only low fractions (< 10% by weight, preferably < 5% by weight, in particular < 3% by weight, especially < 1% by weight) of particle sizes below 100 micrometres.

15 In a preferred embodiment of the invention, a fraction of at least 80% by weight, in particular at least 90% by weight, particularly preferably at least 95% by weight, especially at least 98% by weight of the particles of the biomass possess a particle size of from 100 to 2500 micrometres, preferably 300 to 2500 micrometres, in particular 500 to 2200 micrometres, more preferably 1000 to 2000 micrometers.

20 The mean particle diameter  $d_{50}$  of the particles of the biomass is preferably in the range of 500 to 2200 micrometers, more preferably in the range of 1000 to 2000 micrometers, in particular in the range of 1300 to 1900 micrometers.

Grain or particle size is preferably determined according to the invention by laser diffraction spectrometric methods. Possible methods are described in the text book "Teilchengrößenmessung in der Laborpraxis" [Particle size measurement in the laboratory] by R. H. Müller and R. Schuhmann, Wissenschaftliche Verlagsgesellschaft Stuttgart (1996) and in the text book "Introduction to Particle  
25 Technology" by M. Rhodes, Wiley & Sons (1998). Inasmuch as various methods can be used, the first-cited usable method from the text book of R.H. Müller and R. Schuhmann for the measuring of particle size is preferably used.

The bulk density of the biomass according to the invention is preferably 400 to 800 kg/m<sup>3</sup>, particularly preferably 450 to 750 kg/m<sup>3</sup>, in particular 500 to 750 kg/m<sup>3</sup>.

30 As alternative to the spray-granulation other drying methods, in particular other convective drying methods, like tunnel drying or spray drying, in particular nozzle spray drying, or contact drying methods, like drum drying, or radiation drying methods, like infrared drying, of the concentrated heavy phase would be applicable alternatives, wherein by using those methods normally particles with a smaller or bigger diameter are obtained.

35 According to the invention, during the drying process, an anti-caking agent, in particular silica, preferably a hydrophobic or hydrophilic silica, may optionally be added to the biomass to prevent caking. For this purpose, the fermentation broth comprising biomass as well as the silica are

preferably sprayed into the particular drying zone. Alternatively or additionally, the biomass may be mixed with the anti-caking agent after the drying process. With respect to the use of silica as anti-caking agent reference is made in particular to the patent application EP13187631.0.

5 In a particular embodiment, the biomass according to the invention has a concentration of an anti-caking agent, in particular silica, preferably hydrophilic or hydrophobic silica, of 0.2 to 10% by weight, in particular 0.5 to 7% by weight, especially 0.5 to 5% by weight.

10 Conversion of a fine-grained powder into a coarse-grained dust-free product can be realized by granulating processes. Conventional organic or inorganic auxiliaries or supports such as starch, gelatin, cellulose derivatives or similar substances, which are typically used in food processing or feed processing as binding agents, gelling agents or thickeners, may optionally be used in this subsequent granulation process. Further auxiliaries that are preferably used according to the invention are disclosed in WO 2016/050560, with carboxymethylcellulose being a particular preferred binding agent.

15 Thus, in a particular embodiment of the current invention, the biomass contains an agglomeration auxiliary, in particular a modified polysaccharide, preferably carboxymethylcellulose, in an amount of from 0.05 to 10 wt.-%, preferably in an amount of 0.1 to 5 wt.-%.

A product having the desired particle size and/or particle size distribution can optionally be obtained from the granulate as obtained by drying and/or granulation by subsequent sieving or dust separation.

20 After drying and optionally granulating and/or sieving of the biomass, the dried biomass is preferably stored or packed.

25 The particulate biomass of the invention as well as the aqueous suspensions of the invention can be used in different ways. For example, they can be used in order to produce a foodstuff or feedstuff, as the biomass and aqueous suspensions according to the invention surprisingly turned out to be well accepted as feed ingredient by animals, in particular by beef cattle. Alternatively they may be used directly as foodstuff or feedstuff.

30 A feedstuff or foodstuff comprising a particulate biomass or an aqueous suspension according to the invention is therefore a further subject matter of the present invention. The feedstuff may for example be used for feeding poultry, swine, minks, ruminants, in particular beef cattle or calves, sheep, goats, companion animals or animals held in aquaculture. In a very preferred embodiment of the invention, the feedstuff is used for feeding beef cattle. The feedstuff or foodstuff preferably comprises the biomass in an amount of 2 to 60 wt.-%, preferably in an amount of 5 to 50 wt.-%, more preferably in an amount of 10 to 30 wt.-%.

A further subject matter of the present invention is therefore likewise the use of a particulate biomass and/or of an aqueous suspension according to the invention for producing a foodstuff or feedstuff.

35 A further subject matter of the present invention is therefore likewise a method for producing a feedstuff or foodstuff, in which a particulate biomass and/or an aqueous suspension according to the invention is used, and is preferably mixed with further feedstuff or foodstuff ingredients.

In a preferred embodiment of the invention, the particulate biomass and/or the aqueous suspension is used for producing a foodstuff or feedstuff, in which the biomass and/or the aqueous suspension is preferably mixed with other foodstuff or feedstuff ingredients and is then processed to give the foodstuff or feedstuff.

- 5 The mixture of biomass and/or aqueous suspension and other foodstuff or feedstuff ingredients is processed in a preferred embodiment by an extrusion process, in order to obtain portions of foodstuff or feedstuff ready for sale. Alternatively, a pelleting method may also be used.

A screw or twin-screw extruder is preferably employed in the extrusion process. The extrusion process is preferably carried out at a temperature of 80 – 220°C, particularly 100 – 190°C, a pressure of 10 –  
10 40 Bar, and a shaft rotational speed of 100 – 1000 rpm, particularly 300 – 700 rpm. The residence time of the mixture introduced is preferably 5 – 30 seconds, in particular 10 – 20 seconds.

In a mode of the extrusion process which is preferred in accordance with the invention, the process comprises a compacting step and a compression step.

15 It is preferred to intimately mix the components with each other before carrying out the extrusion process. This is preferably carried out in a drum equipped with vanes. In this mixing step, a preferred embodiment includes an injection of steam, in particular so as to bring about the swelling of the starch which is preferably present.

20 Before being mixed with the biomass and/or aqueous suspension, the further foodstuff or feedstuff ingredients are preferably comminuted – if required – so as to ensure that a homogeneous mixture is obtained in the mixing step. The comminuting of the further foodstuff or feedstuff ingredients may be carried out, for example, using a hammer mill.

A further subject of the current invention is therefore a method of feeding animals, wherein a particulate biomass and/or an aqueous suspension according to the invention are provided to animals, preferably after mixing the particulate biomass and/or the aqueous suspension with further feedstuff  
25 ingredients, wherein the animals are preferably selected from poultry, swine, minks, ruminants, in particular from calves and beef cattle, sheep, goats, companion animals or animals hold in aquaculture.

Alternatively the biomass and/or aqueous suspension according to the invention may be used in land applications, in particular as (organic) fertilizer, NPC (nitrogen/phosphorous/potassium source), soil  
30 enhancer, plant enhancer and/or composting aid, for producing biogas, for wastewater treatment or as alternative fuel, in particular for cement kilns. It might be further used as part of a fermentation medium for producing microorganisms, in particular for producing further PUFAs containing biomass.

A further subject of the current invention is therefore a method for enhancing soil, wherein a particulate biomass and/or an aqueous suspension according to the invention are strewed on and  
35 possibly mixed with ground, in particular with farmland soil or garden soil.

A further subject of the current invention is therefore also a method for fertilizing and/or composting ground, in particular farmland or garden, wherein a particulate biomass and/or an aqueous suspension

according to the invention are strewed on and possibly mixed with ground, in particular with farmland soil or garden soil.

A further subject of the current invention is therefore also a method for producing biogas, wherein a particulate biomass and/or an aqueous suspension according to the invention is subjected to microbial  
5 degradation under anaerobic conditions, in particular by making use of methanogenic bacteria.

A further subject of the current invention is therefore also a method for treatment of wastewater, wherein wastewater is mixed with a particulate biomass and/or an aqueous suspension according to the invention.

A further subject of the current invention is therefore also a method for producing microorganisms, in  
10 particular for producing a PUFAs containing biomass, wherein a particulate biomass and/or aqueous suspension according to the invention is used as part of the fermentation medium.

The method according to the invention may further comprise as a pretreatment step the pasteurization of the suspension of the biomass, before carrying out the lysis of the cells. The pasteurization is preferably carried out for 5 to 80 minutes, in particular 20 to 60 minutes, at a temperature of 50 to  
15 121°C, in particular 50 to 70 °C.

The PUFAs containing cells of the biomass are preferably microbial cells or plant cells. Preferably, the cells are capable of producing the PUFAs due to a polyketide synthase system. The polyketide synthase system may be an endogenous one or, due to genetic engineering, an exogenous one.

Accordingly, "delipidated biomass" according to the invention in particular refers to the residues of  
20 such a PUFAs containing cells comprising biomass, in particular as disclosed further below, after having been subjected to an oil isolation process, in particular as disclosed further before.

The plant cells may in particular be selected from cells of the families Brassicaceae, Elaeagnaceae and Fabaceae. The cells of the family Brassicaceae may be selected from the genus Brassica, in particular from oilseed rape, turnip rape and Indian mustard; the cells of the family Elaeagnaceae may  
25 be selected from the genus Elaeagnus, in particular from the species *Olea europaea*; the cells of the family Fabaceae may be selected from the genus Glycine, in particular from the species *Glycine max*.

The microbial organisms which contain a PUFAs containing lipid are described extensively in the prior art. The cells used may, in this context, in particular be cells which already naturally produce PUFAs (polyunsaturated fatty acids); however, they may also be cells which, as the result of suitable genetic  
30 engineering methods or due to random mutagenesis, show an improved production of PUFAs or have been made capable of producing PUFAs, at all. The production of the PUFAs may be auxotrophic, mixotrophic or heterotrophic.

The biomass preferably comprises cells which produce PUFAs heterotrophically. The cells according to the invention are preferably selected from algae, fungi, particularly yeasts, bacteria, or protists. The  
35 cells are more preferably microbial algae or fungi.

Suitable cells of oil-producing yeasts are, in particular, strains of *Yarrowia*, *Candida*, *Rhodotorula*, *Rhodospiridium*, *Cryptococcus*, *Trichosporon* and *Lipomyces*.

Suitable cells of oil-producing microalgae and algae-like microorganisms are, in particular, microorganisms selected from the phylum Stramenopiles (also called Heterokonta). The  
5 microorganisms of the phylum Stramenopiles may in particular be selected from the following groups of microorganisms: Hamatores, Proteromonads, Opalines, Developayella, Diplophrys, Labrinthulids, Thraustochytrids, Biosecids, Oomycetes, Hypochytridiomycetes, Commation, Reticulosphaera, Pelagomonas, Pelagococcus, Ollicola, Aureococcus, Parmales, Diatoms, Xanthophytes, Phaeophytes (brown algae), Eustigmatophytes, Raphidophytes, Synurids, Axodines (including Rhizochromulinales,  
10 Pedinellales, Dictyochales), Chrysomeridales, Sarcinochrysidales, Hydrurales, Hibberdiales, and Chromulinales. Other preferred groups of microalgae include the members of the green algae and dinoflagellates, including members of the genus *Crypthecodiurn*.

The biomass according to the invention preferably comprises cells, and preferably consists essentially of such cells, of the taxon Labyrinthulomycetes (Labyrinthulea, net slime fungi, slime nets), in  
15 particular those from the family of Thraustochytriaceae. The family of the Thraustochytriaceae (Thraustochytrids) includes the genera *Althomia*, *Aplanochytrium*, *Aurantiochytrium*, *Botryochytrium*, *Elnia*, *Japonochytrium*, *Oblongichytrium*, *Parietichytrium*, *Schizochytrium*, *Sicyoidochytrium*, *Thraustochytrium*, and *Ulkenia*. The biomass particularly preferably comprises cells from the genera *Aurantiochytrium*, *Oblongichytrium*, *Schizochytrium*, or *Thraustochytrium*, above all from the genus  
20 *Schizochytrium*.

In accordance with the invention, the polyunsaturated fatty acid (PUFA) is preferably a highly-unsaturated fatty acid (HUFA).

The cells present in the biomass are preferably distinguished by the fact that they contain at least 20% by weight, preferably at least 30% by weight, in particular at least 35% by weight, of PUFAs, in each  
25 case based on cell dry matter.

According to the current invention, the term "lipid" includes phospholipids; free fatty acids; esters of fatty acids; triacylglycerols; sterols and sterol esters; carotenoids; xanthophylls (e. g., oxycarotenoids); hydrocarbons; isoprenoid-derived compounds and other lipids known to one of ordinary skill in the art. – The terms "lipid" and "oil" are used interchangeably according to the invention.

30 In a preferred embodiment, the majority of the lipids in this case is present in the form of triglycerides, with preferably at least 50% by weight, in particular at least 75% by weight and, in an especially preferred embodiment, at least 90% by weight of the lipids present in the cell being present in the form of triglycerides.

According to the invention, polyunsaturated fatty acids (PUFAs) are understood to mean fatty acids  
35 having at least two, particularly at least three, C-C double bonds. According to the invention, highly-unsaturated fatty acids (HUFAs) are preferred among the PUFAs. According to the invention, HUFAs are understood to mean fatty acids having at least four C-C double bonds.

The PUFAs may be present in the cell in free form or in bound form. Examples of the presence in bound form are phospholipids and esters of the PUFAs, in particular monoacyl-, diacyl- and triacylglycerides. In a preferred embodiment, the majority of the PUFAs is present in the form of triglycerides, with preferably at least 50% by weight, in particular at least 75% by weight and, in an especially preferred embodiment, at least 90% by weight of the PUFAs present in the cell being present in the form of triglycerides.

Preferred PUFAs are omega-3 fatty acids and omega-6 fatty acids, with omega-3 fatty acids being especially preferred. Preferred omega-3 fatty acids here are the eicosapentaenoic acid (EPA, 20:5 $\omega$ -3), particularly the (5Z,8Z,11Z,14Z,17Z)-eicosa-5,8,11,14,17-pentaenoic acid, and the docosahexaenoic acid (DHA, 22:6 $\omega$ -3), particularly the (4Z,7Z,10Z,13Z,16Z,19Z)-docosa-4,7,10,13,16,19-hexaenoic acid.

In a very preferred embodiment of the current invention, cells, in particular a *Schizochytrium* strain, is employed which produces a significant amount of EPA and DHA, simultaneously, wherein DHA is preferably produced in an amount of at least 20 wt.-%, preferably in an amount of at least 30 wt.-%, in particular in an amount of 30 to 50 wt.-%, and EPA is produced in an amount of at least 5 wt.-%, preferably in an amount of at least 10 wt.-%, in particular in an amount of 10 to 20 wt.-% (in relation to the total amount of lipid as contained in the cells, respectively). DHA and EPA producing *Schizochytrium* strains can be obtained by consecutive mutagenesis followed by suitable selection of mutant strains which demonstrate superior EPA and DHA production and a specific EPA:DHA ratio. Any chemical or nonchemical (e.g. ultraviolet (UV) radiation) agent capable of inducing genetic change to the yeast cell can be used as the mutagen. These agents can be used alone or in combination with one another, and the chemical agents can be used neat or with a solvent.

Preferred species of microorganisms of the genus *Schizochytrium*, which produce EPA and DHA simultaneously in significant amounts, as mentioned before, are deposited under ATCC Accession No. PTA-10208, PTA-10209, PTA-10210, or PTA-10211, PTA-10212, PTA-10213, PTA-10214, PTA-10215.

The suspension of biomass according to the present invention, from which the PUFAs containing lipid is obtainable, is preferably a fermentation broth, in particular a fermentation broth with a biomass density of at least 80 or 100 g/l, preferably at least 120 or 140 g/l, more preferably at least 160 or 180 g/l (calculated as dry-matter content). Thus, the suspension may be obtained by culturing and growing suitable cells in a fermentation medium under conditions whereby the PUFAs are produced by the microorganism.

Methods for producing the biomass, in particular a biomass which comprises cells containing lipids, in particular PUFAs, particularly of the order Thraustochytriales, are described in detail in the prior art (see e.g. WO91/07498, WO94/08467, WO97/37032, WO97/36996, WO01/54510). As a rule, the production takes place by cells being cultured in a fermenter in the presence of a carbon source and of a nitrogen source, along with a number of additional substances like minerals that allow growth of the microorganisms and production of the PUFAs. In this context, biomass densities of more than 100 grams per litre and production rates of more than 0.5 gram of lipid per litre per hour may be attained.

The process is preferably carried out in what is known as a fed-batch process, i.e. the carbon and nitrogen sources are fed in incrementally during the fermentation. When the desired biomass has been obtained, lipid production may be induced by various measures, for example by limiting the nitrogen source, the carbon source or the oxygen content or combinations of these.

5 In a preferred embodiment of the current invention, the cells are grown until they reach a biomass density of at least 80 or 100 g/l, more preferably at least 120 or 140 g/l, in particular at least 160 or 180 g/l (calculated as dry-matter content). Such processes are for example disclosed in US 7,732,170.

Preferably, the cells are fermented in a medium with low salinity, in particular so as to avoid corrosion. This can be achieved by using chlorine-free sodium salts as the sodium source instead of sodium  
10 chloride, such as, for example, sodium sulphate, sodium carbonate, sodium hydrogen carbonate or soda ash. Preferably, chloride is used in the fermentation in amounts of less than 3 g/l, in particular less than 500 mg/l, especially preferably less than 100 mg/l.

Suitable carbon sources are both alcoholic and non-alcoholic carbon sources. Examples of alcoholic carbon sources are methanol, ethanol and isopropanol. Examples of non-alcoholic carbon sources are  
15 fructose, glucose, sucrose, molasses, starch and corn syrup.

Suitable nitrogen sources are both inorganic and organic nitrogen sources. Examples of inorganic nitrogen sources are nitrates and ammonium salts, in particular ammonium sulphate and ammonium hydroxide. Examples of organic nitrogen sources are amino acids, in particular glutamate, and urea.

In addition, inorganic or organic phosphorus compounds and/or known growth-stimulating substances  
20 such as, for example, yeast extract or corn steep liquor, may also be added so as to have a positive effect on the fermentation.

The cells are preferably fermented at a pH of 3 to 11, in particular 4 to 10, and preferably at a temperature of at least 20°C, in particular 20 to 40°C, especially preferably at least 30°C. A typical fermentation process takes up to approximately 100 hours.

25 After the fermentation has ended, the cells may be pasteurized in order to kill the cells and to deactivate enzymes which might promote lipid degradation. The pasteurization is preferably effected by heating the biomass to a temperature of 50 to 121°C, preferably 50 to 70°C, for a period of 5 to 80 minutes, in particular 20 to 60 minutes.

Likewise, after the fermentation is ended, antioxidants may be added in order to protect the PUFAs  
30 present in the biomass from oxidative degradation. Preferred antioxidants in this context are BHT, BHA, TBHA, ethoxyquin, beta-carotene, vitamin E, in particular tocopherol, and vitamin C. The antioxidant, if used, is preferably added in an amount of 0.001 to 0.1 wt.-%, preferably in an amount of 0.002 to 0.05 wt.-%, relating to the total amount of the fermentation broth after addition of the antioxidant.

35

## Working examples

### Example 1

An unwashed cell broth containing microbial cells (*Schizochytrium* sp.) at a biomass density of over 100 g/l was heated to 60°C in an agitated vessel. After heating up the suspension, the pH was  
5 adjusted to 7.5 by using caustic soda (50 wt.-% NaOH solution), before an alcalase (Alcalase® 2.4 FG (Novozymes)) was added in liquid form in an amount of 0.5 wt.-% (by weight broth). Stirring was continued for 3 hours at 60°C. After that, the lysed cell mixture was transferred into a forced circulation evaporator (obtained from GEA, Germany) and heated to a temperature of 85°C. The mixture was concentrated in the forced circulation evaporator, until a total dry matter content of about 30 wt.-% was  
10 reached. The concentrated lysed cell mixture was transferred into a new vessel, heated up to 90°C under low shear agitation, while adjusting the pH to 10.5 by adding caustic soda. Low shear agitation was continued for about 30 hours, while keeping the temperature at 90°C and the pH above 9.0 by adding caustic soda.

After that the resulting demulsified mixture was neutralized by adding sulfuric acid to adjust a pH of  
15 7.5. Phase separation into a light phase, containing the oil, and a heavy phase, containing water, cell-debris, residual oil and salts, was carried out mechanically by using a disc stack separator (Alfa Laval Disc Stack Centrifuge, LAPX 404/Clara 20)

After separation of the crude oil, the remaining cell debris were resuspended in the aqueous phase, concentrated and dried by spraygranulation.

20 Due to the efficient demulsification, more than 90 wt.-% of the oil could be separated from the biomass without the addition of organic solvents or sodium chloride.

The remaining heavy phase was converted into a solid biomass by concentrating via evaporation to a total dry matter of 45 wt.-% at a temperature of about 90°C and subsequent drying via spray  
25 granulation in a fluidized bed spray granulator. The resulting biomass exhibits a high bulk density of more than 530 kg/m<sup>3</sup>, a high energy value of about 4000 kcal/kg and very good handling properties, in particular a flowability of 4. Comparable biomasses originating from *Schyzochitria* as available on the market exhibit all a much worse flowability of 6 and a much lower bulk density of between 325 to 500 kg/m<sup>3</sup>.

## Claims

1. A method of separating a polyunsaturated fatty acids (PUFAs) containing lipid from the debris of a biomass, comprising the following steps:
  - a) Providing a suspension of a biomass comprising cells which contain a PUFAs containing lipid;
  - b) Lysing the cells of the biomass;
  - c) Heating the suspension as obtained in step (b) to a temperature of 80°C to 100°C, preferably 85°C to 95°C, more preferably about 90°C, while adjusting the pH to a value of 9.0 to 11.5, preferably 9.0 to 11.0, more preferably 9.0 to 10.5;
  - d) Keeping the temperature and pH value in the ranges as depicted in (c) for at least 10 hours, preferably 15 to 40 hours, more preferably 20 to 36 hours.
2. The method according to claim 1, wherein lysing of the cells of the biomass is carried out enzymatically, mechanically, chemically and/or physically.
3. The method according to claim 2, wherein lysing of the cells of the biomass is carried out as follows:
  - a) Heating the suspension of the biomass to a temperature of between 50°C and 70°C, preferably to a temperature of between 55°C and 65°C, adding a cell wall-degrading enzyme to the fermentation broth, and adjusting an adequate pH value, if necessary, at which the enzyme is properly working;
  - b) Keeping the temperature and pH in the ranges as depicted in (a) for at least one hour, preferably for at least two hours, more preferably for two to four hours.
4. The method according to any of the preceding claims, wherein less than 1 wt.-%, preferably less than 0.5 wt.-%, in particular less than 0.1 wt.-%, of organic solvents and/or less than 1 wt.-%, preferably less than 0.5 wt.-%, in particular less than 0.1 wt.-%, of chloride are used in the method.
5. The method according to any of the preceding claims, wherein after lysing of the cells, the suspension is concentrated to a total dry matter content of 30 to 60 wt.-%, more preferably 35 to 55 wt.-%, preferably by evaporation of water at a temperature not higher than 100°C, more preferably 70°C to 100°C, in particular 80°C to 90°C.
6. The method according to any preceding claims, comprising as further step the harvesting of the PUFAs containing oil, wherein harvesting of the PUFAs containing oil preferably comprises neutralization of the demulsified suspension and subsequent separation of the thus obtained oil containing light phase from the water, salts, residual oil and cell debris containing heavy phase and wherein separation of the oil containing light phase from the water, salt, remaining oil and cell debris containing heavy phase is preferably realized by mechanical

means and in particular at a temperature of 60-90°C, more preferably 70-80°C, and at a pH value of preferably 6-9, more preferably 7-8.5.

- 5
7. The method according to claim 6, comprising as a further step the conversion of the water, salt, residual oil and cell debris containing heavy phase into a dried biomass by drying the biomass to a total dry matter content of more than 90 wt.-%, wherein conversion into a dried biomass is preferably carried out by concentration of the heavy phase to a dry matter content of 30-50 wt.-% and subsequent spray granulation of the biomass by using a fluidized bed granulator.
- 10
8. The method according to any of the preceding claims, wherein the suspension is provided as a fermentation broth with a biomass density of preferably at least 80, 100, 120 or 140 g/l.
- 15
9. The method according to any of the preceding claims, wherein the cells which contain a PUFAs containing lipid are selected from algae, fungi, protists, bacteria, microalgae, plant cells, and mixtures thereof, wherein the microalgae are preferably selected from the phylum Stramenopiles, in particular of the family of Thraustochytrids, more preferably of the genus Schizochytrium.
- 20
10. The method according to any of claims 3 to 9, wherein the cell-wall degrading enzyme is selected from proteases, cellulases, hemicellulases, chitinases, pectinases, sucrases, maltases, lactases, alpha-glucosidases, beta-glucosidases, amylases, lysozymes, neuraminidases, galactosidases, alpha-mannosidases, glucuronidases, hyaluronidases, pullulanases, glucocerebrosidases, galactosylceramidases, acetylgalactosaminidases, fucosidases, hexosaminidases, iduronidases, maltases-glucoamylases, beta-glucanases, mannanases, and combinations thereof.
- 25
11. A PUFAs containing biomass comprising less than 2 wt.-%, preferably less than 0.5 wt.-%, in particular less than 0.1 wt.-%, of a non-polar organic solvent and less than 2 wt.-%, preferably less than 0.5 wt.-%, in particular less than 0.1 wt.-%, of chloride, wherein the biomass preferably contains cells and/or cell debris of the phylum Stramenopiles, in particular of the family of Thraustochytrids, preferably of the genus Schizochytrium.
- 30
12. The biomass according to claim 11, comprising a mixture of DHA and EPA, preferably in a ratio of about 3:2 to about 4:1, wherein the content of DHA is at least 10 wt.-% (relating to the total amount of lipid as contained).
- 35
13. The biomass according to claim 11 or 12, wherein the biomass is a delipidated biomass.
- 40
14. A PUFAs containing aqueous suspension, containing a biomass, characterized by a content of non-polar organic solvents of less than 1 wt.-%, preferably less than 0.1 wt.-%, and by a

content of chloride of less than 1 wt.-%, preferably less than 0.1 wt.-%, wherein the biomass preferably contains cells and/or cell debris of the phylus Stramanopiles, in particular of the family of Thraustochytrids, more preferably of the genus Schizochytrium, and wherein the aqueous suspension is preferably characterized by a total dry matter content of 20 to 60 wt.-%.

5

15. A method of feeding animals, in particular beef cattle, wherein a biomass according to any of claims 11 to 13 and/or an aqueous suspension according to claim 14 are provided to animals, preferably after mixing the particulate biomass and/or the aqueous suspension with further feedstuff ingredients.

10

16. A PUFAs containing lipid, exhibiting the following characteristics: a) a peroxide value of less than 0.5, preferably less than 0.3, in particular less than 0.15 meq/kg; b) an anisidine value of less than 15, preferably less than 10; c) preferably a content of free fatty acids of less than 1 wt.-%; d) preferably a content of moisture and impurities of less than 1 wt.-%, preferably less than 0.5 wt.-%; e) preferably a viscosity of less than 250 cps, more preferably of less than 200 cps, in particular of less than 160 cps; e) preferably a flash point of at least 300°C, more preferably of at least 350°C, in particular of at least 400°C, above all of at least 450°C; f) preferably a content of omega-3 fatty acids, in particular of DHA and EPA, of at least 35 wt.-%, preferably at least 40 or 45 wt.-%, above all at least 50 wt.-%; g) preferably DHA and EPA each in an amount of at least 8 wt.-%, preferably at least 10 wt.-%, above all at least 15 wt.-%; h) preferably an amount of organic solvents of less than 0.5 wt.-%, more preferably less than 0.1 wt.-%, in particular less than 0.05 wt.-%, above all less than 0.01 wt.-%; i) preferably an amount of chlorides of less than 0.1 wt.-%, more preferably less than 0.05 wt.-%, in particular less than 0.01 wt.-%; j) preferably a content of crude fat of more than 90 wt.-%.

15

20

25