



US 20020110108A1

(19) **United States**

(12) **Patent Application Publication**

**Kim et al.**

(10) **Pub. No.: US 2002/0110108 A1**

(43) **Pub. Date: Aug. 15, 2002**

(54) **SIMPLE BLOCK SPACE TIME TRANSMIT DIVERSITY USING MULTIPLE SPREADING CODES**

(52) **U.S. Cl. .... 370/342; 370/441**

(76) Inventors: **Younglok Kim**, Fort Lee, NJ (US);  
**Ariela Zeira**, Huntington, NY (US)

(57)

## ABSTRACT

Correspondence Address:

**VOLPE AND KOENIG, PC**  
**DEPT ICC**  
**SUITE 400, ONE PENN CENTER**  
**1617 JOHN F. KENNEDY BOULEVARD**  
**PHILADELPHIA, PA 19103 (US)**

(21) Appl. No.: **09/999,287**

(22) Filed: **Nov. 15, 2001**


### Related U.S. Application Data



(60) Provisional application No. 60/254,013, filed on Dec. 7, 2000.


The present invention is a system and method for use in a CDMA communication system including a plurality of base stations and a user equipment (UE), each for communicating with each other. The base station has a transmitter which includes a first and second antenna for transmitting a data field of symbols. The first spreading device spreads the first data field using a first channelization code and the second spreading device spreads the second data field using a second channelization code, each channelization code being uniquely associated with one of the first and second antennas. The UE has a receiver for receiving a signal including the first and second spread data fields. The UE includes a joint detection device for detecting the symbols of the first and second data fields using the first and second channelization codes and a decoder for decoding the detected data fields to generate a single data field of symbols.



### Publication Classification


(51) Int. Cl.<sup>7</sup> **H04B 7/216**



**FIG. 1****FIG. 2**



**FIG. 4****FIG. 5**

**FIG. 6**

## SIMPLE BLOCK SPACE TIME TRANSMIT DIVERSITY USING MULTIPLE SPREADING CODES

### BACKGROUND

[0001] The present invention relates to communications systems imploring code division multiple access (CDMA) techniques. More particularly, the present invention relates to a transmission diversity scheme which can be applied to a CDMA communication system.

[0002] Spacial diversity has been proposed for support of very high data rate users within third generation wide band code division multiple access systems such as CDMA. Using multiple antennas, the systems achieve better gains and link quality, which results in increased system capacity. Classically, diversity has been exploited through the use of either beam steering or through diversity combining.

[0003] More recently, it has been realized that coordinated use of diversity can be achieved through the use of space-time codes. Such systems can theoretically increase capacity by up to a factor equaling the number of transmit and receive antennas in the array. Space-time block codes operate on a block of input symbols producing a matrix output over antennas and time.

[0004] In the past, space-time transmit diversity systems have transmitted consecutive symbols simultaneously with their complex conjugates. This type of system, though may result in symbol overlap at the receiving end, with the amount of overlap being dependent on the length of the impulse response of the propagation channel. In time division duplex (TDD) mode, this symbol overlap will have to be accounted for in the joint detection receiver. The joint detector will have to estimate the transmitted symbols and their conjugates, resulting in an increase in complexity of the joint detection.

[0005] In order to alleviate this increase in joint detection, systems have been created which transmit two similar but different data fields. The first data field, having a first portion,  $D_1$ , and a second portion,  $D_2$ , is transmitted by the first antenna. A second data field is produced by modifying the first data field. The negation of the conjugate of  $D_2$ ,  $-D_2^*$ , is the first portion of the second data field and the conjugate of  $D_1$ ,  $D_1^*$ , is the second portion. The second data field is simultaneously transmitted by the second antenna. This type of system results in the joint detection implemented at the receiver needing only to estimate the same amount of symbols as in the case of a single transmit antenna. A block diagram of this system is illustrated in FIG. 1.

[0006] Although the above system reduces the complexity of joint detection for a single data block, joint detection requires the use of two joint detectors at the receiver in a system employing two transmit diversity antennas. Each joint detection device estimates the data from one of the antennas. The estimated data is combined to produce the original data. Therefore, the receiver in such a system has a high complexity resulting in higher receiver expense.

[0007] Accordingly, there exists a need for a transmit diversity system requiring less complexity and receiver expense.

### SUMMARY

[0008] The present invention is a system and method for use in a CDMA communication system including a plurality

of base stations and a user equipment (UE), each for communicating with each other. The base station has a transmitter which includes a first and second antenna for transmitting a data field of symbols. The first spreading device spreads the first data field using a first channelization code and the second spreading device spreads the second data field using a second channelization code, each channelization code being uniquely associated with one of the first and second antennas. The UE has a receiver for receiving a signal including the first and second spread data fields. The UE includes a joint detection device for detecting the symbols of the first and second data fields using the first and second channelization codes and a decoder for decoding the detected data fields to generate a single data field of symbols.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0009] FIG. 1 is a block diagram of a prior art communication system employing space-time transmit diversity.

[0010] FIG. 2 is a block diagram of a transmitter and receiver in a communication system in accordance with the preferred embodiment of the present invention.

[0011] FIG. 3 is a flow diagram of the transmit diversity system of the present invention.

[0012] FIG. 4 is a graph of the performance of the transmit diversity system of the present invention.

[0013] FIG. 5 is a block diagram of a transmitter and receiver in a communication system in accordance with an alternative embodiment of the present invention.

[0014] FIG. 6 is a flow diagram of an alternative transmit diversity system of the present invention.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0015] FIG. 2 is a block diagram of a transmitter 10, preferably located at a base station, and a receiver 20, preferably located at a user equipment (UE), in a CDMA communication system in accordance with the preferred embodiment of the present invention. Although it is preferable to have the transmitter located at a base station and the receiver located at the UE, the receiver and transmitter may switch locations and the present invention operate on an uplink communication. The transmitter 10 comprises a block encoder 11, a plurality of channelization devices 8, 9, a plurality of spreading sequence insertion devices 12, 13, and a plurality of antennas 15, 16. Although FIG. 1 illustrates a transmitter comprising two (2) antennas, it should be apparent to those having skill in the art that more than two (2) antennas may be used, such as N antennas.

[0016] A typical communication burst has two data fields separated by a midamble sequence. Preferably, the same encoding procedure, as discussed in the following, for one data field is also performed on the other data field. Data to be transmitted by the transmitter is produced by a data generator (not shown). The resulting data symbols ( $S_1, S_2, \dots, S_{N/2}$ ,  $(S_{N/2+1}, S_{N/2+2}, \dots, S_N)$  of the first data field, which can be represented by sub-data fields  $D_1$  and  $D_2$ , are input into the block encoder 11, preferably a block space-time transmit diversity (BSTTD) encoder. The block encoder 11 encodes the input symbols and generates the

complex conjugate of  $D_1$  and the negation of the conjugate of  $D_2$ :  $D_1^*$ ,  $-D_2^*$ . The encoder 11 also changes the order of the symbols so that  $-D_2^*$  is ahead of  $D_1^*$ . Preferably, an analogous encoding of the second data field is also performed.

[0017] In accordance with the preferred embodiment of the present invention, the data fields,  $D_1$ ,  $D_2$  and  $-D_2^*$ ,  $D_1^*$  are forwarded to a first and second channelization device 8, 9, respectively. The first channelization device 8 spreads the data blocks  $D_1$ ,  $D_2$  by a first channelization code, and  $-D_2^*$ ,  $D_1^*$  by the second channelization device 9 using a second different channelization code. Each of the spread data blocks from the first and second channelization devices 8, 9 are then scrambled by the scrambling code associated with the transmitter 10.

[0018] Once the symbols  $D_1$ ,  $D_2$ ,  $-D_2^*$ ,  $D_1^*$  have been scrambled, they are mixed with a first and second midamble through training sequence insertion devices 12, 13, producing two communication bursts 17, 18. The two bursts 17, 18 are modulated and simultaneously transmitted to the receiver 20 over antenna 15 and diversity antenna 16, respectively.

[0019] The receiver 20 comprises a joint detection device (JD) 24, a BSTTD decoder 22, a channel estimation device 23 and an antenna 26. The antenna 26 of the UE receives various RF signals including the communication bursts 17, 18 from the transmitter 10. The RF signals are then demodulated to produce a baseband signal.

[0020] The baseband signal is then forwarded to the joint detection device 24 and the channel estimation device 23. As those skilled in the art know, the channel estimation device 23 provides channel information, such as channel impulse responses, to the joint detection device 24.

[0021] The joint detection device 24, coupled to the channel estimation device 23 and BSTTD decoder 22, utilizes the channel information and the channelization codes to detect the soft data symbols  $d_1$ ,  $d_2$ ,  $-d_2^*$ ,  $d_1^*$  in the received signal. The channel impulse response for each burst is determined using that burst's midamble sequence. Since each burst was transmitted using a different spreading code, the joint detection device 24 treats each burst as being transmitted by a different user. As a result, any joint detection device which can recover data from different transmitter sites may be used. Such joint detection devices include zero forcing block linear equalizers, detection devices using Cholesky or approximate Cholesky decomposition, as well as many others. The joint detection device 24 estimates the data symbols of each of the bursts 17, 18 output by the transmitter antennas 15, 16 and forwards the estimates to the BSTTD decoder 22.

[0022] The BSTTD decoder 22, coupled to the joint detection device 24, receives the estimated soft data symbols  $d_1$ ,  $d_2$  and  $-d_2^*$ ,  $d_1^*$  corresponding to the antennas 15, 16 and decodes the symbols to yield a single data field's soft symbols,  $d_{\text{STTD}}$ .

[0023] The flow diagram of the present invention is illustrated in FIG. 3. A data generator generates data to be transmitted to the receiver 20 (step 301). Each data field is separated into two sub-data fields  $D_1$ ,  $D_2$  (step 302). The sub-data fields  $D_1$ ,  $D_2$  are forwarded to the block encoder 11 and the first channelization device 8 (step 303). The sub-data

fields forwarded to the block encoder 11 are encoded (step 304) and forwarded to the second channelization device 9 (step 305). Each channelization device 8, 9 spreads their respective data input using a separate channelization code associated with a respective antenna 15, 16 (step 306). The two spread signals are then scrambled, using the scrambling code associated with the base station (step 307) and transmitted to the receiver 20 over diversity antennas 15, 16 (step 308).

[0024] The receiver 20 receives a RF communication signal including the two spread signals from the diversity antennas 15, 16 (step 309), demodulates the signal and forwards the demodulated signal to the channel estimation device 23 and joint detection device 24 (step 310). The received signal is processed by the channel estimation device 23 (step 311) and the channel information applied by the joint detection device 24 along with the channelization codes, to estimate the transmit symbols from the diversity antennas 15, 16 (step 312). The detected sub-data fields, corresponding to each diversity antenna 15, 16, are forwarded to the BSTTD decoder (step 313), which decodes the soft symbol sub-fields to yield a single data field's soft symbols,  $d_{\text{STTD}}$  (step 314).

[0025] Similar to the preferred embodiment disclosed above, FIG. 5 is a block diagram of an alternative transmitter 40, preferably located at a base station, and a receiver 50, preferably located a user equipment (UE) in a communication system. The transmitter 40 comprises a plurality of channelization devices 48, 49, a plurality of spreading sequence insertion devices 42, 43, and a plurality of antennas 45, 46.

[0026] Data to be transmitted by the transmitter 40 is produced by a data generator (not shown). The resulting data symbols  $(S_1, S_2, \dots, S_{N/2}, (S_{N/2}+1, S_{N/2}+2, \dots, S_N)$  of the first data field, which can be represented by sub-data fields  $D_1$  and  $D_2$ , are input to a first and second channelization device 48, 49, respectively. The first channelization device 8 spreads the data blocks  $D_1$ ,  $D_2$  by a first channelization code, and the second channelization device 49 spreads the data blocks  $D_1$ ,  $D_2$  by a second different channelization code. Each of the spread data blocks from the first and second channelization devices 48, 49 are scrambled by the scrambling code associated with the transmitter 40.

[0027] Once the symbols have been scrambled, they are mixed with a first and second midamble through training sequence insertion devices 42, 43, producing two communication bursts 44, 45. The two bursts 44, 45 are modulated and simultaneously transmitted to the receiver 50 over antenna 46 and diversity antenna 47, respectively.

[0028] The receiver 50 comprises a joint detection device (JD) 54, a decoder 52, a channel estimation device 53 and an antenna 51. The antenna 51 of the UE receives various RF signals including the communication bursts 44, 45 from the transmitter 40. The RF signals are then demodulated to produce a baseband signal.

[0029] The baseband signal is then forwarded to the joint detection device 54 and the channel estimation device 53. The joint detection device 54, coupled to the channel estimation device 53 and decoder 52, utilizes the channel information and the channelization codes to detect the soft data symbols  $d_1$ ,  $d_2$ , in the received signal. The channel

impulse response for each burst is determined using that burst's midamble sequence. Since each burst was transmitted using a different spreading code, the joint detection device 54 treats each burst as being transmitted by a different user. The joint detection device 54 estimates the data symbols of each of the signals 44, 45 output by the transmitter antennas 46, 47 and forwards the estimates to the decoder 52.

[0030] The decoder 52, coupled to the joint detection device 54, receives the estimated soft data symbols  $d_1, d_2$  corresponding to the antennas 46, 47 and decodes the symbols to yield a single data field's soft symbols,  $d$ .

[0031] The flow diagram of the alternative embodiment is illustrated in **FIG. 6**. A data generator generates data to be transmitted to the receiver 40 (step 601). Each data field is separated into two sub-data fields  $D_1, D_2$  (step 602). The sub-data fields  $D_1, D_2$  are forwarded to the first channelization device 48 and to the second channelization device 49 (step 603). Each channelization device 48, 49 spreads their respective data input using a separate channelization code associated with each antenna 46, 47 (step 604). The two spread signals are then scrambled, using the scrambling code associated with the base station (step 605) and transmitted to the receiver 50 over diversity antennas 46, 47 (step 606).

[0032] The receiver 50 receives a RF communication signal including the two spread signals from the diversity antennas 46, 47 (step 607), demodulates the signal and forwards the demodulated signal to the channel estimation device 53 and joint detection device 54 (step 608). The received signal is processed by the channel estimation device 53 (step 609) and the channel information applied by the joint detection device 54 along with the channelization codes, to estimate the transmit symbols from the diversity antennas 46, 47 (step 610). The detected sub-data fields, corresponding to each diversity antenna 46, 47, are forwarded to the decoder 52 (step 611), which decodes the soft symbol sub-fields to yield a single data field's soft symbols,  $d_{\text{STTD}}$  (step 612).

[0033] By using additional channelization codes, the above approaches can be applied to an antenna array having any number of antennas. Each antenna has its own associated channelization code and midamble. If a block encoder is used, the data field transmitted by each of the antennas has a unique encoding, allowing the use of a single joint detector at the receiver.

[0034] The B STTD transmitter with two channelization codes of the present invention allows for the use of a cheaper and simpler method of transmit diversity. The use of different channelization codes per transmit antenna requires only one joint detection device at the receiver resulting in a less complex receiver system than those of the prior art. **FIG. 4** is a graph showing the raw BER of various block STTD decoders. The model is based on all the receivers using a block linear equalizer (BLE) based approach to JD. NTD means the single antenna case, i.e., no transmit diversity. STTD with 1 code is the traditional block STTD JD. STTD with 2 code is the disclosed block STTD transmitter. Simple STTD with 2 code is the transmission system disclosed in the alternative embodiment. As illustrated, the benefit of 2 codes for STTD can be summarized as follows: 1) there is up to a 0.5 dB gain at **0.01** raw Bit error rate over 1 code

STTD; and 2) by eliminating the encoding block in simple STTD with 2 code, the performance degradation is only 0.2 dB at 0.1 raw BER and no degradation at 0.01 raw BER. The performance improvement over NTD is still 1.0 dB and 2.7 dB at **0.1** and 0.01 raw BER.

What is claimed is:

1. A method for transmitting a data field of symbols in a CDMA communication system including a plurality of base stations and a user equipment (UE), wherein each of said base stations include a transmitter and said UE includes a receiver, the method comprising the steps of:

generating a first data field of symbols;

encoding said first data field producing a second data field having complex conjugates of the symbols of said data field;

spreading said first and second data fields, wherein said first data field is spread using a first channelization code and said second data field is spread using a second channelization code, each channelization code being uniquely associated with one of a first and second antennas;

transmitting an RF signal including said first and second spread data fields over a first and second antenna of said transmitter;

detecting the symbols of said first and second data fields using said first and second channelization codes; and decoding said detected data fields to generate a single data field of symbols.

2. The method of claim 1 further comprising the step of scrambling said first and second spread data fields by a scrambling code associated with said transmitter.

3. The method of claim 2 wherein the symbols of said first data field of symbols are grouped into a first and second sub-data field.

4. The method of claim 3, wherein the symbols of said second data field of symbols are grouped into a third and fourth sub-data field, wherein said third sub-data field is the negative complex conjugate of said second sub-data field and said fourth sub-data field is the complex conjugate of said first sub-data field.

5. The method of claim 4 wherein said base station further includes said receiver; and said UE further includes said transmitter.

6. A transmitter for transmitting a data field of symbols in a CDMA communications system including a plurality of base stations and a user equipment (UE), said base stations including said transmitter and said UE including a receiver for communicating with each other, the transmitter comprising:

a first and second antenna for transmitting said data field of symbols;

an encoder for encoding said data field producing a second data field having complex conjugates of the symbols of said data field; and

a first and second spreading device for spreading said first and second data fields, wherein said first spreading device spreads said first data field using a first channelization code and said second spreading device spreads said second data field using a second channel-

ization code, each channelization code being uniquely associated with one of said first and second antennas.

7. The transmitter of claim 6 further comprising a first and second scrambling device for scrambling said first and second spread data fields by a single scrambling code associated with said transmitter.

8. The transmitter of claim 7 wherein said receiver for receiving a signal including said first and second spread data field, comprises:

a joint detection device for detecting the symbols of said first and second data fields using said first and second channelization codes; and

a decoder for decoding said detected data fields to generate a single data field of symbols.

9. The transmitter of claim 8 wherein the symbols of said first data field of symbols are grouped into a first and second sub-data field.

10. The transmitter of claim 9, wherein the symbols of said second data field of symbols are grouped into a third and fourth sub-data field, said third sub-data field being the negative complex conjugate of said second sub-data field and said fourth sub-data field being the complex conjugate of said first sub-data field.

11. A CDMA communication system including a plurality of base stations and a user equipment (UE), each for communicating with each other, said plurality of base stations having a transmitter including:

a first and second means for transmitting a data field of symbols including a first data field;

a means for encoding said data field producing a second data field having complex conjugates of the symbols of said data field; and

a first and second spreading means for spreading said first and second data fields, wherein said first spreading means spreads said first data field using a first channelization code and said second spreading means spreads said second data field using a second channelization code, each channelization code being uniquely associated with one of said first and second transmitting means;

said UE having a means for receiving a signal including said first and second spread data fields, comprising:

a means for detecting the symbols of said first and second data fields using said first and second channelization codes; and

a means for decoding said detected data fields to generate a single data field of symbols.

12. The system of claim 11 further comprising a means for scrambling said first and second spread data fields by a scrambling code associated with said transmitting means.

13. The system of claim 12 wherein the symbols of said first data field of symbols are grouped into a first and second sub-data field.

14. The system of claim 13, wherein the symbols of said second data field of symbols are grouped into a third and fourth sub-data field, wherein said third sub-data field is the negative complex conjugate of said second sub-data field and said fourth sub-data field is the complex conjugate of said first sub-data field.

15. The system of claim 14 wherein said base station further includes said means for receiving and said UE further includes said transmitting means.

16. A method for transmitting a data field of symbols in a CDMA communication system including a plurality of base stations and a user equipment (UE), wherein each of said base stations include a transmitter and said UE includes a receiver, the method comprising the steps of:

generating a data field of symbols;

spreading said first data field using a first channelization code producing a first spread data field;

spreading said first data field using a second channelization code producing a second spread data field, each channelization code being uniquely associated with one of a first and second antennas;

transmitting an RF signal including said first and second spread data fields over a first and second antenna;

detecting the symbols of said data field using said first and second channelization codes; and

decoding said detected data field to generate a single data field of symbols.

17. The method of claim 16 further comprising the steps of scrambling said first and second spread data fields by a scrambling code associated with said transmitter.

18. The method of claim 17 wherein said base station further includes said receiver and said UE further includes said transmitter.

19. A transmitter for transmitting a data field of symbols in a CDMA communications system including a plurality of base stations and a user equipment (UE), said base stations including said transmitter and said UE including a receiver for communicating with each other, the transmitter comprising:

a first and second antenna for transmitting said data field of symbols; and

a first and second spreading device for spreading said data field, wherein said first spreading device spreads said data field using a first channelization code, producing a first spread data field, and said second spreading device spreads said data field using a second channelization code, producing a second spread data field, each channelization code being uniquely associated with one of said first and second antennas.

20. The transmitter of claim 19 further comprising a first and second scrambling device for scrambling said first and second spread data fields by a single scrambling code associated with said transmitter.

21. The transmitter of claim 20 wherein said receiver for receiving a signal including said first and second spread data fields comprises:

a joint detection device for detecting the symbols of said data fields using said first and second channelization codes; and

a decoder for decoding said detected data fields to generate a single data field of symbols.

22. A CDMA communication system including a plurality of base stations and a user equipment (UE), each for communicating with each other, said plurality of base stations having a transmitter including:

a first and second means for transmitting a data field of symbols;

a first and second spreading means for spreading said data field, wherein said first spreading means spreads said data field using a first channelization code producing a first spread data field and said second spreading means spreads said second data field using a second channelization code producing a second spread data field, each channelization code being uniquely associated with one of said first and second transmitting means;

said UE having a means for receiving a signal including said first and second spread data fields, comprising:

a means for detecting the symbols of said first and second spread data fields using said first and second channelization codes; and

a means for decoding said detected data fields to generate a single data field of symbols.

**23.** The system of claim 22 further comprising a means for scrambling said first and second spread data fields by a scrambling code associated with said transmitting means.

\* \* \* \* \*