



(51) International Patent Classification:

B65C 3/16 (2006.01) *B67C 3/24* (2006.01)
B65C 9/04 (2006.01) *B67C 3/26* (2006.01)
B67C 3/10 (2006.01)

(21) International Application Number:

PCT/EP2013/076619

(22) International Filing Date:

13 December 2013 (13.12.2013)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

12199777.9 28 December 2012 (28.12.2012) EP

(71) Applicant: **SIDEL S.p.A. CON SOCIO UNICO** [IT/IT];
Via La Spezia, 241/A, Parma (IT).


(72) Inventors: **ZONI, Roberto**; c/o SIDEL S.p.A. CON SOCIO UNICO, Via La Spezia, 241/A, I-43100 Parma (IT).
MALFATTO, Annalisa; c/o SIDEL S.p.A. CON SOCIO UNICO, Via La Spezia, 241/A, I-43100 Parma (IT).

(74) Agents: **BOGGIO, Luigi** et al.; Studio Torta S.p.A., Via Viotti, 9, I-10121 Torino (IT).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

[Continued on next page]

(54) Title: A MACHINE AND A METHOD FOR FILLING CONTAINERS



(57) Abstract: A method and a machine for filling containers (2), wherein each container (2) is advanced along a path (P) by means of a handling unit (12; 52), is filled with a pourable product by a filling device (14; 53) of the handling unit (12; 52), and is rotated about its longitudinal axis (A) during the step of filling.



(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,

SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

A MACHINE AND A METHOD FOR FILLING CONTAINERS

TECHNICAL FIELD

The present invention relates to a machine and a
5 method for filling containers with pourable products, in
particular carbonated liquids, such as sparkling water,
soft drinks and beer, which the following description
will refer to, although this is in no way intended to
limit the scope of protection as defined by the
10 accompanying claims.

The present invention may be also used to
particular advantage for any type of container, such as
containers or bottles made of glass, plastics, aluminum,
steel and composites, and for any type of pourable
15 product, such as non-carbonated liquids (including still
water, juices, teas, sport drinks, liquid cleaners,
wine, etc), emulsions, suspensions and high viscosity
liquids.

BACKGROUND ART

20 As is known, many pourable products are sold in a
wide range of bottles or containers, which are
sterilized, filled and closed in container handling
plants typically including a plurality of processing
stations or machines, such as rinsing machines, filling
25 machines, capping machines and labelling machines.

These processing stations can be defined by linear
machines or, more frequently, by carousel-type machines.
The following description will refer to carousel-type
machines only, although this is in no way intended to
30 limit the scope of protection of the present
application.

The containers to be handled are generally fed to
and removed from these machines by means of a transport
system including star wheels and linear conveyors.

35 Known container handling plants are therefore
fairly bulky and allow little freedom of choice in terms

of layout; moreover, this kind of plants requires quite complicated adjustments to synchronize the different processing stations and entails relatively high operating and maintenance costs.

5 Another problem posed in respect of known filling machines is the formation of foam at the end of the operation of filling the container.

 This problem is mainly caused by the fact that, for reasons of economy, commercial containers are not such
10 larger than the volume required for accommodating of the contents. Thus, during filling operations, which have to be carried out at high speed, it is common for some amount of liquid in the form of foam to bubble over the top of the container prior to the container being capped
15 or sealed. The product loss can be as high as ten percent, which translates into higher cost for the consumer or lower profitability for the bottler, or both.

 To reduce this product loss, some filling machines
20 include a dwell station that allows for the product foam in a recently filled container to settle prior to capping.

 Other filling machines include a short suction pipe adapted to be introduced into the container to be
25 sealed, and a suction system whereby the foam over the top surface of the liquid is removed and optionally recycled into the product reservoir.

 Some filling machines may also use blast nozzles for blowing any drops and residual foam from the
30 surfaces to be sealed or capped.

 Some filling machines reduce the temperature of the liquid at the mixing tanks or other reservoirs to reduce foaming.

 In certain cases, the containers are purposefully
35 overfilled to compensate for lost product in the form of foam and thereby achieve the desired net fill volume,

which results in undesirable product loss.

Other possible solutions are based on the use of ultrasonic waves for collapsing the foam; in practice, the portion of liquid forming the foam again becomes
5 part of the liquid content of the container rather than being wasted.

DISCLOSURE OF INVENTION

It is an object of the present invention to provide a machine for filling containers, designed to eliminate
10 at least one of the aforementioned drawbacks, and which is cheap and easy to implement.

According to one aspect of the present invention, there is provided a machine for filling containers as claimed in claim 1.

15 The present invention also relates to a method for filling containers as claimed in claim 15.

According to another aspect of the present invention, there is provided a machine for filling containers as claimed in claim 23.

20 The present invention also relates to a method for filling containers as claimed in claim 30.

BRIEF DESCRIPTION OF THE DRAWINGS

A non-limiting embodiment of the present invention will be described by way of example with reference to
25 the accompanying drawings, in which:

Figure 1 shows a schematic top plan view, with parts removed for clarity, of a first embodiment of a machine for filling containers according to the present invention;

30 Figure 2 shows a larger-scale top plan view, with parts removed for clarity, of a part of the Figure 1 machine;

Figure 3 shows a larger-scale, partly sectioned side view of a handling assembly of the Figure 1 machine
35 for carrying and filling a relative container;

Figure 4 shows a schematic top plan view, with parts

removed for clarity, of a second embodiment of a machine for filling containers according to the present invention;

Figure 5 shows a sectioned side view, with parts removed for clarity, of a handling assembly of the Figure 4 machine for carrying and filling a relative container, and

Figure 6 shows a larger-scale sectioned side view, with parts removed for clarity, of a detail of the handling assembly of Figure 5.

BEST MODE FOR CARRYING OUT THE INVENTION

Number 1 in Figure 1 indicates as a whole a machine for filling containers, in particular bottles 2, with pourable products, in the example shown carbonated liquids, such as sparkling water or carbonated beverages, including soft drinks and beer.

As visible in Figure 3, each bottle 2 has a longitudinal axis A and is bounded at the bottom by a bottom wall 3 substantially perpendicular to axis A, and has a top neck 4 substantially coaxial with the axis A.

In the example shown, the bottles 2 filled by machine 1 are made of plastics; however, machine 1 may be also used for other types of containers, such as containers made of aluminum, steel, glass and composites. Moreover, the containers used in machine 1 may be filled with any type of pourable product, including non-carbonated liquids (such as still water, juices, teas, sport drinks, liquid cleaners, wine, etc), emulsions, suspensions and high viscosity liquids.

Machine 1 comprises a conveying device 5 that, according to the present invention, serves not only to fill the bottles 2 but also to label them during the filling process.

In the preferred embodiment as illustrated on the figures, the conveying device 5 comprises a carousel 6, which is mounted to rotate continuously (anticlockwise

in Figures 1 and 2) about a vertical axis B perpendicular to the Figure 1 plane. The carousel 6 receives a succession of empty bottles 2 from an input star wheel 7, which is connected to carousel 6 at a first transfer station 8 and is mounted to rotate continuously about a respective longitudinal axis C parallel to axis B. The carousel 6 releases a succession of filled bottles 2 to an output star wheel 9, which is connected to carousel 6 at a second transfer station 10 and is mounted to rotate continuously about a respective longitudinal axis D parallel to axes B and C.

Machine 1 further comprises a plurality of handling units 12, which are equally spaced angularly about axis B, are mounted along a peripheral portion 11 of carousel 6, and are moved by the carousel 6 along a path P extending about axis B and through stations 8 and 10.

As shown in the enclosed Figures, each handling unit 12 comprises a support device 13 adapted to receive and retain a relative bottle 2 in a vertical position, in which such bottle 2 has its axis A parallel to the axis B of carousel 6, and a filling device 14 for feeding the pourable product into a bottle 2 as the support device 13 travels along path P.

Each filling device 14 is conveniently arranged above the bottle 2 to be filled.

With particular reference to Figure 3, support device 13 of each handling unit 12 comprises a support plate 15 adapted to receive a relative bottle 2 in a vertical position, i.e. resting on support plate 15 with its axis A extending vertically; more specifically, the bottle 2 is arranged with its bottom wall 3 in contact with the support plate 15 and extends vertically from the latter.

Support plate 15 is advantageously mounted on carousel 6 in a rotatable manner about its own axis E, coaxial in use with axis A of the relative bottle 2. In

greater detail, peripheral portion 11 of carousel 6 has a plurality of through holes 16 equally spaced angularly about axis B, and a plurality of support sleeves 17, each protruding downwards from the edge of a relative
5 hole 16; in the example shown, each support sleeve 17 is secured to the bottom face of the edge of the relative hole 16 by screws 18 and extends coaxially with a relative axis E.

Each support plate 15 is secured on top of a
10 relative rotating element 19 engaging both the relative hole 16 and support sleeve 17 in a rotatable manner about relative axis E.

Each support device 13 further comprises an electric motor 20 having a casing 21, coaxially secured
15 to a bottom end of the relative support sleeve 17, and an output shaft 22 supported in a rotatable manner by the casing 21 and coupled to a bottom end of the relative rotating element 19.

In practice, electric motor 20 and rotating element
20 19 of each handling unit 12 define actuator means for rotating a bottle 2 about its axis A during its movement along path P together with carousel 6.

Thanks to this type of arrangement, each bottle 2 has, in use, a revolution motion about axis B together
25 with carousel 6 and a rotary motion about its own axis A as a result of the torque imparted by electric motor 20 to rotating element 19 and support plate 15.

Filling device 14 of each handling unit 12 basically comprises a support block 23 secured, in a
30 manner known per se and not shown, to the carousel 6 and terminating, towards the bottle 2, with a hollow body 24, in the example shown having a tubular configuration; filling device 14 of each handling unit 12 further comprises a filling head 25 engaging hollow body 24 in a
35 fluid-tight manner and adapted to cooperate with the top neck 4 of the relative bottle 2 to perform the filling

operation.

In particular, each filling head 25 defines a filling mouth 26 and has a lower end 25a facing the top neck 4 of the relative bottle 2 and provided with a gasket (known per se and not shown).

Each filling head 25 is supported by the relative support block 23 in a rotatable manner about the relative axis E; each filling head 25 is also supported by the relative support block 23 in a displaceable manner along the relative axis E between a rest position (not shown), in which it has its lower end 25a spaced from the top neck 4 of the relative bottle 2, and a filling position (Figure 3), in which it has the gasket of its lower end 25a in contact with the top neck 4 of the relative bottle 2 so that the relative filling mouth 26 communicates with the inside of the bottle 2 in a fluid-tight manner towards the outside.

In practice, each filling head 25 is supported by the relative support block 23 in an idle manner about axis E and can be displaced along the same axis between the rest position and the filling position; in this way, when a filling head 25 is set in the filling position, rotation of the relative support plate 15 about its axis E is transmitted, through the relative bottle 2, to the filling head 25, which is also driven to rotate about the axis E, so performing a guiding and supporting action on top neck 4 of the bottle 2.

Each filling head 25 defines a central conduit 27, a first annular conduit 28 extending around the conduit 27, and a second annular conduit 29 formed between the side wall of the filling head 25 and the outer side wall of the conduit 28.

Support block 23 of each filling device 14 internally defines at least three different fluid circuits, known per se and only schematically shown in Figure 3:

- a product circuit 30 for connecting, through an ON/OFF valve (known per se and not shown), the relative annular conduit 28 to a tank (known per se and not shown) containing the pourable product;

5 - a pressurization circuit 31 for connecting, through an ON/OFF valve 32, the relative central conduit 27 to a chamber 33 filled with a pressurization fluid, e.g. carbon dioxide; and

10 - a decompression circuit 35 for connecting, through an ON/OFF valve 36, the relative annular conduit 29 to a chamber 37 in turn connected to a discharge device (known per se and not shown).

According to one important aspect of the present invention, each bottle 2 is in use rotated about its axis A, by activating the relative electric motor 20, while the bottle 2 is filled with the pourable product by the relative filling device 14.

Thanks to this additional rotation of the bottle 2 about its axis A during the revolution movement of the same bottle 2 about axis B, it is possible to obtain the following effects:

- the centrifugal force caused by this double rotation generates an additional pressure on the pourable product in the bottle 2, which entraps the carbon dioxide into the product; and

- the pourable product comes down into the bottle 2 along the lateral wall thereof instead of centrally.

Both these effects permits to obtain a significant reduction in the formation of foam at the end of the filling operation.

According to a possible alternative not shown, each support device 13 may be defined by gripping means acting on the top neck 4 of a bottle 2 to retain it in a suspended position. In this case, the rotary motion of each bottle 2 about its axis A may be obtained by an electric motor having a casing, secured to the support

block 23 of the relative filling device 14, and an output shaft connected to the relative filling head 25 and to the gripping means. In practice, in this case, the electric motor would be carried by the relative
5 filling device 14.

According to another important aspect of the present invention, machine 1 further comprises a labelling unit 40 arranged peripherally with respect to carousel 6 and configured to feed a succession of labels
10 41 to the respective handling units 12 while such units are advanced along path P by carousel 6 and pass by the labelling unit 40.

As visible in Figure 1, labelling unit 40 is arranged between input star wheel 7 and output star wheel 7
15 wheel 9 along path P; more specifically, labels 41 are supplied to handling units 12 at a transfer station 42 interposed between transfer stations 8 and 10 along path P and preferably arranged closer to transfer station 8 than transfer station 10.

With particular reference to Figure 2, labelling unit 40 basically comprises a supply assembly 44 for supplying a web 45, provided with the labels 41, along a path Q towards carousel 6, and an interaction device 46
20 interacting with the web 45 at transfer station 42 to separate each label 41 from the rest of the web 45 and supplying such label 41 to the handling unit 12 passing by the transfer station 42.

In the example shown, labels 41 are of the pressure-sensitive type and are originally affixed to
30 web 45 at spaced apart positions.

Supply assembly 44 basically comprises a supply reel 47, off which web 45 is unwound, and a plurality of rollers 48, about which the web 45 is wound to be guided and supplied along path Q; at least one of the
35 rollers 48 is motorized to drive web 45 off the supply reel 47 and towards transfer station 42 of carousel 6.

In the embodiment shown in Figures 2 and 3, interaction device 46 comprises a peeler blade 50, over which the web 45 is pulled, thereby causing each label 41 to separate from the web 45, which is then disposed
5 of. In practice, at transfer station 42, labels 41 are sequentially peeled off web 45 about peeler blade 50 and applied to corresponding bottles 2 sequentially arriving at transfer station 42 as a result of the advancement of handling units 12 by carousel 6.

10 According to a possible alternative not shown, labels 41 may be integral parts of a web, which is then cut by cutting means at the transfer station 42 to feed a succession of labels 41 to the bottles 2 on carousel 6.

15 In order to allow application of each label 41 on the corresponding bottle 2, the latter is rotated about its axis A by activating electric motor 20.

As it will be explained in greater detail hereafter, the application of each label 41 on the
20 corresponding bottle 2 is performed after pressurization of such bottle 2 by opening valve 32 of the relative pressurization circuit 31.

Operation of machine 1 will now be described with reference to the filling of one bottle 2, and therefore
25 to one handling unit 12, and as of the instant in which such bottle 2 is received by support device 13 of the handling unit 12 from input star wheel 7 in order to be filled with the pourable product.

In this condition, the bottle 2 is centered with
30 respect to the relative filling device 14 by moving the filling head 25 from the rest position to the filling position. In particular, the gasket of the lower end 25a of the filling head 25 contacts the top neck 4 of the bottle 2, which reaches a position coaxial with the
35 filling head 25. In practice, the axis A of the bottle 2 is coaxial with the axis E of the filling head 25.

At this point, valve 32 of pressurization circuit 31 is opened (the valve of product circuit 30 and valve 36 of decompression circuit 35 are in a closed condition) and is maintained in that condition up to the
5 moment in which pressure in the bottle 2 reaches a given first value V1, for instance about 1,5 bar, adapted to make the bottle 2 sufficiently rigid for labelling. Then, the valve 32 is closed.

In the meantime, the handling unit 12 reaches
10 transfer station 42, where a label 41 is supplied by labelling unit 40 to the bottle 2; in order to allow application of the label 41 on the bottle 2, the latter is rotated about its axis A by activating electric motor 20. In particular, in this stage, rotary motion imparted
15 by output shaft 22 of electric motor 20 to rotating element 19 and support plate 15 is transmitted to the bottle 2 and from the latter to the filling head 25, which is in contact with the top neck 4 of the bottle 2 and is supported in an idle condition by support block
20 23.

Once the label 41 has been applied on bottle 2, a further pressurization step is carried out by opening valve 32 of pressurization circuit 31, which is maintained in the open condition up to the moment in
25 which pressure in the bottle 2 reaches a given second value V2, for instance about 6 bar, higher than first value V1 and defining the requested condition for the filling operation with the carbonated liquid. Then, the valve 32 is again closed.

30 By opening the valve of product circuit 23, the actual filling of the bottle 2 with the product can be started. This step ends when the product reaches the desired level in the bottle 2.

During this step, electric motor 20 is again
35 activated to rotate the bottle 2 about its axis A. Therefore, the bottle 2 is subjected to a revolution

motion about axis B and a rotary motion about axis A. Thanks to this double rotation about axes A and B, the bottle 2 can be filled at high speed with a reduced formation of foam. As a matter of fact, the centrifugal force caused by this additional rotation about axis A generates an additional pressure on the product in the bottle 2, which entraps the carbon dioxide into the product. Moreover, the product comes down into the bottle 2 along the lateral wall thereof instead of centrally.

The next step is the decompression of the bottle 2, which is achieved by connecting the bottle 2 with decompression circuit 35. At this point, the filling head 25 can be moved to the rest position.

In the case in which the pourable product delivered to the bottle 2 is a non-carbonated liquid, the second pressurization step is not performed.

The advantages of machine 1 and the filling method according to the present invention will be clear from the foregoing description.

In particular, the filling process and the labelling process of the containers are both performed on the same machine. This solution, when compared to a traditional solution using distinct machines for performing such processes, permits to reduce:

- the overall space occupied by the resulting container handling plant;
- the maintenance cost; and
- the operating cost, as only one carousel with a relative motor is used instead of two.

Moreover, the step of pressurizing the containers, normally used in a filling process, is exploited in the labelling process of containers made of a deformable material, such as plastics, for permitting the application of the label directly on the container.

Last but not least, the rotation of each container

about its axis, normally used in a labelling process to permit application of the label on the container, is also used in the filling operation to reduce the formation of foam and thereof to increase the filling speed. In fact, as above explained, the additional rotation of each container about its axis, during the revolution movement of the same container about the carousel axis, permits to obtain the following effects:

- the centrifugal force caused by this additional rotation generates an additional pressure on the pourable product in the container, which, in the case of carbonated liquids, entraps the carbon dioxide into the product; and

- the pourable product comes down into the container along the lateral wall thereof instead of centrally.

Figure 4 shows a machine 51 for filling bottles 2, which differs from the machine shown in Figures 1-3 in that the labeling unit 40 is eliminated and the handling units 12 are eliminated and replaced by respective handling units 52.

As shown in Figures 5 and 6, each handling unit 52 comprises a filling device 53 comprising, in turn, a vertical post 54 with a cylindrical shape, which has a longitudinal axis 55 parallel to axis B, and is fixed to the peripheral portion 11 of the carousel 6.

The post 54 is radially delimited by an inner wall 56 comprising an upper wide portion 57 and a lower narrow portion 58, and is engaged in a sliding manner by a shutter 59 with a tubular shape, which is mounted inside the post 54 coaxial to the axis 55.

The shutter 59 projects downwards from a lower end of the post 54, and is coupled to the post 54 by means of a deformable annular membrane 60, which is interposed between the post 54 and the shutter 59 itself.

The shutter 59 defines, together with the post 54,

a tubular feeding duct 61, which extends between the post 54 and the shutter 59, and is connected to a tank (not shown) of the pourable product to be fed into the bottles 2.

5 The shutter 59 is axially mobile between a lowered closing position, in which the shutter 59 is arranged in contact with the wall 56 so as to be coupled to the post 54 in a fluid-tight manner and close the duct 61, and a raised opening position, in which the duct 61 itself is
10 open.

 The shutter 59 is moved to its raised opening position - and normally kept there - by a spring 62, which is mounted between the post 54 and the shutter 59 coaxial to the axis 55, and is moved to its lowered
15 closing position, against the action of the spring 62, by an actuating cylinder 63.

 The cylinder 63 is obtained in the post 54 coaxial to the axis 55, is provided with a piston 64, which is coupled to the shutter 59 in an axially and angularly
20 fixed manner, and is connected to a known pneumatic device, which is not shown.

 The shutter 59 has, furthermore, a swirler 65, which is obtained on the outer surface of the shutter 59 itself, and extends along - and around - the axis 55, so
25 as to cause the pourable product fed along the duct 61 to have a swirling movement.

 The shutter 59 defines an inner feeding duct 66, which extends inside the shutter 59, and is connected to a feeding device (not shown), which is adapted to feed a
30 gas under pressure along the duct 66 and into the bottles 2.

 The device 53 comprises, furthermore, an actuating cylinder 67 with a tubular shape, which extends around a lower narrow end 68 of the post 54, is mounted coaxial
35 to the axis 55, and is coupled to the post 54 itself in an angularly and axially fixed manner.

The device 53 cooperates with a gripping member 69 for a bottle 2 comprising a substantially cylindrical bell 70, which is coaxial to the axis 55, extends around the cylinder 67, and is arranged with its concavity facing upwards.

The bell 70 is coupled to the cylinder 67 in an axially fixed manner and, furthermore, is coupled to the cylinder 67 in a rotary manner by interposing a rolling bearing 71, so as to rotate, relative to the cylinder 67 itself and under the thrust of an actuating device 72, around the axis 55.

The device 72 comprises an electric motor 73, which is fixed to the post 54, and is provided with an output shaft 74 having a longitudinal axis 75 that is parallel to the axis 55.

The shaft 74 is coupled to the bell 70 by means of a pair of gears 76, of which one is splined to the shaft 74 and the other is obtained on the outer surface of the bell 70 itself.

The gripping member 69 comprises, furthermore, a support plate 77, which projects downwards from the bell 70, is fixed to the bell 70, and supports a pair of holding jaws 78, which are configured to hold a relative bottle 2 in correspondence to its top neck 4.

The jaws 78 are mounted under the plate 77 and are hinged to the plate 77 so as to rotate, relative to the plate 77 itself, around respective fulcrum axes 79, which are parallel to one another and to the axis 55.

The jaws 78 are moved to a clamping position - and normally kept there - by a spring 80, which is interposed between the jaws 78, and are moved to a release position by the thrust exerted on the jaws 78 themselves by the relative bottle 2 during its insertion into the gripping member 69 or its extraction from the gripping member 69.

The cylinder 67 is provided with a pneumatically

operated piston 81, which is mounted so as to slide inside the cylinder 67, extends around the lower end 68, and defines part of a filling head 82.

The head 82 axially projects downwards from the post 54 and comprises, furthermore, a gasket 83 made of an elastomer material, which has an annular shape coaxial to the axis 55, faces, in use, the top neck 4 of the bottle 2, and is coupled to the piston 81 in an axially fixed manner, so as to be moved by the piston 81 between a lowered operating position, in which the gasket 83 is coupled to the top neck 4 in a fluid-tight manner, and a raised rest position, in which the gasket 83 is arranged at a given distance from the upper neck 4 itself.

The gasket 83, furthermore, is coupled to the piston 81 in a rotary manner by interposing a rolling bearing 84, so as to rotate, relative to the piston 81 itself, around the axis 55 under the thrust of the bottle 2.

To this regard, it should be pointed out that the gasket 83 is angularly integral to a lower rotary race 85 of the bearing 84 and that the race 85 radially extends above the gasket 83 so as to define a rotary ring 86 of a mechanical sliding gasket 87.

The gasket 87 allows the piston 81 and the gasket 83, namely the angularly fixed part and the rotary part of the head 82, to be coupled to one another in a fluid-tight manner and comprises, furthermore, a further ring 88, which is mounted above the ring 86 coaxial to the axis 55.

The ring 88 is fixed to the lower free end of a sleeve 89, which is coupled in an angularly fixed and axially sliding manner to the piston 81, and is kept in contact with the ring 86 by a spring 90, which is interposed between the piston 81 and the sleeve 89 itself.

In correspondence to the transfer stations 8, 10, the position of each gripping member 69 and, hence, of the relative jaws 78 around the relative axis 55 is selectively controlled so as to guarantee a correct pick-up and a correct release of the bottles 2, respectively.

The angular position of each gripping member 69 can be selectively controlled by means of an encoder, which is associated with the relative electric motor 73, or by means of a cam mechanism, which cooperates with the bell 70.

According to an embodiment not shown, the gripping members 69 are removed and replaced by respective lower plates, which are arranged under the relative bottles 2 and are motor-operated so as to rotate around the relative axes 55, and the rotation motion is transmitted to the filling heads 82 by means of the bottles 2 themselves. In this case, when the bottles 2 are made of PET, the bottles 2 are pressurized through the feeding duct 66 so as to have a sufficient stiffness, preferably before being caused to rotate around the relative axes 55.

Obviously, the machine 51 has all the advantages deriving from the rotation of the bottles 2 during their filling, as already described for the machine 1.

CLAIMS

1) A machine for filling containers (2) having respective longitudinal axes (A), said machine (1) comprising:

- 5 - a conveying device (5); and
- at least one handling unit (12; 52) fed by the conveying device (5) along a path (P) and comprising support means (13; 69) for receiving and retaining a relative container (2), and at least one filling device
- 10 (14; 53) for feeding a pourable product into the container (2) as the handling unit (12; 52) travels along said path (P);

 characterized by further comprising actuator means (20; 72) for rotating said container (2) about its

15 longitudinal axis (A) while the container (2) is filled with said pourable product by said filling device (14; 53).

2) The machine as claimed in claim 1, wherein said conveying device (5) comprises a conveyor carousel (6)

20 mounted to rotate about an axis (B) to define said path (P).

3) The machine as claimed in claim 1 o 2, wherein said actuator means (20; 72) comprise a motor (20; 73) carried by said conveying device (5) and having an

25 output shaft (22; 74) coupled to said support means (13; 69) so as to cause the rotation of said container (2) about its longitudinal axis (A).

4) The machine as claimed in any one of the preceding claims, wherein said filling device (14; 53)

30 comprises a filling head (25; 82) for pouring the pourable product into said container (2).

5) The machine as claimed in claim 4, wherein said filling device (14; 53) comprises a hollow supporting element (24; 54) secured to said conveying device (5),

35 and wherein said filling head (25; 82) engages said hollow supporting element (24; 54) in a rotatable manner

about a rotation axis (E; 55) coaxial in use with the longitudinal axis (A) of said container (2).

6) The machine as claimed in claim 5, wherein said filling head (25; 82) engages said hollow supporting element (24; 54) in an axially displaceable manner between a first position, in which the filling head (25; 82) contacts the top (4) of the container (2), and a second position, in which the filling head (25; 82) is spaced from the top (4) of the container (2).

10 7) The machine as claimed in claim 5 or 6, wherein said filling head (82) comprises a slide (81) engaging said hollow supporting element (54) in an axially displaceable manner, a sleeve (89) engaging said slide (81) in a rotatable manner, and a mechanical seal (87) for coupling the slide (81) and the sleeve (89) to each other in a fluid tight-manner.

8) The machine as claimed in claim 7, wherein the mechanical seal (87) comprises a first ring (88) coupled in an angularly fixed manner to the slide (81) and a second ring (86) coupled in an angularly fixed manner to the sleeve (89).

9) The machine as claimed in claim 8, wherein the first ring (88) is further coupled in an axially displaceable manner to the slide (81); the filling head (82) further comprising push means (90) arranged between the slide (81) and the first ring (88) to move, and normally maintain, the first ring (88) into contact with the second ring (86).

10) The machine as claimed in claim 8 or 9, wherein the filling head (82) further comprises at least one bearing (84), which is arranged between the slide (81) and the sleeve (89), and comprises a bearing race (85), which is coupled in an angularly fixed manner to the sleeve (89), and is preferably made in one piece together with the second ring (86).

11) The machine as claimed in any one of the

preceding claims, wherein the support means (69) comprise a lower support plate mounted below the container (2) to rotate about a rotation axis (55) coaxial in use with the longitudinal axis (A) of said container (2).

12) The machine as claimed in claim 11, wherein said filling device (53) further comprises a pneumatic circuit (66) for feeding gas under pressure into said container (2), preferably before rotating the lower support plate about said rotation axis (55).

13) The machine as claimed in anyone of the claims from 1 to 10, wherein the support means (69) comprise gripping means (78) acting upon a top neck (4) of a container (2) to retain it in a suspended position.

14) The machine as claimed in claim 13 when dependent on claim 5, wherein the gripping means (78) are coupled in an angularly fixed manner to the filling head (25; 82) to rotate about said rotation axis (E; 55).

15) The machine as claimed in anyone of the foregoing claims and further comprising control means to selectively control the angular position of the support means (13; 69) about said longitudinal axis (A) at least at a pick-up station (8) of the containers (2) in the handling unit (12; 52) and at a release station (10) of the containers (2) from the handling unit (12; 52).

16) The machine as claimed in anyone of the foregoing claims, wherein the filling device (53) further comprises a swirler (65) to impart a swirling movement to the pourable product fed through the filling device (53).

17) A method for filling containers (2) having respective longitudinal axes (A), said method comprising the following steps:

- advancing at least one handling unit (12; 52) along a path (P);

- feeding at least one container (2) to said handling unit (12; 52) to be retained and advanced along said path (P); and

- filling said container (2) with a pourable product by activating a filling device (14; 53) of said handling unit (12; 52);

wherein said step of filling is performed while the handling unit (12; 52) is advanced along said path (P);

characterized by further comprising the step of rotating said container (2) about its longitudinal axis (A) during said step of filling.

18) The method as claimed in claim 17, wherein the rotation of said container (2) about its longitudinal axis (A) is performed by rotating at least a part (13, 25, 26; 69) of said handling unit (12; 52) about a rotation axis (E; 55) coaxial with said longitudinal axis (A).


19) The method as claimed in claim 18 and further comprising the step of selectively controlling the angular position of said part (13, 25, 26; 69) of said handling unit (12; 52) about said rotation axis (E) at least at a pick-up station (8) of the containers (2) in the handling unit (12; 52) and at a release station (10) of the containers (2) from the handling unit (12; 52).


20) The method as claimed in anyone of the claims from 17 to 19, wherein said path (P) has a circular configuration about an axis (B) parallel to said longitudinal axis (A) of said container (2).

21) The method as claimed in anyone of the claims from 17 to 20, wherein the container (2) is rotated about said longitudinal axis (A) by means of a lower support plate mounted below the container (2) to rotate about a rotation axis (E; 55) coaxial with said longitudinal axis (A), and is filled by means of a filling head (82) mounted to rotate about the rotation axis (E; 55) under the thrust of the container (2); the

method further comprising the step of pressurizing the container (2) before rotating the lower support plate about the rotation axis (E; 55).

22) The method as claimed in anyone of the claims
5 17 to 20, wherein the container (2) is rotated about said longitudinal axis (A) by means of gripping means (78) acting upon a top neck (4) of a container (2) to retain it in a suspended position.










FIG. 3








FIG.6

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2013/076619

A. CLASSIFICATION OF SUBJECT MATTER		
INV. B65C3/16	B65C9/04	B67C3/10 B67C3/24 B67C3/26
ADD.		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols) B65C B67C		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) EPO-Internal, WPI Data		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 414 031 A1 (ALFILL GETRAENKETECHNIK [DE]) 27 February 1991 (1991-02-27)	1-9,11, 12,17, 18,20,21
Y	figures 1-3 column 3, line 44 - column 9, line 28 -----	13,14, 16,22
Y	EP 1 251 074 A2 (SIG ALFA S P A [IT] SIG SIMONAZZI SPA [IT] SIMONAZZI SPA [IT]) 23 October 2002 (2002-10-23) figures 1,2 paragraphs [0024] - [0083] -----	13,14,22
Y	WO 2011/007372 A1 (SIDEL SPA CON SOCIO UNICO [IT]; CONFORTI LUCIO [IT]) 20 January 2011 (2011-01-20) figures 1-7 page 12, line 14 - page 13, line 10 ----- -/-	16
☒ Further documents are listed in the continuation of Box C. ☒ See patent family annex.		
* Special categories of cited documents : "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search 26 February 2014		Date of mailing of the international search report 05/03/2014
Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016		Authorized officer Pardo, Ignacio

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2013/076619

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	FR 2 151 725 A5 (BEDIN JEAN) 20 April 1973 (1973-04-20) figure 1 page 1, paragraph 4 - page 3, paragraph 2 -----	1-5,11, 12, 16-18, 20,21
X	JP 2009 029426 A (SHIBUYA KOGYO CO LTD) 12 February 2009 (2009-02-12) figures 6,7 paragraph [0017] -----	1-4,11, 17,18, 20,21

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2013/076619

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0414031	A1	27-02-1991	CA 2023652 A1 22-02-1991
		DE 3927489 A1 28-02-1991	
		EP 0414031 A1 27-02-1991	
		JP H0398894 A 24-04-1991	
EP 1251074	A2	23-10-2002	AT 316040 T 15-02-2006
		DE 60208736 T2 14-09-2006	
		EP 1251074 A2 23-10-2002	
		ES 2257479 T3 01-08-2006	
		IT MI20010838 A1 21-10-2002	
		PT 1251074 E 30-06-2006	
		US 2002166640 A1 14-11-2002	
WO 2011007372	A1	20-01-2011	EP 2454186 A1 23-05-2012
		WO 2011007372 A1 20-01-2011	
FR 2151725	A5	20-04-1973	DE 2241547 A1 15-03-1973
		ES 183631 Y 01-05-1974	
		FR 2151725 A5 20-04-1973	
		IT 964155 B 21-01-1974	
		NL 7212227 A 13-03-1973	
JP 2009029426	A	12-02-2009	JP 4952408 B2 13-06-2012
		JP 2009029426 A 12-02-2009	