



US 20070048875A1

(19) **United States**(12) **Patent Application Publication****Lappe et al.**(10) **Pub. No.: US 2007/0048875 A1**(43) **Pub. Date: Mar. 1, 2007**(54) **METHOD AND SYSTEM FOR TESTING AND CONTROLLING A CUSTODY OF A FLUID SPECIMEN**

09/444,926, filed on Nov. 24, 1999, now Pat. No. 6,514,461, which is a continuation-in-part of application No. 09/245,175, filed on Feb. 5, 1999, now Pat. No. 6,342,183.

(75) Inventors: **Murray Lappe**, Beverly Hills, CA (US); **David A. Birkner**, Wayland, MA (US); **John W. Goodin**, Coto de Caza, CA (US); **Keith Patten**, Los Angeles, CA (US); **Bill Whitford**, Woodland Hills, CA (US)

Publication Classification

(51) **Int. Cl.**
G01N 21/00 (2006.01)
(52) **U.S. Cl.** **436/164**


Correspondence Address:
HOVEY WILLIAMS LLP
2405 GRAND BLVD., SUITE 400
KANSAS CITY, MO 64108 (US)

(73) Assignee: **eScreen, Inc.**, Overland Park, KS(21) Appl. No.: **11/553,819**(22) Filed: **Oct. 27, 2006****Related U.S. Application Data**

(60) Continuation of application No. 10/954,823, filed on Sep. 30, 2004, which is a division of application No. 10/779,014, filed on Feb. 13, 2004, now Pat. No. 6,964,752, which is a division of application No. 10/072,154, filed on Feb. 6, 2002, now Pat. No. 6,716,393, which is a division of application No.

(57) **ABSTRACT**

A system for automatically testing a fluid specimen, e.g., urine, to indicate the presence of specified chemical components in the specimen. The system preferably utilizes an assaying device comprised of a specimen container having a unique identifier thereon and a cap which carries at least one test strip. A method for testing and controlling a custody of the specimen comprises obtaining a specimen from a donor, wherein the specimen is obtained at a service site; storing the specimen in the specimen container; performing a test on the specimen using a reader device in communication with a computer, wherein the test is performed at the service site; providing an electronic chain of custody form that controls a chain of custody procedure for the specimen; and allowing the donor to sign the electronic chain of custody form at the service site by signing an electronic signature pad.






Fig. 1.




Fig. 2.




Fig. 3.





Fig. 4.






Fig. 6.




Fig. 9A





Fig. 9B.






Fig. 8.




Fig. 10A Fig. 10B




Fig. 10C.




Fig. 10D.




Fig. 10E.




Fig. 10F.

METHOD AND SYSTEM FOR TESTING AND CONTROLLING A CUSTODY OF A FLUID SPECIMEN

RELATED APPLICATIONS

[0001] This application is a continuation of U.S. application Ser. No. 10/954,823, filed Sep. 30, 2004, which is a divisional of U.S. application Ser. No. 10/779,014, filed Feb. 13, 2004, now U.S. Pat. No. 6,964,752, which is divisional of U.S. application Ser. No. 10/072,154, filed Feb. 6, 2002, now U.S. Pat. No. 6,716,393, which is a divisional of U.S. application Ser. No. 09/444,926, filed Nov. 25, 1999, now U.S. Pat. No. 6,514,461, which is a continuation-in-part of U.S. application Ser. No. 09/245,175, filed Feb. 5, 1999 by Murray Lappe, et al, now U.S. Pat. No. 6,342,183. U.S. application Ser. No. 11/063,408, filed Feb. 23, 2005; Ser. No. 08/832,957, filed Apr. 4, 1997, now U.S. Pat. No. 5,929,422; Ser. No. 08/801,041, filed Feb. 14, 1997, now U.S. Pat. No. 5,916,815; Ser. No. 09/018,487, filed Feb. 4, 1998, now U.S. Pat. No. 6,036,092; and Ser. No. 09/025,559, filed Feb. 18, 1998, now U.S. Pat. No. 5,902,982, are also related. The disclosures of the aforementioned applications are herein incorporated by reference.

BACKGROUND OF THE INVENTION

[0002] This invention relates generally to systems for automatically testing fluid specimens, e.g. urine or other body fluids, to detect chemical substances or components therein. Such systems can be used, for example, to screen employee applicants for illegal drug use.

[0003] Employee drug testing typically involves an initial screening test to identify specimens which are negative (i.e., no drugs present). This test is usually performed with a low cost immunoassay which is very sensitive to small quantities of drug metabolites. If a drug metabolite is detected (referred to as "presumptive positive"), the specimen is then subjected to a confirmation test which typically utilizes a highly specific test method, such as a gas chromatography/mass spectrometry (GC/MS), to identify the specific drug components in the specimen.

[0004] Traditionally, both the screening and confirmation tests were performed in a common facility, i.e., centralized laboratory. More recently, systems have been implemented which perform the screening test at a local service site. They typically employ drug test kits which follow the tradition of home pregnancy test kits, i.e., they detect the presence of a specific drug substance(s) in a urine specimen. Such drug test kits generally identify, in human readable form, the drug(s) being tested to indicate the presence (or absence) of that drug. The screening test result with respect to each particular drug, and to the specimen as a whole, can either be (1) negative or (2) presumptively positive. If presumptively positive, then the specimen is generally sent to a remote laboratory for confirmation testing.

[0005] Inasmuch as disclosure of a presumptive positive test result can adversely impact an applicant's record and could potentially lead to litigation and employer liability, it is extremely important to prevent the inadvertent dissemination of test result data.

[0006] The aforementioned parent U.S. Pat. No. 6,342,183 describes an apparatus for locally analyzing a specimen to

qualitatively detect specified chemical components therein. The apparatus includes an assaying device comprised of a cup for collecting a fluid specimen and a cap carrying at least one test strip for visually reacting to one or more specified chemical components in the specimen. The assaying device is preferably configured to interact with a reader device capable of reading the reaction of the test strip to produce an electronic data output.

[0007] More particularly, the apparatus described in application Ser. No. 09/245,175 includes an open cup defining an interior volume for accommodating a fluid specimen and an attachable cap configured for mounting on the cup to seal the interior volume. The cap carries at least one test strip and an integrated aliquot delivery mechanism actuatable to wet the test strip with an aliquot derived from the fluid specimen. The aliquot delivery mechanism preferably comprises a pump in the form of a plunger for forcing an aliquot of the fluid specimen onto the test strip. The plunger can be actuated either manually or automatically, e.g., by a piston controlled by a compatible reader device. The reader device preferably includes a microprocessor based controller for actuating the aliquot delivery mechanism, a camera for producing an image of the test strip, and a processor for analyzing the image to produce test result data. The test result data, along with identification data read from a label carried by the cap, can then be stored or communicated, e.g., via a modem.

SUMMARY OF THE INVENTION

[0008] The present invention is directed to an improved system and components thereof for automatically testing a fluid specimen, e.g. urine, saliva, or other body fluids, to indicate for the presence of specified chemical components in the specimen.

[0009] A system in accordance with the invention preferably utilizes an assaying device comprised of a collection cup and a cap which carries at least one test strip. The device includes an integrated aliquot delivery mechanism actuatable to wet the test strip with an aliquot derived from the fluid specimen. The assaying device is configured to operate in conjunction with an electronic reader device capable of actuating the aliquot delivery mechanism and reading the reaction of the test strip.

[0010] A preferred reader device in accordance with the invention preferably defines a keyed receptacle for accommodating a complementary shaped cup housing in a particular orientation. The reader device is comprised of a camera for capturing the image of a test strip, an actuator for actuating an aliquot delivery mechanism, and a microprocessor/controller for (1) controlling the camera and actuator and (2) processing the image.

[0011] In a preferred embodiment of the invention, the reader device preferably also includes a network connectivity device, e.g. modem, for enabling communication with a remote host computer. Although each reader device can operate independently as a stand-alone device, a preferred system in accordance with the invention employs a host computer or server, which communicates, via a public and/or private network, with a plurality of reader devices located at separate service sites. Each service site can be configured to operate as a "thin client" with primary control being exercised by the host computer via the network.

Alternatively, primary control can be exercised by the reader device at each site with only high level supervisory control coming from the host computer.

[0012] A preferred assaying device in accordance with the invention includes a cap carrying multiple test strips including at least one component test strip and at least one adulteration test strip. The cap is either formed of transparent material or is provided with transparent windows to permit external viewing of the test strips by the reader device camera. The cap preferably also carries one or more fiducial marks to facilitate image processing. Further, the cap preferably also carries machine readable identification information, e.g., a bar code label, to positively associate the specimen and test results with the correct individual. Preferably, the cap does not bear any human readable indicia identifying the specimen donor or indicating test results.

[0013] A preferred test strip for testing for the presence of specific chemical components is configured with multiple latent lines (i.e., markings) which can become visible when the strip is wetted. The lines preferably include a control or reference line and multiple drug lines each related to a different chemical component. If all of the latent lines visually appear within a certain test interval, e.g., up to eight minutes, after the strip has been wetted, this will indicate the absence of the specific chemical components sought. However, if any of those specific chemical components are present in concentrations above a certain threshold, their presence will suppress the appearance of one or more of the drug lines to indicate the presence of such chemical components.

[0014] A preferred reader device in accordance with the invention includes a camera located so that the cap is imaged onto the camera focal plane. The reader device includes a piston motor for driving a piston against the assaying device to deliver an aliquot to the test strips. The piston motor also moves a light shield into place around the cap enabling a light source to illuminate the cap to enhance the image for the camera.

[0015] A preferred automatic testing system in accordance with the invention operates as follows:

- [0016] 1. Fluid deposited into cup at local site; secure cap in tamper evident fashion;
- [0017] 2. Site administrator places assaying device, i.e., cup and cap, into "keyed" receptacle of local reader and enters ID information;
- [0018] 3. Reader alerts host computer via communication network;
- [0019] 4. Initiate automatic reader operational sequence:
 - [0020] a. capture cap image and verify acceptability to proceed
 - [0021] b. run piston motor to advance piston into assaying device to force fluid up channels to wet component and adulteration test strips
 - [0022] c. capture cap image and verify acceptability to proceed
 - [0023] d. periodically capture additional cap images during development interval up to about eight minutes

[0024] e. analyze captured image data to determine

[0025] 1. test validity

[0026] 2. test results

[0027] f. locally display test validity/results and/or communicate test validity/results to Host computer

[0028] g. run piston motor to withdraw piston from cup

[0029] 5. Site administrator removes cup from reader

[0030] The camera produces a digital representation of the image incident on the camera focal plane. The processor then analyzes the digital representation to determine the color of the adulteration test strip and to locate visible markings on the component test strip coincident with the reference and drug lines. Image analysis is preferably performed by initially using fiducial marks on the cap to first precisely locate the cap image relative to a reference image. This can, for example, involve rotating, translating, and/or scaling the cap image. Thereafter, the digital representation of each test strip is examined to determine the presence (or absence) of drug lines. This involves first locating the strip reference line by effectively "drawing" a rectangular region around the reference line. The region can be considered as a rectangular matrix of pixels having rows extending across the strip width, each row being comprised of multiple column positions. For each row, the image is examined to determine whether the pixel at each column position exceeds a threshold. The sum of pixels exceeding the threshold is determined for each row. These row sums produce a graph whose x axis is related to the height (i.e., number of rows) of the region and whose y axis is related to the values of the individual row sums. A bell shaped curve will result whose peak locates the reference line. If no reference line is located, the test is terminated. If the reference line is located, then the examination continues in order to locate the drug lines. The detection of drug lines is more difficult because the amplitude, i.e., dark or light, of its pixels can vary widely dependent on several factors including wetting uniformity, urine color, variations amongst test strips, exposure time, etc. In order to compensate for these variations, each drug region is preferably divided into left, center, and right portions. A drug line is presumed to occupy the center portion of each region. However, its exact position and exact width can vary attributable to the aforementioned factors. Moreover, its brightness difference in relation to neighboring areas can be very subtle. Hence, a procedure is used to determine the weight of a line on a relative basis.

[0031] For example, for each drug region graph, the total area under each of three regions (left, center, right) is calculated. The left and right region areas are then numerically summed, and this resulting total area sum is multiplied by an experimentally determined "weighting value," thus producing a weighted sum. If the area of the center region is less than or equal to the weighted sum, no line is present. By using urine samples with known drug concentrations, a weighting value of 0.75 has been experimentally determined to produce very acceptable results.

BRIEF DESCRIPTION OF THE FIGURES

[0032] FIG. 1 is a block diagram of a system in accordance with the invention;

[0033] FIG. 2 is an isometric view of a preferred reader device in accordance with the present invention;

[0034] FIG. 3 is an isometric view of a preferred cup and cap;

[0035] FIG. 4 is a plan view of the cap top surface;

[0036] FIG. 5 is a front sectional view taken substantially along plane 5-5 of FIG. 2;

[0037] FIG. 6 is a top sectional view taken substantially along plane 6-6 of FIG. 5;

[0038] FIG. 7 is a side sectional view taken substantially along plane 7-7 of FIG. 5 showing the piston in its non-actuated position;

[0039] FIG. 8 is a side sectional view similar to FIG. 7 showing the piston in its actuated depressed position to force an aliquot to the cap for wetting the test strips;

[0040] FIG. 9A is a sectional view taken substantially along the plane 9A-9A of FIG. 5 primarily showing the cup interior;

[0041] FIG. 9B is an enlarged sectional view showing the aliquot delivery mechanism of FIG. 9A in greater detail;

[0042] FIG. 10A is a diagrammatic view of a typical test strip used in embodiments of the present invention;

[0043] FIG. 10B is a diagrammatic view of the test strip similar to FIG. 10A but modified to represent rectangular regions used to locate reference and drug lines;

[0044] FIGS. 10C and 10D depict steps employed in analyzing a cap image to locate a strip reference line; and

[0045] FIG. 10E depicts a step employed in analyzing a cap image to locate the presence of a strip drug line.

DETAILED DESCRIPTION

[0046] Attention is initially directed to FIG. 1 which depicts a preferred system 20 in accordance with the invention comprised of multiple service sites 22 respectively identified as 1 through N. Each service site can operate independently as a stand-alone system to perform a screening test, as will be described hereinafter. However, in accordance with a preferred system configuration, the multiple service sites are connected to a network 24, e.g., the Internet, for communication with a host computer 26.

[0047] Each service site includes a reader device 28 configured to cooperate with an assaying device 30 comprised of a specimen collection cup 32 and a cap 34. FIG. 1 depicts a functional block diagram of the reader 28 whereas FIGS. 2 and 4-7 illustrate the reader's structural configuration. The structural configuration of the assaying device 30 is illustrated in FIGS. 2-9.

[0048] Briefly, the reader 28 is comprised of a processor/controller 36 programmed to operate (1) a camera 37 and light source 38 via a camera interface circuit 40 and (2) a piston motor 42 via a motor control circuit 44. As will be discussed hereinafter, the piston motor 42 operates to deliver an aliquot from a specimen in the cup 32 to one or more test strips in the cap 34. The test strips each produce a visible reaction in response to being wetted by the aliquot. The camera 37 and light source 38 operate together to capture an image of the test strip(s) enabling the processor/controller 36

to process the image to determine test validity and whether the specimen is free of chemical components being monitored. The reader 28 preferably operates in conjunction with an input/output device 46 which enables a site attendant to enter information, e.g., donor identification information, via a device such as a touch pad or keyboard, and to view information, e.g. via an LCD display, provided by the processor/controller 36.

[0049] The processor/controller 36 is also preferably connected to the network 24 via a suitable connectivity device 48, e.g., a modem. This enables the reader to upload data, e.g., test results, billing information, etc. to the host computer 26. It also allows the host computer to exercise supervisory control over the processor/controller 36.

[0050] Attention is now directed to FIG. 2 which illustrates the exterior configuration of the reader housing 60. The housing is essentially comprised of a base portion 62, a head portion 64, and an enclosure portion 66, bridging the base and head portions. A receptacle 68 is defined between the base and head portions for receiving an assaying device 30 above a keyed recess 70 formed on base platform 72. The keyed recess 70 is shaped complementary to the lower periphery of the assaying device 30 to place the device in a specific orientation relative to head portion 64. The assaying device 30 is comprised of an open collection cup 32 and a detachable cap 34. The cup 32 defines an interior volume for collecting a fluid specimen, e.g. urine. After the fluid specimen has been deposited into the cup 32, the cap 34 is mounted thereon to seal the interior volume and prevent the fluid specimen from leaking. Inasmuch as each assaying device 30 is intended to be used only once to collect a single specimen, it is preferably fabricated via relatively low cost plastic molding processes.

[0051] It can be noted in FIG. 3 that the cup 32 has an irregular lower periphery 76 particularly configured to mate with the keyed recess 70. The periphery 76 includes an enlarged front portion 78 and a reduced rear portion 80. The reduced rear portion 80 is bounded by fiat finger grip sides 82 having raised surface features 84 extending to an oblique wall surface 86. This irregular configuration of the cup facilitates easy manual handling of the cup enabling it to be readily grasped by the hand of a user and/or administrator. The cup enlarged portion 78 preferably includes an area 88 characterized by multiple vertical fins 90. This area 88 functions as a key or registration area to which an index area 92 on the cap 34 is aligned to assure proper cap/cup sealing. Markings are preferably provided on the cup exterior to indicate maximum and minimum fill levels.

[0052] Briefly, the cap 34 is comprised of a substantially circular member 94 having a top exterior surface 96 and a depending flange or skirt 98. The skirt 98 has a primarily knurled outer surface 100 that preferably defines flat areas 102 and the aforementioned index area 92. The index area 92, which may be defined by vertical slots, is preferably used to align with the aforementioned cup area 88 to visually indicate to a user that the cap has been properly installed onto the cup. The cap 34 is preferably installed onto the cup via a mating thread 104. The cap 34 preferably carries a stop tooth 107 which rotates into engagement with the end fin 90 when the cap is properly installed onto the cup. When properly installed, the cap index area 92 will be aligned with

the cup registration area **88**. Alternative mounting mechanisms, e.g., bayonet mount, can be used to couple the cap **34** to the cup **32**.

[0053] Provision is preferably made to include a tamper evident seal to immediately indicate to a user whether an assaying device, once sealed, has been tampered with. More particularly, note in FIG. 3 that the cap top surface **96** carries a label **106** having a first portion **108** permanently adhered to the surface **96**. A second label portion **110** extends beyond the edge of cap **34** and is intended for sealing against cup area **111** immediately beneath the cup finned area **88**. The label portion **110** carries a suitable adhesive on its under-surface which, prior to use, is protected by release paper **112**. When the release paper is stripped away, label portion **110** can be sealed against cup area **111** to assure that cap **34** cannot be removed from cup **32** without that fact being immediately evident. The label **106** preferably also includes a perforated tear-off third portion **113** which can be affixed to a "B" container in case of split specimen collections, or in the event that a manual chain of custody record is required.

[0054] The cap top surface **96** (FIG. 4) is either transparent or at least defines one or more transparent areas **114**, e.g., windows **114A**, **114B**, and **114C** for enabling a test strip mounted beneath each window to be visible therethrough. As will be discussed hereinafter, the cap defines one or more compartments each of which accommodates a test strip **115** which, when wetted by a fluid specimen, reacts to provide a visual indication indicative of a characteristic of the specimen.

[0055] In the exemplary embodiment illustrated, the window **114C** covers a test strip intended to detect specimen (1) authenticity and (2) adulteration. As is well known, a freshly voided urine specimen can be authenticated by a test strip which senses various characteristics including temperature and/or creatinine content of the specimen. Adulteration of the specimen can be detected by a test strip sensitive to exogenous components, e.g. pH and/or nitrites. Preferably, the test strip changes color when wetted and detection is achieved using a colorimetric technique. Larger windows **114A** and **114B** are intended to reveal test strips **115** for detecting various specific chemical components typically associated with illegal substance abuse. FIG. 10A schematically represents such a component test strip **116** showing multiple latent lines **117** visually represented on an indicator portion **118** extending from an absorbent portion **119**. The latent lines **117** typically include one or more reference or control lines **117R** and multiple drug lines **117D₁**, **117D₂**, etc., each for a different drug or chemical component to be detected. If all of the lines visually appear within a certain test interval, e.g., up to eight minutes, after the absorbent portion **119** has been wetted, this will indicate the absence of the specific chemical components sought (i.e., a "negative" test). However, if any one of those specific chemical components is present in concentration above a certain threshold, its presence will suppress the appearance of one or more of the lines to indicate to an astute observer and/or computer based reader, the presence of that component.

[0056] The cap top surface **96** (FIG. 4) preferably additionally defines a primary bar code area **120**, a secondary bar code area **121**, and one or more fiducial marks **122**, to be discussed hereinafter. All of the windows **114**, bar code

areas, and fiducial marks are arranged around a plunger hole **124** within a tightly dimensioned image field **125** suitable for being imaged onto the focal plane of camera **37**. In an exemplary embodiment, the image field has width and height dimensions respectively equal to **1446** mils and **1084** mils which is imaged onto a camera view field having **640** pixels horizontally and **480** pixels vertically.

[0057] The internal structure and operation of a suitable assaying device **30** is described in aforementioned parent U.S. Pat. No. 6,342,183, whose disclosure is, by reference, incorporated herein. Briefly, as depicted in FIGS. 5-9, the assaying device cap **34** defines descending concentric outer and inner tubular walls **126** and **127**. Multiple passageways **128A**, **128B**, **128C**, **128D** extend vertically between the outer and inner tubular walls **126** and **127**. Each passageway **128** defines a passageway inlet **129** at the lower end of inner tubular wall **127** and a passageway outlet **130** proximate to compartments **131**, respectively accommodating component or adulteration test strips **132**, located beneath the aforementioned windows **114**. Overflow Basins **136**, **138** are respectively located adjacent to the compartments beneath windows **114A**, **114B** to collect any fluid overflow.

[0058] The inner floor **150** of the cup **32** is configured to define an open well **152**. When the cap **34** is installed on the cup **32**, the lower end of the outer tubular wall **126** extends into the well **152** and essentially forms a closed chamber **154** for isolating a portion of the fluid specimen. A plunger **160**, comprised of a plunger pin **162** and plunger element **164**, is mounted in inner tubular wall **127** above chamber **154**. The plunger element **164**, is formed of soft conforming material able to seal against the inner surface of inner tubular wall **127**. The opening **124** in the cap top surface **96** provides access to enable the pin **162** to be depressed.

[0059] As the plunger element **164** is depressed into chamber **154**, the fluid therein is displaced upwardly via inlet **129** through multiple passageways **128**. These passageways, **128A**, **128B**, **128C**, **128D** respectively extend to the aforementioned test strip compartments located below the aforementioned cap windows **114**. Thus, depression of the plunger **160** within the inner tubular wall **127** displaces fluid from the chamber **154** to deliver an aliquot to each of the compartments **131**, each compartment accommodating a separate strip **115** of test material. The device **30** is constructed and dimensioned so that each aliquot comprises a specific volume of fluid.

[0060] Attention is now directed to FIGS. 5-8 which illustrate the internal structure of the reader housing **60**. The housing **60** is formed by a base plate **150** having a vertical frame member **152** secured thereto. The base plate **151** is weighted by block **154** for stability. A shell **160** is affixed to the base plate **150** and frame member **152**. The shell includes a base platform member **72** which defines the aforementioned keyed recess **70**. The shell **160** additionally includes a rear shell member **162** which encloses a rear compartment **164** housing the reader electronic circuit board(s) **166**. An upper shell member **170** encloses a top compartment **172** which houses the camera **37**, light source **38** and piston motor **42**. These devices are structurally supported on arm **176** projecting forwardly from frame member **152**.

[0061] A piston subassembly **180** is mounted for vertical reciprocal motion toward and away from base plate **150**. The piston subassembly is comprised of a support arm **182**

projecting forwardly from slide block **184** mounted for linear movement along guide rails **186**. The support arm **182** carries a piston member **186** aligned with opening **124** in the cap of an assaying device **30** placed in the keyed recess **70**. A lead screw **188** is threaded into hole **190** in support arm **182**. The lead screw can be selectively rotated either clockwise or counterclockwise by piston motor **42** to move the slide block **184** either up or down. FIG. 7 depicts the piston member **186** in its up position providing sufficient clearance to allow an assaying device **30** to be placed on or removed from the keyed recess **70**. FIG. 8 shows the piston member **186** in its down position extending into cap opening **124** to depress plunger **160** to displace fluid from the specimen in cup **32** to wet the test strips **115**.

[0062] It should also be noted that the piston subassembly **180** includes a substantially cylindrical light shield **192** mounted on slide block **184**. The light shield **192** defines a lower edge **194** which seals against the cap top surface **96** when the slide block is in its down position shown in FIG. 8.

[0063] The camera **37** can comprise a commercially available digital camera and appropriate optics for imaging the field **125** (FIG. 4) onto the camera's focal plane. The camera preferably has a resolution of 640 (horizontal).times.480 (vertical) pixels. Imaging is enhanced by selective illumination of light sources **38** and by the shielding effect afforded by light shield **192**.

[0064] A preferred operational sequence for automatically testing a fluid specimen is represented by the following sequential steps:

[0065] 1. Donor at a local site deposits fluid into cup **32**; site administrator enters identification information and secures cap **34** in tamper evident fashion;

[0066] 2. Administrator places cup/cap into "keyed" receptacle **70** of local reader **28** and enters ID information;

[0067] 3. Reader **28** alerts host computer **26** via communication network **24**;

[0068] 4. Host computer **26** (or administrator) initiates reader operational sequence:

[0069] a. camera **37** captures cap image and processor **36** verifies acceptability to proceed

[0070] b. processor **36** runs piston motor **42** to advance piston **164** into cup to force fluid up channels **128** to wet component and adulteration test strips

[0071] c. camera captures additional cap image and verify acceptability to proceed

[0072] d. periodically capture additional cap images during development interval up to about eight minutes

[0073] e. processor analyzes captured image data to determine

[0074] 1. test validity

[0075] 2. test results

[0076] f. processor **36** displays test validity/results on local I/O **46** and/or communicates test validity/results to Host computer **26**

[0077] g. processor **36** runs piston motor to withdraw piston from cup

[0078] 5. Site administrator removes cup from reader

[0079] In step 1, the site administrator first enters donor and client (e.g., employer) information via I/O devices **46** into a database stored either in processor **36** or host computer **26**. The donor voids into a cup **32** and the cap **34** is sealed thereon. The label is extended from the cap to the Cup to assure that it is sealed in tamper evident fashion. Preferably the administrator and donor then initial the sealed label and review the chain of custody document. The donor and administrator both apply their signatures to the signature pad and a copy of the chain of custody document is printed and given to the donor. The donor is then dismissed. Preferably the cup/cap is then placed in the reader.

[0080] Step 4 of the foregoing sequence is automatically executed under the control of programmed microprocessor **36**. In step 4a, the piston has not yet been inserted into the cup and may partially obscure the field of view. In addition, since the piston is not down, the light shield is only partially effective, and extraneous light may enter, further obscuring details. Nevertheless, an initial image is captured by the camera to examine the primary barcode **120** and other cap features to determine if it is valid. If the barcode is not valid, this fact is displayed to the site administrator for further action. An invalid barcode can indicate that the cup is inserted incorrectly, that there is no cup there at all, or that a "fake" cup has been inserted. If the administrator cannot resolve the issue and the barcode is indeed invalid, testing is aborted and the sealed cup is sent for laboratory analysis.

[0081] In step 4b, processor **36** runs the piston motor **42** to lower the piston **164** a predetermined distance. This also lowers the light shield **192** into place against the cap top surface **96** so that the light source **38** is then the only source of light illuminating the cap top. The light source **38** preferably comprises multiple green LED's inasmuch as the lines that appear on typical component test strips exhibit the highest contrast when viewed in green light. With the piston in its down position, it no longer obscures any cap features within the image field **125**.

[0082] In step 4c, another image of the cap is captured and processed to double-check the primary barcode results from the previous step and to read the secondary barcode **121** and the fiducial marks **122**. The fiducial marks **122** are small features printed on the cap directly above the test strip windows **114A**, **114B** and serve as reference points for subsequent processing steps to assure accurate image analysis. Preferably, the barcode labels have their own fiducial marks, which allow the barcodes to be found and read even if the label is askew. If all barcodes and fiducial marks can be located and properly read, then operation proceeds to step 4d. Otherwise, the site administrator is alerted and he/she decides whether to proceed or not.

[0083] The test strips take between two and eight minutes to develop. During step 4d, images are periodically captured and during step 4e, the images are processed and analyzed. Steps 4d and 4e are executed in an iterative loop. If all latent lines become visible after two minutes, the test is concluded

and operation proceeds to step 4f. Otherwise steps 4d and 4e are executed every minute until eight minutes have elapsed. If any of the drug or control lines do not become visible, the assaying device is sent to the lab for further analysis.

[0084] The image analysis executed in step 4e includes an extensive procedure to be discussed hereinafter for discerning a color change on the adulteration test strip and visible reference and drug lines on the component test strip. The detection of these lines can be reasonably challenging because the amplitude, i.e., dark or light, of its pixels can vary widely dependent on several factors including variations in test strips, in wetting, in urine color, etc. In order to produce an optimum image for analysis, a sequence (e.g., 8) of images is actually captured. These multiple images are then mathematically summed divided by the number of images in order to produce an integrated image in which the random electrical and optical “noise” has been reduced by this “averaging” process. This integrated image is then used in the subsequent line detection procedure:

[0085] 4e(1) The fiducial marks **122**, which had been found to exist in step 4c, are now located precisely by looking in a restricted region (as a consequence of the cup being physically positioned by keyed recess **70**) and finding the centroid of the individual fiducial marks. This determines their exact locations within the camera field of view (i.e., 640×480).

[0086] 4e(2) Based on the locations of the fiducial marks, the image is now rotated, translated, minified, and or magnified as necessary so that the resulting image has the fiducial marks **122** (and hence all other cap features) in “standard” positions which is hence presumed for all subsequent operations.

[0087] 4e(3) Using a “map” of the features present on the cap top, each test is individually examined. Although the two test strips can in fact differ in the number of lines present and their specific locations, for the sake of simplicity, the operations on only one typical test strip will be described.

[0088] 4e(4) Based on known default reference and drug line positions, non-overlapping rectangular regions **200** are “drawn” around each reference line **117R** and drug line, e.g., **117D** (FIG. **10B**).

[0089] 4e(5) For the region **200** which contains the reference line **117R**, row sums are produced.

[0090] The number of pixels summed for each row is the “width” of the test strip (e.g., **32** in FIG. **10C**), the number of total row sums for each region is the “height” of the individual region (e.g., **48** in FIG. **10C**). Each of these row sums produces a graph (FIG. **10D**) whose X axis is related to the “height” of the region, and whose Y axis is related to the values of individual row sums. Let it be assumed that individual row sums will be smaller for darker horizontal rows and larger for lighter horizontal rows. The resulting graphs are then preferably normalized so that the Y axis values are between 0 and 100, and then subtracted from 100 so that the darkest row in a given region has the value 100 and the brightest row in a given region has the value 0. Bell shaped curves will result (presuming a drug or control line is present) as depicted in FIG. **10D**.

[0091] 4e(6) The reference line **117R** must be located in order to proceed further and its exact position must be

determined in order to locate the best estimated positions of the drug lines for further processing. The graph for the reference line is examined for a maximum value, which represents the reference line center position. After the center position is located, the regions drawn in substep 4e(4) above are redrawn to center the reference line and drug lines in their respective regions.

[0092] 4e(7) For each drug region, row sums and the resulting graph are produced as described in substep 4e(5) above.

[0093] 4e(8) Each drug region graph is divided into three equal parts, a left, center, and right part as represented in FIG. **10F**. The drug line is presumed to occupy the center portion. However, its exact position and width can vary, and its brightness difference in relation to the neighboring area may be very subtle. Based on different wetting conditions, a dark condition in one region can in fact be lighter than a not-dark condition in another region. Hence, a relative mechanism is used to determine the presence or absence of a drug line.

[0094] 4e(9) For each drug region graph, the total area under each of the three regions (left, center, right) is calculated. The left and right region areas are then numerically summed, and this resulting total area sum is multiplied by an experimentally determined “weighting value”, thus producing a weighted sum. If the area of the center region is greater than this weighted sum, a decision is made that a line is present. If the area of the center region is less than or equal to the weighted sum, a decision is made that no line is present. By using urine samples with known drug concentrations, a weighting value of 0.75 has been found to produce very acceptable results. In order to conceptually understand what is going on, presume that the graph is perfectly symmetric and the drug line is centered in the graph, hence the graph will appear as a bell curve (FIG. **10F**) (this is typical of the actual graphs produced) if a line is present, or at the other extreme, will appear as a flat line if no drug line is present. In the case of a flat line, then the summed areas of the left and right region will be exactly twice ($2 \times X$) the area of the center region (X). If the $2 \times X$ value is weighted by 0.75, the resulting area is now $1.5 \times X$, which is greater than X . Hence no drug line is considered present. In fact, the weighting value would have to be less than 0.5 for a line to be considered present. As the center region grows in amplitude, its area reaches a point that it is now greater than the weighted sum of the left and right regions, and a line is considered present. Note that the presence or absence of a line is not determined by the exact position or shape of this curve, nor by the exact amplitudes of the dark and light components, which can vary widely based on various factors including the degree of wetting, the color of the urine, the particular lot of test strips, the time of exposure, extraneous material on the test strip, and shadows and/or reflections. All of these variations are compensated for in the relatively simple and concise mathematical procedure described which allows the presence or absence of drug lines to be repeatedly determined to a controllable, high degree of accuracy.

[0095] Once all adulteration test strips have been examined for color and all component test strips examined for visible lines, a final test result, for adulteration and identification of drug lines present and/or absent, is locally displayed and/or communicated to the host computer in accordance with aforementioned step 4f.

[0096] The foregoing describes applicants' preferred system for automatically testing fluid specimens to detect specific chemical components therein. The preferred system includes an assaying device comprised of a fluid collection cup and a cap carrying one or more test strips configured to produce visually discernable indications of the components of the specimen and/or specimen adulteration. The visual indications are read by an imager, e.g., digital camera, and interpreted by a processor which executes an analysis procedure to interpret the visual indications. The resulting test results are reported locally or via a communications network to a host computer. Thus, systems in accordance with the invention can quickly (e.g., in less than 15 minutes) and locally automatically test a fluid specimen to provide accurate qualitative test results. The system both assures the confidentiality of donor/specimen test results (by using machine readable, rather than human readable, markings) and a closely controlled chain of custody procedure.

[0097] Although a preferred embodiment has been described, it is understood that many modifications and variations will occur to those skilled in the art which fall within the intended scope of the invention as defined by the appended claims.

What is claimed is:

1. A method of testing a specimen comprising:
 - obtaining a specimen from a donor;
 - storing the specimen in a specimen container;
 - performing a test on the specimen;
 - providing an electronic chain of custody form that controls a chain of custody procedure for the specimen; and
 - allowing the donor to sign the electronic chain of custody form by signing an electronic signature pad.
2. The method as claimed in claim 1, wherein the specimen is obtained at a service site.
3. The method as claimed in claim 2, wherein the test is performed on the specimen at the service site.
4. The method as claimed in claim 3, wherein the test is performed using a reader device.
5. A method of testing a specimen comprising:
 - obtaining a specimen from a donor, wherein the specimen is obtained at a service site;
 - storing the specimen in a specimen container;
 - performing a test on the specimen using a reader device in communication with a computer, wherein the test is performed at the service site;
 - providing an electronic chain of custody form that controls a chain of custody procedure for the specimen; and
 - allowing the donor to sign the electronic chain of custody form at the service site by signing an electronic signature pad.

6. The method as claimed in claim 5, wherein the reader device is in communication with an input/output device that enables entering of information.

7. The method as claimed in claim 6, wherein the input/output device is in communication with the computer.

8. The method as claimed in claim 6, further comprising the step of entering donor information into the input/output device.

9. The method as claimed in claim 5, wherein the specimen is identified by a unique identifier.

10. The method as claimed in claim 9, further comprising the step of validating the unique identifier.

11. A method comprising:

obtaining a specimen from a donor;

storing the specimen in a specimen container on which is located a unique identifier for positively associating the specimen with the donor;

performing a test on the specimen using a reader device in communication with a computer;

uploading a test result obtained with the reader device to the computer;

providing an electronic chain of custody form that controls a chain of custody procedure for the specimen; and

having the donor sign the electronic chain of custody form by signing an electronic signature pad, such that by signing the chain of custody form, a closely controlled chain of custody procedure is administered.

12. The method as claimed in claim 11, wherein the computer is a host computer, and the reader device is in communication with the host computer via a communications network.

13. The method as claimed in claim 12, wherein the test result is uploaded to the host computer via the communications network.

14. The method as claimed in claim 12, wherein the reader device is in communication with an input/output device that enables entering of information and subsequent uploading of the information to the host computer.

15. The method as claimed in claim 11, further comprising the step of entering donor information into the input/output device.

16. The method as claimed in claim 11, further comprising the step of printing a copy of the electronic chain of custody form.

17. The method as claimed in claim 12, further comprising the step of uploading the donor information to the host computer.

18. The method as claimed in claim 11, wherein the reader device is an on-site device operable to perform the test at a service site.

19. The method as claimed in claim 11, further comprising the step of validating the unique identifier.

20. A method of testing a specimen comprising:

obtaining a specimen from a donor;

storing the specimen in a specimen container having a unique identifier associated with it;

inputting the unique identifier into a computer;

performing a test on the specimen;

providing an electronic chain of custody form that controls a chain of custody procedure for the specimen; and

allowing the donor to sign the electronic chain of custody form by signing an electronic signature pad.

21. The method as claimed in claim 20, wherein the specimen is obtained at a service site.

22. The method as claimed in claim 21, wherein the test is performed on the specimen at the service site.

23. The method as claimed in claim 22, wherein the test is performed using a reader device.

24. The method as claimed in claim 23, wherein the reader device reads the unique identifier associated with the specimen container.

* * * * *