

(51) International Patent Classification:

B67D 1/00 (2006.01) B67D 1/08 (2006.01)
B67D 1/06 (2006.01)

(21) International Application Number:

PCT/US2012/036129

(22) International Filing Date:

2 May 2012 (02.05.2012)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

13/116,266 26 May 2011 (26.05.2011) US

(71) Applicant (for all designated States except US): PEP-SICO, INC [US/US]; 700 Anderson Hill Road, Purchase, NY 10577 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): JERSEY, Steven, T. [US/US]; 28805 Aloma Avenue, Laguna Niguel, CA 92677 (US). SEGIET, William, W. [US/US]; 5 Rita Drive, Bethel, CT 06801 (US). SIEGEL, Tom [US/US]; 700 Anderson Hill Road, Purchase, NY (US). KALI, Eddie [US/US]; 700 Anderson Hill Road, Marietta, GA (US). BOGGS, Joseph [US/US]; 28805 Aloma Avenue, Newton, CT (US). BALSTAD, Robert [US/US]; 28805 Aloma Avenue, New Millford, CT (US).

(74) Agent: ROKOS, Rebecca, P.; Banner & Witcoff, Ltd., 10 South Wacker Drive, Suite 3000, Chicago, IL 60606-7407 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))

[Continued on next page]

(54) Title: MULTI -TOWER MODULAR BEVERAGE DISPENSING SYTEM




FIG. 3

(57) Abstract: The disclosure concerns a beverage dispensing system (10) including a multi-tower modular dispensing system comprising at least a first dispensing head (12) and a second dispensing head (912A) at a counter (14), a transfer unit (16) located remotely from the counter, piping (18) extending from the transfer unit to the counter, the transfer unit comprising a centralized ingredient system (20) having a plurality of beverage ingredient sources (22), the centralized ingredient system configured to supply beverage ingredients to the piping for the dispensing of a first beverage at the counter, the piping comprising a main micro bundle (18A), the main micro bundle comprising at least two separate beverage ingredient lines (324, 326).



-
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) — before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

Published:

- with international search report (Art. 21(3))

MULTI -TOWER MODULAR BEVERAGE DISPENSING SYTEM

CROSS-REFERENCE TO RELATED APPLICATION

[01] The present application claims priority to U.S. Application No. 13/116,266, filed May 26, 2011, and entitled “Multi-Tower Modular Dispensing System,” the entire disclosure of which is hereby incorporated by reference in its entirety.

FIELD OF THE INVENTION

[02] This disclosure relates generally to a method and modular beverage dispensing system for the dispensing of beverages, e.g., for restaurants (including fast food restaurants), theatres, convenience stores, gas stations, and other entertainment and/or food service venues.

BACKGROUND

[03] Various beverage dispensers, such as those at restaurants, theatres and other entertainment and/or food service venues, typically have either a “drop in” dispenser apparatus or a counter top type dispenser apparatus. In a drop in dispenser apparatus, the dispenser apparatus is self-contained and may be dropped into an aperture of a counter top. In a counter top type dispenser apparatus, the dispenser apparatus is placed on a counter top. In conventional beverage dispensers, a dispensing head is coupled to a particular drink syrup supply source via a single pipe dedicated to supply the particular drink syrup to that dispensing head, wherein the particular drink syrup supply source is typically located near the counter top, i.e., directly under the counter top, or directly over the counter top.

[04] A user will typically place a cup under the signage of the selected beverage and either press a button or press the cup against a dispensing lever to activate the dispenser so that the selected beverage is delivered from the dispensing head corresponding to the selected beverage and into the cup until pressure is withdrawn from the button or lever.

- [05] Conventional beverage dispensers are typically limited to dispensing drinks having flavoring supply sources located at their respective counters. Thus, a limited number of drinks are typically available at a conventional beverage dispenser. For example, drinks typically available at a conventional beverage dispenser are a regular cola beverage, a diet cola beverage, perhaps one or several non-cola carbonated beverages, such as a lemon-lime flavored carbonated beverage or some other fruit-flavored drink (e.g., orange flavored carbonated beverage, and/or root beer), and perhaps one more non-carbonated beverage(s), such as a tea and/or a lemonade.
- [06] Conventional dispensers are not typically configured to permit a user generate or receive from a single dispensing head a custom-ordered beverage that a consumer may wish to purchase, e.g., a cola flavored with cherry, vanilla, lemon, or lime, etc., or a tea flavored with lemon, orange, peach, raspberry, etc., or a tea having one or more teaspoons of sweetener (sugar, or some other nutritive sweetener or non-nutritive sweetener).
- [07] Conventional dispensers typically require servicing and resupply of flavoring sources at the counter.
- [08] Conventional dispensers typically require a dedicated dispensing head for each particular beverage.
- [09] What is needed is a beverage dispensing system that does not have the limitations and disadvantages of conventional beverage dispensers and methods.

SUMMARY

- [10] Accordingly, there is provided a multi-tower modular dispensing system.
- [11] In one aspect, a multi-tower dispensing system may comprise at least a first dispensing head and a second dispensing head at a counter, a transfer unit located remotely from the counter, and piping extending from the transfer unit to the counter. The transfer unit may comprise a centralized ingredient system having a plurality of beverage ingredient sources. The centralized ingredient system may be configured to supply beverage ingredients to the piping for the dispensing of a first beverage at the counter. The piping

may comprise a main micro bundle, the main micro bundle comprising at least two separate beverage ingredient lines.

- [12] In one aspect, a multi-tower modular dispensing system may comprise at least a first dispensing head at a first counter, at least a second dispensing head at a second counter, the first and second counters remote from each other, a transfer unit located remotely from the first counter and the second counter, and piping extending from the transfer unit to the first counter and the second counter. The transfer unit may comprise a centralized ingredient system having a plurality of beverage ingredient sources. The centralized ingredient system may be configured to supply beverage ingredients to the piping for the dispensing of a first beverage at the first counter and for the dispensing of a second beverage at the second counter. The piping may comprise a main micro bundle, the main micro bundle comprising at least two separate beverage ingredient lines.
- [13] In one aspect, a multi-tower modular dispensing system may comprise a plurality of dispensing heads at a first counter, a plurality of dispensing heads at a second counter, the first and second counters remote from each other, a transfer unit located remotely from the first counter and the second counter, and piping extending from the transfer unit to the first counter and the second counter. The transfer unit may comprise a centralized ingredient system having a plurality of beverage ingredient sources, the centralized ingredient system configured to supply beverage ingredients to the piping for the dispensing of a plurality of beverages at the first counter and for the dispensing of a plurality of beverages at the second counter, the piping comprising at least one main micro bundle, the main micro bundle comprising a plurality of separate beverage ingredient lines.
- [14] The above and other aspects, features and advantages of the present disclosure will be apparent from the following detailed description of the illustrated embodiments thereof which are to be read in connection with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

- [15] FIG. 1 is schematic view of an embodiment of a modular dispensing system according to various aspects of the disclosure.
- [16] FIG. 2 illustrates an embodiment of a central linked ingredient system according to various aspects of the disclosure.
- [17] FIG. 3 illustrates is a perspective of an embodiment of a main micro bundle according to various aspects of the disclosure.
- [18] FIG. 4 illustrates an embodiment of a doser unit according to various aspects of the disclosure.
- [19] FIG. 5 illustrates an embodiment of a tower micro bundle according to various aspects of the disclosure.
- [20] FIG. 6 illustrates an alternative embodiment of a modular dispensing system according to various aspects of the disclosure.
- [21] FIG. 7 illustrates an embodiment of centralized ingredient system according to various aspects of the disclosure.
- [22] FIGs. 8A and 8B illustrate an embodiment of a cartridge for a beverage ingredient according to various aspects of the disclosure.
- [23] FIG. 9 illustrates the embodiment of FIG. 1, with the addition of additional dispensing heads at a single counter according to various aspects of the disclosure.
- [24] FIG. 10 illustrates the embodiment of FIG. 1, with the addition of an additional counter having an additional dispensing head according to various aspects of the disclosure.
- [25] FIG. 11 illustrates the embodiment of FIG 10, with the addition of additional dispensing heads at each counter according to various aspects of the disclosure.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

- [26] The embodiments discussed below may be used to form a wide variety of beverages, including but not limited to cold and hot beverages, and including but not limited to beverages known under any PepsiCo branded name, such as Pepsi-Cola®.
- [27] Referring to FIG. 1, the description of one embodiment of the modular dispensing system of the present disclosure will be described.
- [28] Referring to FIG. 1, a modular dispensing system 10 may be provided comprising a plurality of dispensing heads 12 at a counter location 14, and a transfer unit 16 located remotely from the counter location 14. Piping 18 may extend from the transfer unit 16 to the counter location 14.
- [29] Referring to FIG. 1 and FIG. 2, the transfer unit 16 may comprise a centralized ingredient system 20 having a plurality of sources 22 of beverage ingredients 24, 26, 28, 30, 32, 34, 36, 38, 40, 42, 44, 46, 48, 50, 52, 54, 56, 58, 60, 62, 64, 66, 68, 70, 72, 74, 76, 78, 80, 82, 84, 86, 88, 90, 92, and 94. FIGs. 1 and 2 show that beverage ingredient 94 may be placed next to beverage ingredient 92, and beverage ingredient 94 may flow into an opening 96 of pipe 98. As described in greater detail below, pipe 98 may be one of the pipes that comprise piping 18. The centralized ingredient system 20 may supply beverage ingredients 24 through 94 to a dispensing head 12 for more than one beverage. FIG. 9 illustrates the embodiment of FIG. 1, with the addition of additional dispensing heads 912A and 912B at a single counter 14. FIG. 10 illustrates the embodiment of FIG. 1, with the addition of an additional counter 114 having an additional dispensing head 1012A, and an additional counter 214 having an additional dispensing head 1024A. At least one of the dispensing heads may be a dispensing head for a drive-through pick up window. While the counters in FIG. 10 depicts the counters in series, those of skill in the art will recognize that the counters may also be configured in parallel, e.g., with a separate micro bundle leaving transfer unit 16 for each counter. FIG. 11 illustrates a variation of embodiments shown in FIG. 9 and FIG. 10, showing dispensing heads 12, 912A, and 912B at counter 14 (which may be supplied with beverage ingredients via main micro bundle 18), dispensing heads 1012A, 1012B and 1012C at counter 114

(which may be supplied with beverage ingredients via main micro bundle 18A), and dispensing heads 1024A, 1024B and 1024 at counter 214 (which may be supplied with beverage ingredients via main micro bundle 18B). While the counters in FIG. 11 depicts the counters in parallel, those of skill in the art will recognize that the counters may also be configured in series, e.g., with a single main micro bundle 18 leaving transfer unit 16 and supplying beverage ingredients to each counter 14, 114, and 124 in series. At least one counter may have a dispensing head dedicated supplying beverages for a drive through window. Those of skill in the art will recognize that the system may have the same or different beverage ingredients supplied to different dispensing heads located at different dispensing towers 13, 913, 915, 1013, 1015, 1017, 1113, 1115, and 1117.

- [30] Centralized ingredient system 20 may supply beverage ingredients 24 through 94 for a greater number of beverages than the number of dispensing heads 12 that are located at one counter location 14. As shown in FIG. 10, the centralized ingredient system 20 may supply beverages to dispensing heads located at counter locations 14, 114, 214 that are remote from one another, including but not limited to a counter location 214 for a drive-through window. The centralized ingredient system 20 may be placed at a remote location 100 from counter locations 14, 114, 214, e.g., a back room 102, which preferably is not viewable from at least one counter location. In a preferred embodiment, the centralized ingredient system is not viewable by patrons or customers using a dispenser and/or purchasing a beverage at a counter location.
- [31] The centralized ingredient system 20 may comprise a plurality of highly concentrated ingredients for micro dosing in the preparation of a wide variety of beverages. For example, but not by way of limitation, FIGs. 1, 2, and 3 illustrate thirty-six beverage ingredients 24 through 94. Each beverage ingredient 24 through 94 may be stored in a cartridge or storage container 112. As shown in FIGs. 8A and 8B, cartridge 112 may comprise a bag 116 filled with a beverage ingredient. Each cartridge 112 may store an ingredient that is different from the ingredient stored in every other cartridge 112 that comprise a grouping of plurality of sources 22.

- [32] The centralized ingredient system 20 may comprise a plurality of sweeteners 118 and 120. Sweetener 118 may be a nutritive sweetener, and sweetener 120 may be a non-nutritive sweetener.
- [33] Transfer unit 16 comprises nutritive sweetener cartridge or container 122, which contains nutritive sweetener 118, and corresponding nutritive sweetener in pump line 124, nutritive sweetener pump 126, and nutritive sweetener out pump line 302.
- [34] Transfer unit 16 may comprise non-nutritive sweetener cartridge or container 128, which may contain non-nutritive sweetener 120, and corresponding non-nutritive sweetener in pump line 130, non-nutritive pump 132, and non-nutritive sweetener out pump line 304.
- [35] Pump 126 may pump nutritive sweetener 118, and pump 132 may pump non-nutritive sweetener 120 from the transfer unit 16 through piping 18 to dispensing head 12.
- [36] Other pumps (not shown) may be used to pump beverage ingredients 24 through 94 from the transfer unit 16 through piping 18 to dispensing head 12.
- [37] Another pump or pumps (not shown) may be used to pump water from transfer unit 16 through piping 18 to dispensing head 12. The transfer unit 16 may comprise a water treatment system 134. Water treatment system 134 may be used to treat water. For example, water treatment system 134 may be used to cool water to a desired temperature for a cold beverage. A second water treatment (not shown) may be used to heat water to desired temperature for hot beverages. Water temperature ranges provided by water treatment system(s) used in connection with water treatment systems may be just below about freezing (e.g., to create or prepare a slurry or slush product) through about 180 degrees Fahrenheit (e.g., to create or prepare a hot beverage, such as a coffee or tea). The water treatment system may be any suitable water treatment system that improves taste, reduces odors, and/or reduces chlorines. The water treatment system may be any suitable water treatment system that may improve water quality to near pure water through systems, including but not limited to reverse osmosis (RO). As discussed in greater detail below, treated water is from water treatment system, and a least one beverage ingredient from the centralized ingredient system may be provided to counter location 14. The ratio of water from water treatment system 134 to beverage ingredients

provided from centralized ingredient system 20 for a beverage may be about 200 to 1 by weight. In one embodiment, the minimum ingredient may be about 200:1, or about 75:1, or about 40:1 (e.g., in the form of a flavor or acid), through about 40:1 for non-nutritive sweeteners, and about 6:1 for non-nutritive sweeteners. A base beverage may be prepared with about four streams, e.g., water, a sweetener, flavor, and acid). Additional streams may be added to provide top notes, e.g., cherry flavor, or sweetener blends to reduce calories, such as disclosed in U.S. Serial No. 12/703,048, filed February 9, 2010, which is incorporated herein by reference in its entirety.

- [38] Another pump or pumps (not shown) may be used to pump ice from transfer unit 16 through piping 18 to dispensing head 12. In one preferred embodiment, the transfer unit 16 may comprise an ice machine 136.
- [39] As shown in FIG. 3, piping or main micro bundle 18 may comprise an outer pipe 138, and bundle of smaller inner pipes 140. Inner pipes 140 may comprise beverage ingredient flavor lines 324, 326, 328, 330, 332, 334, 336, 338, 340, 342, 344, 346, 348, 350, 352, 354, 356, and 358, Inner pipes 140 may comprise beverage ingredient acid lines 360, 362, 364, 366, 368, 370, 372, 374, 376, 378, 380, 382, 384, 386, 388, 390, 392, and 394.
- [40] Beverage ingredient flavor line 324 corresponds to beverage ingredient 24, beverage ingredient flavor line 326 corresponds to beverage ingredient 26, etc. The following Table I identifies the correspondence between beverage ingredients and lines.

[41] Table I

Beverage ingredient	Line
24	324
26	326
28	328

30	330
32	332
34	334
36	336
38	338
40	340
42	342
44	344
46	346
48	348
50	350
52	352
54	354
56	356
58	358
60	360
62	362
64	364
66	366
68	368

70	370
72	372
74	374
76	376
78	378
80	380
82	382
84	384
86	386
88	388
90	390
92	392
94	394

[42] Fig. 3 illustrates a water out line 396, water return line 398, ice line 306, nutritive sweetener out pump line 302, and non-nutritive sweetener out pump line 304. Water return line 398 may allow for the circulating of water that is not dispensed from a dispensing head 12 to be returned to transfer unit 16 to makeup cold water to be supplied from transfer unit 16 to doser unit 400. This helps conserve energy since the water in water return line 398 will be closer to the desired temperature than water that has not been previously cooled. A hot water out line and a hot water return line may also be provided. A hot water return line (not show) may be used to allow for the circulating of water that is not dispensed from a dispensing head 12 to be returned to transfer unit 16 to

makeup hot water to be supplied from transfer unit to doser unit 64. This helps conserve energy since the water in a hot water return line will be closer to the desired temperature than water that has not been previously heated. The ice line 306 may be the largest of the lines in the bundle. Water out line 396 and water return line 398 may be about equal diameter, e.g., about 3/8" diameter lines. The nutritive sweetener out pump line 302 may have about equal diameter or slightly larger diameter as the non-nutritive sweetener out pump line 304. For example, the nutritive sweetener line may have a diameter of about 3/8" inches, and the non-nutritive sweetener may have a diameter of about 1/4" inches. The sweetener lines may comprise any desired number, e.g., four different sweetener lines.

[43] As shown in FIG. 4, doser unit 400 may comprise dispenser tower 402, which may comprise dispenser head 12 at counter location 14. Doser unit 400 may comprise an ice hopper 404. Doser unit 404 may receive liquid under pressure and dose appropriately to provide a desired beverage. The dosing of a beverage ingredient may be between about 0.1 cc to about 17 cc. In one embodiment, dosing may be about 0.5 cc to 17 cc for a nutritive sweetener. Dosing may be performed by a sliding vane pump as shown in FIG. 4, or other suitable positive displacement pump, gear pump, piston pump, oscillating pump, or diaphragm pump (not shown). The pump may be controlled through pulse width modulation, stroked or stepped to deliver the appropriate volume of an ingredient to form a beverage. Those of skill in the art will recognize that control of delivery may be achieved through use of an intelligent device, such a computer or purpose embedded electronics. .

[44] As shown in FIG. 5, dispenser tower 402 may comprise a tower micro bundle 406. In the embodiment depicted, tower micro bundle 406 comprises an ice line 500, nine carbonated water lines 502, 504, 506, 508, 510, 512, 514, 516, 518, nine non-carbonated water lines 520, 522, 524, 526, 528, 530, 532, 534, 536 (including one that may be re-circulated or created on demand, e.g., from the cold water circuit, eighteen flavor lines 538, 539, 540, 541, 542, 543, 544, 545, 546, 547, 548, 549, 550, 551, 552, 553, 554, 555, eighteen acid lines 556, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, a nutritive sweetener line 576, and a non-nutritive sweetener line

578. Tower micro bundle 406 may comprise any suitable cladding, including slots and piping.

- [45] A beverage ingredient, such as a sweetener, may be sent through a micro bundle to get better mixing. Instead of using a traditional 3/8" ID or 1/4" ID pipe wherein a sweetener may be dropped to the bottom of a cup and a consumer may not taste the sweetener when drinking a top portion of the beverage in a cup, the present disclosure allows for the use of smaller microtubes to get better mixing and have multiple dispense points (jet it in at a similar rate compared ingredients), and allow for greater dispersion throughout the beverage.
- [46] The modular dispensing system may comprise not only a central acid and flavor system, but also a local dairy and/or juice system. Thus, a beverage may be prepared with a shot of juice, e.g., a cola with a shot of lemon juice and/or lime juice. A beverage, such as a cool frappuccino or hot coffee, may be prepared with a shot of a dairy product, e.g., milk or cream.
- [47] The modular dispensing system allows for the adding of additional dispenser heads to existing towers for dispensing additional beverages while still using the centralized ingredient system or transfer unit. Such existing towers may be present at drive up systems or in-store systems.
- [48] The modular dispensing system may comprise a fast fill system for drive-up applications.
- [49] The modular dispensing system may comprise replacement bags for use in ingredient cartridges.
- [50] The modular dispensing system may comprise auto sanitizing systems, e.g., auto sanitizing of buttons at dispenser towers 66. The sanitizing system may include a sanitizer cartridge, e.g., a sanitizer cartridge replacing an ingredient cartridge. Those skilled in the art will recognize that locking of a portion of the system may be used so that a sanitizing cycle may be run. For example, a lock out feature with cartridge recognition of the sanitizer may be provided to prevent unintentional beverage

dispensing. The lock out feature with cartridge recognition of the sanitizer may have mechanical and electrical redundancy.

- [51] The modular dispensing system may comprise interlocks on sweetener types.
- [52] The modular dispensing system may comprise and/or communicate with a social media system or application. For example, when a mobile device of a consumer is within a predetermined distance from a sensor linked to the modular dispensing system, a message may be sent to the consumer's mobile device that queries the consumer whether the consumer would like to purchase a beverage. Alternatively, or at the same time, a message may appear at a counter location that queries the consumer whether the consumer would like to purchase a beverage. The social media system or application may download to the modular dispensing system the preference or preferences of a consumer based on the consumer's past purchases and/or identified preferences. Thus, the modular dispensing system and/or the social media system or application may query a particular consumer when a mobile device of a consumer is within a predetermined distance from a sensor of the modular dispensing system.
- [53] The modular dispenser system may also receive a beverage order from a consumer via a social media system or application, including but not limited to the social media system or application of a seller of beverages, including but not limited to restaurants, theaters, other entertainment venues, and manufacturers and/or distributors of beverages. A consumer may order a beverage prior to arriving at counter so that the drink may be prepared and placed in a cup by the time or close to the time the consumer arrives at the counter. Alternatively, a cup bearing and RFID identifier may be prepared and made available to the consumer for filling by the time or close to the time the consumer arrives at the counter. For example, see U.S. Serial No. 12/704,217, filed February 11, 2010, published on August 12, 2010 as U.S Patent Application Publication No. 2010/0200110, which is incorporated herein by reference in its entirety. This system saves time for both consumers and beverage sellers by cutting down on wait time, ordering time, and beverage preparation time.

- [54] Thus, the system may recognize an individual and make certain decisions regarding what beverage(s) or type of beverage(s) to offer the individual. The system may change what the system traditionally offers, e.g., a shot of orange juice in a cola beverage, if such a beverage has been ordered by the individual in the past, or the individual has identified the beverage as a preference on social media system or application.
- [55] In addition, the system may handle gifts or promotions given from one entity to another. By way of example, but not limitation, the system may recognize an individual, determine whether that individual has received a gift or is eligible for a promotion, and send a query to the individual as to whether the individual will accept the gift or promotion, such as a free beverage or a beverage at a reduced price.
- [56] The system may provide a gesture interface so that a user may order a beverage at sensor without touching the sensor.
- [57] The system may also provide a sanitizing screen display, including but not limited to, a puff of steam, a wiping motion display, and ultraviolet LED.
- [58] The system may provide a user with variable pricing based on brands being sold, e.g., the system may determine what products a user may receive based on cup size.
- [59] The system may allow for a user to pull into a drive up location and through the user's mobile device (e.g., a personal digital assistant, cell phone, or smart phone), via telephone or Wi-Fi, Bluetooth or other suitable communication system, know where the user is located and shows the user a menu, and may also provide the user with a special drive up line to pick up an order.
- [60] The system may allow for geolocation for advertising due to restricted street sign usage.
- [61] The system may provide designs for various fluid flow paths for micro dosing, e.g., controlling drip, and monitoring an effluent side of the pump.
- [62] Fast fill may include systems that allow for fast fill from the bottom of a cup.
- [63] On-demand carbonation may be provided using the dosing unit.

- [64] FIGs. 6 and 7 illustrate other aspects of the present disclosure. A transfer unit 600 may be similar to transfer unit 16 previously described. Transfer unit 600 may comprise a water treatment system 134. Transfer unit 600 may optionally comprise an ice system (not shown), like the ice machine 136 previously described.
- [65] Transfer unit 600 may comprise a central ingredient system or central reconstitution factory 602, which may be similar to central ingredient system 20 previously described.
- [66] Central reconstitution factory system 602 may be linked to one or more conventional or legacy dispensers 604A, 604B, and 604C using a bundle 606. The linking or connection between central reconstitution factory system 602 and legacy dispensers may be achieved in a backroom at the bundle pump inlet connection. As shown in FIG. 6, central reconstitution factory system 602 may comprise a plurality of beverage ingredients. In FIG. 6, central reconstitution factory 602 comprises twenty beverage ingredients 608, 610, 612, 614, 616, 618, 620, 622, 624, 626, 628, 630, 632, 634, 636, 638, 640, 642, 644, 646. These beverage ingredients may be selected from the group consisting of a beverage flavor ingredient and an acid. Transfer unit 600 may comprise one or more mixing chambers. In FIG. 6, transfer unit 600 comprises mixing chambers 648, 650, 652, 654 and 656, and additional mixing chambers if desired. Mixing chamber 648 may correspond to nozzle dispensers 658 and 660 at legacy dispensers 604A, 604B, and/or 604C, mixing chamber 650 may correspond to nozzle dispenser 662 at legacy dispensers 604A, 604B, and/or 604C, mixing chamber 652 may correspond to nozzle dispenser 664 at legacy dispensers 604A, 604B, and/or 604C, mixing chamber 654 may correspond to nozzle dispenser 666 at legacy dispensers 604A, 604B, and/or 604C, and mixing chamber 656 may correspond to nozzle dispenser 658 at legacy dispensers 604A, 604B, and/or 604C. Additional mixing chambers (not shown) may be provided at transfer unit 600 to correspond to nozzle dispensers 670, 672, 674, and 678 at legacy dispensers 604A, 604B, and/or 604C.
- [67] Beverage ingredients may be supplied to mixing chambers from cartridges 112 previously described, or bag-in-box type containers, which prior to the present disclosure were typically placed at a beverage dispensing counter.

- [68] Syrups and other beverage ingredients may include any of those provided by PepsiCo Inc. to form beverages known under any PepsiCo branded name, such as Pepsi-Cola®. Syrup and other beverage ingredients may be pumped from cartridges 112 or other supply containers by pumps (not shown) to mixing chambers as desired. These pumps may be driven by CO₂ from a tank 671 or 673 and supplied through a CO₂ gas branch line 675. These pumps may comprise conventional syrup pumps, e.g., BIP pumps.
- [69] Each mixing chamber may correspond to a particular beverage to be provided to a nozzle of legacy dispensers 604A, 604B, and/or 604C. In the embodiment shown in FIG. 6, a beverage, e.g., a beverage of regular Pepsi-Cola®, may be formed in mixing chamber 648. Inlets to mixing chamber 648 may comprise a water supply line 680, a sweetener supply line 682, an acid supply line 684, and a flavor supply line 686. Mixing chamber 648 may comprise a beverage out line 688. The sweetener, acid, and flavor ingredients supplied to mixing chamber 648 may be highly concentrated amounts of those ingredients mixed with water prior to being supplied to mixing chamber 648, e.g., a ratio of beverage ingredient to water of about 200 to 1 by weight. After being mixed with water from water supply line 680, the mixture exiting mixing chamber 648 in beverage out line 688 may have a ratio of beverage ingredient to water of about 5 to 1 by weight. Water may be supplied to a mixing chamber from water treatment system 679.
- [70] Sweetener line 682 may supply to a mixing chamber a nutritive sweetener and/or a non-nutritive sweetener. Sweetener line 682 may be either a nutritive sweetener pump line 302 or a non-nutritive sweetener pump out line 304 as previously described.
- [71] Aspects of the disclosure are shown in FIGs. 9, 10, and 11. FIG. 9 shows a multi-tower modular dispensing system that may comprise at least a first dispensing head and a second dispensing head at a counter, a transfer unit located remotely from the counter, and piping extending from the transfer unit to the counter. The transfer unit may comprise a centralized ingredient system having a plurality of beverage ingredient sources. The centralized ingredient system may be configured to supply beverage ingredients to the piping for the dispensing of a first beverage at the counter. The piping may comprise a main micro bundle. The main micro bundle may comprise at least two separate beverage ingredient lines.

- [72] At least one doser unit may be provided corresponding to at least the first dispensing head. The doser unit may be configured to receive a beverage ingredient from the transfer unit and dose a predetermined amount of the beverage ingredient to the first dispensing head.
- [73] The doser unit may be located at the counter. The doser unit may be located below the counter.
- [74] The doser unit may supply an appropriate amount of each beverage ingredient through a tower micro bundle, the tower micro bundle comprising a plurality of separate lines, with each line corresponding to a particular beverage ingredient.
- [75] The transfer unit may comprise a water treatment system, the water treatment system configured to treat water entering the water treatment system so that it has at least one predetermined characteristic upon exiting the water treatment system.
- [76] At least one predetermined characteristic of the water upon exiting the water treatment system may be a temperature that is lower than the temperature of the water entering the water treatment system.
- [77] At least one predetermined characteristic of the water upon exiting the water treatment system is a temperature that is higher than the temperature of the water entering the water treatment system.
- [78] The main micro bundle may comprise a line from the water treatment system to the doser unit.
- [79] The transfer unit may comprise an ice machine. The main micro bundle may comprise a line from the ice machine to the doser unit.
- [80] At least the first dispensing head may be configured to receive ice from an ice hopper and dispense the ice in a predetermined amount along with the other beverage ingredients. The ice hopper may be located at the counter. The ice hopper may be located below the counter.

- [81] At least the first dispensing head may be configured to receive at least one carbonated water line and dispense carbonated water in a predetermined amount along with the other beverage ingredients.
- [82] The first dispensing head and the second dispensing head may be each configured to receive at least at least two beverage ingredients, the at least two beverage ingredients selected from the group consisting of a flavor ingredient and an acid.
- [83] The multi-tower modular dispensing system may comprise at least a first doser unit corresponding to the first dispensing head, and a second doser unit corresponding to the second dispensing head. The first doser unit may be configured to receive a first beverage ingredient from the transfer unit and dose a predetermined amount of the first beverage ingredient to the first dispensing head. The second doser unit may be configured to receive a second beverage ingredient from the transfer unit and dose a predetermined amount of the second beverage ingredient to the second dispensing head. The first beverage ingredient and the second beverage ingredient may be the same or different.
- [84] The first doser unit may be configured to supply an appropriate amount of each beverage ingredient for a first predetermined beverage to the first dispensing head through a first tower micro bundle, the first tower micro bundle comprising a plurality of separate lines, with at least one line corresponding to a particular beverage ingredient of the first predetermined beverage. The second doser unit may be configured to supply an appropriate amount of each beverage ingredient for a second predetermined beverage to the second dispensing head through a second tower micro bundle, the second tower micro bundle comprising a plurality of separate lines, with at least one line corresponding to a particular beverage ingredient of the second predetermined beverage. The first predetermined beverage and the second predetermined beverage are the same or different.
- [85] In one aspect, and as further shown in FIG. 10, a multi-tower modular dispensing system may be provided comprising at least a first dispensing head at a first counter, and at least a second dispensing head at a second counter. The first and second counters may be

remote from each other. A transfer unit may be located remotely from the first counter and the second counter. Piping may extend from the transfer unit to the first counter and the second counter. The transfer unit may comprise a centralized ingredient system having a plurality of beverage ingredient sources. The centralized ingredient system may be configured to supply beverage ingredients to the piping for the dispensing of a first beverage at the first counter and for the dispensing of a second beverage at the second counter. The piping may comprise a main micro bundle. The main micro bundle may comprise at least two separate beverage ingredient lines. The first beverage and the second beverage may be the same or different.

- [86] The piping may be configured to supply beverage ingredients from the transfer unit to the first counter and the second counter in series or in parallel. At least the first counter may comprise at least an additional dispensing head.
- [87] As shown in FIG. 11, a multi-tower modular dispensing system may comprise a plurality of dispensing heads at a first counter, a plurality of dispensing heads at a second counter, the first and second counters remote from each other, a transfer unit located remotely from the first counter and the second counter, and piping extending from the transfer unit to the first counter and the second counter. The transfer unit may comprise a centralized ingredient system having a plurality of beverage ingredient sources, the centralized ingredient system configured to supply beverage ingredients to the piping for the dispensing of a plurality of beverages at the first counter and for the dispensing of a plurality of beverages at the second counter, the piping comprising at least one main micro bundle, the main micro bundle comprising a plurality of separate beverage ingredient lines. The piping may be configured to supply beverage ingredients from the transfer unit to the first counter and the second counter in series or in parallel.
- [88] The invention herein has been described and illustrated with reference to the embodiments of the figures, but it should be understood that the features of the invention are susceptible to modification, alteration, changes or substitution without departing significantly from the spirit of the invention. For example, the dimensions, number, size and shape of the various components may be altered to fit specific applications. Accordingly, the specific embodiments illustrated and described herein are for

illustrative purposes only and the invention is not limited except by the following claims and their equivalents.

We claim:

1. A multi-tower modular dispensing system comprising:

at least a first dispensing head and a second dispensing head at a counter, a transfer unit located remotely from the counter, piping extending from the transfer unit to the counter, the transfer unit comprising a centralized ingredient system having a plurality of beverage ingredient sources, the centralized ingredient system configured to supply beverage ingredients to the piping for the dispensing of a first beverage at the counter, the piping comprising a main micro bundle, the main micro bundle comprising at least two separate beverage ingredient lines.

2. The multi-tower modular dispensing system of claim 1, comprising at least one doser unit corresponding to at least the first dispensing head, the doser unit configured to receive a beverage ingredient from the transfer unit and dose a predetermined amount of the beverage ingredient to the first dispensing head.

3. The multi-tower modular dispensing system of claim 2, wherein the doser unit is located at the counter.

4. The multi-tower modular dispensing system of claim 3, wherein the doser unit is located below the counter.

5. The multi-tower modular dispensing system of claim 2, wherein the doser unit supplies an appropriate amount of each beverage ingredient through a tower micro bundle, the tower micro bundle comprising a plurality of separate lines, with each line corresponding to a particular beverage ingredient.

6. The multi-tower modular dispensing system of claim 1, wherein the transfer unit comprises a water treatment system, the water treatment system configured to treat water entering the water treatment system so that it has at least one predetermined characteristic upon exiting the water treatment system.

7. The multi-tower modular dispensing system of claim 6, wherein the at least one predetermined characteristic of the water upon exiting the water treatment system is a temperature that is lower than the temperature of the water entering the water treatment system.

8. The multi-tower modular dispensing system of claim 6, wherein the at least one predetermined characteristic of the water upon exiting the water treatment system is a temperature that is higher than the temperature of the water entering the water treatment system.

9. The multi-tower modular dispensing system of claim 6, wherein the main micro bundle comprises a line from the water treatment system to the doser unit.

10. The multi-tower modular dispensing system of claim 1, wherein the transfer unit comprises an ice machine.

11. The multi-tower modular dispensing system of claim 10, wherein the main micro bundle comprises a line from the ice machine to the doser unit.

12. The multi-tower modular dispensing system of claim 1, wherein at least the first the dispensing head is configured to receive ice from an ice hopper and dispense the ice in a predetermined amount along with the other beverage ingredients.

13. The multi-tower modular dispensing system of claim 12, wherein the ice hopper is located at the counter.

14. The multi-tower modular dispensing system of claim 13, wherein the ice hopper is located below the counter.

15. The multi-tower modular dispensing system of claim 1, wherein at least the first dispensing head is configured to receive at least one carbonated water line and dispense carbonated water in a predetermined amount along with the other beverage ingredients.

16. The multi-tower modular dispensing system of claim 1, wherein the first dispensing head and the second dispensing head are each configured to receive at least at least two beverage ingredients, the at least two beverage ingredients selected from the group consisting of a flavor ingredient and an acid.

17. The multi-tower modular dispensing system of claim 1, comprising at least a first doser unit corresponding to the first dispensing head, a second doser unit corresponding to the second dispensing head, the first doser unit configured to receive a first beverage ingredient from the transfer unit and dose a predetermined amount of the first beverage ingredient to the first dispensing head, the second doser unit configured to receive a second beverage ingredient

from the transfer unit and dose a predetermined amount of the second beverage ingredient to the second dispensing head.

18. The multi-tower modular dispensing system of claim 17, wherein the first beverage ingredient and the second beverage ingredient are the same or different.

19. The multi-tower modular dispensing system of claim 17, wherein the first doser unit is configured to supply an appropriate amount of each beverage ingredient for a first predetermined beverage to the first dispensing head through a first tower micro bundle, the first tower micro bundle comprising a plurality of separate lines, with at least one line corresponding to a particular beverage ingredient of the first predetermined beverage, wherein the second doser unit is configured to supply an appropriate amount of each beverage ingredient for a second predetermined beverage to the second dispensing head through a second tower micro bundle, the second tower micro bundle comprising a plurality of separate lines, with at least one line corresponding to a particular beverage ingredient of the second predetermined beverage.

20. A multi-tower modular dispensing system comprising:


at least a first dispensing head at a first counter, at least a second dispensing head at a second counter, the first and second counters remote from each other, a transfer unit located remotely from the first counter and the second counter, piping extending from the transfer unit to the first counter and the second counter, the transfer unit comprising a centralized ingredient system having a plurality of beverage ingredient sources, the centralized ingredient system configured to supply beverage ingredients to the piping for the dispensing of a first beverage at the first counter and for the dispensing of a second beverage at the second counter, the piping comprising a main micro bundle, the main micro bundle comprising at least two separate beverage ingredient lines.

21. The multi-tower modular dispensing system of claim 20, wherein the piping is configured to supply beverage ingredients from the transfer unit to the first counter and the second counter in series or in parallel.

22. A multi-tower modular dispensing system comprising a plurality of dispensing heads at a first counter, a plurality of dispensing heads at a second counter, the first and second counters remote from each other, a transfer unit located remotely from the first counter and the

second counter, piping extending from the transfer unit to the first counter and the second counter, the transfer unit comprising a centralized ingredient system having a plurality of beverage ingredient sources, the centralized ingredient system configured to supply beverage ingredients to the piping for the dispensing of a plurality of beverages at the first counter and for the dispensing of a plurality of beverages at the second counter, the piping comprising at least one main micro bundle, the main micro bundle comprising a plurality of separate beverage ingredient lines.

23. The multi-tower modular dispensing system of claim 22, wherein the piping is configured to supply beverage ingredients from the transfer unit to the first counter and the second counter in series or in parallel.






FIG. 2





FIG. 3






FIG. 5






FIG. 6





9/12






FIG. 8B





12/12




FIG. 11

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2012/036129

A. CLASSIFICATION OF SUBJECT MATTER

INV. B67D1/00 B67D1/06 B67D1/08
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
B67D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 009 082 A (ABRAHAM III MARTIN J [US]) 23 April 1991 (1991-04-23)	1
Y	column 4, line 48 - column 5, line 25; figure 1	2-4
X	US 5 368 205 A (GROH JAMES K [US]) 29 November 1994 (1994-11-29)	1
Y	figure 1	2-4
X	EP 1 627 849 A1 (IMI CORNELIUS UK LTD [GB]) 22 February 2006 (2006-02-22)	1
Y	paragraph [0056] - paragraph [0059]; figure 7	2-4
	paragraph [0076] - paragraph [0077]	
Y	US 5 314 091 A (CREDLE JR WILLIAM S [US]) 24 May 1994 (1994-05-24)	2-4
	column 4, line 34 - line 53 column 7, line 25 - line 37; figures 10,22	



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

24 July 2012

Date of mailing of the international search report

25/10/2012

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Desittere, Michiel

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2012/036129

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fees, this Authority did not invite payment of additional fees.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

see additional sheet(s)

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- ☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- ☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. claims: 1-5

Multi-tower beverage dispensing system with doser unit

2. claims: 6-9

Multi-tower beverage dispensing system with water treatment system

3. claims: 10, 11

Multi-tower beverage dispensing system with ice-machine

4. claims: 12-14

Multi-tower beverage dispensing system with dispensing head adapted to dispense ice and a beverage

5. claim: 15

Multi-tower beverage dispensing system with a dispensing head configured to receive a carbonated water line

6. claim: 16

Multi-tower beverage dispensing system with dispensing heads configured to receive each at least two ingredients

7. claims: 17-19

Multi-tower beverage dispensing system with dispensing heads having each a doser unit

8. claims: 20-23

Multi-tower beverage dispensing system with dispensing heads at different counters

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2012/036129

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5009082	A	23-04-1991	NONE
US 5368205	A	29-11-1994	AT 152698 T 15-05-1997 CA 2128260 A1 20-01-1995 DE 69403030 D1 12-06-1997 DE 69403030 T2 11-12-1997 EP 0635455 A1 25-01-1995 US 5368205 A 29-11-1994 US 5573145 A 12-11-1996
EP 1627849	A1	22-02-2006	AT 407094 T 15-09-2008 EP 1627849 A1 22-02-2006 EP 2003088 A1 17-12-2008 ES 2313239 T3 01-03-2009 GB 2417235 A 22-02-2006 GB 2443899 A 21-05-2008 GB 2446728 A 20-08-2008 GB 2449574 A 26-11-2008 GB 2449579 A 26-11-2008 GB 2450262 A 17-12-2008
US 5314091	A	24-05-1994	NONE