

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 December 2003 (18.12.2003)

PCT

(10) International Publication Number
WO 03/104029 A2

(51) International Patent Classification⁷: **B60R**
(21) International Application Number: PCT/US03/17829
(22) International Filing Date: 6 June 2003 (06.06.2003)
(25) Filing Language: English
(26) Publication Language: English

(30) Priority Data:
10/163,586 6 June 2002 (06.06.2002) US

(71) Applicant: **NETSHAPE CORPORATION** [US/US];
29870 Middlebelt, Farmington Hills, MI 48334 (US).

(72) Inventors: **WEISSENBORN, Mark**; 0-435 Fennessey
Street, S.W., Grand Rapids, MI 49544 (US). **EVANS,**
Darin; 2027 Medina Drive, Wixom, MI 48393 (US).
WEYKAMP, Robert; 15485 Royal Oak Drive, Grand
Haven, MI 49417 (US). **POWEL, David**; 15484 Lake
Avenue, Grand Haven, MI 49417 (US).

(74) Agent: **DOLCE, Marcus, P.**; Price, Henevel, Cooper De-
Witt & Litton, 695 Kenmoor, S.E., Post Office Box 2567,
Grand Rapids, MI 49501-2567 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD,
SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ,
VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: BUMPER WITH INTEGRATED FOAM AND NON-FOAM COMPONENTS



(57) Abstract: A bumper system includes a bumper beam having a face and ends, and an energy absorber mounted on the face. The energy absorber has a one-piece injection-molded non-foam piece with box sections and interconnecting straps, and a one-piece or multipiece foam components securely insert-molded onto the injection-molded non-foam piece. Different foam can be used to form differently shaped front surfaces on the foam component. By this arrangement, different energy absorbing systems are provided for vehicles, such as to satisfy the need for different styling and shapes, while still using the same non-foam piece. By this arrangement, the energy absorber is a single unit that can be handled and attached to the bumper beam. At the same time, capital investment in molding dies and tooling is reduced.



WO 03/104029 A2

BUMPER WITH INTEGRATED FOAM AND NON-FOAM COMPONENTS**BACKGROUND**

The present invention relates to vehicle bumper systems having an energy absorber on a bumper beam, and more particularly relates to a bumper system having an energy absorber on the beam that is adapted to provide different levels of energy absorption in selected areas but further adapted to take maximum advantage of mass production.

Vehicle bumper systems often include a bumper beam for strength and a mounted energy absorber to help absorb energy and distribute stress across the bumper beam during impact. However, each different model vehicle requires a slightly different shape or different energy absorption profile, such that each different model vehicle requires a different mold for the energy absorber. Each additional mold is expensive, because they are relatively large and long. Further, it takes time and labor to change molds, and requires downtime of the molding machine.

Accordingly, a bumper system is desired that includes an energy absorber solving the aforementioned problems and having the aforementioned advantages.

SUMMARY OF THE PRESENT INVENTION

In one aspect of the present invention, a bumper system has a face and ends, and has an energy absorber mounted on the face. The energy absorber has an injection-molded piece and a foam piece attached to the injection-molded piece, with the injection-molded piece being one-piece with box-shaped sections interconnected by strap sections, and with the foam piece being one-piece and encapsulating the straps and engaging at least a side of the box-shaped sections.

In another aspect of the present invention, a bumper system includes a bumper beam having a face surface, and an energy absorber engaging the face surface, where the energy absorber has an elongated non-foam injection-molded component with at least three longitudinally-spaced enlarged sections. An enlarged foam component is attached to the injection-molded component, with the enlarged foam component having first foam sections positioned between the enlarged sections and having second foam sections on the enlarged sections.

In yet another aspect of the present invention, a method comprises steps of molding a non-foam plastic component having box sections and strap sections connecting

the box sections, and molding a foam component that encapsulates at least three sides of the strap sections and that is bonded to at least part of the box sections, including forming a final product that can be handled as a unit. The method further includes engaging the unitary member against a face of a bumper beam.

5 In still another aspect of the present invention, a method comprises steps of providing molding dies for molding a non-foam plastic component having box sections interconnected with strap sections, such that the plastic component is shaped for use in a bumper system for providing an energy-absorbing impact strength, and also providing at least first and second molds for molding first and second foam components onto the plastic component, the first and second molds having respective cavities configured to form differently shaped front surfaces on the first and second foam components. The method includes molding the non-foam plastic component using the molding dies, and using the selected one mold in a molding process to form an associated one of the foam components, including attaching the associated foam component to the one of the non-foam plastic components to form a first energy absorber bumper product that can be handled as a unit. The method further includes engaging the unitary bumper product against a face of a bumper beam.

These and other aspects, objects, and features of the present invention will be understood and appreciated by those skilled in the art upon studying the following specification, claims, and appended drawings.

BRIEF DESCRIPTION OF DRAWINGS

Fig. 1 is a fragmentary perspective view of a bumper system including a bumper beam and a face-mounted energy absorber;

Figs. 2-3 are cross sections taken along the lines II-II and III-III in Fig. 1;

Fig. 4 is a front perspective view of a second bumper system including a bumper beam and a modified face-mounted energy absorber;

Fig. 5 is a rear perspective view of the energy absorber shown in Fig. 4;

Figs. 6 and 7 are top and front views of Fig. 4;

Figs. 8-10 are front perspective, front, and top views of a third bumper system;

Fig. 11 is a rear perspective view of the energy absorber shown in Fig. 8;

Fig. 12 is a front perspective view of an injection-molded non-foam "solid" plastic component of the energy absorber shown in Fig. 8; and

Fig. 13 is a top view of a fourth bumper system, utilizing the injection-molded non-foam plastic component shown in Fig. 12 but having first and second enlarged foam components molded thereon, the first being shown in solid lines, the second in phantom lines;

5 Figs. 14-15 and Figs. 16-17 are cross sections taken along the lines XIV-XIV and XV-XV, respectively. Figs. 14-15 being cross sections of the embodiment shown in solid lines, and Figs. 16-17 being cross sections of the embodiment shown in phantom lines; and

10 Fig. 18 is an exploded view of a modified version of the non-foam component shown in Fig. 12.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

A bumper system 8 (Fig. 1) includes a bumper beam 16 having a face and ends, and an energy absorber 10 mounted on the face. The energy absorber 10 has a center-located foam piece 11 engaging the face and an injection-molded end piece 12 securely
15 attached to each end of the foam piece and also engaging the face. By this arrangement, the energy absorber 10 is a single unit that can be handled and attached to the bumper beam 16. Also, the energy absorber 10 can include different end pieces while still using the same foam piece, or alternatively, the energy absorber can include different center pieces while using the same injection-molded non-foam end pieces. Thus, the present
20 inventive concepts provide the advantages of smaller molding dies for molding the injection-molded non-foam components. This is important because molding dies for injection-molded components are considerably more expensive than molding dies for foam components. At the same time, the present methods and apparatus provide the advantages of a single large energy absorber component that can be handled.

25 More specifically, the illustrated energy absorber 10 of Fig. 1 is adapted to advantageously use a common center piece 11 made of foam, and any one of a variety of different injection-molded end pieces attached to the foam. The illustrated end piece 12 includes loops or attachment flanges 13 and is insert-molded onto an end of the foam piece 11 when forming the foam piece 11. The end piece 12 includes a front surface 14
30 angled to match the corner of its particular vehicle, and a notched back surface 15 shaped to mateably receive an end of the bumper beam 16 that it rides on. It is contemplated that different attachment means can be used to attach pieces 11 and 12

together, including adhesive, mechanical attachment, different tabs for insert-molding into the foam, and barb-like tabs that can be poked into the foam, etc. Since the same center piece is used for a number of different models, the overall cost of molding dies is greatly reduced. Restated, the cost of several small injection-molding dies for molding a variety of different end pieces, added to the cost of one large die for the foam center piece, is much lower than the cost of making a multitude of different huge injection-molding dies for each energy absorber.

The same principle applies to a bumper system that uses the same end pieces but different foam molding dies. Restated, the cost of a single set of small injection-molding dies for molding the end pieces, added to the cost of several large dies for making different foam center pieces, is much lower than the cost of making a multitude of different huge injection-molding dies. This concept is discussed in greater detail below. (See Figs. 13-17, and see discussion below.)

A second energy absorber 10a (Figs. 4-7) is mounted to a face of a bumper beam 16 and includes a center-located injection-molded non-foam plastic center piece 20, foam pieces 11 attached to each end of the center piece 20, and injection-molded non-foam end pieces 12 attached to outer ends of each of the foam pieces 11. The pieces 11, 12, and 20 are each molded for optimal localized energy absorption (i.e. for an optimal force versus deflection curve, as well as for total energy absorption based on localized/area-specific impacts and based on particular types of impacts). For example, the injection-molded pieces 12 and 20 include a plurality of interconnected webs forming a honeycomb structure capable of substantial energy absorption prior to deformation of the bumper beam itself.

A modified bumper system (Figs. 8-10) includes a roll-formed B-shaped bumper beam 16 and a modified energy absorber 30b abutted against its face surface. The energy absorber 30b includes an injection-molded piece 31b (Fig. 12), and one or more foam pieces 11b (Figs 8-11) molded onto the injection-molded piece 31b. The injection-molded piece 31b (Fig. 12) is molded of a non-foam "solid" polymer and includes molded end sections 32b (similar to end pieces 12), and molded center and intermediate sections 33b and 34b, all interconnected by longitudinal straps 35b. The end sections 32b (when seen in plan view) each include a triangular outer portion 36b and a triangular inner portion 37b forming a rearwardly-swept angled front surface 38b and a stepped

back surface 39b with a pocket 40b shaped to receive the end of the beam 16. The outer portion 36b includes four parallel walls 41b that extend parallel a length of the beam 16, and that combine with angled walls 42b and 43b to define a honeycomb-like structure in the form of three forwardly open pockets 44b. The inner portion 37b has four parallel walls 45b that combine with angled walls 46b and 47b to define a rigid structure on the face of the end of the bumper beam 16. The honeycomb-like structure of the outer portion 36b and the inner portion 37b combine to provide optimal energy absorption at ends of the bumper beam 16 for optimal corner impact resistance and crush characteristics. The walls 41b and 45b are generally parallel and aligned with each other and extend in a horizontal plane (when in a car-mounted position), such that good corner impact strength is provided. It is noted that the inner and outer portions 36b and 37b are configured to allow a simple molding die, without the need for making undercuts, blind surfaces, and without the need for complex die pulls and slides.

The center and intermediate sections 33b and 34b (Fig. 12) each comprise rearwardly-open box-shaped sections formed by side walls 50b, a top wall 51b, a bottom wall 52b and a front wall 53b. An opening 54b is formed in each of the front walls 53b, and a centered tubular "crush tower" of material 55b extends rearwardly from the marginal material forming the opening 54b to a rear of the energy absorber. The box-like shape of walls 50b/51b/52b/53b along with the crush tower 55b adds considerably to the impact strength of the energy absorber 30b and adds control over the crush sequence and characteristics of impact and bumper system crush stroke versus energy absorption. If the crush tower 55b ends short of the bumper beam 16, then the crush sequence has a stepped function, where the initial crush strength is a little lower, and when the energy absorber 30b crushes to the point where the crush tower 55b hits the bumper beam 16, the impact strength suddenly increases for additional crush stroke distances. Also, the top and bottom walls 51b and 52b are wavy or undulated to provide increased impact strength.

The straps 35b (Fig. 12) extend between and interconnect each of the sections 32b, 33b, and 34b. Their cross sections define a rearwardly-facing U-shape, and are formed by front wall 57b, and top and bottom walls 58b and 59b. The straps 35b permit flexing movement, until the foam sections 11b are molded onto the pieces 31b, at which

time the energy absorber 30b becomes stiff enough to easily handle and assemble onto the bumper beam 16.

It is noted that the entire illustrated energy absorber 30b is configured so that it can be molded by a relatively simple molding die, where the die halves do not include
5 draws, slides, and other moving complex components for making blind and/or hidden surfaces. This greatly simplifies and improves tooling, and reduces costs and capital investment of making the die and keeping the die maintained and operational.

The energy absorber 30b can be attached temporarily to the tubular beam 16 by various means. For example, the illustrated absorber 30b includes rearwardly-extending
10 resilient attachment flanges or "fingers" 70b on top and bottom walls of the energy absorber 30b. The fingers 70b include a protrusion 71b adapted to engage a mating aperture in the beam 16 for temporarily securing the energy absorber 30b to the beam 16. The assembly 30b/16 can then be handled as a unit to facilitate transporting, placing, and then securing the assembly 30b/16 on the vehicle.

Fig. 13 is a top view of a fourth bumper system 8b', utilizing a modified energy
15 absorber 30b'. The energy absorber 30b' includes the same injection-molded non-foam plastic component 31b shown in Fig. 12, but also includes an enlarged one-piece foam component 11b' (shown in solid lines) or one-piece foam component 11b'' (shown in phantom lines) molded thereon. It is contemplated that the foam piece will be made
20 unique to each different vehicle model (i.e. each different fascia style), but the injection-molded part will be the same for each vehicle model (i.e. despite the different fascia style, the same non-foam part can be used.) Advantageously, the foam component (11b' and/or 11b'') can have a different top surface shape or bottom surface shape. For
example, compare the energy absorber 30b' illustrated by solid lines in Fig. 13, with the
25 energy absorber 30b'' illustrated by phantom lines in Fig. 13. Also, compare the energy absorber 30b' in Figs. 13-15, with the energy absorber 30b'' in Figs. 13, 16-17.

Energy absorber 30b' (or 30b'') can be further modified as shown in Fig. 18, by making the end piece telescopingly adjustable on the main center piece. In the
30 modification, the end piece 32b'' is separated from the interconnecting section 35b'' of center piece 31b'', and the end piece 32b'' is given an integrally-formed free-ended interconnecting leg 80b shaped to telescope into an open end 81b of the interconnection

section 35b''. The interconnecting section 32b'' includes inward flanges 82b shaped to capture a cross-sectional shape of the interconnecting leg 80b, and further the interconnecting leg 80b includes protrusions 83b shaped to detentingly engage the apertures 84b in the interconnecting section 80b. By this arrangement, the end piece 32b'' can be adjustingly snap-lockingly engaged with the interconnecting section 25b to a predetermined length. Thus, the same non-foam injection-molded energy absorber assembly (i.e. center piece 31b'' and end pieces 32b'') can be assembled to a desired length for use on a particular model vehicle having a car-width dimension greater than that shown in Fig. 13. It is noted that the telescoping feature (i.e. item 80b) can be located anywhere along a length of the energy absorber, and not just at its end.

It is to be understood that variations and modifications can be made on the aforementioned structure without departing from the concepts of the present invention, and further it is to be understood that such concepts are intended to be covered by the following claims unless these claims by their language expressly state otherwise.

I claim:

1. A bumper system comprising:

a bumper beam having a face and ends; and

an energy absorber mounted on the face, the energy absorber having a non-foam polymeric piece and at least one foam piece attached to the non-foam polymeric piece, with the non-foam polymeric piece being one-piece with box-shaped sections interconnected by strap sections, and with the at least one foam piece being one-piece and encapsulating the straps and engaging at least a side of the box-shaped sections.

2. The bumper system defined in claim 1, wherein the non-foam polymeric piece is molded to the at least one foam piece during the process of molding the foam piece.

3. A bumper system comprising:

a bumper beam having a face surface; and

an energy absorber engaging the face surface, the energy absorber having an elongated non-foam polymeric component with at least three longitudinally-spaced enlarged sections connected by strap sections, and having foam sections positioned between the enlarged sections and covering the strap sections.

4. The bumper system defined in claim 3, wherein the enlarged sections are each box-shaped and have a hollow interior space.

5. The bumper system defined in claim 3, wherein the enlarged sections each include a front wall with marginal material forming an opening therein.

6. A bumper system comprising:

a bumper beam having a face; and

an energy absorber including a first unitary structural component molded from non-foam polymeric material to include a plurality of spaced-apart sections and straps interconnecting the spaced-apart sections, and further including block-shaped foam sections positioned at least partially between the spaced-apart sections, each foam section having a rear surface engaging the face.

7. A bumper system comprising:

a bumper beam having a face; and

an energy absorber including a plurality of alternating sections of hollow non-foam sections and block-shaped foam sections, each having a rear surface engaging the face, wherein the energy absorber includes straps interconnecting adjacent ones of the hollow non-foam sections.

8. The bumper system defined in claim 7, wherein one of the non-foam sections wraps onto an end of the bumper beam.

9. (Amended) The bumper system defined in claim 7, wherein the non-foam and foam sections each include front surfaces that align to define a continuous front surface for extending across a front of a vehicle.

10. A bumper system comprising:

a bumper beam having a face; and

an energy absorber including a plurality of alternating sections of hollow non-foam sections and block-shaped foam sections, each having a rear surface engaging the face, wherein at least one of the hollow non-foam sections includes a front wall, a top wall, a bottom wall, and opposing sidewalls.

11. A bumper system comprising:

a bumper beam having a face; and

an energy absorber including a plurality of alternating sections of hollow non-foam sections and block-shaped foam sections, each having a rear surface engaging the face, wherein at least one of the hollow non-foam sections includes a front wall with marginal material forming a centered aperture, and further includes a tubular section of material extending rearwardly from the marginal material.

12. The bumper system defined in claim 11, wherein the plurality of non-foam sections includes at least three, and the plurality of foam sections includes at least four.

13. A bumper system comprising:
a bumper beam having a face; and
an energy absorber including a plurality of alternating sections of hollow non-foam sections and block-shaped foam sections, each having a rear surface engaging the face, wherein the non-foam and foam sections each include top surfaces that align to define a continuous top surface for extending across a front of a vehicle in a manner adapted to support a vehicle fascia.

14. A bumper system comprising:
a bumper beam having a face; and
an energy absorber including a plurality of alternating sections of hollow non-foam sections and block-shaped foam sections, each having a rear surface engaging the face, wherein the energy absorber includes rearwardly extending resilient attachment flanges that frictionally engage the bumper beam to hold the energy absorber on the bumper beam.

15. A bumper system comprising:
a bumper beam having a face; and
an energy absorber including a plurality of alternating sections of hollow non-foam sections and block-shaped foam sections, each having a rear surface engaging the face, wherein the plurality of non-foam sections include opposite end sections each having parallel walls that extend parallel a length of the beam and angled walls that combine with the parallel walls to define a honeycomb structure in the form of forwardly open pockets.

16. A bumper system comprising:
a bumper beam having a face and ends; and
an energy absorber mounted on the face, the energy absorber having a foam piece engaging the face and an injection-molded end piece securely attached to an end of the foam piece and also engaging the face.

17. The bumper system defined in claim 16, wherein the injection-molded end piece includes attachment flanges that extend into the foam piece and anchor the injection-molded end piece in the foam piece.

18. The bumper system defined in claim 16, wherein the injection-molded end piece is insert-molded into the foam piece during the process of molding the foam piece.

19. The bumper system defined in claim 16, including a second injection-molded piece securely attached to a second end of the foam piece.

20. The bumper system defined in claim 19, wherein the second injection-molded piece comprises a second injection-molded end piece.

21. The bumper system defined in claim 20, including a second foam piece and a center-located third injection-molded piece, the first and second foam pieces being securely attached to ends of the center-located third injection-molded piece, and the first and second end pieces being attached to outer ends of the first and second foam pieces, respectively.

22. A bumper system comprising:
a bumper beam having a face and ends; and
an energy absorber mounted on the face, the energy absorber having at least one foam piece engaging the face and at least one non-foam plastic piece securely attached to an end of the foam piece and also engaging the face, the foam piece and the non-foam piece forming a single member that can be handled and attached as a unit to the bumper beam.

23. A bumper system comprising:
a bumper beam having a face surface; and
an energy absorber engaging the face surface, the energy absorber having an elongated non-foam component with at least three longitudinally-spaced enlarged sections and a plurality of foam sections attached to the non-foam component between the enlarged sections, at least one of the enlarged sections including a front wall with marginal material forming an opening therein.

24. The bumper system defined in claim 23, wherein the foam sections each fill a space defined between sides of the adjacent enlarged sections.

25. The bumper system defined in claim 23, wherein the enlarged sections are each box-shaped and have a hollow interior space.

26. The bumper system defined in claim 23, wherein the non-foam component is one-piece and the enlarged sections are interconnected by connecting straps.

27. The bumper system defined in claim 23, wherein the non-foam component includes end piece sections and wherein the enlarged sections include at least one centered box-shaped section.

28. The bumper system defined in claim 23, wherein a front surface of the energy absorber includes first areas defined by the non-foam component, and further includes second areas defined by the foamed sections.

29. The bumper system defined in claim 23, wherein the non-foam component includes end sections each having a pocket shaped to receive an end of the bumper beam.

30. A bumper system comprising:
a bumper beam having a face surface; and
an energy absorber engaging the face surface, the energy absorber having an elongated non-foam injection-molded component with at least three longitudinally-spaced enlarged sections and a plurality of foam sections attached to the molded component between the enlarged sections;

wherein the enlarged sections are each box-shaped and have a hollow interior space, and further wherein the enlarged sections each include a front wall with marginal material forming an opening therein.

31. The bumper system defined in claim 30, including a crush tower tube that extends from the marginal material rearwardly toward the bumper beam.

32. A bumper system comprising:
a bumper beam having a face surface; and
an energy absorber engaging the face surface, the energy absorber including at least one non-foam section and at least one foam section, the at least one non-foam section

having a rear side and a front side, the rear side of the non-foam section abutting the face surface of the bumper beam, the foam section covering at least a portion of the front side of the non-foam section.

5 33. The bumper system of claim 32, wherein the foam section covers the entire front side of the non-foam section.

34. The bumper system of claim 32, wherein the foam section covers at least a portion of a top and bottom side of the non-foam section.

10

35. The bumper system of claim 32, wherein the foam section covers at least a portion of a top and bottom side of the bumper beam.

36. A method comprising steps of:

15

 molding a plurality of non-foam plastic components each having box sections and strap sections connecting the box sections;

 molding a foam component that encapsulates at least three sides of one of the strap sections and that is bonded to at least part of the box sections, including forming a final product that can be handled as a unit; and

20

 engaging the unitary member against a face of a bumper beam.

37. The method defined in claim 36, wherein the non-foam plastic component is one-piece.

25

38. The method defined in claim 36, wherein the foam component is one-piece.

39. A method comprising steps of:

30

 providing molding dies for molding a non-foam plastic component having box sections interconnected with strap sections, such that the plastic component is shaped for use in a bumper system for providing an energy-absorbing impact strength;

 providing at least first and second molds for molding first and second foam components onto the plastic component, the first and second molds having respective cavities configured to form differently shaped front surfaces on the first and second foam components;

molding a plurality of the non-foam plastic components using the molding dies;
selecting one of the first and second molds;

5 using the selected one mold in a molding process to form an associated one of the
foam components, including attaching the associated foam component to the one of the
non-foam plastic components to form a first energy absorber bumper product that can be
handled as a unit; and
engaging the unitary bumper product against a face of a bumper beam.

10 40. The method defined in claim 39, including selecting the other of the first and
second molds, using the selected other mold to form an associated second one of the foam
components, including attaching the second associated foam component to another one of
the non-foam plastic components to form a second energy absorber bumper product that
can be handled as a unit, the second energy absorber bumper product being different than
the first energy absorber bumper product.

