

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
3 July 2003 (03.07.2003)

PCT

(10) International Publication Number
WO 03/053545 A1

(51) International Patent Classification⁷: **B01D 53/04**

(21) International Application Number: PCT/US02/38624

(22) International Filing Date: 5 December 2002 (05.12.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/025,662 19 December 2001 (19.12.2001) US

(71) Applicant: **SUD-CHEMIE PROTOTECH, INC.**
[US/US]; 12 Fremont Street, Needham, MA 02494 (US).

(72) Inventors: **HUANG, Yinyan**; 12 Nancy Lane, Framing-
ham, MA 01701 (US). **MACKENZIE, Scott**; 32 Webster
Road, Lexington, MA 02421 (US). **BAR-ILAN, Amiran**;
79 University Road, Brookline, MA 02445 (US).

(74) Agent: **COX, Scott, R.**; Lynch, Cox, Gilman & Mahan,
P.S.C., 400 West Market Street, Suite 2200, Louisville, KY
40202 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,

GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU,
ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK,
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for all designations*
- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations*

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



WO 03/053545 A1

(54) Title: AN EXHAUST TREATMENT AND FILTRATION SYSTEM FOR MOLTEN CARBONATE FUEL CELLS

(57) Abstract: A filter system for adsorbing contaminants from an exhaust stream from a molten carbonate fuel cell including a filter substrate, a high surface area inorganic adsorbent secured to the filter substrate by an inorganic binder and an inorganic acid secured to the filter substrate. Also disclosed is a process for preparing the filter system for filtering exhaust gas from the molten carbonate fuel cell and a process for using the filtering system in a molten carbonate fuel cell system.

AN EXHAUST TREATMENT AND FILTRATION SYSTEM FOR MOLTEN
CARBONATE FUEL CELLS

5

Background of Invention

This invention relates to an exhaust system for adsorbing contaminants from an exhaust stream of a molten carbonate fuel cell. More particularly, it relates to a filter system for adsorbing contaminants from a molten carbonate fuel cell, wherein the filter system includes a filter substrate, an inorganic adsorbent secured to the filter substrate by an inorganic binder and an acidic material coated onto the filter substrate. The invention also relates to a process for the preparation of and use of the filter system within a molten carbonate fuel cell system.

Fuel cell systems represent a new technological approach to supplying energy. There has been a great interest in fuel cell technology because energy can be produced by such cells with high efficiency without creating many of the problems that are common when using fossil fuels, especially the environmental problems.

A fuel cell is an electrochemical device which continuously converts chemical energy of a reducing agent and an oxidant fuel to electrical energy by a process involving an essentially invariant electrode - an

electrolyte system. Fuel cells work at high efficiency with an emission level for undesirable pollutants far below that of the strictest industrial standards for conventional energy sources.

5 There are a number of different types of fuel cells with some classified based on working temperature and others classified by the fuels or oxidants that are used. Another method for distinguishing among different types of fuel cells is by the type of electrolyte that is used, such as
10 alkaline fuel cells, phosphoric acid fuel cells, solid oxide fuel cells, proton exchange membrane fuel cells and molten carbonate fuel cells.

 Molten carbonate fuel cells (MCFC) operate at about 600°C - 650°C and typically comprise a reformer for
15 converting hydrocarbon fuels to hydrogen and carbon monoxide, a burner and a plurality of molten carbonate fuel cell stacks. These fuel cells operate by reacting oxygen contained in an oxidant stream with carbon dioxide and free electrons at a cathode to produce carbonate ions. These
20 carbonate ions migrate across a molten carbonate electrolyte to an anode where they react with hydrogen and carbon monoxide contained in a fuel system to produce water, carbon dioxide and free electrons. The free electrons pass through an external load back to the cathode thereby producing

electricity while the carbon dioxide, water and any remaining hydrogen exits the anode into an exhaust stream. Typical MCFC systems also include an anode exhaust, downstream oxidation catalyst, which is located downstream from the fuel cell electrodes, and which oxidizes hydrocarbons, hydrogen and carbon monoxide contained in the exhaust stream. A general discussion of fuel cells, including molten carbonate fuel cell systems, is disclosed in Kordesch, et al., *Environment Impact of Fuel Cell Technology* (Chem. Rev. 1995, pp. 191-207). See also U.S. Patent Nos. 5,308,456, 5,213,912 and 5,079,103.

The MCFC uses a molten carbonate salt mixture as the electrolyte. The composition of the electrolyte may vary but usually includes lithium carbonate and potassium carbonate. Because the operating temperature of the MCFC is about 600°C - 650°C, the carbonate salt mixture is liquid. During operation, some alkali carbonates are often discharged from the fuel cell stacks into the exhaust stream. Such alkali carbonates are poisonous to the downstream oxidation catalyst. These alkali carbonates may also poison other components of the fuel cell system. Thus, it is imperative that these alkali carbonate contaminants be removed from the exhaust stream of the MCFC system.

Monolithic catalyst adsorbents are commonly utilized to

remove contaminants from various types of exhaust streams. For example, monolithic catalyst products having a cellular or honeycomb structure have been utilized in stationary emission control situations, food cooking facilities as disclosed in U.S. Patent No. 5,431,887 and for chemical synthesis and processing facilities. Monolithic catalyst products are also utilized in the automotive industry and for NOx conversion in feed streams.

Catalyst adsorbent products of this type are generally fabricated by preparing a substantially homogeneous cellular ceramic or metallic monolithic structure and securing a catalyst adsorbent material to that monolithic structure. The catalyst adsorbent product can also be formed by impregnating the monolithic structure with the catalyst adsorbent material and then heat treating the coated monolith to produce the final product.

Conventional washcoating techniques for production of catalytic monolith products generally comprise preparing a coating formed from a high surface area oxide blended with one or more catalytic adsorbents and dipping the monolith structure into that coating blend. These washcoats are then secured to the monolithic structure. Methods of coating a preformed high surface area washcoat onto a monolithic support are disclosed in U.S. Patent Nos. 4,900,712,

5,431,887, 5,556,189 and 5,693,298.

Several patents disclose the combination of catalytically active washcoat compositions comprising an alumina binder and catalytically active noble metals for the oxidation of hydrocarbons and/or the reduction of nitrogen oxides for field abatement, automotive exhaust control and the like, including, for example, U.S. Patent Nos. 6,150,291, 6,093,378, 6,080,377, 5,773,423 and 5,354,720.

In U.S. Patent No. 5,206,202 a honeycomb substrate structure is coated with a catalytic iron/vanadium mixture blended with an alumina or titania binder.

In another example, U.S. Patent No. 5,776,423 discloses a process for the preparation of a metallic zeolite catalyst adsorbent for NOx abatement. This patent discloses a process for the formation of a copper and iron ZSM-5 zeolite product using an alumina coating and silica sol binder. See also U.S. Patent No. 6,150,291 and 5,354,720.

Other catalyst adsorbents for purifying exhaust gases are disclosed by U.S. Patent Nos. 5,443,803 and 5,354,720. Each of these patents discloses the use of a silica sol as a binder for an active metal coated onto a monolithic structure.

U.S. Patent No. 6,004,896 discloses a hydrocarbon absorber and a method of making same. A ZSM-5 zeolite is

treated with phosphoric acid and then blended into a slurry for washcoating onto a monolithic structure. The preferred binder for the slurry is alumina, although the composition of the binder may also include silica and/or zirconia or their precursors.

U.S. Patent No. 4,564,607 discloses a catalyst composition comprising a compound containing a heteropolyacid as a base and whiskers placed on a carrier which may be formed into a honeycomb.

U.S. Patent No. 5,813,764 discloses a catalytic microcalorimeter sensor for monitoring exhaust gas conversions. The sensor disclosed is a washcoat obtained by mixing silica sol and alumina sol. The washcoat is used as the catalytic material itself and the components thereof are not used as binder materials. This patent also discloses the use of catalytically active metal particles. See the related patent, U.S. Patent No. 5,707,148.

While monolithic catalyst adsorbent products having a cellular or honeycomb structure have increasingly been utilized for emission control situations, such as in the automotive industry or for the adsorption of gases in feed and exhaust streams, such as are created during some food preparation processes, the use of a catalyst adsorbent for adsorbing inorganic contaminants in a fuel cell,

particularly a molten carbonate fuel cell, has not been considered.

Accordingly, it is an object of this invention to disclose an exhaust treatment system for adsorbing
5 contaminants from a molten carbonate fuel cell (MCFC) system including a filter system and an oxidation catalyst.

It is a further object of the invention to disclose a filter system for filtering an exhaust stream of a MCFC which absorbs alkali carbonate contaminants, which system
10 comprises a filter substrate, an inorganic adsorbent secured to the filter substrate by an inorganic binder and an acidic material.

It is a still further object of the invention to disclose a filter system contained in the exhaust treatment
15 system for adsorbing specific contaminants from an exhaust stream of a MCFC prior to passage of the exhaust stream through an oxidation catalyst comprising a filter substrate, a high surface area inorganic adsorbent secured to the filter substrate by an inorganic binder and an inorganic
20 acid secured to the filter substrate.

It is a still further object of the invention to disclose a process for filtering contaminants which are present in an exhaust stream of a MCFC by passing the exhaust fuel stream through an exhaust treatment system.

It is a still further object of the invention to disclose a process for filtering contaminants which are present in the exhaust stream of a MCFC comprising passing a fuel stream through the MCFC and filtering contaminants from the exhaust stream by use of a filter system of an exhaust treatment system prior to passing the filtered exhaust stream through an oxidation catalyst system.

It is a still further object of the invention to disclose a process for preparing a filter system of an exhaust treatment system for filtering exhaust gases from a MCFC comprising preparing a filtering substrate, coating the filtering substrate with an inorganic adsorbent by use of an inorganic binder and treating the coated filter substrate with an acidic material.

It is a further object of the invention to disclose a process for preparing a filter system for filtering exhaust gases from a MCFC prior to passage of the exhaust gases through an oxidation catalyst comprising preparing a filter substrate and coating the filter substrate in a single coating step with a solution comprising an inorganic adsorbent, an inorganic acidic material and an inorganic binder.

These and other aspects of the invention are obtained by various designs of the filter system, the process of its

manufacture and the process of its use.

Summary of the Invention

The present invention is an exhaust treatment system,
5 utilized in a MCFC for adsorbing contaminants given off by
the MCFC, wherein the filter system comprises a filter
substrate, an inorganic adsorbent secured to the filter
substrate by an inorganic binder, and an acidic material
coated onto the filter substrate. Preferably, the inorganic
10 adsorbent is a high surface area inorganic adsorbent and the
acidic material is an inorganic acid.

The present invention is also a process for filtering
contaminants contained in an exhaust stream of a MCFC
comprising passing a fuel stream through the MCFC and
15 filtering contaminants from the exhaust stream by use of a
filter system, wherein the filter system comprises a filter
substrate, an inorganic adsorbent secured to the filter
substrate by an inorganic binder and an acidic material
coated onto the filter substrate. After filtration, at
20 least a substantial portion of the exhaust stream passes
through an oxidation catalyst to remove other contaminants
from the exhaust stream.

The present invention also is a process for preparing
a filter system for filtering the exhaust stream from a

MCFC, which process comprises preparing a filter substrate, coating the filter substrate with an inorganic adsorbent by use of an inorganic binder, and treating the coated filter substrate with an acidic material. In an alternate preferred process the acidic material is blended with the inorganic adsorbent and the inorganic binder and coated onto the filter substrate in a single process step.

Detailed Description of the Invention

The present invention relates to an exhaust treatment system used in a molten carbonate fuel cell (MCFC) system. Typical MCFC include a fuel system feed line, a reformer catalyst, a molten carbonate fuel cell, a burner for that system and an exhaust stream. The MCFC can contain either a single MCFC cell or a plurality of MCFC cells which are typically connected in series. Each fuel cell of the MCFC has an anode chamber, a cathode chamber, an anode, a cathode and a molten carbonate electrolyte disposed there between and in intimate contact with the anode and the cathode.

Operation of the MCFC system requires the introduction of a fuel stream and water vapor to the reformer. The fuel feed stream is generally a conventional hydrocarbon fuel, such as natural gas, propane, coal gas or others. As the fuel typically contains sulfur impurities, it is preferred

to desulfurize the fuel prior to introducing it into the MCFC by use of a sulfur adsorbent, such as is disclosed in U.S. Patent No. 5,308,456. Following desulfurization, the fuel stream contacts the reformer catalyst where it reacts in an endothermic reaction to form hydrogen, carbon dioxide and carbon monoxide. Heat for this endothermic reaction is preferably provided at least partially by combustion of exhaust waste gases from the anode exhaust recycle stream. The reformer catalyst is a conventional steam reformer catalyst, which may be formed from a blend of a nickel-based catalyst and a noble metal, such as platinum, ruthenium, palladium, rhodium, among others. There are three conventional options for reforming fuels for MCFC systems: external reforming, direct internal reforming and indirect internal reforming.

The reformed fuel stream, containing hydrogen and carbon monoxide, contacts the anode which is a conventional catalyst for use within a MCFC. At the anode the hydrogen or carbon monoxide reacts with carbonate ions to form carbon dioxide, water and free electrons. The water, carbon dioxide, unconverted hydrogen, carbon monoxide, hydrocarbons and by-products then exit the anode chamber as anode exhaust. A portion of the anode exhaust may be recycled to the reformer while the remaining anode exhaust stream is

directed to the burners. The cathode exhaust recycle stream supplies oxygen necessary for operation of the burner. The combined stream is directed to the burner where it is burned to form water, carbon dioxide and other by-products. The burner is typically a catalytic burner containing a combustion catalyst in the form of pellets or honeycomb monolith. Burners typically operate at temperatures between about 600° and 860°C, preferably around 650°C.

The oxygen combustion stream is introduced into the cathode chamber. At the cathode, the stream intimately contacts a conventional catalyst where oxygen and carbon dioxide in the stream react with the free electrons which are passed from the anode to produce carbonate ions. These carbonate ions migrate across the molten carbonate electrolyte to the anode where they react with hydrogen and carbon monoxide to form water, carbon dioxide and free electrons. The feed stream exits the cathode chamber as a cathode exhaust stream, most of which is vented.

The exhaust stream from the MCFC is preferentially passed through an oxidation catalyst for the removal of hydrogen, carbon monoxide and hydrocarbons. However, during normal procedures components of the electrolyte mixture, usually lithium carbonate and potassium carbonate, are also present in the exhaust stream as contaminants. It is

important that these inorganic contaminants be removed from the exhaust stream prior to its passage through the exhaust steam oxidation catalyst as these contaminants can deactivate this catalyst. The exhaust treatment system of the invention is designed to trap these contaminants given off by the MCFC as well as oxidizing hydrocarbons, hydrogen and carbon monoxide which are present in the exhaust stream.

The exhaust treatment system includes the filter system for trapping alkali carbonates and the oxidation catalyst. The filter system for adsorbing the carbonate contaminants is comprised of a filter substrate, an inorganic adsorbent secured to the filter substrate by an inorganic binder and an acidic material coated onto the filter substrate.

One limitation on the composition of the filter substrate is that the MCFC operates at temperatures above 600°C. Thus, the filter substrate must be selected from materials which are stable at these operating temperatures. Among the preferred substrate materials are conventional metallic filter substrates comprised of stainless steel, iron-chromium alloys and other alloys. In addition, non-metallic filter substrates may also be utilized which are stable at the operating temperature of the MCFC, such as cordierite, ceramic, silicon carbide, alumina, zirconia, and mullite. Specific preferred embodiments of the composition

of filter substrate that are useful include a stainless steel screen manufactured by McNichols Co. or a ceramic product manufactured by Praxair Inc.

5 The inorganic adsorbent which is coated onto the filter substrate is preferably a high surface area inorganic adsorbent, such as a high surface area alumina, silica, titania, titania-silica, silica-alumina, silica-zirconia, and zeolites, either modified or unmodified. The preferred inorganic adsorbent has a surface area of at least about 100
10 m²/g, although lower surface area adsorbents can also be utilized. While lower surface area adsorbents, such as silica carbide, cordierite, alpha alumina and zirconia, may be used, higher surface area adsorbents are preferred for high efficiency performance.

15 For inorganic adsorbents to effectively filter contaminants in the exhaust stream of an MCFC, it is important that there be a strong adhesion between the inorganic adsorbent and the filter substrate. This strong adhesion is provided by the inorganic binder which binds the
20 inorganic adsorbent to the filter substrate. Among the preferred inorganic binders are sols of alumina, silica, zirconia, titania and ceria and combinations thereof. Other binders may also be used, such as boehmite and aluminum nitrate. Further, depending upon the nature of the filter

substrate and the inorganic adsorbent that is utilized, the binder system may also be formed from a combination of two or more different sols. The viscosity of the binder system depends on the type of filter substrate and inorganic binder that are utilized.

The inorganic adsorbent and binder are blended together conventionally for application to the filter substrate. Washcoating is the preferred method to apply the inorganic adsorbent to the filter substrate. The ratio of the adsorbent to the binder is preferably from about 100:1 to about 4:1, by weight. The washcoat slurry is prepared by blending the adsorbent and the binder with water followed by ballmilling or homogenization. The solids content of the washcoat slurry is typically about 20 percent to 50 percent, by weight.

Coating is performed by dipping the filter substrate into the slurry containing the inorganic adsorbent and the inorganic binder. Following dipping, the coated filter substrate is treated to remove excess slurry, for example, by air-knifing or suction filtration. Following the loading with the inorganic adsorbent and binder, the coated filter substrate is dried and calcined at a temperature of about 500°C for about 30 minutes to 2 hours to fix the inorganic adsorbent onto the filter substrate. The process may be

repeated two or more times to achieve the proper loading. The total washcoat loading is preferably about 2g/in³ (60 g/l) and can be in the range of about 0.5-4 g/in³ (30-240 g/l), based on the geometric dimensions of the filter substrate.

The contaminants such as lithium carbonate or potassium carbonate which are present in the exhaust stream from the MCFC are generally basic materials. Thus, the activity of the filter element is enhanced by coating the filter element with an acidic material. The preferred acidic materials are inorganic acids. Such inorganic acids are preferred because of the high temperature at which the MCFC system is operated. In addition, because the exhaust stream from an MCFC also contains high levels of moisture, in a preferred embodiment the acid utilized is preferably not a water soluble acid, such as sulfuric acid or hydrochloric acid. Accordingly, in a preferred embodiment the inorganic acid is a non-water soluble acid with high thermal stability. In a more preferred embodiment, the acid is a heterophosphoric acid or a polyphosphoric acid, such as phosphomolybdic acid or phosphotungstic acid.

In one preferred process the acidic material is added to the coated metallic filter substrate after the inorganic adsorbent is secured to the surface of the filter substrate

by impregnation. In an alternative preferred embodiment, the acidic material is added to the washcoat containing the inorganic adsorbent and the inorganic binder prior to the initial coating of the filter substrate.

5 If the inorganic acid is added in a separate step to the coated filter substrate, the coated filter substrate is impregnated with an aqueous solution containing the acidic material. The concentration of the acidic material on the coated filter substrate depends on the method of coating
10 that is utilized. These methods are well recognized in the industry. After addition of the acidic material, the filter is dried and calcined at about 500°C for about 2 hours.

 The ratio of the inorganic adsorbent to inorganic binder on the filter substrate is preferably from about 100
15 to 1 to about 4 to 1 and more preferably from about 20 to 1 to 10 to 1, by weight. The ratio of the inorganic adsorbent to acidic material is preferably from about 200 to 1 to about 5 to 1, preferably from about 100 to 1 to about 10 to 1 and most preferably about 20 to 1.

20 The filter system includes the filter substrate coated with a material, wherein the material comprises 60 to 95 percent inorganic adsorbent, preferably 80 to 95 percent; 1 to 40 percent inorganic binder, preferably 1 to 20 percent; and 0.1 to 20 percent acidic material, preferably 0.1 to 5

percent.

An important feature of this filter system is that the pressure drop should be kept as low as reasonable. To achieve an acceptable pressure drop, preferably monolithic, either ceramic or metallic, supports are utilized for the filter system. Acceptable pressure drop depends on the specific design of the MCFC system that is utilized. The composition of the filter system should balance the need for a high loading with the maintenance of a low pressure drop.

The filter system comprising a filter substrate onto which an inorganic adsorbent has been secured by an inorganic binder and onto which an inorganic acid has been secured is useful as an element of the exhaust treatment system for adsorbing contaminants from the exhaust stream from a molten carbonate fuel cell system. After the coated filter is formed, it is placed on line.

The coated filter is designed to remove inorganic contaminants, such as lithium or potassium carbonate, from the feed stream down to levels of about 1 ppm. Without the use of the filter system of the invention, the carbonates deposited on the oxidation catalyst can reach levels of up to 4-5 percent loading after a few months operation. Further, if not filtered, the carbonates may also damage other components of the fuel cell system.

Once the filter system has been utilized on stream for a significant period of time, it may be regenerated. Regeneration can be performed by washing the loaded filter system with deionized water followed by drying.

5 As discussed above, the coated filter is designed to filter the exhaust stream from a MCFC prior to passage of that exhaust stream through an oxidation catalyst. The oxidation catalyst utilized as an element of the exhaust treatment system is designed to remove unconverted hydrogen,
10 carbon monoxide and hydrocarbons from the exhaust stream. The oxidation catalyst utilized in this system is a conventional catalyst designed for the removal of these contaminants from the exhaust stream of a fuel cell. For example, such catalysts are often comprised of precious
15 metals loaded onto a conventional support, such as an alumina support, as disclosed for example in U.S. Patent Nos. 6,010,675, 6,299,995 and 6,254,807.

 Modifications may be made to the present invention which will occur to those skilled in the art. Such
20 inventions are within the scope of the invention as defined in the appended claims.

Claims

1. A filter system for adsorbing contaminants from a molten carbonate fuel cell exhaust stream comprising

a filter substrate coated with a material, wherein
5 the material comprises

an inorganic adsorbent coated onto the filter substrate by use of an inorganic binder, and

an acidic material coated onto the filter substrate.

10 2. The filter system of Claim 1 wherein the composition of the filter substrate is selected from a group of materials consisting of ceramic, alumina, titania, zirconia, boria, corundum, silica, magnesia, silica-zirconia, titania-zirconia, titania-silica, silica-alumina,
15 silicon carbides, cordierite, mullite, and metallic materials, such as stainless steel, iron chromium alloy and other metallic alloys, and mixtures and combinations thereof, preferably a metallic or ceramic material.

20 3. The filter system of any of Claims 1 - 2 wherein the inorganic adsorbent is selected from the group consisting of alumina, silica, titania, titania-silica, silica-alumina, zirconia silica-zirconia, ceria, zeolites, either modified or unmodified and mixtures thereof, preferably a high surface area inorganic adsorbent selected

from the group consisting of high surface area alumina, silica, titania, zirconia, ceria, titania-silica, silica-alumina, silica-zirconia, zeolites, and mixtures thereof, and most preferably a high surface area alumina with a surface area greater than 100 m²/g.

4. The filter system of any of Claims 1 - 3 wherein the inorganic binder for binding the inorganic adsorbent to the filter substrate is selected from the group consisting of sols of alumina, silica, zirconia, ceria, titania, boehmite and aluminum nitrate, and blends of two or more different binders.

5. The filter system of any of Claims 1 - 4 wherein the filter substrate comprises a stainless steel screen and the inorganic binder comprises ceria.

6. The filter system of any of Claims 1 - 5 wherein the acidic material comprises an inorganic acid, preferably a non-water soluble inorganic acid, and most preferably a heterophosphoric acid or a polyphosphoric acid, such as phosphomolybdic acid or phosphotungstic acid.

7. The filter system of any of Claims 1 - 6 wherein the material coating the filter substrate comprises 60 to 95 percent, preferably 80 - 95 percent inorganic adsorbent; 1 to 40 percent, preferably 1 to 20 percent inorganic binder; and 0.01 to 20 percent, preferably 0.1 to 5 percent acidic

material.

8. A process for preparing a filter system for filtering exhaust gases from a molten carbonate fuel cell prior to passage through an oxidation catalyst comprising

5

preparing a filter substrate,

coating the filter substrate with an inorganic adsorbent by use of an inorganic binder, and

treating the coated filter substrate with an acidic material.

10

9. A process for filtering contaminants which are present in an exhaust stream from a molten carbonate fuel cell comprising

passing a fuel stream through the molten carbonate fuel cell,

15

passing at least a portion of an exhaust stream from the fuel cell containing inorganic contaminants through a filter system, and

filtering the inorganic contaminants from the exhaust stream by use of the filter system, wherein the filter system comprises a filter substrate, an inorganic adsorbent secured to the filter substrate by an inorganic binder and an acidic material coated onto the filter substrate.

20

10. The process of Claim 9 further comprising passing

at least a portion of the filtered exhaust stream after passage through the filter system through an oxidation catalyst system.

5 11. An exhaust treatment system for adsorbing contaminants from a molten carbonate fuel cell comprising the filter system of Claim 1 and an oxidation catalyst.

INTERNATIONAL SEARCH REPORT

 International Application No
 PCT/US 02/38624

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 B01D53/04		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols) IPC 7 B01D		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EPO-Internal, PAJ, WPI Data		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 004 896 A (ADDIEGO WILLIAM P) 21 December 1999 (1999-12-21) cited in the application	1-4, 6, 8
A	claims 1,5	5, 7, 10, 11

X	WO 99 61134 A (OKADA TAKAO ; SAKATA SOICHIRO (JP); SATO KATSUMI (JP); TAKAHASHI HI) 2 December 1999 (1999-12-02) & US 6 352 578 B1 (OKADA TAKAO ; SAKATA SOICHIRO (JP); SATO KATSUMI (JP); TAKAHASHI HI) 5 March 2002 (2002-03-05) column 14, line 11 - line 19; claim 1	1, 3, 6, 8

	-/--	
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
° Special categories of cited documents :		
A document defining the general state of the art which is not considered to be of particular relevance *E* earlier document but published on or after the international filing date *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) *O* document referring to an oral disclosure, use, exhibition or other means *P* document published prior to the international filing date but later than the priority date claimed		*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. *&* document member of the same patent family
Date of the actual completion of the international search 15 April 2003		Date of mailing of the international search report 24/04/2003
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer Faria, C

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 02/38624

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>PATENT ABSTRACTS OF JAPAN vol. 1995, no. 01, 28 February 1995 (1995-02-28) & JP 06 283186 A (YOUYUU TANSANENGATA NENRYO DENCHI HATSUDEN SYST GIJUTSU KENKYU KUMIAI), 7 October 1994 (1994-10-07) abstract</p> <p>-----</p>	9-11

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No
PCT/US 02/38624

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6004896	A	21-12-1999	US 6001320 A	14-12-1999
WO 9961134	A	02-12-1999	JP 11333226 A	07-12-1999
			CN 1270539 T	18-10-2000
			WO 9961134 A1	02-12-1999
			TW 422725 B	21-02-2001
			US 6352578 B1	05-03-2002
JP 06283186	A	07-10-1994	NONE	