(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
6 December 2007 (06.12.2007)

PCT

(10) International Publication Number
WO 2007/140054 A1

(51) International Patent Classification:
A43B 9/02 (2006.01) *A43D 8/16* (2006.01)
A43B 23/02 (2006.01)

(21) International Application Number:
PCT/US2007/066696

(22) International Filing Date: 16 April 2007 (16.04.2007)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
11/442,679 25 May 2006 (25.05.2006) US

(71) Applicant *(for JP, KR only)*: **NIKE, INC.** [US/US]; One Bowerman Drive, Beaverton, OR 97006-6453 (US).

(71) Applicant: **NIKE INTERNATIONAL, LTD.** [US/US]; One Bowerman Drive, Beaverton, OR 97006-6453 (US).

(72) Inventor; and

(75) Inventor/Applicant *(for US only)*: **MESCHTER, James** [US/US]; c/o Nike, Inc., One Bowerman Drive, Beaverton, OR 97006-6453 (US).

(74) Agents: **KUZARA, Byron, S.** et al.; Plumsea Law Group, LLC, 10411 Motor City Drive, Suite 320, Bethesda, MD 20817 (US).


(81) Designated States *(unless otherwise indicated, for every kind of national protection available)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States *(unless otherwise indicated, for every kind of regional protection available)*: ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) **Title:** ARTICLE OF FOOTWEAR HAVING AN UPPER WITH THREAD STRUCTURAL ELEMENTS



(57) **Abstract:** An article of footwear includes an upper that is at least partially formed from a base layer and thread sections that lie adjacent a surface of the base layer. The thread sections are positioned to provide structural elements that, for example, restrain stretch in directions corresponding with longitudinal axes of the thread sections. In some configurations of the footwear, a first portion of the thread sections may extend between forefoot and heel regions of the footwear, and a second portion of the thread sections may extend vertically. An embroidering process may be utilized to position the thread sections on the base layer.

WO 2007/140054 A1

ARTICLE OF FOOTWEAR HAVING AN UPPER WITH THREAD STRUCTURAL ELEMENTS

BACKGROUND

[01] Conventional articles of footwear generally include two primary elements, an upper and a sole structure. The upper is secured to the sole structure and forms a void on the interior of the footwear for comfortably and securely receiving a foot. The sole structure is secured to a lower surface of the upper so as to be positioned between the upper and the ground. In some articles of athletic footwear, for example, the sole structure may include a midsole and an outsole. The midsole may be formed from a polymer foam material that attenuates ground reaction forces to lessen stresses upon the foot and leg during walking, running, and other ambulatory activities. The outsole is secured to a lower surface of the midsole and forms a ground-engaging portion of the sole structure that is formed from a durable and wear-resistant material. The sole structure may also include a sockliner positioned within the void and proximal a lower surface of the foot to enhance footwear comfort.

[02] The upper generally extends over the instep and toe areas of the foot, along the medial and lateral sides of the foot, and around the heel area of the foot. In some articles of footwear, such as basketball footwear and boots, the upper may extend upward and around the ankle to provide support for the ankle. Access to the void on the interior of the upper is generally provided by an ankle opening in a heel region of the footwear. A lacing system is often incorporated into the upper to adjust the fit of the upper, thereby permitting entry and removal of the foot from the void within the upper. The lacing system also permits the wearer to modify certain dimensions of the upper, particularly girth, to accommodate feet with varying dimensions. In addition, the upper may include a tongue that extends under the lacing system to enhance adjustability of the footwear, and the upper may incorporate a heel counter to limit movement of the heel.

[03] Various materials are conventionally utilized in manufacturing the upper. The upper of athletic footwear, for example, may be formed from multiple material layers that include

an exterior layer, an intermediate layer, and an interior layer. The materials forming the exterior layer of the upper may be selected based upon the properties of stretch-resistance, wear-resistance, flexibility, and air-permeability, for example. With regard to the exterior layer, the toe area and the heel area may be formed of leather, synthetic leather, or a rubber material to impart a relatively high degree of wear-resistance. Leather, synthetic leather, and rubber materials may not exhibit the desired degree of flexibility and air-permeability for various other areas of the exterior layer of the upper. Accordingly, the other areas of the exterior layer may be formed from a synthetic textile, for example. The exterior layer of the upper may be formed, therefore, from numerous material elements that each impart different properties to the upper. The intermediate layer of the upper is conventionally formed from a lightweight polymer foam material that provides cushioning and enhances comfort. Similarly, the interior layer of the upper may be formed of a comfortable and moisture-wicking textile that removes perspiration from the area immediately surrounding the foot. In some articles of athletic footwear, the various layers may be joined with an adhesive, and stitching may be utilized to join elements within a single layer or to reinforce specific areas of the upper. Accordingly, the conventional upper has a layered configuration, and the individual layers each impart different properties to various areas of the footwear.

SUMMARY

[04] One aspect of the invention is an article of footwear having an upper and a sole structure secured to the upper. The upper includes a base layer, a thread, and a securing element. The base layer defines a first surface and an opposite second surface. The thread has a section that lies adjacent to the first surface and is substantially parallel to the first surface for a distance of more than twelve millimeters, for example. In addition, the securing element joins the thread to the base layer.

[05] Another aspect of the invention is an article of footwear having an upper with a base layer and a plurality of thread sections. The base layer has a first surface and an opposite second surface. The thread sections are separate from the base layer and lie adjacent to at least a portion of the first surface. At least a portion of the thread sections are

substantially aligned. The upper defines a first direction corresponding with longitudinal axes of the thread sections, and the upper defines a second direction that is orthogonal to the first direction. The upper is substantially non-stretch in the first direction, and the upper is stretchable by at least ten percent in the second direction.

[06] Yet another aspect of the invention is a method of manufacturing an article of footwear having an upper and a sole structure. The method includes embroidering a base layer with at least one thread to locate a plurality of sections of the thread adjacent a surface of the base layer for a distance of more than twelve millimeters. The base layer and the at least one thread are incorporated into the upper, and the upper is secured to the sole structure.

[07] The advantages and features of novelty characterizing various aspects of the invention are pointed out with particularity in the appended claims. To gain an improved understanding of the advantages and features of novelty, however, reference may be made to the following descriptive matter and accompanying drawings that describe and illustrate various embodiments and concepts related to the aspects of the invention.

DESCRIPTION OF THE DRAWINGS

[08] The foregoing Summary, as well as the following Detailed Description, will be better understood when read in conjunction with the accompanying drawings.

[09] Figure 1 is a lateral side elevational view of an article of footwear having an upper in accordance with aspects of the present invention.

[10] Figure 2 is a medial side elevational view of the article of footwear.

[11] Figure 3 is a top plan view of the article of footwear.

[12] Figure 4 is a bottom plan view of the article of footwear.

[13] Figure 5 is a rear elevational view of the article of footwear.

[14] Figure 6 is a top plan view of a first embroidered element that forms at least a portion of a lateral side of the upper.

[15] Figure 7 is a top plan view of a second embroidered element that forms at least a portion of a medial side of the upper.

[16] Figures 8A-8O are top plan views illustrating a procedure for forming the first embroidered element and the second embroidered element.

[17] Figures 9A-9D are elevational views of a procedure for assembling the footwear.

[18] Figures 10A-10D are perspective views of a first procedure for securing threads to the base portion.

[19] Figures 11A-11D are perspective views of a second procedure for securing threads to the base portion.

[20] Figures 12A-12C are perspective views of a third procedure for securing threads to the base portion.

DETAILED DESCRIPTION

Introduction

[21] The following discussion and accompanying figures disclose an article of footwear having an upper with an embroidered configuration. In addition, various methods of manufacturing the upper are disclosed. The upper and the methods are disclosed with reference to footwear having a configuration that is suitable for running, and particularly sprinting. Concepts associated with the upper are not limited solely to footwear designed for running, however, and may be applied to a wide range of athletic footwear styles, including baseball shoes, basketball shoes, cross-training shoes, cycling shoes, football shoes, tennis shoes, soccer shoes, walking shoes, and hiking boots, for example. The concepts may also be applied to footwear styles that are generally considered to be non-

athletic, including dress shoes, loafers, sandals, and work boots. The concepts disclosed herein apply, therefore, to a wide variety of footwear styles.

General Footwear Structure

[22] An article of footwear 10 is depicted in Figures 1-5 as having the general configuration of a running shoe and includes a sole structure 20 and an upper 30. For reference purposes, footwear 10 may be divided into three general regions: a forefoot region 11, a midfoot region 12, and a heel region 13, as shown in Figures 1 and 2. Footwear 10 also includes a lateral side 14 and a medial side 15. Forefoot region 11 generally includes portions of footwear 10 corresponding with the toes and the joints connecting the metatarsals with the phalanges. Midfoot region 12 generally includes portions of footwear 10 corresponding with the arch area of the foot, and heel region 13 corresponds with rear portions of the foot, including the calcaneus bone. Lateral side 14 and medial side 15 extend through each of regions 11-13 and correspond with opposite sides of footwear 10. Regions 11-13 and sides 14-15 are not intended to demarcate precise areas of footwear 10. Rather, regions 11-13 and sides 14-15 are intended to represent general areas of footwear 10 to aid in the following discussion. In addition to footwear 10, regions 11-13 and sides 14-15 may also be applied to sole structure 20, upper 30, and individual elements thereof.

[23] Sole structure 20 is secured to upper 30 and extends between the foot and the ground when footwear 10 is worn. In addition to providing traction, sole structure 20 may attenuate ground reaction forces when compressed between the foot and the ground during walking, running, or other ambulatory activities. The configuration of sole structure 20 may vary significantly to include a variety of conventional or nonconventional structures. As an example, however, a suitable configuration for sole structure 20 is depicted in Figures 1 and 2, for example, as including a first sole element 21 and a second sole element 22.

[24] First sole element 21 extends through a longitudinal length of footwear 10 (i.e., through each of regions 11-13) and may be formed from a polymer foam material, such as polyurethane or ethylvinylacetate. Portions of upper 30 wrap around sides of first sole

element 21 and are secured to a lower area of first sole element 21. In each of regions 11-13, the lower area of first sole element 21 is exposed to form a portion of a ground-contacting surface of footwear 10. The portions of upper 30 that are secured to the lower area of first sole element 21 are also exposed in regions 12 and 13 and may contact the ground during use. An upper area of first sole element 21 is positioned to contact a lower (i.e., plantar) surface of the foot and forms, therefore, a foot-supporting surface within upper 30. In some configurations, however, a sockliner may be located within upper 30 and adjacent the upper area of first sole element 21 to form the foot-supporting surface of footwear 10.

[25] Second sole element 22 is located in each of regions 11 and 12 and is secured to either or both of first sole element 21 and upper 30. Whereas portions of first sole element 21 extend into upper 30, second sole element 22 is positioned on an exterior of footwear 10 to form a portion of the ground-contacting surface in regions 11 and 12. In order to impart traction, second sole element 22 includes a plurality of projections 23, which may have the configuration of removable spikes. Suitable materials for second sole element 22 include a variety of rubber or other polymer materials that are both durable and wear-resistant.

[26] Upper 30 defines a void within footwear 10 for receiving and securing the foot relative to sole structure 20. More particularly, the void is shaped to accommodate a foot and extends along the lateral side of the foot, along the medial side of the foot, over the foot, and under the foot. Access to the void is provided by an ankle opening 31 located in at least heel region 13. A lace 32 extends through various lace apertures 33 in upper 30 and permits the wearer to modify dimensions of upper 30 to accommodate feet with varying proportions. Lace 32 also permits the wearer to loosen upper 30 and facilitate removal of the foot from the void. Although not depicted, upper 30 may include a tongue that extends under lace 32 to enhance the comfort or adjustability of footwear 10.

[27] The primary elements of upper 30, in addition to lace 32, are a first embroidered element 40 and a second embroidered element 50. First embroidered element 40 forms portions of upper 30 corresponding with lateral side 14, and second embroidered element 50 forms

portions of upper 30 corresponding with medial side 15. Accordingly, each of embroidered elements 40 and 50 extend through each of regions 11-13. In general, and as described in greater detail below, upper 30 is substantially assembled by joining edges of embroidered elements 40 and 50 in forefoot region 11 and heel region 13 to impart a general shape of the void. In addition, assembling upper 30 involves incorporating lace 32 and wrapping portions of embroidered elements 40 and 50 around the sides of first sole element 21 and securing the portions to the lower area of first sole element 21.

First Embroidered Element

[28] First embroidered element 40 is depicted individually in Figure 6 as including a base layer 41 and a plurality of threads 42. An embroidery process, which will be described in greater detail below, is utilized to secure or locate threads 42 relative to base layer 41. In general, base layer 41 is a substrate to which threads 42 are secured during the embroidery process, and threads 42 are located to form structural elements in upper 30. As structural elements, threads 42 may limit the stretch of upper 30 in particular directions or threads 42 may reinforce areas of upper 30, for example.

[29] Although base layer 41 is depicted as a single element of material, base layer 41 may be formed from a plurality of joined elements. Similarly, base layer 41 may be a single layer of material, or base layer may be formed from multiple coextensive layers. As an example, base layer 41 may include a connecting layer or other securing element that bonds, secures, or otherwise joins portions of threads 42 to base layer 41.

[30] Base layer 41 defines various edges 43a-43d that are utilized for reference in the following material. Edge 43a extends through each of regions 11-13 and defines a portion of ankle opening 31. Edge 43b is primarily located in forefoot region 11 and forms end points for various threads 42. Edge 43c, which is located opposite edge 43b, is primarily located in heel region 13 and forms an opposite end point for the various threads 42. Edges 43a and 43c respectively join with second embroidered element 50 in forefoot region 11 and heel region 13 during the manufacture of footwear 10. Edge 43d, which is located opposite edge 43a, extends through each of regions 11-13 and wraps around first sole element 21 and is secured to the lower area of first sole element 21. The

specific configuration of base layer 41, and the corresponding positions and shapes of edges 43a-43d, may vary significantly depending upon the configuration of footwear 10.

[31] Base layer 41 may be formed from any generally two-dimensional material. As utilized with respect to the present invention, the term "two-dimensional material" or variants thereof is intended to encompass generally flat materials exhibiting a length and a width that are substantially greater than a thickness. Accordingly, suitable materials for base layer 41 include various textiles, polymer sheets, or combinations of textiles and polymer sheets, for example. Textiles are generally manufactured from fibers, filaments, or yarns that are, for example, either (a) produced directly from webs of fibers by bonding, fusing, or interlocking to construct non-woven fabrics and felts or (b) formed through a mechanical manipulation of yarn to produce a woven fabric. The textiles may incorporate fibers that are arranged to impart one-directional stretch or multi-directional stretch, and the textiles may include coatings that form a breathable and water-resistant barrier, for example. The polymer sheets may be extruded, rolled, or otherwise formed from a polymer material to exhibit a generally flat aspect. Two-dimensional materials may also encompass laminated or otherwise layered materials that include two or more layers of textiles, polymer sheets, or combinations of textiles and polymer sheets. In addition to textiles and polymer sheets, other two-dimensional materials may be utilized for base layer 41. Although two-dimensional materials may have smooth or generally untextured surfaces, some two-dimensional materials will exhibit textures or other surface characteristics, such as dimpling, protrusions, ribs, or various patterns, for example. Despite the presence of surface characteristics, two-dimensional materials remain generally flat and exhibit a length and a width that are substantially greater than a thickness.

[32] Portions of threads 42 extend through base layer 41 or lie adjacent to base layer 41. In areas where threads 42 extend through base layer 41, threads 42 are directly joined or otherwise secured to base layer 41. In areas where threads 42 lie adjacent to base layer 41, threads 42 may be unsecured to base layer 41 or may be joined with a connecting layer or other securing element that bonds, secures, or otherwise joins portions of threads 42 to base layer 41. In order to form structural elements in upper 30, multiple threads 42

or sections of an individual thread 42 may be collected into one of various thread groups 44a-44e. Thread group 44a includes threads 42 that extend between edge 43b and edge 43c, thereby extending through each of regions 11-13 of footwear 10. Thread group 44b includes threads 42 that are positioned immediately adjacent to lace apertures 33 and extend radially-outward from lace apertures 33. Thread group 44c includes threads 42 that extend from thread group 44b (i.e., an area that is adjacent to lace apertures 33) to an area adjacent to edge 43d. Thread group 44d includes threads 42 that extend from edge 43c to edge 43d and are primarily located in heel region 13.

[33] Article of footwear 10 is depicted as having the general configuration of a running shoe. During walking, running, or other ambulatory activities, forces induced in footwear 10 may tend to stretch upper 30 in various directions, and the forces may be concentrated at various locations. Each of threads 42 are located to form structural elements in upper 30. More particularly, thread groups 44a-44d are collections of multiple threads 42 or sections of an individual thread 42 that form structural elements to resist stretching in various directions or reinforce locations where forces are concentrated. Thread group 44a extends through the portions of first embroidered element 40 that correspond with regions 11-13 to resist stretch in a longitudinal direction (i.e., in a direction extending through each of regions 11-13 and between edges 43b and 43c). Thread group 44b is positioned adjacent to lace apertures 33 to resist force concentrations due to tension in lace 32. Thread group 44c extends in a generally orthogonal direction to thread group 44a to resist stretch in the medial-lateral direction (i.e., in a direction extending around upper 30). In addition, thread group 44d is located in heel region 13 to form a heel counter that limits movement of the heel. Thread group 44e extends around a periphery of base layer 41 and corresponds in location with edges 43a-43d. Accordingly, threads 42 are located to form structural elements in upper 30.

[34] Threads 42 may be formed from any generally one-dimensional material. As utilized with respect to the present invention, the term "one-dimensional material" or variants thereof is intended to encompass generally elongate materials exhibiting a length that is substantially greater than a width and a thickness. Accordingly, suitable materials for threads 42 include various filaments and yarns, for example. Filaments may be formed

from a plurality of synthetic materials such as rayon, nylon, polyester, and polyacrylic, with silk being the primary, naturally-occurring exception. In addition, various engineering fibers, such as aramid fibers, para-aramid fibers, and carbon fibers, may be utilized. Yarns may be formed from at least one filament or a plurality of fibers. Whereas filaments have an indefinite length, fibers have a relatively short length and generally go through spinning or twisting processes to produce a yarn of suitable length. With regarding to yarns formed from filaments, these yarns may be formed from a single filament or a plurality of individual filaments grouped together. Yarns may also include separate filaments formed from different materials, or yarns may include filaments that are each formed from two or more different materials. Similar concepts also apply to yarns formed from fibers. Accordingly, filaments and yarns may have a variety of configurations exhibiting a length that is substantially greater than a width and a thickness. In addition to filaments and yarns, other one-dimensional materials may be utilized for threads 42. Although one-dimensional materials will often have a cross-section where width and thickness are substantially equal (e.g., a round or square cross-section), some one-dimensional materials may have a width that is greater than a thickness (e.g., a rectangular cross-section). Despite the greater width, a material may be considered one-dimensional if a length of the material is substantially greater than a width and a thickness of the material.

Second Embroidered Element

[35] Second embroidered element 50 is depicted individually in Figure 7 as including a base layer 51 and a plurality of threads 52. An embroidery process, which is similar to the embroidery process utilized to form first embroidered element 50, is utilized to secure or locate threads 52 relative to base layer 51. In general, base layer 51 is a substrate to which threads 52 are secured during the embroidery process, and threads 52 are located to form structural elements in upper 30. As structural elements, threads 52 may limit the stretch of upper 30 in particular directions or threads 52 may reinforce areas of upper 30, for example.

[36] Base layer 51 may be formed from any generally two-dimensional material, including any of the two-dimensional materials discussed above for base layer 41. Although base layer 51 is depicted as a single element of material, base layer 51 may be formed from a plurality of joined elements. Similarly, base layer 51 may be a single layer of material, or base layer may be formed from multiple coextensive layers. As an example, base layer 51 may include a connecting layer or other securing element that bonds, secures, or otherwise joins portions of threads 52 to base layer 51. Furthermore, threads 52 may be formed from any generally one-dimensional material, including any of the one-dimensional materials discussed above for threads 42.

[37] Base layer 51 defines various edges 53a-53d that are utilized for reference in the following material. Edge 53a extends through each of regions 11-13 and defines a portion of ankle opening 31. Edge 53b is primarily located in forefoot region 11 and forms end points for various threads 52. Edge 53c, which is located opposite edge 53b, is primarily located in heel region 13 and forms an opposite end point for the various threads 52. Edges 53a and 53c respectively join with second embroidered element 40 in forefoot region 11 and heel region 13 during the manufacture of footwear 10. Edge 53d, which is located opposite edge 53a, extends through each of regions 11-13 and wraps around first sole element 21 and is secured to the lower area of first sole element 21. The specific configuration of base layer 51, and the corresponding positions and shapes of edges 53a-53d, may vary significantly depending upon the configuration of footwear 10.

[38] Portions of threads 52 may extend through base layer 51 or lie adjacent to base layer 51. In areas where threads 52 extend through base layer 51, threads 52 are directly joined or otherwise secured to base layer 51. In areas where threads 52 lie adjacent to base layer 51, threads 52 may be unsecured to base layer 51 or may be joined with a connecting layer or other securing element that bonds, secures, or otherwise joins portions of threads 52 to base layer 51. In order to form structural elements in upper 30, multiple threads 52 or sections of an individual thread 52 may be collected into one of various thread groups 54a-54e. Thread group 54a includes threads 52 located in forefoot region 11 and forward portions of midfoot region 12, and the various threads 52 in thread group 54a extend rearward and in the longitudinal direction from edge 53b. Thread group 54b includes

threads 52 that are positioned immediately adjacent to lace apertures 33 and extend radially-outward from lace apertures 33. Thread group 54c includes threads 52 that extend from thread group 54b (i.e., an area that is adjacent to lace apertures 33) to an area adjacent to edge 53d. Thread group 54d includes threads 52 that extend from edge 53c to edge 53d and are primarily located in heel region 13. Thread group 54e includes threads 52 located in heel region 13 and rearward portions of midfoot region 12, and the various threads 52 in thread group 54e extend forward and in the longitudinal direction from edge 53c. Thread group 54f extends around a periphery of base layer 51 and corresponds in location with edges 53a-53d.

[39] As discussed with respect to first embroidered element 40, forces induced in footwear 10 may tend to stretch upper 30 in various directions, and the forces may be concentrated at various locations. Each of threads 52 are located to form structural elements in upper 30. More particularly, thread groups 54a-54e are collections of multiple threads 52 or sections of an individual thread 52 that form structural elements to resist stretching in various directions or reinforce locations where forces are concentrated. Thread group 54a extends through the portions of second embroidered element 50 that correspond with at least forefoot region 11 to resist stretch in a longitudinal direction. Thread group 54b is positioned adjacent to lace apertures 33 to resist force concentrations due to tension in lace 32. Thread group 54c extends in a generally orthogonal direction to thread groups 54a and 54e to resist stretch in the medial-lateral direction (i.e., in a direction extending around upper 30). Thread group 54d is located in heel region 13 to form an opposite side of the heel counter that limits movement of the heel. In addition, thread group 54e is located in at least heel region 13 to resist stretch in a longitudinal direction. Accordingly, threads 52 are located to form structural elements in upper 30.

Structural Elements

[40] As discussed in the Background section above, a conventional upper may be formed from multiple material layers that each impart different properties to various areas of the upper. During use, an upper may experience significant tensile forces, and one or more layers of material are positioned in areas of the upper to resist the tensile forces. That is,

individual layers may be incorporated into specific portions of the upper to resist tensile forces that arise during use of the footwear. As an example, a woven textile may be incorporated into an upper to impart stretch resistance in the longitudinal direction. A woven textile is formed from yarns that interweave at right angles to each other. If the woven textile is incorporated into the upper for purposes of longitudinal stretch-resistance, then only the yarns oriented in the longitudinal direction will contribute to longitudinal stretch-resistance, and the yarns oriented orthogonal to the longitudinal direction will not generally contribute to longitudinal stretch-resistance. Approximately one-half of the yarns in the woven textile are, therefore, superfluous to longitudinal stretch-resistance. As a further example, the degree of stretch-resistance required in different areas of the upper may vary. Whereas some areas of the upper may require a relatively high degree of stretch-resistance, other areas of the upper may require a relatively low degree of stretch-resistance. Because the woven textile may be utilized in areas requiring both high and low degrees of stretch-resistance, some of the yarns in the woven textile are superfluous in areas requiring the low degree of stretch-resistance. In each of these examples, the superfluous yarns add to the overall mass of the footwear, without adding beneficial properties to the footwear. Similar concepts apply to other materials, such as leather and polymer sheets, that are utilized for one or more of wear-resistance, flexibility, air-permeability, cushioning, and moisture-wicking, for example.

[41] Based upon the above discussion, materials utilized in the conventional upper formed from multiple layers of material may have superfluous portions that do not significantly contribute to the desired properties of the upper. With regard to stretch-resistance, for example, a layer may have material that imparts (a) a greater number of directions of stretch-resistance or (b) a greater degree of stretch-resistance than is necessary or desired. The superfluous portions of these materials may, therefore, add to the overall mass of the footwear without contributing beneficial properties.

[42] In contrast with the conventional layered construction, upper 30 is constructed to minimize the presence of superfluous material. Base layers 41 and 51 provide a covering for the foot, but exhibit a relatively low mass. Some of threads 42 and 52 (i.e., thread groups 44a, 54a, 44c, 54c, 44d, 54d, and 54e) are located to provide stretch-resistance in

particular, desired directions, and the number of threads 42 and 52 are selected to impart only the desired degree of stretch-resistance. Other threads 42 and 52 (i.e., thread groups 44b, 44e, 54b, and 54f) are located to reinforce specific areas of upper 20. Accordingly, the orientations, locations, and quantity of threads 42 and 52 are selected to provide structural elements that are tailored to a specific purpose.

[43] Each of thread groups 44a-44d and 54a-54e are groups of threads 42 and 52 that provide structural elements, as described above. More particularly, however, thread group 44a is located to provide longitudinal stretch-resistance on lateral side 14, and the number of threads 42 in thread group 44a is selected to provide a specific degree of stretch-resistance. Similarly, thread groups 54a and 54e are located to provide longitudinal stretch-resistance in regions 11 and 13 of medial side 15, and the number of threads 52 in thread groups 54a and 54e are selected to provide a specific degree of stretch-resistance in regions 11 and 13. Each of thread groups 44b and 54b reinforce lace apertures 33, and the numbers of threads around each lace aperture 33 is selected to provide specific degrees of reinforcement. Each of thread groups 44c and 54c extend from lace apertures 33 and are selected to provide a specific degree of stretch-resistance in a direction extending around upper 30, and the number of threads 42 in thread groups 44c and 54c is selected to provide a specific degree of stretch-resistance. Furthermore, thread groups 44d and 54d are located to form a heel counter, and the number of threads in thread groups 44d and 54d impart a specific degree of stability to the heel counter. Thread groups 44e and 54f reinforce edges of embroidered elements 40 and 50, including portions of embroidered elements 40 and 50 that form ankle opening 31 and portions of embroidered elements 40 and 50 that are joined to each other or to other portions of footwear 10. Accordingly, the properties imparted by threads 42 and 52 at least partially depend on the orientations, locations, and quantity of threads 42 and 52.

[44] Depending upon the specific configuration of footwear 10 and the intended use of footwear 10, base layers 41 and 51 may be non-stretch materials, materials with one-directional stretch, or materials with two-directional stretch, for example. In general, materials with two-directional stretch provide upper 30 with a greater ability to conform with the contours of the foot, thereby enhancing the comfort of footwear 10. In

configurations where base layers 41 and 51 have two-directional stretch, the combination of base layers 41 and 51 and threads 42 and 52 effectively vary the stretch characteristics of upper 30 in specific locations. With regard to first embroidered element 40, the combination of base layer 41 with two-directional stretch and threads 42 forms zones in upper 30 that have different stretch characteristics, and the zones include (a) first zones where no threads 42 are present and upper 30 exhibits two-directional stretch, (b) second zones where threads 42 are present and do not cross each other, and upper 30 exhibits one-directional stretch in a direction that is orthogonal to threads 42, and (c) third zones where threads 42 are present and do cross each other, and upper 30 exhibits substantially no stretch. Similar concepts apply to second embroidered element 50.

[45] The first zones includes areas where no threads are present. Referring to Figure 6, examples of the first zones are identified by reference numerals 45a and are locations where no threads 42 are present. Because threads 42 are not present in the first zones, base layer 41 is not restrained by threads 42 and upper 30 is free to stretch in two-directions. The second zones include areas where threads 42 are present, but do not cross each other at substantially right angles. Referring to Figure 6, examples of the second zones are identified by reference numerals 45b. Because threads 42 are substantially aligned in the second zones, threads 42 resist stretch in the direction aligned with threads 42 lie. Threads 42 do not, however, resist stretch in directions orthogonal to threads 42. Accordingly, base layer 41 is free to stretch in the direction that is orthogonal to threads 42, thereby providing upper 30 with one-directional stretch. In some configurations, base layer 41 may stretch by at least ten percent in the direction that is orthogonal to threads 42, whereas base layer 41 is substantially non-stretch in the direction aligned with threads 42. The third zones include areas where threads 42 are present and cross each other at substantially right angles (i.e., at angles greater than sixty degrees). Referring to Figure 6, examples of the third zones are identified by reference numerals 45c. Because threads 42 cross each other at substantially right angles, threads 42 resist stretch in substantially all directions. Accordingly, base layer 41 is not free to stretch in any direction, thereby providing a relatively non-stretch configuration to upper 30 in the third zones. Similar concepts apply to second embroidered element 50, and examples of areas corresponding with the first zones are identified by reference numerals 55a in Figure 7, areas

corresponding with the second zones are identified by reference numerals 55b in Figure 7, and areas corresponding with the third zones are identified by reference numerals 55c in Figure 7.

[46] Transitions between the zones occur at interfaces between areas where the relative numbers and orientations of threads 42 and 52 change. At the interface between zones, upper 30 may change from having two-directional stretch to one-directional stretch, from having two-directional stretch to no stretch, or from having one-directional stretch to no stretch, for example. Given that the difference between zones is the relative numbers and orientations of threads 42 and 52, the transitions between zones may occur abruptly. That is, in the space of a thickness of one of threads 42 and 52, upper 30 may transition from one zone to another zone. Various structures may be employed to decrease the abruptness of a transition between zones. For example, threads 42 and 52 that are adjacent to a zone transition may have stretch characteristics. When transitioning from the first zone to the second zone, for example, the stretch characteristics of threads 42 and 52 at the interface will decrease the abruptness of the transition. Structurally, threads 42 and 52 adjacent to a transition (i.e., near the boundary of a thread group) may have greater stretch than threads 42 and 52 further from the transition (i.e., near the center of a thread group). In addition to stretch, threads 42 and 52 formed from a non-stretch material may have a crimped (i.e., zigzag) shape to permit degrees of stretch at the transition.

[47] Threads 42 and 52 may be utilized to modify properties of footwear 10 other than stretch-resistance. For example, threads 42 and 52 may be utilized to provide additional wear-resistance in specific areas of upper 30. For example, threads 42 and 52 may be concentrated in areas of upper 30 that experience wear, such as in forefoot region 11 and adjacent to sole structure 20. If utilized for wear-resistance, threads 42 and 52 may be selected from materials that also exhibit relatively high wear-resistance properties. Threads 42 and 52 may also be utilized to modify the flex characteristics of upper 30. That is, areas with relatively high concentrations of threads 42 and 52 may flex to a lesser degree than areas with relatively low concentrations of threads 42 and 52. Similarly,

areas with relatively high concentrations of threads 42 and 52 may be less air-permeable than areas with relatively low concentrations of threads 42 and 52.

[48] The orientations, locations, and quantity of threads 42 and 52 in Figures 1-7 are intended to provide an example of a suitable configuration for footwear 10 within various aspects of the invention. In other configurations for footwear 10, various thread groups 44a-44d and 54a-54e may be absent, or additional thread groups may be present to provide further structural elements in footwear 10. If further longitudinal stretch-resistance is desired, then a thread group similar to thread group 44a may be included on medial side 14, or thread groups 54a and 54e may be modified to extend through midfoot region 12. If further stretch-resistance around upper 30 is desired, then additional threads 42 and 52 may be added to thread groups 44c and 54c. Similarly, further stretch-resistance around upper 30 may be provided by adding a thread group that extends around forefoot region 11 or a thread group that extends around heel region 13.

[49] The running style or preferences of an individual may also determine the orientations, locations, and quantity of threads 42 and 52. For example, some individuals may have a relatively high degree of pronation (i.e., an inward roll of the foot), and having a greater number of threads 42 in thread group 44c may reduce the degree of pronation. Some individuals may also prefer greater longitudinal stretch resistance, and footwear 10 may be modified to include further threads 42 in thread group 44a. Some individuals may also prefer that upper 30 fit more snugly, which may require adding more threads 42 and 52 to thread groups 44b, 44c, 54b, and 44c. Accordingly, footwear 10 may be customized to the running style or preferences of an individual through changes in the orientations, locations, and quantity of threads 42 and 52.

[50] Base layers 41 and 51 are depicted as having a configuration that cooperatively covers substantially all of the medial and lateral sides of the foot. As discussed above, base layers 41 and 51 are substrates to which threads 42 and 52 are secured during the embroidery process. In some configurations, however, portions of base layers 41 and 51 may be absent such that threads 42 and 52 are positioned immediately adjacent the foot or a sock worn over the foot. That is, base layers 41 and 51 may be formed with

apertures or cut-outs that expose the foot. In other configurations, base layers 42 and 52 or portions thereof may be formed from a water-soluble material that is removed following the embroidery process. That is, upper 30 may be dissolved following securing threads 42 and 52 to base layers 41 and 51. Accordingly, base layers 41 and 51 may be partially or entirely absent in some configurations of footwear 10.

[51] A majority of the overall lengths of threads 42 and 52 lie adjacent to base layers 41 and 51, but are not directly secured to base layers 41 and 51. In order to ensure that threads 42, for example, remain properly-positioned, a connecting layer or other securing element that bonds, secures, or otherwise joins portions of threads 42 to base layer 41 may be utilized. The connecting element or other securing element may be, for example, a sheet of thermoplastic polymer that is located between threads 42 and base layer 41 and heated to bond threads 42 and base layer 41 together. The connecting element or other securing element may also be a sheet of thermoplastic polymer or a textile, for example, that extends over threads 42 and base layer 41 to bond threads 42 and base layer 41 together. In addition, the connecting element or other securing element may be an adhesive that bonds threads 42 and base layer 41 together. In some configurations, additional threads may stitched over threads 42 to secure threads 42 to base layer 41. Accordingly, a variety of structures or methods may be utilized to secure threads 42 to base layer 41. Similar concepts may be applied to join base layer 51 and threads 52.

[52] The portions of threads 42 within the various thread groups 44a, 44c, and 44d may be substantially parallel to each other. As depicted in Figure 6, for example, the distances between the portions of threads 42 actually change. That is, threads 42 radiate outward. With regard to thread group 44a, the various threads 42 are relatively close to each other in midfoot region 12. As threads 42 extend toward forefoot region 11 and heel region 13, however, the distances between individual threads 42 increases. Accordingly, threads 42 radiate outward in forefoot region 11 and heel region 13. Similarly, the various threads 42 in thread groups 44c also radiate outward and away from lace apertures 33. In portions of upper 30 that are close to lace apertures 33, threads 42 are relatively close to each other, but tend to separate or radiate outward in portions of upper 30 that are further from lace apertures 33. The radiating characteristic discussed above may operate, for

example, to distribute forces from a relatively small area (e.g., each of lace apertures 33) to a larger area. That is, the radiating characteristic may be utilized to distribute forces over areas of upper 30.

[53] Based upon the above discussion, upper 30 is at least partially formed through an embroidery process that forms structural elements from threads 42 and 52. Depending upon the orientations, locations, and quantity of threads 42 and 52, different structural elements may be formed in upper 30. As examples, the structural elements may impart stretch-resistance to specific areas, reinforce areas, enhance wear-resistance, modify the flexibility, or provide areas of air-permeability. Accordingly, by controlling the orientations, locations, and quantity of threads 42 and 52, the properties of upper 30 and footwear 10 may be controlled.

Embroidery Process

[54] An example of a method for manufacturing each of embroidered elements 40 and 50 is depicted in Figures 8A-8O. In general, the various steps utilized to form first embroidered element 40 are similar to the steps utilized to form second embroidered element 50. Accordingly, the following discussion focuses upon the manufacturing method for first embroidered element 40, with an understanding that second embroidered element 50 may be manufactured in a similar manner.

[55] First embroidered element 40 is at least partially formed through an embroidery process, which may be performed by either machine or hand. With regard to machine embroidery, a variety of conventional embroidery machines may be utilized to form first embroidered element 40, and the embroidery machines may be programmed to embroider specific patterns or designs from one or a plurality of threads. In general, an embroidery machine forms patterns or designs by repeatedly securing a thread to various locations such that portions of the thread extend between the locations and are visible. More particularly, the embroidery machine forms a series of lock-stitches by (a) piercing a first location of base layer 41 with a needle to pass a first loop of thread 42 through base layer 41, (b) securing the first loop of thread 42 with another thread that passes through the first loop, (c) moving the needle to a second location such that thread 42 extends from the

first location to the second location and is visible on a surface of base layer 41, (d) piercing the second location of base layer 41 with the needle to pass a second loop of thread 42 through base layer 41, and (e) securing the second loop of thread 42 with the other thread that passes through the second loop. Accordingly, the embroidery machine operates to secure thread 42 to two defined locations and also extend thread 42 between the two locations. By repeatedly performing these steps, embroidery is formed by thread 42 on base layer 41.

[56] Conventional embroidery machines may form patterns or designs on base layer 41 by forming satin-stitches, running-stitches, or fill-stitches, each of which may utilize a lock-stitch to secure thread 42 to base layer 41. Satin-stitches are a series of zigzag-shaped stitches formed closely together. Running-stitches extend between two points and are often used for fine details, outlining, and underlay. Fill-stitches are series of running stitches formed closely together to form different patterns and stitch directions, and fill-stitches are often utilized to cover relatively large areas. With regard to satin-stitches, conventional embroidery machines generally limit satin stitches to twelve millimeters. That is, the distance between a first location and a second location where a thread is secured to a base layer is conventionally limited to twelve millimeters when an embroidery machine is forming satin-stitches. Conventional satin-stitch embroidery, therefore, involves threads that extend between locations separated by twelve millimeters or less. Forming embroidered element 40, however, may require that the embroidery machine be modified to form satin-stitches extending between locations spaced by more than twelve millimeters. In some aspects of the invention, stitches may be spaced by more than five centimeters, for example. That is, a thread may be continuously exposed on a surface of base layer 41 by more than twelve millimeters or by more than five centimeters, for example.

[57] With respect to Figure 8A, base layer 41 is depicted in combination with a hoop 60, which has the configuration of a conventional rectangular hoop utilized in embroidery operations. The primary elements of hoop 60 are an outer ring 61, an inner ring 62, and a tensioner 63. As is known in the art, outer ring 61 extends around inner ring 62, and peripheral portions of base layer 41 extend between outer ring 61 and inner ring 62.

Tensioner 63 adjusts the tension in outer ring 61 such that inner ring 62 is positioned within outer ring 61 and base layer 41 is firmly held in place. In this configuration, a central area of base layer 41 is positioned on a single plane and may be in slight tension in order to ensure that base layer 41 is securely-positioned during further steps of the manufacturing process. In general, therefore, hoop 60 is utilized as a frame that securely-positions base layer 41 during the embroidery operation that forms first embroidered element 40.

[58] Once base layer 41 is secured within hoop 60, an embroidery machine begins locating and securing threads 42 to base layer 41. Initially, the embroidery machine forms an outline of first embroidered element 40, as depicted in Figure 8B. The outline includes thread group 44e, which extends around the perimeter of first embroidered element 40 and corresponds with edges 43a-43d. The portion of edge 43a that forms ankle opening 31 is depicted as having a thicker configuration than other areas of thread group 44e, which imparts reinforcement to ankle opening 31. In further configurations of first embroidered element 40, all of thread group 44e may exhibit the thicker configuration, or the portion of edge 43a that forms ankle opening 31 may have a relatively thin configuration. Furthermore, thread group 44e may be partially or entirely absent in some configurations of first embroidered element 40. Various types of stitches may be utilized to form thread group 44e, including satin-stitches, running-stitches, fill-stitches, or combinations thereof.

[59] Following the formation of thread group 44e, thread group 44a may be formed. Referring to Figure 8C, a portion 42a of thread 42 extends between two points that are positioned outside of first embroidered element 40. End points of portion 42a are secured with a lock-stitch, and the central area of portion 42a (i.e., the area of portion 42a other than the end points) lies adjacent to base layer 41 and is unsecured to base layer 41. That is, the central area of portion 42a is continuously exposed on the surface of base layer 41. The embroidery machine then form a relatively short portion 42b of thread 42, and also forms another portion 42c that crosses portion 42a, as depicted in Figure 8D. This general procedure then repeats until thread group 44a is completed, as depicted in Figure 8E.

[60] Thread group 44c is formed in a manner that is similar to thread group 44a. Referring to Figure 8F, a portion 42d of thread 42 extends between two points that are positioned within the outline formed by thread group 44e. End points of portion 42d are secured with a lock-stitch, and the central area of portion 42d (i.e., the area of portion 42d other than the end points) lies adjacent to base layer 41 and is unsecured to base layer 41. In addition, the central area crosses thread group 44a. The embroidery machine then form a relatively short portion 42e of thread 42, and also forms another portion 42f that also crosses thread group 44a, as depicted in Figure 8G. This general procedure then repeats until one of the various portions of thread group 44c is completed, as depicted in Figure 8H. The embroidery machine then forms one of the various portions of thread groups 44b using a plurality of satin-stitches, for example, as depicted in Figure 8I. The procedures discussed above for forming one of the various portions of thread group 44c and one of the various portions of thread groups 44b is repeated four additional times to form each of thread groups 44c and 44b, as depicted in Figure 8J.

[61] In some configurations, the ends of thread group 44c may abut a perimeter of thread group 44b. As depicted in the figures, however, thread group 44c extends beyond a perimeter of thread group 44b. That is, thread group 44c may extend over the thread 42 that forms thread group 44b, or thread group 44b may extend over the thread 42 that forms thread group 44c. More particularly, the thread 42 from each of thread groups 44b and 44c may be intertwined. When lace 32 extends through lace apertures 33 and is tensioned, thread group 44b reinforces lace apertures 33 and thread group 44c distributes the tensile force along the sides of upper 30. By intertwining thread groups 44b and 44c, forces upon lace apertures 33 are more effectively transmitted to thread group 44c.

[62] Thread group 44d is formed in a manner that is similar to thread groups 44a and 44c. Referring to Figure 8K, a portion 42g of thread 42 extends between two points that are positioned adjacent to the outline formed by thread group 44e in heel region 13. End points of portion 42d are secured with a lock-stitch, and the central area of portion 42d (i.e., the area of portion 42d other than the end points) lies adjacent to base layer 41 and is unsecured to base layer 41. That is, the central area of portion 42d is continuously exposed on the surface of base layer 41. In addition, the central area crosses thread group

44a. This general procedure then repeats until thread group 44d is completed, as depicted in Figure 8L.

[63] Once thread group 44d is completed, lace apertures 33 may be formed through base layer 41 in areas that correspond with the centers of thread groups 44b. In addition, first embroidered element 40 may be cut from portions of base layer 41 that are outside of thread group 44e, thereby forming edges 43a-43d, as depicted in Figure 8M. In cutting first embroidered element 40 from extraneous portions of base layer 41, portions of thread 42 that forms thread group 44a are severed. As noted above, base layer 41 may include a connecting layer or other securing element that bonds, secures, or otherwise joins portions of threads 42 to base layer 41. The connecting layer or other securing element, which is described in greater detail below, may be added or utilized prior to cutting first embroidered element 40 from extraneous portions of base layer 41.

[64] The general procedure described above and depicted in Figures 8A-8M for forming first embroidered element 40 discusses a particular order for forming each of thread groups 44a-44e. In the order discussed, thread groups 44c and 44d cross over thread group 44a, which places thread group 44a between base layer 41 and thread groups 44c and 44d. The discussed order also forms thread groups 44b and 44c in a generally concurrent manner. That is, a portion of thread group 44c was formed, then a portion of thread group 44b was formed, and this procedure repeated until each of thread groups 44b and 44c were completed. The order discussed above is, however, an example of the various orders that may be used to form first embroidered element 40, and a variety of other orders for forming each of thread groups 44a-44e may also be utilized. Accordingly, the general procedure described above and depicted in Figures 8A-8M provides an example of the manner in which first embroidered element 40 may be made, and a variety of other procedures may alternately be utilized.

[65] Second embroidered element 50 is formed through an embroidery process that may be similar to the process for forming first embroidered element 40. With reference to Figure 8N, second embroidered element 50 is depicted following the embroidery process that forms thread groups 54a-54f. Lace apertures 33 may then be formed through base layer

51 in areas that correspond with the centers of thread groups 54b. In addition, second embroidered element 50 may be cut from portions of base layer 51 that are outside of thread group 54f, thereby forming edges 53a-53d, as depicted in Figure 8O. Prior to cutting second embroidered element 50 from extraneous portions of base layer 51, a connecting layer or other securing element that bonds, secures, or otherwise joins portions of threads 52 to base layer 51 may be added, as described in greater detail below. As with first embroidered element 40, a variety of orders for forming each of thread groups 54a-54f may be utilized.

Footwear Assembly

[66] Footwear 10 is assembled once embroidered element 40 and 50 are formed in the manner discussed above. An example of one manner in which footwear 10 may be assembled is depicted in Figures 9A-9D. Initially, the manufacture of upper 30 is substantially completed by securing embroidered elements 40 and 50 together in forefoot region 11 and heel region 13, as depicted in Figure 9A. More particularly, forward portions of edges 43a and 53a are joined, and each of edges 43c and 53c are also joined. Various types of stitching or adhesives, for example, may be utilized to join embroidered elements 40 and 50.

[67] Following the completion of upper 30, sole elements 21 and 22 are positioned, as depicted in Figure 9B. First sole element 21 is then located between embroidered elements 40 and 50 such that lower portions of embroidered elements 40 and 50 wrap around sides of first sole element 21. An adhesive, for example, is then utilized to secure the lower portions of embroidered elements 40 and 50 to the lower area of first sole element 21, as depicted in Figure 9C. When assembled in this manner, then upper area of first sole element 21 is positioned to provide a foot-supporting surface within upper 30. In some configurations, however, a sockliner may be located within upper 30 and adjacent the upper area of first sole element 21 to form the foot-supporting surface of footwear 10.

[68] Second sole element 22 is then secured (e.g., with an adhesive) to first sole element 21 and embroidered elements 40 and 50, as depicted in Figure 9D. In this position, each of

embroidered elements 40 and 50, first sole element 21, and second sole element 22 form portions of the ground-contacting surface of footwear 10. In order to impart additional traction, projections 23 having the form of removable spikes may be incorporated into second sole element 22. Finally, lace 32 is threaded through lace apertures 33 in a conventional manner to substantially complete the assembly of footwear 10.

Securing Element

[69] Each segment of thread 42 (e.g., portions 42a-42g) have two end points and a central portion extending between the end points. The end points are secured with a lock-stitch, and the central area (i.e., the area of a segments other than the end points) lies adjacent to base layer 41 and is unsecured to base layer 41. In order to secure the central area to base layer 41, a connecting layer that bonds, secures, or otherwise joins portions of threads 42 to base layer 41 may be utilized. The following discussion presents various methods by which a connecting layer or other securing agent may be added to first embroidered element 40. Similar concepts also apply to second embroidered element 50.

[70] One procedure for securing portions of threads 42 to base layer 41 is depicted in Figures 10A-10D. With reference to Figure 10A, first embroidered element 40 is depicted as being formed through the embroidery process, but uncut from the extraneous portions of base layer 41 (i.e., as in Figure 8L). In addition, a connecting layer 70 is depicted as being superimposed over the surface of first embroidered element 40 that includes threads 42.

[71] Connecting layer 70 is a sheet of a thermoplastic polymer material with a thickness between one-thousandth of a millimeter and three millimeters, for example. Suitable polymer materials for connecting layer 70 include polyurethane and ethylvinylacetate, for example. In order to heat connecting layer 70 and bond connecting layer 70 to first embroidered element 40, connecting layer 70 and first embroidered element 40 are placed between a pair of platens 71 and 72 of a heated press, as depicted in Figure 10B. As the temperature of connecting layer 70 rises, the polymer material forming connecting layer 70 rises such that the polymer material infiltrates the structures of base layer 41 and threads 42. Upon removal from the heated press, connecting layer 70 cools and

effectively bonds threads 42 to base layer 41, as depicted in Figure 10C. First embroidered element 40 may then be cut from extraneous portions of base layer 41.

[72] Connecting layer 70 ensures that thread group 44a remains intact following the removal of first embroidered element 40 from the extraneous portions of base layer 41. In addition, connecting layer 70 ensures that portions of thread groups 44c and 44d, for example, remain properly positioned relative to base layer 41. Although end portions of the various segments of thread 42 that form thread groups 44c and 44d are secured to base layer 41 with lock-stitches, the central portions are unsecured to base layer 41 without the presence of connecting layer 70. Accordingly, connecting layer 70 effectively bonds each of threads 42 to base layer 41.

[73] Base layer 41 may exhibit an air-permeable structure that allows perspiration and heated air to exit upper 20. The addition of connecting layer 70 may, however, decrease the degree to which upper 20 is air-permeable. Whereas connecting layer 70 is depicted in Figure 10A as having a discontinuous structure, connecting layer 70 may also be formed to have various apertures that correspond with areas of first embroidered element 40 where connecting layer 70 is not desired. Accordingly, apertures in connecting layer 40 may be utilized to enhance the air-permeable properties of upper 30. In addition, decreasing the quantity of material utilized for connecting layer 70 has an advantage of minimizing the mass of footwear 10.

[74] Another procedure for securing portions of threads 42 to base layer 41 is depicted in Figures 11A-11D. With reference to Figure 11A, base layer 41 is depicted as being joined to connecting layer 70 prior to the addition of threads 42. The embroidery process is then utilized to form thread groups 44a-44e such that connecting layer 70 is between base layer 41 and threads 42, as depicted in Figure 11B. In order to heat connecting layer 70 and bond threads 42 to base layer 41, connecting layer 70 and first embroidered element 40 are placed between the platens 71 and 72 of a heated press, as depicted in Figure 11C. Upon removal from the heated press, connecting layer 70 cools and effectively bonds threads 42 to base layer 41. First embroidered element 40 may then be cut from extraneous portions of base layer 41, as depicted in Figure 11D. During the

embroidery process, threads 42 may be placed in tension, which tends to pull inward on base layer 41. An advantage to applying connecting layer 70 to base layer 41 prior to the embroidery process is that connecting layer 70 assists in resisting the inward pull of threads 42.

[75] Yet another procedure for securing portions of threads 42 to base layer 41 is depicted in Figures 12A-12C. With reference to Figure 12A, first embroidered element 40 is depicted as being formed through the embroidery process, but uncut from the extraneous portions of base layer 41 (i.e., as in Figure 8L). An adhesive securing element is then sprayed or otherwise applied to first embroidered element 40, as depicted in Figure 12B, thereby securing threads 42 to base layer 41. First embroidered element 40 may then be cut from extraneous portions of base layer 41, as depicted in Figure 12C.

Conclusion

[76] Based upon the above discussion, upper 30 is at least partially formed through an embroidery process that forms structural elements from threads 42 and 52. Depending upon the orientations, locations, and quantity of threads 42 and 52, different structural elements may be formed in upper 30. As examples, the structural elements may impart stretch-resistance to specific areas, reinforce areas, enhance wear-resistance, modify the flexibility, or provide areas of air-permeability. Accordingly, by controlling the orientations, locations, and quantity of threads 42 and 52, the properties of upper 30 and footwear 10 may be controlled.

[77] The invention is disclosed above and in the accompanying drawings with reference to a variety of embodiments. The purpose served by the disclosure, however, is to provide an example of the various features and concepts related to aspects of the invention, not to limit the scope of aspects of the invention. One skilled in the relevant art will recognize that numerous variations and modifications may be made to the embodiments described above without departing from the scope of the invention, as defined by the appended claims.

CLAIMS

That which is claimed is:

1. An article of footwear having an upper and a sole structure secured to the upper, the upper comprising:

a textile layer at least partially formed from a plurality of yarns, the textile layer having a first surface and an opposite second surface, the textile layer defining a first area and a second area spaced apart by a distance of at least five centimeters, and the textile layer defining a third area and a fourth area also spaced apart by a distance of at least five centimeters;

a first thread group having first thread sections that extend between the first area and the second area, the first thread sections lying adjacent to the first surface and substantially parallel to the first surface, and the first thread sections being separate from the yarns of the textile layer; and

a second thread group having second thread sections extending between the third area and the fourth area, the second thread sections lying adjacent to the first surface and substantially parallel to the first surface, and the second thread sections being separate from the yarns of the textile layer,

wherein at least some of the first thread sections are oriented to extend in a first direction, and at least some of the second thread sections cross the first thread sections and are oriented to extend in a second direction.

2. The article of footwear recited in claim 1, wherein the first area is in a forefoot region of the upper and the second area is in a heel region of the upper.

3. The article of footwear recited in claim 2, wherein the third area is adjacent a lace receiving portion of the upper and the fourth area is adjacent the sole structure.

4. The article of footwear recited in claim 3, wherein the upper includes a third thread group having third thread sections extending around the lace receiving portion.

5. The article of footwear recited in claim 4, wherein the lace receiving portion is an aperture extending through the textile layer.

6. The article of footwear recited in claim 1, wherein the first thread sections do not extend through the textile layer in an area located between the first area and the second area, and the second thread sections do not extend through the textile layer in an area located between the third area and the fourth area.

7. The article of footwear recited in claim 1, wherein the textile layer stretches at least ten percent prior to tensile failure, and the first thread sections and the second thread sections restrain stretch of the textile layer in directions corresponding with longitudinal axes of the first thread sections and the second thread sections.

8. The article of footwear recited in claim 1, wherein the first thread sections are formed from an individual thread.

9. The article of footwear recited in claim 8, wherein the second thread sections are formed from the individual thread.

10. The article of footwear recited in claim 1, wherein the first direction is offset by at least sixty degrees from the second direction

11. An article of footwear having an upper and a sole structure secured to the upper, the upper comprising:

a textile layer at least partially formed from a plurality of yarns, the textile layer having a first surface and an opposite second surface;

a plurality of first thread sections extending from a forefoot region of the upper to a heel region of the upper, the first thread sections lying adjacent to the first surface and not extending through the first surface in an area between the forefoot region and the heel region, and the first thread sections being separate from the yarns of the textile layer;

a plurality of second thread sections extending from an upper area of the upper to a lower area of the upper, the second thread sections lying adjacent to the first surface and not extending through the first surface in an area between the upper area and the lower area, and the second thread sections being separate from the yarns of the textile layer,

the first thread sections and the second thread sections having a crossed configuration.

12. The article of footwear recited in claim 11, wherein the upper includes a plurality of third thread sections extending around lace receiving portions of the upper.

13. The article of footwear recited in claim 12, wherein the lace receiving portions are apertures extending through the textile layer.

14. The article of footwear recited in claim 11, wherein the upper includes a plurality of third thread sections that are positioned in the heel region and extend from the upper area to the lower area.

15. The article of footwear recited in claim 11, wherein the upper includes a plurality of third thread sections that are positioned adjacent edges of the textile layer.

16. The article of footwear recited in claim 11, wherein the textile layer is a material with at least two-directional stretch, and the upper including:

a first zone wherein the upper has two-directional stretch properties, the first thread sections and the second thread sections being absent from the first zone;

a second zone wherein the upper has one-directional stretch properties, only one of the first thread sections and the second thread sections being present in the second zone; and

a third zone wherein the upper has substantially non-stretch properties, each of the first thread sections and the second thread sections being present in the third zone.

17. The article of footwear recited in claim 11, wherein either (a) the first thread sections extend between the second thread sections and the textile layer or (b) the second thread sections extend between the first thread sections and the textile layer.

18. The article of footwear recited in claim 11, wherein the upper includes a securing element that joins the first thread sections and the second thread sections to the textile layer, and the securing element is a layer of polymer material that bonds the first thread sections and the second thread sections to the textile layer.

19. The article of footwear recited in claim 11, wherein the upper includes a securing element that joins the first thread sections and the second thread sections to the textile layer, and the securing element is an adhesive applied to at least the textile layer.

20. The article of footwear recited in claim 11, wherein the textile layer forms at least a section of a lateral side of the upper, and the upper includes another textile layer with thread sections that either extend (a) in a direction corresponding with a direction between the forefoot region and the heel region or (b) from the upper area of the upper to the lower area of the upper.

21. An article of footwear having an upper and a sole structure secured to the upper, at least a portion of the upper comprising:

a base layer having a first surface and an opposite second surface; and

a plurality of thread sections that are separate from the base layer and lie adjacent to at least a portion of the first surface, at least a portion of the thread sections being substantially aligned,

the upper defining a first direction corresponding with longitudinal axes of the thread sections, and the upper defining a second direction that is orthogonal to the first direction, the upper being substantially non-stretch in the first direction, and the upper being stretchable by at least ten percent in the second direction.

22. The article of footwear recited in claim 21, wherein the base layer is a textile material that stretches at least ten percent prior to tensile failure.

23. The article of footwear recited in claim 22, wherein the thread sections are substantially non-stretch.

24. The article of footwear recited in claim 21, wherein the thread sections extend in a direction of a longitudinal length of the footwear.

25. The article of footwear recited in claim 21, wherein the thread sections cross each other.

26. The article of footwear recited in claim 21, wherein the thread sections extend from an upper area to a lower area of the upper.

27. The article of footwear recited in claim 21, wherein a securing element joins the thread sections to the base layer, and the securing element is a layer of polymer material.

28. The article of footwear recited in claim 21, wherein a securing element joins the thread sections to the base layer, and the securing element is an adhesive applied to at least the base layer.

29. The article of footwear recited in claim 21, wherein a portion of the thread sections are not parallel.

30. The article of footwear recited in claim 21, wherein the thread sections are formed from different threads with different properties.




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5



40
41
42
42
33
33
33
43a
43b
43c
43d
44a
44b
44c
44d
44e
45a
45b
45c

Figure 6




Figure 7




Figure 8A




Figure 8B




Figure 8C




Figure 8D




Figure 8E




Figure 8F




Figure 8G




Figure 8H




Figure 8I



60
63
44b
44c
44a
44e
42
40
62
44b
44b
44b
44b
44b
44c
44c
44c
41
44e
42
61
44a

Figure 8J




Figure 8K



60
63
62
40
41
61
44a
44c
44e
42
44b
44b
44b
44b
44b
44c
44c
44e
42
44d
44a
42
44d

Figure 8L



40
41
44a
44e
44c
33
42
44b
44b
44b
44b
33
44c
44c
44e
42
44d
44d
42

Figure 8M




Figure 8N




Figure 80




Figure 9A



20
44a
42
41
44e
40
50
30
23
22
23
33
44c
44b
54f
52
51
21
50
31
40
44d

Figure 9B




Figure 9C





Figure 9D

Figure 10A






Figure 10B




Figure 10C




Figure 10D




Figure 11A




Figure 11B




Figure 11C




Figure 11D




Figure 12A




Figure 12B




Figure 12C

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2007/066696

A. CLASSIFICATION OF SUBJECT MATTER
INV. A43B9/02 A43B23/02 A43D8/16

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
A43B A43D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)
EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 98/43506 A (FILA USA INC [US]) 8 October 1998 (1998-10-08)	1-5, 7-17, 20-30
Y	page 5, line 4 - page 11, line 23 page 13, line 33 - page 14, line 29; figures 5c,5d	6,18,19
Y	FR 1 462 349 A (PIERRE FLORENCE) 24 February 1967 (1967-02-24) page 2; figures	6,18,19
A	FR 2 457 651 A1 (FRAPIMA SARL FRAPIMA SARL [FR]) 26 December 1980 (1980-12-26) the whole document	1-30
A	US 2 205 356 A (ROSE GRUENSFELDER ET AL) 18 June 1940 (1940-06-18) the whole document	1-30

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
29 August 2007	07/09/2007

Name and mailing address of the ISA/	Authorized officer
European Patent Office, P.B. 5818 Patentlaan 2 NL – 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Cianci, Sabino

Form PCT/ISA/210 (second sheet) (April 2005)

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No
PCT/US2007/066696

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9843506	A	08-10-1998	NONE	
FR 1462349	A	24-02-1967	NONE	
FR 2457651	A1	26-12-1980	NONE	
US 2205356	A	18-06-1940	NONE	