



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) Publication number:

0 358 269 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication of patent specification: 01.12.93 (51) Int. Cl.⁵: **G11B 23/03**

(21) Application number: **89202212.0**

(22) Date of filing: **01.09.89**

(54) **Disc cassette**

(30) Priority: **05.09.88 NL 8802185**

(43) Date of publication of application:
14.03.90 Bulletin 90/11

(45) Publication of the grant of the patent:
01.12.93 Bulletin 93/48

(84) Designated Contracting States:
BE DE FR GB IT

(56) References cited:

EP-A- 0 042 062	EP-A- 0 146 656
EP-A- 0 255 185	DE-A- 2 644 894
GB-A- 2 173 631	US-A- 3 062 552
US-A- 3 593 327	US-A- 4 159 494

(73) Proprietor: **N.V. Phillips' Gloeilampenfabrieken**
Groenewoudseweg 1
NL-5621 BA Eindhoven(NL)

(72) Inventor: **Ouwerkerk, Cornelis**
c/o INT. OCTROOIBUREAU B.V.
Prof. Holstlaan 6
NL-5656 AA Eindhoven(NL)
Inventor: **Beyersbergen van Henegouwen,**
Cornelis Martin
c/o INT. OCTROOIBUREAU B.V.
Prof. Holstlaan 6
NL-5656 AA Eindhoven(NL)

(74) Representative: **Van Weele, Paul Johannes**
Frits et al
INTERNATIONAAL OCTROOIBUREAU B.V.
Prof. Holstlaan 6
NL-5656 AA Eindhoven (NL)

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

Description

FIELD OF THE INVENTION

The invention relates to a cassette, comprising a rotatable information disc whose information is readable by means of a pick-up which moves parallel to the disc-surface and which forms part of an apparatus, a housing having first and second main walls parallel to the disc, side walls, a front wall and a rear wall, which walls together bound a disc-receiving space in which the disc is rotatable, the first main wall being formed with a first opening to give a pick-up access to the disc surface.

Cassettes of this type are employed, for example, in conjunction with a magnetic disc or an optical disc for the storage of computer data. Alternatively, the disc may carry audio and/or video information. The housing of the cassette affords ample protection for the disc accommodated in it, so that cassettes of this type are very suitable for professional uses or in environments in which a careful treatment of the disc is not readily possible, such as in cars.

PRIOR ART

Cassettes of the type defined in the opening paragraph are known, for example from European Patent Application 0,255,185 A1 (herewith incorporated by reference, PHQ 86-015). This document describes a cassette having openings in both main walls, which openings can be closed by means of a slide which is movable over the exterior of the housing. When the cassette is inserted into an apparatus the cassette slide is opened against spring force by cooperation with a part provided in the apparatus, so that the two openings are freely accessible to allow the passage of a pick-up to the disc surface. The openings in the main walls take the form of rectangular slots which are symmetrical relative to a radius of the disc. Consequently, the openings cannot be wider than maximum 1/3 of the width of the cassette.

In practice, it is found that even such a wide opening is not always adequate. In principle, optical discs are read by means of two types of optical devices, namely translating devices or pivoting devices. In order to preclude problems in reading the optical information of the disc pick-ups in translating devices are preferably moved over the disc surface in such a way that the read objective moves along a radius of the disc. The objective is suspended so as to be movable to some extent both in the focusing direction and along the disc radius, which requires a suspension construction which generally has a shape which is asymmetrical relative to the disc radius. The objective should be

disposed at a very small distance from the disc, so that until now it was necessary to bring the entire pick-up, i.e. including the suspension construction, in the proximity of the disc surface and hence into the opening in the main wall of the cassette.

In the case of pivotal optical devices the objective follows a curved path whose centre is the pivotal centre of the device. A prior art cassette for use with a pivoting pick-up device is known from UK Patent Application GB 2 173 631 A. A curved opening is provided in a roughly diagonal direction in one of the main walls. No slide is provided for shutting off the opening. The curved path of a pivotal optical device should be so as to minimise angular errors occurring during reading. As is generally known from the technology of pick-up arms for scanning gramophone discs, this results in the curved path not being symmetrical relative to a disc radius but subtends a specific angle relative to the radius at any point. Further information relating to the path of an optical pivotal arm can be found in United States Patent Specification US 4,403,316 (herewith incorporated by reference, PHN 10.134).

European Application 0 375 461 A1 (herewith incorporated by reference, PHN 12.479), which has been published after the application date of the present case, describes a cassette which also has openings in both main walls, the openings having a larger width than those of the first mentioned prior-art cassette. Again the openings of this cassette are closed, in the present case by means of two slides which are movable in opposite directions. The use of two oppositely movable slides enables the openings to be given a width substantially equal to half the width of the cassette.

SUMMARY OF THE INVENTION

Problem

The openings in the main wall of the cassettes known from European application EP 0 255 185 A1 and UK application GB 2 173 631 A are rather narrow for many uses. The opening in the cassette disclosed in European application EP 0 335 461 A1 is generally large enough. This advantage of a larger opening and hence a wider field of use for the cassette, however, is obtained at the expense of some new drawbacks. The larger openings in the main walls weaken the construction of the cassette. If slides are used more parts are needed than in the first-mentioned cassette. Moreover, in the apparatus to be used in conjunction with the cassette more parts are necessary for opening the two slides, so that more space is needed. The narrow elongate shape of the slides may give rise to slanting effects, which may impair a correct opening and closure of the slides.

Solution

It is an object of the invention to provide a cassette of the type defined in the opening sentence which does not have the drawbacks of said prior-art cassettes, which combines an optimum rigidity of the housing with an optimum accessibility of different types of pick-up to the disc, and which requires a minimal number of parts. To this end the invention provides a cassette comprising a rotatable information disc whose information is readable by means of a pick-up which moves parallel to the disc surface and which forms part of an apparatus, a housing comprising first and second main walls parallel to the disc, side walls, a front wall, and a rear wall, which walls together bound a disc-receiving space in which the disc is rotatable, the first main wall being formed with a first opening to give a pick-up access to the disc surface, the first opening having a shape which is asymmetrical relative to a radius of the disc perpendicular to the front wall, a second opening in the first main wall for giving a drive spindle of a drive arrangement access to the center of the disc, the first opening having at least substantially the shape of a rectangle and the second opening being at least substantially circular, the width of the first opening being substantially equal to the diameter of the second opening, the two openings partly overlapping one another, and the long sides of the rectangle being parallel to the said radius.

The use of an offset rectangular first opening surprisingly results in the effect that both for asymmetrical shaped translating pick-ups and pivotal pick-ups adequate space for access to the disc surface can be obtained with an opening of a width which is even slightly smaller than one third of the width of the cassette. In apparatuses comprising a radially translating pick-up the use of the cassette in accordance with the invention makes it necessary to allow for the orientation of the suspension construction of the pick-up relative to the disc radius. In this respect the cassette imposes a limitation on the freedom in designing the apparatus. However, in practice this limitation is not essential because for the construction of an apparatus it is irrelevant whether the suspension construction is situated at one side of the radius or at the other side of the radius. It is merely required that the designer of the apparatus knows in advance at which side the suspension construction is to be arranged.

Pivotal type optical pick-ups are frequently used in optical audio-disc players, in combination with Compact Discs (CDs). Typically, the radius of the pivotal movement of the objective is approximately 30 mm. CDs have a radius of 60 mm or 40 mm. In cassettes in accordance with the invention

containing discs of these diameters the customary pivotal devices can be employed without any problems.

It is known per se, for example from the cited prior art documents, to render the centre of the disc also accessible from the exterior through openings in the main walls, so that the disc can be mounted directly on a spindle in a drive arrangement and can be pressed onto the spindle by means of a disc-pressure member which forms part of the apparatus. This does not require any provisions in the cassette itself, which contributes to a simple construction of the cassette and the use of a minimal number of parts. It is obvious that the central opening should be disposed symmetrically relative to a radius of the disc. If the two openings in the main wall of the cassette in accordance with the invention are suitably combined with each other and, moreover, the width of the first opening is made substantially equal to the diameter of the second opening this will yield a cassette in which the combined asymmetrical opening has a minimal width, so that the cassette construction is only weakened to a minimal extent.

In particular when magneto-optical discs are used an embodiment of the invention is of interest wherein the second main wall is formed with a third opening situated opposite the first opening, the third opening having a shape which is symmetrical relative to a radius of the disc perpendicular to the front wall, and the width of the third opening being at the most equal to the width of the first opening. When magneto-optical discs are used the third opening need not be as wide as the first opening and merely serves to provide access to the disc surface for a magnetic element. Currently it is envisaged that the magnetic elements to be used in magneto-optical players will have a substantially symmetrical shape. In order to minimise the area of the third opening it is therefore desirable that the opening is situated symmetrically in the cassette.

A further embodiment of the invention is of interest comprising a slide which is movable over the first main wall between a closed position, in which the first opening is covered, and an open position, in which the first opening is freely accessible from the exterior, having at one side of the slide an asymmetrical profile adapted to the asymmetrical shape of the first opening.

This embodiment of the invention provides a cassette comprising a slide whose dimensions can be minimal because the slide is adapted to the asymmetrical opening in the main wall of the cassette in such a way that this opening is fully exposed when the slide is open.

The cassette in accordance with the invention can be utilised advantageously with a slide or without a slide. If no slide is used it is obvious that the

disc is less effectively protected against dust and other extraneous influences. However, this also means that the reproducing apparatus does not require any provisions for opening a slide and the cassette is cheaper. The use of cassettes without a slide is therefore of particular interest in those cases where a very good protection of the disc is of less importance and a simple construction of the apparatus and of the cassette are more important. This applies in particular to the use of CDs in CD-players mounted in the dashboard of a car. In view of the limited mounting space it is important to minimise the number of additional parts in the player. In a car the cassette should provide a certain degree of protection for the CD to enable the CD to be handled more conveniently while driving, but the CD need not be better protected against dust than normally. As a consumer product the cassette should preferably be inexpensive. For many other uses, for example in the professional field, however, a better protection of the disc is very desirable.

For cassettes of the aforementioned type whose second main wall is also formed with an opening an embodiment of the invention is of interest, wherein in the closed position the slide covers both the first and the second opening and at one side the slide has a profile adapted both to the asymmetrical shape of the first opening and to the second opening, so that in the open position of the slide the second opening is also freely accessible from the exterior.

By correctly adapting the profile of the slide only a minimal displacement is necessary to expose both openings completely, so that no useful area is lost.

A further embodiment of the invention is of interest wherein near the first opening the housing of the cassette has a truncated corner adapted to cooperate with means of an apparatus to preclude misinsertion of the cassette, and the truncated corner is situated at that side of the first opening towards which the slide is moved during its movement to the closed position.

In many cases it is important that misinsertion of the cassette into the apparatus is prevented by providing an apparatus with means adapted to cooperate with parts of the cassette. The last mentioned embodiment of the invention ensures that the slide does not cover any parts of the cassette which are important for cooperation with parts of the apparatus provided to preclude misinsertion.

An embodiment of the invention is of interest for cassettes having openings in both main walls, the cassette having the feature that the slide is also movable over the second main wall and in the open position exposes the third opening to provide access from the exterior.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is an exploded view of a first embodiment of the cassette in accordance with the invention, Fig. 2 shows the cassette of Fig. 1 with a closed asymmetrical slide in a perspective view to a slightly enlarged scale,

Fig. 3 is a perspective view as shown in Fig. 2, but now with the slide in the open position,

Fig. 4 is a diagrammatic plan view of the openings in the first main wall of the cassette,

Fig. 5 is a view similar to that of Fig. 4, showing the openings in the second main wall of the cassette,

Fig. 6 is an underneath view of a cassette in a modified embodiment, comprising an open asymmetrical slide, and

Fig. 7 is a plan view of the cassette shown in Fig. 6.

DESCRIPTION OF THE EMBODIMENTS SHOWN IN THE DRAWINGS.

Fig. 1 shows a cassette with a rotatable information disc 1 whose information is readable by means of a pick-up which moves parallel to the disc surface and which forms part of an apparatus. Only the outline of the disc is shown in broken lines. The pick-up needed for reading the information of the disc is not shown in the drawing. Neither the disc itself nor the pick-up are of any further relevance to the invention.

The cassette comprises a housing consisting of two shells 2A and 2B, which are permanently secured to one another. The shells comprise first and second main walls 3A and 3B parallel to the information disc. Moreover, side walls 4A, 4B and 5A, 5B are provided as well as a front wall 6A, 6B and a rear wall 7. The entire rear wall is removable to replace the disc in the cassette. For further details on the use of a rear cassette wall which can be opened to replace the disc reference is made to the afore mentioned Patent Application 8,800,820 (PHN 12.479). It is to be noted only that the wall 7 can be snapped onto the remainder of the cassette housing by means of projections 8. Together the walls bound a disc-receiving space in which the disc is arranged so as to be rotatable. The first main wall 2A is formed with a first opening 9 to give a pick-up access to the disc surface.

The opening 9 has an asymmetrical shape relative to a radius 10 of the disc 1 in a which is perpendicular to the front wall 6.

The first main wall 3A also has a second opening 11, which serves to give a drive spindle of a drive arrangement access to the centre of the disc 1. The first opening 9 is of at least substantially rectangular shape and the second opening 11 is

circular. The width W9 of the first opening is substantially equal to the diameter d of the second opening. For the sake of clarity the outlines of the two openings are again indicated in Fig.4. Both openings partly overlap one another in the shaded area 12 in Fig. 4. The first opening 9 is offset in the direction 13 perpendicular to the radius 10 which extends parallel to the long sides 14 of the opening 9.

The second main wall 3B is formed with a third opening 15, which is situated opposite the first opening 9 in the first main wall. The third opening 15 has a shape which is symmetrical relative to the radius 10 of the disc. Its width W15 is substantially equal to the width W9 of the first opening but may also be smaller. The second main wall 3B is formed with a fourth opening 16 which, like the second opening 11, is circular and has the same diameter d. For the sake of clarity Fig. 5 shows the combination of the third and the fourth opening. These two openings overlap one another in an area 17.

The cassette comprises a slide 18. This slide is movable over the outer side of the first main wall 3A between a closed position - see Fig. 2 - in which the first opening 9 is covered and an open position - see Fig. 3 - in which the first opening is freely accessible from the exterior. At one side the slide has a profile 19 which corresponds to that of the nearest side 4 of the housing. The other side has an asymmetrical profile 20 adapted to the asymmetrical shape of the first opening 9.

The slide 18 comprises two portions 18A and 18B which are movable over the first and over the second main wall respectively. The two parts are interconnected by a connecting portion 18C at the front of the cassette. This connecting portion has an opening 21 for actuating the slide by means provided in an apparatus. In the closed position the slide closes both the first opening 9 and the second opening 11. The profile 20 at the other side of the slide is adapted both to the asymmetrical shape of the first opening and also to that of the second opening 11. Thus it is achieved that in the open position of the slide 18, see Fig. 3, the second opening 11 is also freely accessible from the exterior. In other words, the profile 20 has such a shape that in the closed position both opening are covered and in the open position both openings are freely accessible. This is possible because both openings have the same width, so that only a minimal travel of the slide is required or, in other words, a maximum useful area is exposed with a specific stroke of the slide.

Near the first opening 9 the cassette housing has a truncated corner 22 which is adapted to cooperate with means provided in an apparatus to prevent misinsertion of the cassette into the ap-

paratus. The truncated corner is situated at that side of the first opening 9 towards which the slide 18 is moved during closure of the slide. Thus the truncated corner cannot in any way be covered by the slide.

With its portion 18B the slide 18 also moves over the second main wall 3B and in the closed position it closes the third opening 15 and the fourth opening 16, thus exposing them to provide free access from the exterior in the open position. As the first opening up to and including the fourth opening all have the same transverse dimension when the free area is as large as possible, the four openings are completely exposed at the same time to give free access to the disc with a minimum travel of the slide.

Figs.6 and 7 relate to a cassette which differs only in a few respects from that shown in Figs. 1 to 3. Therefore, the second embodiment will be described only briefly. The housing 23 of the cassette has a first main wall 24 and a second main wall 25. The first main wall is formed with a first opening 26 and a second opening 27, and the second main wall is formed with a third opening 28 and a fourth opening 29. The slide 30 comprises portions 30A and 30B, which slide over the first and the second main wall respectively. The first opening 26 and the third opening 28 are of rectangular shape. Their longitudinal directions extend in the same direction as the radius 31. The profile 32 at one side of the portion 30A of the slide 30 is adapted to the asymmetrical position of the first opening 26 and to the circular third opening 27. In the closed position the portion 30A engages with relates 33, 34 and 35 formed in the first main wall 24. At the other side the portion 30A of the slide 30 has a profile 36 of the same shape as a profile 32, so that the portion 30A has the same width W over its entire length. The portion 30B of the slide at the other side of the cassette has the same width. A rebate 37 is provided to engage with the portion 30B in the closed position.

For a satisfactory guidance of the slide on the cassette, cover plates 38A and 38B are arranged at opposite sides of the cassette, underneath which plates the free ends of the portions 30A and 30B of the slide can move with clearance.

The first embodiment of the cassette shown in Figs 1 to 3 also comprises similar cover plates 39A and 39B. Fig. 1 also shows some parts provided for guiding the slide 18 on the cassette. These parts comprise a pin 40 and a guide block 41. This block is connected to the wall 18C of the slide 18 in a manner not shown, for example by means of an adhesive, and is slidably mounted on the pin 40. The drawings do not show the resilient means for urging the slide towards the closed position. These resilient means may comprise, for example, a hel-

ical spring arranged around the pin 40 and acting against the side wall 4B of the cassette at one end and against the guide block 41 at the other end.

Within the scope of the invention many modified embodiments are possible which nevertheless utilise the basic idea of the invention, namely the use of an asymmetrical opening in the cassette in order to obtain a wide field of use for the cassette with a minimal area of the opening by making the cassette suitable for cooperation with various types of pick-ups of drive apparatuses. A comparison of the cassette in accordance with the invention with other prior art cassette not yet considered may reveal further advantages of the cassette in accordance with the invention. Apart from an optical disc the cassette may contain any other type of disc, such as a magnetic disc, a magneto-optical disc, a disc formed with surface grooves etc.

Claims

1. A cassette comprising a rotatable information disc (1) whose information is readable by means of a pick-up which moves parallel to the disc surface and which forms part of an apparatus, a housing (2A, 2B) comprising first and second main walls (3A, 3B) parallel to the disc, side walls (4A, 4B; 5A, 5B), a front wall (6A, 6B), and a rear wall (7), which walls together bound a disc-receiving space in which the disc is rotatable, the first main wall (2A) being formed with a first opening (9) to give a pick-up access to the disc surface, the first opening having a shape which is asymmetrical relative to a radius (10) of the disc perpendicular to the front wall (6), a second opening (11) in the first main wall (3A) for giving a drive spindle of a drive arrangement access to the center of the disc, the first opening (9) having at least substantially the shape of a rectangle and the second opening (11) being at least substantially circular, the width (W9) of the first opening being substantially equal to the diameter (d) of the second opening, the two openings partly overlapping one another, and the long sides (14) of the rectangle being parallel to the said radius (10).

2. A cassette as claimed in Claim 1, the second main wall (3B) being formed with a third opening (15) situated opposite the first opening (9), the third opening (15) having a shape which is symmetrical relative to a radius (10) of the disc perpendicular to the front wall, and the width (W15) of the third opening (15) being at the most equal to the width (W9) of the first opening (9).

3. A cassette as claimed in Claim 1 comprising a slide (18) which is movable over the first main wall (3A) between a closed position, in which the first opening is covered, and an open position, in which the first opening is freely accessible from the exterior, the slide having an asymmetrical profile (20) at one side adapted to the asymmetrical shape of the first opening (9).

4. A cassette as claimed in Claims 1-3 wherein in the closed position the slide (18) covers both the first and the second openings (9, 11), and at one side the slide has a profile (20) adapted both to the asymmetrical shape of the first opening (9) and to the second opening (11), so that in the open position of the slide (18) the second opening is also freely accessible from the exterior.

5. A cassette as claimed in Claims 1-3, wherein near the first opening (9) the housing of the cassette has a truncated corner (22) adapted to cooperate with means of an apparatus to preclude misinsertion of the cassette, and the truncated corner is situated at that side of the first opening towards which the slide (18) is moved during its movement to the closed position.

6. A cassette as claimed in Claims 2-3 wherein the slide (18) is also movable over the second main wall (3B) and in the open position exposes the third opening to provide access from the exterior.

Patentansprüche

1. Eine Kassette mit einer drehbaren Datenplatte (1), deren Daten mittels eines parallel zur Plattenoberfläche beweglichen und Bestandteil eines Geräts bildenden Abtasters gelesen werden können, sowie einem Gehäuse (2A, 2B) mit einer ersten und einer zweiten zur Platte parallelen Hauptwand (3A, 3B), Seitenwänden (4A, 4B; 5A, 5B), einer Vorderwand (6A, 6B) und einer Rückwand (7), wobei diese Wände gemeinsam einen Aufnahmeraum für die Platte umschließen, in dem sich die Platte drehen kann, wobei die erste Hauptwand (3A) mit einer ersten Öffnung (9) für den Zugang eines Abtasters zur Plattenoberfläche versehen ist, welche erste Öffnung eine zu einem senkrecht zur Vorderwand (6) stehenden Radius (10) der Platte asymmetrische Form hat, und in der ersten Hauptwand (3A) eine zweite Öffnung (11) für den Zugang einer Antriebsspindel einer Antriebsvorrichtung zur Plattenmitte vorge-

sehen ist, wobei die erste Öffnung (9) zumindest im wesentlichen rechteckförmig und die zweite Öffnung (11) zumindest im wesentlichen kreisförmig ist, während die Breite (W9) der ersten Öffnung ungefähr gleich dem Durchmesser (d) der zweiten Öffnung ist, wobei die beiden Öffnungen einander teilweise überlappen und die langen Seiten (14) des Rechtecks zu dem genannten Radius (10) parallel verlaufen.

2. Kassette nach Anspruch 1, bei der die zweite Hauptwand (3B) mit einer der ersten Öffnung (9) gegenüberliegenden dritten Öffnung (15) versehen ist, welche dritte Öffnung (15) eine zu einem senkrecht zur Vorderwand liegenden Radius (10) der Platte symmetrische Form hat, während die Breite (W15) der dritten Öffnung (15) der Breite (W9) der ersten Öffnung (9) höchstens gleich ist.
3. Kassette nach Anspruch 1 mit einem zwischen einer geschlossenen Lage, in der die erste Öffnung geschlossen ist, und einer offenen Lage, in der die erste Öffnung von außen frei zugänglich ist, über die erste Hauptwand (3A) beweglichen Schieber (18), der an einer Seite ein der asymmetrischen Form der ersten Öffnung (9) angepaßtes asymmetrisches Profil (20) aufweist.
4. Kassette nach den Ansprüchen 1 - 3, bei der der Schieber (18) in geschlossener Lage sowohl die erste als auch die zweite Öffnung (9, 11) verschließt und an einer Seite ein sowohl der asymmetrischen Form der ersten Öffnung (9) als auch der zweiten Öffnung (11) angepaßtes Profil (20) aufweist, so daß die zweite Öffnung bei geöffneter Lage des Schiebers (18) von außen frei zugänglich ist.
5. Kassette nach den Ansprüchen 1 - 3, bei der das Gehäuse in der Nähe der ersten Öffnung (9) mit einer abgeschrägten Ecke (22) versehen ist, die mit Mitteln eines Geräts zur Verhinderung eines fehlerhaften Einführens der Kassette zusammenwirken kann und diese abgeschrägte Ecke sich an derjenigen Seite der ersten Öffnung befindet, zu der sich der Schieber (18) bei seiner Bewegung in die geschlossene Lage hinbewegt.
6. Kassette nach den Ansprüchen 2 - 3, bei der der Schieber (18) auch über die zweite Hauptwand (3B) verschiebbar ist und in offener Lage die dritte Öffnung für den Zugang von außen freigibt.

Revendications

1. Cassette comprenant un disque d'information rotatif (1) dont l'information peut être lue à l'aide d'un pick-up qui se déplace parallèlement à la surface du disque et qui fait partie d'un appareil, un boîtier (2A, 2B) présentant des première et deuxième parois principales (3A, 3B) parallèles au disque, des parois latérales (4A, 4B; 5A, 5B), une paroi avant (6A, 6B) et une paroi arrière (7), parois qui enferment ensemble un espace de réception de disque dans lequel peut tourner le disque, la première paroi principale (2A) étant munie d'une première ouverture (9) pour donner à un pick-up l'accès à la surface du disque, la première ouverture présentant une forme qui est asymétrique par rapport à un rayon (10) du disque perpendiculaire à la paroi avant (6), une deuxième ouverture (11) ménagée dans la première paroi principale (3A) pour donner à un arbre d'entraînement d'un dispositif d'entraînement l'accès au centre du disque, la première ouverture (9) présentant au moins pratiquement la forme d'un rectangle et la deuxième ouverture (11) étant au moins pratiquement circulaire, la largeur (W9) de la première ouverture étant pratiquement égale au diamètre (d) de la deuxième ouverture, les deux ouvertures chevauchant partiellement et les côtés longs (14) du rectangle étant parallèles audit rayon (10).
2. Cassette selon la revendication 1, dont la deuxième paroi principale (3B) est munie d'une troisième ouverture (15) située vis-à-vis de la première ouverture (9), la troisième ouverture (15) présentant une forme qui est symétrique par rapport à un rayon (10) du disque perpendiculaire à la paroi avant et la largeur (W15) de la troisième ouverture (15) est au maximum égale à la largeur (W9) de la première ouverture (9).
3. Cassette selon la revendication 1 munie d'une coulisse (18) qui peut se déplacer sur la première paroi principale (3A) entre une position fermée, dans laquelle la première ouverture est recouverte, et une position ouverte dans laquelle la première ouverture est librement accessible à partir de l'extérieur, la coulisse présentant d'un côté un profil asymétrique (20) qui est adapté à la forme asymétrique de la première ouverture (9).
4. Cassette selon les revendications 1 à 3, dans laquelle, dans la position fermée, la coulisse (18) recouvre tant les première et deuxième

ouvertures (9, 11) et présente d'un côté un profil (20) qui est adapté à la forme asymétrique de la première ouverture (9) ainsi qu'à celle de la deuxième ouverture (11) de façon que dans la position ouverte de la coulisse (18) la deuxième ouverture soit également librement accessible à partir de l'extérieur.

5

5. Cassette selon les revendications 1 à 3, dans laquelle, près de la première ouverture (9), le boîtier de la cassette présente un angle tronqué (22) adapté pour coopérer avec des moyens d'un appareil pour empêcher une introduction erronée de la cassette et l'angle tronqué se situe du côté de la première ouverture vers lequel se déplace la coulisse (18) pendant son déplacement vers la position fermée.

10

15

6. Cassette selon les revendications 2 à 3, dans laquelle la coulisse (18) peut également se déplacer sur la deuxième paroi principale (3B) et dégage la troisième ouverture dans la position ouverte pour permettre l'accès à partir de l'extérieur.

20

25

30

35

40

45

50

55






FIG.1






FIG. 4




FIG. 6




FIG. 5




FIG. 7

REGISTER ENTRY FOR EP0358269

European Application No EP89202212.0 filing date 01.09.1989

Application in Dutch

Priority claimed:

05.09.1988 in Netherlands - doc: 8802185

Designated States BE DE FR GB IT

Title DISC CASSETTE.

Applicant/Proprietor

N.V. PHILIPS' GLOEILAMPENFABRIEKEN, Groenewoudseweg 1, NL-5621 BA

Eindhoven, Netherlands

[ADP No. 50311273001]

Inventors

CORNELIS OUWERKERK, c/o INT. OCTROOIBUREAU B.V. Prof. Holstlaan 6, NL-5656
AA Eindhoven, Netherlands [ADP No. 55674410001]CORNELIS MARTIN BEYERSBERGEN VAN HENEGOUWEN, c/o INT. OCTROOIBUREAU B.V.
Prof. Holstlaan 6, NL-5656 AA Eindhoven, Netherlands [ADP No. 53360418001]

Classified to

G11B

Address for Service

R J BOXALL, PHILIPS ELECTRONICS, Patents and Trade Marks Dept, Philips
House, 1-19 Torrington Place, LONDON, WC1E 7HD, United Kingdom

[ADP No. 00974790004]

EPO Representative

PAUL JOHANNES FRITS VAN WEELE, INTERNATIONAAL OCTROOIBUREAU B.V. Prof.
Holstlaan 6, NL-5656 AA Eindhoven, Netherlands

[ADP No. 50145630001]

Publication No EP0358269 dated 14.03.1990

Publication in English

Examination requested 11.09.1990

Patent Granted with effect from 01.12.1993 (Section 25(1)) with title DISC
CASSETTE.

03.11.1994 Notification of change of Address For Service name and address of
R J BOXALL, PHILIPS ELECTRONICS, Patents and Trade Marks Dept,
Philips House, 1-19 Torrington Place, LONDON, WC1E 7HD, United
Kingdom [ADP No. 00974790004]

to

PHILIPS ELECTRONICS, Patents and Trade Marks Department, Cross Oak
Lane, REDHILL, Surrey, RH1 5HA, United Kingdom

[ADP No. 00658492006]

dated 05.09.1994. Official evidence filed on gb2235868

Entry Type 7.1 Staff ID. MH Auth ID. EO

**** END OF REGISTER ENTRY ****

OA80-01
EP

OPTICS - PATENTS

11/11/94 17:05:22
PAGE: 1

RENEWAL DETAILS

PUBLICATION NUMBER

EP0358269 /

PROPRIETOR(S)

changed su D^r
N.V. Philips' Gloeilampenfabrieken, Groenewoudseweg 1, NL-5621 BA,
Netherlands

DATE FILED

01.09.1989 /

DATE GRANTED

01.12.1993 /

DATE NEXT RENEWAL DUE

01.09.1995

DATE NOT IN FORCE

DATE OF LAST RENEWAL

01.09.1994

YEAR OF LAST RENEWAL

06

STATUS

PATENT IN FORCE /