

(12) **United States Patent**
Leach et al.

(10) **Patent No.:** **US 11,711,340 B2**
(45) **Date of Patent:** ***Jul. 25, 2023**

(54) **PROTECTING COMMUNICATION LINK BETWEEN CONTENT DELIVERY NETWORK AND CONTENT ORIGIN SERVER**

(58) **Field of Classification Search**
CPC H04L 63/02; H04L 63/1441; H04L 67/1095; H04L 61/2539
See application file for complete search history.

(71) Applicant: **Fastly Inc.**, San Francisco, CA (US)

(56) **References Cited**

(72) Inventors: **Sean A. Leach**, Castle Pines, CO (US);
Artur Bergman, San Francisco, CA (US); **Thomas J. Daly**, Nashua, NH (US)

U.S. PATENT DOCUMENTS

6,829,654 B1 12/2004 Jungck
8,464,334 B1* 6/2013 Singhal H04L 63/0414
726/13

(73) Assignee: **Fastly, Inc.**, San Francisco, CA (US)

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 85 days.

CN 1707957 A * 12/2005
CN 1871863 A 11/2006

(Continued)

This patent is subject to a terminal disclaimer.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **16/853,083**

B. Molina, "A Closer Look at a Content Delivery Network Implementation," IEEE Melecon, May 12-15, 2004, Dubrovnik, Croatia, 4 pages.

(22) Filed: **Apr. 20, 2020**

(Continued)

(65) **Prior Publication Data**

US 2020/0252373 A1 Aug. 6, 2020

Primary Examiner — Meng Li

Related U.S. Application Data

(57) **ABSTRACT**

(63) Continuation of application No. 16/037,962, filed on Jul. 17, 2018, now Pat. No. 10,630,641, which is a (Continued)


A privatized link between an origin server and a content delivery network is provided. A privatized link can be a direct connection that does not route over the internet. Another privatized link is one that rotates IP addresses. An origin server may be assigned to use a set of multiple IP addresses for communication with the content delivery network. However, at any given time, the origin server is only using a small number of IP addresses. When one of the IP addresses being used to communicate with the content delivery network comes under attack, the origin server switches to another IP address in the set in order to continue serving content to the content delivery network via an IP address that is not under attack.

(51) **Int. Cl.**
H04L 9/40 (2022.01)
H04L 61/5092 (2022.01)

(Continued)

(52) **U.S. Cl.**
CPC **H04L 63/02** (2013.01); **H04L 61/2539** (2013.01); **H04L 61/5092** (2022.05); (Continued)

20 Claims, 6 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/806,317, filed on Jul. 22, 2015, now Pat. No. 10,044,673.

(51) **Int. Cl.**

H04L 61/2539 (2022.01)
H04L 67/02 (2022.01)
H04L 61/5007 (2022.01)
H04L 61/5038 (2022.01)
H04L 61/5061 (2022.01)

(52) **U.S. Cl.**

CPC *H04L 61/5007* (2022.05); *H04L 61/5038* (2022.05); *H04L 61/5061* (2022.05); *H04L 63/1441* (2013.01); *H04L 67/02* (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

9,197,604 B1 * 11/2015 Quilter H04L 61/2503
 2004/0010601 A1 * 1/2004 Afergan H04L 67/1001
 709/229
 2004/0103205 A1 * 5/2004 Larson H04L 63/0428
 709/229
 2010/0175131 A1 7/2010 Sheymov
 2012/0191836 A1 * 7/2012 Ogata H04L 61/5092
 709/223

2014/0098662 A1 4/2014 Jungck et al.
 2015/0042792 A1 * 2/2015 Krischer H04N 7/18
 709/224
 2015/0058976 A1 2/2015 Carney et al.
 2015/0281331 A1 * 10/2015 Steiner H04L 67/1014
 709/203
 2016/0028765 A1 * 1/2016 Lingafelt H04L 63/1458
 726/23
 2019/0158533 A1 5/2019 Holloway et al.

FOREIGN PATENT DOCUMENTS

EP 2109280 A1 1/2013
 WO 20070458 A1 11/2000
 WO 2005010708 A2 2/2005

OTHER PUBLICATIONS

Leyi Shi, "DoS Evading Mechanism upon Service Hopping," IFIP International Conference on Network and Parallel Computing—Workshops, 2007, 4 pages.
 Chunlei Zhao, "Technique and Application of End-hopping in Network Defense," First ACIS International Symposium on Cryptography, and Network Security, Data Mining and Knowledge Discovery E-commerce and its Applications, and Embedded Systems, 2010, 5 pages.

* cited by examiner




FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6

1

**PROTECTING COMMUNICATION LINK
BETWEEN CONTENT DELIVERY
NETWORK AND CONTENT ORIGIN
SERVER**

RELATED APPLICATIONS

This applications is a Continuation of, and claims priority to pending U.S. patent application Ser. No. 16/037,962, titled "PROTECTING COMMUNICATIONS BETWEEN A CONTENT DELIVERY NETWORK AND AN ORIGIN SERVER", filed Jul. 17, 2018, and to U.S. Pat. No. 10,044,673, titled "PROTECTING COMMUNICATION LINK BETWEEN CONTENT DELIVERY NETWORK AND CONTENT ORIGIN SERVER," filed Jul. 22, 2015, the contents of which are incorporated herein by reference in their entirety.

TECHNICAL FIELD

Aspects of the disclosure are related to the field of packet communication networks and delivery of content from a source server to content servers.

TECHNICAL BACKGROUND

Internet web pages, online information, and media content such as audio, video, photographs, and the like are requested and delivered to end users via computer network systems. Requests for the content are sent over the network to a source server, processed, and the content is delivered to the end user via the network. The source server can include origin or hosting servers which originally host the network content. Unfortunately, a single source server may not be able to serve a large number of concurrent requests for content. In addition, the requesting server may be distant geographically or network routing-wise from the source server. This can slow the process of delivering content to the point where users are dissatisfied, or abandon the request for content.

To address this problem, content delivery networks were developed. Content delivery networks cache content from a source server (a.k.a. origin server) for more rapid and reliable delivery to end users. A content delivery network may have many content nodes (up to thousands) distributed across a large geographic area (or network routing area) in order to provide faster, lower latency, and more reliable access to content for the end users, regardless of their geographic or network location.

The content delivery process begins with a user submitting a request to a browser. When a user enters a uniform resource locator (URL), a domain name system (DNS) request is triggered and an IP address is retrieved. In a content delivery network structure, the domain name of the URL is translated by a mapping system into the IP address of a content server, which can have the content cached locally, to serve the content to the user. If the content is cached by the content server, the content server can directly service the end user's request. If the content is not cached in the content server, or the content from the origin server is out-of-date or stale, the content server can receive the content from the origin server and cache it. Once cached, the content server can typically provide the content quickly.

An origin server, however, may be the subject of a malicious attack. If, while under attack, the origin server is

2

unable to provide the content to the content server, many of the advantages and functions of content delivery network can be disrupted.

OVERVIEW

Systems, methods, apparatuses, and software for ensuring delivery of content from an origin server to a content delivery network are disclosed herein. In one example, a method of protecting an origin server website from attack is disclosed. The method includes providing a content delivery network (CDN) having a set of content servers (CS) to provide content delivery on behalf of a set of participating content providers. The at least one of the set of content providers source content for delivery by the CDN from an origin server. A privatized link between at least one of the set of content servers and the origin server is provided.

In another example, a communication system includes a content delivery network (CDN) having a set of content servers (CS) to provide content delivery on behalf of a set of participating content providers. At least one of the set of content providers is to source content for delivery by the CDN from an origin server. The communication system also includes a privatized link between at least one of the set of content servers and the origin server.

In another example, a method of supplying content to a content delivery network (CDN) includes establishing a communication link between an origin server and a CDN using a first IP address for the origin server. The origin server is to provide content to the CDN by responding to requests from the CDN directed to the first IP address. The method also includes determining that the first IP address is under attack. The method also includes, in response to determining the first IP address is under attack, selecting a second IP address to be associated with the origin server. The method also includes establishing a communication link between the origin server and the CDN using the second IP address for the origin server. The origin server is now to provide content to the CDN by responding to requests from the CDN directed to the second IP address.

BRIEF DESCRIPTION OF THE DRAWINGS

Many aspects of the disclosure can be better understood with reference to the following drawings. The components in the drawings are not necessarily to scale, emphasis instead being placed upon clearly illustrating the principles of the present disclosure. Moreover, in the drawings, like reference numerals designate corresponding parts throughout the views. While multiple examples are described in connection with these drawings, the disclosure is not limited to the examples disclosed herein. On the contrary, the intent is to cover all alternatives, modifications, and equivalents.

FIG. 1 illustrates a communication system.

FIG. 2 illustrates a method of operating a content delivery network.

FIG. 3 illustrates a communication system.

FIG. 4 illustrates a method of operating a content delivery network.

FIG. 5 illustrates a method of responding to a malicious attack on an origin server.

FIG. 6 illustrates a content node.

DETAILED DESCRIPTION

Network content, such as web content, typically comprises text, hypertext markup language (HTML) pages,

pictures, digital media content, video, audio, code, scripts, or other content viewable and rendered by an end user device in a browser or other specialized application. This network content can be stored and served by origin servers that are owned or operated by content originators. When content servers or a content delivery network are employed, such as in FIG. 1, the content servers can act as proxies that cache network content for delivery to end user devices. The content servers can maintain recently accessed and popular content as cached from the origin servers. Thus, content servers exchange data with the origin servers when new or un-cached information is requested by the end users, or if the content source data has changed. An origin server, however, may be the subject of a malicious attack. For example, the IP address of the origin server may be subject to a denial of service (DoS) or distributed denial of service (DDoS) attack. If the attack is successful, the origin server would be unable to provide the content to the content server and the many advantages and functions of content delivery network would be disrupted.

In an embodiment, a privatized link between an origin server and the content delivery network is provided. One example of a privatized link is a direct connection that does not route over the internet. Because this connection does not route over the internet, it is more immune to attacks that come from the internet. Another privatized link is one that rotates IP addresses. For example, an origin server may be assigned to use a set of multiple IP addresses for communication with the content delivery network. However, at any given time, the origin server is only using a small number (e.g., 1 or 2) of IP addresses. When one of the IP addresses being used to communicate with the content delivery network comes under attack, the origin server switches to another IP address in the set in order to continue serving content to the content delivery network via an IP address that is not under attack.

FIG. 1 illustrates a communication system. Communication system 100 includes content delivery network 110, end user devices 130-132, origin servers 140-141, management system 160, and analytics system 180. Content delivery network 110 includes one or more content servers (CS) 111-113. Each of content servers 111-113 can include one or more data storage systems, such as data storage system 120 of content server 113. End user devices 130-132 are representative of a plurality of end user devices which can request and receive network content, and any number of end user devices 130-132 can be associated with each of content servers 111-113. Content servers 111-113 and end users 130-132 communicate over associated network links 170-172. Content delivery network 110 and origin servers 140-141 communicate over associated network links 173-174. Content delivery network 110 and management system 160 communicate over link 175. Content delivery network 110 and analytics system 180 communicate over link 176. Although not shown in FIG. 1 for clarity, each of content servers 111-113 can also communicate with each other over one or more network links.

To further illustrate FIG. 1, a brief description of the operation of communication system 100 is included. In operation, end user devices 130-132 request network content, such as content 145-146 associated with origin servers 140-141. Instead of these requests being handled by the individual origin servers 140-141, individual content servers 111-113 of content delivery network 110 receive the content requests over ones of links 170-172 and processes the content requests for delivery of the content to the associated end user devices 130-132. Requested network content that is

already stored in ones of content servers 111-113 can be provided quickly to the end user devices, while network content that is not already stored in ones of content servers 111-113 can be responsively requested by an associated one of content servers 111-113 from an appropriate origin server 140-141 for delivery by the content server 111-113 and possible caching by the content servers 111-113. In this manner, each of content servers 111-113 can act as intermediary proxy nodes to provide local and fast access for end user devices 130-132 to network content of origin servers 140-141 without burdening origin servers 140-141. For example, content server 113 includes cached content 121, which can include at least portions of any of the content originated at origin servers 140-141.

Data storage system 120 shows exemplary cached content for content server 113, although any of the content servers of FIG. 1 can include similar content. Each web page is indicated by a domain name or web address, namely www.alpha.com, www.beta.net, and www.gamma.gov.

Management system 160 handles configuration changes and status information collection and delivery for system operators and for the origin server operators or managers. For example, operator device 150 can transfer configuration 151 for delivery to management system 160, where configuration 151 can alter the handling of network content requests by content servers 111-113, among other operations. Also, management system 160 can monitor status information for the operation of content servers 111-113, such as operational statistics, and provide this status information as 153 to operator device 150. Furthermore, operator device 150 can transfer content 152 for delivery to origin servers 140-141 to include in content 145-146. Although one operator device 150 is shown in FIG. 1, it should be understood that this is merely representative and communication system 100 can include many operator devices for receiving status information, providing configuration information, or transferring content to origin servers.

Analytics system 180 can include communication interfaces, network interfaces, processing systems, computer systems, microprocessors, storage systems, storage media, or some other processing devices or software systems, and can be distributed among multiple devices. Examples of analytics system 180 can include software such as an operating system, logs, databases, utilities, drivers, networking software, and other software stored on a computer-readable medium.

Content servers 111-113, origin servers 140-141, management system 160, and analytics system 180 can each include communication interfaces, network interfaces, processing systems, computer systems, microprocessors, storage systems, storage media, or some other processing devices or software systems, and can be distributed among multiple devices. Examples of content servers 111-113, origin servers 140-141, management system 160, and analytics system 180 can each include software such as an operating system, logs, databases, utilities, drivers, networking software, and other software stored on a computer-readable medium. Content delivery network 110, in addition to including content servers 111-113, can include equipment and links to route communications between content servers 111-113 and any of end user devices 130-132, origin servers 140-141, management system 160, and analytics system 180, among other operations.

End user devices 130-132 can each be a user device, subscriber equipment, customer equipment, access terminal, smartphone, personal digital assistant (PDA), computer, tablet computing device, e-book, Internet appliance, media

player, game console, smartwatch, or some other user communication apparatus, including combinations thereof.

Communication links **170-176** each use metal, glass, optical, air, space, or some other material as the transport media. Communication links **170-176** can each use various communication protocols, such as wireless communications, cellular communications, IEEE 802.11 (WiFi), Long Term Evolution (LTE), Time Division Multiplex (TDM), asynchronous transfer mode (ATM), Internet Protocol (IP), Ethernet, synchronous optical networking (SONET), hybrid fiber-coax (HFC), circuit-switched, communication signaling, or some other communication format, including combinations, improvements, or variations thereof. Communication links **170-176** can each be a direct link or can include intermediate networks, systems, or devices, and can include a logical network link transported over multiple physical links. Although one main link for each of links **170-176** is shown in FIG. 1, it should be understood that links **170-176** are merely illustrative to show communication modes or access pathways. In other examples, further links can be shown, with portions of the further links shared and used for different communication sessions or different content types, among other configurations. Communication links **170-176** can each include many different signals sharing the same associated link, as represented by the associated lines in FIG. 1, comprising resource blocks, access channels, paging channels, notification channels, forward links, reverse links, user communications, communication sessions, overhead communications, carrier frequencies, other channels, timeslots, spreading codes, transportation ports, logical transportation links, network sockets, packets, or communication directions.

Content delivery network **110** (which has at least content servers **111-113**) provides content to end users **130-132** on behalf of origin servers **140-141**. In order to help protect against a malicious attack on an origin server **140-141**, privatized links **173-174** between at least one of content servers **111-113** and a respective origin server **140-141** are provided. In an embodiment, link **173** is privatized by providing a direct connection that does not route over the internet.

In an embodiment, link **174** is privatized by selecting a set of private IP addresses for use as IP addresses for origin server **141** to use for communication between content delivery network **110** and origin server **141**. For example, a set of IP addresses that span the range of 23.235.33.0 to 23.235.33.255 (a.k.a., a /24 range) may be selected by management system **160** or configuration **151** to be the private IP addresses used by origin server **141** to communicate with content delivery network **110**. A first IP address of the set of private IP addresses is selected as origin server **141**'s IP address for communication on link **174** between origin server **141** and content delivery network **110**. As long as communication link **174** is functioning adequately with origin server **141** using the first IP address, origin server **141** can continue to use the first IP address.

However, when it is determined that the first IP address is under malicious attack (e.g., it is the target of a DDoS attack), the use of the first IP address by origin server **141** subjects origin server **141** (and link **174**) to the malicious attack. In response to the first IP address coming under attack, origin server **141** and content delivery network **110** are configured such that origin server will use a second IP address in the set of private IP addresses for communication between origin server **141** and content delivery network **110**.

For example, origin server **141** and content delivery network **110** may be configured to use a set of IP addresses

that span the range of 23.235.33.0 to 23.235.33.255 (a.k.a., a /24 IP address range) to be the private IP addresses used by origin server **141** to communicate with content delivery network **110**. Origin server **141** may start by using, for example, the IP address 23.235.33.17 (a.k.a., a /32 IP address). When it is determined that the IP address 23.235.33.17 is under malicious attack, origin server **141** may be configured to use, for example, the IP address 23.235.33.78. Content delivery network **110** would also be configured such that it knows that the IP address 23.235.33.78 corresponds to origin server **141** and therefore directs its requests to the second IP address. Thus, since origin server **141** is no longer responding to the first IP address of 23.235.33.17 because it now responding to the second IP address of 23.235.33.78, the effect of the malicious attack on link **174** is reduced or eliminated. As each IP address comes under attack, content delivery network **110** and origin server **141** can each mutually switch the IP address used for communication with origin server **141** to a new IP address from the set of private IP addresses—thus mitigating or eliminating the effects of subsequent malicious attacks on origin server **141** and/or link **174**.

In the previous example, the selected set of private IP addresses was a contiguous range of IP addresses. This set of example private IP addresses all shared a common routing prefix (i.e., 23.235.33.XXX, or a /24 range). However, it should be understood that a set of non-contiguous IP addresses could have been selected. These non-contiguous IP addresses may have more than one routing prefix. It should also be understood that origin server **141** and/or content delivery network may use a predetermined (e.g., randomized, formulaic, sequential, listed, etc.) order for selecting the next IP address to be used. It should also be understood that the set of IP private addresses may be in the range allocated to content delivery network **110**. In this manner, it may be more difficult for attackers to differentiate between a content server **111-113** and origin server **141**. Finally, it should be understood that after an IP address is determined to no longer be under attack, it may be reselected to be the IP address of origin server **141**.

FIG. 2 illustrates a method of operating a content delivery network. The steps illustrated in FIG. 2 may be performed by one or more elements of communication system **100**. A content delivery network having a set of content servers is provided to perform content delivery on behalf of an origin server (**202**). For example, content delivery network **110** having content servers **111-113** can be provided to supply the delivery of content **146** on behalf of origin server **141**.

A privatized link between at least one of the content servers and the origin server is provided (**204**). For example, link **174** between content delivery network **110** and origin server **174** may be privatized. Link **174** may be privatized by establishing a direct connection between content delivery network **110** and origin server **141** that does not route over the internet. In another example, link **174** may be privatized by switching IP addresses for origin server **141** whenever the IP address being used by origin server **141** comes under malicious attack. The IP address to be used by origin server **141** after an attack may be selected from a predetermined range of contiguous IP addresses, or list of non-contiguous IP addresses. The IP address may be selected in a predetermined order (e.g., sequentially, randomly, formulaically, or from a non-sequential ordered list).

FIG. 3 illustrates a communication system. In FIG. 3, communication system **300** comprises content delivery network **310**, network **315**, end user devices **330-332**, and origin server **340**. Content delivery network **310** include

content servers **311-313**. Origin server **340** includes content **345**. Origin server **340** also includes IP address list **390**. End user devices **330-332** are operatively coupled to content servers **311-313**, respectively, by links **370-372**. Origin server **340** is operatively coupled to content delivery network **310** (and thus content servers **311-313**) via network **315**. Network **315** can route communication between content delivery network **310** and origin server **340** using at least IP address **391** or IP address **392** from list **390**.

End user devices **330-332** are representative of a plurality of end user devices which can request and receive network content which is sourced from origin server **340**. Any number of end user devices **330-332** can be associated with each of content servers **311-313**. Content servers **311-313** and end users **330-332** communicate over associated network links **370-372**. Content delivery network **310** and origin server **340** communicate via network **315**. Each of content servers **311-313** can also communicate with each other over one or more network links (not shown in FIG. 3.)

End user devices **330-332** request network content, such as content **345**, that is sourced by origin server **340**. Instead of these requests being handled by the origin server **340**, individual content servers **311-313** of content delivery network **310** receive the content requests over ones of links **370-372**. The content servers **311-313** respond to and processes the content requests in order to deliver the content to the requesting end user device **330-332**. Requested network content that is already stored in a content server **311-313** can be provided from the content server **311-313** directly to the requesting end user device **330-332** without first retrieving the content **345** from origin server **340**. Network content that is not already stored in a content server **311-313** can be requested by a content server **311-313** from origin server **340**. Once the content server **311-313** receives the content **345** from origin server **340**, the content server **311-313** can deliver the content **345** to the requesting end user device **330-332**. Each content server **311-313** that receives the content **345** may also cache the content **345**. In this manner, each of content servers **311-313** can act as intermediary proxy nodes to provide local and fast access for end user **330-332** to network content **345** of origin server **340** without additionally burdening origin server **340**.

Content servers **311-313**, end user devices **330-332**, and origin server **340** can each include communication interfaces, network interfaces, processing systems, computer systems, microprocessors, storage systems, storage media, or some other processing devices or software systems, and can be distributed among multiple devices. Examples of content servers **311-313** and origin server **340** each include software such as an operating system, logs, databases, utilities, drivers, networking software, and other software stored on a computer-readable medium. Content delivery network **310**, in addition to including content servers **311-313**, can include configurations, equipment, and links to route communications between content servers **311-313**, end user devices **330-332**, and origin server **340**, among other operations.

End user devices **330-332** can each be a user device, subscriber equipment, customer equipment, access terminal, smartphone, personal digital assistant (PDA), computer, tablet computing device, e-book, Internet appliance, media player, game console, smartwatch, or some other user communication apparatus, including combinations thereof.

Communication system **300** can comprise wired and/or wireless communication networks that include processing nodes, routers, gateways, physical and/or wireless data links for carrying data among various network elements, includ-

ing combinations thereof, and can include a local area network, a wide area network, and an internetwork (including the Internet), or portions thereof (e.g., network **315**.) Communication system **300** can also comprise wireless networks, including base station, wireless communication nodes, telephony switches, internet routers, network gateways, computer systems, communication links, or some other type of communication equipment, and combinations thereof.

Wired network protocols that may be utilized by communication system **300** may comprise Ethernet, Fast Ethernet, Gigabit Ethernet, Local Talk (such as Carrier Sense Multiple Access with Collision Avoidance), Token Ring, Fiber Distributed Data Interface (FDDI), and Asynchronous Transfer Mode (ATM). Wireless network protocols that may be utilized by communication system **300** may comprise code division multiple access (CDMA) 1xRTT, Global System for Mobile communications (GSM), Universal Mobile Telecommunications System (UMTS), High-Speed Packet Access (HSPA), Evolution Data Optimized (EV-DO), EV-DO rev. A, Third Generation Partnership Project Long Term Evolution (3GPP LTE), and Worldwide Interoperability for Microwave Access (WiMAX).

Links between elements of communication system **300**, can be, for example, twisted pair cable, coaxial cable or fiber optic cable, or combinations thereof. Links between elements of communication system **300** can be radio frequency, microwave, infrared, or other similar signal. Links between elements of communication system **300** can use a suitable communication protocol, for example, internet protocol, Ethernet, Global System for Mobile telecommunications (GSM), Code Division Multiple Access (CDMA), Worldwide Interoperability for Microwave Access (WiMAX), or Long Term Evolution (LTE), or combinations thereof. Other wireless protocols can also be used. Other network elements may be present to facilitate communication between among elements of communication system **300** which are omitted for clarity, including additional processing nodes, routers, gateways, and physical and/or wireless data links for carrying data among the various network elements.

In an embodiment, traffic between content delivery network **310** and origin server **340** routes through network **315**. Network **315** may be a part of a shared or 'open' network such as part of the internet. To properly route communication between content delivery network **310** and origin server **340** via network **315**, origin server **340** is associated with an IP address (e.g., IP address #1 **391**—23.235.33.27). Origin server **340** may be the subject of a malicious attack directed to an IP address it is currently using (e.g., IP address #1 **391**). This attack may disrupt the communication between content delivery network **310** and origin server **340**. This disruption may prevent content delivery network **310** from serving some requests by end user devices **330-332**.

When communication system **300** (and origin server **340** and/or content delivery network **310**, in particular) determine (or are informed) that the IP address being used by origin server **340** is under attack, origin server **340** stops using that IP address and selects a new IP address for communication via network **315**. For example, origin server may have been using IP address #1 **391** for communication routed via network **315**. When it is determined that IP address #1 is under attack (e.g., by a DDoS attack via network **315**), origin server **340** is configured with a new IP address (e.g., IP address #2 **392**) to use for communication with content delivery network **310** via network **315**. This new IP address is selected from IP address list **390**.

For example, origin server **340** and content delivery network **310** may be configured to use a set of IP addresses that span the range of, for example, 23.235.33.0 to 23.235.33.255 (a.k.a., a /24 IP address range) to be the private IP addresses in list **390** used by origin server **340** to communicate with content delivery network **310** via network **315**. Origin server **340** may start by using, for example, IP address #1 (e.g., 23.235.33.27). When it is determined that IP address #1 (e.g., 23.235.33.27) is under malicious attack, origin server **340** is reconfigured to use, for example, IP address #2 (e.g., 23.235.33.61). Content delivery network **310** is also reconfigured such that it knows to use IP address #2 to route communication with origin server **340** via network **315**. Thus, since origin server **340** is no longer responding to IP address #1 (e.g., 23.235.33.27) because it now responding to IP address #2 (e.g., 23.235.33.61), the effect of the malicious attack on origin server **340** is reduced or eliminated. As each IP address in IP address list **390** comes under attack, content delivery network **310** and origin server **340** cooperate to switch to another IP address from IP address list **390**—thus mitigating or eliminating the effects of subsequent malicious attacks on origin server **340**.

It should be understood that the list of IP addresses **390** may be a set of contiguous IP addresses (e.g., a /24 range). It should also be understood that IP address list **390** may comprise a non-contiguous list of IP addresses. These non-contiguous IP addresses may have more than one routing prefix. It should also be understood that origin server **340** and/or content delivery network **310** may use a predetermined (e.g., randomized, formulaic, sequential, listed, etc.) order for selecting the next IP address from IP address list **390**. It should also be understood that the members of IP address list **390** may be a range allocated to content delivery network **310**. Finally, it should be understood that after an IP address is determined to no longer be under attack, it may be reselected from IP address list **390** to be the IP address of origin server **340**.

FIG. 4 illustrates a method of operating a content delivery network. The steps illustrated in FIG. 4 may be performed by one or more elements of communication system **100** and/or communication system **300**. A set of private IP addresses are selected for use as IP addresses for the origin server for communication between the content delivery network and the origin server (**402**). For example, IP addresses list **390** may be selected for use as possible IP addresses for origin server **340**. The association between origin server **340** and the IP addresses on IP addresses list **390** may be kept secret, or hidden, from other users of network **315**.

The content delivery network communicates with the origin server using a first IP address of the set of private IP addresses (**404**). For example, content delivery network **310** may use IP address #1 (e.g., 23.235.33.27) from IP address list **390** to route communication with origin server **340** through network **315**.

It is determined that the first IP address is the subject of an attack (**406**). For example, origin server **340** may determine that its network interface associated with IP address #1 (e.g., 23.235.33.27) is the subject of a malicious attack (e.g., a SYN flood attack or a UDP flood attack) coming via network **315**.

The content delivery network communicates with the origin server using a second IP address of the set of private IP addresses (**408**). For example, in response to detecting an attack on IP address #1 (e.g., 23.235.33.27), content delivery network **310** and/or origin server **340** may be reconfigured

to use IP address #2 (e.g., 23.235.33.61) from IP address list **390** to route communication with origin server **340** through network **315**.

FIG. 5 illustrates a method of responding to a malicious attack on an origin server. The steps illustrated in FIG. 5 may be performed by one or more elements of communication system **100** and/or communication system **300**. A communication link is established between an origin server and a content delivery network using a first IP address for the origin server where the origin server is to provide content to the content delivery network by responding to requests for the content delivery network directed to the first IP address (**502**). For example, a communication link via network **315** can be established between origin server **340** and content delivery network **310** where origin server **340** responds to requests for content **345** that are directed to IP address #1 (e.g., 23.235.33.27).

It is determined that the first IP address is under attack (**504**). For example, origin server **340** may determine that its network interface associated with IP address #1 (e.g., 23.235.33.27) is under attack using traffic directed to IP address #1 (e.g., 23.235.33.27) via network **315**.

In response to determining that the first IP address is under attack, a second IP address is selected to be associated with the origin server (**506**). For example, in response to detecting an attack on IP address #1 (e.g., 23.235.33.27), content delivery network **310** and/or origin server **340** may select IP address #2 (e.g., 23.235.33.61) from IP address list **390** to be associated with origin server **340**.

A communication link is established between the origin server and the content delivery network using the second IP address for the origin server where the origin server is to provide content to the content delivery network by responding to requests for the content delivery network directed to the second IP address (**508**). For example, origin server **340** and content delivery network **310** can be reconfigured to use IP address #2 for a communication link via network **315** where origin server **340** is to respond to requests for content **345** that are directed to IP address #2 (e.g., 23.235.33.61).

To further describe the equipment and operation of a content server, FIG. 6 is provided which illustrates content server **600**. Content server **600** can be an example of content servers **111-113** of FIG. 1, and content servers **311-313** of FIG. 3, although variations are possible. Content server **600** includes network interface **601** and processing system **610**. Processing system **610** includes processing circuitry **611**, random access memory (RAM) **612**, and storage **613**, although further elements can be included, such as discussed in FIGS. 1 and 3. Example contents of RAM **612** are further detailed in RAM space **620**, and example contents of storage **613** are further detailed in storage system **660**.

Processing circuitry **611** can be implemented within a single processing device but can also be distributed across multiple processing devices or sub-systems that cooperate in executing program instructions. Examples of processing circuitry **611** include general purpose central processing units, microprocessors, application specific processors, and logic devices, as well as any other type of processing device. In some examples, processing circuitry **611** includes physically distributed processing devices, such as cloud computing systems.

Network interface **601** includes one or more network interfaces for communicating over communication networks, such as packet networks, the Internet, and the like. The network interfaces can include one or more local or wide area network communication interfaces which can communicate over Ethernet or Internet protocol (IP) links.

Network interface **601** can include network interfaces configured to communicate using one or more network addresses, which can be associated with different network links. Examples of network interface **601** include network interface card equipment, transceivers, modems, and other communication circuitry.

RAM **612** and storage **613** together can comprise a non-transitory data storage system, although variations are possible. RAM **612** and storage **613** can each comprise any storage media readable by processing circuitry **611** and capable of storing software. RAM **612** can include volatile and nonvolatile, removable and non-removable media implemented in any method or technology for storage of information, such as computer readable instructions, data structures, program modules, or other data. Storage **613** can include non-volatile storage media, such as solid state storage media, flash memory, phase change memory, magnetic memory, or as illustrated by storage system **460** in this example. RAM **612** and storage **613** can each be implemented as a single storage device but can also be implemented across multiple storage devices or sub-systems. RAM **612** and storage **613** can each comprise additional elements, such as controllers, capable of communicating with processing circuitry **611**.

Software stored on or in RAM **612** or storage **613** can comprise computer program instructions, firmware, or some other form of machine-readable processing instructions having processes that when executed a processing system direct content server **600** to operate as described herein. For example, software drives content server **600** to receive requests for content, determine if the content is stored in content server **600**, retrieve content from origin servers, transfer content to end user devices, manage data storage systems for handling and storing the content, among other operations. The software can also include user software applications. The software can be implemented as a single application or as multiple applications. In general, the software can, when loaded into a processing system and executed, transform the processing system from a general-purpose device into a special-purpose device customized as described herein.

RAM space **620** illustrates a detailed view of an example configuration of RAM **612**. It should be understood that different configurations are possible. RAM space **620** includes applications **630**, operating system (OS) **640**, and content RAM cache **650**. Content RAM cache **650** includes RAM space for temporary storage of content, such as dynamic random access memory (DRAM).

Applications **630** include content interface **631**, configuration interface **632**, tracking module **633**, and content caching application **634**. Content caching application **634** handles caching of content and management of storage spaces, such as content RAM cache **650** and storage space **665**, as well as exchanges content, data, and instructions via content interface **631**, configuration interface **632**, and tracking module **633**. Content caching application **634** can comprise a custom application, Varnish caching software, hypertext transfer protocol (HTTP) accelerator software, or other content caching and storage applications, including variation, modifications, and improvements thereof. Applications **630** and OS **640** can reside in RAM space **620** during execution and operation of content server **600**, and can reside in system software storage space **662** on storage system **660** during a powered-off state, among other locations and states. Applications **630** and OS **640** can be loaded into RAM space **620** during a startup or boot procedure as described for computer operating systems and applications.

Content interface **631**, configuration interface **632**, and tracking module **633** each allow a user to interact with and exchange data with content caching application **634**. In some examples, each of content interface **631**, configuration interface **632**, and tracking module **633** comprise an application programming interface (API). Content interface **631** allows for exchanging content for caching in content server **600** by content caching application **634**, and can also receive instructions to purge or erase data from content server **600**. Content interface **631** can retrieve tracking elements as well as network and web page content from origin servers for delivery to end users. Configuration interface **632** allows for altering the configuration of various operational features of content caching application **634**. In some examples, configuration interface **632** comprises a scripting language interface, such as Varnish Configuration Language (VCL), Perl, PHP, Javascript, or other scripting or interpreted language-based interfaces. Tracking module **633** can log and track requests by end user devices for tracking elements found in various web pages cached by content node **600**, and deliver log data or tracking information to external systems, among other operations. Content interface **631**, configuration interface **632**, and tracking module **633** can each communicate with external systems via network interface **601** over any associated network links.

Storage system **660** illustrates a detailed view of an example configuration of storage **613**. Storage system **660** can comprise flash memory such as NAND flash or NOR flash memory, phase change memory, magnetic memory, among other solid state storage technologies. As shown in FIG. 6, storage system **660** includes system software **662**, as well as content **661** stored in storage space **665**. As described above, system software **662** can be a non-volatile storage space for applications **630** and OS **640** during a powered-down state of content server **600**, among other operating software. Content **661** includes cached content, such as the web content examples in FIG. 1, which can include text, data, pictures, video, audio, web pages, scripting, code, dynamic content, or other network content. Content **661** can also include tracking elements, such as transparent GIFs, web bugs, Javascript tracking elements, among other tracking elements. In this example, content **661** includes network content and web pages associated with one or more websites, as indicated by www.gamma.gov, www.alpha.com, and www.beta.net.

Content server **600** is generally intended to represent a computing system with which at least software **630** and **640** are deployed and executed in order to render or otherwise implement the operations described herein. However, content server **600** can also represent any computing system on which at least software **630** and **640** can be staged and from where software **630** and **640** can be distributed, transported, downloaded, or otherwise provided to yet another computing system for deployment and execution, or yet additional distribution.

The included descriptions and figures depict specific embodiments to teach those skilled in the art how to make and use the best mode. For the purpose of teaching inventive principles, some conventional aspects have been simplified or omitted. Those skilled in the art will appreciate variations from these embodiments that fall within the scope of the invention. Those skilled in the art will also appreciate that the features described above can be combined in various ways to form multiple embodiments. As a result, the invention is not limited to the specific embodiments described above, but only by the claims and their equivalents.

13

What is claimed is:

1. A method comprising:
 - establishing a privatized link between a network node and an origin server by assigning a plurality of network addresses to the origin server and configuring the network node and the origin server to mutually cycle through the plurality of network addresses, whereby the network node directs a request to a selected network address of the plurality of network addresses to request content from the origin server; and
 - in response to an attack on the selected network address, selectively cycling through the plurality of network addresses mutually in the origin server and the network node, such that the network node directs a request to a new selected network address for requesting content from the origin server by the network node.
2. The method of claim 1 further comprising:
 - the network node comprises a content delivery network; and
 - sending a content request from the content delivery network to the origin server via the selected network address in response to receiving a request for the content that cannot be serviced by data cached at the content delivery network.
3. The method of claim 1 further comprising:
 - assigning the plurality of network addresses to the origin server from a set of network addresses allocated to the network node.
4. The method of claim 1 further comprising:
 - selectively cycling through the plurality of network addresses in a predetermined order.
5. The method of claim 4 further comprising:
 - the predetermined order is known to both the network node and the origin server; and
 - selectively cycling through the plurality of network addresses at both the network node and the origin server in response to the attack.
6. The method of claim 4, further comprising the predetermined order is a formulaic order.
7. The method of claim 4, further comprising the plurality of network addresses include a set of non-contiguous internet protocol (IP) addresses assigned to the origin server as a group.
8. An apparatus comprising:
 - a data storage medium storing instructions;
 - processing circuitry operatively coupled to the data storage medium that, when executing the instructions, operates to:
 - establish a privatized link between a network node and an origin server by assigning a plurality of network addresses to the origin server and configuring the network node and the origin server to mutually cycle through the plurality of network addresses;
 - transmit origin requests for media content to an origin server via a selected network address from the plurality of network addresses assigned to the origin server; and
 - in response to an attack on the selected network address, selectively cycle through the plurality of network addresses mutually in the origin server and the network node, such that the network node directs a request to a new selected network address for requesting content from the origin server.
9. The apparatus of claim 8 further comprising:
 - the processing circuitry includes a proxy node of a content delivery network; and
 - the processing circuitry further operating to send a content request to the origin server via the selected network

14

- address in response to receiving a request for the content that cannot be serviced by data cached at the proxy node.
10. The apparatus of claim 9 further comprising:
 - the plurality of network addresses are assigned to the origin server from a set of network addresses allocated to the content delivery network.
 11. The apparatus of claim 9 comprising the processing circuitry further operating to selectively cycle through the plurality of network addresses in a predetermined order.
 12. The apparatus of claim 11 further comprising:
 - the predetermined order is known to both the processing circuitry and the origin server; and
 - the processing circuitry further operating to selectively cycle through the plurality of network addresses in the predetermined order to continue communicating with the origin server when the origin server selectively cycles through the plurality of network addresses in the predetermined order in response to the attack.
 13. The apparatus of claim 11, wherein the predetermined order is a formulaic order.
 14. The apparatus of claim 11, wherein the plurality of network addresses include a set of non-contiguous internet protocol (IP) addresses assigned to the origin server as a group.
 15. A memory device storing instructions that, when executed, cause a processing system to perform a method comprising:
 - establishing a privatized link between a network node and an origin server by assigning a plurality of network addresses to the origin server and configuring the network node and the origin server to mutually cycle through the plurality of network addresses, whereby the network node directs a request to a selected network address of the plurality of network addresses to request content from the origin server; and
 - in response to an attack on the selected network address, selectively cycling through the plurality of network addresses mutually in the origin server and the network node, such that the network node directs a request to a new selected network address for requesting content from the origin server by the network node.
 16. The memory device of claim 15 storing instructions that, when executed, cause the processing system to perform the method further comprising:
 - selectively cycling through the plurality of network addresses in a predetermined order known to both the network node and the origin server.
 17. The memory device of claim 16 storing instructions that, when executed, cause the processing system to perform the method further comprising:
 - returning to a first selected network address from the plurality of network addresses once the attack has stopped.
 18. The memory device of claim 17 storing instructions that, when executed, cause the processing system to perform the method further comprising:
 - the network node comprises a content delivery network; and
 - sending a content request from the content delivery network to the origin server via the selected network address in response to receiving a request for the content that cannot be serviced by data cached at the content delivery network.
 19. The memory device of claim 18 storing instructions that, when executed, cause the processing system to perform the method further comprising:

15

assigning the plurality of network addresses to the origin server from a set of network addresses allocated to the network node.

20. The memory device of claim **19** wherein the plurality of network addresses include a set of non-contiguous internet protocol (IP) addresses assigned to the origin server as a group.

* * * * *

16