



(12) **United States Patent**  
**Abraham et al.**

(10) **Patent No.:** **US 7,994,975 B2**  
(45) **Date of Patent:** **Aug. 9, 2011**

(54) **METHOD AND SYSTEM FOR RF  
INTERFERENCE MITIGATION USING A  
BLANKING WATCHGUARD**

(75) Inventors: **Charles Abraham**, Los Gatos, CA (US);  
**Kambiz Shoarinejad**, Tustin, CA (US);  
**Jared Welz**, Seal Beach, CA (US)

(73) Assignee: **Broadcom Corporation**, Irvine, CA  
(US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **12/573,952**

(22) Filed: **Oct. 6, 2009**

(65) **Prior Publication Data**

US 2011/0080319 A1 Apr. 7, 2011

(51) **Int. Cl.**  
**G01S 19/21** (2010.01)  
**G01S 19/24** (2010.01)

(52) **U.S. Cl.** ..... **342/357.59**; 342/357.63

(58) **Field of Classification Search** ..... 342/357.59,  
342/357.63

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,114,105 A \* 9/1978 Duncan ..... 455/223  
7,295,635 B2 \* 11/2007 Coataniec et al. .... 375/346  
7,362,264 B2 \* 4/2008 Landmark ..... 342/357.59

\* cited by examiner

*Primary Examiner* — Thomas H Tarcza


*Assistant Examiner* — Cassi Galt

(74) *Attorney, Agent, or Firm* — McAndrews, Held &  
Malloy, Ltd.

(57) **ABSTRACT**

A global navigation satellite system (GNSS) enabled mobile device may be operable to monitor and determine counts at which autoblack signals are asserted over time intervals corresponding to consecutive time windows during the RF interference mitigation process using autoblanking. The GNSS enabled mobile device may be operable to disable the generation of a blank signal when the count may be greater than a particular count threshold at the end of the time window. The GNSS enabled mobile device may be operable to enable the generation of a blank signal when the count may be less than or equal to a particular count threshold at the end of the time window. The blank signals may be used to blank the processing of the received GNSS signals.

**20 Claims, 6 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

1

# METHOD AND SYSTEM FOR RF INTERFERENCE MITIGATION USING A BLANKING WATCHGUARD

CROSS-REFERENCE TO RELATED  
APPLICATIONS/INCORPORATION BY  
REFERENCE

Not applicable

## FIELD OF THE INVENTION

Certain embodiments of the invention relate to wireless communication. More specifically, certain embodiments of the invention relate to a method and system for RF interference mitigation using a blanking watchguard.

## BACKGROUND OF THE INVENTION

The global positioning system (GPS), the global orbiting navigation satellite system (GLONASS), and the satellite navigation system GALILEO are examples of global navigation satellite systems (GNSS). A GNSS utilizes an earth-orbiting constellation of a plurality of satellites each broadcasting GNSS signals which indicates its precise location and ranging information. From particular locations on or near the earth, GNSS receivers may detect valid GNSS signals using a temperature compensated crystal oscillator (TCXO) and take various GNSS measurements such as pseudorange, carrier phase, and/or Doppler to calculate navigation information such as GNSS receiver positions, velocity, and time.

The GNSS receivers may be integrated within or externally coupled to mobile devices for exemplary navigation applications comprising E911, location-based 411, location-based messaging. The mobile devices may provide connections to access applications such as route tracking, multimedia communication, song downloading, instant messaging, making phone call, and/or mobile television (TV). In mobile devices there may be multiple sources of RF interference. Such interference may be present in a GNSS band and may result from unintentional sources, such as TV/FM harmonics, radar, MSS, or may result from hostile (jamming) efforts. Some interference sources are continuous, such as WCDMA transmissions or spurious emissions from other circuits, while others are pulse (burst), such as GSM or EDGE transmissions.

Further limitations and disadvantages of conventional and traditional approaches will become apparent to one of skill in the art, through comparison of such systems with the present invention as set forth in the remainder of the present application with reference to the drawings.

## BRIEF SUMMARY OF THE INVENTION

A system and/or method for RF interference mitigation using a blanking watchguard, substantially as shown in and/or described in connection with at least one of the figures, as set forth more completely in the claims.

Various advantages, aspects and novel features of the present invention, as well as details of an illustrated embodiment thereof, will be more fully understood from the following description and drawings.

## BRIEF DESCRIPTION OF SEVERAL VIEWS OF THE DRAWINGS

FIG. 1 is a diagram illustrating an exemplary communication system that is operable to provide RF interference mitigation using a blanking watchguard, in accordance with an embodiment of the invention.

2

FIG. 2 is a block diagram illustrating an exemplary GNSS enabled mobile device that is operable to provide RF interference mitigation using a blanking watchguard, in accordance with an embodiment of the invention.

FIG. 3 is a block diagram illustrating an exemplary GNSS receiver that is operable to provide RF interference mitigation using a blanking watchguard, in accordance with an embodiment of the invention.

FIG. 4 is a block diagram illustrating an exemplary GNSS autoblanker that is operable to provide RF interference mitigation using a blanking watchguard, in accordance with an embodiment of the invention.

FIG. 5 is a flow chart illustrating exemplary steps for RF interference mitigation using autoblanking, in accordance with an embodiment of the invention.

FIG. 6 is a flow chart illustrating exemplary steps for blanking watchguard during RF interference mitigation process, in accordance with an embodiment of the invention.

## DETAILED DESCRIPTION OF THE INVENTION

Certain embodiments of the invention can be found in a method and system for RF interference mitigation using a blanking watchguard. In various embodiments of the invention, a global navigation satellite system (GNSS) enabled mobile device may be operable to determine a rate at which autoblank signals are asserted. The autoblank signals may be asserted during the RF interference mitigation process using autoblanking. The GNSS enabled mobile device may be operable to control the processing of received GNSS signals based on the determined rate of asserted autoblank signals. In this regard, the GNSS enabled mobile device may be operable to monitor the autoblank signals over time intervals corresponding to consecutive time windows. The GNSS enabled mobile device may be operable to determine a count of the autoblank signals that are received during the time interval corresponding to the time window. The GNSS enabled mobile device may be operable to compare the determined count to a count threshold. In this regard, the count may be, for example, a percentage of time within the time window when the autoblank signals are received, and the count threshold may be a particular percentage of time. The count may also be, for example, a total number of the autoblank signals received during the time window, and the count threshold may be a particular number of the autoblank signals. The GNSS enabled mobile device may be operable to disable the generation of a blank signal when the count is greater than the count threshold at the end of the time window. The GNSS enabled mobile device may be operable to enable the generation of a blank signal when the count is less than or equal to the count threshold at the end of the time window, and the blank signal is used to blank the processing of received GNSS signals. The GNSS enabled mobile device may be operable to disable the generation of a blank signal when the count is greater than the count threshold at a time, for example, prior to the end of the time window. The GNSS enabled mobile device may be operable to enable the generation of a blank signal when the count is less than or equal to the count threshold at a time, for example, prior to the end of the time window, and the blank signal is used to blank the processing of received GNSS signals.

FIG. 1 is a diagram illustrating an exemplary communication system that is operable to provide RF interference mitigation using a blanking watchguard, in accordance with an embodiment of the invention. Referring to FIG. 1, there is shown a communication system 100. The communication system comprises a plurality of GNSS enabled mobile

devices **110**, of which GNSS enabled mobile devices **110a-110d** are illustrated, a GNSS infrastructure **120**, a wireless communication network **130**. The GNSS infrastructure **120** comprises a plurality of GNSS satellites such as GNSS satellites **120a** through **120c**.

A GNSS enabled mobile device such as the GNSS enabled mobile device **110a** may comprise suitable logic, circuitry, interfaces and/or code that are operable to communicate radio signals across the wireless communication network **130**. The GNSS enabled mobile device **110a** may be operable to receive GNSS broadcast signals from a plurality of visible GNSS satellites such as GNSS satellites **120a** through **120c** in the GNSS infrastructure **120**. The received GNSS signals may be utilized to determine navigation information such as a position fix and/or a velocity of the GNSS enabled mobile device **110a**. The determined navigation information such as a position fix of the GNSS enabled mobile device **110a** may be communicated with, for example, the wireless communication network **130**, for various navigation applications such as E911, location-based 411, location-based messaging, etc.

The GNSS signals that are received by the GNSS enabled mobile device **110a** may comprise RF interference. In some instances when the RF interference level is high, the RF interference may almost wipe out the GNSS signal to the point where it may be better not to process the GNSS signal (blank the GNSS signal processing) during that time using a RF interference mitigation method, such as, for example, the autoblanking method. Some RF interference occurs continuously such as in WCDMA transmissions (continuous jammer) in the wireless communication network **130** and some RF interference occurs for a short burst of time such as in GSM or EDGE transmissions (burst jammer) in the wireless communication network **130**. In instances when the RF interference is a continuous jammer, the autoblank signals asserted using autoblanking may not be stopped for a long time or may never be stopped during the RF interference mitigation process. In this regard, the GNSS enabled mobile device **110a** may be operable to perform the RF interference mitigation using autoblanking and blank monitoring with watchguard. During the RF interference mitigation process, the GNSS enabled mobile device **110a** may be operable to assert autoblank signals using autoblanking. The GNSS enabled mobile device **110a** may be operable to monitor and determine the rate of the autoblank signals and control the blanking of processing of received GNSS signals based on the rate of the autoblank signals. In instances when it is determined that the rate of the autoblank signals is too high, for example, the rate exceeds a particular rate threshold, the GNSS enabled mobile device **110a** may be operable to disable or stop the blanking of processing of received GNSS signals.

A GNSS satellite such as the GNSS satellite **120a** may comprise suitable logic, circuitry, interfaces and/or code that is operable to provide satellite navigational information to various GNSS receivers on earth. In an embodiment of the invention, the GNSS receivers, such as GPS, GALILEO or GLONASS receivers, may be integrated within GNSS capable mobile devices such as the GNSS enabled mobile devices **110a** through **110d**.

The wireless communication network **130** may comprise suitable logic, circuitry, interfaces and/or code that may be operable to provide voice and data services to various mobile devices such as the GNSS enabled mobile devices **110a-110d** by using wireless communication technologies such as, for example, WCDMA, GSM, GPRS, UMTS, EDGE, EGPRS, LTE, WiMAX, Wi-Fi, and/or Bluetooth.

In operation, a GNSS enabled mobile device such as the GNSS enabled mobile device **110a** may be operable to detect and receive GNSS signals from, for example, the GNSS satellites **120a-120c**. The GNSS enabled mobile device **110a** may be operable to perform the RF interference mitigation using autoblanking and blank monitoring with watchguard. During the RF interference mitigation process, the GNSS enabled mobile device **110a** may be operable to assert autoblank signals using autoblanking. The GNSS enabled mobile device **110a** may be operable to monitor and determine the rate of the autoblank signals and control the blanking of processing of received GNSS signals based on the rate of the autoblank signals. In instances when it is determined that the rate of autoblank signals is too high, for example, the rate exceeds a particular rate threshold, the GNSS enabled mobile device **110a** may be operable to disable or stop the blanking of processing of received GNSS signals.

FIG. 2 is a block diagram illustrating an exemplary GNSS enabled mobile device that is operable to provide RF interference mitigation using a blanking watchguard, in accordance with an embodiment of the invention. Referring to FIG. 2, there is shown a GNSS enabled mobile device **200**. The GNSS enabled mobile device **200** may comprise a GNSS receiver **202**, a wireless transceiver **204**, a host processor **208**, and a memory **210**.

The GNSS receiver **202** may comprise suitable logic, circuitry, interfaces and/or code that may be operable to detect and receive GNSS signals from a plurality of visible GNSS satellites **120a-120c**. The GNSS receiver **202** may be operable to utilize the received GNSS signals to calculate navigation information such as a position fix and/or velocity of the GNSS receiver **202**. The calculated navigation information may be provided to the host processor **208** to be communicated with the wireless communication network **130** for various navigation applications such as, for example, location-based 411. The GNSS receiver **202** may be operable to perform RF interference mitigation using autoblanking and blank monitoring with watchguard. During the RF interference mitigation process, the GNSS receiver **202** may be operable to assert autoblank signals using autoblanking. The GNSS receiver **202** may be operable to monitor and determine the rate of the autoblank signals and control the blanking of processing of received GNSS signals based on the rate of the autoblank signals. In instances when it is determined that the rate of autoblank signals is too high, for example, the rate exceeds a particular rate threshold, the GNSS receiver **202** may be operable to disable or stop the blanking of processing of received GNSS signals.

The wireless transceiver **204** may comprise suitable logic, circuitry, interfaces and/or code that may be operable to communicate radio signals over the wireless communication network **130**.

The host processor **208** may comprise suitable logic, circuitry, interfaces and/or code that may be operable to process signals from the GNSS receiver **202** and the wireless transceiver **204**. The host processor **208** may be operable to communicate signals with the wireless communication network **130** via the wireless transceiver **204**. The host processor **208** may be operable to communicate navigation information with the wireless communication network **130** for various navigation applications such as location-based 411 and/or roadside assistance.

The memory **210** may comprise suitable logic, circuitry, and/or code that operable to store information such as executable instructions and data that may be utilized by the host processor **208**. The memory **210** may comprise RAM, ROM,

low latency nonvolatile memory such as flash memory and/or other suitable electronic data storage.

In operation, the GNSS receiver **202** may be operable to receive GNSS signals from a plurality of visible GNSS satellites **120a-120c**. The GNSS receiver **202** may be operable to perform RF interference mitigation using autoblanking and blank monitoring with watchdog. During the RF interference mitigation process, the GNSS receiver **202** may be operable to assert autoblank signals using autoblanking. The GNSS receiver **202** may be operable to monitor and determine the rate of the autoblank signals. The GNSS receiver **202** may be operable to control the blanking of the received GNSS signals based on the determined rate of the autoblank signals. In instances when it is determined that the rate of autoblank signals is too high, for example, the rate exceeds a particular rate threshold, the GNSS receiver **202** may be operable to disable or stop the blanking of processing of received GNSS signals.

FIG. **3** is a block diagram illustrating an exemplary GNSS receiver that is operable to provide RF interference mitigation using a blanking watchdog, in accordance with an embodiment of the invention. Referring to FIG. **3**, there is shown a GNSS receiver **300**. The GNSS receiver **300** may comprise a GNSS antenna **301**, a GNSS front-end **302**, a GNSS processor **304**, a GNSS autoblanker **306**, and a GNSS memory **308**.

The GNSS antenna **301** may comprise suitable logic, circuitry, interfaces and/or code that may be operable to receive GNSS signals from a plurality of visible GNSS satellites such as the GNSS satellites **120a** through **120c**. The GNSS antenna **301** may be operable to communicate the received GNSS signals to the GNSS front-end **302** for further processing.

The GNSS front-end **302** may comprise suitable logic, circuitry, interfaces and/or code that may be operable to convert the received GNSS signals to GNSS baseband signals, which may be suitable for further processing in the GNSS baseband processor **304** and in the GNSS autoblanker **306**. The GNSS front-end **302** may be operable to detect and track GNSS signals.

The GNSS baseband processor **304** may comprise suitable logic, circuitry, interfaces and/or code that may be operable to process GNSS baseband signals from the GNSS front-end **302** to extract the information and data bits conveyed in the received GNSS signals. The GNSS baseband processor **304** may be operable to perform functions such as clock recovery, channel selection, demodulation, and/or decoding. The GNSS baseband processor **304** may be operable to calculate navigation information such as a position fix using the GNSS baseband signals from the GNSS front-end **302**. The GNSS baseband processor **304** may be operable to communicate the calculated navigation information with the host processor **208** for various navigation applications such as E911 supported by the wireless communication network **130**. The GNSS baseband processor **304** may be operable to process blanking signals from the GNSS autoblanker **306**. Instances when the GNSS baseband processor **304** receives blanking signals from the GNSS autoblanker **306**, the GNSS baseband processor **304** may be operable to stop the processing of received GNSS signals until the blanking signals stop.

The GNSS autoblanker **306** may comprise suitable logic, circuitry, interfaces and/or code that may be operable to receive signals from the GNSS front-end **302** and perform RF interference mitigation using autoblanking and blank monitoring with watchdog. During the RF interference mitigation process, the GNSS autoblanker **306** may be operable to assert autoblank signals using autoblanking. The GNSS autoblanker **306** may be operable to monitor and determine the rate of the autoblank signals and control the blanking of

processing of received GNSS signals based on the rate of the autoblank signals. In instances when it is determined that the rate of autoblank signals is too high, for example, the rate exceeds a particular rate threshold, the GNSS autoblanker **306** may be operable to disable or stop the blanking of processing of received GNSS signals. The GNSS autoblanker **306** may be operable to communicate blanking signals with the GNSS baseband processor **304** for further processing.

The GNSS memory **308** may comprise suitable logic, circuitry, interfaces and/or code that may enable storage of information such as executable instructions and data that may be utilized by the GNSS baseband processor **304**. The executable instructions may be utilized to calculate a position fix of the GNSS receiver **300** using GNSS measurements. The data may comprise the determined position fix of the GNSS receiver **300**. The GNSS memory **308** may comprise RAM, ROM, low latency nonvolatile memory such as flash memory and/or other suitable electronic data storage.

In operation, the GNSS antenna **301** may be operable to receive GNSS signals for GNSS measurements. The GNSS front-end **302** may be operable to process the received GNSS signals and convert into GNSS baseband signals. The converted GNSS baseband signals may be communicated with the GNSS baseband processor **304** for GNSS baseband processing. The processed GNSS baseband signals may be used to calculate a position fix of the GNSS receiver **300**. The calculated position fix may be forward to the host processor **210** for a navigation application. The GNSS autoblanker **306** may be operable to receive signals from the GNSS front-end **302** and perform RF interference mitigation using autoblanking and blank monitoring with watchdog. During the RF interference mitigation process, the GNSS autoblanker **306** may be operable to assert autoblank signals using autoblanking. The GNSS autoblanker **306** may be operable to monitor and determine the rate of the autoblank signals. The GNSS autoblanker **306** may be operable to control the blanking of processing of the received GNSS signals based on the determined rate of the autoblank signals. In instances when it is determined that the rate of autoblank signals is too high, for example, the rate exceeds a particular rate threshold, the GNSS autoblanker **306** may be operable to disable or stop the blanking of processing of received GNSS signals. The GNSS autoblanker **306** may be operable to communicate blanking signals with the GNSS baseband processor **304** for further processing. In instances when the GNSS baseband processor **304** receives the blanking signals from the GNSS autoblanker **306**, the GNSS baseband processor **304** may be operable to stop the processing of received GNSS signals until the blanking signals stop.

FIG. **4** is a block diagram illustrating an exemplary GNSS autoblanker that is operable to provide RF interference mitigation using a blanking watchdog, in accordance with an embodiment of the invention. Referring to FIG. **4**, there is shown a GNSS autoblanker **400**. The GNSS autoblanker **400** may comprise an autoblank detector **402**, a blank monitor **404**, a GNSS signal **410**, an autoblank signal **420**, and a blank signal **430**.

The autoblank detector **402** may comprise suitable logic, circuitry, interfaces and/or code that may be operable to receive a GNSS signal **410** from, for example, an ADC converter in the GNSS front-end **302** described with respect to FIG. **3**, detect the level of RF interference and assert an autoblank signal **420** during a RF interference mitigation process. If the RF interference level is high, it may almost wipe out the GNSS signal **410** to the point where it may be better not to process the GNSS signal **410** (blank the GNSS signal processing) during that time using a RF interference

mitigation method, such as, for example, the autoblanking method implemented by the autoblank detector **410**. In an exemplary embodiment of the invention, the autoblank detector **402** may be operable to establish consecutive time windows namely, for example, detector time windows for detecting the received GNSS signal **410** for RF interference level. The autoblank detector **402** may establish a signal level threshold as a reference for signal levels of received GNSS signals **410**. During the time interval within the detector time window, the number of received GNSS signals **410** whose absolute signal levels exceed the signal level threshold may be computed. The autoblank detector **402** may establish another threshold, namely, for example, a signal number threshold as a reference for above mentioned number of received GNSS signals **410** whose absolute signal levels exceed the signal level threshold. The autoblank detector **402** may be operable to assert an autoblank signal **420** if the number of received GNSS signals **410** whose absolute signal levels exceed the signal level threshold exceeds the signal number threshold.

The blank monitor **404** may comprise suitable logic, circuitry, interfaces and/or code that may be operable to receive an autoblank signal **420** which may be asserted by the autoblank detector **402**, monitor the received autoblank signals **420** and determine whether a blank signal **430** may be generated or enabled based on the result of the monitoring of received autoblank signals **420**. An autoblank signal **420** may be asserted in instances when RF interference is detected. Some RF interference is on continuously such as in WCDMA transmissions (continuous jammer) and some RF interference is on only for a burst of time such as in GSM or EDGE transmissions (burst jammer). In instances when the RF interference is a burst jammer, an autoblank signal **420** may be stopped as soon as the RF interference may go away and the RF interference mitigation process may be stopped. On the other hand, in instances when the RF interference is a continuous jammer, an autoblank signal **420** may not be stopped for a long time or may never be stopped during a RF interference mitigation process.

A blanking watchdog process may be implemented by the blank monitor **404**. In an exemplary embodiment of the invention, the blank monitor **404** may be operable to establish consecutive time windows namely, for example monitor time windows. The monitor time window may be much longer than the detector time window used for autoblanking. A count may be computed based on the number of total autoblank signals **420** received during the time interval within the monitor time window. The blank monitor **404** may be operable to establish a threshold namely, for example, a count threshold as a reference for above mentioned count. In instances when the count exceeds the count threshold at the end of the monitor time window, the generation of a blank signal **430** may be disabled. In instances when the count does not exceed the count threshold at the end of the monitor time window, the generation of a blank signal **430** may be enabled. The blank signal **430**, instead of the autoblank signal **420**, may be used to blank the processing of GNSS signals **410**, for example, to stop the correlation process performed in the GNSS baseband processor **304** described with respect to FIG. 3. The computed count may be a percentage of time within the monitor time window when one or more of autoblank signals **420** are received and the count threshold may be a particular percentage of time. The computed count may be the number of total autoblank signals **420** received during the time interval within the monitor time window and the count threshold may be a particular number of autoblank signals **420**. In an embodiment of the invention, the generation of a blank signal **430**

may be disabled or enabled at a time prior to the end of the monitor time window, for example, at the middle of the monitor time window.

In operation, the autoblank detector **402** may be operable to receive GNSS signals **410** during the RF interference mitigation process. During each of the consecutive detector time windows, the number of received GNSS signals **410** whose absolute signal levels exceed the signal level threshold may be computed. The autoblank detector **402** may be operable to assert an autoblank signal **420** if the number of received GNSS signals **410** whose absolute signal levels exceed the signal level threshold exceeds the signal number threshold. The blank monitor **404** may be operable to receive autoblank signals **420** which may be asserted by the autoblank detector **402**. During each of the consecutive monitor time windows, a count, for example, the percentage of time within the monitor time window when one or more of autoblank signals **420** are received or the number of total autoblank signals **420** received during the time interval within the monitor time window may be computed. The blank monitor **404** may be operable to stop or disable the blank signals **430** in instances when the count exceeds the count threshold at the end or, for example, at the middle of the monitor time window. The blank monitor **404** may be operable to generate or enable the blank signals **430** in instances when the count does not exceed the count threshold at the end or at a time prior to the end of the monitor time window, for example, at the middle of the monitor time window.

FIG. 5 is a flow diagram illustrating exemplary steps for RF interference mitigation using autoblanking, in accordance with an embodiment of the invention. Referring to FIG. 5, the exemplary steps may start with step **510**. In step **510**, the autoblank detector **402** may be operable to receive GNSS signals. In step **512**, the autoblank detector **402** may compute the number of received GNSS signals whose absolute signal levels exceed the signal level threshold during the detector time window. In step **514**, the end of the detector time window is checked. In instances when the end of the detector time window is reached, the exemplary steps may proceed to step **516**. In step **516**, in instances when the computed number is greater than the signal number threshold, the exemplary steps may proceed to step **518**. In step **518**, the autoblank detector **402** may assert an autoblank signal and the exemplary steps may proceed to step **510**. In step **514**, in instances when the end of the detector time window is not reached, the exemplary steps may proceed to step **510**. In step **516**, in instances when the computed number is less than or equal to the signal number threshold, the exemplary steps may proceed to step **510**.

FIG. 6 is a flow diagram illustrating exemplary steps for blanking watchdog during RF interference mitigation process, in accordance with an embodiment of the invention. Referring to FIG. 6, the exemplary steps may start with step **610**. In step **610**, the blank monitor **404** may be operable to receive autoblank signals **420** from the autoblank detector **402**. In step **612**, the blank monitor **404** may compute a count based on the number of total autoblank signals **420** received during the monitor time window. In step **614**, the end of the monitor time window is checked. In instances when the end of the monitor time window is reached, the exemplary steps may proceed to step **616**. In step **616**, in instances when the count is greater than the count threshold, the exemplary steps may proceed to step **618**. In step **618**, the blank monitor **404** may be operable to disable the generation of a blank signal **430** and exemplary steps may proceed to step **610**. In step **614**, in instances when the end of the monitor time window is not reached, the exemplary steps may proceed to step **610**. In step **616**, in instances when the count is less than or equal to the

count threshold, the exemplary steps may proceed to step 620. In step 620, the blank monitor 404 may be operable to enable the generation of a blank signal and the exemplary steps may proceed to step 610.

In various embodiments of the invention, a global navigation satellite system (GNSS) enabled mobile device 200 may be operable to determine a rate at which autoblank signals 420 are asserted. The autoblank signals 420 may be asserted during the RF interference mitigation process using autoblanking. The GNSS enabled mobile device 200 may be operable to control the processing of received GNSS signals 410 based on the determined rate of asserted autoblank signals 420. In this regard, the GNSS enabled mobile device 200 may be operable to monitor the autoblank signals 420 over time intervals corresponding to consecutive time windows. The GNSS enabled mobile device 200 may be operable to determine a count of the autoblank signals 420 that are received during the time interval corresponding to the time window. The GNSS enabled mobile device 200 may be operable to compare the determined count to a count threshold. In this regard, the count may be, for example, a percentage of time within the time window when the autoblank signals 420 are received, and the count threshold may be a particular percentage of time. The count may also be, for example, a total number of the autoblank signals 420 received during the time window, and the count threshold may be a particular number of the autoblank signals 420. The GNSS enabled mobile device 200 may be operable to disable the generation of a blank signal 430 when the count is greater than the count threshold at the end of the time window. The GNSS enabled mobile device 200 may be operable to enable the generation of a blank signal 430 when the count is less than or equal to the count threshold at the end of the time window, and the blank signal 430 is used to blank the processing of received GNSS signals 410. The GNSS enabled mobile device 200 may be operable to disable the generation of a blank signal 430 when the count is greater than the count threshold at a time, for example, prior to the end of the time window. The GNSS enabled mobile device 200 may be operable to enable the generation of a blank signal 430 when the count is less than or equal to the count threshold at a time, for example, prior to the end of the time window, and the blank signal 430 is used to blank the processing of the received GNSS signals 410.

Another embodiment of the invention may provide a machine and/or computer readable storage and/or medium, having stored thereon, a machine code and/or a computer program having at least one code section executable by a machine and/or a computer, thereby causing the machine and/or computer to perform the steps as described herein for RF interference mitigation using a blanking watchdog.

Accordingly, the present invention may be realized in hardware, software, or a combination of hardware and software. The present invention may be realized in a centralized fashion in at least one computer system or in a distributed fashion where different elements are spread across several interconnected computer systems. Any kind of computer system or other apparatus adapted for carrying out the methods described herein is suited. A typical combination of hardware and software may be a general-purpose computer system with a computer program that, when being loaded and executed, controls the computer system such that it carries out the methods described herein.

The present invention may also be embedded in a computer program product, which comprises all the features enabling the implementation of the methods described herein, and which when loaded in a computer system is able to carry out these methods. Computer program in the present context

means any expression, in any language, code or notation, of a set of instructions intended to cause a system having an information processing capability to perform a particular function either directly or after either or both of the following: a) conversion to another language, code or notation; b) reproduction in a different material form.

While the present invention has been described with reference to certain embodiments, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted without departing from the scope of the present invention. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the present invention without departing from its scope. Therefore, it is intended that the present invention not be limited to the particular embodiment disclosed, but that the present invention will include all embodiments falling within the scope of the appended claims.

What is claimed is:

1. A method for communication, the method comprising: performing by one or more processors and/or circuits in a global navigation satellite system (GNSS) enabled mobile device:
  - determining a rate at which autoblank signals are asserted for each of consecutive time windows; and,
  - controlling processing of received GNSS signals based on said determined rate.
2. The method according to claim 1, comprising monitoring said autoblank signals over time intervals corresponding to said consecutive time windows.
3. The method according to claim 2, comprising determining a count of said autoblank signals that are received during said time interval corresponding to said time window.
4. The method according to claim 3, comprising comparing said determined count to a count threshold.
5. The method according to claim 4, wherein said count comprises a percentage of time within said time window when said autoblank signals are received, and said count threshold comprises a particular percentage of time.
6. The method according to claim 4, wherein said count comprises a total number of said autoblank signals received during said time window, and said count threshold comprises a particular number of said autoblank signals.
7. The method according to claim 4, comprising disabling generation of a blank signal when said count is greater than said count threshold at an end of said time window, wherein said blank signal is used to blank said processing of said received GNSS signals.
8. The method according to claim 4, comprising enabling generation of a blank signal when said count is less than or equal to said count threshold at an end of said time window, wherein said blank signal is used to blank said processing of said received GNSS signals.
9. The method according to claim 4, comprising disabling generation of a blank signal when said count is greater than said count threshold at a time prior to an end of said time window, wherein said blank signal is used to blank said processing of said received GNSS signals.
10. The method according to claim 4, comprising enabling generation of a blank signal when said count is less than or equal to said count threshold at a time prior to an end of said time window, wherein said blank signal is used to blank said processing of said received GNSS signals.
11. A system for communication, the system comprising: one or more processors and/or circuits for use in a global navigation satellite system (GNSS) enabled mobile device, wherein said one or more processors and/or circuits are operable to:

**11**

determine a rate at which autoblack signals are asserted for each of consecutive time windows; and, control processing of received GNSS signals based on said determined rate.

**12.** The system according to claim **11**, wherein said one or more processors and/or circuits are operable to monitor said autoblack signals over time intervals corresponding to said consecutive time windows.

**13.** The system according to claim **12**, wherein said one or more processors and/or circuits are operable to determine a count of said autoblack signals that are received during said time interval corresponding to said time window.

**14.** The system according to claim **13**, wherein said one or more processors and/or circuits are operable to compare said determined count to a count threshold.

**15.** The system according to claim **14**, wherein said count comprises a percentage of time within said time window when said autoblack signals are received, and said count threshold comprises a particular percentage of time.

**16.** The system according to claim **14**, wherein said count comprises a total number of said autoblack signals received during said time window, and said count threshold comprises a particular number of said autoblack signals.

**17.** The system according to claim **14**, wherein said one or more processors and/or circuits are operable to disable gen-

**12**

eration of a blank signal when said count is greater than said count threshold at an end of said time window, and said blank signal is used to blank said processing of said received GNSS signals.

**18.** The system according to claim **14**, wherein said one or more processors and/or circuits are operable to enable generation of a blank signal when said count is less than or equal to said count threshold at an end of said time window, and said blank signal is used to blank said processing of said received GNSS signals.

**19.** The system according to claim **14**, wherein said one or more processors and/or circuits are operable to disable generation of a blank signal when said count is greater than said count threshold at a time prior to an end of said time window, and said blank signal is used to blank said processing of said received GNSS signals.

**20.** The system according to claim **14**, wherein said one or more processors and/or circuits are operable to enable generation of a blank signal when said count is less than or equal to said count threshold at a time prior to an end of said time window, and said blank signal is used to blank said processing of said received GNSS signals.

\* \* \* \* \*