

(19) **DANMARK**

(10) **DK/EP 2600656 T3**



(12)

Oversættelse af europæisk patentskrift

Patent- og
Varemærkestyrelsen

-
- (51) Int.Cl.: **H 04 W 48/16 (2009.01)** *H 04 W 48/12 (2009.01)*
- (45) Oversættelsen bekendtgjort den: **2015-03-30**
- (80) Dato for Den Europæiske Patentmyndigheds bekendtgørelse om meddelelse af patentet: **2014-12-31**
- (86) Europæisk ansøgning nr.: **13153807.6**
- (86) Europæisk indleveringsdag: **2008-10-28**
- (87) Den europæiske ansøgnings publiceringsdag: **2013-06-05**
- (30) Prioritet: **2007-10-29 US 983511 P**
- (62) Stamansøgningsnr: **08845555.5**
- (84) Designerede stater: **AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR**
- (73) Patenthaver: **InterDigital Patent Holdings, Inc., 200 Bellevue Parkway , Suite 300, Wilmington, DE 19809, USA**
- (72) Opfinder: **Somasundaram, Shankar, Flat 150, Clarence Gate Gardens, London, NW1 6AP, Storbritannien**
Pasad, Kalpendu R., 6E. Nicholai Stret, Hicksville, NY 11801, USA
WANG, Jin, 14 Leicester Court, Princeton, NJ 08540, USA
- (74) Fuldmægtig i Danmark: **Awapatent A/S, Rigensgade 11, 1316 København K, Danmark**
- (54) Benævnelse: **Systeminformationsopdateringer i LTE**
- (56) Fremdragne publikationer:
EP-A- 2 007 087
WO-A-2005/117297
WO-A-2008/050958
NOKIA CORPORATION ET AL: "System Information Scheduling - Clarifications", 3GPP DRAFT; R2-080156, 3RD GENERATION PARTNERSHIP PROJECT (3GPP), MOBILE COMPETENCE CENTRE ; 650, ROUTE DES LUCIOLES ; F-06921 SOPHIA-ANTIPOLIS CEDEX ; FRANCE, vol. tsg_ran\WG2_RL2\TSGR2_60bis\Docs, no. Sevilla, Spain; 20080114, 7 January 2008 (2008-01-07), XP050138036,

EP 2 600 656 B1

Description

FIELD OF INVENTION

5 [0001] The present invention is related to wireless communication systems.

BACKGROUND

10 [0002] The Third Generation Partnership Project (3GPP) has initiated the Long Term Evolution (LTE) program to bring new technology, new network architecture, new configurations and new applications and services to wireless networks in order to provide improved spectral efficiency and faster user experiences. In an LTE compliant network, a wireless transmit receive unit (WTRU) may receive system information updates. Included in the system information updates may be the size and location of a Physical HARQ Indicator Channel (PHICH).

15 [0003] A WTRU may receive updated system information on a Primary Broadcast Channel (P-BCH) or Dynamic-BCH (D-BCH). Resource allocation for system information updates may be fixed or variable, but variable resource allocation is preferred for signaling efficiency.

[0004] Variable resource allocation, however, suffers from a disadvantage. A WTRU may experience excessive latency when waking from Discontinuous Reception (DRX) cycle and excessive overhead may be required to signal system update information. A WTRU may need to wait as long as 80 ms before it receives an entire D-BCH message. Latency becomes an issue if the eNodeB (eNB) is permitted to change system information every D-BCH cycle.

20 [0005] If a WTRU wakes up from DRX exactly at the D-BCH boundary, it has to wait at least 80 ms for D-BCH to be completely received before it can decode and retrieve the system information update. During this interval, the WTRU does not know if the system information has changed since its last uplink (UL) transmission. If the WTRU wakes up in the middle of the D-BCH cycle, then it cannot decode the D-BCH in its current cycle. The result may be as much as a 150 ms delay, which is not acceptable for time sensitive applications such as voice over Internet protocol (VoIP). Similar latency is experienced when system information updates are transmitted on the P-BCH, with a potential latency of 70 ms.

25 [0006] WO 2005117297 relates to a method for indicating the validity of a channel configuration. Configuration information for establishing the reception of a physical channel carrying point-to-multipoint services is sent via a point-to-multipoint control channel to a mobile terminal. Validity information is sent together with the configuration information for indicating to the mobile terminal when or how long the configuration information is valid.

30 [0007] Therefore, there exists a need for an improved method and apparatus for signaling system information updates.

SUMMARY

35 [0008] Methods and apparatuses as defined by the appended independent claims are provided.

[0009] A method and apparatus for receiving system information updates may include a wireless transmit receive unit (WTRU) receiving a system frame number. The WTRU may also receive system information messages in a modification period. The modification period has a boundary determined by the system frame number. The WTRU may receive a system information change notification after a first modification change boundary and determine that the system information is valid until a second modification change boundary.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010]

45 Figure 1 shows an example wireless communication system including a plurality of WTRUs and an eNB in accordance with one embodiment; and

Figure 2 is a functional block diagram of a WTRU and the eNB of Figure 2.

50 DETAILED DESCRIPTION

[0011] When referred to hereafter, the terminology "wireless transmit/receive unit (WTRU)" includes but is not limited to a user equipment (UE), a mobile station, a fixed or mobile subscriber unit, a pager, a cellular telephone, a personal digital assistant (PDA), a computer, or any other type of user device capable of operating in a wireless environment. When referred to hereafter, the terminology "base station" includes but is not limited to a Node-B, a site controller, an access point (AP), or any other type of interfacing device capable of operating in a wireless environment.

55 [0012] System information, such as a location and size of a downlink Physical HARQ Indicator Channel (PHICH), may be transmitted between an eNB and a WTRU. If the WTRU is waking from the Discontinuous Reception (DRX) cycle

EP 2 600 656 B1

and waiting for the Dynamic Broadcast Channel (D-BCH) or Primary-BCH (P-BCH), unwanted latency may be incurred.

[0013] System information updates may occur at specific radio frames. A system information message may be transmitted more than once during a single modification period. The information in the message may be repeated.

[0014] A WTRU may obtain a system frame number (SFN) during initial access. In order to recognize a modification period boundary, the WTRU may determine the boundary by calculating $\text{mod}(\text{SFN}, n)$, where n is an integer value configured by system information, signaled to the WTRU or calculated by the WTRU using a predefined formula. Alternatively, the WTRU may determine the boundary by calculating $\text{mod}(\text{SFN}, n \times A)$, where "A" may correspond to the length of the P-BCH or D-BCH expressed in 10ms radio frames. For example, if the length is 40ms, the value of A is 4.

[0015] When the network changes system information, it first may notify a WTRU about the change. The notification may be done throughout a first modification period. In a second modification period, the network may transmit the updated system information. The second modification period may follow directly after the first modification period. Upon receiving a change notification, the WTRU may determine that the current system information is valid until the next modification period boundary.

[0016] A Paging message may be used to inform a WTRU in Idle mode or connected mode about a system information change. If a WTRU receives a paging message that includes a system information modification message, the WTRU may determine that the system information may change at the next modification boundary. The Paging message is a radio resource control (RRC) message and may have a paging cycle similar to the paging cycle already in use by the WTRU. Alternatively, the paging cycle may be different than the paging cycle in use by the WTRU.

[0017] More specifically, the system information, for example, the PHICH configuration, may be signaled on the D-BCH. If the D-BCH is transmitted over 80 ms (defined as a D-BCH cycle), a WTRU may listen to the D-BCH at $n \times 80\text{ms}$ intervals for a prospective update of system information, including, for example, the PHICH configuration. If a WTRU wakes up in the middle of the $n \times 80\text{ms}$ cycle, it is not required to check the D-BCH for system information since the system information, such as PHICH configuration, for example, is static during this interval. This may result in a reduction in latency as the WTRU can begin uplink (UL) communication without having to wait for a D-BCH cycle to complete.

[0018] Similarly, if the system information change is transmitted on the P-BCH, a configuration update can be signaled every $n \times 40\text{ms}$, where 40ms is the P-BCH transmission time. A WTRU may read the P-BCH every $\text{mod}(\text{SFN}, n \times 4)$, where 4 corresponds to the length of D-BCH cycle in number of 10ms radio frames. A WTRU can join the network at any time between the system information update cycle, that is, anytime in the $n \times 40\text{ms}$ interval.

[0019] Figure 1 shows a wireless communication system 100 including a plurality of WTRUs 110 and an e Node B (eNB) 120. As shown in Figure 1, the WTRUs 110 are in communication with the eNB 120. Although three WTRUs 110 and one eNB 120 are shown in Figure 1, it should be noted that any combination of wireless and wired devices may be included in the wireless communication system 100.

[0020] Figure 2 is a functional block diagram 200 of a WTRU 110 and the base station 120 of the wireless communication system 100 of Figure 1. As shown in Figure 1, the WTRU 110 is in communication with the eNB 120. The WTRU 110 is configured to receive system information and system information updates from the eNB 120. The eNB 120 may be configured to transmit, and the WTRU 110 configured to receive, signals on the P-BCH and the D-BCH. The WTRU 110 may also be configured to operate in a DRX mode and/or a DTX mode. The WTRU 110 may be configured to receive paging messages and other RRC messages. The WTRU 110 may determine the boundaries of the system information modification based on the SFN.

[0021] In addition to the components that may be found in a typical WTRU, the WTRU 110 includes a processor 215, a receiver 216, a transmitter 217, and an antenna 218. The WTRU 110 may also include a user interface 221, which may include, but is not limited to, an LCD or LED screen, a touch screen, a keyboard, a stylus, or any other typical input/output device. The WTRU 110 may also include memory 219, both volatile and non-volatile as well as interfaces 220 to other WTRU's, such as USB ports, serial ports and the like. The receiver 216 and the transmitter 217 are in communication with the processor 215. The antenna 218 is in communication with both the receiver 216 and the transmitter 217 to facilitate the transmission and reception of wireless data.

[0022] In addition to the components that may be found in a typical eNB, the eNB 120 includes a processor 225, a receiver 226, a transmitter 227, and an antenna 228. The receiver 226 and the transmitter 227 are in communication with the processor 225. The antenna 228 is in communication with both the receiver 226 and the transmitter 227 to facilitate the transmission and reception of wireless data.

[0023] The number of possible resource allocation sizes for system information may be reduced to a subset of the maximum number of possibilities. If the size of the system information resource allocation, such as for PHICH, can be only one of m different values, where m is a positive integer, then $\log_2(m)$ bits are required to signal the m sizes. The value of m may be fixed by the network, or an eNB may optimize control channel availability by using a different value of m under different load conditions. For example, if the load is high, the eNB may benefit from a finer granularity of the resource assignments and, therefore, select a larger value of m . If the load is low and some waste in system information resources can be tolerated, then the eNB can use a smaller value of m .

[0024] The eNB may further be restricted to changing system information resource allocation by a particular delta. As

EP 2 600 656 B1

an example, using 2 bits, an eNB may transmit the messages shown in Table 1.

TABLE 1: Message mapping to two (2) bit signal

Number of bits to signal delta in system information size	Increase/Decrease in system information size
00	No change since previous allocation
01	Increase allocation by k_I resources
10	Decrease allocation by k_D resource
11	Unused or use it for increase/decrease by other number of resources.

[0025] In Table 1, k_I is the delta by which the number of resources can be increased and k_D is the delta by which the number of resources can be reduced. k_I and k_D can be equal or different. The value of m , k_I and k_D can be signaled to the WTRU at initial access or may be fixed and made static over the entire network. As shown in Table 1, if the WTRU receives "00", the WTRU may determine that the new resource allocation is the same as the previous resource allocation. A "01" received by the WTRU indicates that the resources allocation is increased by k_I . A "10" received by the WTRU indicates that the allocation is decreased by k_D . It should be understood that in an alternative embodiment, the eNB may use more than 2 bits or have more levels of granularity to signal to the WTRU.

[0026] A parameter Δn may be defined as a number of D-BCH cycles before the WTRU aligns with the next system information update. After $\Delta n \times 80\text{ms}$, the WTRU may align with the system information update cycle. Following the alignment, the WTRU reads the D-BCH for updates every $n \times 80\text{ms}$ interval. Δn may be WTRU specific and can be signaled on the random access channel (RACH) response.

[0027] If system information resource assignments change only in a semi-static manner, the D-BCH overhead can be reduced by not transmitting the system information parameters until their scheduled reporting cycle. Two D-BCH formats may be used. A first format includes the system information resource signaling that occurs every $n \times 80\text{ms}$. A second format may be shorter than the first format and not include system information. A WTRU that misses reading the D-BCH or P-BCH during a system information update, due to, for example, a late wake up, may use the D-BCH or P-BCH format to recognize a D-BCH carrying system information.

[0028] An eNB may have some flexibility in changing the value of n . If an eNB decides to change n , the eNB may issue a page to a WTRU. In response to the page, the WTRU may read the P-BCH channel at the beginning for following the P-BCH cycle. In the following cycle, the P-BCH carries System Information Blocks (SIBs) that carry the value of n . As n can be any number of bits, the update cycle is $2^n \times 80\text{msec}$.

Examples useful for understanding the invention.

[0029]

1. A wireless transmit receive unit (WTRU) comprising a user interface, a memory, a receiver configured to receive a system frame number and system information messages in a modification period and a processor configured to determine a modification period boundary based on the system frame number.
2. The WTRU as in embodiment 1 wherein the receiver is further configured to receive an update notification in a first modification period and a plurality of system information updates in a second modification period.
3. The WTRU as in embodiment 1 or 2 wherein the receiver is further configured to receive an update notification and the processor is further configured to determine that system information is valid until a next modification period.
4. The WTRU as in any one of embodiments 1-3 wherein the processor is further configured to determine the modification boundary based on the SFN and an integer value.

[0030] Although the features and elements are described in particular combinations, each feature or element can be used alone without the other features and elements or in various combinations with or without other features and elements. The methods or flow charts provided may be implemented in a computer program, software, or firmware tangibly embodied in a computer-readable storage medium for execution by a general purpose computer or a processor. Examples of computer-readable storage mediums include a read only memory (ROM), a random access memory (RAM), a register, cache memory, semiconductor memory devices, magnetic media such as internal hard disks and removable disks, magneto-optical media, and optical media such as CD-ROM disks, and digital versatile disks (DVDs).

[0031] Suitable processors include, by way of example, a general purpose processor, a special purpose processor,

EP 2 600 656 B1

a conventional processor, a digital signal processor (DSP), a plurality of microprocessors, one or more microprocessors in association with a DSP core, a controller, a microcontroller, Application Specific Integrated Circuits (ASICs), Field Programmable Gate Arrays (FPGAs) circuits, any other type of integrated circuit (IC), and/or a state machine.

[0032] A processor in association with software may be used to implement a radio frequency transceiver for use in a wireless transmit receive unit (WTRU), user equipment (UE), terminal, base station, radio network controller (RNC), or any host computer. The WTRU may be used in conjunction with modules, implemented in hardware and/or software, such as a camera, a video camera module, a videophone, a speakerphone, a vibration device, a speaker, a microphone, a television transceiver, a hands free headset, a keyboard, a Bluetooth® module, a frequency modulated (FM) radio unit, a liquid crystal display (LCD) display unit, an organic light-emitting diode (OLED) display unit, a digital music player, a media player, a video game player module, an Internet browser, and/or any wireless local area network (WLAN) module.

P A T E N T K R A V

1. Fremgangsmåde, som udøves i en trådløs sende/modtage-enhed, WTRU, hvilken fremgangsmåde er
kendetegnet ved at omfatte:
 - 5 at der modtages en underretning om en forestående systeminformationsopdatering i en første modifikationsperiode;
 at der i lyset af underretningen modtages ny systeminformation i en anden modifikationsperiode, hvor starten på den anden modifikationsperiode kan bestemmes på basis af et systemframe-nummer, SFN, og en heltalsværdi "n".
 - 10 2. Fremgangsmåde ifølge krav 1, hvor den anden modifikationsperiode følger den første modifikationsperiode.
 3. Fremgangsmåde ifølge krav 2, hvor der er en modifikationsperiodegrænse mellem den første modifikationsperiode og den anden modifikationsperiode.
 4. Fremgangsmåde ifølge krav 3 hvor modifikationsperiodegrænsen kan bestemmes på basis af SFN'et og heltalsværdien "n".
 - 15 5. Fremgangsmåde ifølge krav 4, hvor modifikationsperiodegrænsen kan bestemmes ifølge en modulusoperation på basis af SFN'et og heltalsværdien "n".
 6. Fremgangsmåde ifølge krav 4, som yderligere omfatter at bestemme modifikationsperiodegrænsen.
 - 20 7. Fremgangsmåde ifølge krav 1, hvor den systeminformation, der er i brug før modtagelsen af den nye systeminformation, betragtes som værende gyldig indtil den nye systeminformation er i brug.
 8. Fremgangsmåde ifølge krav 1, som yderligere omfatter, at der tilvejebringes et systemframe-nummer, SFN.
 - 25 9. Fremgangsmåde ifølge krav 1, som yderligere omfatter, at der tilvejebringes en heltalsværdi "n".
 10. Fremgangsmåde ifølge krav 1, hvor heltalsværdien "n" konfigureres af systeminformation.
 11. Fremgangsmåde ifølge krav 1, som yderligere omfatter at beregne heltalsværdien "n" på basis af en forudbestemt formel.
 - 30 12. Fremgangsmåde ifølge krav 1, som yderligere omfatter, at der modtages en paging-meddelelse, der indbefatter en systeminformationsmodifikationsmeddelelse.
 13. Fremgangsmåde ifølge krav 1, som yderligere omfatter, at der modtages en radio-resursestyringsmeddelelse, RRC-meddelelse, der indbefatter en systeminformationsmodifikationsmeddelelse.
 - 35 14. Trådløs sende/modtage-enhed, WTRU,
kendetegnet ved at den omfatter:
 en processor til at modtage en underretning om en forestående systeminformationsopdatering i en første modifikationsperiode, og til

- i lyset af underretningen at modtage ny systeminformation i en anden modifikationsperiode, hvor starten på den anden modifikationsperiode kan bestemmes på basis af et systemframe-nummer, SFN, og en heltalsværdi "n".
- 5 15. WTRU ifølge krav 14, hvor den anden modifikationsperiode følger den første modifikationsperiode.
16. WTRU ifølge krav 15, hvor der er en modifikationsperiodegrænse mellem den første modifikationsperiode og den anden modifikationsperiode.
17. WTRU ifølge krav 16, hvor modifikationsperiodegrænsen kan bestemmes på basis af SFN'et og heltalsværdien "n".
- 10 18. WTRU ifølge krav 17, hvor modifikationsperiodegrænsen kan bestemmes ifølge en modulusoperation på basis af SFN'et og heltalsværdien "n".
19. WTRU ifølge krav 17, som yderligere omfatter at bestemme modifikationsperiodegrænsen.
- 15 20. WTRU ifølge krav 14, hvor den systeminformation, der er i brug før modtagelsen af den nye systeminformation, betragtes som værende gyldig indtil den nye systeminformation er i brug.
21. WTRU ifølge krav 14, som yderligere omfatter at tilvejebringe et systemframe-nummer, SFN.
22. WTRU ifølge krav 14, som yderligere omfatter at tilvejebringe en heltalsværdi "n".
- 20 23. WTRU ifølge krav 14, hvor heltalsværdien "n" er konfigureret af systeminformation.
24. WTRU ifølge krav 14, som yderligere omfatter at beregne heltalsværdien "n" på basis af en forudbestemt formel.
25. WTRU ifølge krav 14, som yderligere omfatter at modtage en paging-meddelelse, der indbefatter en systeminformationsmodifikationsmeddelelse.
- 25 26. WTRU ifølge krav 14, som yderligere omfatter at modtage en radioresursestyringsmeddelelse, RRC-meddelelse, der indbefatter en systeminformationsmodifikationsmeddelelse.
27. Fremgangsmåde, som udføres i en udviklet NodeB, eNB, hvilken fremgangsmåde er **kendetegnet ved at** omfatte:
- 30 at der sendes en underretning om en forestående systeminformationsopdatering i en første modifikationsperiode;
- at der i lyset af underretningen sendes nye systeminformationer i en anden modifikationsperiode, hvor starten på den anden modifikationsperiode kan bestemmes på basis af et systemframe-nummer, SFN, og en heltalsværdi "n".
- 35 28. Udviklet NodeB, eNB, **kendetegnet ved at** omfatte:
- en processor til at sende en underretning om en forestående systeminformationsopdatering i en første modifikationsperiode, og til i lyset af underretningen at sende nye systeminformationer i en anden modifikationsperiode, hvor starten på den anden modifikationsperiode kan bestemmes på basis af et systemframe-nummer,
- 40 SFN, og en heltalsværdi "n".




FIG.1

200




FIG.2