

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets

(11) Publication number:

0 223 882
B1

(12)

EUROPEAN PATENT SPECIFICATION

(43) Date of publication of the patent specification:
09.05.90

(51) Int. Cl.⁵: **A63B 49/00**

(21) Application number: **85201947.0**

(22) Date of filing: **22.11.85**

(54) **Strung sports racket with tension transmitting devices.**

(43) Date of publication of application:
03.06.87 Bulletin 87/23

(45) Publication of the grant of the patent:
09.05.90 Bulletin 90/19

(84) Designated Contracting States:
AT CH DE FR GB IT LI LU NL SE

(56) References cited:
DE-A- 2 611 970
US-A- 1 542 177
US-A- 3 567 225
US-A- 4 462 592

(73) Proprietor: **KARAKAL CORPORATION OF THE AMERICAS, 500 Esplanade Drive, Suite 1000, Oxnard, CA 93031(US)**

(72) Inventor: **Sines, Randy D., P.O. Box 6414, Oxnard California 93031(US)**
Inventor: **Farber, Bruce W., P.O. Box 685, Oak View California 93022(US)**

(74) Representative: **Konings, Lucien Marie Cornelis Joseph et al, OCTROOBUREAU ARNOLD & SIEDSMA Sweelinckplein 1, NL-2517 GK Den Haag(NL)**

EP 0 223 882 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

Description

Field of the Invention

This invention relates to transmission of tension among the various strings of a strung sports racket upon impact with a ball or other playing object.

Background

Most conventional sports rackets have strings which are each effectively anchored as they pass across the head or face opening to the next string hole. String elasticity, static string tension, frame stiffness, strung area geometry, and balance are all factors known to affect power, control, comfort and equipment performance. Many shapes, sizes, material, string tension, weights, even grips have been tried to improve the various games.

There remains a need for optimizing power and control features of a strung racket while minimizing the complexity of mechanisms for achieving such results. It is also desirable to incorporate simple, yet effective, features in a strung racket that will produce a higher coefficient of restitution (increased power for the same exertion), lower stress in the racket frame during the hit (lower magnitude vibrations), and lower peak tension in the strings during the hit. It is further desirable to provide improved performance by balancing forces applied to the hit object by providing even dynamic string tension which approaches that of a uniform membrane, reducing edge effects on off-center hits, and producing a longer dwell time thereby providing better control and larger string deflection for additional power.

The invention particularly relates to the improvement of a sports racket as indicated in the preamble of claim 1. A sports racket of this kind is disclosed in US-A 4 462 592. The tension transmitting device of the prior art sports racket consists of a combination of a steel wiring and rocker means pivotably connected to said steel wiring. In order to further improve simplicity of structure and assembling the invention proposes the characterising feature of claim 1.

The invention also proposes a string tension transmitting device as claimed in claim 6.

Brief description of the drawings

Preferred forms of the present invention are shown in the accompanying drawings in which:

Fig. 1 is a view of a tennis racket with portions broken away to illustrate features of the present invention;

Fig. 2 is an enlarged sectional view taken through a portion of the racket head frame and taken along line 2-2 in Fig. 3;

Fig. 3 is a fragmented view illustrating a portion of a string arrangement and portions of a racket including features of the present invention; and

Fig. 4 is a pictorial view of a rocker device with a portion thereof broken away.

Detailed Description of the Preferred Embodiment

The present invention can be incorporated in any size or geometry sports racket made from any common material. For purposes of this application, an exemplary configuration is that of a mid-sized tennis racket, made from graphite fiber impregnated resin.

The exemplary racket is shown at 10 in Fig. 1 of the drawings. The racket 10 includes an elongated handle 11 extending from a handgrip 12 along a shaft 13 to a throat 14. The throat 14 is secured or integral with a head frame 17.

The head frame 17 is planar with the handle 11 and defines a string opening 18. A string 19 may be threaded through the head frame 17 in a crisscross fashion of individual string chords 20. This woven pattern defines a planar racket face for impact with a ball or other playing object. It is preferable that the string incorporated for use with the present invention be a single strand of gut or conventional synthetic string material. The string can be tied at opposed ends to the head frame in any conventional manner.

The head frame includes an outer surface 21 that is oriented perpendicularly to the planar racket opening. An inner surface 22 of the frame 17 defines the opening configuration. String is threaded through the head frame between surfaces 21 and 22 through string holes 24.

Conventional string holes are formed through the racket head frame in substantially radial orientations. The string, however, is oriented in chord lengths that are preferably longitudinal and transverse with respect to the handle. The strings therefore are tightened against conventionally formed hole peripheries at vertices of angles formed between the radial holes and the transverse or longitudinal strings. This produces a binding or anchoring effect on the string chords.

String holes 24 are arranged to be coaxial with the strings passing through them and are preferably arranged in two groups. A first or longitudinal group of string holes 24 are formed through the racket head frame along parallel longitudinal axes and spaced across the head frame to receive string portions forming the longitudinal chords. A second group of string holes are formed up the sides of the head frame between surfaces 21 and 22. The second group of holes are also parallel to one another and spaced along the head length in transverse orientation to the longitudinal string chords. The particular orientation of the string chords can vary.

String holes 24 are preferably of sufficient size to loosely receive the string chords. The chord segments can thus be centered within the holes without touching or rubbing against the head frame material between the outer and inner surfaces 21 and 22. The string chords 20 are therefore loosely received rather than anchored in the holes 24.

The head frame 17 may be provided with an annular channel 25 extending about its outer periphery. The base of channel 25 serves as the outwardly facing head frame surface 21 for purposes of this description. The surface 21 is advantageously situated between channel walls 26 as shown in Fig. 2.

Important features of the present invention are embodied in a tension transmitting means generally shown at 27. The tension transmitting means can be provided in the form of individual rockers 28 as shown in Figs. 2 through 4. Tension transmitting means 27 is intended to transmit tension from one string chord to an adjacent chord using a rocking action.

A preferred rocker means 28 is shown in detail in Fig. 4. It includes a top surface 34 and bottom surface 35. The bottom surface is advantageously convex, preferably cylindrical. Surfaces 34 and 35 extend between smoothly curved ends 36. A groove or recess 37 may be formed along the top surface 34 to receive and orient a string in perpendicular orientation to the preferably cylindrical configuration of the bottom surface 35. Convex side walls 38 may extend between the bottom surface 35 and top surface 34, as best shown in Figs. 2 and 4.

The lengths of the individual rockers are such that string cords draped over the top surfaces 34 and guided over ends 36 through adjacent string holes 24 can be centered precisely within the string holes 24. Contact is made with the racket frame only by way of rockers 28. This effectively eliminates frictional contact between the string cords and the frame head. The actual length dimension between rocker ends 36 is less than the distance between centers of adjacent parallel string holes 24 by approximately the diameter of the string being used.

The bottom surfaces 35 of each rocker is arranged to be received with its longitudinal axis perpendicular to the racket opening or face. Contact between the rocker surfaces and the outer head frame surface exists along approximately parallel tangential lines of contact perpendicular to the planer face of the racket.

Orientation of the rocker surfaces to the racket face is important in three ways. Firstly, the tangential lines of contact provide rolling or rocking motion thus reducing friction between the two surfaces to a minimum, even with considerable tension being applied to one or both of the two adjacent string chords. Secondly, the tangential line contact, versus point contact, enables the rockers to withstand the high Hertzian stresses developed at the contact interface. Thirdly, the lines of contact are preferably oriented perpendicular to the planer string opening to provide high frictional resistance against sliding when the racket is impacted by a ball or other object. If rockers 28 slide along the lines of contact then one of the convex side walls 38 of rockers 28 will come into contact with an adjacent channel wall 26. Convex walls 38 are preferably semi-spherical and contact the channel wall at only a single tangential point. Such contact will prevent further sliding motion of the rocker with minimal effect upon the rocking capability of the rockers.

Figs. 1 and 3 indicate the preferred use of a plurality of rockers positioned between the string and outer head frame surface 21 at all string holes about the racket head frame. This arrangement supports all string chords in a tension transmitting and substantially friction free manner.

It is preferable that the individual rockers be

formed of a substantially rigid material such as aluminum or other lightweight, yet high strength, material. High strength plastic, such as graphite-filled polyamide may also be used, as can any material which provides the necessary rigidity and can withstand the high Hertzian stresses developed along the contact surfaces.

It is possible for an existing sports racket to be retrofitted with rockers between adjacent string segments to provide the roll tension transmitting capability. The rockers would function especially well in conjunction with a racket having oversized string holes or holes redrilled to loosely receive the strings coaxially therein.

Rackets according to this invention are preferably strung with relatively long, continuous strings which are passed through the frame and over tension transmitting means 27. The relatively long continuous strings supported by the tensioning means allows the string tension to be uniformly distributed over a relatively large or entire area of the racket. This greater distribution of strain energy reduces localized high stresses which otherwise occur in conventional string rackets. The total amount of elongation or strain developed in the strings is accordingly increased because of the longer effective string length over which the tension is distributed. This provides several very beneficial advantages.

One advantage is the higher initial tension which can be used to string the racket. This higher static string tension can be used with less risk of string breakage because of the more even distribution of tension throughout the racket face. The overall deflection of the racket face will also be greater than with conventional rackets wherein only a relatively small percentage of the strings share the peak loading at impact. The even distribution of strain and increased overall deflection of the string face provide a smaller restoring angle for impacts occurring near the racket frame thus providing increased velocity. This increases the preferred hitting area or "sweet zone" of the racket. The relative change in tension during impact is also less, thus reducing the apparent difference in control between hard and soft hits, and giving the player a wider range of available hits. Greater deflection also provides an overall longer dwell time during impact which improves control and power transmission to the ball. The ball also sees a more evenly balanced force profile when hit, especially near the frame of the racket. This improves control considerably when compared to conventional rackets which experience abnormally high string tensions near the frame due to the relatively shorter string lengths. The invention also allows more energy to be transmitted to the ball thus reducing the levels of shock and vibration experience by the player.

The invention is also advantageous in reducing friction and wear. Wear at the crisscross string intersections is reduced because the tension forcing the overlapping strings together is substantially reduced thus decreasing the frictional forces proportionately. This lower friction at the string intersections complements the minimal friction associated

with the tension transmitting action of rockers 28.

Stringing of the racket may be accomplished in substantially the usual manner, with rockers 28 inserted as stringing progresses. One rocker is placed between the string and outer head frame surface 21 at each wrap where the string passes through one hole and extends over the outer surface to be received through the next adjacent hole.

An important advantage of the present invention over other rackets employing pulley systems or saddle string mounts is the basic simplicity of the structure. It further allows the weight of the racket head to be maintained at a relatively low value. Prior art apparatus added to a conventional racket head significantly increase the head weight and adversely affect racket valance and performance. Other advantages are the small size and external positioning of the tension transmitting means so that there is no interference or intrusion into the string opening 18. This is a important since anything extending into the opening 18 will effectively diminish the opening size or decrease the effective string length.

Claims

1. A sports racket comprising:

an elongated handle;

a head frame at an end of the handle defining a planar string opening;

wherein the head frame includes an outward facing surface substantially perpendicular to the planar string opening and an inside surface defining the opening;

a first group of substantially parallel first string holes formed through the head frame oriented in a first direction and adapted for loosely receiving at least one racket string therethrough;

a second group of substantially parallel second string holes formed through the head frame oriented transversely with respect to the first direction and adapted to loosely receive at least one racket string therethrough; and

rocker means positionable between two string holes; said rocker means being rigid in a plane parallel to the string holes, and having a string receiving surface thereon adapted to receive and guide a racket string through the string holes;

characterized in that the rocker means are contacting directly the outward facing surface of the head frame along a rocking line of contact perpendicular to the string holes and parallel to a plane tangential to the outward facing surface.

2. The sports racket as claimed by claim 1 wherein the rocker means is an elongated rigid body having: a substantially cylindrical bottom rocking surface for rocking engagement with the outward facing surface of the head frame; and

a top surface opposite the bottom rocking surface having a string receiving recess formed therein.

3. The sports racket as claimed by claim 2 wherein the outward facing surface is situated at the base of a channel formed about the frame head for loosely receiving the rocker means therein.

4. The sports racket of claim 3 wherein the rocker means are oriented with the axis of the bottom cy-

lindrical rocking surface oriented transversely to the planar string opening to the head frame.

5. The sports racket as claimed by claim 4 wherein the rigid body of the rocker means includes convex side walls joining the substantially cylindrical rocking surface and the string receiving surface.

6. A string tension transmitting device for a stringed racket having a racket head frame defining a substantially planar string opening and having an outward facing head frame surface substantially perpendicular to the planar string opening and with a plurality of string holes formed through the head frame from the outward surface into the opening, the device comprising:

a rocker body having a top side and a bottom side, and being substantially rigid in a plane passing through said top and bottom sides;

string receiving means on the top side of the rocker body for receiving a portion of string therein and for guiding the string through two string holes in the racket head;

characterized in that the rocker means are adapted for contacting the outward facing surface of the head frame along a rocking line of contact perpendicular to the string holes and parallel to a plane tangential to the outward facing surface.

7. The device as claimed by claim 6 wherein the top surface includes a string receiving groove and the bottom rocker surface is substantially cylindrical about an axis oriented substantially perpendicular to the string receiving groove.

8. The device as claimed by claim 7, wherein the top and bottom surfaces are elongated and joined at curved ends over which a string extends.

9. The sports racket as claimed in claim 1, characterized in that the outward facing surface is situated at the base of a channel formed about the frame head for loosely receiving the rocker means with the longitudinal axis of the rocking surface oriented substantially perpendicular to the planar string opening.

Patentansprüche

1. Sportschläger mit einem verlängerten Griff, einem an einem Ende des Griffs ausgebildeten, eine ebene Bespannungsöffnung bildenden Kopffahmen, wobei der Kopffahmen eine im wesentlichen orthogonal zu der ebenen Bespannungsöffnung verlaufende Außenfläche und eine die Bespannungsöffnung bildende Innenfläche aufweist, einer ersten Gruppe von im wesentlichen parallel zueinander durch den Kopffahmen hindurch verlaufenden, in einer ersten Richtung orientierten ersten Bespannungslöchern zur losen Aufnahme zumindest einer Schlägerbespannung, einer zweiten Gruppe von im wesentlichen parallel zueinander durch den Kopffahmen hindurch quer zu der ersten Richtung verlaufenden zweiten Bespannungslöchern zur losen Aufnahme zumindest einer Schlägerbespannung, zwischen jeweils zwei Bespannungslöchern anordenbaren Kippaufnehmern,

wobei die Kippaufnehmer in einer Ebene parallel zu den Besspannungslöchern steif ausgebildet sind und eine Fläche zur Aufnahme und Führung einer Schlägerbesspannung durch die Besspannungslöcher hindurch aufweisen;

dadurch gekennzeichnet, daß die Kippaufnehmer die Außenfläche des Kopfrahmens entlang einer orthogonal zu den Besspannungslöchern und parallel zu einer tangential zur Außenfläche verlaufenden Kontaktlinie direkt kontaktieren.

2. Sportschläger nach Anspruch 1, dadurch gekennzeichnet, daß der Kippaufnehmer als langgestreckter, steifer Körper ausgeführt ist und daß der Kippaufnehmer

eine im wesentlichen walzenförmige Bodenkipplfläche, die mit der Außenfläche des Kopfrahmens Kippkontakt hat und

eine der Bodenkipplfläche gegenüberliegende obere Fläche mit einer darin ausgebildeten Ausnehmung zur Aufnahme einer Besspannung aufweist.

3. Sportschläger nach Anspruch 2, dadurch gekennzeichnet, daß die Außenfläche des Kopfrahmens an der Basis eines um den Kopfrahmens herum ausgebildeten Kanals angeordnet ist und daß der Kanal zur losen Aufnahme der Kippaufnehmer dient.

4. Sportschläger nach Anspruch 3, dadurch gekennzeichnet, daß die Kippaufnehmer so angeordnet sind, daß die Achse der Bodenkipplfläche quer zur ebenen Besspannungsöffnung des Kopfrahmens verläuft.

5. Sportschläger nach Anspruch 4, dadurch gekennzeichnet, daß der steife Körper des Kippaufnehmers konvexe Seitenwandungen aufweist und daß die konvexen Seitenwandungen die im wesentlichen walzenförmige Bodenkipplfläche und die die Besspannung aufnehmende Fläche miteinander verbindet.

6. Spannungsübertragungseinrichtung zur Übertragung von Spannungen in einem mit einer Besspannung versehenen Sportschläger, wobei der Sportschläger einen eine im wesentlichen ebene Besspannungsöffnung bildenden Kopfrahmens aufweist, wobei der Kopfrahmens eine orthogonal zu der ebenen Besspannungsöffnung verlaufende Außenfläche aufweist, wobei durch den Kopfrahmens hindurch von der Außenfläche des Kopfrahmens her in die Besspannungsöffnung hinein eine Mehrzahl von Besspannungslöchern ausgebildet sind und wobei die Spannungsübertragungseinrichtung

einen eine Oberseite und eine Bodenseite aufweisenden, in einer durch die Oberseite und Bodenseite verlaufenden Ebene im wesentlichen steifen Kippkörper und

eine auf der Oberseite des Kippkörpers ausgebildete Aufnahmevorrichtung zur Aufnahme eines Teils der Besspannung und zum Führen der Besspannung durch zwei in dem Schlägerkopf ausgebildete Besspannungslöcher aufweist.

7. Spannungsübertragungseinrichtung nach Anspruch 6, dadurch gekennzeichnet, daß die Oberseite des Kippkörpers eine Nut zur Aufnahme der Besspannung aufweist und daß die Bodenseite im wesentlichen walzenförmig um eine im wesentlichen orthogonal zur Nut ausgerichtete Achse ausgebildet ist.

8. Spannungsübertragungseinrichtung nach Anspruch 7, dadurch gekennzeichnet, daß die Oberseite und die Bodenseite jeweils langgestreckt sind und an gebogenen Enden, über die sich eine Besspannung erstreckt, verbunden sind.

9. Sportschläger nach Anspruch 1, dadurch gekennzeichnet, daß die Außenfläche des Kopfrahmens an der Basis eines um den Kopfrahmens herum ausgebildeten Kanals angeordnet ist, daß der Kanal zur losen Aufnahme der Kippaufnehmer dient und daß die Längsachse der Kippfläche im wesentlichen orthogonal zur ebenen Besspannungsöffnung ausgebildet ist.

Revendications

1. Raquette de sport comprenant:

– une poignée allongée (12, 11, 13);
– un cadre de la tête (27) à une extrémité de la poignée définissant une ouverture plane (18) pour le cordage;

dans laquelle le cadre de la tête comporte une surface dirigée vers l'extérieur (21) essentiellement perpendiculaire à l'ouverture plane (18) pour le cordage et une surface intérieure (22) définissant l'ouverture;

– un premier groupe de premiers trous essentiellement parallèles pour recevoir le cordage ménagés à travers le cadre de tête, orientés dans une première direction et prévus pour être traversés par au moins une corde de raquette de manière lâche;

– un deuxième groupe de deuxièmees trous essentiellement parallèles pour recevoir le cordage ménagés à travers le cadre de tête, orientés transversalement par rapport à la première direction et prévus pour être traversés par au moins une corde de raquette de manière lâche; et

– des moyens basculeurs (28) pouvant être positionnés entre deux trous pour le cordage; lesdits moyens basculeurs (28) étant rigides dans un plan parallèle aux trous pour le cordage et présentant une surface de réception de la corde conçue pour recevoir et guider une corde de raquette à travers les trous pour le cordage;

caractérisée en ce que les moyens basculeurs (28) sont en contact direct avec la surface du cadre de la tête dirigée vers l'extérieur le long d'une ligne de contact, par basculement, perpendiculaire aux trous pour le cordage et parallèle à un plan tangentiel à la surface dirigée vers l'extérieur.

2. Raquette de sport selon la revendication 1, caractérisée en ce que le moyen basculeur (28) est un corps rigide allongé comprenant:

– une surface de fond (35) basculante essentiellement cylindrique d'engagement par basculement sur la surface du cadre de la tête dirigée vers l'extérieur; et

– une surface supérieure (34) opposée à la surface de fond (35) basculante présentant un évidement (37) en forme de creux pour la réception de la corde.

3. Raquette de sport selon la revendication 2, caractérisée en ce que la surface dirigée vers l'extérieur est située à la base d'un évidement (25) en forme de canal ménagé le long de la tête de cadre pour

recevoir les moyens basculeurs (28) de manière lâche.

4. Raquette de sport selon la revendication 3, caractérisée en ce que les moyens basculeurs (28) sont orientés de telle sorte que l'axe de la surface de fond (35) cylindrique basculante soit orienté transversalement par rapport à l'ouverture plane (18) du cadre de la tête pour le cordage. 5

5. Raquette de sport selon la revendication 4, caractérisée en ce que le corps rigide des moyens basculeurs (28) comporte des parois latérales convexes (38) joignant la surface basculante essentiellement cylindrique et la surface recevant la corde. 10

6. Dispositif transmettant la tension d'un cordage pour une raquette cordée présentant un cadre de la tête de raquette définissant une ouverture essentiellement plane pour le cordage et ayant une surface de cadre de la tête dirigée vers l'extérieur essentiellement perpendiculaire à l'ouverture plane (18) pour le cordage, une pluralité de trous pour les cordes étant ménagés à travers le cadre de la tête depuis la surface dirigée vers l'extérieur dans l'ouverture, le dispositif comportant: 15

– un corps basculeur (28) ayant un côté supérieur et un côté de fond, et étant essentiellement rigide dans un plan traversant lesdits côtés supérieur et du fond; 20

– des moyens recevant les cordes sur le côté supérieur du corps basculant pour loger une partie de corde et pour guider la corde à travers deux trous pour la corde ménagés dans la tête de raquette; caractérisé en ce que les moyens basculeurs (28) sont conçus pour entrer en contact avec la surface du cadre de la tête dirigée vers l'extérieur le long d'une ligne de contact, par basculement, perpendiculaire aux trous pour le cordage et parallèle à un plan tangentiel à la surface dirigée vers l'extérieur. 25

7. Dispositif selon la revendication 6, caractérisé en ce que la surface supérieure (34) comporte un évidement (37) en forme de rainure pour la réception de la corde et en ce que la surface de fond (35) du basculeur est essentiellement cylindrique autour d'un axe orienté essentiellement perpendiculairement à l'évidement en forme de rainure pour la réception de la corde. 30

8. Dispositif selon la revendication 7, caractérisé en ce que les surfaces supérieure et de fond sont allongées et réunies à des extrémités incurvées (36) sur lesquelles s'étend une corde. 35

9. Raquette de sport selon la revendication 1, caractérisée en ce que la surface dirigée vers l'extérieur est située à la base d'un évidement (25) en forme de canal ménagé autour de la tête du cadre pour recevoir les moyens basculeurs (28) de manière lâche de sorte que l'axe longitudinal de la surface basculante soit orienté essentiellement perpendiculairement à l'ouverture plane (18) pour le cordage. 40

60

65

