



US009981501B2

(12) **United States Patent**
Solheim et al.

(10) **Patent No.:** **US 9,981,501 B2**
(45) **Date of Patent:** ***May 29, 2018**

(54) **COLLAPSIBLE WHEELS AND METHODS OF MAKING COLLAPSIBLE WHEELS**

(71) Applicant: **KARSTEN MANUFACTURING CORPORATION**, Phoenix, AZ (US)

(72) Inventors: **John A. Solheim**, Phoenix, AZ (US);
Eric V. Cole, Phoenix, AZ (US)

(73) Assignee: **Karsten Manufacturing Corporation**, Phoenix, AZ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 408 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/337,640**

(22) Filed: **Jul. 22, 2014**

(65) **Prior Publication Data**

US 2014/0332128 A1 Nov. 13, 2014

Related U.S. Application Data

(63) Continuation of application No. 14/063,601, filed on Oct. 25, 2013, now Pat. No. 8,833,864.

(60) Provisional application No. 61/719,634, filed on Oct. 29, 2012.

(51) **Int. Cl.**

B60B 25/00 (2006.01)
B60B 9/26 (2006.01)
B60B 19/04 (2006.01)
B60B 25/02 (2006.01)

(52) **U.S. Cl.**

CPC **B60B 9/26** (2013.01); **B60B 19/04** (2013.01); **B60B 25/00** (2013.01); **B60B 25/02** (2013.01); **B60B 2900/351** (2013.01); **B60Y 2200/86** (2013.01); **Y10T 29/49513** (2015.01)

(58) **Field of Classification Search**

CPC B60B 9/04; B60B 19/00; B60B 19/04; B60B 25/00; B60B 25/002; B60B 25/004
USPC ... 301/10.1, 11.1, 13.1, 14-15, 29.2, 30-34; 152/12, 17-19, 75, 80, 377
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,602,823 A	7/1986	Berg	
5,967,543 A	10/1999	Taylor	
7,610,830 B2	11/2009	Serrano Gil	
8,091,596 B2	1/2012	Louden	
8,833,864 B2*	9/2014	Solheim	B60B 25/00
			301/15
2009/0211675 A1	8/2009	Louden	
2010/0201098 A1	8/2010	Fitzsimons	
2011/0080038 A1	4/2011	Tan	

(Continued)

FOREIGN PATENT DOCUMENTS

AU	2001291482 B2	9/2001
CN	2461792 Y	11/2001
CN	102328717 A	1/2012

(Continued)

OTHER PUBLICATIONS

International Search Report from corresponding PCT Application No. PCT/US2013/066843, dated Mar. 28, 2014.


(Continued)

Primary Examiner — Jason R Bellinger

(57) **ABSTRACT**

Embodiments of collapsible wheels and methods of making collapsible wheels are generally described herein. Other embodiments may be described and claimed.

20 Claims, 19 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0032497 A1 2/2012 Sheu et al.
2014/0117637 A1 5/2014 Solheim et al.

FOREIGN PATENT DOCUMENTS

CN 2022443869 U 5/2012
NZ 531830 A 7/2005
WO 2004103794 A1 2/2004

OTHER PUBLICATIONS

Written Opinion from the International Searching Authority from corresponding PCT Application No. PCT/US2013/066843, dated Mar. 28, 2014.

International Search Report and Written Opinion of the International Searching Authority for International Application No. PCT/US2016/062101 filed Nov. 15, 2016.

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8






Fig. 12






Fig. 13

Fig. 14






Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21






Fig. 22






Fig. 25




Fig. 26




Fig. 27




Fig. 28




Fig. 29




Fig. 30




Fig. 31




Fig. 32




Fig. 33




Fig. 34




Fig. 35





Fig. 36

Fig. 37






Fig. 38




Fig. 39




Fig. 40




Fig. 41




Fig. 42




Fig. 43




Fig. 44

1

COLLAPSIBLE WHEELS AND METHODS OF MAKING COLLAPSIBLE WHEELS

RELATED APPLICATION

The present application is a continuation of U.S. patent application Ser. No. 14/063,601, filed on Oct. 25, 2013, which is now U.S. Pat. No. 8,833,864, which claims the benefit of U.S. Provisional Patent Application Ser. No. 61/719,634, filed Oct. 29, 2012, the disclosure of which is incorporated by reference.

FIELD

The present application generally relates to wheels, and more generally to collapsible wheels and methods of making collapsible wheels.

BACKGROUND

Some sporting equipment may require a wheeled vehicle for transportation. For example, kayaks may be transported to a river or lake on a wheeled kayak cart. Prior to launching the kayak on water, the kayak cart is removed from the kayak and may be stored on the kayak. The kayak cart may have a frame that is collapsible to reduce the size of the cart when not in use. In another example, an individual playing golf can carry his golf bag on his shoulder, with a golf pull cart or an electric golf cart. Golf pull carts typically have a frame to which two wheels for moving the cart are attached. The frame may also include a handle that is held by an individual for balancing, pulling or pushing the cart, and a platform or base for mounting the individual's golf bag. The frame may be collapsible to reduce the size of the pull cart when not in use for storage and/or transportation.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a wheel according to one embodiment shown in an expanded position.

FIG. 2 is a perspective view of the wheel of FIG. 1 shown in a collapsed position.

FIG. 3 is a perspective view of the wheel of FIG. 1 shown without a tire according to one embodiment.

FIG. 4 is a perspective view of the wheel of FIG. 3 shown in the collapsed position.

FIG. 5 is a perspective view of two wheel sections of the wheel of FIG. 1.

FIG. 6 is a partial front perspective view of the wheel of FIG. 1 shown in the expanded position.

FIG. 7 shows a tire for use with a wheel according to one embodiment.

FIGS. 8-9 show sections of the tire of FIG. 7.

FIGS. 10-11 show mounting of the tire of FIG. 7 on the wheel of FIG. 3 according to one embodiment.

FIG. 12 shows a wheel section of the wheel of FIG. 1.

FIG. 13 shows an axle for the wheel of FIG. 1.

FIG. 14 shows the axle of FIG. 13 mounted in the wheel of FIG. 1.

FIGS. 15-18 show the wheel of FIG. 1 with an expansion and collapsing mechanism according to one embodiment.

FIGS. 19 and 20 show a wheel according to another embodiment in an expanded position and a collapsed position, respectively.

FIGS. 21 and 22 show a wheel according to another embodiment in a collapsed position.

2

FIGS. 23-25 show the wheel of FIGS. 21 and 22 in an expanded position.

FIG. 26 shows a side view of a wheel according to one embodiment.

FIG. 27 shows a side view of a wheel according to one embodiment.

FIGS. 28 and 29 show side views of a wheel according to one embodiment in the expanded position and the collapsed position, respectively.

FIGS. 30 and 31 show side views of a wheel according to one embodiment.

FIGS. 32 and 33 show perspective views of a wheel according to one embodiment.

FIG. 34 shows a partial perspective view of the wheel section of a wheel according to one embodiment having a tire section.

FIGS. 35, 36 and 38 show a wheel according to one embodiment in an expanded position.

FIGS. 37, 39 and 40 show the wheel of FIG. 35 in a collapsed position.

FIG. 41 shows perspective cross-sectional views of spokes of the wheel of FIG. 35.

FIG. 42 shows a flow chart of a method to manufacture a wheel according to one embodiment.

FIGS. 43 and 44 show a cart for carrying a golf club bag in deployed and stowed positions, respectively, having wheels according to one embodiment.

DETAILED DESCRIPTION

Referring to FIGS. 1 and 2, a wheel 100 according to one example of the apparatus, methods, and articles of manufacture described herein is shown. The wheel 100 includes a hub assembly 102 and a tire 104, at least a portion of which is mounted around the hub assembly 102 for contact with the ground. The wheel 100 also includes an axle 106 over which the hub assembly 102 is rotatably mounted. A wheel 100 or a plurality of wheels 100 may be used on a cart or a vehicle for transporting any object.

FIG. 1 shows the wheel 100 in an expanded position. To reduce the size of the wheel 100 for transportation and/or storage, an individual may collapse the wheel 100 to a collapsed position shown in FIG. 2. For example, a trunk of an automobile may not have sufficient space to accommodate a pull cart for golf clubs when the wheels 100 of the pull cart are in the expanded position. By placing the wheels 100 in the collapsed position, the pull cart and the wheels 100 may fit inside the trunk of the automobile for transportation. Accordingly, collapsing the wheels from an expanded position to a collapsed position allows the wheels and or any object to which the wheels are attached to occupy less space. Furthermore, as discussed in detail below, each wheel 100 may be removable from a pull cart to further reduce the space that may be occupied by the pull cart and the wheels 100.

Referring also to FIGS. 3-6, the hub assembly 102 is shown in the expanded and collapsed positions, respectively. The hub assembly 102 includes a plurality stacked wheel sections 110. Each wheel section 110 includes a hub section 112 with a central bore 114. The wheel sections 110 may be concentrically stacked so that the central bores 114 are axially aligned to form an elongated bore for receiving the axle 106. Each wheel section 110 may include at least one spoke 116 and a rim 118. In the example of FIGS. 1-5, each wheel section 110 has a first pair of spokes 116 that radially projects from the hub section 112 to connect to a first rim 118, and a second pair of spokes 116 that radially projects

from the hub section 112 opposite to the first pair of spokes 116 to connect to a second rim 118. Each rim 118 receives and supports a section of the tire 104. Each wheel section 110 may include any number of spokes 116 that extend from the hub section 112 to one or more rims 118. For example, each rim 118 may be connected to only one spoke 116 or a plurality of spokes 116. The spokes 116 may be in any shape. For example, each spoke 116 may be straight, bent in one or more locations along the length of the spoke, and/or have a curvature. In the examples of FIGS. 1-5, the spokes 116 may be curved so as to function as springs when the wheel 100 is used. Accordingly, when forces are exerted on the rim 118 during the operation of the wheel 100, the curved shape of each spoke 116 facilitates elastic bending of the spoke 116 such that the spoke 116 provides a shock absorbing function.

Each wheel section 110 may be freely rotatable about the axle 106 to allow expansion of the wheel sections 110 from a collapsed position shown in FIG. 4 to an expanded position shown in FIG. 3. The number of wheel sections 110, the thickness of each wheel section 110, and/or the radial span of each wheel section 110 may be determined so that in the expanded position of the wheel 100, a full circular wheel, i.e., about 360°, is defined by the wheel 100 and the rims 118 provide sufficient support for the tire 104 for proper operation of the wheel 100. Providing sufficient support for the tire 104 at any instant during the operation of the wheel 100 may be defined by the number of contact points between the wheel 100 and the ground. Each rim 118 may be defined as having one contact point, which although referred to herein as a contact point, may represent an area of the rim 118 that contacts the ground. Increasing the number of contact points between the wheel 100 and the ground may increase the stability of the wheel 100, hence increase the stability of the vehicle, i.e., pull cart, to which the wheel 100 is attached.

The radial span of each wheel section 110 may determine the radial position of each wheel section 110 relative to an adjacent wheel section 110 in the expanded position of the wheel 100 and the number of wheel sections 110 that may be needed. Radial span 119 as shown in FIG. 5 and as used herein may generally define a length of the rim 118 that contacts the ground during the operation of the wheel 100. For example, if each rim 118 of a pair of rims 118 of a wheel section 110 define a radial span of about 90°, only two wheel sections 110 may be required so that the rims 118 define a full circle or about 360° without generally any overlap or gap between two adjacent rims 118; or each rim 118 may generally define a 90° radial span on a full circle that defines the wheel 100. In other words, each wheel section 110 may generally define a 180° radial span on a full circle that defines the wheel. In another example, if each rim 118 of a pair of rims 118 of a wheel section 110 has a radial span 119 of about 45°, four wheel sections 110 may be required, i.e., eight rims 118, so that the rims 118 define a full circle or about 360° without generally any overlap or gap between two adjacent rims 118. Accordingly, a general configuration of the wheel 100 may be defined by the following example equation:

$$\frac{360^\circ}{NW} C = R \quad (1)$$

Where W represents the number of wheel sections, N represents the number of opposing rims 118 on each wheel (e.g., N is 2 in the example of FIGS. 2-5), C represents the

number of ground contact points, and R represents the radial spacing of each wheel section relative to an adjacent wheel section (in degrees).

As described above, increasing the number of contact points between the wheel 100 and the ground may increase the stability of the wheel 100. Each rim 118 may contact the ground at one contact point. By providing multiple contact points, i.e., multiple rims 118, which contact the ground at any instant, the stability of the wheel 100 may increase. In other words, increasing the number of contact points with the ground at any instant during the operation of the wheel 100 increases the width of the wheel 100, thereby increasing the number of wheel sections 110 that may be used to form the wheel 100.

Referring to FIG. 5, an example of the wheel 100 is shown where each wheel section has a rim 118 that has a radial span 119 of about 45°. Accordingly, adjacent wheel sections 110 may be generally radially spaced apart by about 45° in the expanded position of the wheel 100 as shown in FIG. 5. In the example of FIG. 5, four wheel sections 110, i.e., eight rims 118, would be required to define a full circle or about 360°. Thus, if the wheel 100 is constructed with four wheel sections 110, only one rim 118, i.e., one contact point, contacts the ground at any instant. To increase the stability of the wheel 100, sixteen wheel sections 110 may be provided as shown in the example of FIG. 4 so that at any instant during the operation of the wheel 100, four contact points on the wheel 100 contact the ground, i.e., four rims 118 define the width of the wheel 100. Any number of wheel sections 110 may be provided for increasing or reducing contact points. For example, twenty wheel sections 110 would provide five contact points with the ground at any instant for the wheel 100. In another example, twelve wheel sections 110 would provide three contact points with the ground. According to the above, when each rim 118 spans about 45°, at least eight rims 118 may be required so that at any instant during the operation of the wheel 100 one contact point contacts the ground. To increase the number of contact points along the width of the wheel when each rim 118 has a radial span 119 of about 45°, multiples of four wheel sections 110 may be provided. In the example of FIG. 4, sixteen wheel sections 110 for the wheel 100 provide four contact points at any instance during the operation of the wheel as shown in FIG. 6.

Increasing the number of wheel sections 110 may increase the stability of the wheel 100 and/or the amount of weight that the wheel 100 may support. However, increasing the number of wheel sections 110 may also increase the size and/or the weight of the wheel 100 in the collapsed position. Accordingly, the size of each wheel section 110, and other properties of each wheel section 110 as described herein may be determined depending on the size and load of the cart to which one or more wheels 100 may be attached.

FIG. 6 illustrates an expanded position of two wheel sections 110. The rim 118 of each wheel section 110 includes a radial projection 120. Referring to FIGS. 7-11, the tire 104 may include an inner surface 130 and an outer surface 132. The outer surface 132 may be smooth or have threads. The inner surface 130 may have any configuration to provide mounting of the tire 104 on the rims 118. In the examples of FIGS. 8 and 9, the inner surface 130 includes a plurality of generally parallel ribs 134 that define a plurality of generally parallel grooves 136 between the ribs 134. The ribs 134 and the grooves 136 may radially span a portion of the inner surface 130. In the examples of FIGS. 8 and 9, the ribs 134 and the grooves 136 span the entire 360° of the inner surface 130 of the tire 104.

Referring to FIGS. 10 and 11, the distance between adjacent grooves 136 generally corresponds to the distance between the projections 120 of adjacent wheel sections 110. Additionally, the cross-sectional shape of each groove 136 may generally correspond to the cross-sectional shape of the projections 120. Accordingly, when the tire 104 is mounted on the wheel sections 110, the projections 120 may engage the grooves 136 and generally fit within the grooves 136. The projections 120 and the grooves 136 may have any cross-sectional shape. In the example of FIG. 11, the projections 120 are shown to have a generally triangular cross-sectional shape and the grooves 136 are also shown to have a generally corresponding triangular cross-sectional shape. Furthermore, the size of the grooves 136 may generally correspond to the size of the projections 120. For a tire 104 that is constructed from an elastic material such as rubber, the grooves 136 may be alternatively formed to be smaller than the projections 120 so that the grooves 136 elastically expand when receiving the projections 120 to provide a generally formfitting engagement with the projections 120. The tire may be attached to one or more of the rims 118 such that the tire is maintained in a mounted configuration on the wheel 100 in both the collapsed and expanded positions of the wheel 100.

As described above, each wheel section 110 may be positioned relative to an adjacent wheel section 110 at a certain angle during the operation of the wheel 100 to provide a sufficient number of contact points and generally evenly distributed contact point locations for the wheel 100. For example, the wheel sections 110 of FIG. 5 are positioned at about 45° relative to each other in the expanded position to provide four evenly distributed contact points at any instant during the operation of the wheel 100. The angle between the wheel sections 110 in the expanded position that provides a sufficient number of contact points and generally evenly distributes the contact point locations on the wheel may be referred to herein as the expansion angle. The expansion angle is shown in equation (1) as the variable R. Thus, the expansion angle for the example of FIG. 5 is about 45°.

As described in detail above and with respect to equation (1), the expansion angle may be different depending on the configuration and/or properties of the wheel sections 110. To limit the expansion of the wheel sections 110 relative to each other and/or to provide positioning of the wheel sections 110 relative to each other at the expansion angle, the wheel 100 may include an expansion angle limiting mechanism by which rotation of each wheel section 110 relative to an adjacent wheel section 110 is limited to the expansion angle. According to one example shown in FIG. 12, the angle limiting mechanism includes a radial slot 140 on the hub section 112 of each wheel section 110 and a pin 144 that may be located on the hub section 112 opposite to the slot 142 relative to the central bore 114. The arc length of each radial slot 140 may be generally no greater than the expansion angle. In the example of FIG. 12, the arc length of the radial slot 140 is about 45°, which is the same as the expansion angle. When the wheel sections 110 are assembled as described in detail below, i.e., stacked on top of each other, the pin 144 of each wheel section 110 is placed inside the slot 140 of an adjacent wheel section 110. Accordingly, when adjacent wheel sections are rotated relative to each other, the pin 144 moves in the slot 140. However, the radial movement of the pin 144, which defines the radial movement of the wheel section 110 having the pin 144, is bound by the arc length of the slot 140.

Each slot 140 includes a first end 150 and a second end 152. In the collapsed position of the wheel 100, the pin 144 of each wheel section 110 is located near the first end 150 of the slot 140 of an adjacent wheel section 110. As the wheel 100 is expanded, the pin 144 moves in the slot 140 from the first end 150 until the pin 144 contacts the second end 152 of the slot 140. Thus, the slot 140 limits rotation of the two adjacent wheel sections 110 relative to each other to the expansion angle or the radial arc length of the slot 140. The position of each slot 140 and pin 144 may be determined to allow expanding and collapsing of the wheel 100 as disclosed. In the example of FIG. 12, the first end 150 of the slots 140 is generally located along a center longitudinal axis 154 of the hub section 112. Accordingly, the second end 152 of the slot 140 is located about 45° from the first end 150. The pin 144 is also located on the center longitudinal axis 154, but is located opposite to the first end 150 of the slot 140 relative to the central bore 114. As described in detail below, the arrangement of the pin 144 and the slot 140 as shown in FIG. 12 provides for each wheel section 110 to be rotated relative to an adjacent wheel section by the expansion angle.

After the wheel 100 is expanded, which is defined by each wheel section 110 having the expansion angle relative to an adjacent wheel section 110, the wheel 100 may be maintained in the expanded position by any type of latching, locking and/or similar mechanisms that prevents the wheel sections 110 from rotating relative to each other. For example, each wheel section 110 may include an aperture (not shown) positioned on the hub section 112 such that when the wheel sections 110 are in the expanded position of the wheel 100, all of the apertures of the wheel sections 110 are generally aligned to receive a rod (not shown). Therefore, the rod prevents the wheel sections 110 from rotating relative to each other. In another example, a U-shaped bracket (not shown) which has a width that is generally similar to the collective width of the hub sections 112 may be placed over the hub sections 112 to prevent the hub sections 112 from rotating relative to each other.

Referring to FIGS. 13 and 14, the wheel sections 110 may be rotationally mounted on an axle 106. The axle 106 may be defined by a cylindrical shaft 160 having a first end 162 and a second end 164. In the example of FIGS. 13 and 14, the axle 106 may further include a mounting bracket 166 having a first bracket section 168 and the second bracket section 170. The mounting bracket 166 may facilitate mounting or attachment of the wheel 100 to a cart, such as a golf pull cart. The wheel sections 110 may be mounted on the shaft 160 by inserting the shaft 160 from the first end 162 in the central bore 114 of each wheel section 110. The axle 106 may include a mechanism by which the first wheel section 110 that is mounted on the shaft 160 is held stationary to allow expansion of the wheel 100 from a collapsed position. In one example as shown in FIG. 13, the first bracket section 160 includes a pinhole 170 for receiving the pin 144 of the first mounted wheel section 110. Engagement of the pin 144 in the pinhole 170 of the first mounted wheel section 110 maintains the first mounted wheel section 110 fixed to the first bracket section 160 to allow expansion of the wheel 100 from a collapsed position to an expanded position. After the wheel 100 is expanded, the pin 144 may be removed from the pinhole 170 to allow rotation of the wheel 100 about the shaft 160.

The axle 106 may further include a wheel holding mechanism by which the wheel 100 is maintained on the shaft 160 during the operation of the wheel 100. The wheel holding mechanism may include any configuration to prevent the

7

wheel 100 from sliding off the shaft 106 or being removed from the shaft 106 during the operation of the wheel 100. For example, the first end 162 of the shaft 160 may be threaded to receive a correspondingly threaded nut (an example is shown in FIG. 22). The threaded nut increases the diameter of the shaft 160 at the first end 162 to a diameter that is greater than the central bores 114 of the hub sections 112. Accordingly, the wheel sections 110 are stopped by the nut when reaching the first end 162 of the shaft 160.

In the example of FIG. 13, the shaft 160 includes an annular recess 172 at or near the first end 162 of the shaft 160. As shown in FIG. 14, after the wheel sections 110 are mounted on the shaft 160, a spring clip 174 may be mounted over and pressed onto the shaft 160 so that the spring clip 174 snaps into and remains in the annular recess 172. The spring clip 174 increases the diameter of the shaft 160 at the first end 162 to a diameter that is greater than the diameters of the central bores 114 of the hub sections 112. Accordingly, the wheel sections 110 are stopped by the spring clip 174 when reaching the first end 162 of the shaft 160. The axle 106 may also include a washer 176 or the like mounted between the spring clip 174 and the last mounted wheel section 110. To provide easier installation of the spring clip 174 into the annular recess 174, the first end 162 of the shaft may be tapered as shown in FIGS. 13 and 14 so that pressing the spring clip 174 onto the first end 162 gradually expands the spring clip 174 when being mounted on to the shaft 160. Thus, the spring clip 174 remains engaged in the annular recess 172 until it is expanded with or without a tool by an individual for removal of the spring clip 174 from the shaft 160, which then allows removal of the wheel sections from the shaft 160. At the second end 164 of the shaft 160 an annular shoulder 178 may be provided so that the first mounted wheel section 110 is spaced from the first bracket section 168.

FIG. 2 shows the wheel 100 in the collapsed position having the tire 104 mounted thereon. The tire 104 may be constructed from an elastic material such as rubber. Furthermore, the inner diameter of the tire 104 may be smaller than an outer diameter of a circle defined by the wheel 100 in the expanded position. Accordingly, the tire may be easily mounted over the wheel 100 in the collapsed position. However, the tire 104 may elastically expand when the wheel 100 is expanded. The elastic expansion of the tire 104 may create a restoring force in the tire 104 by which the tire 104 is pressed onto the rims 118 (for example the projections 120 are pressed in the grooves 136) to maintain the tire 104 on the wheel 100 during the operation of the wheel 100.

To expand the wheel 100 from a collapsed position to the expanded position, each of the wheel sections 110 may be rotated by hand. In one example shown in FIGS. 15 and 16, the wheel 100 includes a hubcap 200 by which the wheel sections 110 may be rotated relative to each other to expand the wheel 100. The hubcap 200 may include two opposing handles 202 and 204 that can be held by an individual for rotating the hubcap 200. The hubcap 200 may include a pin (not shown) on an inner surface thereof that may engage inside the slot 140 of the last mounted wheel section 110. The hubcap 200 may be rotationally mounted on the shaft 106. Accordingly, when the hubcap 200 is turned about the shaft 106 by an individual, the pin on the inner surface of the hubcap 200 moves in the slot 140 of the first wheel section 110 until the pin engages the second end 152 of the slot 140. After the first wheel section 110 is turned at the expansion angle, the pin 144 of the first wheel section 110 engages the second end 152 in the slots 140 of the second wheel section 110 as described above. Accordingly, further rotation of the

8

hubcap 200 causes the second wheel section 110 to rotate relative to the third wheel section 110 at the expansion angle. Continuing the rotation of the hubcap 200 rotates the remaining wheel sections 110 until the wheel 100 is completely expanded. The hubcap of 200 may be mounted on the shaft 160 between the last mounted wheel section 110 and the spring clip of 174. When holding the handles 202 and 204, an individual can also hold the second bracket section 166 to provide leverage when expanding the wheel 100.

FIGS. 17 and 18 show a wheel 400 according to another example. The wheel 400 is similar in certain aspects to the wheel 100. Accordingly, similar parts of the wheel 100 and the wheel 400 are referred to with the same reference numbers. The wheel 400 includes a plurality of wheel sections 110 that are mounted on an axle 406 (shown in FIG. 17). The axle 406 includes a first end 462 (shown in FIG. 17) and a second end (not shown). The axle 406 receives the wheel sections 110 by being inserted into the central bores 114 of the wheel sections 110. The second end of the axle 406 includes a base 470 that is larger in diameter than the diameter of the central bore 114 of the wheel sections 110. Accordingly, when the wheel sections 110 are mounted on the axle 406, the wheel sections 110 are bound at the second end of the axle by the base 470. To prevent the wheel sections 110 from being removed from the axle 406 during the operation of the wheel 400, the second end 462 the axle 406 may be threaded to receive a correspondingly threaded nut 480. Thus, tightening the nut 480 on threaded first end 462 of the axle 406 prevents the wheel sections 110 from being removed from the axle 406 during the operation of the wheel 400. Alternatively, the wheel 400 may include a wheel holding mechanism similar to the wheel holding mechanism of the wheel 100 as described in detail above. The wheel 400 includes a hubcap 200 which may be used to expand the wheel 400 from the collapse position to the expanded position as described in detail above with respect to the wheel 100.

Referring to FIG. 18, the first mounted wheel section 110 may include two opposing handles 502 and 504 on the central hub section 112 that are position similar to the handles 202 and 204 of the hubcap 200. Accordingly, an individual can expand the wheel 400 from the collapsed position by holding the handles 202 and 204 with one hand and rotating the handles 202 and 204 in one direction and holding the handles 502 and 504 with the other hand and rotating the handles 502 and 504 in the opposite direction to rotate the wheel sections relative to each other to expand the wheel 400 to the expanded position. The handles 502 and 504 may be part of a hubcap (not shown) that is mounted on the axle 406 before the first mounted wheel section 110 is mounted on the axle 406. Alternatively as shown in FIGS. 17 and 18, the handles 502 and 504 may be an integral part of the first mounted wheel section 110.

Referring to FIGS. 19 and 20, a wheel 600 according to another embodiment is shown. The wheel 600 is similar in some aspects to the wheels 100 and 400. Accordingly, similar parts of the wheels 100, 400 and 600 are referred to with the same reference numbers. The wheel 600 includes a plurality of wheel sections 610. Each wheel section 610 includes a hub section 612 with a central bore (not shown). Each wheel section 610 includes a pair of spaced apart generally straight spokes 616 on each side of the perimeter section of the hub section 612 that project radially outward and connect to a generally curved rim 618. The distance between each pair of spokes 616 may increase from the hub section 612 to the rim 618. Accordingly, each pair of spokes 616 and the corresponding rim 618 defines a generally

trapezoidal shape. The wheel **600** includes an axle **606** that is mounted through the central bores of the wheel sections **610**. The axle **606** and the mechanisms and methods by which the axle **606** is operatively connected to the wheel and the cart are similar to the axle **106** and **406**. Accordingly, a detailed description of the axle **606** is not provided.

Referring to FIGS. **21-25** a wheel **800** according to another example is shown. The wheel **800** includes a hub assembly **802** and a tire (not shown) that is mounted on the hub assembly **802** as described below. The wheel **800** also includes an axle **806** on which the hub assembly **802** and a tire are rotatably mounted. The hub assembly **802** includes a plurality of wheel sections **810** that are concentrically mounted on the axle **806**. Each wheel section **810** includes a hub section **812** having a central bore **814** for receiving a section of the axle **806**.

The tire may be mounted on a plurality of rims **818** that are positioned along a perimeter of a circle **817** that defines a central plane of the wheel **800**. Each rim **818** is generally oriented perpendicular to the circle **817** (shown in FIG. **24**) and is convex relative to the hub sections **812**. Accordingly, each rim **818** is concave relative to the tire (not shown) so as to receive a curved section of the tire. Each rim **818** is attached to two spaced apart hub sections **812** by two spokes **816**, respectively. The two hub sections **812** to which a rim **818** is attached with the spokes **816** are spaced apart so that the spokes **816** form a V-shaped support for each rim **818**. For example, as shown in FIG. **22**, the spokes **816** that support a rim **818** are connected to hub sections **812** are spaced apart by five hub sections **812**. Thus, each hub section **812** has one spoke **816** on one side thereof that partially supports a first corresponding rim **818**, and another spoke **816** on the opposite side thereof that partially supports a second corresponding rim **818**.

FIGS. **23-25** show the expanded position of the wheel **800**. The spokes **816** are positioned on the hub sections **812** such that when the wheel **800** is in the expanded position, the spokes **816** are evenly distributed around the wheel, i.e., radially spaced apart on the circle **817** at a similar expansion angle. In the example of FIGS. **23-25**, the spokes **816** are shown to be generally 30° apart in the expanded position of the wheel **800**. FIGS. **21** and **22** show the collapsed position of the wheel **800**. To collapse the wheel **800**, the hub sections **812** may be rotated relative to each other until the rims **818** contact each other and prevent further rotation of the hub sections **812**. To expand the wheel **800**, the hub sections **812** may be rotated in an opposite direction relative to each other such that the wheel **800** reaches the expanded position shown in FIG. **23**. Because each spoke **816** is located on a different hub section **812**, the wheel **800** may require a rotation of less than 180° for expansion from the collapsed position to the expanded position. Accordingly, to expand the wheel **800** from the collapsed position as shown in FIG. **21**, the spoke **820** is rotated clockwise until the spoke **820** is positioned close to spoke **822** and is prevented from further rotation by an expansion limiting mechanism as described below. Simultaneously, the spoke **824** is rotated clockwise until it is positioned close to spoke **826** and is prevented from further rotation by the expansion limiting mechanism. Thus, the largest rotation of a hub section **812** may be less than 180° to expand the wheel from the collapsed position to the expanded position.

To prevent further rotation of the hub sections **812** relative to each other when the wheel **800** reaches the expanded position shown in FIG. **23**, the wheel **800** may include an expansion limiting mechanism as described above. Accordingly, each wheel section **810** may include a radial slot (not

shown) on the hub section **812** and a pin (not shown) that may be located on the hub section **812** opposite to the slot relative to the central bore **814**. The arc length of each radial slot **140** may be generally no greater than the expansion angle. In the example of FIG. **24** the arc length of the radial slot is about 30° , which is the same as the expansion angle.

A tire (not shown) may be mounted on the wheel **800** before or after the wheel is expanded. The tire may be constructed from a solid piece of rubber or other type of plastic material that has sufficient elasticity to allow mounting of the tire on the wheel **800**. Alternatively, the tire may be in the form of an inflatable tube that may be mounted on the rims **818**. Accordingly, the tire may be inflated by an individual before operating the wheel **810**. Alternatively yet, the tire may be attached to one or more of the rims **818** such that the tire is maintained in a mounted configuration on the wheel **800** in both the collapsed and expanded positions of the wheel **800**.

FIGS. **26-33** show several exemplary wheels and/or wheel sections according to the disclosure. A wheel section **1010** as shown in FIG. **26** may include at least one spoke **1016** on each side of a hub section **1012**. The wheel section **1010** also includes a least one rim **1018** attached to each spoke **1016**. Each spoke **1016** and the corresponding rim **1018** generally define a T-shaped spoke and rim assembly. A wheel section **1110** as shown in FIG. **27** may include at least one spoke **1116** on each side of a hub section **1112**. The wheel section **1110** also includes at least one rim **1118** attached to each spoke **1116**. Each spoke **1116** and the corresponding rim **1118** generally define an L-shaped spoke and rim assembly. According to the exemplary wheel sections **1010** and **1110**, at least one rim and at least one spoke may be attached to each other in any configuration. For example, an end of a spoke may be attached to a center of the length of the rim as shown by the wheel section **1010** to provide a generally T-shaped spoke and the rim assembly. With the exemplary wheel section **1110** however, the end of the spoke is attached to one end of the rim. Therefore, a spoke and a rim may be attached to each other in any configuration and with any type of offset relative to each other.

FIGS. **28** and **29** show a wheel **1200** according to another example. The wheel **1200** includes a plurality of wheel sections **1210**, where each wheel section **1210** may have a different configuration as compared to one or more of the other wheel sections **1210**. For example, each wheel section **1210** may have different shaped spokes **1216**. The spokes **1216** may be straight, curved, L shaped, Z shaped and/or have any other shape that may be different from the spokes **1216** of one or more of the other wheel sections **1210**. Depending on the shape of each spoke **1216**, each spoke may have different thickness, may be constructed from a different material and/or have a certain property that may be different from or similar to one or more other spokes **1216** of one or more other wheel sections **1210**. A tire **1204** may be mounted on the wheel **1200** in both the collapsed position in the expanded position of the wheel **1200**.

FIGS. **30** and **31** show a wheel **1300** according to another example. The wheel **1300** includes a plurality of spokes **1316**. Each spoke may be flexible so as to deform from an extended position corresponding to the expanded position of the wheel **1300** to a deformed position corresponding to the collapsed position of the wheel **1300**. FIG. **30** shows an example of the wheel **1300** in the process of being expanded between the collapse position and the expanded position shown in FIG. **31**. In the extended position of the spokes **1316** as shown in FIG. **31**, the spokes **1316** have sufficient

11

collective rigidity to support the loads on the tire **1304** and the hub assembly **1302** to provide operation of the wheel **1300** as disclosed. However, the spokes **1316** are flexible so that the wheel **1300** may be collapsed by deforming the spokes **1316** to collapse the wheel **1300**. As shown in the example of FIG. **30**, the spokes **1316** may be deformed by being bent and stacked on top of each other around the hub **1312**. The spokes **1316** may also provide a shock absorbing function for the wheel **1300**. The wheel **1300** may include a singular hub **1312** to which all of the flexible spokes **1316** are attached. Alternatively, the wheel **1300** may include a plurality of hub sections, where each hub section is rotatable relative to an adjacent hub section to facilitate collapsing and expanding of the wheel **1300** which one or more spokes **1316** may be attached. As shown in FIGS. **30** and **31**, the wheel **1300** may also include a tire **1304**, which may be similar to the exemplary tires disclosed herein.

FIGS. **32** and **33** show a wheel **1400** according to another example. The wheel **1400** includes a hub **1412** to which the rim **1418** is attached. The rim **1418** includes a first rim section **1420** and a second rim section **1422** that are pivotally mounted to the hub **1412** by one or more hinges **1424**. As shown in FIG. **33**, the first rim section **1420** and the second rim section **1422** can be pivoted at the hinge **1424** to collapse the wheel **1400** from the expanded position shown in FIG. **32** to a collapsed position (not shown). Thus, the size of the wheel **1400** may be reduced for storage and/or transportation upon collapsing the wheel from the expanded position.

Referring to FIG. **34**, a section of a wheel **1500** according to another example is shown. The wheel **1500** includes at least one spoke **1516** and at least one rim **1518** that is attached to the spoke **1516**. The wheel **1500** may not include a one-piece tire similar to the examples described above. Instead, a tire section **1504** is attached to each rim **1518**. Accordingly, when the wheel **1500** is expanded to an expanded position, the tire sections **1504** collectively define a tire for the wheel **1500**. Therefore, the tire for the wheel **1500** is defined by a plurality of tire sections **1504** and any gaps that may be present between adjacent tire sections **1504**. As with the examples described above, the tire section **1504** may be constructed from an elastic material such as rubber. The tire sections **1504** may then be attached to a rim **1518** with an adhesive, one or more fasteners and/or one or more other types of attachment devices or procedures.

Referring to FIGS. **35-41**, a wheel **1600** according to another example is shown. The wheel **1600** includes a hub assembly **1602**. The wheel **1600** may include a tire (not shown) that may be mounted on the hub assembly **1602**. Alternatively, the wheel **1600** may include a plurality of tire sections as described above with respect to the wheel **1500**. Alternatively yet, the wheel **1600** may operate without a tire. The wheel **1600** also includes an axle **1606** on which the hub assembly **1602** is rotatably mounted. The hub assembly **1602** includes a plurality of wheel sections **1610** that are concentrically mounted on the axle **1606**. Each wheel section **1610** includes a hub section **1612** having a central bore **1614** for receiving a section of the axle **1606**.

The wheel **1600** includes a plurality of rims **1618** that are configured to define a path on a circumferential or circular band **1617** having a width **1619**. The path defined by the rims **1618** may be substantially continuous. The circular band **1617** defines a circular contact area similar to a tire (shown in FIG. **38**) between the wheel **1600** and the ground. In the expanded position of the wheel **1600**, each rim **1618** may be oriented such that at least one point on at least one rim **1618** contacts the ground. In one example, each rim **1618** is positioned diagonally on the circular band **1617**.

12

Each rim **1618** may be radially spaced apart from an adjacent rim **1618** as long as the space does not provide a large enough gap to substantially disturb or hinder generally smooth rolling of the wheel **1600** on the ground. Alternatively, each rim **1618** may not have a radial gap relative to an adjacent rim **1618**. Alternatively yet, each rim **1618** may have a radial overlap with an adjacent rim **1618**. In the example of FIG. **38**, each rim **1618** has a small gap relative to an adjacent rim **1618**. Each rim **1618** may also be curved so that points on adjacent rims **1618** that are spaced apart at a certain angle are located on the circular band **1617**. Thus, as shown in FIG. **35**, the rim **1618** defines a portion of a path on a generally continuous circle in the expanded position of the wheel **1600**. In other words, the curvature of each rim **1618** may generally follow the curvature for the circle defining a plane of the wheel **1600**.

Each rim **1618** is attached to two spaced apart hub sections **1612** by two spokes **1616**, respectively. The two hub sections **1612** to which a rim **1618** is attached with the spokes **1616** are spaced apart so that the spokes **1616** form a V-shaped support for each rim **1618**. For example, as shown in FIG. **41**, the spokes **1616** that support a rim **1618** are connected to hub sections **1612** are spaced apart by four hub sections **1612**. Thus, each hub section **1612** has one spoke **1616** on one side thereof that partially supports a first corresponding rim **1618**, and another spoke **1616** on the opposite side thereof that partially supports a second corresponding rim **1618**.

FIGS. **35**, **36** and **38** show the expanded position of the wheel **1600**. The spokes **1616** are positioned on the hub sections **1612** such that when the wheel **1600** is in the expanded position, the spokes **1616** are evenly distributed around the wheel, i.e., radially equally spaced apart at a similar expansion angle. In the example of FIG. **35**, the spokes **1616** are shown to be generally 30° apart in the expanded position of the wheel **1600**. FIGS. **37**, **39** and **40** show the collapsed position of the wheel **1600**. To collapse the wheel **1600**, the hub sections **1612** may be rotated relative to each other until the rims **1618** contact each other and prevent further rotation of the hub sections **1612**. Each spoke **1616** may have a certain cross-sectional shape to provide a more compact collapsed position for the wheel **1600**. For example, each spoke **1616** may have a diamond shaped cross-section as shown in FIG. **41**. Accordingly, when the wheel **1600** is collapsed, each spoke **1616** may be positioned relative to an adjacent spoke **1616** in the complementary or a formfitting manner. Therefore, the spokes **1616** may collectively occupy less space as compared to a scenario where each spoke **1616** has a certain shape that does not lend itself to such complementary fitting with an adjacent spoke **1616**.

To expand the wheel **1600**, the hub sections **1612** may be rotated in an opposite direction relative to each other such that the wheel **1600** reaches the expanded position **1612**. Because each spoke **1616** is located on a different hub section **1612**, the wheel **1600** may require a rotation of less than 180° for expansion from the collapsed position to the expanded position as described in detail with respect to the wheel **800**, hence not repeated herein. Thus, the largest rotation of a hub section **1612** may be less than 180° to expand the wheel **1600** from the collapsed position to the expanded position.

To prevent further rotation of the hub sections **1612** relative to each other when the wheel **1600** reaches the expanded position, the wheel **1600** may include an expansion limiting mechanism as described above. Accordingly, each wheel section **1610** may include a radial slot (not

13

shown) on the hub section **1612** and a pin (not shown) that may be located on the hub section **1612** opposite to the slot relative to the central bore **1614**. The arc length of each radial slot may be generally no greater than the expansion angle.

Similar to the example of FIG. **34**, each rim **1618** may include a tire section (not shown) that is attached to each rim **1618**. For example, each tire section (not shown) may be a generally rectangular strip of rubber or like elastic materials that is attached to each rim **1618** along the length of the rim **1618**. Thus, each tire section generally follows the orientation and the spatial position of each rim **1618** on the circular band **1617** as described above. Accordingly, when the wheel **1600** is expanded to an expanded position, the tire sections collectively define a tire for the wheel **1600**. As with the examples described above, a tire section may be constructed from an elastic material such as rubber. The tire sections may then be attached to a rim **1618** with an adhesive, one or more fasteners and/or one or more other types of attachment devices or procedures.

A tire (not shown) may be mounted on the wheel **1600** before after the wheel is expanded. The tire may be constructed from a solid piece of rubber or other type of plastic material that has sufficient elasticity to allow mounting of the tire on the wheel **1600**. Alternatively, the tire may be in the form of an inflatable tube that may be mounted on the rims **1618**. Alternatively yet, the tire may be attached to one or more of the rims **1618** such that the tire is maintained in a mounted configuration on the wheel **1600** in both the collapsed and expanded positions of the wheel **1600**.

Referring to FIG. **42**, a method **1700** for constructing a wheel according to one example is shown. The method comprises forming a plurality of wheel sections (block **1702**), and assembling the wheel sections on an axle (block **1704**). The method **1700** may also include forming a tire (not shown) and/or mounting or attaching a tire on the wheel sections (not shown). A wheel according to the disclosure may be constructed from any metal or metal alloys, plastic, composite materials, wood or a combination thereof. For example, each wheel section such as the wheel sections **110** of the wheel **100** may be formed in one piece from a plastic material by injection molding. In an injection molding process, a mold having a cavity defining a wheel section may be used. Molten plastic material is injected in the mold and cooled. The molded and cooled wheel section is then removed from the mold. The molded wheel section may also be smoothed or cleaned to remove injection molding residue. Alternatively, a wheel section may be constructed by stamping (i.e., punching using a machine press or a stamping press, blanking, embossing, bending, flanging, coining, or casting), forging, machining or a combination thereof, or other processes used for manufacturing metal, composite, plastic or wood parts. Each wheel section may be formed in one piece. Alternatively, components of each wheel section may be formed by processes and materials described herein and assembled to form the wheel section. For example, the wheel section **110** may be formed by assembling a separately manufactured hub section **212**, spokes **216** and rim **218**. A hub section **212**, one or more spokes **216**, and a rim **218** may be attached to each other by one or more adhesives, welding, soldering and/or fasteners. The disclosed materials and/or processes may be used to manufacture any of the disclosed wheel, axle and/or tire components. A tire may be manufactured from an elastic material to provide shock absorption for a pull cart to which one or more disclosed wheels are attached. A tire may be formed from rubber or

14

other plastic materials. A tire may be formed as an inflatable tube or a solid flexible material.

Referring to FIG. **43**, a golf pull cart **1800** for supporting and transporting a golf club bag is shown having wheels **100**. Although the pull cart **1800** is shown with the wheels **100**, any of the wheels described herein may be used with a golf pull cart. The golf pull cart **1800** may include a frame **1810** on which a golf club bag (not shown) may be rested. The golf club bag may also be supported by a bottom support **1812**, a bottom side support **1813** and a top side support **1814**. The frame **1810** may also include one or more straps (not shown) for securing a golf club bag to the frame **1810**. The pull cart **1800** may further include two feet **1820** in **1822** that extend outwardly from the frame **1810** opposite to each other. Each foot supports a wheel **100**. The frame may also include a hinge **1824** having two hinge rods **1826** and **1828** by which the feet **1820** in **1822** may be pivoted and collapsed so that the feet **1820** and **1822** extend along the frame **1810**. The frame **1810** may also collapse at the hinge so as to provide a compact golf pull cart **1800** for transportation to and from a golf course, driving range or any golf related facility. A collapsed golf pull cart **1800** is shown in FIG. **44**. To further reduce the size of the golf pull cart **1800**, the wheels **100** may be collapsed as described in detail herein. Furthermore, the wheels **100** may be removed from the pull cart **1800** and stored separately. Thus, using the wheels **100** or any of the wheels described herein can reduce the size of any vehicle, such as a golf pull cart, for easier storage and/or transportation. Alternatively, a golf club bag (not shown) may include attachment points or axles for directly attaching two collapsible wheels as described in detail herein to the golf club bag. For example, a golf club bag may be provided with two collapsible wheels that can be stored in one or more pockets of the golf club bag. An individual may carry the golf club bag or attach the two wheels to an axle on the golf club bag, expand the wheels, and pull the golf club bag by using the wheels. The use of collapsible wheels as described in detail herein is not limited to golf pull carts. Collapsible wheels as described in detail herein may be used for kayak carts, grocery carts, small wagons that are typically used by children, any type of luggage, luggage carts, coolers and/or any other wheeled utility cart, trailer, enclosed storage device, or a vehicle.

Although a particular order of actions is described above, these actions may be performed in other temporal sequences. For example, two or more actions described above may be performed sequentially, concurrently, or simultaneously. Alternatively, two or more actions may be performed in reversed order. Further, one or more actions described above may not be performed at all. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

While the invention has been described in connection with various aspects, it will be understood that the invention is capable of further modifications. This application is intended to cover any variations, uses or adaptation of the invention following, in general, the principles of the invention, and including such departures from the present disclosure as come within the known and customary practice within the art to which the invention pertains.

What is claimed is:

1. A wheel comprising:
 - a plurality of wheel sections, each wheel section comprising:
 - a rim portion;
 - a hub portion defining a rotational axis;

15

a pair of spokes extending from the hub to the rim portion and being attached to the rim portion; wherein the plurality of wheel sections are rotatable relative to each other about the rotational axis from a collapsed position wherein the rim portions of the plurality of wheel sections define a segment of a circle to an expanded position wherein the rim portions of the plurality of wheels sections define the circle.

2. The wheel of claim 1, wherein the wheel sections are substantially fixed from rotation relative to each other in the expanded position.

3. The wheel of claim 1, further comprising a tire configured to be mountable on the rim portions in the collapsed position or the expanded position.

4. The wheel of claim 1, wherein each rim portion comprises a tire portion.

5. The wheel of claim 1, each wheel section comprising a radially configured slot and a pin configured to be received in the slot of another wheel section, wherein movement of the pin of one wheel section inside the slot of an adjacent wheel section defines a range of rotation of the one wheel section relative to the adjacent wheel section.

6. The wheel of claim 1, wherein the plurality of wheel sections define groups of wheel sections with each group comprising a pair of the wheel sections, and wherein the spokes of the wheel sections of each pair of wheel sections extend from the hub of the corresponding wheel section to the same rim portion.

7. The wheel of claim 1, wherein the rim portions substantially define a path on a circumferential band around the wheel sections in the expanded position.

8. The wheel of claim 1, further comprising an axle configured to removably receive the hub of each wheel section by being insertable in a central bore of each wheel section being coaxial with the rotational axis of the wheel section, wherein each wheel section is rotational relative to the axle.

9. A method of manufacturing a wheel comprising: forming a plurality of wheel sections so that each wheel section comprises a rim portion, a hub portion defining a rotational axis, and a pair of spokes extending from the hub to the rim portion and being attached to the rim portion;

wherein the plurality of wheel sections are rotatable relative to each other about the rotational axis from a collapsed position wherein the rim portions of the plurality of wheel sections define a segment of a circle to an expanded position wherein the rim portions of the plurality of wheels sections define at least one full circle.

16

10. The method of claim 9, further comprising forming a locking mechanism configured to substantially fix the wheel sections from rotating relative to each other in the expanded position.

11. The method of claim 9, further comprising forming a tire configured to be mountable on the rim portions in the collapsed position or the expanded position.

12. The method of claim 9, forming a tire section on each rim portion.

13. The method of claim 9, further comprising forming a radially configured slot and a pin on each wheel section, the pin configured to be received in the slot of another wheel section, wherein movement of the pin of one wheel section inside the slot of an adjacent wheel section defines a range of rotation of the one wheel section relative to the adjacent wheel section.

14. The method of claim 9, further comprising forming the plurality of wheel section such that the spokes of two wheel sections extend from the hub of the corresponding wheel sections to the same rim portion.

15. The method of claim 9, wherein the rim portions substantially define a path on a circumferential band around the wheel sections in the expanded position.

16. The method of claim 9, further comprising forming an axle configured to removably receive the hub of each wheel section by being insertable in a central bore of each wheel section being coaxial with the rotational axis of the wheel section, wherein each wheel section is rotational relative to the axle.

17. A wheel comprising:

a plurality of planar hub sections staked on top of each other to define a hub having a rotational axis;

a plurality of rim portions;

a plurality of spokes, each spoke extending from one of the plurality of hub sections to one of the plurality of rim portions and being attached to the rim portion;

wherein the hub sections are rotatable relative to each other about the rotational axis from a collapsed position wherein the rim portions form a segment of a rim of the wheel to an expanded position wherein the rim portions define the rim of the wheel; and

wherein the hub sections are substantially fixed from rotation relative to each other in the expanded position.

18. The wheel of claim 17, further comprising a tire configured to be mountable on the rim portions in the collapsed position or the expanded position.

19. The wheel of claim 17, wherein each rim portion comprises a tire portion.

20. The wheel of claim 17, wherein each of the rim portions extends diagonally along a circumferential band defining the rim of the wheel.

* * * * *