




(86) Date de dépôt PCT/PCT Filing Date: 2008/03/28
(87) Date publication PCT/PCT Publication Date: 2008/10/09
(85) Entrée phase nationale/National Entry: 2009/09/25
(86) N° demande PCT/PCT Application No.: AU 2008/000445
(87) N° publication PCT/PCT Publication No.: 2008/119115
(30) Priorité/Priority: 2007/03/30 (AU2007901728)

(51) Cl.Int./Int.Cl. *F42B 5/188* (2006.01),
F42B 30/00 (2006.01), *F42B 33/00* (2006.01),
F42B 5/18 (2006.01)
(71) Demandeur/Applicant:
TECHVENTURE INVESTMENTS PTY LTD, AU
(72) Inventeur/Inventor:
HARRISON, LESLIE MERVYN, AU
(74) Agent: BORDEN LADNER GERVAIS LLP

(54) Titre : PROCÉDE DE FABRICATION DE MUNITION
(54) Title: A METHOD OF MANUFACTURING AMMUNITION



(57) **Abrégé/Abstract:**

A method of manufacturing ammunition (10) for firing from the barrel of a weapon comprises forming a mould (32) having an interior surface, placing a core (42) in the mould (32) to produce a casting void (43) and pouring a liquefied solidifiable material into the casting void (43). Upon solidification of the material, the core (42) is removed to produce a projectile body (12) having a closed end and an opposite end. The removal of the core (42) also creates the cavity (18) in the projectile body (12) that opens onto the opposite end. The projectile body (12) is removed from the mould (32) and a quantity of propellant (22) is deposited into the cavity (18) through the opposite end. A seal (26) which incorporates a primer is pressed into the opposite end. Circumferential flanges (30a) and (30b) are integrally moulded with the projectile body (12).

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
9 October 2008 (09.10.2008)

PCT

(10) International Publication Number
WO 2008/119115 A1

(51) International Patent Classification:

F42B 5/188 (2006.01) *F42B 30/00* (2006.01)
F42B 5/18 (2006.01) *F42B 33/00* (2006.01)

(21) International Application Number:

PCT/AU2008/000445

(22) International Filing Date: 28 March 2008 (28.03.2008)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

2007901728 30 March 2007 (30.03.2007) AU

(71) Applicant (for all designated States except US):
TECHVENTURE INVESTMENTS PTY LTD
[AU/AU]; 35 Vintage Lane, The Vines, Western Australia
6069 (AU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **HARRISON, Leslie,**
Mervyn [AU/AU]; 40 Chatsworth Drive, Hocking, West-
ern Australia 6065 (AU).

(74) Agent: **GRIFFITH HACK**; Level 19, 109 St Georges
Terrace, Perth, W.A. 6000 (AU).


(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA,
CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE,
EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID,
IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC,
LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN,
MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV,
SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN,
ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL,
NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG,
CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

(54) Title: A METHOD OF MANUFACTURING AMMUNITION



(57) Abstract: A method of manufacturing ammunition (10) for firing from the barrel of a weapon comprises forming a mould (32) having an interior surface, placing a core (42) in the mould (32) to produce a casting void (43) and pouring a liquefied solidifiable material into the casting void (43). Upon solidification of the material, the core (42) is removed to produce a projectile body (12) having a closed end and an opposite end. The removal of the core (42) also creates the cavity (18) in the projectile body (12) that opens onto the opposite end. The projectile body (12) is removed from the mould (32) and a quantity of propellant (22) is deposited into the cavity (18) through the opposite end. A seal (26) which incorporates a primer is pressed into the opposite end. Circumferential flanges (30a) and (30b) are integrally moulded with the projectile body (12).

- 1 -

A METHOD OF MANUFACTURING AMMUNITIONField of the Invention

5 The present invention relates to a method of manufacturing ammunition for firing from the barrel of a weapon, and in particular, but not exclusively, firearm ammunition.

Background of the Invention

10

A common firearm ball type ammunition, as opposed to shotgun ammunition, comprises a metallic cartridge case containing a volume of propellant, with a primer fixed in a base of the case and a bullet or projectile releasably
15 pressed into an opposite end of the case. When this type of ammunition is in use, a firing pin impacts on the primer which in turn produces a flame to initiate deflagration of the propellant. As the propellant deflagrates inside the case, it produces large volumes of
20 gas which ejects the bullet or projectile from the case, propelling the bullet through the barrel of the weapon from which the ammunition is fired.

The manufacturing process for this type of ammunition is
25 well known and relatively straight forward. Typically, the cases are formed by a stamping or drawing process. A primer is loaded into the base of the cartridge, the cartridge filled with propellant, and the bullet or projectile which is usually made by a casting process
30 pressed into the cartridge.

The present invention proposes a different manufacturing process and produces a different type of ammunition.

35

- 2 -

Summary of the Invention

In the claims of this application and in the description of the invention, except where the context requires
5 otherwise due to express language or necessary implication, the words "comprise" or variations such as "comprises" or "comprising" are used in an inclusive sense, i.e. to specify the presence of the stated features but not to preclude the presence or addition of further
10 features in various embodiments of the invention.

According to one aspect of the present invention there is provided a method of manufacturing, a caseless projectile for firing from a barrel of a small arms weapon the method
15 comprising:

forming a mould having an interior surface and an opening at a first end;

placing a core into the opening in the mould to produce a casting void between the core and the interior
20 surface;

introducing a liquefied solidifiable material into the casting void;

relatively shaping the mould and the core wherein upon removing the core a projectile body is formed having
25 a closed nose;

withdrawing the core from the projectile body to create an opposite open end in the projectile body and a cavity which opens onto the opposite open end;

removing the projectile body from the mould; and,
30 depositing a propellant in the cavity.

The method may further comprise sealing the opposite end with a seal. The seal may comprise a primer.

35 The method may further comprise forming a seat in the cavity for seating the seal. In one embodiment, forming the seat may comprise configuring one or both of the core and the mould in a manner to produce a seat void into which the liquefied material flows to form, upon

- 3 -

solidification, the seat. In this embodiment the seat void is circular in shape to produce a circular seat or land. In an alternate embodiment, the core may be provided with a plurality of elongated grooves which
5 create rib voids in the cavity, into which the liquefied material flows to form, upon solidification, corresponding ribs along the inside of the cavity. In this embodiment, the seat is formed by ends of the ribs nearest the opposite end.

10

However in yet a further embodiment the method of forming the seat may comprise placing an insert into the mould, the insert having an open end disposed inside the cavity and inboard of the opposite end, the open end forming a
15 lip inside of the cavity, the lip constituting the seat.

The placing of the insert into the mould may comprise forming an insert, placing the insert on the core, and inserting the core into the mould, wherein, the insert is
20 retained in the projectile body when the core is removed from the projectile body.

The method may further comprise forming a core with a plug and a spigot extending axially from the plug. In this
25 embodiment, the grooves may be formed along the spigot. The forming of the mould may comprise forming the mould from at least two separate parts which can be brought together to produce the casting void, and moved apart to facilitate removal of the projectile body from the mould.

30

The forming of the mould may further comprise forming the mould with open opposite first and second ends and wherein the placing of the core in the mould comprises inserting the core into the mould from the first end, and

- 4 -

introducing the liquefied material comprising pouring the material into the mould from the second end.

One embodiment of the method may further comprise forming
5 one or more circumferential grooves in the interior surface of the mould into which the liquefiable material flows, to form, upon solidification one or more corresponding circumferential flanges about an outside surface of the projectile body. When the projectile is in
10 use, the or each flange engages rifling, and may act as a seal against an inner surface of a barrel of a weapon from which the ammunition is fired. More particularly in one embodiment the method may comprise configuring the mould so that a maximum diameter D_1 of body is less than a bore
15 diameter D_b of the barrel. In addition, the circumferential grooves may be formed of a depth so that the corresponding flanges have an outer diameter $D_b < D_2 \leq D_g (1 + \Delta)$ where $0.05 \geq \Delta \geq 0$ and where D_g is a groove diameter of the barrel.

20

In an alternate embodiment, the mould may be provided with a circumferential ridge about its interior surface which, upon solidification of the liquefiable material, forms a corresponding circumferential groove about the projectile
25 body. This embodiment further comprises the step of engaging a sealing ring in the circumferential groove. In use, the sealing ring can form a seal against an inner circumferential surface of a barrel of a weapon from which the ammunition is fired. In a variation to this
30 embodiment, the circumferential ridge may be one of a plurality of ridges each forming a circumferential groove about the projectile body.

According to a further aspect of the invention there is
35 provided a method of manufacturing a caseless projectile for firing from a small arms weapon the method comprising:

- 4a -

providing a mould comprising two portions which when brought together form an interior surface of mould, the portions each provided with at least one semi circular groove the grooves on the portions being aligned to
5 together form a circumferential groove in the internal surface;
placing a core in the mould to produce a casting void between the core and the interior surface introducing a liquefied solidifiable material into the casing void;
10 relatively shaping the mould and the core wherein upon removing the core from the mould and opening the mould a projectile body is made from the material, the projectile body having a closed nose at a forward end of the body, an opposite open end and one or more integrally formed
15 circumferential flanges extending about on a outer surface of the body at locations corresponding of the circumferential grooves in the interior surface of the mould.

20 According to a further aspect of the invention there is provided a method of manufacturing a caseless projectile for firing from a barrel of a small arms weapon the method comprising:
forming a mould having an interior surface;
25 placing an insert having an open end on a core and placing the core in the mould to produce a casting void between an exterior surface of the insert and the interior surface;
introducing a liquefied solidifiable material into
30 the casting void;
the mould and core being shaped wherein upon removing the core, a projectile body is formed having a closed nose and an opposite open end, with the insert being retained in the projectile body, an interior of the
35 insert forming a cavity which opens onto the opposite open end;
removing the projectile body from the mould; and,
depositing a propellant in the insert

- 5 -

Brief Description of the Drawings

Embodiments of the present invention will now be described
by way of example only with reference to the accompanying
5 drawings in which:

Figure 1a is a side elevation of a left half of a mould
used in an embodiment of the present method of
manufacturing a projectile;

10 Figure 1b is a front elevation view of the left hand mould
shown in Figure 1a;

Figure 1c is a front elevation view of a right half of the
mould;

Figure 1d is a side elevation of the right half of the
15 mould shown in Figure 1c;

Figure 2 is an end elevation of the mould with the right
and left halves shown in Figures 1 put together;

Figure 3a is a side elevation view of a core incorporated
in an embodiment of the method;

20 Figure 3b is an end elevation view of the core shown in
Figure 2a;

Figure 4a is a side elevation of a core incorporated in a
further embodiment of the method;

Figure 4b is an end elevation view of the core shown in
25 Figure 4a;

Figure 5a is a schematic representation of a core and
insert that may be used in a further embodiment of the
method;

Figure 5b is a partial section view of a round of
30 ammunition manufactured using the core and insert shown in
Figure 5a; and

Figure 6 is a partial cut away view of a round of
ammunition manufactured in accordance with an embodiment
of the present invention.

- 6 -

Detailed Description of the Preferred Embodiments

Embodiments of the present method facilitate the manufacture of ammunition of the type described in Applicant's co-pending international publication no. WO 2005/095884. An embodiment of around of ammunition 10 is depicted in Figure 6 which shows a projectile body 12 comprising a first (leading) end 14 and a second trailing, axially opposed end 16. An internal cavity 18 is formed between the ends 14 and 16 and holds a volume of a propellant 22. The first end 14 is closed by a nose 20 that is formed integrally with the body 12. End 16 is sealed with a base seal 26 that includes a primer 24 for igniting the propellant 22. A flame from the primer 24 is directed through a flash hole 28 formed in the base seal 26. The base seal 26 is pressed onto a seat 29 formed inside the body 12. Seals 30 in the form of circumferential flanges are provided about the body 12 for maintaining gas pressure of deflagrating propellant. In particular, the seals 30 form a seal against an inner circumferential surface (ie the groove diameter) of a barrel of a weapon from which the ammunition 10 is fired. Typically this would be the barrel of a fire arm. The ammunition 10 is caseless ammunition in that the propellant is held entirely with the projectile body 12 and there is no case or cartridge holding any propellant on to which the projectile body is attached.

Figures 1a - 2 depict an embodiment of a mould 32 incorporated in the present method for manufacturing the ammunition 10. Figures 1a and 1b; and, Figures 1c and 1d depict left and right side portions 34a and 34b (hereinafter referred to in general as "portions 34") respectively of the mould 32. The portions 34 have mirror image configurations. The portions 34a and 34b are

- 7 -

provided with recesses 36a and 36b (referred to in general
as "recesses 36") in their respective surfaces 38a and
38b. When the portions 34 are brought together to form
the mould 32 respective surfaces 38a and 38b form an
5 interior surface 40 of the mould 32.

The interior surface 40 is in a general configuration
complimentary to the exterior shape of the projectile body
12. In order to form the cavity 18 in the projectile body
10 12 a core 42 (see Figures 1a, 3a and 3b) is inserted into
the mould 32. In particular, placing the core 42 in the
mould 32 results in the formation of a casting void 43
(one half of which is shown in Figure 1b between the core
42 and the interior surface 40.

15

In the illustrated embodiment, the interior surface 40 of
the mould 32 is formed with two circumferential grooves,
formed by semicircular grooves 44a and 44b and the other
by semicircular grooves 46a and 46b. Semicircular grooves
20 44a and 44b in the mould portions 34a and 34b together
form one of the circumferential grooves in the interior
surface 40 while the semicircular grooves 46a and 46b in
the mould portions 34a and 34b when brought together form
a second circumferential groove in the interior surface
25 40. A liquefied solidifiable material such a molten lead
is poured into the mould 32 and flows into the casting
void 43, the grooves to form the body 12 an
circumferential flanges, which act as seals 30a and 30b
extending about the projectile body 12 shown in Figure 6.

30

The mould portion 34a is formed with a pair of
semicircular dimples 48 which are diametrically opposed
about the recess 36a. The mould portion 34b is formed
with a pair of hemispherical recesses 50 diametrically
35 opposed about the recess 36b. The dimples 48 and recesses

- 8 -

50 are relatively located so as to register with each other when the portions 34 are brought together to form the mould 32. Channels 52 are formed in a side of the portions 34 opposite the surfaces 38a,38b for seating a
5 spring or clamp to hold the portions 34 together while the molten lead is poured into the mould 32.

As is apparent from Figures 1a - 1d, the mould 32 is formed with open opposite ends 54 and 56. The core 42 is
10 inserted into the end 54 prior to the introduction or pouring of molten lead into the mould 32. The mould 32 is then orientated so that the casting void 43 is vertically disposed with the end 54 lowermost and supported on a surface. Each recess 36 has a major length 58 extending
15 from the end 56 toward the end 54 of constant diameter which leads to a step wise increased diameter part 60 that opens onto the end 54.

Figures 3a and 3b depict an embodiment of the core 42
20 comprising a plug 62 and a spigot 64 extending coaxially from the plug 62. The plug 62 has a base 65 of a configuration so as to seat in the increased diameter part 60 and abut against circumferential and radial surfaces of the part 60. The plug 62 further includes a reduced
25 diameter portion 66 that is dimensioned to extend into and abut against a corresponding length of an inner circumferential wall of the part 58 of each recess 36. The base 65 and reduced diameter portion 66 in effect seal the open end 54 of the mould 32. This substantially
30 closes the end 54 to prevent or substantially minimise leakage of molten lead.

Extending from the portion 66 is a further step wise reduced diameter portion 68. The spigot 64 extends
35 coaxially with the portion 68 and has a slightly smaller

- 9 -

diameter. The difference in the diameter between the portion 68 and the spigot 64 forms the seat 29 in the projectile body 12 (see Figure 6).

5 To facilitate easy removal of the core 42 from the projectile body 12 the spigot 64 is provided with a slight taper so as to reduce in outer diameter in a direction away from the plug 62. A blind hole 69 is formed in the base 65 coaxial with the spigot 64. The hole 69 receives
10 a tool to assist in gripping and thus extracting the core 42 from the body 12.

A typical sequence of events in the manufacture of the projectile 10 is as follows:

- 15 (a) bring the mould portions 34 together with the dimples 48 seated in the hemispherical seats 50 and then clamp the portions 34 together by a clamp or spring seated in the grooves 52;
- (b) insert the core 42 into the mould 32 from the open
20 end 54 seating the plug 62 and in particular the base 65 in the increased diameter portion 60 of the recess 36 to thereby form the casting void 43 between the core 42 and the interior surface 38;
- (c) introduce (i.e. pour) the liquefied solidifiable
25 material such as molten lead into the casting void;
- (d) upon or just prior to solidification of the molten lead, remove the core 42 from the projectile body 12 to create a cavity 18 in the body 12 which opens onto an open end 16 of the body 12;
- 30 (e) separate the mould portions 34 and remove the projectile body 12;
- (f) depositing a quantity of propellant 22 into the cavity 18;
- (g) press the seal 26 into the body 12 onto the seat 29
35 to seal the end 16.

- 10 -

However in a minor variation the core could be removed after opening the mould to remove the body, ie step (e) could be performed before step (f).

5 Figures 4a and 4b depict an alternate form of the core, denoted herein as core 42' that may be used in an alternate embodiment of the present method. The core 42' is identical with the core 42 with the exception of the inclusion of three elongate and evenly spaced grooves 70
10 that extend along the length of the spigot 64. The grooves 70 create rib voids in the casting cavity 43 into which molten lead flows to form, upon solidification, corresponding integrally formed ribs 72 (shown in phantom in Figure 8) along the inside of the cavity 18 in the
15 projectile body 12. The ribs 72 form two functions. Firstly, they provide increased strength to the projectile body 12, and secondly, ends of the ribs 72 nearest the end 16 act as lands which together form an alternate configuration seat 29 for the seal 26. Thus, in this
20 embodiment, the method creates a seat which, instead of being a ring like structure comprises three lands onto which the seal 26 can be pressed.

Figures 5a and 5b depict a variation in the method by
25 which an insert or sleeve 80 in the form of a cylindrical tube having a closed end 82 is moulded into the ammunition 10. The insert 80 is carried by a modified core 42''. The core 42'' differs from the core 42 by omission of the reduced diameter part 68 so that the spigot 64 extends
30 directly from the reduced diameter portion 66. The core 42'' with the insert 80 carried on the spigot 64 is inserted into the mould 32. After the molten lead has solidified, and the core 42'' is extracted leaving the insert 80 inside the body 12 as depicted in Figure 5b. A
35 rim of the open end of the insert 80 may also act to form

- 11 -

the seat 29. As shown in Figure 5b an upper portion of the body 12 near end 16 may have a thickened wall and partially overhang the upper end of the insert 80, still leaving the seat 29 for the seal 26. Although in an
5 alternate embodiment the wall of the body 12 may be of substantially uniform width with no overhang of the upper (open) end of the insert 80.

An advantage of using the insert 80 is that it may be made
10 from a stronger material than that used for the body 12, (for example high tensile steel) providing greater hoop strength to the body 12 for the purposes of confining deflagrating propellant. In particular, the sleeve will minimise radial expansion of the body 12 to reduce the
15 likelihood of the outer surface of the body 12 contacting the rifling in a barrel after commencement of deflagration. The mould 32 may be configured to have an inner diameter D_1 , corresponding to a maximum outer diameter of the body 12, which is less than or equal to a
20 bore diameter of a weapon from which the ammunition 10 is to be fired, and an inner diameter D_2 , corresponding to the outer diameter of the seals 30a,30b, between a minimum which is at least greater than the bore diameter and a maximum which is greater than a groove diameter of the
25 weapon. Thus, for example, if the bore diameter is signified as D_b and the groove diameter as D_g , then $D_1 \leq D_b$ and $D_b < D_2 \leq D_g(1+\Delta)$ where $.05 \geq \Delta \geq 0$. In this way, prior to firing the ammunition 10, the ammunition 10 will have a body 12 of a maximum diameter less than or at most equal
30 to the bore diameter, and seals 30a,30b will have a diameter that will engage the rifling and also engage the groove diameter of the weapon. When the seals 30a,30b engage the groove diameter and the rifling, a seal is formed which substantially eliminates the escape of high
35 pressure gas past the ammunition 10. Indeed in a further

- 12 -

embodiment the seals may have different diameters to each other. For example, the seal 30b may have a diameter equal to the groove diameter D_g with the rear seal 30a having a diameter equal to or marginally less than a
5 breech diameter. In this way the rear seal 30a will centrally position the ammunition with respect to a central axis of the barrel.

In embodiments where the insert 80 is incorporated in the
10 method of manufacturing, after firing of the ammunition 10, the insert 80 may confine radial expansion of the ammunition 10 as it travels along the barrel of the weapon to the extent that D_1 is always less than the bore diameter so that the outer surface of the body does not
15 have any substantive contact with the rifling. This minimises drag in the barrel and maximises thrust produced by the propellant.

In the above discussion the term "bore diameter" is
20 intended to define the internal diameter of a barrel measured from the tops of diametrically opposed lands forming the rifling, ie the smallest internal diameter. If the lands are not opposed, then the bore diameter is the diameter of a circle inscribed to touch the top of the
25 lands. The bore diameter is the inside diameter of the barrel before the rifling is cut. The term "groove diameter" is intended to define the diametrical measurement of the bore of a rifled barrel, measured from the bottom of opposing grooves (ie the largest internal
30 diameter). If the grooves are not opposed, the groove diameter is deemed to be the diameter of a circle inscribed to touch the bottoms of the grooves. Now that embodiments of the invention have been described in detail it will be apparent to those skilled in the relevant arts
35 that numerous modifications and variations may be made

- 13 -

without departing from the basic inventive concepts. For example, the method described depicts the manufacture of a mould 32 having a single casting cavity 40. However a mould 32 may be formed with any number of cavities so as to form multiple projectile bodies 12 from a single mould. Alternately, a plurality of separate moulds 32 each having a single casting cavity 40 may be cast simultaneously to again form multiple projectile bodies 12 in a single casting step. Figures 5a and 5b depict the use of an insert 80 having one open end and a closed end 82. However in an alternate embodiment, both ends of the insert 80 may be open. Further, while the liquefied solidifiable material is described in the specification as being lead, other materials could be used including for example various metals and alloys such as aluminium, steel, and brass; rubbers; or settable plastics and resins. The use of an insert 80 may provide further benefits when the liquefiable material is a plastics material or a rubber material in protecting the body 12 from being consumed by the deflagrating propellant.

All such modifications and variations together with others that would be obvious to a person of ordinary skill in the art are deemed to be within the scope of the present invention the nature of which is to be determined from the above description and the appended claims.

- 14 -

The claims defining the present invention are as follows:

1. A method of manufacturing, a caseless projectile for firing from a barrel of a small arms weapon the method comprising:
 - forming a mould having an interior surface and an opening at a first end;
 - placing a core into the opening in the mould to produce a casting void between the core and the interior surface;
 - introducing a liquefied solidifiable material into the casting void;
 - relatively shaping the mould and the core wherein upon removing the core a projectile body is formed having a closed nose;
 - withdrawing the core from the projectile body to create an opposite open end in the projectile body and a cavity which opens onto the opposite open end;
 - removing the projectile body from the mould; and,
 - depositing a propellant in the cavity.
2. The method according to claim 1, further comprising forming one or more circumferential grooves in the interior surface of the mould into which the liquefiable material flows, wherein, upon solidification one or more corresponding circumferential flanges are integrally formed about an outside surface of the projectile body.
3. The method according to claim 2, wherein the mould is configured so that a maximum diameter D_1 of the projectile body is less than a bore diameter D_b of the barrel.
4. The method according to claim 2 or 3, wherein the circumferential grooves are formed of a depth so that the corresponding flanges have an outer diameter D_2 where $D_b < D_2 \leq D_g(1+\Delta)$ and where $0.05 \geq \Delta \geq 0$ wherein D_g is a groove diameter of the barrel.

- 15 -

5. The method according to any one of claims 1 - 4, further comprising placing an insert into the mould, the insert having an open end disposed inside the cavity and inboard of the opposite open end, whereby the insert is
5 moulded into said body and defines said cavity.

6. The method according to claim 5, comprising forming said insert of a material having greater hoop strength than the body.

10

7. The method according to claim 5 or 6, wherein placing the insert in the mould comprises placing the insert on the core, and inserting the core into the mould, wherein, the insert is retained in the projectile body when the
15 core is removed from the projectile body.

8. The method according to any one of claims 1 - 7, further comprising sealing the opposite open end with a seal.

20

9. The method according to claim 8, wherein the seal is provided as a primer for initiating deflagration of the propellant.

25

10. The method according to claim 8 or 9, further comprising forming a seat in the cavity for seating the seal.

30

11. The method according to claim 10, wherein forming the seat comprises configuring one or both of the core and the mould in a manner to produce a seat void into which the liquefied material flows to form, upon solidification, the seat.

35

12. The method according to any one of claims 5 - 7, further comprising utilising the open end of the insert as

- 16 -

a seat and sealing the opposite open end of the body by inserting a primer onto said seat.

13. The method according to any one of claims 1 - 12,
5 wherein forming the mould comprises forming the mould from at least two separate parts which can be brought together to produce the casting void, and moved apart to facilitate removal of the projectile body from the mould.

10 14. The method according to claim 13, wherein forming the mould comprises forming the mould with open opposite first and second ends and wherein the placing of the core into the mould comprises inserting the core into the mould from the first end, and introducing the liquefied material
15 comprising pouring the material into the mould from the second end.

15. The method according to claim 4, wherein the forming of one or more circumferential grooves comprises forming
20 two spaced apart circumferential grooves to produce two spaced apart circumferential flanges about the body wherein a first flange is near the closed end and the second flange is near the opposite open end and wherein the second flange has an outer diameter greater than an
25 outer diameter of the first flange.

16. A method of manufacturing a caseless projectile for firing from a small arms weapon the method comprising: providing a mould comprising two portions which when
30 brought together form an interior surface of mould, the portions each provided with at least one semi circular groove the grooves on the portions being aligned to together form a circumferential groove in the internal surface;

35 placing a core in the mould to produce a casting void between the core and the interior surface;

- 17 -

introducing a liquefied solidifiable material into the casing void;

relatively shaping the mould and the core wherein upon removing the core from the mould and opening the mould a projectile body is made from the material, the projectile body having a closed nose at a forward end of the body, an opposite open end and one or more integrally formed circumferential flanges extending about on a outer surface of the body at locations corresponding of the circumferential grooves in the interior surface of the mould.

17. The method according to claim 16, further comprising placing an insert into the mould, the insert having an open end disposed inside the cavity and inboard of the opposite open end, whereby the insert is moulded into said body and defines said cavity.

18. The method according to claim 17, comprising forming said insert of a material having greater hoop strength than the body.

19. The method according to claim 18, wherein placing the insert in the mould comprises placing the insert on the core, and inserting the core into the mould, wherein, the insert is retained in the projectile body when the core is removed from the projectile body.

20. The method according to any one of claims 16 - 19 comprising removing the core by withdrawing the core from the open opposite end of the projectile body.

21. The method according to any one of claims 16 - 19, further comprising sealing the opposite open end with a seal.

- 18 -

22. The method according to any one of claims 16 - 19, further comprising utilising the open end of the insert as a seat and sealing the opposite open end of the body by inserting a primer onto said seat.

5

23. A method of manufacturing a caseless projectile for firing from a barrel of a small arms weapon the method comprising:

forming a mould having an interior surface;

10 placing an insert having an open end on a core and placing the core in the mould to produce a casting void between an exterior surface of the insert and the interior surface;

15 introducing a liquefied solidifiable material into the casting void;

the mould and core being shaped wherein upon removing the core, a projectile body is formed having a closed nose and an opposite open end, with the insert being retained in the projectile body, an interior of the 20 insert forming a cavity which opens onto the opposite open end;

removing the projectile body from the mould; and, depositing a propellant in the insert.

25 24. The method according to claim 23, further comprising forming one or more circumferential grooves in the interior surface of the mould into which the liquefiable material flows, wherein, upon solidification one or more corresponding circumferential flanges are integrally 30 formed about an outside surface of the projectile body.

25. The method according to claim 23 or 24, comprising forming said insert of a material having greater hoop strength than the body.

35

26. The method according to any one of claims 23 - 25, further comprising utilising the open end of the insert as

- 19 -

a seat and sealing the opposite end of the body by inserting a primer onto said seat.

27. The method according to any one of claims 23 - 26,
5 comprising configuring the mould so that a maximum diameter D_1 of the projectile body is less than a bore diameter D_b of the barrel.

28. The method according to claim 27, comprising forming
10 the circumferential grooves of a depth so that the corresponding flanges have an outer diameter D_2 where $D_b < D_2 \leq D_g(1+\Delta)$ and where $0.05 \geq \Delta \geq 0$ wherein D_g is a groove diameter of the barrel.

29. The method according to any one of claims 23 - 28,
15 wherein forming the mould comprises forming the mould from at least two separate portions, each of the portions extending for a length greater than a length of the projectile body and wherein the portions can be brought
20 together to produce the casting void, and moved apart to facilitate removal of the projectile body from the mould.

1 / 6




Fig 1d




Fig 1c




Fig 1b




Fig 1a




Fig 2

3 / 6




Fig 3b








Fig 3a


4 / 6



5 / 6



6 / 6






Fig 1a




Fig 1b




Fig 1c




Fig 1d