

(19) **DANMARK**

(10) **DK/EP 2811173 T3**



Patent- og  
Varemærkestyrelsen

(12) Oversættelse af  
europæisk patentskrift

- 
- (51) Int.Cl.: **F 16 K 37/00 (2006.01)**
- (45) Oversættelsen bekendtgjort den: **2018-10-29**
- (80) Dato for Den Europæiske Patentmyndigheds bekendtgørelse om meddelelse af patentet: **2018-07-25**
- (86) Europæisk ansøgning nr.: **13170449.6**
- (86) Europæisk indleveringsdag: **2013-06-04**
- (87) Den europæiske ansøgnings publiceringsdag: **2014-12-10**
- (84) Designerede stater: **AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR**
- (73) Patenthaver: **DANFOSS POWER SOLUTIONS ApS, Nordborgvej 81, 6430 Nordborg, Danmark**
- (72) Opfinder: **Hjorth, Henrik, Stjerneparken 91, 6300 Gråsten, Danmark**  
**Christensen, Erik, Nørskov 21, 6200 Åbenrå, Danmark**
- (74) Fuldmægtig i Danmark: **Patrade A/S, Ceresbyen 75, 8000 Århus C, Danmark**
- (54) Benævnelse: **HYDRAULISK SYSTEM OG FREMGANGSMÅDE TIL DRIFT AF HUDRAULISK SYSTEM**
- (56) Fremdragne publikationer:  
**EP-A1- 2 570 744**  
**GB-A- 2 271 491**  
**US-A1- 2004 083 278**  
**US-A1- 2006 282 657**



# DESCRIPTION

**[0001]** The present invention relates to a hydraulic system according to claim 1. Furthermore, the invention relates to a method according to claim 4. Prior art examples for such a system and method are known from GB 2 271 491 A. The set of parameters comprises at least one parameter, for example, a maximum flow at the output of the valve, a maximum allowable pressure, a maximum allowable operating speed and so on. In many cases the set of parameters is determined by the consumer connected to the hydraulic valve. The set of parameters may be loaded into the primary memory via the bus.

**[0002]** However, such a procedure is time-consuming and requires special equipment.

**[0003]** The object underlying the invention is to facilitate service work.

**[0004]** This object is solved in a hydraulic system as defined in claim 1.

**[0005]** In this way the group of valves forms a backup system for the parameters for the valves. The set of parameters of each valve is stored in the primary memory of this particular valve. However, when the memory is damaged or the valve has to be replaced, the set of parameter is not lost, but stored in the secondary memory of another valve. Since the other valve is contained in the same group of valves, it is relative simple to download the set of parameters from the secondary memory of the other valve to the primary memory of the specific valve. Each valve comprises an address unique in said group of valves. This address can be used to identify the valve and consequently to identify the primary memory and at least a spare part valve is provided having an address different from all addresses in said group. The spare part valve can therefore be used to replace any similar valve in said group without being fixed to a specific position.

**[0006]** Preferably the valves are electro-hydraulic valves. An electro-hydraulic valve can be controlled by means of electric energy, in other words by means of electrical signals. The set of parameters can easily be transformed into electrical signals thereby performing an operation of the valve which makes it sure that the parameters are taken into account.

**[0007]** Preferably each valve comprises a microcontroller. The microcontroller uses the set of parameters stored in the primary memory during operation of the valve. The microcontroller can get operating demands via the bus. The bus can be a field bus, e.g. a CAN-bus.

**[0008]** The object is solved in a method as defined in claim 4. In this way a set of parameters is stored at least in two different places in the group of valves. Therefore, even if the set of parameters is lost in one location, it can easily be backed up from the other location.

**[0009]** Preferably during a check-phase the primary memory and the secondary memory of each valve are compared with each other. In this way it is possible to check whether the

contents of the primary memory of a specific valve still coincides with the contents of the secondary memory which is physically away from the primary memory since it is positioned in another valve of the group. When there are differences between the primary memory and the secondary memory, appropriate corrections can be made.

**[0010]** In this case it is preferred that a check sum value of a memory area of said primary memory and a check sum value of a memory area of said secondary memory are calculated and compared with each other. The use of a check sum value is a simple means for comparing the primary memory and the secondary memory. Only one value per memory has to be calculated so that the examination can be done without heavy work load.

**[0011]** In a preferred embodiment in case of a defect valve or a replacement of a valve by a spare part valve, said set of parameters is downloaded from said secondary memory of said other valve into the primary memory of said defect valve or of said spare part valve. The term "defect valve" means that the primary memory and the secondary memory have differences. It does not necessarily mean that the valve is defect in a mechanical sense. However, it means that it cannot be guaranteed that the operational behavior is as it should be. In such a case or in a case of a replacement the secondary memory of a valve apart from the defect or of the spare part valve can be used to download the set of parameters so that after the download the specific valve can be used without further service work.

**[0012]** In a preferred embodiment a first valve comprising a secondary memory of another valve examines if the other valve is available on the bus and, if it is not available, however a spare part is available, the primary memory of said spare part valve is updated by the secondary memory of said first valve. The examination can be performed by use of the microcontroller which basically has to use only the address of the valve the set of parameters of which is stored in the secondary memory. If this address is available in the group of valves, for example, via the bus, it can be checked whether the two memories have the same content. If this address is not available, however, a valve with a spare part address is available, the valve group will determine, if one or more valve(s) is/are missing. The missing valve, for example with the lowest address, will be recreated by updating its back-up into the spare part. After updating, the check sum is calculated and controlled by the back-up valve.

**[0013]** Preferably, said check-phase is a start phase. In other words, the check is made during each start of the hydraulic system.

**[0014]** An embodiment of the invention will now be described in more detail with reference to the drawing, wherein:

The only Fig.: is a schematic illustration of a hydraulic system.

**[0015]** A hydraulic system 1 comprises a group of at least two valves, in the present embodiment three valves 2a, 2b, 2c. The valves 2a, 2b, 2c can be connected mechanically, i.e. they can form a valve bloc, however, this is not necessary. They can be of different mechanical construction or they can be of the same mechanical construction. Each valve 2a, 2b, 2c

comprises at least a pressure supply port P, a tank port T and one or more working ports A, B.

**[0016]** Each valve 2a, 2b, 2c comprises a valve element 3a, 3b, 3c in a valve housing 4a, 4b, 4c. The valve element 3a, 3b, 3c can be, for example, a spool or a slide. Each valve element 3a, 3b, 3c can be moved or operated by means of a drive 5a, 5b, 5c. The drive 5a, 5b, 5c is preferably an electro-hydraulic drive, i.e. the energy for moving the valve element 3a, 3b, 3c is provided by a hydraulic fluid under pressure and this pressure is controlled electrically, for example by means of a solenoid. The position of the valve element 3a, 3b, 3c in its valve housing 4a, 4b, 4c determines a flow of hydraulic fluid from the pressure supply port P to one of the working ports A, B and from the other working port B, A to the tank port T. The valves 2a, 2b, 2c may have further ports which are not shown.

**[0017]** Each valve 2a, 2b, 2c comprises a microcontroller 6a, 6b, 6c which is shown to be connected with the drive 5a, 5b, 5c. Furthermore, each valve 2a, 2b, 2c is provided with an address 7a, 7b, 7c. The address 7a, 7b, 7c is shown to be a separate "part". However, it can be part of or stored in a memory of the microcontroller 6a, 6b, 6c.

**[0018]** All valves 2a, 2b, 2c are connected to a bus 8, for example a field bus, such as a CAN bus. Operating commands for actuating the valve 2a, 2b, 2c can be transmitted via the bus 8.

**[0019]** Each valve 2a, 2b, 2c comprises a primary memory 9a, 9b, 9c and a secondary memory 10a, 10b, 10c. The primary memory 9a and the secondary memory 10a of the valve 2a are shown to be physically separated from each other. However, they can be physically combined in a common memory element. The same is true for the primary memories 9b, 9c and the secondary memories 10b, 10c of the other valves 2b, 2c.

**[0020]** The primary memory 9a, 9b, 9c of each valve 2a, 2b, 2c stores a set of parameters for this valve. The set of parameters comprises at least a parameter, however, in most cases the set of parameters comprises more than one parameter. Such a parameter can be the allowable maximum flow, the allowable maximum pressure, the allowable maximum speed of movement of the valve element 3a, 3b, 3c, and so on. The memories 9a, 9b, 9c; 10a, 10b, 10c are non-volatile memories (EEPROM). The set of parameters can be used for control and set-up of each specific valve.

**[0021]** The set of parameters for the valve 2a is not only available in the primary memory 9a in this valve 2a. However, it is available as well in a secondary memory 10b of another valve 2b. In the same way, the set of parameters of the valve 2b is not only available in the primary memory 9b of this valve, but also in the secondary memory 10c of another valve 2c. The set-up parameter of the valve 2c is available in the primary memory 9c of this valve 2c and additionally in the secondary memory 10a of the valve 2a.

**[0022]** Consequently, when new parameters are downloaded to a valve, the parameters must be stored in both the memory of the valve and in the memory of a different valve. When parameters are downloaded for the valve 2a, they are stored in the primary memory 9a of this

valve 2a and in the secondary memory 10b of the other valve 2b.

**[0023]** During each start of the hydraulic system or of the groups of valves 2a, 2b, 2c, the so called "back-up valve" will examine, if the valve, for which it comprises a secondary memory, is available on the field bus 8. In other words, the back-up valve is the valve comprising the secondary memory 10b, 10c, 10a for another valve 2a, 2b, 2c. If this other valve 2a, 2b, 2c is available on the bus 8, both the valves 2a, 2b, 2c and the back-up valves 2b, 2c, 2a calculate a check sum value of the memory area of the primary memory 9a, 9b, 9c and of the secondary memory 10b, 10c, 10a. The back-up valve 2b, 2c, 2a send the check sum of the secondary memory 10b, 10c, 10a to the primary valve 2a, 2b, 2c. If the check sum values of equal, the valves 2a, 2b, 2c will continue the starting procedure. If the check sum values are not equal, the primary valves 2a, 2b, 2c must updated its parameters into the back-up valves 2b, 2c, 2a, so that all values are equal. Another possibility would be that the primary memory 9a, 9b, 9c is updated by the contents of the secondary memory 10b, 10c, 10a.

**[0024]** If the check sum values of the primary memory and the secondary memory are different, the valve is deemed to be a "defect valve". However, in many cases, this "defect" can be removed by updating the primary memory 9a, 9b, 9c.

**[0025]** In some cases it is necessary to replace a valve, for example, if the valve shows a mechanical defect.

**[0026]** It is assumed that the valve 2c has been replaced by a spare part valve. Therefore, the address 7c of the valve 2c has changed.

**[0027]** During each start of the valve group of the valves 2a, 2b and the replaced valve 2c, the back-up valve (in this case valve 2a) will examine if the valve 2c, for which it comprises a secondary memory 10a is available on the bus 8. If it is not available, however, a valve with a spare part address is available, the valve group will determine, if one or more valve(s) is/are missing. The missing valve 2c with the lowest address will be recreated by updating its back-up into the spare part 2c. After updating, the check sum is calculated and controlled by the back-up valve 2a.

**[0028]** By adding a new spare part valve and make a new start, this procedure can be repeated.

**[0029]** When all required valves have been updated, the valve group will function correctly after the next start.

**[0030]** A hydraulic consumer 11a, 11b, 11c is connected to each of the valves 2a, 2b, 2c shown. The consumer 11a, 11b, 11c could be a hydraulic cylinder, for example for controlling the scoop of a backhoe.

**[0031]** The valves 2a, 2b, 2c shown are usually joined in groups, which are connected to a

supply, for example from a pump, and to a tank. The input for the valve group often consists of a so called end module, to which also the supply is connected. The end module can also have a built-in microcontroller with memory etc. In this end module it could be imagined to store all parameters for the whole group, so that they were all gathered in one place. In this situation it could be imagined that the module coming right after the end module could contain a backup of the parameters for all valves in the group and that this backup could be used, if, for some reason the end module had to be replaced.

**[0032]** Usually, the CAN bus will have a connection to a central controller, and it can thus be imagined that, if the vehicle has several valve groups, the central controller can collect all parameters for all groups, so that whole groups can be replaced without problems.

**[0033]** Usually, the valves 2a, 2b, 2c shown will also have some sort of built-in transducer that measures the deflection of the valve slide (for example an LVDT transducer), and this/these parameter(s) can also be stored in the memory.

## **REFERENCES CITED IN THE DESCRIPTION**

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

### **Patent documents cited in the description**

- GB2271491A **[0001]**

**PATENTKRAV**

1. Et hydraulisk system (1) omfattende en gruppe af mindst to ventiler (2a, 2b, 2c) forbundet til en samleskinne (8), hver af nævnte ventiler (2a, 2b, 2c) omfatter et ventilhus (4a, 4b, 4c), et ventilelement (3a, 3b, 3c) og en primær hukommelse (9a, 9b, 9c) til lagring af et sæt af parametre af ventilen (2a, 2b, 2c), hvor hver ventil (2a, 2b, 2c) omfatter mindst en trykforsyningsport (P), en tankport (T), en eller flere arbejdsporte (A, B) og en sekundær hukommelse (10a, 10b, 10c) til lagring af nævnte sæt af parametre af en forskellig ventil (2a, 2b, 2c) af nævnte gruppe, hvor positionen af ventilelementet (3a, 3b, 3c) i dets ventilhus (4a, 4b, 4c) bestemmer en strøm af hydraulikvæske fra trykforsyningsporten (P) til en af arbejdsportene (A, B) og fra den anden arbejdsport (B, A) til tankporten, hvor hver ventil (2a, 2b, 2c) omfatter en unik adresse (7a, 7b, 7c) i nævnte gruppe af ventiler og der findes mindst en reservedelsventil med en adresse forskellig fra alle adresserne (7a, 7b, 7c) i nævnte gruppe.
2. Hydraulisk system ifølge krav 1, **kendetegnet ved**, at ventilerne (2a, 2b, 2c) er elektrohydrauliske ventiler.
3. Hydraulisk system ifølge krav 1 eller 2, **kendetegnet ved**, at hver ventil (2a, 2b, 2c) omfatter en mikrocontroller (6a, 6b, 6c).
4. En fremgangsmåde til drift af et hydraulisk system omfattende en gruppe af mindst to ventiler (2a, 2b, 2c) forbundet til en samleskinne (8), hvor hver ventil (2a, 2b, 2c) omfatter et ventilhus (4a, 4b, 4c), et ventilelement (3a, 3b, 3c) og en primær hukommelse (9a, 9b, 9c) til lagring af et sæt af parametre for ventilen, hvor hver ventil (2a, 2b, 2c) omfatter mindst en trykforsyningsport (P), en tankport (T), en eller flere arbejdsporte (A, B) og nævnte sæt af parametre er lagret i en sekundær hukommelse (10a, 10b, 10c) af en anden ventil (2a, 2b, 2c) af nævnte gruppe, hvor positionen af ventilelementet (3a, 3b, 3c) i dets ventilhus (4a, 4b, 4c) bestemmer en strøm af hydraulikvæske fra trykforsyningsporten (P) til en af arbejdsportene (A, B) og fra den anden arbejdsport (B, A) til tankporten, hvor hver ventil (2a, 2b, 2c) omfatter en unik adresse (7a, 7b, 7c) i nævnte gruppe af ventiler og der findes mindst en reservedelsventil med en adresse forskellig fra alle adresserne (7a, 7b, 7c) i nævnte gruppe.

5. Fremgangsmåden ifølge krav 4, **kendetegnet ved**, at den primære hukommelse (9a, 9b, 9c) og den sekundære hukommelse (10a, 10b, 10c) under en kontrolfase sammenlignes med hinanden.
- 5      6. Fremgangsmåden ifølge krav 5, **kendetegnet ved**, at en kontrolsumværdi af et hukommelsesområde af nævnte primære hukommelse (9a, 9b, 9c) og en kontrolsumværdi af et hukommelsesområde af den sekundære hukommelse (10a, 10b, 10c) er beregnet og sammenlignet med hinanden.
- 10     7. Fremgangsmåden ifølge ethvert af kravene 4-6, **kendetegnet ved**, at i tilfælde af en defekt ventil eller en udskiftning af en ventil med en reservedelsventil, nævnte sæt af parametre hentes fra nævnte sekundære hukommelse (10a, 10b, 10c) af nævnte anden ventil ind i den primære hukommelse (9a, 9b, 9c) af nævnte defekte ventil eller af nævnte reservedelsventil.
- 15     8. Fremgangsmåden ifølge kravene 6 til 7, **kendetegnet ved**, at en første ventil omfattende en sekundær hukommelse (10a, 10b, 10c) af en anden ventil undersøger om en anden ventil er til rådighed på samleskinen (8) og, hvis den ikke er tilgængelig, men en reservedelsventil er til rådighed opdateres den primære hukommelse (9a, 9b, 9c) af
- 20     nævnte reservedelsventil af den sekundære hukommelse (10a, 10b, 10c) af nævnte første ventil.
9. Fremgangsmåden ifølge ethvert af kravene 5-8, **kendetegnet ved**, at nævnte kontrolfase er en startfase.

## DRAWINGS

