



(51) International Patent Classification:			15/908,057	28 February 2018 (28.02.2018)	US
<i>A61B 17/29</i> (2006.01) <i>A61B 90/00</i> (2016.01)			15/908,143	28 February 2018 (28.02.2018)	US
<i>A61B 17/00</i> (2006.01) <i>A61B 17/128</i> (2006.01)			15/908,040	28 February 2018 (28.02.2018)	US
<i>A61B 17/122</i> (2006.01) <i>A61B 18/14</i> (2006.01)			15/908,012	28 February 2018 (28.02.2018)	US
			15/908,058	28 February 2018 (28.02.2018)	US
(21) International Application Number:					
PCT/US2018/057238			62/649,327	28 March 2018 (28.03.2018)	US
			62/649,302	28 March 2018 (28.03.2018)	US
(22) International Filing Date:			62/649,310	28 March 2018 (28.03.2018)	US
24 October 2018 (24.10.2018)			62/649,296	28 March 2018 (28.03.2018)	US
(25) Filing Language:			62/649,309	28 March 2018 (28.03.2018)	US
English			62/649,333	28 March 2018 (28.03.2018)	US
(26) Publication Language:			62/649,291	28 March 2018 (28.03.2018)	US
English			62/649,294	28 March 2018 (28.03.2018)	US
(30) Priority Data:			62/649,300	28 March 2018 (28.03.2018)	US
62/578,844	30 October 2017 (30.10.2017)	US	62/649,307	28 March 2018 (28.03.2018)	US
62/578,835	30 October 2017 (30.10.2017)	US	62/649,313	28 March 2018 (28.03.2018)	US
62/578,855	30 October 2017 (30.10.2017)	US	62/649,315	28 March 2018 (28.03.2018)	US
62/578,793	30 October 2017 (30.10.2017)	US	62/649,320	28 March 2018 (28.03.2018)	US
62/578,804	30 October 2017 (30.10.2017)	US	62/649,323	28 March 2018 (28.03.2018)	US
62/578,817	30 October 2017 (30.10.2017)	US	62/659,900	19 April 2018 (19.04.2018)	US
62/611,341	28 December 2017 (28.12.2017)	US	62/665,128	01 May 2018 (01.05.2018)	US
62/611,339	28 December 2017 (28.12.2017)	US	62/665,134	01 May 2018 (01.05.2018)	US
62/611,340	28 December 2017 (28.12.2017)	US	62/665,139	01 May 2018 (01.05.2018)	US
15/908,021	28 February 2018 (28.02.2018)	US	62/665,129	01 May 2018 (01.05.2018)	US

(54) Title: SURGICAL INSTRUMENT SYSTEMS COMPRISING BATTERY ARRANGEMENTS




FIG. 65

(57) Abstract: A surgical instrument system comprising a handle, a shaft, and a disposable power module is disclosed. The handle comprises a motor, a control switch, and a motor-control processor which is in communication with the control switch. In various instances, the disposable power module comprises a disposable battery and a display unit configured to indicate at least one function of the surgical instrument system.

62/665,192	01 May 2018 (01.05.2018)	US
62/665,177	01 May 2018 (01.05.2018)	US
16/112,097	24 August 2018 (24.08.2018)	US

(71) **Applicant: ETHICON LLC** [US/US]; #475 Street C, Suite 401, Los Frailes Industrial Park, Guaynabo, PR 00969 (US).

(72) **Inventor: SHELTON, Frederick E., IV**; 4545 Creek Road, Cincinnati, OH 45242 (US).

(74) **Agent: GEISLER, Brian T.** et al.; K&L Gate LLP, 210 Sixth Avenue, Pittsburgh, PA 15222-2613 (US).

(81) **Designated States** (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*
- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*

Published:

- *with international search report (Art. 21(3))*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

TITLE

5 SURGICAL INSTRUMENT SYSTEMS COMPRISING BATTERY ARRANGEMENTS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Non-Provisional Patent Application Serial No. 16/112,097, entitled SURGICAL INSTRUMENT SYSTEMS COMPRISING BATTERY
10 ARRANGEMENTS, filed August 24, 2018, the disclosure of which is incorporated by reference herein in its entirety. This application claims the benefit of U.S. Provisional Patent Application Serial No. 62/659,900, entitled METHOD OF HUB COMMUNICATION, filed April 19, 2018, the disclosure of which is incorporated by reference herein in its entirety. This application claims the benefit of U.S. Provisional Patent Application Serial No. 62/665,128,
15 entitled MODULAR SURGICAL INSTRUMENTS, filed May 1, 2018, of U.S. Provisional Patent Application Serial No. 62/665,129, entitled SURGICAL SUTURING SYSTEMS, filed May 1, 2018, of U.S. Provisional Patent Application Serial No. 62/665,134, entitled SURGICAL CLIP APPLIER, filed May 1, 2018, of U.S. Provisional Patent Application Serial No. 62/665,139, entitled SURGICAL INSTRUMENTS COMPRISING CONTROL SYSTEMS,
20 filed May 1, 2018, of U.S. Provisional Patent Application Serial No. 62/665,177, entitled SURGICAL INSTRUMENTS COMPRISING HANDLE ARRANGEMENTS, filed May 1, 2018, and of U.S. Provisional Patent Application Serial No. 62/665,192, entitled SURGICAL DISSECTORS, filed May 1, 2018, the disclosures of which are incorporated by reference herein in their entireties. This application claims the benefit of U.S. Provisional Patent
25 Application Serial No. 62/649,291, entitled USE OF LASER LIGHT AND RED-GREEN-BLUE COLORATION TO DETERMINE PROPERTIES OF BACK SCATTERED LIGHT, filed March 28, 2018, of U.S. Provisional Patent Application Serial No. 62/649,294, entitled DATA STRIPPING METHOD TO INTERROGATE PATIENT RECORDS AND CREATE ANONYMIZED RECORD, filed March 28, 2018, of U.S. Provisional Patent Application Serial
30 No. 62/649,296, entitled ADAPTIVE CONTROL PROGRAM UPDATES FOR SURGICAL DEVICES, filed March 28, 2018, of U.S. Provisional Patent Application Serial No. 62/649,300, entitled SURGICAL HUB SITUATIONAL AWARENESS, filed March 28, 2018, of U.S. Provisional Patent Application Serial No. 62/649,302, entitled INTERACTIVE SURGICAL SYSTEMS WITH ENCRYPTED COMMUNICATION CAPABILITIES, filed March
35 28, 2018, of U.S. Provisional Patent Application Serial No. 62/649,307, entitled AUTOMATIC TOOL ADJUSTMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS, filed March 28, 2018, of U.S. Provisional Patent Application Serial No. 62/649,309, entitled SURGICAL HUB

SPATIAL AWARENESS TO DETERMINE DEVICES IN OPERATING THEATER, filed March 28, 2018, of U.S. Provisional Patent Application Serial No. 62/649,310, entitled COMPUTER IMPLEMENTED INTERACTIVE SURGICAL SYSTEMS, filed March 28, 2018, of U.S. Provisional Patent Application Serial No. 62/649,313, entitled CLOUD INTERFACE FOR COUPLED SURGICAL DEVICES, filed March 28, 2018, of U.S. Provisional Patent Application Serial No. 62/649,315, entitled DATA HANDLING AND PRIORITIZATION IN A CLOUD ANALYTICS NETWORK, filed March 28, 2018, of U.S. Provisional Patent Application Serial No. 62/649,320, entitled DRIVE ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS, filed March 28, 2018, of U.S. Provisional Patent Application Serial No. 62/649,323, entitled SENSING ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS, filed March 28, 2018, of U.S. Provisional Patent Application Serial No. 62/649,327, entitled CLOUD-BASED MEDICAL ANALYTICS FOR SECURITY AND AUTHENTICATION TRENDS AND REACTIVE MEASURES, filed March 28, 2018, and of U.S. Provisional Patent Application Serial No. 62/649,333, entitled CLOUD-BASED MEDICAL ANALYTICS FOR CUSTOMIZATION AND RECOMMENDATIONS TO A USER, filed March 28, 2018, the disclosures of which are incorporated by reference herein in their entireties. This application claims the benefit of U.S. Non-Provisional Patent Application Serial No. 15/908,012, entitled SURGICAL INSTRUMENT HAVING DUAL ROTATABLE MEMBERS TO EFFECT DIFFERENT TYPES OF END EFFECTOR MOVEMENT, filed February 28, 2018, of U.S. Non-Provisional Patent Application Serial No. 15/908,021, entitled SURGICAL INSTRUMENT WITH REMOTE RELEASE, filed February 28, 2018, of U.S. Non-Provisional Patent Application Serial No. 15/908,040, entitled SURGICAL INSTRUMENT WITH ROTARY DRIVE SELECTIVELY ACTUATING MULTIPLE END EFFECTOR FUNCTIONS, filed February 28, 2018, of U.S. Non-Provisional Patent Application Serial No. 15/908,057, entitled SURGICAL INSTRUMENT WITH ROTARY DRIVE SELECTIVELY ACTUATING MULTIPLE END EFFECTOR FUNCTIONS, filed February 28, 2018, of U.S. Non-Provisional Patent Application Serial No. 15/908,058, entitled SURGICAL INSTRUMENT WITH MODULAR POWER SOURCES, filed February 28, 2018, and of U.S. Non-Provisional Patent Application Serial No. 15/908,143, entitled SURGICAL INSTRUMENT WITH SENSOR AND/OR CONTROL SYSTEMS, filed February 28, 2018, the disclosures of which are incorporated by reference herein in their entireties. This application claims the benefit of U.S. Provisional Patent Application Serial No. 62/611,339, entitled ROBOT ASSISTED SURGICAL PLATFORM, filed December 28, 2017, of U.S. Provisional Patent Application Serial No. 62/611,340, entitled CLOUD-BASED MEDICAL ANALYTICS, filed December 28, 2017, and of U.S. Provisional Patent Application Serial No. 62/611,341, entitled INTERACTIVE SURGICAL PLATFORM, filed December 28, 2017, the disclosures of which are incorporated by reference herein in their entireties. This

application claims the benefit of U.S. Provisional Patent Application Serial No. 62/578,793, entitled SURGICAL INSTRUMENT WITH REMOTE RELEASE, filed October 30, 2017, of U.S. Provisional Patent Application Serial No. 62/578,804, entitled SURGICAL INSTRUMENT HAVING DUAL ROTATABLE MEMBERS TO EFFECT DIFFERENT TYPES OF END EFFECTOR MOVEMENT, filed October 30, 2017, of U.S. Provisional Patent Application Serial No. 62/578,817, entitled SURGICAL INSTRUMENT WITH ROTARY DRIVE SELECTIVELY ACTUATING MULTIPLE END EFFECTOR FUNCTIONS, filed October 30, 2017, of U.S. Provisional Patent Application Serial No. 62/578,835, entitled SURGICAL INSTRUMENT WITH ROTARY DRIVE SELECTIVELY ACTUATING MULTIPLE END EFFECTOR FUNCTIONS, filed October 30, 2017, of U.S. Provisional Patent Application Serial No. 62/578,844, entitled SURGICAL INSTRUMENT WITH MODULAR POWER SOURCES, filed October 30, 2017, and of U.S. Provisional Patent Application Serial No. 62/578,855, entitled SURGICAL INSTRUMENT WITH SENSOR AND/OR CONTROL SYSTEMS, filed October 30, 2017, the disclosures of which are incorporated by reference herein in their entireties.

BACKGROUND

[0002] The present invention relates to surgical systems and, in various arrangements, to grasping instruments that are designed to grasp the tissue of a patient, dissecting instruments configured to manipulate the tissue of a patient, clip appliers configured to clip the tissue of a patient, and suturing instruments configured to suture the tissue of a patient, among others.

BRIEF DESCRIPTION OF THE DRAWINGS

[0003] Various features of the embodiments described herein, together with advantages thereof, may be understood in accordance with the following description taken in conjunction with the accompanying drawings as follows:

[0004] FIG. 1 illustrates a surgical system comprising a handle and several shaft assemblies - each of which are selectively attachable to the handle in accordance with at least one embodiment;

[0005] FIG. 2 is an elevational view of the handle and one of the shaft assemblies of the surgical system of FIG. 1;

[0006] FIG. 3 is a partial cross-sectional perspective view of the shaft assembly of FIG. 2;

[0007] FIG. 4 is another partial cross-sectional perspective view of the shaft assembly of FIG. 2;

[0008] FIG. 5 is a partial exploded view of the shaft assembly of FIG. 2;

[0009] FIG. 6 is a partial cross-sectional elevational view of the shaft assembly of FIG. 2;

[0010] FIG. 7 is an elevational view of a drive module of the handle of FIG. 1;

- [0011] FIG. 8 is a cross-sectional perspective view of the drive module of FIG. 7;
- [0012] FIG. 9 is an end view of the drive module of FIG. 7;
- [0013] FIG. 10 is a partial cross-sectional view of the interconnection between the handle and shaft assembly of FIG. 2 in a locked configuration;
- 5 [0014] FIG. 11 is a partial cross-sectional view of the interconnection between the handle and shaft assembly of FIG. 2 in an unlocked configuration;
- [0015] FIG. 12 is a cross-sectional perspective view of a motor and a speed reduction gear assembly of the drive module of FIG. 7;
- [0016] FIG. 13 is an end view of the speed reduction gear assembly of FIG. 12;
- 10 [0017] FIG. 14 is a partial perspective view of an end effector of the shaft assembly of FIG. 2 in an open configuration;
- [0018] FIG. 15 is a partial perspective view of the end effector of FIG. 14 in a closed configuration;
- [0019] FIG. 16 is a partial perspective view of the end effector of FIG. 14 articulated in a first direction;
- 15 [0020] FIG. 17 is a partial perspective view of the end effector of FIG. 14 articulated in a second direction;
- [0021] FIG. 18 is a partial perspective view of the end effector of FIG. 14 rotated in a first direction;
- 20 [0022] FIG. 19 is a partial perspective view of the end effector of FIG. 14 rotated in a second direction;
- [0023] FIG. 20 is a partial cross-sectional perspective view of the end effector of FIG. 14 detached from the shaft assembly of FIG. 2;
- [0024] FIG. 21 is an exploded view of the end effector of FIG. 14 illustrated with some components removed;
- 25 [0025] FIG. 22 is an exploded view of a distal attachment portion of the shaft assembly of FIG. 2;
- [0026] FIG. 22A is an exploded view of the distal portion of the shaft assembly of FIG. 2 illustrated with some components removed;
- 30 [0027] FIG. 23 is another partial cross-sectional perspective view of the end effector of FIG. 14 detached from the shaft assembly of FIG. 2;
- [0028] FIG. 24 is a partial cross-sectional perspective view of the end effector of FIG. 14 attached to the shaft assembly of FIG. 2;
- [0029] FIG. 25 is a partial cross-sectional perspective view of the end effector of FIG. 14 attached to the shaft assembly of FIG. 2;
- 35 [0030] FIG. 26 is another partial cross-sectional perspective view of the end effector of FIG. 14 attached to the shaft assembly of FIG. 2;

- [0031] FIG. 27 is a partial cross-sectional view of the end effector of FIG. 14 attached to the shaft assembly of FIG. 2 depicting a first, second, and third clutch of the end effector;
- [0032] FIG. 28 depicts the first clutch of FIG. 27 in an unactuated condition;
- [0033] FIG. 29 depicts the first clutch of FIG. 27 in an actuated condition;
- 5 [0034] FIG. 30 depicts the second clutch of FIG. 27 in an unactuated condition;
- [0035] FIG. 31 depicts the second clutch of FIG. 27 in an actuated condition;
- [0036] FIG. 32 depicts the third clutch of FIG. 27 in an unactuated condition;
- [0037] FIG. 33 depicts the third clutch of FIG. 27 in an actuated condition;
- [0038] FIG. 34 depicts the second and third clutches of FIG. 27 in their unactuated
- 10 conditions and the end effector of FIG. 14 locked to the shaft assembly of FIG. 2;
- [0039] FIG. 35 depicts the second clutch of FIG. 27 in its unactuated condition and the third clutch of FIG. 27 in its actuated condition;
- [0040] FIG. 36 depicts the second and third clutches of FIG. 27 in their actuated conditions and the end effector of FIG. 14 unlocked from the shaft assembly of FIG. 2;
- 15 [0041] FIG. 37 is a partial cross-sectional view of a shaft assembly in accordance with at least one alternative embodiment comprising sensors configured to detect the conditions of the first, second, and third clutches of FIG. 27;
- [0042] FIG. 38 is a partial cross-sectional view of a shaft assembly in accordance with at least one alternative embodiment comprising sensors configured to detect the conditions of
- 20 the first, second, and third clutches of FIG. 27;
- [0043] FIG. 39 depicts the first and second clutches of FIG. 38 in their unactuated conditions and a sensor in accordance with at least one alternative embodiment;
- [0044] FIG. 40 depicts the second and third clutches of FIG. 38 in their unactuated conditions and a sensor in accordance with at least one alternative embodiment;
- 25 [0045] FIG. 41 is a partial cross-sectional view of a shaft assembly in accordance with at least one embodiment;
- [0046] FIG. 42 is a partial cross-sectional view of the shaft assembly of FIG. 41 comprising a clutch illustrated in an unactuated condition;
- [0047] FIG. 43 is a partial cross-sectional view of the shaft assembly of FIG. 41 illustrating
- 30 the clutch in an actuated condition;
- [0048] FIG. 44 is a partial cross-sectional view of a shaft assembly in accordance with at least one embodiment comprising first and second clutches illustrated in an unactuated condition;
- [0049] FIG. 45 is a perspective view of the handle drive module of FIG. 7 and one of the
- 35 shaft assemblies of the surgical system of FIG. 1;
- [0050] FIG. 46 is another perspective view of the handle drive module of FIG. 7 and the shaft assembly of FIG. 45;

- [0051] FIG. 47 is a partial cross-sectional view of the shaft assembly of FIG. 45 attached to the handle of FIG. 1;
- [0052] FIG. 48 is another partial cross-sectional view of the shaft assembly of FIG. 45 attached to the handle of FIG. 1;
- 5 [0053] FIG. 49 is a partial cross-sectional perspective view of the shaft assembly of FIG. 45;
- [0054] FIG. 50 is a schematic of the control system of the surgical system of FIG. 1.
- [0055] FIG. 51 is an elevational view of a handle in accordance with at least one embodiment and one of the shaft assemblies of the surgical system of FIG. 1;
- 10 [0056] FIG. 52A is a partial top view of a drive module of the handle of FIG. 51 illustrated in a first rotation configuration;
- [0057] FIG. 52B is a partial top view of the drive module of FIG. 52A illustrated in a second rotation configuration;
- [0058] FIG. 53A is a partial top view of the drive module of FIG. 52A illustrated in a first articulation configuration;
- 15 [0059] FIG. 53B is a partial top view of the drive module of FIG. 52A illustrated in a second articulation configuration;
- [0060] FIG. 54 is a partial cross-sectional perspective view of a drive module in accordance with at least one embodiment;
- 20 [0061] FIG. 55 is a partial perspective view of the drive module of FIG. 54 illustrated with some components removed;
- [0062] FIG. 56 is a partial cross-sectional view of the drive module of FIG. 54 illustrating an eccentric drive in a disengaged condition; and
- [0063] FIG. 57 is a partial cross-sectional view of the drive module of FIG. 54 illustrating the eccentric drive of FIG. 56 in an engaged condition.
- 25 [0064] FIG. 58 illustrates a surgical instrument system comprising a handle and several shaft assemblies - each of which are selectively attachable to the handle in accordance with at least one embodiment;
- [0065] FIG. 59 is an elevational view of the handle and one of the shaft assemblies of the surgical instrument system of FIG. 58;
- 30 [0066] FIG. 60 is an elevational view of a drive module of the handle of FIG. 58;
- [0067] FIG. 61 is a cross-sectional perspective view of the drive module of FIG. 60;
- [0068] FIG. 62 is an end view of the drive module of FIG. 60;
- [0069] FIG. 63 is a perspective view of the handle drive module of FIG. 60 and one of the shaft assemblies of the surgical instrument system of FIG. 58;
- 35 [0070] FIG. 64 is another perspective view of the handle drive module of FIG. 58 and the shaft assembly of FIG. 63;

- [0071] FIG. 65 is a partial cross-sectional perspective view of a handle drive module in accordance with at least one embodiment;
- [0072] FIG. 66 illustrates a surgical instrument system comprising several handle assemblies and a shaft assembly selectively attachable to the handle assemblies in accordance with at least one embodiment;
- 5 [0073] FIG. 66A is an elevational view of a handle assembly of FIG. 66 in accordance with at least one embodiment;
- [0074] FIG. 66B is an elevational view of a handle assembly of FIG. 66 in accordance with at least one embodiment;
- 10 [0075] FIG. 66C is an elevational view of a handle assembly of FIG. 66 in accordance with at least one embodiment;
- [0076] FIG. 66D is an elevational view of a handle assembly and the shaft assembly of FIG. 66 in accordance with at least one embodiment;
- [0077] FIG. 66E is an elevational view of the handle assembly of FIG. 66B attached to the shaft assembly of FIG. 66 in accordance with at least one embodiment;
- 15 [0078] FIG. 66F is an elevational view of the handle assembly of FIG. 66B and the shaft assembly of FIG. 66 in accordance with at least one embodiment;
- [0079] FIG. 66G is an elevational view of the handle assembly of FIG. 66C and the shaft assembly of FIG. 66 in accordance with at least one embodiment;
- 20 [0080] FIG. 67 is a perspective view of the shaft assembly of FIG. 66;
- [0081] FIG. 68A is a proximal end view of the handle assembly of FIG. 66A;
- [0082] FIG. 68B is a proximal end view of the handle assembly of FIG. 66B;
- [0083] FIG. 68C is a proximal end view of the handle assembly of FIG. 66C;
- [0084] FIG. 68D is a proximal end view of the shaft assembly of FIG. 66D;
- 25 [0085] FIG. 69 illustrates a chart depicting various functions of the surgical instrument system of FIG. 66;
- [0086] FIG. 70 is an exploded view of one of the handle assemblies and the shaft assembly of FIG. 66;
- [0087] FIG. 71 depicts various aspects of the handle assembly of FIG. 70;
- 30 [0088] FIG. 72 is an exploded view of the handle assembly of FIG. 66B and the shaft assembly of FIG. 66;
- [0089] FIG. 73 depicts various aspects of the handle assembly of FIG. 72;
- [0090] FIG. 73A is a proximal end view of the handle assembly of FIG. 72;
- [0091] FIG. 73B illustrates a chart depicting various functions of the handle assembly of FIG. 72;
- 35 [0092] FIG. 74 is a partial exploded view the handle assembly of FIG. 66A and the shaft assembly of FIG. 66;

- [0093] FIG. 75 depicts various aspects of the handle assembly of FIG. 74;
- [0094] FIG. 75A is a proximal end view of the handle assembly of FIG. 74;
- [0095] FIG. 75B illustrates a chart depicting various functions of the handle assembly of FIG. 74;
- 5 [0096] FIG. 76 illustrates a shaft assembly in accordance with at least one embodiment;
- [0097] FIG. 76A is a block diagram illustrating the electrical connections of a surgical instrument system in accordance with at least one embodiment;
- [0098] FIG. 77 illustrates a surgical system comprising a handle and a shaft assembly in accordance with at least one embodiment;
- 10 [0099] FIG. 77A is a perspective view of the handle assembly of FIG. 77;
- [0100] FIG. 77B is a cut-away view of a curved cylinder of the handle assembly of FIG. 77;
- [0101] FIG. 78A is a partial cross-sectional view of the curved cylinder of FIG. 77A illustrating an electroactive polymer located in the cylinder in a non-energized state;
- [0102] FIG. 78B is a partial cross-sectional view of the curved cylinder of FIG. 77A illustrating the electroactive polymer located in the cylinder in an energized state;
- 15 [0103] FIG. 79 is a block diagram illustrating various aspects of the handle and shaft assembly of FIG. 77 in accordance with at least one embodiment;
- [0104] FIG. 80 is a graph illustrating the relationship between the forces experienced by an end effector and shaft of the surgical system of FIG. 77 and the voltage applied to the electroactive polymer over time;
- 20 [0105] FIG. 81 is a graph illustrating the compressive force applied by the electroactive polymer over time;
- [0106] FIG. 82 illustrates a surgical system comprising a handle and a shaft assembly in accordance with at least one embodiment;
- 25 [0107] FIG. 83 is a partial perspective view of the shaft assembly of FIG. 82 comprising a locking mechanism;
- [0108] FIG. 84 is a perspective view of the locking mechanism of FIG. 83 in an unlocked configuration;
- [0109] FIG. 85 is a perspective view of the locking mechanism of FIG. 83 in a locked configuration;
- 30 [0110] FIGS. 85A-85C illustrate the locking mechanism of FIG. 83 in three different states during the operation of the surgical instrument system;
- [0111] FIG. 86 is a partial perspective view of a distal attachment portion selectively attachable to the surgical system of FIG. 82;
- 35 [0112] FIG. 87 is a graph illustrating possible drive force curves of the distal attachment portion of FIG. 86; and

[0113] FIG. 88 is a flow chart illustrating a start-up process of a surgical instrument system in accordance with at least one embodiment.

[0114] Corresponding reference characters indicate corresponding parts throughout the several views. The exemplifications set out herein illustrate various embodiments of the invention, in one form, and such exemplifications are not to be construed as limiting the scope of the invention in any manner.

DETAILED DESCRIPTION

[0115] Applicant of the present application owns the following U.S. Patent Applications that were filed on August 24, 2018 and which are each herein incorporated by reference in their respective entireties:

- U.S. Patent Application Serial No. 16/112,129, entitled SURGICAL SUTURING INSTRUMENT CONFIGURED TO MANIPULATE TISSUE USING MECHANICAL AND ELECTRICAL POWER;
- U.S. Patent Application Serial No. 16/112,155, entitled SURGICAL SUTURING INSTRUMENT COMPRISING A CAPTURE WIDTH WHICH IS LARGER THAN TROCAR DIAMETER;
- U.S. Patent Application Serial No. 16/112,168, entitled SURGICAL SUTURING INSTRUMENT COMPRISING A NON-CIRCULAR NEEDLE;
- U.S. Patent Application Serial No. 16/112,180, entitled ELECTRICAL POWER OUTPUT CONTROL BASED ON MECHANICAL FORCES;
- U.S. Patent Application Serial No. 16/112,193, entitled REACTIVE ALGORITHM FOR SURGICAL SYSTEM;
- U.S. Patent Application Serial No. 16/112,099, entitled SURGICAL INSTRUMENT COMPRISING AN ADAPTIVE ELECTRICAL SYSTEM;
- U.S. Patent Application Serial No. 16/112,112, entitled CONTROL SYSTEM ARRANGEMENTS FOR A MODULAR SURGICAL INSTRUMENT;
- U.S. Patent Application Serial No. 16/112,119, entitled ADAPTIVE CONTROL PROGRAMS FOR A SURGICAL SYSTEM COMPRISING MORE THAN ONE TYPE OF CARTRIDGE;
- U.S. Patent Application Serial No. 16/112,109, entitled SURGICAL INSTRUMENT SYSTEMS COMPRISING HANDLE ARRANGEMENTS;
- U.S. Patent Application Serial No. 16/112,114, entitled SURGICAL INSTRUMENT SYSTEMS COMPRISING FEEDBACK MECHANISMS;
- U.S. Patent Application Serial No. 16/112,117, entitled SURGICAL INSTRUMENT SYSTEMS COMPRISING LOCKOUT MECHANISMS;

- U.S. Patent Application Serial No. 16/112,095, entitled SURGICAL INSTRUMENTS COMPRISING A LOCKABLE END EFFECTOR SOCKET;
 - U.S. Patent Application Serial No. 16/112,121, entitled SURGICAL INSTRUMENTS COMPRISING A SHIFTING MECHANISM;
 - 5 - U.S. Patent Application Serial No. 16/112,151, entitled SURGICAL INSTRUMENTS COMPRISING A SYSTEM FOR ARTICULATION AND ROTATION COMPENSATION;
 - U.S. Patent Application Serial No. 16/112,154, entitled SURGICAL INSTRUMENTS COMPRISING A BIASED SHIFTING MECHANISM;
 - U.S. Patent Application Serial No. 16/112,226, entitled SURGICAL INSTRUMENTS
 - 10 COMPRISING AN ARTICULATION DRIVE THAT PROVIDES FOR HIGH ARTICULATION ANGLES;
 - U.S. Patent Application Serial No. 16/112,062, entitled SURGICAL DISSECTORS AND MANUFACTURING TECHNIQUES;
 - U.S. Patent Application Serial No. 16/112,098, entitled SURGICAL DISSECTORS
 - 15 CONFIGURED TO APPLY MECHANICAL AND ELECTRICAL ENERGY;
 - U.S. Patent Application Serial No. 16/112,237, entitled SURGICAL CLIP APPLIER CONFIGURED TO STORE CLIPS IN A STORED STATE;
 - U.S. Patent Application Serial No. 16/112,245, entitled SURGICAL CLIP APPLIER COMPRISING AN EMPTY CLIP CARTRIDGE LOCKOUT;
 - 20 - U.S. Patent Application Serial No. 16/112,249, entitled SURGICAL CLIP APPLIER COMPRISING AN AUTOMATIC CLIP FEEDING SYSTEM;
 - U.S. Patent Application Serial No. 16/112,253, entitled SURGICAL CLIP APPLIER COMPRISING ADAPTIVE FIRING CONTROL; and
 - U.S. Patent Application Serial No. 16/112,257, entitled SURGICAL CLIP APPLIER
 - 25 COMPRISING ADAPTIVE CONTROL IN RESPONSE TO A STRAIN GAUGE CIRCUIT.
- [0116]** Applicant of the present application owns the following U.S. Patent Applications that were filed on May 1, 2018 and which are each herein incorporated by reference in their respective entireties:
- U.S. Patent Application Serial No. 62/665,129, entitled SURGICAL SUTURING
 - 30 SYSTEMS;
 - U.S. Provisional Patent Application Serial No. 62/665,139, entitled SURGICAL INSTRUMENTS COMPRISING CONTROL SYSTEMS;
 - U.S. Patent Application Serial No. 62/665,177, entitled SURGICAL INSTRUMENTS COMPRISING HANDLE ARRANGEMENTS;
 - 35 - U.S. Patent Application Serial No. 62/665,128, entitled MODULAR SURGICAL INSTRUMENTS;

- U.S. Patent Application Serial No. 62/665,192, entitled SURGICAL DISSECTORS;
and

- U.S. Patent Application Serial No. 62/665,134, entitled SURGICAL CLIP APPLIER.

[0117] Applicant of the present application owns the following U.S. Patent Applications that
5 were filed on February 28, 2018 and which are each herein incorporated by reference in
their respective entireties:

- U.S. Patent Application Serial No. 15/908,021, entitled SURGICAL INSTRUMENT
WITH REMOTE RELEASE;

10 - U.S. Patent Application Serial No. 15/908,012, entitled SURGICAL INSTRUMENT
HAVING DUAL ROTATABLE MEMBERS TO EFFECT DIFFERENT TYPES OF END
EFFECTOR MOVEMENT;

- U.S. Patent Application Serial No. 15/908,040, entitled SURGICAL INSTRUMENT
WITH ROTARY DRIVE SELECTIVELY ACTUATING MULTIPLE END EFFECTOR
FUNCTIONS;

15 - U.S. Patent Application Serial No. 15/908,057, entitled SURGICAL INSTRUMENT
WITH ROTARY DRIVE SELECTIVELY ACTUATING MULTIPLE END EFFECTOR
FUNCTIONS;

- U.S. Patent Application Serial No. 15/908,058, entitled SURGICAL INSTRUMENT
WITH MODULAR POWER SOURCES; and

20 - U.S. Patent Application Serial No. 15/908,143, entitled SURGICAL INSTRUMENT
WITH SENSOR AND/OR CONTROL SYSTEMS.

[0118] Applicant of the present application owns the following U.S. Patent Applications that
were filed on October 30, 2017 and which are each herein incorporated by reference in their
respective entireties:

25 - U.S. Provisional Patent Application Serial No. 62/578,793, entitled SURGICAL
INSTRUMENT WITH REMOTE RELEASE;

- U.S. Provisional Patent Application Serial No. 62/578,804, entitled SURGICAL
INSTRUMENT HAVING DUAL ROTATABLE MEMBERS TO EFFECT DIFFERENT TYPES
OF END EFFECTOR MOVEMENT;

30 - U.S. Provisional Patent Application Serial No. 62/578,817, entitled SURGICAL
INSTRUMENT WITH ROTARY DRIVE SELECTIVELY ACTUATING MULTIPLE END
EFFECTOR FUNCTIONS;

- U.S. Provisional Patent Application Serial No. 62/578,835, entitled SURGICAL
INSTRUMENT WITH ROTARY DRIVE SELECTIVELY ACTUATING MULTIPLE END
35 EFFECTOR FUNCTIONS;

- U.S. Provisional Patent Application Serial No. 62/578,844, entitled SURGICAL
INSTRUMENT WITH MODULAR POWER SOURCES; and

- U.S. Provisional Patent Application Serial No. 62/578,855, entitled SURGICAL INSTRUMENT WITH SENSOR AND/OR CONTROL SYSTEMS.

[0119] Applicant of the present application owns the following U.S. Provisional Patent Applications, filed on December 28, 2017, the disclosure of each of which is herein incorporated by reference in its entirety:

- U.S. Provisional Patent Application Serial No. 62/611,341, entitled INTERACTIVE SURGICAL PLATFORM;

- U.S. Provisional Patent Application Serial No. 62/611,340, entitled CLOUD-BASED MEDICAL ANALYTICS; and

- U.S. Provisional Patent Application Serial No. 62/611,339, entitled ROBOT ASSISTED SURGICAL PLATFORM.

[0120] Applicant of the present application owns the following U.S. Provisional Patent Applications, filed on March 28, 2018, each of which is herein incorporated by reference in its entirety:

- U.S. Provisional Patent Application Serial No. 62/649,302, entitled INTERACTIVE SURGICAL SYSTEMS WITH ENCRYPTED COMMUNICATION CAPABILITIES;

- U.S. Provisional Patent Application Serial No. 62/649,294, entitled DATA STRIPPING METHOD TO INTERROGATE PATIENT RECORDS AND CREATE ANONYMIZED RECORD;

- U.S. Provisional Patent Application Serial No. 62/649,300, entitled SURGICAL HUB SITUATIONAL AWARENESS;

- U.S. Provisional Patent Application Serial No. 62/649,309, entitled SURGICAL HUB SPATIAL AWARENESS TO DETERMINE DEVICES IN OPERATING THEATER;

- U.S. Provisional Patent Application Serial No. 62/649,310, entitled COMPUTER IMPLEMENTED INTERACTIVE SURGICAL SYSTEMS;

- U.S. Provisional Patent Application Serial No. 62/649,291, entitled USE OF LASER LIGHT AND RED-GREEN-BLUE COLORATION TO DETERMINE PROPERTIES OF BACK SCATTERED LIGHT;

- U.S. Provisional Patent Application Serial No. 62/649,296, entitled ADAPTIVE CONTROL PROGRAM UPDATES FOR SURGICAL DEVICES;

- U.S. Provisional Patent Application Serial No. 62/649,333, entitled CLOUD-BASED MEDICAL ANALYTICS FOR CUSTOMIZATION AND RECOMMENDATIONS TO A USER;

- U.S. Provisional Patent Application Serial No. 62/649,327, entitled CLOUD-BASED MEDICAL ANALYTICS FOR SECURITY AND AUTHENTICATION TRENDS AND

REACTIVE MEASURES;

- U.S. Provisional Patent Application Serial No. 62/649,315, entitled DATA HANDLING AND PRIORITIZATION IN A CLOUD ANALYTICS NETWORK;

- U.S. Provisional Patent Application Serial No. 62/649,313, entitled CLOUD INTERFACE FOR COUPLED SURGICAL DEVICES;

- U.S. Provisional Patent Application Serial No. 62/649,320, entitled DRIVE ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS;

5 - U.S. Provisional Patent Application Serial No. 62/649,307, entitled AUTOMATIC TOOL ADJUSTMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS; and

- U.S. Provisional Patent Application Serial No. 62/649,323, entitled SENSING ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS.

[0121] Applicant of the present application owns the following U.S. Patent Applications,
10 filed on March 29, 2018, each of which is herein incorporated by reference in its entirety:

- U.S. Patent Application Serial No. 15/940,641, entitled INTERACTIVE SURGICAL SYSTEMS WITH ENCRYPTED COMMUNICATION CAPABILITIES;

- U.S. Patent Application Serial No. 15/940,648, entitled INTERACTIVE SURGICAL SYSTEMS WITH CONDITION HANDLING OF DEVICES AND DATA CAPABILITIES;

15 - U.S. Patent Application Serial No. 15/940,656, entitled SURGICAL HUB COORDINATION OF CONTROL AND COMMUNICATION OF OPERATING ROOM DEVICES;

- U.S. Patent Application Serial No. 15/940,666, entitled SPATIAL AWARENESS OF SURGICAL HUBS IN OPERATING ROOMS;

20 - U.S. Patent Application Serial No. 15/940,670, entitled COOPERATIVE UTILIZATION OF DATA DERIVED FROM SECONDARY SOURCES BY INTELLIGENT SURGICAL HUBS;

- U.S. Patent Application Serial No. 15/940,677, entitled SURGICAL HUB CONTROL ARRANGEMENTS;

25 - U.S. Patent Application Serial No. 15/940,632, entitled DATA STRIPPING METHOD TO INTERROGATE PATIENT RECORDS AND CREATE ANONYMIZED RECORD;

- U.S. Patent Application Serial No. 15/940,640, entitled COMMUNICATION HUB AND STORAGE DEVICE FOR STORING PARAMETERS AND STATUS OF A SURGICAL DEVICE TO BE SHARED WITH CLOUD BASED ANALYTICS SYSTEMS;

30 - U.S. Patent Application Serial No. 15/940,645, entitled SELF DESCRIBING DATA PACKETS GENERATED AT AN ISSUING INSTRUMENT;

- U.S. Patent Application Serial No. 15/940,649, entitled DATA PAIRING TO INTERCONNECT A DEVICE MEASURED PARAMETER WITH AN OUTCOME;

35 - U.S. Patent Application Serial No. 15/940,654, entitled SURGICAL HUB SITUATIONAL AWARENESS;

- U.S. Patent Application Serial No. 15/940,663, entitled SURGICAL SYSTEM DISTRIBUTED PROCESSING;

- U.S. Patent Application Serial No. 15/940,668, entitled AGGREGATION AND REPORTING OF SURGICAL HUB DATA;
 - U.S. Patent Application Serial No. 15/940,671, entitled SURGICAL HUB SPATIAL AWARENESS TO DETERMINE DEVICES IN OPERATING THEATER;
 - 5 - U.S. Patent Application Serial No. 15/940,686, entitled DISPLAY OF ALIGNMENT OF STAPLE CARTRIDGE TO PRIOR LINEAR STAPLE LINE;
 - U.S. Patent Application Serial No. 15/940,700, entitled STERILE FIELD INTERACTIVE CONTROL DISPLAYS;
 - U.S. Patent Application Serial No. 15/940,629, entitled COMPUTER IMPLEMENTED
10 INTERACTIVE SURGICAL SYSTEMS;
 - U.S. Patent Application Serial No. 15/940,704, entitled USE OF LASER LIGHT AND RED-GREEN-BLUE COLORATION TO DETERMINE PROPERTIES OF BACK SCATTERED LIGHT;
 - U.S. Patent Application Serial No. 15/940,722, entitled CHARACTERIZATION OF
15 TISSUE IRREGULARITIES THROUGH THE USE OF MONO-CHROMATIC LIGHT REFRACTIVITY; and
 - U.S. Patent Application Serial No. 15/940,742, entitled DUAL CMOS ARRAY IMAGING.
- [0122]** Applicant of the present application owns the following U.S. Patent Applications,
20 filed on March 29, 2018, each of which is herein incorporated by reference in its entirety:
- U.S. Patent Application Serial No. 15/940,636, entitled ADAPTIVE CONTROL PROGRAM UPDATES FOR SURGICAL DEVICES;
 - U.S. Patent Application Serial No. 15/940,653, entitled ADAPTIVE CONTROL PROGRAM UPDATES FOR SURGICAL HUBS;
 - 25 - U.S. Patent Application Serial No. 15/940,660, entitled CLOUD-BASED MEDICAL ANALYTICS FOR CUSTOMIZATION AND RECOMMENDATIONS TO A USER;
 - U.S. Patent Application Serial No. 15/940,679, entitled CLOUD-BASED MEDICAL ANALYTICS FOR LINKING OF LOCAL USAGE TRENDS WITH THE RESOURCE ACQUISITION BEHAVIORS OF LARGER DATA SET;
 - 30 - U.S. Patent Application Serial No. 15/940,694, entitled CLOUD-BASED MEDICAL ANALYTICS FOR MEDICAL FACILITY SEGMENTED INDIVIDUALIZATION OF INSTRUMENT FUNCTION;
 - U.S. Patent Application Serial No. 15/940,634, entitled CLOUD-BASED MEDICAL ANALYTICS FOR SECURITY AND AUTHENTICATION TRENDS AND REACTIVE
35 MEASURES;
 - U.S. Patent Application Serial No. 15/940,706, entitled DATA HANDLING AND PRIORITIZATION IN A CLOUD ANALYTICS NETWORK; and

- U.S. Patent Application Serial No. 15/940,675, entitled CLOUD INTERFACE FOR COUPLED SURGICAL DEVICES.

[0123] Applicant of the present application owns the following U.S. Patent Applications, filed on March 29, 2018, each of which is herein incorporated by reference in its entirety:

- 5 - U.S. Patent Application Serial No. 15/940,627, entitled DRIVE ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS;
- U.S. Patent Application Serial No. 15/940,637, entitled COMMUNICATION ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS;
- U.S. Patent Application Serial No. 15/940,642, entitled CONTROLS FOR ROBOT-
10 ASSISTED SURGICAL PLATFORMS;
- U.S. Patent Application Serial No. 15/940,676, entitled AUTOMATIC TOOL ADJUSTMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS;
- U.S. Patent Application Serial No. 15/940,680, entitled CONTROLLERS FOR ROBOT-ASSISTED SURGICAL PLATFORMS;
- 15 - U.S. Patent Application Serial No. 15/940,683, entitled COOPERATIVE SURGICAL ACTIONS FOR ROBOT-ASSISTED SURGICAL PLATFORMS;
- U.S. Patent Application Serial No. 15/940,690, entitled DISPLAY ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS; and
- U.S. Patent Application Serial No. 15/940,711, entitled SENSING ARRANGEMENTS
20 FOR ROBOT-ASSISTED SURGICAL PLATFORMS.

[0124] Applicant of the present application owns the following U.S. Provisional Patent Applications, filed on March 30, 2018, each of which is herein incorporated by reference in its entirety:

- U.S. Provisional Patent Application Serial No. 62/650,887, entitled SURGICAL
25 SYSTEMS WITH OPTIMIZED SENSING CAPABILITIES;
- U.S. Provisional Patent Application Serial No. 62/650,877, entitled SURGICAL SMOKE EVACUATION SENSING AND CONTROLS;
- U.S. Provisional Patent Application Serial No. 62/650,882, entitled SMOKE EVACUATION MODULE FOR INTERACTIVE SURGICAL PLATFORM; and
- 30 - U.S. Provisional Patent Application Serial No. 62/650,898, entitled CAPACITIVE COUPLED RETURN PATH PAD WITH SEPARABLE ARRAY ELEMENTS.

[0125] Applicant of the present application owns the following U.S. Provisional Patent Application, filed on April 19, 2018, which is herein incorporated by reference in its entirety:

- U.S. Provisional Patent Application Serial No. 62/659,900, entitled METHOD OF
35 HUB COMMUNICATION.

[0126] Numerous specific details are set forth to provide a thorough understanding of the overall structure, function, manufacture, and use of the embodiments as described in the

specification and illustrated in the accompanying drawings. Well-known operations, components, and elements have not been described in detail so as not to obscure the embodiments described in the specification. The reader will understand that the embodiments described and illustrated herein are non-limiting examples, and thus it can be appreciated that the specific structural and functional details disclosed herein may be representative and illustrative. Variations and changes thereto may be made without departing from the scope of the claims.

[0127] The terms "comprise" (and any form of comprise, such as "comprises" and "comprising"), "have" (and any form of have, such as "has" and "having"), "include" (and any form of include, such as "includes" and "including"), and "contain" (and any form of contain, such as "contains" and "containing") are open-ended linking verbs. As a result, a surgical system, device, or apparatus that "comprises," "has," "includes", or "contains" one or more elements possesses those one or more elements, but is not limited to possessing only those one or more elements. Likewise, an element of a system, device, or apparatus that "comprises," "has," "includes", or "contains" one or more features possesses those one or more features, but is not limited to possessing only those one or more features.

[0128] The terms "proximal" and "distal" are used herein with reference to a clinician manipulating the handle portion of the surgical instrument. The term "proximal" refers to the portion closest to the clinician and the term "distal" refers to the portion located away from the clinician. It will be further appreciated that, for convenience and clarity, spatial terms such as "vertical", "horizontal", "up", and "down" may be used herein with respect to the drawings. However, surgical instruments are used in many orientations and positions, and these terms are not intended to be limiting and/or absolute.

[0129] Various exemplary devices and methods are provided for performing laparoscopic and minimally invasive surgical procedures. However, the reader will readily appreciate that the various methods and devices disclosed herein can be used in numerous surgical procedures and applications including, for example, in connection with open surgical procedures. As the present Detailed Description proceeds, the reader will further appreciate that the various instruments disclosed herein can be inserted into a body in any way, such as through a natural orifice, through an incision or puncture hole formed in tissue, etc. The working portions or end effector portions of the instruments can be inserted directly into a patient's body or can be inserted through an access device that has a working channel through which the end effector and elongate shaft of a surgical instrument can be advanced.

[0130] A surgical instrument, such as a grasper, for example, can comprise a handle, a shaft extending from the handle, and an end effector extending from the shaft. In various instances, the end effector comprises a first jaw and a second jaw, wherein one or both of the jaws are movable relative to the other to grasp the tissue of a patient. That said, an end

effector of a surgical instrument can comprise any suitable arrangement and can perform any suitable function. For instance, an end effector can comprise first and second jaws configured to dissect or separate the tissue of a patient. Also, for instance, an end effector can be configured to suture and/or clip the tissue of a patient. In various instances, the end effector and/or shaft of the surgical instrument are configured to be inserted into a patient through a trocar, or cannula, and can have any suitable diameter, such as approximately 5 mm, 8 mm, and/or 12 mm, for example. U.S. Patent Application Serial No. 11/013,924, entitled TROCAR SEAL ASSEMBLY, now U.S. Patent No. 7,371,227, is incorporated by reference in its entirety. The shaft can define a longitudinal axis and at least a portion of the end effector can be rotatable about the longitudinal axis. Moreover, the surgical instrument can further comprise an articulation joint which can permit at least a portion of the end effector to be articulated relative to the shaft. In use, a clinician can rotate and/or articulate the end effector in order to maneuver the end effector within the patient.

[0131] A surgical instrument system is depicted in FIG. 1. The surgical instrument system comprises a handle assembly 1000 which is selectively usable with a shaft assembly 2000, a shaft assembly 3000, a shaft assembly 4000, a shaft assembly 5000, and/or any other suitable shaft assembly. The shaft assembly 2000 is attached to the handle assembly 1000 in FIG. 2 and the shaft assembly 4000 is attached to the handle assembly 1000 in FIG. 45. The shaft assembly 2000 comprises a proximal portion 2100, an elongate shaft 2200 extending from the proximal portion 2100, a distal attachment portion 2400, and an articulation joint 2300 rotatably connecting the distal attachment portion 2400 to the elongate shaft 2200. The shaft assembly 2000 further comprises a replaceable end effector assembly 7000 attached to the distal attachment portion 2400. The replaceable end effector assembly 7000 comprises a jaw assembly 7100 configured to be opened and closed to clamp and/or manipulate the tissue of a patient. In use, the end effector assembly 7000 can be articulated about the articulation joint 2300 and/or rotated relative to the distal attachment portion 2400 about a longitudinal axis to better position the jaw assembly 7100 within the patient, as described in greater detail further below.

[0132] Referring again to FIG. 1, the handle assembly 1000 comprises, among other things, a drive module 1100. As described in greater detail below, the drive module 1100 comprises a distal mounting interface which permits a clinician to selectively attach one of the shaft assemblies 2000, 3000, 4000, and 5000, for example, to the drive module 1100. Thus, each of the shaft assemblies 2000, 3000, 4000, and 5000 comprises an identical, or an at least similar, proximal mounting interface which is configured to engage the distal mounting interface of the drive module 1100. As also described in greater detail below, the mounting interface of the drive module 1100 mechanically secures and electrically couples the selected shaft assembly to the drive module 1100. The drive module 1100 further

comprises at least one electric motor, one or more controls and/or displays, and a controller configured to operate the electric motor- the rotational output of which is transmitted to a drive system of the shaft assembly attached to the drive module 1100. Moreover, the drive module 1100 is usable with one or more power modules, such as power modules 1200 and 1300, for example, which are operably attachable to the drive module 1100 to supply power thereto.

[0133] Further to the above, referring again to FIGS. 1 and 2, the handle drive module 1100 comprises a housing 1110, a first module connector 1120, and a second module connector 1120'. The power module 1200 comprises a housing 1210, a connector 1220, one or more release latches 1250, and one or more batteries 1230. The connector 1220 is configured to be engaged with the first module connector 1120 of the drive module 1100 in order to attach the power module 1200 to the drive module 1100. The connector 1220 comprises one or more latches 1240 which mechanically couple and fixedly secure the housing 1210 of the power module 1200 to the housing 1110 of the drive module 1100. The latches 1240 are movable into disengaged positions when the release latches 1250 are depressed so that the power module 1200 can be detached from the drive module 1100. The connector 1220 also comprises one or more electrical contacts which place the batteries 1230, and/or an electrical circuit including the batteries 1230, in electrical communication with an electrical circuit in the drive module 1100.

[0134] Further to the above, referring again to FIGS. 1 and 2, the power module 1300 comprises a housing 1310, a connector 1320, one or more release latches 1350, and one or more batteries 1330 (FIG. 47). The connector 1320 is configured to be engaged with the second module connector 1120' of the drive module 1100 to attach the power module 1300 to the drive module 1100. The connector 1320 comprises one or more latches 1340 which mechanically couple and fixedly secure the housing 1310 of the power module 1300 to the housing 1110 of the drive module 1100. The latches 1340 are movable into disengaged positions when the release latches 1350 are depressed so that the power module 1300 can be detached from the drive module 1100. The connector 1320 also comprises one or more electrical contacts which place the batteries 1330 of the power module 1300, and/or an electrical power circuit including the batteries 1330, in electrical communication with an electrical power circuit in the drive module 1100.

[0135] Further to the above, the power module 1200, when attached to the drive module 1100, comprises a pistol grip which can allow a clinician to hold the handle 1000 in a manner which places the drive module 1100 on top of the clinician's hand. The power module 1300, when attached to the drive module 1100, comprises an end grip which allows a clinician to hold the handle 1000 like a wand. The power module 1200 is longer than the power module 1300, although the power modules 1200 and 1300 can comprise any suitable length. The

power module 1200 has more battery cells than the power module 1300 and can suitably accommodate these additional battery cells owing to its length. In various instances, the power module 1200 can provide more power to the drive module 1100 than the power module 1300 while, in some instances, the power module 1200 can provide power for a longer period of time. In some instances, the housing 1110 of the drive module 1100 comprises keys, and/or any other suitable features, which prevent the power module 1200 from being connected to the second module connector 1120' and, similarly, prevent the power module 1300 from being connected to the first module connector 1120. Such an arrangement can assure that the longer power module 1200 is used in the pistol grip arrangement and that the shorter power module 1300 is used in the wand grip arrangement. In alternative embodiments, the power module 1200 and the power module 1300 can be selectively coupled to the drive module 1100 at either the first module connector 1120 or the second module connector 1120'. Such embodiments provide a clinician with more options to customize the handle 1000 in a manner suitable to them.

[0136] In various instances, further to the above, only one of the power modules 1200 and 1300 is coupled to the drive module 1100 at a time. In certain instances, the power module 1200 can be in the way when the shaft assembly 4000, for example, is attached to the drive module 1100. Alternatively, both of the power modules 1200 and 1300 can be operably coupled to the drive module 1100 at the same time. In such instances, the drive module 1100 can have access to power provided by both of the power modules 1200 and 1300. Moreover, a clinician can switch between a pistol grip and a wand grip when both of the power modules 1200 and 1300 are attached to the drive module 1100. Moreover, such an arrangement allows the power module 1300 to act as a counterbalance to a shaft assembly, such as shaft assemblies 2000, 3000, 4000, or 5000, for example, attached to the drive module 1100.

[0137] Referring to FIGS. 7 and 8, the handle drive module 1100 further comprises a frame 1500, a motor assembly 1600, a drive system 1700 operably engaged with the motor assembly 1600, and a control system 1800. The frame 1500 comprises an elongate shaft that extends through the motor assembly 1600. The elongate shaft comprises a distal end 1510 and electrical contacts, or sockets, 1520 defined in the distal end 1510. The electrical contacts 1520 are in electrical communication with the control system 1800 of the drive module 1100 via one or more electrical circuits and are configured to convey signals and/or power between the control system 1800 and the shaft assembly, such as the shaft assembly 2000, 3000, 4000, or 5000, for example, attached to the drive module 1100. The control system 1800 comprises a printed circuit board (PCB) 1810, at least one microprocessor 1820, and at least one memory device 1830. The board 1810 can be rigid and/or flexible and can comprise any suitable number of layers. The microprocessor 1820 and the memory

device 1830 are part of a control circuit defined on the board 1810 which controls the operation of the motor assembly 1600, as described in greater detail below.

[0138] Referring to FIGS. 12 and 13, the motor assembly 1600 comprises an electric motor 1610 including a housing 1620, a drive shaft 1630, and a gear reduction system. The electric motor 1610 further comprises a stator including windings 1640 and a rotor including magnetic elements 1650. The stator windings 1640 are supported in the housing 1620 and the rotor magnetic elements 1650 are mounted to the drive shaft 1630. When the stator windings 1640 are energized with an electric current controlled by the control system 1800, the drive shaft 1630 is rotated about a longitudinal axis. The drive shaft 1630 is operably engaged with a first planetary gear system 1660 which includes a central sun gear and several planetary gears operably intermeshed with the sun gear. The sun gear of the first planetary gear system 1660 is fixedly mounted to the drive shaft 1630 such that it rotates with the drive shaft 1630. The planetary gears of the first planetary gear system 1660 are rotatably mounted to the sun gear of a second planetary gear system 1670 and, also, intermeshed with a geared or splined inner surface 1625 of the motor housing 1620. As a result of the above, the rotation of the first sun gear rotates the first planetary gears which rotate the second sun gear. Similar to the above, the second planetary gear system 1670 further comprises planetary gears 1665 (FIG. 13) which drive a third planetary gear system and, ultimately, the drive shaft 1710. The planetary gear systems 1660, 1670, and 1680 cooperate to gear down the speed applied to the drive shaft 1710 by the motor shaft 1620. Various alternative embodiments are envisioned without a speed reduction system. Such embodiments are suitable when it is desirable to drive the end effector functions quickly. Notably, the drive shaft 1630 comprises an aperture, or hollow core, extending therethrough through which wires and/or electrical circuits can extend.

[0139] The control system 1800 is in communication with the motor assembly 1600 and the electrical power circuit of the drive module 1100. The control system 1800 is configured to control the power delivered to the motor assembly 1600 from the electrical power circuit. The electrical power circuit is configured to supply a constant, or at least nearly constant, direct current (DC) voltage. In at least one instance, the electrical power circuit supplies 3 VDC to the control system 1800. The control system 1800 comprises a pulse width modulation (PWM) circuit which is configured to deliver voltage pulses to the motor assembly 1600. The duration or width of the voltage pulses, and/or the duration or width between the voltage pulses, supplied by the PWM circuit can be controlled in order to control the power applied to the motor assembly 1600. By controlling the power applied to the motor assembly 1600, the PWM circuit can control the speed of the output shaft of the motor assembly 1600. In addition to or in lieu of a PWM circuit, the control system 1800 can include a frequency modulation (FM) circuit. As discussed in greater detail below, the

control system 1800 is operable in more than one operating mode and, depending on the operating mode being used, the control system 1800 can operate the motor assembly 1600 at a speed, or a range of speeds, which is determined to be appropriate for that operating mode.

5 **[0140]** Further to the above, referring again to FIGS. 7 and 8, the drive system 1700 comprises a rotatable shaft 1710 comprising a splined distal end 1720 and a longitudinal aperture 1730 defined therein. The rotatable shaft 1710 is operably mounted to the output shaft of the motor assembly 1600 such that the rotatable shaft 1710 rotates with the motor output shaft. The handle frame 1510 extends through the longitudinal aperture 1730 and
10 rotatably supports the rotatable shaft 1710. As a result, the handle frame 1510 serves as a bearing for the rotatable shaft 1710. The handle frame 1510 and the rotatable shaft 1710 extend distally from a mounting interface 1130 of the drive module 1110 and are coupled with corresponding components on the shaft assembly 2000 when the shaft assembly 2000 is assembled to the drive module 1100. Referring primarily to FIGS. 3-6, the shaft assembly
15 2000 further comprises a frame 2500 and a drive system 2700. The frame 2500 comprises a longitudinal shaft 2510 extending through the shaft assembly 2000 and a plurality of electrical contacts, or pins, 2520 extending proximally from the shaft 2510. When the shaft assembly 2000 is attached to the drive module 1100, the electrical contacts 2520 on the shaft frame 2510 engage the electrical contacts 1520 on the handle frame 1510 and create
20 electrical pathways therebetween.

[0141] Similar to the above, the drive system 2700 comprises a rotatable drive shaft 2710 which is operably coupled to the rotatable drive shaft 1710 of the handle 1000 when the shaft assembly 2000 is assembled to the drive module 1100 such that the drive shaft 2710 rotates with the drive shaft 1710. To this end, the drive shaft 2710 comprises a splined
25 proximal end 2720 which mates with the splined distal end 1720 of the drive shaft 1710 such that the drive shafts 1710 and 2710 rotate together when the drive shaft 1710 is rotated by the motor assembly 1600. Given the nature of the splined interconnection between the drive shafts 1710 and 2710 and the electrical interconnection between the frames 1510 and 2510, the shaft assembly 2000 is assembled to the handle 1000 along a longitudinal axis;
30 however, the operable interconnection between the drive shafts 1710 and 2710 and the electrical interconnection between the frames 1510 and 2510 can comprise any suitable configuration which can allow a shaft assembly to be assembled to the handle 1000 in any suitable manner.

[0142] As discussed above, referring to FIGS. 3-8, the mounting interface 1130 of the
35 drive module 1110 is configured to be coupled to a corresponding mounting interface on the shaft assemblies 2000, 3000, 4000, and 5000, for example. For instance, the shaft assembly 2000 comprises a mounting interface 2130 configured to be coupled to the

mounting interface 1130 of the drive module 1100. More specifically, the proximal portion 2100 of the shaft assembly 2000 comprises a housing 2110 which defines the mounting interface 2130. Referring primarily to FIG. 8, the drive module 1100 comprises latches 1140 which are configured to releasably hold the mounting interface 2130 of the shaft assembly 2000 against the mounting interface 1130 of the drive module 1100. When the drive module 1100 and the shaft assembly 2000 are brought together along a longitudinal axis, as described above, the latches 1140 contact the mounting interface 2130 and rotate outwardly into an unlocked position. Referring primarily to FIGS. 8, 10, and 11, each latch 1140 comprises a lock end 1142 and a pivot portion 1144. The pivot portion 1144 of each latch 1140 is rotatably coupled to the housing 1110 of the drive module 1100 and, when the latches 1140 are rotated outwardly, as mentioned above, the latches 1140 rotate about the pivot portions 1144. Notably, each latch 1140 further comprises a biasing spring 1146 configured to bias the latches 1140 inwardly into a locked position. Each biasing spring 1146 is compressed between a latch 1140 and the housing 1110 of the drive module 1100 such that the biasing springs 1146 apply biasing forces to the latches 1140; however, such biasing forces are overcome when the latches 1140 are rotated outwardly into their unlocked positions by the shaft assembly 2000. That said, when the latches 1140 rotate outwardly after contacting the mounting interface 2130, the lock ends 1142 of the latches 1140 can enter into latch windows 2140 defined in the mounting interface 2130. Once the lock ends 1142 pass through the latch windows 2140, the springs 1146 can bias the latches 1140 back into their locked positions. Each lock end 1142 comprises a lock shoulder, or surface, which securely holds the shaft assembly 2000 to the drive module 1100.

[0143] Further to the above, the biasing springs 1146 hold the latches 1140 in their locked positions. The distal ends 1142 are sized and configured to prevent, or at least inhibit, relative longitudinal movement, i.e., translation along a longitudinal axis, between the shaft assembly 2000 and the drive module 1100 when the latches 1140 are in their locked positions. Moreover, the latches 1140 and the latch windows 1240 are sized and configured to prevent relative lateral movement, i.e., translation transverse to the longitudinal axis, between the shaft assembly 2000 and the drive module 1100. In addition, the latches 1140 and the latch windows 2140 are sized and configured to prevent the shaft assembly 2000 from rotating relative to the drive module 1100. The drive module 1100 further comprises release actuators 1150 which, when depressed by a clinician, move the latches 1140 from their locked positions into their unlocked positions. The drive module 1100 comprises a first release actuator 1150 slideably mounted in an opening defined in the first side of the handle housing 1110 and a second release actuator 1150 slideably mounted in an opening defined in a second, or opposite, side of the handle housing 1110. Although the release actuators 1150 are actuatable separately, both release actuators 1150 typically need to be depressed

to completely unlock the shaft assembly 2000 from the drive module 1100 and allow the shaft assembly 2000 to be detached from the drive module 1100. That said, it is possible that the shaft assembly 2000 could be detached from the drive module 1100 by depressing only one release actuator 1150.

5 **[0144]** Once the shaft assembly 2000 has been secured to the handle 1000 and the end effector 7000, for example, has been assembled to the shaft 2000, the clinician can maneuver the handle 1000 to insert the end effector 7000 into a patient. In at least one instance, the end effector 7000 is inserted into the patient through a trocar and then manipulated in order to position the jaw assembly 7100 of the end effector assembly 7000
10 relative to the patient's tissue. Oftentimes, the jaw assembly 7100 must be in its closed, or clamped, configuration in order to fit through the trocar. Once through the trocar, the jaw assembly 7100 can be opened so that the patient tissue fit between the jaws of the jaw assembly 7100. At such point, the jaw assembly 7100 can be returned to its closed configuration to clamp the patient tissue between the jaws. The clamping force applied to
15 the patient tissue by the jaw assembly 7100 is sufficient to move or otherwise manipulate the tissue during a surgical procedure. Thereafter, the jaw assembly 7100 can be re-opened to release the patient tissue from the end effector 7000. This process can be repeated until it is desirable to remove the end effector 7000 from the patient. At such point, the jaw assembly 7100 can be returned to its closed configuration and retracted through the trocar. Other
20 surgical techniques are envisioned in which the end effector 7000 is inserted into a patient through an open incision, or without the use of the trocar. In any event, it is envisioned that the jaw assembly 7100 may have to be opened and closed several times throughout a surgical technique.

[0145] Referring again to FIGS. 3-6, the shaft assembly 2000 further comprises a
25 clamping trigger system 2600 and a control system 2800. The clamping trigger system 2600 comprises a clamping trigger 2610 rotatably connected to the proximal housing 2110 of the shaft assembly 2000. As discussed below, the clamping trigger 2610 actuates the motor 1610 to operate the jaw drive of the end effector 7000 when the clamping trigger 2610 is actuated. The clamping trigger 2610 comprises an elongate portion which is graspable by
30 the clinician while holding the handle 1000. The clamping trigger 2610 further comprises a mounting portion 2620 which is pivotably connected to a mounting portion 2120 of the proximal housing 2110 such that the clamping trigger 2610 is rotatable about a fixed, or an at least substantially fixed, axis. The closure trigger 2610 is rotatable between a distal position and a proximal position, wherein the proximal position of the closure trigger 2610 is
35 closer to the pistol grip of the handle 1000 than the distal position. The closure trigger 2610 further comprises a tab 2615 extending therefrom which rotates within the proximal housing 2110. When the closure trigger 2610 is in its distal position, the tab 2615 is positioned

above, but not in contact with, a switch 2115 mounted on the proximal housing 2110. The switch 2115 is part of an electrical circuit configured to detect the actuation of the closure trigger 2610 which is in an open condition the closure trigger 2610 is in its open position. When the closure trigger 2610 is moved into its proximal position, the tab 2615 comes into
5 contact with the switch 2115 and closes the electrical circuit. In various instances, the switch 2115 can comprise a toggle switch, for example, which is mechanically switched between open and closed states when contacted by the tab 2615 of the closure trigger 2610. In certain instances, the switch 2115 can comprise a proximity sensor, for example, and/or any suitable type of sensor. In at least one instance, the switch 2115 comprises a Hall Effect
10 sensor which can detect the amount in which the closure trigger 2610 has been rotated and, based on the amount of rotation, control the speed in which the motor 1610 is operated. In such instances, larger rotations of the closure trigger 2610 result in faster speeds of the motor 1610 while smaller rotations result in slower speeds, for example. In any event, the electrical circuit is in communication with the control system 2800 of the shaft assembly
15 2000, which is discussed in greater detail below.

[0146] Further to the above, the control system 2800 of the shaft assembly 2000 comprises a printed circuit board (PCB) 2810, at least one microprocessor 2820, and at least one memory device 2830. The board 2810 can be rigid and/or flexible and can comprise any suitable number of layers. The microprocessor 2820 and the memory device 2830 are
20 part of a control circuit defined on the board 2810 which communicates with the control system 1800 of the handle 1000. The shaft assembly 2000 further comprises a signal communication system 2900 and the handle 1000 further comprises a signal communication system 1900 which are configured to convey data between the shaft control system 2800 and the handle control system 1800. The signal communication system 2900 is configured
25 to transmit data to the signal communication system 1900 utilizing any suitable analog and/or digital components. In various instances, the communication systems 2900 and 1900 can communicate using a plurality of discrete channels which allows the input gates of the microprocessor 1820 to be directly controlled, at least in part, by the output gates of the microprocessor 2820. In some instances, the communication systems 2900 and 1900 can
30 utilize multiplexing. In at least one such instance, the control system 2900 includes a multiplexing device that sends multiple signals on a carrier channel at the same time in the form of a single, complex signal to a multiplexing device of the control system 1900 that recovers the separate signals from the complex signal.

[0147] The communication system 2900 comprises an electrical connector 2910 mounted
35 to the circuit board 2810. The electrical connector 2910 comprises a connector body and a plurality of electrically-conductive contacts mounted to the connector body. The electrically-conductive contacts comprise male pins, for example, which are soldered to electrical traces

defined in the circuit board 2810. In other instances, the male pins can be in communication with circuit board traces through zero-insertion-force (ZIF) sockets, for example. The communication system 1900 comprises an electrical connector 1910 mounted to the circuit board 1810. The electrical connector 1910 comprises a connector body and a plurality of electrically-conductive contacts mounted to the connector body. The electrically-conductive contacts comprise female pins, for example, which are soldered to electrical traces defined in the circuit board 1810. In other instances, the female pins can be in communication with circuit board traces through zero-insertion-force (ZIF) sockets, for example. When the shaft assembly 2000 is assembled to the drive module 1100, the electrical connector 2910 is operably coupled to the electrical connector 1910 such that the electrical contacts form electrical pathways therebetween. The above being said, the connectors 1910 and 2910 can comprise any suitable electrical contacts. Moreover, the communication systems 1900 and 2900 can communicate with one another in any suitable manner. In various instances, the communication systems 1900 and 2900 communicate wirelessly. In at least one such instance, the communication system 2900 comprises a wireless signal transmitter and the communication system 1900 comprises a wireless signal receiver such that the shaft assembly 2000 can wirelessly communicate data to the handle 1000. Likewise, the communication system 1900 can comprise a wireless signal transmitter and the communication system 2900 can comprise a wireless signal receiver such that the handle 1000 can wirelessly communicate data to the shaft assembly 2000.

[0148] As discussed above, the control system 1800 of the handle 1000 is in communication with, and is configured to control, the electrical power circuit of the handle 1000. The handle control system 1800 is also powered by the electrical power circuit of the handle 1000. The handle communication system 1900 is in signal communication with the handle control system 1800 and is also powered by the electrical power circuit of the handle 1000. The handle communication system 1900 is powered by the handle electrical power circuit via the handle control system 1800, but could be directly powered by the electrical power circuit. As also discussed above, the handle communication system 1900 is in signal communication with the shaft communication system 2900. That said, the shaft communication system 2900 is also powered by the handle electrical power circuit via the handle communication system 1900. To this end, the electrical connectors 1910 and 2010 connect both one or more signal circuits and one or more power circuits between the handle 1000 and the shaft assembly 2000. Moreover, the shaft communication system 2900 is in signal communication with the shaft control system 2800, as discussed above, and is also configured to supply power to the shaft control system 2800. Thus, the control systems 1800 and 2800 and the communication systems 1900 and 2900 are all powered by the electrical power circuit of the handle 1000; however, alternative embodiments are envisioned

in which the shaft assembly 2000 comprises its own power source, such as one or more batteries, for example, an and electrical power circuit configured to supply power from the batteries to the handle systems 2800 and 2900. In at least one such embodiment, the handle control system 1800 and the handle communication system 1900 are powered by the handle electrical power system and the shaft control system 2800 and the handle communication system 2900 are powered by the shaft electrical power system.

[0149] Further to the above, the actuation of the clamping trigger 2610 is detected by the shaft control system 2800 and communicated to the handle control system 1800 via the communication systems 2900 and 1900. Upon receiving a signal that the clamping trigger 2610 has been actuated, the handle control system 1800 supplies power to the electric motor 1610 of the motor assembly 1600 to rotate the drive shaft 1710 of the handle drive system 1700, and the drive shaft 2710 of the shaft drive system 2700, in a direction which closes the jaw assembly 7100 of the end effector 7000. The mechanism for converting the rotation of the drive shaft 2710 to a closure motion of the jaw assembly 7100 is discussed in greater detail below. So long as the clamping trigger 2610 is held in its actuated position, the electric motor 1610 will rotate the drive shaft 1710 until the jaw assembly 7100 reaches its fully-clamped position. When the jaw assembly 7100 reaches its fully-clamped position, the handle control system 1800 cuts the electrical power to the electric motor 1610. The handle control system 1800 can determine when the jaw assembly 7100 has reached its fully-clamped position in any suitable manner. For instance, the handle control system 1800 can comprise an encoder system which monitors the rotation of, and counts the rotations of, the output shaft of the electric motor 1610 and, once the number of rotations reaches a predetermined threshold, the handle control system 1800 can discontinue supplying power to the electric motor 1610. In at least one instance, the end effector assembly 7000 can comprise one or more sensors configured to detect when the jaw assembly 7100 has reached its fully-clamped position. In at least one such instance, the sensors in the end effector 7000 are in signal communication with the handle control system 1800 via electrical circuits extending through the shaft assembly 2000 which can include the electrical contacts 1520 and 2520, for example.

[0150] When the clamping trigger 2610 is rotated distally out of its proximal position, the switch 2115 is opened which is detected by the shaft control system 2800 and communicated to the handle control system 1800 via the communication systems 2900 and 1900. Upon receiving a signal that the clamping trigger 2610 has been moved out of its actuated position, the handle control system 1800 reverses the polarity of the voltage differential being applied to the electric motor 1610 of the motor assembly 1600 to rotate the drive shaft 1710 of the handle drive system 1700, and the drive shaft 2710 of the shaft drive system 2700, in an opposite direction which, as a result, opens the jaw assembly 7100 of the

end effector 7000. When the jaw assembly 7100 reaches its fully-open position, the handle control system 1800 cuts the electrical power to the electric motor 1610. The handle control system 1800 can determine when the jaw assembly 7100 has reached its fully-open position in any suitable manner. For instance, the handle control system 1800 can utilize the encoder system and/or the one or more sensors described above to determine the configuration of the jaw assembly 7100. In view of the above, the clinician needs to be mindful about holding the clamping trigger 2610 in its actuated position in order to maintain the jaw assembly 7100 in its clamped configuration as, otherwise, the control system 1800 will open jaw assembly 7100. With this in mind, the shaft assembly 2000 further comprises an actuator latch 2630 configured to releasably hold the clamping trigger 2610 in its actuated position to prevent the accidental opening of the jaw assembly 7100. The actuator latch 2630 can be manually released, or otherwise defeated, by the clinician to allow the clamping trigger 2610 to be rotated distally and open the jaw assembly 7100.

[0151] The clamping trigger system 2600 further comprises a resilient biasing member, such as a torsion spring, for example, configured to resist the closure of the clamping trigger system 2600. The torsion spring can also assist in reducing and/or mitigating sudden movements and/or jitter of the clamping trigger 2610. Such a torsion spring can also automatically return the clamping trigger 2610 to its unactuated position when the clamping trigger 2610 is released. The actuator latch 2630 discussed above can suitably hold the clamping trigger 2610 in its actuated position against the biasing force of the torsion spring.

[0152] As discussed above, the control system 1800 operates the electric motor 1610 to open and close the jaw assembly 7100. The control system 1800 is configured to open and close the jaw assembly 7100 at the same speed. In such instances, the control system 1800 applies the same voltage pulses to the electric motor 1610, albeit with different voltage polarities, when opening and closing the jaw assembly 7100. That said, the control system 1800 can be configured to open and close the jaw assembly 7100 at different speeds. For instance, the jaw assembly 7100 can be closed at a first speed and opened at a second speed which is faster than the first speed. In such instances, the slower closing speed affords the clinician an opportunity to better position the jaw assembly 7100 while clamping the tissue. Alternatively, the control system 1800 can open the jaw assembly 7100 at a slower speed. In such instances, the slower opening speed reduces the possibility of the opening jaws colliding with adjacent tissue. In either event, the control system 1800 can decrease the duration of the voltage pulses and/or increase the duration between the voltage pulses to slow down and/or speed up the movement of the jaw assembly 7100.

[0153] As discussed above, the control system 1800 is configured to interpret the position of the clamping trigger 2610 as a command to position the jaw assembly 7100 in a specific configuration. For instance, the control system 1800 is configured to interpret the proximal-

most position of the clamping trigger 2610 as a command to close the jaw assembly 7100 and any other position of the clamping trigger as a command to open the jaw assembly 7100. That said, the control system 1800 can be configured to interpret the position of the clamping trigger 2610 in a proximal range of positions, instead of a single position, as a command to close the jaw assembly 7100. Such an arrangement can allow the jaw assembly 7000 to be better responsive to the clinician's input. In such instances, the range of motion of the clamping trigger 2610 is divided into ranges - a proximal range which is interpreted as a command to close the jaw assembly 7100 and a distal range which is interpreted as a command to open the jaw assembly 7100. In at least one instance, the range of motion of the clamping trigger 2610 can have an intermediate range between the proximal range and the distal range. When the clamping trigger 2610 is in the intermediate range, the control system 1800 can interpret the position of the clamping trigger 2610 as a command to neither open nor close the jaw assembly 7100. Such an intermediate range can prevent, or reduce the possibility of, jitter between the opening and closing ranges. In the instances described above, the control system 1800 can be configured to ignore cumulative commands to open or close the jaw assembly 7100. For instance, if the closure trigger 2610 has already been fully retracted into its proximal-most position, the control assembly 1800 can ignore the motion of the clamping trigger 2610 in the proximal, or clamping, range until the clamping trigger 2610 enters into the distal, or opening, range wherein, at such point, the control system 1800 can then actuate the electric motor 1610 to open the jaw assembly 7100.

[0154] In certain instances, further to the above, the position of the clamping trigger 2610 within the clamping trigger range, or at least a portion of the clamping trigger range, can allow the clinician to control the speed of the electric motor 1610 and, thus, the speed in which the jaw assembly 7100 is being opened or closed by the control assembly 1800. In at least one instance, the sensor 2115 comprises a Hall Effect sensor, and/or any other suitable sensor, configured to detect the position of the clamping trigger 2610 between its distal, unactuated position and its proximal, fully-actuated position. The Hall Effect sensor is configured to transmit a signal to the handle control system 1800 via the shaft control system 2800 such that the handle control system 1800 can control the speed of the electric motor 1610 in response to the position of the clamping trigger 2610. In at least one instance, the handle control system 1800 controls the speed of the electric motor 1610 proportionately, or in a linear manner, to the position of the clamping trigger 2610. For example, if the clamping trigger 2610 is moved half way through its range, then the handle control system 1800 will operate the electric motor 1610 at half of the speed in which the electric motor 1610 is operated when the clamping trigger 2610 is fully-retracted. Similarly, if the clamping trigger 2610 is moved a quarter way through its range, then the handle control system 1800 will

operate the electric motor 1610 at a quarter of the speed in which the electric motor 1610 is operated when the clamping trigger 2610 is fully-retracted. Other embodiments are envisioned in which the handle control system 1800 controls the speed of the electric motor 1610 in a non-linear manner to the position of the clamping trigger 2610. In at least one instance, the control system 1800 operates the electric motor 1610 slowly in the distal portion of the clamping trigger range while quickly accelerating the speed of the electric motor 1610 in the proximal portion of the clamping trigger range.

[0155] As described above, the clamping trigger 2610 is movable to operate the electric motor 1610 to open or close the jaw assembly 7100 of the end effector 7000. The electric motor 1610 is also operable to rotate the end effector 7000 about a longitudinal axis and articulate the end effector 7000 relative to the elongate shaft 2200 about the articulation joint 2300 of the shaft assembly 2000. Referring primarily to FIGS. 7 and 8, the drive module 1100 comprises an input system 1400 including a rotation actuator 1420 and an articulation actuator 1430. The input system 1400 further comprises a printed circuit board (PCB) 1410 which is in signal communication with the printed circuit board (PCB) 1810 of the control system 1800. The drive module 1100 comprises an electrical circuit, such as a flexible wiring harness or ribbon, for example, which permits the input system 1400 to communicate with the control system 1800. The rotation actuator 1420 is rotatably supported on the housing 1110 and is in signal communication with the input board 1410 and/or control board 1810, as described in greater detail below. The articulation actuator 1430 is supported by and in signal communication with the input board 1410 and/or control board 1810, as also described in greater detail below.

[0156] Referring primarily to FIGS. 8, 10, and 11, further to the above, the handle housing 1110 comprises an annular groove or slot defined therein adjacent the distal mounting interface 1130. The rotation actuator 1420 comprises an annular ring 1422 rotatably supported within the annular groove and, owing to the configuration of the sidewalls of the annular groove, the annular ring 1422 is constrained from translating longitudinally and/or laterally with respect to the handle housing 1110. The annular ring 1422 is rotatable in a first, or clockwise, direction and a second, or counter-clockwise direction, about a longitudinal axis extending through the frame 1500 of the drive module 1100. The rotation actuator 1420 comprises one or more sensors configured to detect the rotation of the annular ring 1422. In at least one instance, the rotation actuator 1420 comprises a first sensor positioned on a first side of the drive module 1100 and a second sensor positioned on a second, or opposite, side of the drive module 1100 and the annular ring 1422 comprises a detectable element which is detectable by the first and second sensors. The first sensor is configured to detect when the annular ring 1422 is rotated in the first direction and the second sensor is configured to detect when the annular ring 1422 is rotated in the

second direction. When the first sensor detects that the annular ring 1422 is rotated in the first direction, the handle control system 1800 rotates the handle drive shaft 1710, the drive shaft 2710, and the end effector 7000 in the first direction, as described in greater detail below. Similarly, the handle control system 1800 rotates the handle drive shaft 1710, the drive shaft 2710, and the end effector 7000 in the second direction when the second sensor detects that the annular ring 1422 is rotated in the second direction. In view of the above, the reader should appreciate that the clamping trigger 2610 and the rotation actuator 1420 are both operable to rotate the drive shaft 2710.

[0157] In various embodiments, further to the above, the first and second sensors comprise switches which are mechanically closable by the detectable element of the annular ring 1422. When the annular ring 1422 is rotated in the first direction from a center position, the detectable element closes the switch of the first sensor. When the switch of the first sensor is closed, the control system 1800 operates the electric motor 1610 to rotate the end effector 7000 in the first direction. When the annular ring 1422 is rotated in the second direction toward the center position, the detectable element is disengaged from the first switch and the first switch is re-opened. Once the first switch is re-opened, the control system 1800 cuts the power to the electric motor 1610 to stop the rotation of the end effector 7000. Similarly, the detectable element closes the switch of the second sensor when the annular ring 1422 is rotated in the second direction from the center position. When the switch of the second sensor is closed, the control system 1800 operates the electric motor 1610 to rotate the end effector 7000 in the second direction. When the annular ring 1422 is rotated in the first direction toward the center position, the detectable element is disengaged from the second switch and the second switch is re-opened. Once the second switch is re-opened, the control system 1800 cuts the power to the electric motor 1610 to stop the rotation of the end effector 7000.

[0158] In various embodiments, further to the above, the first and second sensors of the rotation actuator 1420 comprise proximity sensors, for example. In certain embodiments, the first and second sensors of the rotation actuator 1420 comprise Hall Effect sensors, and/or any suitable sensors, configured to detect the distance between the detectable element of the annular ring 1422 and the first and second sensors. If the first Hall Effect sensor detects that the annular ring 1422 has been rotated in the first direction, then, as discussed above, the control system 1800 will rotate the end effector 7000 in the first direction. In addition, the control system 1800 can rotate the end effector 7000 at a faster speed when the detectable element is closer to the first Hall Effect sensor than when the detectable element is further away from the first Hall Effect sensor. If the second Hall Effect sensor detects that the annular ring 1422 has been rotated in the second direction, then, as discussed above, the control system 1800 will rotate the end effector 7000 in the second

direction. In addition, the control system 1800 can rotate the end effector 7000 at a faster speed when the detectable element is closer to the second Hall Effect sensor than when the detectable element is further away from the second Hall Effect sensor. As a result, the speed in which the end effector 7000 is rotated is a function of the amount, or degree, in which the annular ring 1422 is rotated. The control system 1800 is further configured to evaluate the inputs from both the first and second Hall Effect sensors when determining the direction and speed in which to rotate the end effector 7000. In various instances, the control system 1800 can use the closest Hall Effect sensor to the detectable element of the annular ring 1422 as a primary source of data and the Hall Effect sensor furthest away from the detectable element as a confirmational source of data to double-check the data provided by the primary source of data. The control system 1800 can further comprise a data integrity protocol to resolve situations in which the control system 1800 is provided with conflicting data. In any event, the handle control system 1800 can enter into a neutral state in which the handle control system 1800 does not rotate the end effector 7000 when the Hall Effect sensors detect that the detectable element is in its center position, or in a position which is equidistant between the first Hall Effect sensor and the second Hall Effect sensor. In at least one such instance, the control system 1800 can enter into its neutral state when the detectable element is in a central range of positions. Such an arrangement would prevent, or at least reduce the possibility of, rotational jitter when the clinician is not intending to rotate the end effector 7000.

[0159] Further to the above, the rotation actuator 1420 can comprise one or more springs configured to center, or at least substantially center, the rotation actuator 1420 when it is released by the clinician. In such instances, the springs can act to shut off the electric motor 1610 and stop the rotation of the end effector 7000. In at least one instance, the rotation actuator 1420 comprises a first torsion spring configured to rotate the rotation actuator 1420 in the first direction and a second torsion spring configured to rotate the rotation actuator 1420 in the second direction. The first and second torsion springs can have the same, or at least substantially the same, spring constant such that the forces and/or torques applied by the first and second torsion springs balance, or at least substantially balance, the rotation actuator 1420 in its center position.

[0160] In view of the above, the reader should appreciate that the clamping trigger 2610 and the rotation actuator 1420 are both operable to rotate the drive shaft 2710 and either, respectively, operate the jaw assembly 7100 or rotate the end effector 7000. The system that uses the rotation of the drive shaft 2710 to selectively perform these functions is described in greater detail below.

[0161] Referring to FIGS. 7 and 8, the articulation actuator 1430 comprises a first push button 1432 and a second push button 1434. The first push button 1432 is part of a first

articulation control circuit and the second push button 1434 is part of a second articulation circuit of the input system 1400. The first push button 1432 comprises a first switch that is closed when the first push button 1432 is depressed. The handle control system 1800 is configured to sense the closure of the first switch and, moreover, the closure of the first articulation control circuit. When the handle control system 1800 detects that the first articulation control circuit has been closed, the handle control system 1800 operates the electric motor 1610 to articulate the end effector 7000 in a first articulation direction about the articulation joint 2300. When the first push button 1432 is released by the clinician, the first articulation control circuit is opened which, once detected by the control system 1800, causes the control system 1800 to cut the power to the electric motor 1610 to stop the articulation of the end effector 7000.

[0162] In various instances, further to the above, the articulation range of the end effector 7000 is limited and the control system 1800 can utilize the encoder system discussed above for monitoring the rotational output of the electric motor 1610, for example, to monitor the amount, or degree, in which the end effector 7000 is rotated in the first direction. In addition to or in lieu of the encoder system, the shaft assembly 2000 can comprise a first sensor configured to detect when the end effector 7000 has reached the limit of its articulation in the first direction. In any event, when the control system 1800 determines that the end effector 7000 has reached the limit of articulation in the first direction, the control system 1800 can cut the power to the electric motor 1610 to stop the articulation of the end effector 7000.

[0163] Similar to the above, the second push button 1434 comprises a second switch that is closed when the second push button 1434 is depressed. The handle control system 1800 is configured to sense the closure of the second switch and, moreover, the closure of the second articulation control circuit. When the handle control system 1800 detects that the second articulation control circuit has been closed, the handle control system 1800 operates the electric motor 1610 to articulate the end effector 7000 in a second direction about the articulation joint 2300. When the second push button 1434 is released by the clinician, the second articulation control circuit is opened which, once detected by the control system 1800, causes the control system 1800 to cut the power to the electric motor 1610 to stop the articulation of the end effector 7000.

[0164] In various instances, the articulation range of the end effector 7000 is limited and the control system 1800 can utilize the encoder system discussed above for monitoring the rotational output of the electric motor 1610, for example, to monitor the amount, or degree, in which the end effector 7000 is rotated in the second direction. In addition to or in lieu of the encoder system, the shaft assembly 2000 can comprise a second sensor configured to detect when the end effector 7000 has reached the limit of its articulation in the second direction. In any event, when the control system 1800 determines that the end effector 7000

has reached the limit of articulation in the second direction, the control system 1800 can cut the power to the electric motor 1610 to stop the articulation of the end effector 7000.

[0165] As described above, the end effector 7000 is articulatable in a first direction (FIG. 16) and/or a second direction (FIG. 17) from a center, or unarticulated, position (FIG. 15).

5 Once the end effector 7000 has been articulated, the clinician can attempt to re-center the end effector 7000 by using the first and second articulation push buttons 1432 and 1434. As the reader can appreciate, the clinician may struggle to re-center the end effector 7000 as, for instance, the end effector 7000 may not be entirely visible once it is positioned in the patient. In some instances, the end effector 7000 may not fit back through a trocar if the end
10 effector 7000 is not re-centered, or at least substantially re-centered. With that in mind, the control system 1800 is configured to provide feedback to the clinician when the end effector 7000 is moved into its unarticulated, or centered, position. In at least one instance, the feedback comprises audio feedback and the handle control system 1800 can comprise a speaker which emits a sound, such as a beep, for example, when the end effector 7000 is
15 centered. In certain instances, the feedback comprises visual feedback and the handle control system 1800 can comprise a light emitting diode (LED), for example, positioned on the handle housing 1110 which flashes when the end effector 7000 is centered. In various instances, the feedback comprises haptic feedback and the handle control system 1800 can comprise an electric motor comprising an eccentric element which vibrates the handle 1000
20 when the end effector 7000 is centered. Manually re-centering the end effector 7000 in this way can be facilitated by the control system 1800 slowing the motor 1610 when the end effector 7000 is approaching its centered position. In at least one instance, the control system 1800 slows the articulation of the end effector 7000 when the end effector 7000 is within approximately 5 degrees of center in either direction, for example.

25 **[0166]** In addition to or in lieu of the above, the handle control system 1800 can be configured to re-center the end effector 7000. In at least one such instance, the handle control system 1800 can re-center the end effector 7000 when both of the articulation buttons 1432 and 1434 of the articulation actuator 1430 are depressed at the same time. When the handle control system 1800 comprises an encoder system configured to monitor
30 the rotational output of the electric motor 1610, for example, the handle control system 1800 can determine the amount and direction of articulation needed to re-center, or at least substantially re-center, the end effector 7000. In various instances, the input system 1400 can comprise a home button, for example, which, when depressed, automatically centers the end effector 7000.

35 **[0167]** Referring primarily to FIGS. 5 and 6, the elongate shaft 2200 of the shaft assembly 2000 comprises an outer housing, or tube, 2210 mounted to the proximal housing 2110 of the proximal portion 2100. The outer housing 2210 comprises a longitudinal aperture 2230

extending therethrough and a proximal flange 2220 which secures the outer housing 2210 to the proximal housing 2110. The frame 2500 of the shaft assembly 2000 extends through the longitudinal aperture 2230 of the elongate shaft 2200. More specifically, the shaft 2510 of the shaft frame 2500 necks down into a smaller shaft 2530 which extends through the longitudinal aperture 2230. That said, the shaft frame 2500 can comprise any suitable arrangement. The drive system 2700 of the shaft assembly 2000 also extends through the longitudinal aperture 2230 of the elongate shaft 2200. More specifically, the drive shaft 2710 of the shaft drive system 2700 necks down into a smaller drive shaft 2730 which extends through the longitudinal aperture 2230. That said, the shaft drive system 2700 can comprise any suitable arrangement.

[0168] Referring primarily to FIGS. 20, 23, and 24, the outer housing 2210 of the elongate shaft 2200 extends to the articulation joint 2300. The articulation joint 2300 comprises a proximal frame 2310 mounted to the outer housing 2210 such that there is little, if any, relative translation and/or rotation between the proximal frame 2310 and the outer housing 2210. Referring primarily to FIG. 22, the proximal frame 2310 comprises an annular portion 2312 mounted to the sidewall of the outer housing 2210 and tabs 2314 extending distally from the annular portion 2312. The articulation joint 2300 further comprises links 2320 and 2340 which are rotatably mounted to the frame 2310 and mounted to an outer housing 2410 of the distal attachment portion 2400. The link 2320 comprises a distal end 2322 mounted to the outer housing 2410. More specifically, the distal end 2322 of the link 2320 is received and fixedly secured within a mounting slot 2412 defined in the outer housing 2410. Similarly, the link 2340 comprises a distal end 2342 mounted to the outer housing 2410. More specifically, the distal end 2342 of the link 2340 is received and fixedly secured within a mounting slot defined in the outer housing 2410. The link 2320 comprises a proximal end 2324 rotatably coupled to a tab 2314 of the proximal articulation frame 2310. Although not illustrated in FIG. 22, a pin extends through apertures defined in the proximal end 2324 and the tab 2314 to define a pivot axis therebetween. Similarly, the link 2340 comprises a proximal end 2344 rotatably coupled to a tab 2314 of the proximal articulation frame 2310. Although not illustrated in FIG. 22, a pin extends through apertures defined in the proximal end 2344 and the tab 2314 to define a pivot axis therebetween. These pivot axes are collinear, or at least substantially collinear, and define an articulation axis A of the articulation joint 2300.

[0169] Referring primarily to FIGS. 20, 23, and 24, the outer housing 2410 of the distal attachment portion 2400 comprises a longitudinal aperture 2430 extending therethrough. The longitudinal aperture 2430 is configured to receive a proximal attachment portion 7400 of the end effector 7000. The end effector 7000 comprises an outer housing 6230 which is closely received within the longitudinal aperture 2430 of the distal attachment portion 2400

such that there is little, if any, relative radial movement between the proximal attachment portion 7400 of the end effector 7000 and the distal attachment portion 2400 of the shaft assembly 2000. The proximal attachment portion 7400 further comprises an annular array of lock notches 7410 defined on the outer housing 6230 which is releasably engaged by an end effector lock 6400 in the distal attachment portion 2400 of the shaft assembly 2000. When the end effector lock 6400 is engaged with the array of lock notches 7410, the end effector lock 6400 prevents, or at least inhibits, relative longitudinal movement between the proximal attachment portion 7400 of the end effector 7000 and the distal attachment portion 2400 of the shaft assembly 2000. As a result of the above, only relative rotation between the proximal attachment portion 7400 of the end effector 7000 and the distal attachment portion 2400 of the shaft assembly 2000 is permitted. To this end, the outer housing 6230 of the end effector 7000 is closely received within the longitudinal aperture 2430 defined in the distal attachment portion 2400 of the shaft assembly 2000.

[0170] Further to the above, referring to FIG. 21, the outer housing 6230 further comprises an annular slot, or recess, 6270 defined therein which is configured to receive an O-ring 6275 therein. The O-ring 6275 is compressed between the outer housing 6230 and the sidewall of the longitudinal aperture 2430 when the end effector 7000 is inserted into the distal attachment portion 2400. The O-ring 6275 is configured to resist, but permit, relative rotation between the end effector 7000 and the distal attachment portion 2400 such that the O-ring 6275 can prevent, or reduce the possibility of, unintentional relative rotation between the end effector 7000 and the distal attachment portion 2400. In various instances, the O-ring 6275 can provide a seal between the end effector 7000 and the distal attachment portion 2400 to prevent, or at least reduce the possibility of, fluid ingress into the shaft assembly 2000, for example.

[0171] Referring to FIGS. 14-21, the jaw assembly 7100 of the end effector 7000 comprises a first jaw 7110 and a second jaw 7120. Each jaw 7110, 7120 comprises a distal end which is configured to assist a clinician in dissecting tissue with the end effector 7000. Each jaw 7110, 7120 further comprises a plurality of teeth which are configured to assist a clinician in grasping and holding onto tissue with the end effector 7000. Moreover, referring primarily to FIG. 21, each jaw 7110, 7120 comprises a proximal end, i.e., proximal ends 7115, 7125, respectively, which rotatably connect the jaws 7110, 7120 together. Each proximal end 7115, 7125 comprises an aperture extending therethrough which is configured to closely receive a pin 7130 therein. The pin 7130 comprises a central body 7135 closely received within the apertures defined in the proximal ends 7115, 7125 of the jaws 7110, 7120 such that there is little, if any, relative translation between the jaws 7110, 7120 and the pin 7130. The pin 7130 defines a jaw axis J about which the jaws 7110, 7120 can be rotated and, also, rotatably mounts the jaws 7110, 7120 to the outer housing 6230 of the end

effector 7000. More specifically, the outer housing 6230 comprises distally-extending tabs 6235 having apertures defined therein which are also configured to closely receive the pin 7130 such that the jaw assembly 7100 does not translate relative to a shaft portion 7200 of the end effector 7000. The pin 7130 further comprises enlarged ends which prevent the jaws 7110, 7120 from becoming detached from the pin 7130 and also prevents the jaw assembly 7100 from becoming detached from the shaft portion 7200. This arrangement defines a rotation joint 7300.

[0172] Referring primarily to FIGS. 21 and 23, the jaws 7110 and 7120 are rotatable between their open and closed positions by a jaw assembly drive including drive links 7140, a drive nut 7150, and a drive screw 6130. As described in greater detail below, the drive screw 6130 is selectively rotatable by the drive shaft 2730 of the shaft drive system 2700. The drive screw 6130 comprises an annular flange 6132 which is closely received within a slot, or groove, 6232 (FIG. 25) defined in the outer housing 6230 of the end effector 7000. The sidewalls of the slot 6232 are configured to prevent, or at least inhibit, longitudinal and/or radial translation between the drive screw 6130 and the outer housing 6230, but yet permit relative rotational motion between the drive screw 6130 and the outer housing 6230. The drive screw 6130 further comprises a threaded end 6160 which is threadably engaged with a threaded aperture 7160 defined in the drive nut 7150. The drive nut 7150 is constrained from rotating with the drive screw 6130 and, as a result, the drive nut 7150 is translated when the drive screw 6130 is rotated. In use, the drive screw 6130 is rotated in a first direction to displace the drive nut 7150 proximally and in a second, or opposite, direction to displace the drive nut 7150 distally. The drive nut 7150 further comprises a distal end 7155 comprising an aperture defined therein which is configured to closely receive pins 7145 extending from the drive links 7140. Referring primarily to FIG. 21, a first drive link 7140 is attached to one side of the distal end 7155 and a second drive link 7140 is attached to the opposite side of the distal end 7155. The first drive link 7140 comprises another pin 7145 extending therefrom which is closely received in an aperture defined in the proximal end 7115 of the first jaw 7110 and, similarly, the second drive link 7140 comprises another pin extending therefrom which is closely received in an aperture defined in the proximal end 7125 of the second jaw 7120. As a result of the above, the drive links 7140 operably connect the jaws 7110 and 7120 to the drive nut 7150. When the drive nut 7150 is driven proximally by the drive screw 6130, as described above, the jaws 7110, 7120 are rotated into the closed, or clamped, configuration. Correspondingly, the jaws 7110, 7120 are rotated into their open configuration when the drive nut 7150 is driven distally by the drive screw 6130.

[0173] As discussed above, the control system 1800 is configured to actuate the electric motor 1610 to perform three different end effector functions - clamping/opening the jaw

assembly 7100 (FIGS. 14 and 15), rotating the end effector 7000 about a longitudinal axis (FIGS. 18 and 19), and articulating the end effector 7000 about an articulation axis (FIGS. 16 and 17). Referring primarily to FIGS. 26 and 27, the control system 1800 is configured to operate a transmission 6000 to selectively perform these three end effector functions. The transmission 6000 comprises a first clutch system 6100 configured to selectively transmit the rotation of the drive shaft 2730 to the drive screw 6130 of the end effector 7000 to open or close the jaw assembly 7100, depending on the direction in which the drive shaft 2730 is rotated. The transmission 6000 further comprises a second clutch system 6200 configured to selectively transmit the rotation of the drive shaft 2730 to the outer housing 6230 of the end effector 7000 to rotate the end effector 7000 about the longitudinal axis L. The transmission 6000 also comprises a third clutch system 6300 configured to selectively transmit the rotation of the drive shaft 2730 to the articulation joint 2300 to articulate the distal attachment portion 2400 and the end effector 7000 about the articulation axis A. The clutch systems 6100, 6200, and 6300 are in electrical communication with the control system 1800 via electrical circuits extending through the shaft 2510, the connector pins 2520, the connector pins 1520, and the shaft 1510, for example. In at least one instance, each of these clutch control circuits comprises two connector pins 2520 and two connector pins 1520, for example.

[0174] In various instances, further to the above, the shaft 2510 and/or the shaft 1510 comprise a flexible circuit including electrical traces which form part of the clutch control circuits. The flexible circuit can comprise a ribbon, or substrate, with conductive pathways defined therein and/or thereon. The flexible circuit can also comprise sensors and/or any solid state component, such as signal smoothing capacitors, for example, mounted thereto. In at least one instance, each of the conductive pathways can comprise one or more signal smoothing capacitors which can, among other things, even out fluctuations in signals transmitted through the conductive pathways. In various instances, the flexible circuit can be coated with at least one material, such as an elastomer, for example, which can seal the flexible circuit against fluid ingress.

[0175] Referring primarily to FIG. 28, the first clutch system 6100 comprises a first clutch 6110, an expandable first drive ring 6120, and a first electromagnetic actuator 6140. The first clutch 6110 comprises an annular ring and is slideably disposed on the drive shaft 2730. The first clutch 6110 is comprised of a magnetic material and is movable between a disengaged, or unactuated, position (FIG. 28) and an engaged, or actuated, position (FIG. 29) by electromagnetic fields EF generated by the first electromagnetic actuator 6140. In various instances, the first clutch 6110 is at least partially comprised of iron and/or nickel, for example. In at least one instance, the first clutch 6110 comprises a permanent magnet. As illustrated in FIG. 22A, the drive shaft 2730 comprises one or more longitudinal key slots

6115 defined therein which are configured to constrain the longitudinal movement of the clutch 6110 relative to the drive shaft 2730. More specifically, the clutch 6110 comprises one or more keys extending into the key slots 6115 such that the distal ends of the key slots 6115 stop the distal movement of the clutch 6110 and the proximal ends of the key slots 6115 stop the proximal movement of the clutch 6110.

[0176] When the first clutch 6110 is in its disengaged position (FIG. 28), the first clutch 6110 rotates with the drive shaft 2130 but does not transmit rotational motion to the first drive ring 6120. As can be seen in FIG. 28, the first clutch 6110 is separated from, or not in contact with, the first drive ring 6120. As a result, the rotation of the drive shaft 2730 and the first clutch 6110 is not transmitted to the drive screw 6130 when the first clutch assembly 6100 is in its disengaged state. When the first clutch 6110 is in its engaged position (FIG. 29), the first clutch 6110 is engaged with the first drive ring 6120 such that the first drive ring 6120 is expanded, or stretched, radially outwardly into contact with the drive screw 6130. In at least one instance, the first drive ring 6120 comprises an elastomeric band, for example. As can be seen in FIG. 29, the first drive ring 6120 is compressed against an annular inner sidewall 6135 of the drive screw 6130. As a result, the rotation of the drive shaft 2730 and the first clutch 6110 is transmitted to the drive screw 6130 when the first clutch assembly 6100 is in its engaged state. Depending on the direction in which the drive shaft 2730 is rotated, the first clutch assembly 6100 can move the jaw assembly 7100 into its open and closed configurations when the first clutch assembly 6100 is in its engaged state.

[0177] As described above, the first electromagnetic actuator 6140 is configured to generate magnetic fields to move the first clutch 6110 between its disengaged (FIG. 28) and engaged (FIG. 29) positions. For instance, referring to FIG. 28, the first electromagnetic actuator 6140 is configured to emit a magnetic field EF_L which repulses, or drives, the first clutch 6110 away from the first drive ring 6120 when the first clutch assembly 6100 is in its disengaged state. The first electromagnetic actuator 6140 comprises one or more wound coils in a cavity defined in the shaft frame 2530 which generate the magnetic field EF_L when current flows in a first direction through a first electrical clutch circuit including the wound coils. The control system 1800 is configured to apply a first voltage polarity to the first electrical clutch circuit to create the current flowing in the first direction. The control system 1800 can continuously apply the first voltage polarity to the first electric shaft circuit to continuously hold the first clutch 6110 in its disengaged position. While such an arrangement can prevent the first clutch 6110 from unintentionally engaging the first drive ring 6120, such an arrangement can also consume a lot of power. Alternatively, the control system 1800 can apply the first voltage polarity to the first electrical clutch circuit for a sufficient period of time to position the first clutch 6110 in its disengaged position and then discontinue applying the first voltage polarity to the first electric clutch circuit, thereby resulting in a lower consumption

of power. That being said, the first clutch assembly 6100 further comprises a first clutch lock 6150 mounted in the drive screw 6130 which is configured to releasably hold the first clutch 6110 in its disengaged position. The first clutch lock 6150 is configured to prevent, or at least reduce the possibility of, the first clutch 6110 from becoming unintentionally engaged with the first drive ring 6120. When the first clutch 6110 is in its disengaged position, as illustrated in FIG. 28, the first clutch lock 6150 interferes with the free movement of the first clutch 6110 and holds the first clutch 6110 in position via a friction force and/or an interference force therebetween. In at least one instance, the first clutch lock 6150 comprises an elastomeric plug, seat, or detent, comprised of rubber, for example. In certain instances, the first clutch lock 6150 comprises a permanent magnet which holds the first clutch 6110 in its disengaged position by an electromagnetic force. In any event, the first electromagnetic actuator 6140 can apply an electromagnetic pulling force to the first clutch 6110 that overcomes these forces, as described in greater detail below.

[0178] Further to the above, referring to FIG. 29, the first electromagnetic actuator 6140 is configured to emit a magnetic field EF_D which pulls, or drives, the first clutch 6110 toward the first drive ring 6120 when the first clutch assembly 6100 is in its engaged state. The coils of the first electromagnetic actuator 6140 generate the magnetic field EF_D when current flows in a second, or opposite, direction through the first electrical clutch circuit. The control system 1800 is configured to apply an opposite voltage polarity to the first electrical clutch circuit to create the current flowing in the opposite direction. The control system 1800 can continuously apply the opposite voltage polarity to the first electrical clutch circuit to continuously hold the first clutch 6110 in its engaged position and maintain the operable engagement between the first drive ring 6120 and the drive screw 6130. Alternatively, the first clutch 6110 can be configured to become wedged within the first drive ring 6120 when the first clutch 6110 is in its engaged position and, in such instances, the control system 1800 may not need to continuously apply a voltage polarity to the first electrical clutch circuit to hold the first clutch assembly 6100 in its engaged state. In such instances, the control system 1800 can discontinue applying the voltage polarity once the first clutch 6110 has been sufficiently wedged in the first drive ring 6120.

[0179] Notably, further to the above, the first clutch lock 6150 is also configured to lockout the jaw assembly drive when the first clutch 6110 is in its disengaged position. More specifically, referring again to FIG. 28, the first clutch 6110 pushes the first clutch lock 6150 in the drive screw 6130 into engagement with the outer housing 6230 of the end effector 7000 when the first clutch 6110 is in its disengaged position such that the drive screw 6130 does not rotate, or at least substantially rotate, relative to the outer housing 6230. The outer housing 6230 comprises a slot 6235 defined therein which is configured to receive the first clutch lock 6150. When the first clutch 6110 is moved into its engaged position, referring to

FIG. 29, the first clutch 6110 is no longer engaged with the first clutch lock 6150 and, as a result, the first clutch lock 6150 is no longer biased into engagement with the outer housing 6230 and the drive screw 6130 can rotate freely with respect to the outer housing 6230. As a result of the above, the first clutch 6110 can do at least two things - operate the jaw drive when the first clutch 6110 is in its engaged position and lock out the jaw drive when the first clutch 6110 is in its disengaged position.

[0180] Moreover, further to the above, the threads of the threaded portions 6160 and 7160 can be configured to prevent, or at least resist, backdriving of the jaw drive. In at least one instance, the thread pitch and/or angle of the threaded portions 6160 and 7160, for example, can be selected to prevent the backdriving, or unintentional opening, of the jaw assembly 7100. As a result of the above, the possibility of the jaw assembly 7100 unintentionally opening or closing is prevented, or at least reduced.

[0181] Referring primarily to FIG. 30, the second clutch system 6200 comprises a second clutch 6210, an expandable second drive ring 6220, and a second electromagnetic actuator 6240. The second clutch 6210 comprises an annular ring and is slideably disposed on the drive shaft 2730. The second clutch 6210 is comprised of a magnetic material and is movable between a disengaged, or unactuated, position (FIG. 30) and an engaged, or actuated, position (FIG. 31) by electromagnetic fields EF generated by the second electromagnetic actuator 6240. In various instances, the second clutch 6210 is at least partially comprised of iron and/or nickel, for example. In at least one instance, the second clutch 6210 comprises a permanent magnet. As illustrated in FIG. 22A, the drive shaft 2730 comprises one or more longitudinal key slots 6215 defined therein which are configured to constrain the longitudinal movement of the second clutch 6210 relative to the drive shaft 2730. More specifically, the second clutch 6210 comprises one or more keys extending into the key slots 6215 such that the distal ends of the key slots 6215 stop the distal movement of the second clutch 6210 and the proximal ends of the key slots 6215 stop the proximal movement of the second clutch 6210.

[0182] When the second clutch 6210 is in its disengaged position, referring to FIG. 30, the second clutch 6210 rotates with the drive shaft 2730 but does not transmit rotational motion to the second drive ring 6220. As can be seen in FIG. 30, the second clutch 6210 is separated from, or not in contact with, the second drive ring 6220. As a result, the rotation of the drive shaft 2730 and the second clutch 6210 is not transmitted to the outer housing 6230 of the end effector 7000 when the second clutch assembly 6200 is in its disengaged state. When the second clutch 6210 is in its engaged position (FIG. 31), the second clutch 6210 is engaged with the second drive ring 6220 such that the second drive ring 6220 is expanded, or stretched, radially outwardly into contact with the outer housing 6230. In at least one instance, the second drive ring 6220 comprises an elastomeric band, for example. As can

be seen in FIG. 31, the second drive ring 6220 is compressed against an annular inner sidewall 7415 of the outer housing 6230. As a result, the rotation of the drive shaft 2730 and the second clutch 6210 is transmitted to the outer housing 6230 when the second clutch assembly 6200 is in its engaged state. Depending on the direction in which the drive shaft 2730 is rotated, the second clutch assembly 6200 can rotate the end effector 7000 in a first direction or a second direction about the longitudinal axis L when the second clutch assembly 6200 is in its engaged state.

[0183] As described above, the second electromagnetic actuator 6240 is configured to generate magnetic fields to move the second clutch 6210 between its disengaged (FIG. 30) and engaged (FIG. 31) positions. For instance, the second electromagnetic actuator 6240 is configured to emit a magnetic field EF_L which repulses, or drives, the second clutch 6210 away from the second drive ring 6220 when the second clutch assembly 6200 is in its disengaged state. The second electromagnetic actuator 6240 comprises one or more wound coils in a cavity defined in the shaft frame 2530 which generate the magnetic field EF_L when current flows in a first direction through a second electrical clutch circuit including the wound coils. The control system 1800 is configured to apply a first voltage polarity to the second electrical clutch circuit to create the current flowing in the first direction. The control system 1800 can continuously apply the first voltage polarity to the second electric clutch circuit to continuously hold the second clutch 6210 in its disengaged position. While such an arrangement can prevent the second clutch 6210 from unintentionally engaging the second drive ring 6220, such an arrangement can also consume a lot of power. Alternatively, the control system 1800 can apply the first voltage polarity to the second electrical clutch circuit for a sufficient period of time to position the second clutch 6210 in its disengaged position and then discontinue applying the first voltage polarity to the second electric clutch circuit, thereby resulting in a lower consumption of power. That being said, the second clutch assembly 6200 further comprises a second clutch lock 6250 mounted in the outer housing 6230 which is configured to releasably hold the second clutch 6210 in its disengaged position. Similar to the above, the second clutch lock 6250 can prevent, or at least reduce the possibility of, the second clutch 6210 from becoming unintentionally engaged with the second drive ring 6220. When the second clutch 6210 is in its disengaged position, as illustrated in FIG. 30, the second clutch lock 6250 interferes with the free movement of the second clutch 6210 and holds the second clutch 6210 in position via a friction and/or interference force therebetween. In at least one instance, the second clutch lock 6250 comprises an elastomeric plug, seat, or detent, comprised of rubber, for example. In certain instances, the second clutch lock 6250 comprises a permanent magnet which holds the second clutch 6210 in its disengaged position by an electromagnetic force. That said, the

second electromagnetic actuator 6240 can apply an electromagnetic pulling force to the second clutch 6210 that overcomes these forces, as described in greater detail below.

[0184] Further to the above, referring to FIG. 31, the second electromagnetic actuator 6240 is configured to emit a magnetic field EF_D which pulls, or drives, the second clutch 6210 toward the second drive ring 6220 when the second clutch assembly 6200 is in its engaged state. The coils of the second electromagnetic actuator 6240 generate the magnetic field EF_D when current flows in a second, or opposite, direction through the second electrical shaft circuit. The control system 1800 is configured to apply an opposite voltage polarity to the second electrical shaft circuit to create the current flowing in the opposite direction. The control system 1800 can continuously apply the opposite voltage polarity to the second electric shaft circuit to continuously hold the second clutch 6210 in its engaged position and maintain the operable engagement between the second drive ring 6220 and the outer housing 6230. Alternatively, the second clutch 6210 can be configured to become wedged within the second drive ring 6220 when the second clutch 6210 is in its engaged position and, in such instances, the control system 1800 may not need to continuously apply a voltage polarity to the second shaft electrical circuit to hold the second clutch assembly 6200 in its engaged state. In such instances, the control system 1800 can discontinue applying the voltage polarity once the second clutch 6210 has been sufficiently wedged in the second drive ring 6220.

[0185] Notably, further to the above, the second clutch lock 6250 is also configured to lockout the rotation of the end effector 7000 when the second clutch 6210 is in its disengaged position. More specifically, referring again to FIG. 30, the second clutch 6210 pushes the second clutch lock 6250 in the outer shaft 6230 into engagement with the articulation link 2340 when the second clutch 6210 is in its disengaged position such that the end effector 7000 does not rotate, or at least substantially rotate, relative to the distal attachment portion 2400 of the shaft assembly 2000. As illustrated in FIG. 27, the second clutch lock 6250 is positioned or wedged within a slot, or channel, 2345 defined in the articulation link 2340 when the second clutch 6210 is in its disengaged position. As a result of the above, the possibility of the end effector 7000 unintentionally rotating is prevented, or at least reduced. Moreover, as a result of the above, the second clutch 6210 can do at least two things - operate the end effector rotation drive when the second clutch 6210 is in its engaged position and lock out the end effector rotation drive when the second clutch 6210 is in its disengaged position.

[0186] Referring primarily to FIGS. 22, 24, and 25, the shaft assembly 2000 further comprises an articulation drive system configured to articulate the distal attachment portion 2400 and the end effector 7000 about the articulation joint 2300. The articulation drive system comprises an articulation drive 6330 rotatably supported within the distal attachment

portion 2400. That said, the articulation drive 6330 is closely received within the distal attachment portion 2400 such that the articulation drive 6330 does not translate, or at least substantially translate, relative to the distal attachment portion 2400. The articulation drive system of the shaft assembly 2000 further comprises a stationary gear 2330 fixedly mounted to the articulation frame 2310. More specifically, the stationary gear 2330 is fixedly mounted to a pin connecting a tab 2314 of the articulation frame 2310 and the articulation link 2340 such that the stationary gear 2330 does not rotate relative to the articulation frame 2310. The stationary gear 2330 comprises a central body 2335 and an annular array of stationary teeth 2332 extending around the perimeter of the central body 2335. The articulation drive 6330 comprises an annular array of drive teeth 6332 which is meshingly engaged with the stationary teeth 2332. When the articulation drive 6330 is rotated, the articulation drive 6330 pushes against the stationary gear 2330 and articulates the distal attachment portion 2400 of the shaft assembly 2000 and the end effector 7000 about the articulation joint 2300.

[0187] Referring primarily to FIG. 32, the third clutch system 6300 comprises a third clutch 6310, an expandable third drive ring 6320, and a third electromagnetic actuator 6340. The third clutch 6310 comprises an annular ring and is slideably disposed on the drive shaft 2730. The third clutch 6310 is comprised of a magnetic material and is movable between a disengaged, or unactuated, position (FIG. 32) and an engaged, or actuated, position (FIG. 33) by electromagnetic fields EF generated by the third electromagnetic actuator 6340. In various instances, the third clutch 6310 is at least partially comprised of iron and/or nickel, for example. In at least one instance, the third clutch 6310 comprises a permanent magnet. As illustrated in FIG. 22A, the drive shaft 2730 comprises one or more longitudinal key slots 6315 defined therein which are configured to constrain the longitudinal movement of the third clutch 6310 relative to the drive shaft 2730. More specifically, the third clutch 6310 comprises one or more keys extending into the key slots 6315 such that the distal ends of the key slots 6315 stop the distal movement of the third clutch 6310 and the proximal ends of the key slots 6315 stop the proximal movement of the third clutch 6310.

[0188] When the third clutch 6310 is in its disengaged position, referring to FIG. 32, the third clutch 6310 rotates with the drive shaft 2730 but does not transmit rotational motion to the third drive ring 6320. As can be seen in FIG. 32, the third clutch 6310 is separated from, or not in contact with, the third drive ring 6320. As a result, the rotation of the drive shaft 2730 and the third clutch 6310 is not transmitted to the articulation drive 6330 when the third clutch assembly 6300 is in its disengaged state. When the third clutch 6310 is in its engaged position, referring to FIG. 33, the third clutch 6310 is engaged with the third drive ring 6320 such that the third drive ring 6320 is expanded, or stretched, radially outwardly into contact with the articulation drive 6330. In at least one instance, the third drive ring 6320 comprises an elastomeric band, for example. As can be seen in FIG. 33, the third drive ring

6320 is compressed against an annular inner sidewall 6335 of the articulation drive 6330.

As a result, the rotation of the drive shaft 2730 and the third clutch 6310 is transmitted to the articulation drive 6330 when the third clutch assembly 6300 is in its engaged state.

Depending on the direction in which the drive shaft 2730 is rotated, the third clutch assembly

5 6300 can articulate the distal attachment portion 2400 of the shaft assembly 2000 and the end effector 7000 in a first or second direction about the articulation joint 2300.

[0189] As described above, the third electromagnetic actuator 6340 is configured to generate magnetic fields to move the third clutch 6310 between its disengaged (FIG. 32) and engaged (FIG. 33) positions. For instance, referring to FIG. 32, the third electromagnetic

10 actuator 6340 is configured to emit a magnetic field EF_L which repulses, or drives, the third clutch 6310 away from the third drive ring 6320 when the third clutch assembly 6300 is in its disengaged state. The third electromagnetic actuator 6340 comprises one or more wound coils in a cavity defined in the shaft frame 2530 which generate the magnetic field EF_L when

15 current flows in a first direction through a third electrical clutch circuit including the wound coils. The control system 1800 is configured to apply a first voltage polarity to the third electrical clutch circuit to create the current flowing in the first direction. The control system 1800 can continuously apply the first voltage polarity to the third electric clutch circuit to continuously hold the third clutch 6310 in its disengaged position. While such an arrangement can prevent the third clutch 6310 from unintentionally engaging the third drive

20 ring 6320, such an arrangement can also consume a lot of power. Alternatively, the control system 1800 can apply the first voltage polarity to the third electrical clutch circuit for a sufficient period of time to position the third clutch 6310 in its disengaged position and then discontinue applying the first voltage polarity to the third electric clutch circuit, thereby resulting in a lower consumption of power.

25 **[0190]** Further to the above, the third electromagnetic actuator 6340 is configured to emit a magnetic field EF_D which pulls, or drives, the third clutch 6310 toward the third drive ring 6320 when the third clutch assembly 6300 is in its engaged state. The coils of the third electromagnetic actuator 6340 generate the magnetic field EF_D when current flows in a second, or opposite, direction through the third electrical clutch circuit. The control system

30 1800 is configured to apply an opposite voltage polarity to the third electrical shaft circuit to create the current flowing in the opposite direction. The control system 1800 can continuously apply the opposite voltage polarity to the third electric shaft circuit to continuously hold the third clutch 6310 in its engaged position and maintain the operable engagement between the third drive ring 6320 and the articulation drive 6330. Alternatively,

35 the third clutch 6210 can be configured to become wedged within the third drive ring 6320 when the third clutch 6310 is in its engaged position and, in such instances, the control system 1800 may not need to continuously apply a voltage polarity to the third shaft

electrical circuit to hold the third clutch assembly 6300 in its engaged state. In such instances, the control system 1800 can discontinue applying the voltage polarity once the third clutch 6310 has been sufficiently wedged in the third drive ring 6320. In any event, the end effector 7000 is articulatable in a first direction or a second direction, depending on the direction in which the drive shaft 2730 is rotated, when the third clutch assembly 6300 is in its engaged state.

[0191] Further to the above, referring to FIGS. 22, 32, and 33, the articulation drive system further comprises a lockout 6350 which prevents, or at least inhibits, the articulation of the distal attachment portion 2400 of the shaft assembly 2000 and the end effector 7000 about the articulation joint 2300 when the third clutch 6310 is in its disengaged position (FIG. 32). Referring primarily to FIG. 22, the articulation link 2340 comprises a slot, or groove, 2350 defined therein wherein the lockout 6350 is slideably positioned in the slot 2350 and extends at least partially under the stationary articulation gear 2330. The lockout 6350 comprises an attachment hook 6352 engaged with the third clutch 6310. More specifically, the third clutch 6310 comprises an annular slot, or groove, 6312 defined therein and the attachment hook 6352 is positioned in the annular slot 6312 such that the lockout 6350 translates with the third clutch 6310. Notably, however, the lockout 6350 does not rotate, or at least substantially rotate, with the third clutch 6310. Instead, the annular groove 6312 in the third clutch 6310 permits the third clutch 6310 to rotate relative to the lockout 6350. The lockout 6350 further comprises a lockout hook 6354 slideably positioned in a radially-extending lockout slot 2334 defined in the bottom of the stationary gear 2330. When the third clutch 6310 is in its disengaged position, as illustrated in FIG. 32, the lockout 6350 is in a locked position in which the lockout hook 6354 prevents the end effector 7000 from rotating about the articulation joint 2300. When the third clutch 6310 is in its engaged position, as illustrated in FIG. 33, the lockout 6350 is in an unlocked position in which the lockout hook 6354 is no longer positioned in the lockout slot 2334. Instead, the lockout hook 6354 is positioned in a clearance slot defined in the middle or body 2335 of the stationary gear 2330. In such instances, the lockout hook 6354 can rotate within the clearance slot when the end effector 7000 rotates about the articulation joint 2300.

[0192] Further to the above, the radially-extending lockout slot 2334 depicted in FIGS. 32 and 33 extends longitudinally, i.e., along an axis which is parallel to the longitudinal axis of the elongate shaft 2200. Once the end effector 7000 has been articulated, however, the lockout hook 6354 is no longer aligned with the longitudinal lockout slot 2334. With this in mind, the stationary gear 2330 comprises a plurality, or an array, of radially-extending lockout slots 2334 defined in the bottom of the stationary gear 2330 such that, when the third clutch 6310 is deactuated and the lockout 6350 is pulled distally after the end effector 7000 has been articulated, the lockout hook 6354 can enter one of the lockout slots 2334 and lock

the end effector 7000 in its articulated position. Thus, as a result, the end effector 7000 can be locked in an unarticulated and an articulated position. In various instances, the lockout slots 2334 can define discrete articulated positions for the end effector 7000. For instance, the lockout slots 2334 can be defined at 10 degree intervals, for example, which can define discrete articulation orientations for the end effector 7000 at 10 degree intervals. In other instances, these orientations can be at 5 degree intervals, for example. In alternative embodiments, the lockout 6350 comprises a brake that engages a circumferential shoulder defined in the stationary gear 2330 when the third clutch 6310 is disengaged from the third drive ring 6320. In such an embodiment, the end effector 7000 can be locked in any suitable orientation. In any event, the lockout 6350 prevents, or at least reduces the possibility of, the end effector 7000 unintentionally articulating. As a result of the above, the third clutch 6310 can do things - operate the articulation drive when it is in its engaged position and lock out the articulation drive when it is in its disengaged position.

[0193] Referring primarily to FIGS. 24 and 25, the shaft frame 2530 and the drive shaft 2730 extend through the articulation joint 2300 into the distal attachment portion 2400. When the end effector 7000 is articulated, as illustrated in FIGS. 16 and 17, the shaft frame 2530 and the drive shaft 2730 bend to accommodate the articulation of the end effector 7000. Thus, the shaft frame 2530 and the drive shaft 2730 are comprised of any suitable material which accommodates the articulation of the end effector 7000. Moreover, as discussed above, the shaft frame 2530 houses the first, second, and third electromagnetic actuators 6140, 6240, and 6340. In various instances, the first, second, and third electromagnetic actuators 6140, 6240, and 6340 each comprise wound wire coils, such as copper wire coils, for example, and the shaft frame 2530 is comprised of an insulative material to prevent, or at least reduce the possibility of, short circuits between the first, second, and third electromagnetic actuators 6140, 6240, and 6340. In various instances, the first, second, and third electrical clutch circuits extending through the shaft frame 2530 are comprised of insulated electrical wires, for example. Further to the above, the first, second, and third electrical clutch circuits place the electromagnetic actuators 6140, 6240, and 6340 in communication with the control system 1800 in the drive module 1100.

[0194] As described above, the clutches 6110, 6210, and/or 6310 can be held in their disengaged positions so that they do not unintentionally move into their engaged positions. In various arrangements, the clutch system 6000 comprises a first biasing member, such as a spring, for example, configured to bias the first clutch 6110 into its disengaged position, a second biasing member, such as a spring, for example, configured to bias the second clutch 6210 into its disengaged position, and/or a third biasing member, such as a spring, for example, configured to bias the third clutch 6110 into its disengaged position. In such arrangements, the biasing forces of the springs can be selectively overcome by the

electromagnetic forces generated by the electromagnetic actuators when energized by an electrical current. Further to the above, the clutches 6110, 6210, and/or 6310 can be retained in their engaged positions by the drive rings 6120, 6220, and/or 6320, respectively.

More specifically, in at least one instance, the drive rings 6120, 6220, and/or 6320 are comprised of an elastic material which grips or frictionally holds the clutches 6110, 6210, and/or 6310, respectively, in their engaged positions. In various alternative embodiments, the clutch system 6000 comprises a first biasing member, such as a spring, for example, configured to bias the first clutch 6110 into its engaged position, a second biasing member, such as a spring, for example, configured to bias the second clutch 6210 into its engaged position, and/or a third biasing member, such as a spring, for example, configured to bias the third clutch 6110 into its engaged position. In such arrangements, the biasing forces of the springs can be overcome by the electromagnetic forces applied by the electromagnetic actuators 6140, 6240, and/or 6340, respectively, as needed to selectively hold the clutches 6110, 6210, and 6310 in their disengaged positions. In any one operational mode of the surgical system, the control assembly 1800 can energize one of the electromagnetic actuators to engage one of the clutches while energizing the other two electromagnetic actuators to disengage the other two clutches.

[0195] Although the clutch system 6000 comprises three clutches to control three drive systems of the surgical system, a clutch system can comprise any suitable number of clutches to control any suitable number of systems. Moreover, although the clutches of the clutch system 6000 slide proximally and distally between their engaged and disengaged positions, the clutches of a clutch system can move in any suitable manner. In addition, although the clutches of the clutch system 6000 are engaged one at a time to control one drive motion at a time, various instances are envisioned in which more than one clutch can be engaged to control more than one drive motion at a time.

[0196] In view of the above, the reader should appreciate that the control system 1800 is configured to, one, operate the motor system 1600 to rotate the drive shaft system 2700 in an appropriate direction and, two, operate the clutch system 6000 to transfer the rotation of the drive shaft system 2700 to the appropriate function of the end effector 7000. Moreover, as discussed above, the control system 1800 is responsive to inputs from the clamping trigger system 2600 of the shaft assembly 2000 and the input system 1400 of the handle 1000. When the clamping trigger system 2600 is actuated, as discussed above, the control system 1800 activates the first clutch assembly 6100 and deactivates the second clutch assembly 6200 and the third clutch assembly 6300. In such instances, the control system 1800 also supplies power to the motor system 1600 to rotate the drive shaft system 2700 in a first direction to clamp the jaw assembly 7100 of the end effector 7000. When the control system 1800 detects that the jaw assembly 7100 is in its clamped configuration, the control

system 1800 stops the motor assembly 1600 and deactivates the first clutch assembly 6100. When the control system 1800 detects that the clamping trigger system 2600 has been moved to, or is being moved to, its unactuated position, the control system 1800 activates, or maintains the activation of, the first clutch assembly 6100 and deactivates, or maintains the deactivation of, the second clutch assembly 6200 and the third clutch assembly 6300. In such instances, the control system 1800 also supplies power to the motor system 1600 to rotate the drive shaft system 2700 in a second direction to open the jaw assembly 7100 of the end effector 7000.

[0197] When the rotation actuator 1420 is actuated in a first direction, further to the above, the control system 1800 activates the second clutch assembly 6200 and deactivates the first clutch assembly 6100 and the third clutch assembly 6300. In such instances, the control system 1800 also supplies power to the motor system 1600 to rotate the drive shaft system 2700 in a first direction to rotate the end effector 7000 in a first direction. When the control system 1800 detects that the rotation actuator 1420 has been actuated in a second direction, the control system 1800 activates, or maintains the activation of, the second clutch assembly 6200 and deactivates, or maintains the deactivation of, the first clutch assembly 6100 and the third clutch assembly 6300. In such instances, the control system 1800 also supplies power to the motor system 1600 to rotate the drive shaft system 2700 in a second direction to rotate the drive shaft system 2700 in a second direction to rotate the end effector 7000 in a second direction. When the control system 1800 detects that the rotation actuator 1420 is not actuated, the control system 1800 deactivates the second clutch assembly 6200.

[0198] When the first articulation actuator 1432 is depressed, further to the above, the control system 1800 activates the third clutch assembly 6300 and deactivates the first clutch assembly 6100 and the second clutch assembly 6200. In such instances, the control system 1800 also supplies power to the motor system 1600 to rotate the drive shaft system 2700 in a first direction to articulate the end effector 7000 in a first direction. When the control system 1800 detects that the second articulation actuator 1434 is depressed, the control system 1800 activates, or maintains the activation of, the third clutch assembly 6200 and deactivates, or maintains the deactivation of, the first clutch assembly 6100 and the second clutch assembly 6200. In such instances, the control system 1800 also supplies power to the motor system 1600 to rotate the drive shaft system 2700 in a second direction to articulate the end effector 7000 in a second direction. When the control system 1800 detects that neither the first articulation actuator 1432 nor the second articulation actuator 1434 are actuated, the control system 1800 deactivates the third clutch assembly 6200.

[0199] Further to the above, the control system 1800 is configured to change the operating mode of the stapling system based on the inputs it receives from the clamping trigger system 2600 of the shaft assembly 2000 and the input system 1400 of the handle 1000. The control

system 1800 is configured to shift the clutch system 6000 before rotating the shaft drive system 2700 to perform the corresponding end effector function. Moreover, the control system 1800 is configured to stop the rotation of the shaft drive system 2700 before shifting the clutch system 6000. Such an arrangement can prevent the sudden movements in the end effector 7000. Alternatively, the control system 1800 can shift the clutch system 600 while the shaft drive system 2700 is rotating. Such an arrangement can allow the control system 1800 to shift quickly between operating modes.

[0200] As discussed above, referring to FIG. 34, the distal attachment portion 2400 of the shaft assembly 2000 comprises an end effector lock 6400 configured to prevent the end effector 7000 from being unintentionally decoupled from the shaft assembly 2000. The end effector lock 6400 comprises a lock end 6410 selectively engageable with the annular array of lock notches 7410 defined on the proximal attachment portion 7400 of the end effector 7000, a proximal end 6420, and a pivot 6430 rotatably connecting the end effector lock 6400 to the articulation link 2320. When the third clutch 6310 of the third clutch assembly 6300 is in its disengaged position, as illustrated in FIG. 34, the third clutch 6310 is contact with the proximal end 6420 of the end effector lock 6400 such that the lock end 6410 of the end effector lock 6400 is engaged with the array of lock notches 7410. In such instances, the end effector 7000 can rotate relative to the end effector lock 6400 but cannot translate relative to the distal attachment portion 2400. When the third clutch 6310 is moved into its engaged position, as illustrated in FIG. 35, the third clutch 6310 is no longer engaged with the proximal end 6420 of the end effector lock 6400. In such instances, the end effector lock 6400 is free to pivot upwardly and permit the end effector 7000 to be detached from the shaft assembly 2000.

[0201] The above being said, referring again to FIG. 34, it is possible that the second clutch 6210 of the second clutch assembly 6200 is in its disengaged position when the clinician detaches, or attempts to detach, the end effector 7000 from the shaft assembly 2000. As discussed above, the second clutch 6210 is engaged with the second clutch lock 6250 when the second clutch 6210 is in its disengaged position and, in such instances, the second clutch lock 6250 is pushed into engagement with the articulation link 2340. More specifically, the second clutch lock 6250 is positioned in the channel 2345 defined in the articulation 2340 when the second clutch 6210 is engaged with the second clutch lock 6250 which may prevent, or at least impede, the end effector 7000 from being detached from the shaft assembly 2000. To facilitate the release of the end effector 7000 from the shaft assembly 2000, the control system 1800 can move the second clutch 6210 into its engaged position in addition to moving the third clutch 6310 into its engaged position. In such instances, the end effector 7000 can clear both the end effector lock 6400 and the second clutch lock 6250 when the end effector 7000 is removed.

[0202] In at least one instance, further to the above, the drive module 1100 comprises an input switch and/or sensor in communication with the control system 1800 via the input system 1400, and/or the control system 1800 directly, which, when actuated, causes the control system 1800 to unlock the end effector 7000. In various instances, the drive module 1100 comprises an input screen 1440 in communication with the board 1410 of the input system 1400 which is configured to receive an unlock input from the clinician. In response to the unlock input, the control system 1800 can stop the motor system 1600, if it is running, and unlock the end effector 7000 as described above. The input screen 1440 is also configured to receive a lock input from the clinician in which the input system 1800 moves the second clutch assembly 6200 and/or the third clutch assembly 6300 into their unactuated states to lock the end effector 7000 to the shaft assembly 2000.

[0203] FIG. 37 depicts a shaft assembly 2000' in accordance with at least one alternative embodiment. The shaft assembly 2000' is similar to the shaft assembly 2000 in many respects, most of which will not be repeated herein for the sake of brevity. Similar to the shaft assembly 2000, the shaft assembly 2000' comprises a shaft frame, i.e., shaft frame 2530'. The shaft frame 2530' comprises a longitudinal passage 2535' and, in addition, a plurality of clutch position sensors, i.e., a first sensor 6180', a second sensor 6280', and a third sensor 6380' positioned in the shaft frame 2530'. The first sensor 6180' is in signal communication with the control system 1800 as part of a first sensing circuit. The first sensing circuit comprises signal wires extending through the longitudinal passage 2535'; however, the first sensing circuit can comprise a wireless signal transmitter and receiver to place the first sensor 6180' in signal communication with the control system 1800. The first sensor 6180' is positioned and arranged to detect the position of the first clutch 6110 of the first clutch assembly 6100. Based on data received from the first sensor 6180', the control system 1800 can determine whether the first clutch 6110 is in its engaged position, its disengaged position, or somewhere in-between. With this information, the control system 1800 can assess whether or not the first clutch 6110 is in the correct position given the operating state of the surgical instrument. For instance, if the surgical instrument is in its jaw clamping/opening operating state, the control system 1800 can verify whether the first clutch 6110 is properly positioned in its engaged position. In such instances, further to the below, the control system 1800 can also verify that the second clutch 6210 is in its disengaged position via the second sensor 6280' and that the third clutch 6310 is in its disengaged position via the third sensor 6380'. Correspondingly, the control system 1800 can verify whether the first clutch 6110 is properly positioned in its disengaged position if the surgical instrument is not in its jaw clamping/opening state. To the extent that the first clutch 6110 is not in its proper position, the control system 1800 can actuate the first electromagnetic actuator 6140 in an attempt to properly position the first clutch 6110. Likewise, the control

system 1800 can actuate the electromagnetic actuators 6240 and/or 6340 to properly position the clutches 6210 and/or 6310, if necessary.

[0204] The second sensor 6280' is in signal communication with the control system 1800 as part of a second sensing circuit. The second sensing circuit comprises signal wires extending through the longitudinal passage 2535'; however, the second sensing circuit can comprise a wireless signal transmitter and receiver to place the second sensor 6280' in signal communication with the control system 1800. The second sensor 6280' is positioned and arranged to detect the position of the second clutch 6210 of the first clutch assembly 6200. Based on data received from the second sensor 6280', the control system 1800 can determine whether the second clutch 6210 is in its engaged position, its disengaged position, or somewhere in-between. With this information, the control system 1800 can assess whether or not the second clutch 6210 is in the correct position given the operating state of the surgical instrument. For instance, if the surgical instrument is in its end effector rotation operating state, the control system 1800 can verify whether the second clutch 6210 is properly positioned in its engaged position. In such instances, the control system 1800 can also verify that the first clutch 6110 is in its disengaged position via the first sensor 6180' and, further to the below, the control system 1800 can also verify that the third clutch 6310 is in its disengaged position via the third sensor 6380'. Correspondingly, the control system 1800 can verify whether the second clutch 6110 is properly positioned in its disengaged position if the surgical instrument is not in its end effector rotation state. To the extent that the second clutch 6210 is not in its proper position, the control system 1800 can actuate the second electromagnetic actuator 6240 in an attempt to properly position the second clutch 6210. Likewise, the control system 1800 can actuate the electromagnetic actuators 6140 and/or 6340 to properly position the clutches 6110 and/or 6310, if necessary.

[0205] The third sensor 6380' is in signal communication with the control system 1800 as part of a third sensing circuit. The third sensing circuit comprises signal wires extending through the longitudinal passage 2535'; however, the third sensing circuit can comprise a wireless signal transmitter and receiver to place the third sensor 6380' in signal communication with the control system 1800. The third sensor 6380' is positioned and arranged to detect the position of the third clutch 6310 of the third clutch assembly 6300. Based on data received from the third sensor 6380', the control system 1800 can determine whether the third clutch 6310 is in its engaged position, its disengaged position, or somewhere in-between. With this information, the control system 1800 can assess whether or not the third clutch 6310 is in the correct position given the operating state of the surgical instrument. For instance, if the surgical instrument is in its end effector articulation operating state, the control system 1800 can verify whether the third clutch 6310 is properly positioned in its engaged position. In such instances, the control system 1800 can also verify that the

first clutch 6110 is in its disengaged position via the first sensor 6180' and that the second clutch 6210 is in its disengaged position via the second sensor 6280'. Correspondingly, the control system 1800 can verify whether the third clutch 6310 is properly positioned in its disengaged position if the surgical instrument is not in its end effector articulation state. To the extent that the third clutch 6310 is not in its proper position, the control system 1800 can actuate the third electromagnetic actuator 6340 in an attempt to properly position the third clutch 6310. Likewise, the control system 1800 can actuate the electromagnetic actuators 6140 and/or 6240 to properly position the clutches 6110 and/or 6210, if necessary.

[0206] Further to the above, the clutch position sensors, i.e., the first sensor 6180', the second sensor 6280', and the third sensor 6380' can comprise any suitable type of sensor. In various instances, the first sensor 6180', the second sensor 6280', and the third sensor 6380' each comprise a proximity sensor. In such an arrangement, the sensors 6180', 6280', and 6380' are configured to detect whether or not the clutches 6110, 6210, and 6310, respectively, are in their engaged positions. In various instances, the first sensor 6180', the second sensor 6280', and the third sensor 6380' each comprise a Hall Effect sensor, for example. In such an arrangement, the sensors 6180', 6280', and 6380' can not only detect whether or not the clutches 6110, 6210, and 6310, respectively, are in their engaged positions but the sensors 6180', 6280', and 6380' can also detect how close the clutches 6110, 6210, and 6310 are with respect to their engaged or disengaged positions.

[0207] FIG. 38 depicts the shaft assembly 2000' and an end effector 7000" in accordance with at least one alternative embodiment. The end effector 7000" is similar to the end effector 7000 in many respects, most of which will not be repeated herein for the sake of brevity. Similar to the end effector 7000, the shaft assembly 7000" comprises a jaw assembly 7100 and a jaw assembly drive configured to move the jaw assembly 7100 between its open and closed configurations. The jaw assembly drive comprises drive links 7140, a drive nut 7150", and a drive screw 6130". The drive nut 7150" comprises a sensor 7190" positioned therein which is configured to detect the position of a magnetic element 6190" positioned in the drive screw 6130". The magnetic element 6190" is positioned in an elongate aperture 6134" defined in the drive screw 6130" and can comprise a permanent magnet and/or can be comprised of iron, nickel, and/or any suitable metal, for example. In various instances, the sensor 7190" comprises a proximity sensor, for example, which is in signal communication with the control system 1800. In certain instances, the sensor 7190" comprises a Hall Effect sensor, for example, in signal communication with the control system 1800. In certain instances, the sensor 7190" comprises an optical sensor, for example, and the detectable element 6190" comprises an optically detectable element, such as a reflective element, for example. In either event, the sensor 7190" is configured to communicate

wirelessly with the control system 1800 via a wireless signal transmitter and receiver and/or via a wired connection extending through the shaft frame passage 2532', for example.

[0208] The sensor 7190", further to the above, is configured to detect when the magnetic element 6190" is adjacent to the sensor 7190" such that the control system 1800 can use this data to determine that the jaw assembly 7100 has reached the end of its clamping stroke. At such point, the control system 1800 can stop the motor assembly 1600. The sensor 7190" and the control system 1800 are also configured to determine the distance between where the drive screw 6130" is currently positioned and where the drive screw 6130" should be positioned at the end of its closure stroke in order to calculate the amount of closure stroke of the drive screw 6130" that is still needed to close the jaw assembly 7100. Moreover, such information can be used by the control system 1800 to assess the current configuration of the jaw assembly 7100, i.e., whether the jaw assembly 7100 is in its open configuration, its closed configuration, or a partially closed configuration. The sensor system could be used to determine when the jaw assembly 7100 has reached its fully open position and stop the motor assembly 1600 at that point. In various instances, the control system 1800 could use this sensor system to confirm that the first clutch assembly 6100 is in its actuated state by confirming that the jaw assembly 7100 is moving while the motor assembly 1600 is turning. Similarly, the control system 1800 could use this sensor system to confirm that the first clutch assembly 6100 is in its unactuated state by confirming that the jaw assembly 7100 is not moving while the motor assembly 1600 is turning.

[0209] FIG. 39 depicts a shaft assembly 2000''' and an end effector 7000''' in accordance with at least one alternative embodiment. The shaft assembly 2000''' is similar to the shaft assemblies 2000 and 2000' in many respects, most of which will not be repeated herein for the sake of brevity. The end effector 7000''' is similar to the end effectors 7000 and 7000" in many respects, most of which will not be repeated herein for the sake of brevity. Similar to the end effector 7000, the end effector 7000''' comprises a jaw assembly 7100 and a jaw assembly drive configured to move the jaw assembly 7100 between its open and closed configurations and, in addition, an end effector rotation drive that rotates the end effector 7000''' relative to the distal attachment portion 2400 of the shaft assembly 2000'. The end effector rotation drive comprises an outer housing 6230''' that is rotated relative to a shaft frame 2530''' of the end effector 7000''' by the second clutch assembly 6200. The shaft frame 2530''' comprises a sensor 6290''' positioned therein which is configured to detect the position of a magnetic element 6190''' positioned in and/or on the outer housing 6230'''. The magnetic element 6190''' can comprise a permanent magnet and/or can be comprised of iron, nickel, and/or any suitable metal, for example. In various instances, the sensor 6290''' comprises a proximity sensor, for example, in signal communication with the control system 1800. In certain instances, the sensor 6290''' comprises a Hall Effect sensor, for example, in

signal communication with the control system 1800. In either event, the sensor 6290''' is configured to communicate wirelessly with the control system 1800 via a wireless signal transmitter and receiver and/or via a wired connection extending through the shaft frame passage 2532', for example. In various instances, the control system 1800 can use the sensor 6290''' to confirm whether the magnetic element 6190''' is rotating and, thus, confirm that the second clutch assembly 6200 is in its actuated state. Similarly, the control system 1800 can use the sensor 6290''' to confirm whether the magnetic element 6190''' is not rotating and, thus, confirm that the second clutch assembly 6200 is in its unactuated state. The control system 1800 can also use the sensor 6290''' to confirm that the second clutch assembly 6200 is in its unactuated state by confirming that the second clutch 6210 is positioned adjacent the sensor 6290'''.

[0210] FIG. 40 depicts a shaft assembly 2000'''' in accordance with at least one alternative embodiment. The shaft assembly 2000'''' is similar to the shaft assemblies 2000, 2000', and 2000''' in many respects, most of which will not be repeated herein for the sake of brevity.

Similar to the shaft assembly 2000, the shaft assembly 2000'''' comprises, among other things, an elongate shaft 2200, an articulation joint 2300, and a distal attachment portion 2400 configured to receive an end effector, such as end effector 7000', for example. Similar to the shaft assembly 2000, the shaft assembly 2000'''' comprises an articulation drive, i.e., articulation drive 6330'''' configured to rotate the distal attachment portion 2400 and the end effector 7000' about the articulation joint 2300. Similar to the above, a shaft frame 2530'''' comprises a sensor positioned therein configured to detect the position, and/or rotation, of a magnetic element 6390'''' positioned in and/or on the articulation drive 6330'''. The magnetic element 6390'''' can comprise a permanent magnet and/or can be comprised of iron, nickel, and/or any suitable metal, for example. In various instances, the sensor comprises a proximity sensor, for example, in signal communication with the control system 1800. In certain instances, the sensor comprises a Hall Effect sensor, for example, in signal communication with the control system 1800. In either event, the sensor is configured to communicate wirelessly with the control system 1800 via a wireless signal transmitter and receiver and/or via a wired connection extending through the shaft frame passage 2532', for example. In various instances, the control system 1800 can use the sensor to confirm whether the magnetic element 6390'''' is rotating and, thus, confirm that the third clutch assembly 6300 is in its actuated state. Similarly, the control system 1800 can use the sensor to confirm whether the magnetic element 6390'''' is not rotating and, thus, confirm that the third clutch assembly 6300 is in its unactuated state. In certain instances, the control system 1800 can use the sensor to confirm that the third clutch assembly 6300 is in its unactuated state by confirming that the third clutch 6310 is positioned adjacent the sensor.

[0211] Referring to FIG. 40 once again, the shaft assembly 2000''' comprises an end effector lock 6400' configured to releasably lock the end effector 7000', for example, to the shaft assembly 2000'''. The end effector lock 6400' is similar to the end effector lock 6400 in many respects, most of which will not be discussed herein for the sake of brevity.

5 Notably, though, a proximal end 6420' of the lock 6400' comprises a tooth 6422' configured to engage the annular slot 6312 of the third clutch 6310 and releasably hold the third clutch 6310 in its disengaged position. That said, the actuation of the third electromagnetic assembly 6340 can disengage the third clutch 6310 from the end effector lock 6400'. Moreover, in such instances, the proximal movement of the third clutch 6310 into its
10 engaged position rotates the end effector lock 6400' into a locked position and into engagement with the lock notches 7410 to lock the end effector 7000' to the shaft assembly 2000'''. Correspondingly, the distal movement of the third clutch 6310 into its disengaged position unlocks the end effector 7000' and allows the end effector 7000' to be disassembled from the shaft assembly 2000'''.

15 [0212] Further to the above, an instrument system including a handle and a shaft assembly attached thereto can be configured to perform a diagnostic check to assess the state of the clutch assemblies 6100, 6200, and 6300. In at least one instance, the control system 1800 sequentially actuates the electromagnetic actuators 6140, 6240, and/or 6340 - in any suitable order - to verify the positions of the clutches 6110, 6210, and/or 6310,
20 respectively, and/or verify that the clutches are responsive to the electromagnetic actuators and, thus, not stuck. The control system 1800 can use sensors, including any of the sensors disclosed herein, to verify the movement of the clutches 6110, 6120, and 6130 in response to the electromagnetic fields created by the electromagnetic actuators 6140, 6240, and/or 6340. In addition, the diagnostic check can also include verifying the motions of the drive
25 systems. In at least one instance, the control system 1800 sequentially actuates the electromagnetic actuators 6140, 6240, and/or 6340 - in any suitable order - to verify that the jaw drive opens and/or closes the jaw assembly 7100, the rotation drive rotates the end effector 7000, and/or the articulation drive articulates the end effector 7000, for example. The control system 1800 can use sensors to verify the motions of the jaw assembly 7100
30 and end effector 7000.

[0213] The control system 1800 can perform the diagnostic test at any suitable time, such as when a shaft assembly is attached to the handle and/or when the handle is powered on, for example. If the control system 1800 determines that the instrument system passed the diagnostic test, the control system 1800 can permit the ordinary operation of the instrument
35 system. In at least one instance, the handle can comprise an indicator, such as a green LED, for example, which indicates that the diagnostic check has been passed. If the control system 1800 determines that the instrument system failed the diagnostic test, the control

system 1800 can prevent and/or modify the operation of the instrument system. In at least one instance, the control system 1800 can limit the functionality of the instrument system to only the functions necessary to remove the instrument system from the patient, such as straightening the end effector 7000 and/or opening and closing the jaw assembly 7100, for example. In at least one respect, the control system 1800 enters into a limp mode. The limp mode of the control system 1800 can reduce a current rotational speed of the motor 1610 by any percentage selected from a range of about 75% to about 25%, for example. In one example, the limp mode reduces a current rotational speed of the motor 1610 by 50%. In one example, the limp mode reduces the current rotational speed of the motor 1610 by 75%. The limp mode may cause a current torque of the motor 1610 to be reduced by any percentage selected from a range of about 75% to about 25%, for example. In one example, the limp mode reduces a current torque of the motor 1610 by 50%. The handle can comprise an indicator, such as a red LED, for example, which indicates that the instrument system failed the diagnostic check and/or that the instrument system has entered into a limp mode. The above being said, any suitable feedback can be used to warn the clinician that the instrument system is not operating properly such as, for example, an audible warning and/or a tactile or vibratory warning, for example.

[0214] FIGS. 41-43 depict a clutch system 6000' in accordance with at least one alternative embodiment. The clutch system 6000' is similar to the clutch system 6000 in many respects, most of which will not be repeated herein for the sake of brevity. Similar to the clutch system 6000, the clutch system 6000' comprises a clutch assembly 6100' which is actuatable to selectively couple a rotatable drive input 6030' with a rotatable drive output 6130'. The clutch assembly 6100' comprises clutch plates 6110' and drive rings 6120'. The clutch plates 6110' are comprised of a magnetic material, such as iron and/or nickel, for example, and can comprise a permanent magnet. As described in greater detail below, the clutch plates 6110' are movable between unactuated positions (FIG. 42) and actuated positions (FIG. 43) within the drive output 6130'. The clutch plates 6110' are slideably positioned in apertures defined in the drive output 6130' such that the clutch plates 6110' rotate with the drive output 6130' regardless of whether the clutch plates 6110' are in their unactuated or actuated positions.

[0215] When the clutch plates 6110' are in their unactuated positions, as illustrated in FIG. 42, the rotation of the drive input 6030' is not transferred to the drive output 6130'. More specifically, when the drive input 6030' is rotated, in such instances, the drive input 6030' slides past and rotates relative to the drive rings 6120' and, as a result, the drive rings 6120' do not drive the clutch plates 6110' and the drive output 6130'. When the clutch plates 6110' are in their actuated positions, as illustrated in FIG. 43, the clutch plates 6110' resiliently compress the drive rings 6120' against the drive input 6030'. The drive rings 6120' are

comprised of any suitable compressible material, such as rubber, for example. In any event, in such instances, the rotation of the drive input 6030' is transferred to the drive output 6130' via the drive rings 6120' and the clutch plates 6110'. The clutch system 6000' comprises a clutch actuator 6140' configured to move the clutch plates 6110' into their actuated positions.

5 The clutch actuator 6140' is comprised of a magnetic material such as iron and/or nickel, for example, and can comprise a permanent magnet. The clutch actuator 6140' is slideably positioned in a longitudinal shaft frame 6050' extending through the drive input 6030' and can be moved between an unactuated position (FIG. 42) and an actuated position (FIG. 43) by a clutch shaft 6060'. In at least one instance, the clutch shaft 6060' comprises a polymer
10 cable, for example. When the clutch actuator 6140' is in its actuated position, as illustrated in FIG. 43, the clutch actuator 6140' pulls the clutch plates 6110' inwardly to compress the drive rings 6120', as discussed above. When the clutch actuator 6140' is moved into its unactuated position, as illustrated in FIG. 42, the drive rings 6120' resiliently expand and push the clutch plates 6110' away from the drive input 6030'. In various alternative
15 embodiments, the clutch actuator 6140' can comprise an electromagnet. In such an arrangement, the clutch actuator 6140' can be actuated by an electrical circuit extending through a longitudinal aperture defined in the clutch shaft 6060', for example. In various instances, the clutch system 6000' further comprises electrical wires 6040', for example, extending through the longitudinal aperture.

20 **[0216]** FIG. 44 depicts an end effector 7000a including a jaw assembly 7100a, a jaw assembly drive, and a clutch system 6000a in accordance with at least one alternative embodiment. The jaw assembly 7100a comprises a first jaw 7110a and a second jaw 7120a which are selectively rotatable about a pivot 7130a. The jaw assembly drive comprises a translatable actuator rod 7160a and drive links 7140a which are pivotably coupled to the
25 actuator rod 7160a about a pivot 7150a. The drive links 7140a are also pivotably coupled to the jaws 7110a and 7120a such that the jaws 7110a and 7120a are rotated closed when the actuator rod 7160a is pulled proximally and rotated open when the actuator rod 7160a is pushed distally. The clutch system 6000a is similar to the clutch systems 6000 and 6000' in many respects, most of which will not be repeated herein for the sake of brevity. The clutch
30 system 6000a comprises a first clutch assembly 6100a and a second clutch assembly 6200a which are configured to selectively transmit the rotation of a drive input 6030a to rotate the jaw assembly 7100a about a longitudinal axis and articulate the jaw assembly 7100a about an articulation joint 7300a, respectively, as described in greater detail below.

[0217] The first clutch assembly 6100a comprises clutch plates 6110a and drive rings
35 6120a and work in a manner similar to the clutch plates 6110' and drive rings 6120' discussed above. When the clutch plates 6110a are actuated by an electromagnetic actuator 6140a, the rotation of the drive input 6030a is transferred to an outer shaft housing 7200a.

More specifically, the outer shaft housing 7200a comprises a proximal outer housing 7210a and a distal outer housing 7220a which is rotatably supported by the proximal outer housing 7210a and is rotated relative to the proximal outer housing 7210a by the drive input 6030a when the clutch plates 6110a are in their actuated position. The rotation of the distal outer housing 7220a rotates the jaw assembly 7100a about the longitudinal axis owing to fact that the pivot 7130a of the jaw assembly 7100a is mounted to the distal outer housing 7220a. As a result, the outer shaft housing 7200a rotates the jaw assembly 7100a in a first direction when the outer shaft housing 7200a is rotated in a first direction by the drive input 6030a. Similarly, the outer shaft housing 7200a rotates the jaw assembly 7100a in a second direction when the outer shaft housing 7200a is rotated in a second direction by the drive input 6030a. When the electromagnetic actuator 6140a is de-energized, the drive rings 6120a expand and the clutch plates 6110a are moved into their unactuated positions, thereby decoupling the end effector rotation drive from the drive input 6030a.

[0218] The second clutch assembly 6200a comprises clutch plates 6210a and drive rings 6220a and work in a manner similar to the clutch plates 6110' and drive rings 6120' discussed above. When the clutch plates 6210a are actuated by an electromagnetic actuator 6240a, the rotation of the drive input 6030a is transferred to an articulation drive 6230a. The articulation drive 6230a is rotatably supported within an outer shaft housing 7410a of an end effector attachment portion 7400a and is rotatably supported by a shaft frame 6050a extending through the outer shaft housing 7410a. The articulation drive 6230a comprises a gear face defined thereon which is operably intermeshed with a stationary gear face 7230a defined on the proximal outer housing 7210a of the outer shaft housing 7200a. As a result, the articulation drive 6230a articulates the outer shaft housing 7200a and the jaw assembly 7100a in a first direction when the articulation drive 6230a is rotated in a first direction by the drive input 6030a. Similarly, the articulation drive 6230a articulates the outer shaft housing 7200a and the jaw assembly 7100a in a second direction when the articulation drive 6230a is rotated in a second direction by the drive input 6030a. When the electromagnetic actuator 6240a is de-energized, the drive rings 6220a expand and the clutch plates 6210a are moved into their unactuated positions, thereby decoupling the end effector articulation drive from the drive input 6030a.

[0219] Further to the above, the shaft assembly 4000 is illustrated in FIGS. 45-49. The shaft assembly 4000 is similar to the shaft assemblies 2000, 2000', 2000'', and 2000''' in many respects, most of which will not be repeated herein for the sake of brevity. The shaft assembly 4000 comprises a proximal portion 4100, an elongate shaft 4200, a distal attachment portion 2400, and an articulate joint 2300 which rotatably connects the distal attachment portion 2040 to the elongate shaft 4200. The proximal portion 4100, similar to the proximal portion 2100, is operably attachable to the drive module 1100 of the handle

1000. The proximal portion 4100 comprises a housing 4110 including an attachment interface 4130 configured to mount the shaft assembly 4000 to the attachment interface 1130 of the handle 1000. The shaft assembly 4000 further comprises a frame 4500 including a shaft 4510 configured to be coupled to the shaft 1510 of the handle frame 1500 when the shaft assembly 4000 is attached to the handle 1000. The shaft assembly 4000 also comprises a drive system 4700 including a rotatable drive shaft 4710 configured to be operably coupled to the drive shaft 1710 of the handle drive system 1700 when the shaft assembly 4000 is attached to the handle 1000. The distal attachment portion 2400 is configured to receive an end effector, such as end effector 8000, for example. The end effector 8000 is similar to the end effector 7000 in many respects, most of which will not be repeated herein for the sake of brevity. That said, the end effector 8000 comprises a jaw assembly 8100 configured to, among other things, grasp tissue.

[0220] As discussed above, referring primarily to FIGS. 47-49, the frame 4500 of the shaft assembly 4000 comprises a frame shaft 4510. The frame shaft 4510 comprises a notch, or cut-out, 4530 defined therein. As discussed in greater detail below, the cut-out 4530 is configured to provide clearance for a jaw closure actuation system 4600. The frame 4500 further comprises a distal portion 4550 and a bridge 4540 connecting the distal portion 4550 to the frame shaft 4510. The frame 4500 further comprises a longitudinal portion 4560 extending through the elongate shaft 4200 to the distal attachment portion 2400. Similar to the above, the frame shaft 4510 comprises one or more electrical traces defined thereon and/or therein. The electrical traces extend through the longitudinal portion 4560, the distal portion 4550, the bridge 4540, and/or any suitable portion of the frame shaft 4510 to the electrical contacts 2520. Referring primarily to FIG. 48, the distal portion 4550 and longitudinal portion 4560 comprise a longitudinal aperture defined therein which is configured to receive a rod 4660 of the jaw closure actuation system 4600, as described in greater detail below.

[0221] As also discussed above, referring primarily to FIGS. 48 and 49, the drive system 4700 of the shaft assembly 4000 comprises a drive shaft 4710. The drive shaft 4710 is rotatably supported within the proximal shaft housing 4110 by the frame shaft 4510 and is rotatable about a longitudinal axis extending through the frame shaft 4510. The drive system 4700 further comprises a transfer shaft 4750 and an output shaft 4780. The transfer shaft 4750 is also rotatably supported within the proximal shaft housing 4110 and is rotatable about a longitudinal axis extending parallel to, or at least substantially parallel to, the frame shaft 4510 and the longitudinal axis defined therethrough. The transfer shaft 4750 comprises a proximal spur gear 4740 fixedly mounted thereto such that the proximal spur gear 4740 rotates with the transfer shaft 4750. The proximal spur gear 4740 is operably intermeshed with an annular gear face 4730 defined around the outer circumference of the

drive shaft 4710 such that the rotation of the drive shaft 4710 is transferred to the transfer shaft 4750. The transfer shaft 4750 further comprises a distal spur gear 4760 fixedly mounted thereto such that the distal spur gear 4760 rotates with the transfer shaft 4750. The distal spur gear 4760 is operably intermeshed with an annular gear 4770 defined around the outer circumference of the output shaft 4780 such that the rotation of the transfer shaft 4750 is transferred to the output shaft 4780. Similar to the above, the output shaft 4780 is rotatably supported within the proximal shaft housing 4110 by the distal portion 4550 of the shaft frame 4500 such that the output shaft 4780 rotates about the longitudinal shaft axis. Notably, the output shaft 4780 is not directly coupled to the input shaft 4710; rather, the output shaft 4780 is operably coupled to the input shaft 4710 by the transfer shaft 4750. Such an arrangement provides room for the manually-actuated jaw closure actuation system 4600 discussed below.

[0222] Further to the above, referring primarily to FIGS. 47 and 48, the jaw closure actuation system 4600 comprises an actuation, or scissors, trigger 4610 rotatably coupled to the proximal shaft housing 4110 about a pivot 4620. The actuation trigger 4610 comprises an elongate portion 4612, a proximal end 4614, and a grip ring aperture 4616 defined in the proximal end 4614 which is configured to be gripped by the clinician. The shaft assembly 4000 further comprises a stationary grip 4160 extending from the proximal housing 4110. The stationary grip 4160 comprises an elongate portion 4162, a proximal end 4164, and a grip ring aperture 4166 defined in the proximal end 4164 which is configured to be gripped by the clinician. In use, as described in greater detail below, the actuation trigger 4610 is rotatable between an unactuated position and an actuated position (FIG. 48), i.e., toward the stationary grip 4160, to close the jaw assembly 8100 of the end effector 8000.

[0223] Referring primarily to FIG. 48, the jaw closure actuation system 4600 further comprises a drive link 4640 rotatably coupled to the proximal shaft housing 4110 about a pivot 4650 and, in addition, an actuation rod 4660 operably coupled to the drive link 4640. The actuation rod 4660 extends through an aperture defined in the longitudinal frame portion 4560 and is translatable along the longitudinal axis of the shaft frame 4500. The actuation rod 4660 comprises a distal end operably coupled to the jaw assembly 8100 and a proximal end 4665 positioned in a drive slot 4645 defined in the drive link 4640 such that the actuation rod 4660 is translated longitudinally when the drive link 4640 is rotated about the pivot 4650. Notably, the proximal end 4665 is rotatably supported within the drive slot 4645 such that the actuation rod 4660 can rotate with the end effector 8000.

[0224] Further to the above, the actuation trigger 4610 further comprises a drive arm 4615 configured to engage and rotate the drive link 4640 proximally, and translate the actuation rod 4660 proximally, when the actuation trigger 4610 is actuated, i.e., moved closer to the proximal shaft housing 4110. In such instances, the proximal rotation of the drive link 4640

resiliently compresses a biasing member, such as a coil spring 4670, for example, positioned intermediate the drive link 4640 and the frame shaft 4510. When the actuation trigger 4610 is released, the compressed coil spring 4670 re-expands and pushes the drive link 4640 and the actuation rod 4660 distally to open the jaw assembly 8100 of the end effector 8000. Moreover, the distal rotation of the drive link 4640 drives, and automatically rotates, the actuation trigger 4610 back into its unactuated position. That being said, the clinician could manually return the actuation trigger 4610 back into its unactuated position. In such instances, the actuation trigger 4610 could be opened slowly. In either event, the shaft assembly 4000 further comprises a lock configured to releasably hold the actuation trigger 4610 in its actuated position such that the clinician can use their hand to perform another task without the jaw assembly 8100 opening unintentionally.

[0225] In various alternative embodiments, further to the above, the actuation rod 4660 can be pushed distally to close the jaw assembly 8100. In at least one such instance, the actuation rod 4660 is mounted directly to the actuation trigger 4610 such that, when the actuation trigger 4610 is actuated, the actuation trigger 4610 drives the actuation rod 4660 distally. Similar to the above, the actuation trigger 4610 can compress a spring when the actuation trigger 4610 is closed such that, when the actuation trigger 4610 is released, the actuation rod 4660 is pushed proximally.

[0226] Further to the above, the shaft assembly 4000 has three functions - opening/closing the jaw assembly of an end effector, rotating the end effector about a longitudinal axis, and articulating the end effector about an articulation axis. The end effector rotation and articulation functions of the shaft assembly 4000 are driven by the motor assembly 1600 and the control system 1800 of the drive module 1100 while the jaw actuation function is manually-driven by the jaw closure actuation system 4600. The jaw closure actuation system 4600 could be a motor-driven system but, instead, the jaw closure actuation system 4600 has been kept a manually-driven system such that the clinician can have a better feel for the tissue being clamped within the end effector. While motorizing the end effector rotation and actuation systems provides certain advantages for controlling the position of the end effector, motorizing the jaw closure actuation system 4600 may cause the clinician to lose a tactile sense of the force being applied to the tissue and may not be able to assess whether the force is insufficient or excessive. Thus, the jaw closure actuation system 4600 is manually-driven even though the end effector rotation and articulation systems are motor-driven.

[0227] FIG. 50 is a logic diagram of the control system 1800 of the surgical system depicted in FIG. 1 in accordance with at least one embodiment. The control system 1800 comprises a control circuit. The control circuit includes a microcontroller 1840 comprising a processor 1820 and a memory 1830. One or more sensors, such as sensors 1880, 1890,

6180', 6280', 6380', 7190'', and/or 6290''', for example, provide real time feedback to the processor 1820. The control system 1800 further comprises a motor driver 1850 configured to control the electric motor 1610 and a tracking system 1860 configured to determine the position of one or more longitudinally movable components in the surgical instrument, such as the clutches 6110, 6120, and 6130 and/or the longitudinally-movable drive nut 7150 of the jaw assembly drive, for example. The tracking system 1860 is also configured to determine the position of one or more rotational components in the surgical instrument, such as the drive shaft 2530, the outer shaft 6230, and/or the articulation drive 6330, for example. The tracking system 1860 provides position information to the processor 1820, which can be programmed or configured to, among other things, determine the position of the clutches 6110, 6120, and 6130 and the drive nut 7150 as well as the orientation of the jaws 7110 and 7120. The motor driver 1850 may be an A3941 available from Allegro Microsystems, Inc., for example; however, other motor drivers may be readily substituted for use in the tracking system 1860. A detailed description of an absolute positioning system is described in U.S. Patent Application Publication No. 2017/0296213, entitled SYSTEMS AND METHODS FOR CONTROLLING A SURGICAL STAPLING AND CUTTING INSTRUMENT, the entire disclosure of which is hereby incorporated herein by reference.

[0228] The microcontroller 1840 may be any single core or multicore processor such as those known under the trade name ARM Cortex by Texas Instruments, for example. In at least one instance, the microcontroller 1840 is a LM4F230H5QR ARM Cortex-M4F Processor Core, available from Texas Instruments, for example, comprising on-chip memory of 256 KB single-cycle flash memory, or other non-volatile memory, up to 40 MHz, a prefetch buffer to improve performance above 40 MHz, a 32 KB single-cycle serial random access memory (SRAM), internal read-only memory (ROM) loaded with StellarisWare® software, 2 KB electrically erasable programmable read-only memory (EEPROM), one or more pulse width modulation (PWM) modules and/or frequency modulation (FM) modules, one or more quadrature encoder inputs (QEI) analog, one or more 12-bit Analog-to-Digital Converters (ADC) with 12 analog input channels, for example, details of which are available from the product datasheet.

[0229] In various instances, the microcontroller 1840 comprises a safety controller comprising two controller-based families such as TMS570 and RM4x known under the trade name Hercules ARM Cortex R4, also by Texas Instruments. The safety controller may be configured specifically for IEC 61508 and ISO 26262 safety critical applications, among others, to provide advanced integrated safety features while delivering scalable performance, connectivity, and memory options.

[0230] The microcontroller 1840 is programmed to perform various functions such as precisely controlling the speed and/or position of the drive nut 7150 of the jaw closure

assembly, for example. The microcontroller 1840 is also programmed to precisely control the rotational speed and position of the end effector 7000 and the articulation speed and position of the end effector 7000. In various instances, the microcontroller 1840 computes a response in the software of the microcontroller 1840. The computed response is compared
5 to a measured response of the actual system to obtain an “observed” response, which is used for actual feedback decisions. The observed response is a favorable, tuned, value that balances the smooth, continuous nature of the simulated response with the measured response, which can detect outside influences on the system.

[0231] The motor 1610 is controlled by the motor driver 1850. In various forms, the motor
10 1610 is a DC brushed driving motor having a maximum rotational speed of approximately 25,000 RPM, for example. In other arrangements, the motor 1610 includes a brushless motor, a cordless motor, a synchronous motor, a stepper motor, or any other suitable electric motor. The motor driver 1850 may comprise an H-bridge driver comprising field-effect transistors (FETs), for example. The motor driver 1850 may be an A3941 available from
15 Allegro Microsystems, Inc., for example. The A3941 driver 1850 is a full-bridge controller for use with external N-channel power metal oxide semiconductor field effect transistors (MOSFETs) specifically designed for inductive loads, such as brush DC motors. In various instances, the driver 1850 comprises a unique charge pump regulator provides full (>10 V) gate drive for battery voltages down to 7 V and allows the A3941 to operate with a reduced
20 gate drive, down to 5.5 V. A bootstrap capacitor may be employed to provide the above-battery supply voltage required for N-channel MOSFETs. An internal charge pump for the high-side drive allows DC (100% duty cycle) operation. The full bridge can be driven in fast or slow decay modes using diode or synchronous rectification. In the slow decay mode, current recirculation can be through the high-side or the lowside FETs. The power FETs are
25 protected from shoot-through by resistor adjustable dead time. Integrated diagnostics provide indication of undervoltage, overtemperature, and power bridge faults, and can be configured to protect the power MOSFETs under most short circuit conditions. Other motor drivers may be readily substituted.

[0232] The tracking system 1860 comprises a controlled motor drive circuit arrangement
30 comprising one or more position sensors, such as sensors 1880, 1890, 6180', 6280', 6380', 7190", and/or 6290"', for example. The position sensors for an absolute positioning system provide a unique position signal corresponding to the location of a displacement member. As used herein, the term displacement member is used generically to refer to any movable member of the surgical system. In various instances, the displacement member may be
35 coupled to any position sensor suitable for measuring linear displacement. Linear displacement sensors may include contact or non-contact displacement sensors. Linear displacement sensors may comprise linear variable differential transformers (LVDT),

differential variable reluctance transducers (DVRT), a slide potentiometer, a magnetic sensing system comprising a movable magnet and a series of linearly arranged Hall Effect sensors, a magnetic sensing system comprising a fixed magnet and a series of movable linearly arranged Hall Effect sensors, an optical sensing system comprising a movable light source and a series of linearly arranged photo diodes or photo detectors, or an optical sensing system comprising a fixed light source and a series of movable linearly arranged photo diodes or photo detectors, or any combination thereof.

[0233] The position sensors 1880, 1890, 6180', 6280', 6380', 7190", and/or 6290"', for example, may comprise any number of magnetic sensing elements, such as, for example, magnetic sensors classified according to whether they measure the total magnetic field or the vector components of the magnetic field. The techniques used to produce both types of magnetic sensors encompass many aspects of physics and electronics. The technologies used for magnetic field sensing include search coil, fluxgate, optically pumped, nuclear precession, SQUID, Hall-Effect, anisotropic magnetoresistance, giant magnetoresistance, magnetic tunnel junctions, giant magnetoeimpedance, magnetostrictive/piezoelectric composites, magnetodiode, magnetotransistor, fiber optic, magnetooptic, and microelectromechanical systems-based magnetic sensors, among others.

[0234] In various instances, one or more of the position sensors of the tracking system 1860 comprise a magnetic rotary absolute positioning system. Such position sensors may be implemented as an AS5055EQFT single-chip magnetic rotary position sensor available from Austria Microsystems, AG and can be interfaced with the controller 1840 to provide an absolute positioning system. In certain instances, a position sensor comprises a low-voltage and low-power component and includes four Hall-Effect elements in an area of the position sensor that is located adjacent a magnet. A high resolution ADC and a smart power management controller are also provided on the chip. A CORDIC processor (for Coordinate Rotation Digital Computer), also known as the digit-by-digit method and Volder's algorithm, is provided to implement a simple and efficient algorithm to calculate hyperbolic and trigonometric functions that require only addition, subtraction, bitshift, and table lookup operations. The angle position, alarm bits, and magnetic field information are transmitted over a standard serial communication interface such as an SPI interface to the controller 1840. The position sensors can provide 12 or 14 bits of resolution, for example. The position sensors can be an AS5055 chip provided in a small QFN 16-pin 4x4x0.85mm package, for example.

[0235] The tracking system 1860 may comprise and/or be programmed to implement a feedback controller, such as a PID, state feedback, and adaptive controller. A power source converts the signal from the feedback controller into a physical input to the system, in this case voltage. Other examples include pulse width modulation (PWM) and/or frequency

modulation (FM) of the voltage, current, and force. Other sensor(s) may be provided to measure physical parameters of the physical system in addition to position. In various instances, the other sensor(s) can include sensor arrangements such as those described in U.S. Patent No. 9,345,481, entitled STAPLE CARTRIDGE TISSUE THICKNESS SENSOR

5 SYSTEM, which is hereby incorporated herein by reference in its entirety; U.S. Patent Application Publication No. 2014/0263552, entitled STAPLE CARTRIDGE TISSUE THICKNESS SENSOR SYSTEM, which is hereby incorporated herein by reference in its entirety; and U.S. Patent Application Serial No. 15/628,175, entitled TECHNIQUES FOR ADAPTIVE CONTROL OF MOTOR VELOCITY OF A SURGICAL STAPLING AND
10 CUTTING INSTRUMENT, which is hereby incorporated herein by reference in its entirety. In a digital signal processing system, absolute positioning system is coupled to a digital data acquisition system where the output of the absolute positioning system will have finite resolution and sampling frequency. The absolute positioning system may comprise a compare and combine circuit to combine a computed response with a measured response
15 using algorithms such as weighted average and theoretical control loop that drives the computed response towards the measured response. The computed response of the physical system takes into account properties like mass, inertial, viscous friction, inductance resistance, etc., to predict what the states and outputs of the physical system will be by knowing the input.

20 **[0236]** The absolute positioning system provides an absolute position of the displacement member upon power up of the instrument without retracting or advancing the displacement member to a reset (zero or home) position as may be required with conventional rotary encoders that merely count the number of steps forwards or backwards that the motor 1610 has taken to infer the position of a device actuator, drive bar, knife, and the like.

25 **[0237]** A sensor 1880 comprising a strain gauge or a micro-strain gauge, for example, is configured to measure one or more parameters of the end effector, such as, for example, the strain experienced by the jaws 7110 and 7120 during a clamping operation. The measured strain is converted to a digital signal and provided to the processor 1820. In addition to or in lieu of the sensor 1880, a sensor 1890 comprising a load sensor, for example, can measure
30 the closure force applied by the closure drive system to the jaws 7110 and 7120. In various instances, a current sensor 1870 can be employed to measure the current drawn by the motor 1610. The force required to clamp the jaw assembly 7100 can correspond to the current drawn by the motor 1610, for example. The measured force is converted to a digital signal and provided to the processor 1820. A magnetic field sensor can be employed to
35 measure the thickness of the captured tissue. The measurement of the magnetic field sensor can also be converted to a digital signal and provided to the processor 1820.

[0238] The measurements of the tissue compression, the tissue thickness, and/or the force required to close the end effector on the tissue as measured by the sensors can be used by the controller 1840 to characterize the position and/or speed of the movable member being tracked. In at least one instance, a memory 1830 may store a technique, an equation, and/or a look-up table which can be employed by the controller 1840 in the assessment. In various instances, the controller 1840 can provide the user of the surgical instrument with a choice as to the manner in which the surgical instrument should be operated. To this end, the display 1440 can display a variety of operating conditions of the instrument and can include touch screen functionality for data input. Moreover, information displayed on the display 1440 may be overlaid with images acquired via the imaging modules of one or more endoscopes and/or one or more additional surgical instruments used during the surgical procedure.

[0239] As discussed above, the drive module 1100 of the handle 1000 and/or the shaft assemblies 2000, 3000, 4000, and/or 5000, for example, attachable thereto comprise control systems. Each of the control systems can comprise a circuit board having one or more processors and/or memory devices. Among other things, the control systems are configured to store sensor data, for example. They are also configured to store data which identifies the shaft assembly to the handle 1000. Moreover, they are also configured to store data including whether or not the shaft assembly has been previously used and/or how many times the shaft assembly has been used. This information can be obtained by the handle 1000 to assess whether or not the shaft assembly is suitable for use and/or has been used less than a predetermined number of times, for example.

[0240] A drive module 1100' in accordance with at least one alternative embodiment is illustrated in FIGS. 51-53. The drive module 1100' is similar to the drive module 1100 in many respects, most of which will not be discussed herein for the sake of brevity. The drive module 1100' comprises an actuator 1420' configured to control the rotation and articulation of the end effector 7000. Similar to the actuator 1420, discussed above, the actuator 1420' is rotatable about a longitudinal axis LA that extends through a shaft assembly attached to the drive module 1100. For instance, the longitudinal axis LA extends through the center, or substantially the center, of the elongate shaft 2200 of the shaft assembly 3000 (FIG. 1) when the shaft assembly 3000 is assembled to the drive module 1100'. The longitudinal axis LA also extends through the center, or substantially the center, of the end effector 7000 when the end effector 7000 is attached to the shaft assembly 3000, for example.

[0241] The actuator 1420' is rotatable within a channel 1190' defined in the housing 1110 in a first direction to rotate the end effector 7000 in the first direction and, similarly, in a second, or opposite, direction to rotate the end effector 7000 in the second direction. Similar to the drive module 1100, the drive module 1100' comprises a sensor system in

communication with the control system 1800 configured to detect the rotation of the actuator 1420' about the longitudinal axis LA. In at least one instance, the sensor system comprises a first sensor 1422' configured to detect the rotation of the actuator 1420' about the longitudinal axis LA in the first direction (FIG. 52A) and a second sensor 1424' configured to detect the rotation of the actuator 1420' about the longitudinal axis LA in the second direction (FIG. 52B). The first and second sensors 1422' and 1424' comprise Hall Effect sensors, for example, but could comprise any suitable type of sensor. In at least one such instance, further to the above, the actuator 1420' comprises a center magnetic element 1426' positioned in the top of the actuator 1420' which is detectable by the first and second sensors 1422' and 1424' to determine the rotation of the actuator 1420'. The center magnetic element 1426' can comprise a permanent magnet and/or can be comprised of iron and/or nickel, for example.

[0242] Further to the above, the control system 1800 is configured to control the motor assembly 1600 and the clutch system 6000 to rotate the end effector 7000 about the longitudinal axis LA in the first direction when the actuator 1420' is rotated about the longitudinal axis LA in the first direction. Similarly, the control system 1800 is configured to control the motor assembly 1600 and the clutch system 6000 to rotate the end effector 7000 about the longitudinal axis LA in the second direction when the actuator 1420' is rotated about the longitudinal axis LA in the second direction. By associating the rotation of the end effector 7000 about the longitudinal axis LA with the rotation of the actuator 1420' about the longitudinal axis LA, the clinician is provided with a system that is very intuitive to use.

[0243] As discussed above, the end effector 7000 is configured to rotate about a longitudinal axis within a socket defined in the distal attachment portion 2400 of the shaft assembly 2000. Depending on the amount of rotation desired, the end effector 7000 can be rotated less than 360 degrees or more than 360 degrees in either direction. In various instances, the end effector 7000 can be rotated through several rotations in either direction. In alternative embodiments, the rotation of the end effector 7000 about the longitudinal axis can be limited. In at least one embodiment, the shaft assembly 2000 comprises one or more stops which limit the rotation of the end effector 7000 to less than one rotation. In certain embodiments, the control system 1800 monitors the rotation of the drive shaft 1710, such as by an encoder and/or an absolute positioning sensor system, for example, and limits the rotation of the end effector 7000 by stopping or pausing the motor 1610 when the end effector 7000 has reached the end of its permitted range. In at least one instance, the control system 1800 can disengage the second clutch 6210 from the drive shaft 2730 to stop or pause the rotation of the end effector 7000 when the end effector 7000 has reached the end of its permitted range.

[0244] Further to the above, the drive module 1100' and/or a shaft module attached to the drive module 1100' can provide feedback to the clinician that the end effector 7000 has reached the end of its rotation. The drive module 1100' and/or the shaft module attached thereto can comprise an indicator light 1427', such as a red LED, for example, on a first side of the module housing 1110' which is illuminated by the control system 1800 when the end effector 7000 has reached the end of its permitted rotation in the first direction, as illustrated in FIG. 52A. In at least one instance, the drive module 1100' and/or the shaft module attached thereto can comprise an indicator light 1429', such as a red LED, for example, on a second side of the module housing 1110' which is illuminated by the control system 1800 when the end effector 7000 has reached the end of its permitted rotation in the second direction, as illustrated in FIG. 52B. In various instances, further to the above, the illumination of either the first light 1427' or the second light 1429' can indicate to the clinician that the motor 1610 has been paused and that the end effector 7000 is no longer rotating. In at least one instance, the first light 1427' and/or the second light 1429' can blink when the motor 1610 is paused.

[0245] In addition to or in lieu of the above, the drive module 1100' and/or the shaft assembly attached thereto can comprise an annular series, or array, of indicator lights 1428' extending around the perimeter thereof which is in communication with the control system 1800 and can indicate the rotational orientation of the end effector 7000. In at least one instance, the control system 1800 is configured to illuminate the particular indicator light which corresponds, or at least substantially corresponds, with the position in which the top of the end effector 7000 is oriented. In at least one instance, the center of the first jaw 7110 can be deemed the top of the end effector 7000, for example. In such instances, the illuminated light indicates the top-dead-center position of the end effector 7000. In other instances, the control system 1800 can illuminate the particular indicator light which corresponds, or at least substantially corresponds, with the position in which the bottom, or bottom-dead-center, of the end effector 7000 is oriented. In at least one instance, the center of the second jaw 7210 can be deemed the bottom of the end effector 7000, for example. As a result of the above, the illuminated indicator light can follow the rotation of the end effector 7000 around the array of indicator lights 1428'.

[0246] Further to the above, the actuator 1420' is also rotatable, or tiltable, about a transverse axis TA within the housing channel 1190'. The sensor system of the drive module 1100' is further configured to detect the rotation of the actuator 1420' about the transverse axis TA in a first tilt direction and a second tilt direction. In at least one instance, the sensor system comprises a first tilt sensor 1423' configured to detect the rotation of the actuator 1420' about the longitudinal axis TA in the first tilt direction (FIG. 53A) and a second tilt sensor 1425' configured to detect the rotation of the actuator 1420' in the second tilt

direction (FIG. 53B). The first and second tilt sensors 1423' and 1425' comprise Hall Effect sensors, for example, but could comprise any suitable type of sensor. The actuator 1420' further comprises a first lateral magnetic element adjacent the first tilt sensor 1423', the motion of which is detectable by the first tilt sensor 1423'. The actuator 1420' also
5 comprises a second lateral magnetic element adjacent the second tilt sensor 1425', the motion of which is detectable by the second tilt sensor 1425'. The first and second lateral magnetic elements can comprise a permanent magnet and/or can be comprised of iron and/or nickel, for example. As illustrated in FIGS. 53A and 53B, the lateral sides of the actuator 1420' are movable proximally and distally about the transverse axis TA and, as a
10 result, the first and second lateral magnetic elements are also movable proximally and distally relative to the first and second tilt sensors. The reader should appreciate that, while the first and second lateral magnetic elements actually travel along arcuate paths about the transverse axis TA, the distances in which the first and second lateral magnetic elements move is small and, as a result, the arcuate motion of the first and second lateral magnetic
15 elements approximates translation in the proximal and distal directions.

[0247] In various embodiments, further to the above, the entire actuator 1420' comprises a magnetic ring of material which is detectable by the tilt sensors 1423' and 1425' of the drive module 1100'. In such embodiments, the rotation of the actuator 1420' about the longitudinal axis LA would not create a compound motion relative to the tilt sensors when the
20 actuator 1420' is tilted. The magnetic ring of material can comprise a permanent magnet and/or can be comprised of iron and/or nickel, for example.

[0248] In any event, when the sensor system detects that the actuator 1420' has been tilted in the first direction, as illustrated in FIG. 53A, the control system 1800 operates the motor assembly 1600 and the clutch system 6000 to articulate the end effector 7000 about
25 the articulation joint 2300 in the first direction. Similarly, the control system 1800 operates the motor assembly 1600 and the clutch system 6000 to articulate the end effector 7000 about the articulation joint 2300 in the second direction when the sensor system detects that the actuator 1420' has been tilted in the second direction, as illustrated in FIG. 53B. By associating the rotation of the end effector 7000 about the articulation joint 2300 with the
30 rotation of the actuator 1420' about the transverse axis TA, the clinician is provided with a system that is very intuitive to use.

[0249] Further to the above, the actuator 1420' comprises a biasing system configured to center the actuator 1420' in its unrotated and untilted position. In various instances, the biasing system comprises first and second rotation springs configured to center the actuator
35 1420' in its unrotated position and first and second tilt springs configured to center the actuator 1420' in its untilted position. These springs can comprise torsion springs and/or linear displacement springs, for example.

[0250] As discussed above, the end effector 7000 rotates relative to the distal attachment portion 2400 of the shaft assembly 3000. Such an arrangement allows the end effector 7000 to be rotated without having to rotate the shaft assembly 3000, although embodiments are possible in which an end effector and shaft assembly rotate together. That said, by rotating the end effector 7000 relative to the shaft assembly 3000, all of the rotation of the surgical system occurs distally relative to the articulation joint 2300. Such an arrangement prevents a large sweep of the end effector 7000 when the end effector 7000 is articulated and then rotated. Moreover, the articulation joint 2300 does not rotate with the end effector 7000 and, as a result, the articulation axis of the articulation joint 2300 is unaffected by the rotation of the end effector 7000. In order to mimic this arrangement, the transverse axis TA does not rotate with the actuator 1420'; rather, the transverse axis TA remains stationary with respect to the drive module 1100'. That said, in alternative embodiments, the transverse axis TA can rotate, or track the end effector 7000, when the articulation joint rotates with the end effector. Such an arrangement can maintain an intuitive relationship between the motion of the actuator 1420' and the motion of the end effector 7000.

[0251] Further to the above, the transverse axis TA is orthogonal, or at least substantially orthogonal, to the longitudinal axis LA. Similarly, the articulation axis of the articulation joint 2300 is orthogonal, or at least substantially orthogonal, to the longitudinal axis LA. As a result, the transverse axis TA is parallel to, or at least substantially parallel to, the articulation axis.

[0252] In various alternative embodiments, the tiltable actuator 1420' is only used to control the articulation of the end effector 7000 and is not rotatable about the longitudinal axis LA. Rather, in such embodiments, the actuator 1420' is only rotatable about the transverse axis TA. In at least one instance, the housing of the drive module 1100' comprises two posts 1421' (FIG. 51) about which the actuator 1120' is rotatably mounted which defines the transverse axis TA. The posts 1421' are aligned along a common axis. The above being said, the posts 1421', or any suitable structure, can be used in embodiments in which the actuator 1420' is both rotatable and tiltable to control the rotation and articulation of the end effector 7000. In at least one such instance, the actuator 1420' comprises an annular groove defined therein in which the posts 1421' are positioned.

[0253] In various instances, the drive module 1100 and/or the shaft assembly attached thereto can comprise a series, or array, of indicator lights 1438' which is in communication with the control system 1800 and can indicate the articulation orientation of the end effector 7000. In at least one instance, the control system 1800 is configured to illuminate the particular indicator light which corresponds, or at least substantially corresponds, with the position in which the end effector 7000 is articulated. As a result of the above, the illuminated indicator light can follow the articulation of the end effector 7000. Such an array

of indicator lights can assist a clinician in straightening the end effector 7000 before attempting to remove the end effector 7000 from a patient through a trocar. In various instances, an unstraightened end effector may not pass through a trocar and prevent the removable of the end effector from the patient.

5 **[0254]** A drive module 1100" in accordance with at least one alternative embodiment is illustrated in FIGS. 54-57. The drive module 1100" is similar to the drive modules 1100 and 1100' in many respects, most of which will not be discussed herein for the sake of brevity. The drive module 1100" comprises a feedback system configured to inform the clinician using the surgical instrument system that the drive shaft and/or any other rotatable
10 component of the surgical instrument system is rotating. The feedback system can use visual feedback, audio feedback, and/or tactile feedback, for example. Referring primarily to FIG. 55, the drive module 1100" comprises a tactile feedback system which is operably engageable with the drive shaft 1710" of the drive module 1100". The tactile feedback system comprises a slideable clutch 1730", a rotatable drive ring 1750", and an eccentric, or
15 offset, mass 1770" mounted to the drive ring 1750". The clutch 1730" is slideable between an unactuated position (FIG. 56) and an actuated position (FIG. 57) along the drive shaft 1710". The drive shaft 1710" comprises one or more slots 1740" defined therein which are configured to constrain the movement of the slideable clutch 1730" relative to the drive shaft 1710" such that the clutch 1730" translates longitudinally relative to the drive shaft 1710" but
20 also rotates with the drive shaft 1710". The frame shaft 1510" of the handle frame 1500" comprises an electromagnet 1530" embedded therein which is configured to emit a first electromagnetic field to slide the clutch 1730" toward its actuated position, as illustrated in FIG. 57, and a second, or opposite, electromagnetic field to slide the clutch 1730" toward its unactuated position, as illustrated in FIG. 56. The clutch 1730" is comprised of a permanent
25 magnet and/or a magnetic material such as iron and/or nickel, for example. The electromagnet 1530" is controlled by the control system 1800 to apply a first voltage polarity to a circuit including the electromagnet 1530" to create the first electromagnetic field and a second, or opposite, voltage polarity to the circuit to create the second electromagnetic field.

[0255] When the clutch 1730" is in its unactuated position, as illustrated in FIG. 56, the
30 clutch 1730" is not operably engaged with the drive ring 1750". In such instances, the clutch 1730" rotates with the drive shaft 1710", but rotates relative to the drive ring 1750". Stated another way, the drive ring 1750" is stationary when the clutch 1730" is in its unactuated position. When the clutch 1730" is in its actuated position, as illustrated in FIG. 57, the clutch 1730" is operably engaged with an angled face 1760" of the drive ring 1750" such that
35 the rotation of the drive shaft 1710" is transmitted to the drive ring 1750" via the clutch 1730" when the drive shaft 1710" is rotated. The eccentric, or offset, mass 1770" is mounted to the drive ring 1750" such that the eccentric mass 1770" rotates with the drive ring 1750". In at

least one instance, the eccentric mass 1770" is integrally-formed with the drive ring 1750". When the drive ring 1750" and eccentric mass 1770" rotate with the drive shaft 1710", the eccentric mass 1770" creates a vibration that can be felt by the clinician through the drive module 1100" and/or the power modules assembled thereto. This vibration confirms to the clinician that the drive shaft 1710" is rotating. In at least one instance, the control system 1800 energizes the electromagnet 1530" when one of the clutches of the clutch system 6000 is energized. In such instances, the vibration can confirm to the clinician that the drive shaft 1710" is rotating and that one of the clutches in the clutch system 6000 is engaged with the drive shaft 1710". In at least one instance, the clutch 1730" can be actuated when the jaw assembly 7100, for example, has reached or is reaching its closed position such that the clinician knows that the tissue has been clamped within the jaw assembly 7100 and that the surgical instrument can be used to manipulate the tissue. The above being said, the tactile feedback system, and/or any other feedback system, of the drive module 1100" can be used to provide tactile feedback when appropriate.

[0256] Sterilization processes are part of customary surgical preparation procedures. A variety of sterilization processes exist for surgical instruments. Various methods include sterilization by way of autoclave which utilizes high heat and pressure, and sterilization utilizing steam, dry heat, and/or radiation, for example. However, one of the most widely used methods of sterilization is ethylene oxide processing. Ethylene oxide is an alkylating chemical compound which inhibits and disrupts the DNA of microorganisms in order to prevent reproduction of those organisms. Ethylene oxide processing is a highly effective sterilization process, but it does not come without cost. Some of the early steps involved during ethylene oxide processing involve heating the surgical instruments to a sustainable internal temperature and humidifying the surgical instruments. Often times, the surgical instruments undergo the heating and humidifying processes for anywhere from twelve to seventy-two hours during a single sterilization process. In addition to the heat and humidity, the potency of ethylene oxide tends to affect the soft electronic circuitry of powered surgical instruments. In the field of endoscopy, certain components of the powered endoscopy surgical instruments, such as display screens, for example, react poorly to the sterilization process when ethylene oxide is used. Improperly functioning display screens could result in difficulties and/or delays during a surgical procedure. Thus, a need exists for a surgical instrument system which incorporates a variety of cost-efficient disposable and replaceable components in order to avoid the damage caused by the sterilization process.

[0257] A surgical instrument system is illustrated in FIG. 58. The surgical instrument system illustrated in FIG. 58 is similar to the surgical instrument system depicted in FIG. 1 in many respects, most of which will not be repeated herein out of the sake of brevity. The surgical instrument system comprises a variety of interchangeable shaft assemblies and

power modules, as will be discussed in greater detail below. The surgical instrument system comprises a handle assembly 11000. The handle assembly 11000 is usable with a variety of interchangeable shaft assemblies, such as a shaft assembly 12000, a shaft assembly 13000, a shaft assembly 14000, a shaft assembly 15000, and/or other any other suitable shaft assembly. The interchangeable shaft assemblies 12000, 13000, 14000, and 15000 are similar to the shaft assemblies 2000, 3000, 4000, and 5000 in many respects. Similar to the shaft assembly 2000, the shaft assembly 12000 comprises a proximal end portion 12100 and an elongate shaft 12200 extending from the proximal end portion 12100. The shaft assembly 12000 also comprises an end effector 12400 which is rotatably attached to the elongate shaft 12200 by an articulation joint 12300. The end effector 12400 comprises a first jaw 17000 and a second jaw 17100. Similar to the shaft assembly 12000, the shaft assembly 13000 comprises a proximal end portion 13100, and an elongate shaft 13200 extending from the proximal end portion 13100. The shaft assembly 13000 is also configured for use with the end effector 12400 which is rotatably attached to the elongate shaft 13200 by an articulation joint 12300. Similar to the shaft assembly 12000, the shaft assembly 14000 comprises a proximal end portion 14100, and an elongate shaft 14200 extending from the proximal end portion 14100. The shaft assembly 14000 is also configured for use with an end effector 12400' which is rotatably attached to the elongate shaft 14200 by an articulation joint 12300. The end effector 12400' comprises a first jaw 18000 and a second jaw 18100. The shaft assembly 15000 comprises similar components to those of the shaft assemblies 12000, 13000, and 14000, many of which will not be discussed in detail for the sake of brevity.

[0258] Still referring to FIG. 58, the handle assembly 11000 comprises a drive module 11100. The drive module 11100 comprises a distal mounting interface 11130 which allows for the selective and separate engagement of any one of the shaft assemblies 12000, 13000, 14000, and 15000 with the drive module 11100. Each of the shaft assemblies 12000, 13000, 14000, and 15000 comprises the same or a substantially similar proximal mounting interface which is configured to engage the distal mounting interface of the drive module 11100. Still referring to FIG. 58, the shaft assembly 12000 comprises a proximal mounting interface 12130 which is configured for attachment to the distal mounting interface 11130 of the drive module 11100 by at least one latch 11140 of the drive module 11100. Similarly, the shaft assembly 13000 comprises a proximal mounting interface 13130 which is configured for attachment to the distal mounting interface 11130 of the drive module 11100 by at least one latch 11140 of the drive module 11100. Also, similarly, the shaft assembly 14000 comprises a proximal mounting interface 14130 which is configured for attachment to the distal mounting interface 11130 of the drive module 11100 by at least one latch 11140 of the drive module 11100. Likewise, the shaft assembly 15000 comprises a proximal

mounting interface 15130 which is configured for attachment to the distal mounting interface 11130 of the drive module 11100. The drive module 11100 is configured to electrically couple to each of the shaft assemblies 12000, 13000, 14000, and 15000. The surgical instrument system comprises a motor positioned in the handle assembly 11000, as will be discussed in greater detail below. Each of the shaft assemblies 12000, 13000, 14000, and 15000 comprises a control circuit as will be discussed in greater detail below. The control circuit is configured to interact with the motor in order to control various functions of the surgical instrument system. The surgical instrument system further comprises a motor-control processor which is configured to communicate with the control circuit in order to control the motor. Referring to FIG. 76A, the processor is positioned in any suitable portion of the surgical instrument apart from the drive module 11100. For example, the processor is positioned in a shaft assembly of the surgical instrument system. The handle assembly 11000 is configured for use with at least one power module as will be discussed in greater detail below.

[0259] Referring to FIGS. 58 and 59, the drive module 11100 comprises a housing 11110 which is capable of use with a variety of power modules such as the power modules 11200 and 11300, for example. In various instances, each power module 11200 and 11300 comprises one or more battery cells, as illustrated in FIG. 59, which are configured to enable pistol, scissor, and/or pencil grip configurations comprising different load requirements. In particular, the housing 11110 comprises a first attachment portion 11120 and a second attachment portion 11120' which are configured to engage either the power module 11200 or the power module 11300 at either the bottom of the handle assembly 11000 or the proximal end of the handle assembly 11000 depending on which shaft assembly is attached to the handle assembly 11000. For example, when the shaft assembly 14000 is attached to the handle assembly 11000, a power module is attached to the proximal end of the handle assembly 11000 in a first configuration as illustrated in FIG. 58. As another example, when the shaft assembly 13000 is attached to the handle assembly 11000, a power module is attached to the bottom of the handle assembly 11000 in a second configuration. As illustrated in FIGS. 58 and 59, the first configuration and the second configuration are different from one another.

[0260] Still referring to FIG. 59, the drive module 11100 comprises a rotation actuator 11420 which is similar to the rotation actuator 1420, which is described in greater detail above. The drive module 11100 further comprises release actuators 11150 which, when depressed by a clinician, move the latches 11140 from their locked positions into their unlocked positions. The drive module 11100 comprises a first release actuator 11150 slideably mounted in an opening defined in the first side of the handle housing 11110 and a

second release actuator 11150 slideably mounted in an opening defined in a second, or opposite, side of the handle housing 11110.

[0261] Referring to FIGS. 59 and FIG. 60, the drive module 11100 comprises an articulation actuator 11430. The articulation actuator 11430 comprises a first push button 11432 and a second push button 11434. The first push button 11432 is part of a first articulation control circuit and the second push button 11434 is part of a second articulation circuit of an input system similar to the input system 1400 discussed in greater detail above.

[0262] Referring again to FIG. 58, the surgical instrument system comprises a power module 11200. The power module 11200 comprises a housing 11210, a connector portion 11220, and at least one battery (as illustrated in at least FIG. 59). The connector portion 11220 is configured to be engaged with the first connector portion 11120 in order to attach the power module 11200 to the bottom of the handle assembly 11000. The power module 11200 comprises at least one latch 11240 positioned at the top of the power module 11200 which is configured to secure the power module 11200 to the bottom of the drive module 11100. More specifically, the latch 11240 is configured to securely attach the housing 11210 of the power module 11200 to the housing 11110 of the drive module 11100 located within the handle assembly 11000. The connector portion 11220 comprises a plurality of electrical contacts which enable an electrical connection between the power module 11200 and the drive module 11100. The power module 11200 comprises a release latch 11250 which is configured to release the power module 11250 from the drive module 11000.

[0263] Referring again to FIG. 58, the surgical instrument system comprises a power module 11300. The power module 11300 comprises a housing 11310, a connector portion 11320, and at least one battery. The connector portion 11320 is configured to be engaged with the second connector portion 11120' in order to attach the power module 11300 to the handle assembly 11000. The power module 11300 comprises at least one latch 11340 positioned at a distal end of the power module 11300 which is configured to secure the power module 11300 to the drive module 11100. More specifically, the latch 11340 is configured to securely attach the housing 11310 of the power module 11300 to the housing 11110 of the drive module 11100 located within the handle assembly 11000. The connector portion 11320 comprises a plurality of electrical contacts which enable an electrical connection between the power module 11300 and the drive module 11100.

[0264] Still referring to FIG. 58, the power module 11200 and the power module 11300 each comprise at least one display unit. The power module 11200 comprises a display unit 11440 located on the power module housing 11210. The power module 11300 comprises a display unit 11440'. The display units 11440 and 11440' can comprise any suitable display screen, for example, configured for use with a powered surgical device. In various instances, the display units 11440 and 11440' comprise an electrochromic display. The

electrochromic display comprises an array of electrodes created from a metal oxide semiconductor. The electrodes are mounted on a flexible film comprising attachments of electrochromic molecules. As a charge is applied to the semiconducting electrodes, the electrochromic molecules travel to the surface of the film to receive the charge. As the electrochromic molecules are charged, a change in color occurs in the molecules. Suitable versions of this type of display screen are available from Ntera and Seiko, for instance.

[0265] In certain instances, the display units 11440 and 11440' comprise an electrophoretic display. The electrophoretic display comprises titanium dioxide particles approximately one micrometer in diameter which are dispersed in a hydrocarbon oil, for example. A dark-colored dye is also added to the oil, along with surfactants and charging agents that cause the particles to take on an electric charge. The mixture of titanium dioxide particles and hydrocarbon oil is placed between two parallel conductive plates separated by a gap of 10 to 100 micrometers, for example. The parallel conductive plates comprise opposite charges from one another. When a voltage is applied across the two plates, the titanium dioxide particles migrate electrophoretically to the plate that bears the opposite charge from the charge of the particles. When the particles are located at the front (viewing) side of the display, it appears white, because light is scattered back to the viewer by the high-index titanium dioxide particles. When the particles are located at the rear side of the display, it appears dark, because the incident light is absorbed by the colored dye. If the rear electrode is divided into a number of small picture elements (pixels), then an image can be formed by applying the appropriate voltage to each region of the display to create a pattern of reflecting and absorbing regions.

[0266] Other suitable variations of display screens include various types of liquid-crystal displays including liquid-crystal character display modules, thin film transistor liquid-crystal displays, and/or any other suitable display screens. Liquid crystal character display modules are flat-panel displays which use the light-modulating properties of liquid crystals in order to produce images in color or monochrome by using a backlight or a reflector. Thin film transistor liquid-crystal displays use thin-film transistor technology to provide for improved image qualities including, but not limited to, contrast. Additional types of display screens comprise touch screen capable screens and/or active matrix backplanes comprising an amorphous silicon semiconductor or a polythiophene semiconductor, for example.

[0267] Referring primarily to FIG. 59, the power module 11200 is attached to the handle assembly 11000 in a first orientation. When the power module 11200 is positioned in the first orientation, a first maximum level of power is supplied to the surgical instrument system. As seen in FIG. 59, the surgical instrument system comprises a pistol grip when the power module 11200 is attached to the surgical instrument. Still referring to FIG. 59, the power module 11200 comprises at least a first battery 11230 and a second battery 11260.

Referring to FIG. 60, the power module 11300 comprises a housing 11310 which is configured to attach the power module 11300 to the handle assembly 11000 in a second orientation. The second orientation of the power module 11300 is configured to supply an appropriate amount of power when the surgical instrument comprises a pencil or wand grip configuration. The power module 11200 is configured to supply more power to the surgical instrument when the power 11200 is in the first orientation, and the power module 11300 is configured to supply less power to the surgical instrument in the second orientation. The use of various power modules ensures that the necessary amount of power for the operation of the surgical instrument system is provided. With respect to FIGS. 60-62, the drive module 11100 comprises the same and/or similar components as the drive module 1100 discussed in detail above with respect to FIGS. 7-9. That is, the drive module 11100 interacts with each of the shaft assemblies 12000, 13000, 14000, and 15000 in the same and/or a similar manner as the drive module 1100 interacts with the shaft assemblies 2000, 3000, 4000, and 5000.

[0268] FIGS. 63-65 illustrate the surgical instrument system comprising the power module 11300 in the first orientation for use with the scissor grip configuration of the shaft assembly 14000. The surgical instrument system illustrated in FIGS. 63-65 is similar in some aspects to the surgical instrument system illustrated in FIGS. 45-47, which is discussed in greater detail above and is also configured for use with the power module 11300 which comprises the display unit 11440'. Various surgical instruments described herein are compatible with the power modules 11200 and 11300.

[0269] Turning now to FIG. 66, a surgical instrument system can comprise a variety of handle assemblies such as a pencil grip handle, a scissor grip handle, a pistol grip handle, among others, and a shaft assembly, such as the shaft assembly 20000, for example, that can be used with each of the handle assemblies. The surgical instrument system comprises a first handle assembly 21000, which is a pencil grip handle. Referring primarily to FIGS. 66A and 68A, the first handle assembly 21000 comprises one electric drive motor, a first drive shaft 21100, and a first set of controls which controls the one electric drive motor. The drive shaft 21100 of the one drive motor is configured to be coupled with a drive system of the shaft assembly 20000 when the shaft assembly 20000 is attached to the handle assembly 21000. The drive motor used in connection with the surgical instrument system of FIG. 66 is similar in many respects to other motors discussed in detail above, such as the motor 1610, for example. The first handle assembly 21000 further comprises a plurality of electrical contacts 21022 for placing the handle assembly 21000 in electrical communication with the shaft assembly 20000 via electrical contacts 20022 defined thereon. Referring to FIGS. 66 and 66A, the first handle assembly 21000 further comprises an insertable power module 21020 at the proximal end of the handle assembly 21000.

[0270] The surgical instrument system further comprises a second handle assembly 22000, which is a scissors grip handle. Referring primarily to FIG. 66B, the second handle assembly 22000 comprises first and second electric drive motors, a drive shaft 22100, a second drive shaft 22200, a first set of controls which controls the first drive motor, and a second set of controls which controls the second drive motor. The first drive shaft 22100 and the second drive shaft 22200 of the first and second drive motors can be coupled with two drive systems of the shaft assembly 20000. The first and second drive motors are similar in many respects to other motors discussed in detail above, such as the motor 1610, for example. The second handle assembly 22000 further comprises a plurality of electrical contacts 22022 for placing the handle assembly 22000 in electrical communication with the shaft assembly 20000 via electrical contacts 20022 defined thereon as seen in FIG. 66D. Referring primarily to FIGS. 66 and 66B, the second handle assembly 22000 further comprises an insertable power module 22020 at the proximal end of the handle assembly 22000.

[0271] Referring to FIG. 66 and 66C, the surgical instrument system further comprises a third handle assembly 23000, which is a pistol grip handle. The third handle assembly 23000 comprises first, second, and third electric drive motors, a first drive shaft 23100, a second drive shaft 23200, a third drive shaft 23300, a first set of controls which controls the first drive motor, a second set of controls which controls the second drive motor, and a third set of controls which controls the third drive motor. The third handle assembly 23000 comprises a third set of controls. The first drive shaft 23100, the second drive shaft 23200, and the third drive shaft 23300 can be coupled with the three drive systems of the shaft assembly 20000. The third handle assembly 23000 further comprises a plurality of electrical contacts 23022 for placing the handle assembly 23000 in electrical communication with the shaft assembly 20000 via electrical contacts 20022 defined thereon as seen in FIG. 66C and 66G. The third handle assembly 23000 further comprises an insertable power module 23020 at the proximal end of the handle assembly 23000.

[0272] Further to the above, the shaft assembly 20000 comprises three drive systems which are drivable by a drive motor of a handle assembly - this is, of course, assuming that the handle assembly that the shaft assembly 20000 is attached to has a sufficient number of drive motors to drive all three drive systems of the shaft assembly 20000. Stated another way, the first handle assembly 21000 has only one drive motor to drive one of the drive systems of the shaft assembly 20000 and, similarly, the second handle assembly 22000 has only two drive motors to drive two of the drive systems of the shaft assembly 20000. Thus, two drive systems of the shaft assembly 20000 cannot be driven by the first handle assembly 21000 and one drive system of the shaft assembly 20000 cannot be driven by the second handle assembly 22000. In various instances, the undriven system, or systems, of

the shaft assembly 20000 can remain inert while the other drive system, or systems, of the shaft assembly 20000 are being used. In at least one embodiment, the handle assemblies 21000 and 22000 can be configured to lock out the drive systems of the shaft assembly 20000 that aren't being used. In at least one instance, the handle assembly 21000
5 comprises two stationary posts extending therefrom which engage the second and third drive systems of the shaft assembly 20000 when the shaft assembly 20000 is assembled to the handle assembly 21000. The stationary posts prevent the second and third drive systems of the shaft assembly 20000 from being unintentionally actuated. Similarly, the handle assembly 22000 comprises one stationary post extending therefrom which engages
10 the third drive system of the shaft assembly 20000 to prevent the third drive system from being unintentionally actuated. The third handle assembly 23000 does not comprise stationary posts to lock a drive system of the shaft assembly 20000 as all three drive systems of the shaft assembly 20000 are coupled to a drive motor in the third handle assembly 23000.

[0273] In addition to or in lieu of the above, the shaft assembly 20000 can comprise a second lock that is biased into a locked configuration to lock the second drive system in place and a third lock that is biased into a locked configuration to lock the third drive in place. When the shaft assembly 20000 is attached to the first handle assembly 21000, the shaft assembly 20000 does not receive electrical power from the first handle assembly 21000 to
20 unlock the second lock or the third lock. When the shaft assembly 20000 is attached to the second handle assembly 22000, the shaft assembly 20000 receives electrical power from the second handle assembly 22000, via the electrical contacts 22022, and the second lock is unlocked so that the second drive system of the shaft assembly 20000 can be used by the second handle assembly 22000. That said, the second handle assembly 22000 does not
25 receive electrical power from the second handle assembly 22000 to unlock the third lock as the second and third locks are part of separate and distinct circuits. When the shaft assembly 20000 is attached to the third handle assembly 23000, the shaft assembly 20000 receives power from the third handle assembly 23000, via the electrical contacts 23022, to unlock the second and third locks so that the second and third drive systems of the shaft
30 assembly 20000 can be used by the third handle assembly 23000.

[0274] As discussed above and referring to FIG. 66, the shaft assembly 20000 is selectively attachable to the first handle assembly 21000, the second handle assembly 22000, and the third handle assembly 23000. That being said, the handle assemblies 21000, 22000, and 23000 are all configured to be held differently by a clinician. The pen
35 configuration of the first handle assembly 21000 is configured to be held, or pinched, between the clinician's thumb and index finger on one hand. The scissors configuration of the second handle assembly 22000 is configured to be gripped by an outstretched hand of

the clinician. The pistol configuration of the third handle assembly 23000 is configured to be gripped by a closed, clenched hand of the clinician. As a result, the handle configurations 21000, 22000, and 23000 can be configured such that the shaft assembly 20000 is attached thereto in different orientations to match the grip orientation of the clinician's hand. For instance, the shaft assembly 20000 is attached to the handle assembly 21000 in a first orientation and attached to the shaft assemblies 22000 and 23000 in a second orientation which is rotated 90 degrees from the first orientation. Such an arrangement matches the typical expectations of the clinician regarding the orientation of the shaft assembly 20000 relative to their hand. Similarly, the first set of controls on the first handle assembly 21000 for controlling the first drive motor can be oriented 90 degrees relative to the orientation of the first set of controls on the second handle assembly 22000 and the third handle assembly 23000. Moreover, it can be desirable for a certain function of the shaft assembly 20000 to be always coupled to a motor-driven drive system regardless of the handle assembly that it is attached to. To achieve this, in various instances, the shaft assembly 20000 may have to be attached to the handles 21000, 22000, and 23000 in different orientations to align the articulation drive system, for example, to a motor-driven drive system.

[0275] Further information regarding the different configurations of the handle assemblies 21000, 22000, and 23000 are presented in FIG. 69. For example, the pencil handle assembly 21000 comprises a motor-driven output which is configured to enable right and left articulation of the shaft 20400. The end effector can be manually rotated relative to the shaft 20400. The pencil handle assembly 21000 is not configured to perform any actuation motions of the end effector or rotation of the shaft 20400 as it does not comprise a motor driven output for the actuation motions of the end effector or the rotation of the shaft 20400. As another example, the scissor grip handle assembly 22000 comprises a motor-driven output which is configured to enable right and left articulation of the shaft 20400. The scissor grip handle assembly 22000 comprises another motor-driven output which is configured to enable a first actuation motion of the end effector. The scissor grip handle assembly 22000 is not configured to perform a second actuation motion of the end effector or rotation of the shaft 20400 as it does not comprise a motor-driven output for the second actuation motion of the end effector or the rotation of the shaft 20400. As another example, the pistol handle assembly 23000 comprises motor-driven outputs which are configured to enable right and left articulation of the shaft 20400. The pistol handle assembly also comprises motor-driven outputs which are configured to enable the first and second actuation motions of the end effector as well as rotation of the shaft 20400 via a motor and a shiftable transmission.

[0276] Referring primarily to FIGS. 66D and 68D, a handle assembly 24000, which is similar to the handle assembly 22000 in many respects, comprises at least one spring

loaded pin 24024 which is configured to flex to allow the shaft assembly 20000 to be releasably held to the shaft assembly 20000. Such an arrangement can be adapted to the handle assemblies 21000, 22000, and 23000 to releasably hold the shaft assembly 20000 thereto. Similar to the handle assembly 22000, the handle assembly 24000 comprises a set of electrical contacts 24022, a first drive shaft 24100, and a second drive shaft 24200.

[0277] As discussed above, the shaft assembly 20000 comprises a first drive shaft 20100, a second drive shaft 20200, and a third drive shaft 20300, each of which enables a particular function of the surgical instrument system by establishing a mechanical connection with a drive shaft in any one of the handle assemblies 21000, 22000, and 23000 - so long as the handle assembly has a sufficient number of drives to be coupled to. While the shaft assembly 20000 is attached to the first handle assembly 21000, certain functions of the surgical instrument and/or the end effector are enabled and certain functions of the surgical instrument and/or the end effector are locked out as seen in FIG. 69 and described in greater detail above. For example, the first handle assembly 21000 can drive the articulation system of the shaft 20400 with its one drive motor. All other functions of the shaft assembly 20000 would have to be performed by the manual manipulation of the first handle assembly 21000. Referring primarily to FIG. 66, the pencil grip configuration of the handle assembly 21000 does not afford a motor-driven output for actuating the end effector and/or rotating the shaft 20400.

[0278] The second handle assembly 22000 comprises two motors configured to drive two of the drives of the shaft assembly 20000. While the shaft assembly 20000 is attached to the second handle assembly 22000, certain functions of the surgical instrument and/or the end effector are enabled and certain functions of the surgical instrument and/or the end effector are locked out as seen in Table A of FIG. 69 and described in greater detail above. The first motor of the second handle assembly 22000 drives the articulation drive of the shaft assembly 20000 and the second motor of the second handle assembly 22000 drives a jaw assembly of the shaft assembly 20000 to move the jaw assembly between open and closed configurations. The third function of the shaft assembly 20000, i.e., the rotation of the jaw assembly about a longitudinal axis must be performed manually by rotating the second handle assembly 22000 about the longitudinal axis. The third handle assembly 23000 comprises three motors configured to drive all three of the drives of the shaft assembly 20000. While the shaft assembly 20000 is attached to the third handle assembly 23000 in the third orientation, none of the functions of the surgical instrument and/or the end effector are locked out as seen in Table A of FIG. 69 and described in greater detail above.

[0279] Referring to FIG. 70, the third handle assembly 23000 comprises a pistol grip configured for use with a smoke evacuation tube 23400. The smoke evacuation tube 23400 is configured to fit inside a groove 23420 within the handle assembly 23000. The shaft

assembly 20000 further comprises a smoke evacuation tube 20410 which fits over the shaft 20400. Referring to FIG. 71, the third handle assembly 23000 comprises a first motor 23062 configured to power the right and left articulation of the end effector. The third handle assembly comprises a second motor configured to power the jaw drive of the shaft assembly 20000. The third handle assembly 23000 comprises a third motor configured to power the rotation of the end effector about the longitudinal axis. The handle assembly 23000 further comprises a first gear box 23064 to reduce the speed of the first motor and a second gear box 23068 to reduce the speed of the second motor. Still referring to FIG. 71, the insertable power module 23020 comprises at least two battery cells 23040 and 23050.

[0280] Referring to FIG. 72, the second handle assembly 22000 comprises a scissor grip configuration for use with a smoke evacuation tube 22400. The smoke evacuation tube 22400 is configured to fit inside a groove 22420 within the handle assembly 22000. Referring to FIG. 73, the handle assembly 22000 comprises a first motor 22062 and a second motor 22066 which are configured to power certain functions of the surgical instrument system as discussed above. Referring to FIG. 73B for example, the first motor 22062 is configured to power right and left articulation of the end effector, for example. The second motor 22066 is configured to power the jaw drive of the shaft assembly 20000. When the handle assembly 22000 is in use, the rotation of the end effector is performed manually by the clinician. The handle assembly 22000 further comprises a first speed reduction gear box 22064 and a second speed reduction gear box 22068 disposed within the handle assembly 22000. Still referring to FIG. 73, the insertable power module 22020 comprises at least two battery cells 22040 and 22050.

[0281] Referring to FIG. 74, the first handle assembly 21000 comprises a pencil grip configured for use with a smoke evacuation tube 21400. The smoke evacuation tube 21400 is configured to fit inside a groove 21420 within the handle assembly 21000. The shaft assembly 20000 further comprises a smoke evacuation tube 20410 which fits over the shaft 20400. Referring to FIG. 75, the handle assembly 21000 comprises a motor 21062 which is configured to power the right and left articulation of the end effector. When the handle assembly 21000 is in use, the rotation of the end effector is performed manually by the clinician, and certain functions such as a first actuation motion and a second actuation motion of the end effector are locked out as seen in FIG. 75B. The handle assembly 21000 further comprises a speed reduction gear box 21064 disposed within the handle assembly 21000. Still referring to FIG. 75, the insertable power module 21020 comprises at least two battery cells 21040 and 21050.

[0282] Referring to FIG. 77, various surgical instrument systems described herein comprise one or more feedback systems which are configured to alert the clinician as to the state of the surgical instrument system. The surgical instrument system comprises a handle

assembly 26000 which includes a first drive 26100, a second drive 26200, and a third drive 26300 which are configured to permit drive systems within the handle assembly 26000 to be operably coupled to the drive systems of a shaft assembly 27000. The shaft assembly 27000 is similar to the shaft assembly 20000 in many respects. The handle assembly 26000 further comprises a plurality of electrical contacts 26022 configured to place the handle assembly 26000 in electrical communication with the shaft assembly 27000. The shaft assembly 27000 comprises an actuation rod 27700 extending within a shaft 27770, wherein the actuation rod 27700 is drivable by a drive system of the handle assembly 26000. The shaft assembly 27000 further comprises an end effector 27200 rotatably attached to the shaft 27770 about an articulation joint 27300. The end effector 27200 comprises a first jaw 27220 and a second jaw 27222 which are movable between open and closed positions in response to the motions of the actuation rod 27700. The handle assembly 26000 further comprises a curved trigger 26400 rotatably connected to the handle assembly 26000 which, as described in greater detail below, is used to control the drive system. The curved trigger 26400 comprises a curved trigger rod 26500 extending therefrom, as also discussed in greater detail below.

[0283] Referring to FIG. 79, further to the above, the handle assembly 26000 comprises a motor control system 26010 which is configured to run a motor 26030 configured to drive the drive system of the shaft assembly 27000 as mentioned above. The handle assembly 26000 further comprises a power module 26028 configured to supply power to the motor 26030 at the direction of a motor control system 26010. The handle assembly 26000 comprises a trigger sensor 26800 which is in communication with the motor control system 26010 and is configured to monitor the motion of the trigger 26400. The trigger sensor 26800 is configured to generate a voltage potential which is detectable by the motor control system 26010 - the magnitude of which can be used to ascertain the actuation and/or position of the trigger 26400. In response to the signal from the trigger sensor 26800, the motor control system 26010 is configured to run the motor 26030 to drive the drive rod 26050. In various instances, the trigger sensor 26800 comprises a variable resistance sensor, for example, and the speed of the motor 26030 is responsive to the signal provided by the trigger sensor 26800.

[0284] As the drive rod 26050 is driven distally by the motor 26030, the drive rod 26050 experiences a force load. There is a wide range of acceptable force loads that the drive rod 26050 may experience during use. That said, such force loads can suggest certain information about the performance of the surgical system. For instance, force loads toward the top of the acceptable range can indicate that thick and/or dense tissue is captured within the end effector 27200 while force loads toward the bottom of the acceptable range can indicate that thin and/or less dense tissue is captured within the end effector 27200, for

example. Without more, this information is not conveyed to the clinician as the trigger 26400 is not mechanically coupled to the drive rod 26050; rather, the trigger 26400 is electrically coupled to the motor 26030 via the motor control system 26010. Without this information, a clinician may not fully appreciate what is occurring within the surgical system. To this end, the surgical instrument system comprises means for detecting the force load experienced by the drive rod 26050 and communicating this information to the clinician. In at least one instance, the surgical instrument system comprises one or more load cells and/or strain gauges configured to detect the force load within the drive rod 26050. In addition to or in lieu of these mechanical detection systems, the motor control system 26010 is configured to monitor the current drawn by the electric motor 26030 during use and this information as a proxy for the force load being experienced by the drive rod 26050. Referring to FIG. 79, the handle assembly comprises a current sensor 26012 in communication with the power control system 26020, and/or the motor control system 26010, which is configured to monitor the amount of current drawn by the motor 26030. Discussed below are systems which can restore the clinician's sense for the loads being experienced within the drive system based on the load data supplied to the power control system 26020.

[0285] Referring to FIGS. 77A and 77B, the handle assembly 26000 further comprises an electroactive polymer (hereinafter "EAP") 26600 positioned within an aperture defined therein. The EAP 26600 is in signal communication with the power control system 26020 and is responsive to a voltage output provided by the power control system 26020.

Referring primarily to FIG. 77B, the handle assembly 26000 comprises a curved cylinder 26900 which surrounds a portion of the curved trigger rod 26500 of the trigger 26400. More specifically, the curved trigger rod 26500 comprises a trigger bar 26550 extending through the curved cylinder 26900 positioned within the handle assembly 26000. The EAP 26600 is radially constrained by the sidewalls of the curved aperture defined in the handle 26000. The EAP 26600 reacts to the voltage potential applied thereto by the power control system 26020 and expands and contracts proportionately in size to the magnitude of the force being applied to the drive rod 26050. When the voltage applied to the EAP 26600 is increased, the walls of the handle assembly 26000 prevent the EAP 26600 from expanding. As a result, the EAP 26600 expands toward the trigger bar 26550 extending from the curved trigger 26500 and, thus, applies a compressive force to the trigger bar 26550. The compression force applied by the EAP 26600 on the trigger bar 26550 compresses the trigger bar 26550 which, in turn, creates a drag force between the EAP 26600 and the trigger bar 26550 when the trigger bar 26550 is moved by the trigger 26400. This drag force is felt by the clinician pulling the trigger 26400 and directly communicates the forces of the end effector 27200 to the clinician. As the magnitude of the load force experienced by the drive rod 26050 increases, the voltage applied to the EAP 26600 by the power control system 26020

increases, and the drag experienced by the trigger 26400 also increases. As the magnitude of the load force experienced by the drive rod 26050 decreases, the voltage applied to the EAP 26600 by the power control system 26020 decreases, and the drag experienced by the trigger 26400 also decreases. These relationships are linearly proportional; however, any proportional relationship could be used. Moreover, further to the above, the magnitude of the voltage potential applied to the EAP 26600 by the power control system 26020 is proportionately coupled to the motor current drawn by the motor 26030, the voltage supplied by the load cell circuit, and/or the voltage supplied by the strain gauge circuit, for example.

[0286] Turning to FIG. 78A, the EAP 26600 is shown in a non-energized state before the voltage potential is applied to the EAP 26600. As seen in FIG. 78A, there is space defined between the EAP 26600 within the curved cylinder 26900 and the curved trigger 26500. Referring to FIG. 78B, as the voltage potential is applied to the EAP 26600, the EAP 26600 constricts the trigger bar 26550 of the curved trigger 26500 which creates the drag force discussed above. The relationship between the forces on the end effector 27200 and/or the shaft 27770 and the compressive force on the curved trigger 26500 is further illustrated in FIGS. 80 and 81.

[0287] Referring to FIG. 80, L_1 illustrates the torque experienced by the motor drive shaft. L_2 illustrates the load force experienced by the drive rod 26050. L_3 illustrates the voltage applied to the EAP 26600. The load force on the drive rod 26050 and the torque on the motor drive shaft are proportional to the amount of voltage applied to the EAP 26600. That is, as the load force and torque increase, as illustrated by way of L_1 and L_2 in FIG. 80, the voltage applied to the EAP 26600 also increases. Further to the above, there is a proportional relationship between the compressive force applied to the trigger 26500 and the voltage applied to the EAP 26600. As the voltage applied to the EAP 26600 increases, the drag force on the trigger 26500 increases, as discussed in greater detail above. The voltage applied to the EAP 26600 increases as a reaction to the amount of current flowing through the motor 26030 which is an indicator of the forces on the drive rod 26050 and the torques on the motor drive shaft. Referring to FIG. 81, L_4 illustrates the change in the voltage potential applied to the EAP 26600 over time.

[0288] Turning to FIG. 86, additional feedback systems similar to those are configured for use with suturing devices. In particular, various surgical instrument systems are equipped with programs which are capable of measuring bending and axial loads applied to a suturing device shaft such as the shaft 28100 of the suturing device 28000 illustrated in FIG. 86. The suturing device 28000 comprises at least one motor configured to provide power to the suturing device during a surgical procedure. The suturing device 28000 further comprises a distal head 28300 rotatably connected to the shaft 28100 by an articulation joint 28200. The handle of the suturing device 28000 comprises a display which is configured to indicate a

predefined proportion of loads to a user. The surgical instrument systems described herein are also configured for use with robotic surgical systems as well as cloud-based technology. Various applications disclosed which are incorporated by reference disclose situational awareness of an interactive HUB system which is configured to define various surgical steps. The devices, systems, and methods disclosed in the Subject Application can also be used with the devices, systems, and methods disclosed in U.S. Provisional Patent Application No. 62/659,900, entitled METHOD OF HUB COMMUNICATION, filed on April 19, 2018, U.S. Provisional Patent Application No. 62/611,341, entitled INTERACTIVE SURGICAL PLATFORM, filed on December 28, 2017, U.S. Provisional Patent Application No. 62/611,340, entitled CLOUD-BASED MEDICAL ANALYTICS, filed on December 28, 2017, and U.S. Provisional Patent Application No. 62/611,339, entitled ROBOT ASSISTED SURGICAL PLATFORM, filed on December 28, 2017, which are incorporated by reference in their entireties herein. Such surgical steps include providing the handle of the suturing device 28000 with an updated ratio of the amount of the load being exerted as a portion of the suture stitch or knot tension. The tension is used by the user to create more standardization of the stitch to stitch tightness. Further uses are contemplated which include instructional uses for new users of the surgical instrument systems described herein. FIG. 87 further illustrates the relationship between the forces applied to the shaft 28100 and the distal head 28300 based on the different motors (e.g. the motor supplying power to perform an actuation motion of an end effector and the motor supplying power to perform a distal head rotation motion).

[0289] The surgical instrument systems discussed in greater detail above are configured for use with locking and safety mechanisms. The locking mechanisms comprise electrical sensing means configured to detect whether a modular attachment is in a usable or unusable state. The locking mechanisms further comprise electrical sensing means configured to detect whether a loadable mechanism is in a usable or unusable state. FIG. 82 illustrates an exemplary shaft assembly 30000 which is similar to the shaft assembly 20000. The locking mechanisms which will be discussed in greater detail below are configured for use with any of the surgical instrument systems described herein. The shaft assembly 30000 comprises a drive 30100, a second drive 30200, and a third drive 30300. The shaft assembly 30000 comprises a plurality of electrical contacts 30022 configured to place the shaft assembly 30000 in electrical communication with any of the handle assemblies described herein upon being attached thereto. The shaft assembly 30000 further comprises an on-board control circuit 30500. One example of a single use lockout 30400 is illustrated in FIG. 83. The single use lockout comprises a lock solenoid 30410, a lock spring 30420, and a lock pin 30430 as seen in FIGS. 84 and 85. The lock solenoid 30410 is energized upon power being supplied to the shaft assembly 30000.

[0290] In such instances, the lock solenoid 30410 is configured to push the lock pin 30430 outwardly into a locked position; however the lock pin 30430 is held in a staged position until the shaft assembly 30000 is detached from the handle. At such point, the lock spring 30420 can push the lock pin 30430 from its staged position into its locked position. In various instances, the shaft assembly 30000 comprises a lock shoulder 30440 configured to hold the lock pin 30430 in its locked position and prevent the lock pin 30430 from being reset. In such instances, the lock pin 30430 protrudes proximally from the housing of the shaft assembly 30000 which prevents the shaft assembly 30000 from being reattached to a handle. While the solenoid 30410 can drive the lock pin 30430 into its locked position in certain instances; in other instances, the solenoid 30410 holds the lock pin 30430 in its unlocked position until energized by the attachment of the shaft assembly 30000 to the handle wherein, at such point, the solenoid 30410 can release the lock pin 30430 such that the lock spring 30420 can move the lock pin 30430 into its staged position where the shaft assembly 30000 is attached to the handle and into its locked position once the shaft assembly 30000 is removed from the handle.

[0291] Other lockout mechanisms comprise a locking member which immobilizes a drive shaft of a surgical instrument if a modular shaft is attached to an incompatible handle can be used. For example, when a scissor grip handle is attached to an articulating clip applier shaft with distal head rotation, a lockout prevents distal head rotation drive because the scissor grip handle is used for only one drive system which is often the clip drive. In various instances, the lockout fixes the rotation of the distal head by engaging a lockout member into the drive shaft at the proximal end of the shaft.

An additional locking mechanism for use with the surgical instrument systems described herein comprises a distal locking mechanism which prevents actuation motions of a clip applier or suturing device if a loaded cartridge is not in the jaws. A similar lockout mechanism comprises a distal locking mechanism which prevents actuation motions of a clip applier or suturing device if a spent cartridge is positioned in the jaws. The distal locking mechanism further comprises a means for sensing the engagement state of the distal lockout through a power system of the surgical instrument in order to prevent the activation of the motor or to instruct the motor to provide haptic vibration feedback that the handle assembly is incompatible with the attachment portion. Additional lockout assemblies include a modular lockout which prohibits or changes the operation of the motor if the shaft is detected to be in an unusable state.

[0292] Turning now to FIG. 88, an exemplary system for identifying the components of a surgical instrument system is disclosed. Step 32100 comprises attaching a shaft module to a handle assembly. Step 32200 comprises attaching a battery to a handle assembly. Step 32300 comprises energizing a safety circuit or watchdog processor wherein either is

compatible with surgical instrument systems discussed in greater detail above. Decision 32400 comprises the verification of the integrity of the electrical circuit within the surgical instrument system. If the integrity of the circuit is bad, then the system is configured to display an error signal and shut down in step 32410. If the integrity of the circuit is good, the system is configured to identify and log a serial number associated with a handle assembly, battery, and/or shaft assembly, as illustrated in step 32420. Decision 32500 is configured to identify the type of handle assembly. For example, if the handle assembly is a simple scissors handle, the system is configured to control a program for a simple mechanism configuration which includes a shaft rotation lockout, as illustrated in step 32500. If the system determines that the handle assembly is not a simple scissors handle, then the system is configured to verify the functionality of all instrument mechanisms as illustrated in step 32510.

[0293] With further reference to FIG. 88, once the system identifies the type of handle assembly, the system is configured to determine whether the shaft assembly comprises a loadable portion in decision 32600, and is further configured to determine the status of the loadable portion. If the loadable portion is unloaded, the system is configured to generate an error message in step 32610 which indicates that the system is waiting for the loadable portion to be reloaded before a surgical procedure can continue. If the loadable portion is loaded, the system is configured detect whether a display unit is present during decision 32700. If the surgical instrument does not comprise a display unit, for example, the system is configured use a simple green light to indicate that the surgical instrument is ready for use. If the surgical instrument comprises a display unit, for example, the system configures the display unit for use with whatever shaft assembly is attached to the surgical instrument in step 32720. Additional systems comprise the identification of various compatible shaft assemblies and handle assemblies. Other systems comprise the identification of the status of a power module and the status of the power module. The verification processes described above are configured for use with any of the surgical instrument systems described herein. The surgical instruments, modules, systems, and methods disclosed herein can be used with the various disclosures incorporated by reference. The devices, systems, and methods disclosed in the Subject Application can also be used with the devices, systems, and methods disclosed in U.S. Provisional Patent Application No. 62/659,900, entitled METHOD OF HUB COMMUNICATION, filed on April 19, 2018, U.S. Provisional Patent Application No. 62/611,341, entitled INTERACTIVE SURGICAL PLATFORM, filed on December 28, 2017, U.S. Provisional Patent Application No. 62/611,340, entitled CLOUD-BASED MEDICAL ANALYTICS, filed on December 28, 2017, and U.S. Provisional Patent Application No. 62/611,339, entitled ROBOT ASSISTED

SURGICAL PLATFORM, filed on December 28, 2017, which are incorporated by reference in their entireties herein.

[0294] The surgical instrument systems described herein are motivated by an electric motor; however, the surgical instrument systems described herein can be motivated in any suitable manner. In certain instances, the motors disclosed herein may comprise a portion or portions of a robotically controlled system. U.S. Patent Application Serial No. 13/118,241, entitled SURGICAL STAPLING INSTRUMENTS WITH ROTATABLE STAPLE DEPLOYMENT ARRANGEMENTS, now U.S. Patent No. 9,072,535, for example, discloses several examples of a robotic surgical instrument system in greater detail, the entire disclosure of which is incorporated by reference herein.

[0295] The surgical instrument systems described herein can be used in connection with the deployment and deformation of staples. Various embodiments are envisioned which deploy fasteners other than staples, such as clamps or tacks, for example. Moreover, various embodiments are envisioned which utilize any suitable means for sealing tissue. For instance, an end effector in accordance with various embodiments can comprise electrodes configured to heat and seal the tissue. Also, for instance, an end effector in accordance with certain embodiments can apply vibrational energy to seal the tissue. In addition, various embodiments are envisioned which utilize a suitable cutting means to cut the tissue.

[0296] The entire disclosures of:

- U.S. Patent Application Serial No. 11/013,924, entitled TROCAR SEAL ASSEMBLY, now U.S. Patent No. 7,371,227;
- U.S. Patent Application Serial No. 11/162,991, entitled ELECTROACTIVE POLYMER-BASED ARTICULATION MECHANISM FOR GRASPER, now U.S. Patent No. 7,862,579;
- U.S. Patent Application Serial No. 12/364,256, entitled SURGICAL DISSECTOR, now U.S. Patent Application Publication No. 2010/0198248;
- U.S. Patent Application Serial No. 13/536,386, entitled EMPTY CLIP CARTRIDGE LOCKOUT, now U.S. Patent No. 9,282,974;
- U.S. Patent Application Serial No. 13/832,786, entitled CIRCULAR NEEDLE APPLIER WITH OFFSET NEEDLE AND CARRIER TRACKS, now U.S. Patent No. 9,398,905;
- U.S. Patent Application Serial No. 12/592,174, entitled APPARATUS AND METHOD FOR MINIMALLY INVASIVE SUTURING, now U.S. Patent No. 8,123,764;
- U.S. Patent Application Serial No. 12/482,049, entitled ENDOSCOPIC STITCHING DEVICES, now U.S. Patent No. 8,628,545;

- U.S. Patent Application Serial No. 13/118,241, entitled SURGICAL STAPLING INSTRUMENTS WITH ROTATABLE STAPLE DEPLOYMENT ARRANGEMENTS, now U.S. Patent No. 9,072,535;
- U.S. Patent Application Serial No. 11/343,803, entitled SURGICAL INSTRUMENT HAVING RECORDING CAPABILITIES, now U.S. Patent No. 7,845,537;
- U.S. Patent Application Serial No. 14/200,111, entitled CONTROL SYSTEMS FOR SURGICAL INSTRUMENTS, now U.S. Patent No. 9,629,629;
- U.S. Patent Application Serial No. 14/248,590, entitled MOTOR DRIVEN SURGICAL INSTRUMENTS WITH LOCKABLE DUAL DRIVE SHAFTS, now U.S. Patent No. 9,826,976;
- 10 - U.S. Patent Application Serial No. 14/813,242, entitled SURGICAL INSTRUMENT COMPRISING SYSTEMS FOR ASSURING THE PROPER SEQUENTIAL OPERATION OF THE SURGICAL INSTRUMENT, now U.S. Patent Application Publication No. 2017/0027571;
- U.S. Patent Application Serial No. 14/248,587, entitled POWERED SURGICAL STAPLER, now U.S. Patent No. 9,867,612;
- 15 - U.S. Patent Application Serial No. 12/945,748, entitled SURGICAL TOOL WITH A TWO DEGREE OF FREEDOM WRIST, now U.S. Patent No. 8,852,174;
- U.S. Patent Application Serial No. 13/297,158, entitled METHOD FOR PASSIVELY DECOUPLING TORQUE APPLIED BY A REMOTE ACTUATOR INTO AN
- 20 INDEPENDENTLY ROTATING MEMBER, now U.S. Patent No. 9,095,362;
- International Application No. PCT/US2015/023636, entitled SURGICAL INSTRUMENT WITH SHIFTABLE TRANSMISSION, now International Patent Publication No. WO 2015/153642 A1;
- International Application No. PCT/US2015/051837, entitled HANDHELD
- 25 ELECTROMECHANICAL SURGICAL SYSTEM, now International Patent Publication No. WO 2016/057225 A1;
- U.S. Patent Application Serial No. 14/657,876, entitled SURGICAL GENERATOR FOR ULTRASONIC AND ELECTROSURGICAL DEVICES, U.S. Patent Application Publication No. 2015/0182277;
- 30 - U.S. Patent Application Serial No. 15/382,515, entitled MODULAR BATTERY POWERED HANDHELD SURGICAL INSTRUMENT AND METHODS THEREFOR, U.S. Patent Application Publication No. 2017/0202605;
- U.S. Patent Application Serial No. 14/683,358, entitled SURGICAL GENERATOR SYSTEMS AND RELATED METHODS, U.S. Patent Application Publication No.
- 35 2016/0296271;
- U.S. Patent Application Serial No. 14/149,294, entitled HARVESTING ENERGY FROM A SURGICAL GENERATOR, U.S. Patent No. 9,795,436;

- U.S. Patent Application Serial No. 15/265,293, entitled TECHNIQUES FOR CIRCUIT TOPOLOGIES FOR COMBINED GENERATOR, U.S. Patent Application Publication No. 2017/0086910; and

- U.S. Patent Application Serial No. 15/265,279, entitled TECHNIQUES FOR OPERATING GENERATOR FOR DIGITALLY GENERATING ELECTRICAL SIGNAL WAVEFORMS AND SURGICAL INSTRUMENTS, U.S. Patent Application Publication No. 2017/0086914, are hereby incorporated by reference herein.

[0297] *Examples*

Example 1 - A surgical instrument system comprising a handle, and a shaft. The handle comprises a housing, a motor disposed within the handle, at least one control switch, and a motor-control processor in communication with the at least one control switch to control the motor, wherein the processor is not positioned in the handle. The surgical instrument system also comprises a disposable battery housing configured to be attached to the housing. The disposable battery housing comprises a disposable battery and a display unit.

Example 2 - The surgical instrument system of Example 1, further comprising a controller.

Example 3 - The surgical instrument system of Example 2, wherein the controller is located within the shaft.

Example 4 - The surgical instrument system of Examples 2 or 3, wherein the controller comprises a control circuit configured to control the display unit on the disposable battery housing.

Example 5 - The surgical instrument system of Examples 1, 2, 3, or 4, wherein the display unit on the disposable battery housing is touch screen capable.

Example 6 - The surgical instrument system of Examples 1, 2, 3, 4, or 5, wherein the display unit comprises a multi-color display configured to indicate at least one function of the surgical instrument system to a user.

Example 7 - A surgical instrument comprising a handle, a shaft, and a disposable power module. The handle comprises a housing, a motor located in the handle, and at least one control switch. The disposable power module comprises a disposable battery and a display unit. The surgical instrument also comprises a motor-control processor in communication with the at least one control switch to control the motor, wherein the processor is positioned in at least one of the shaft and the disposable power module.

Example 8 - The surgical instrument of Example 7, further comprising a controller.

Example 9 - The surgical instrument of Example 8, wherein the controller is located within the shaft.

Example 10 - The surgical instrument of Examples 8 or 9, wherein the controller comprises a control circuit configured to control the display unit on the disposable power module.

Example 11 - The surgical instrument of Examples 7, 8, 9, or 10, wherein the display unit on the disposable power module is touch screen capable.

Example 12 - The surgical instrument of Examples 7, 8, 9, 10, or 11, wherein the display unit comprises a multi-color display configured to indicate at least one function of the surgical

5 instrument.

Example 13 - A surgical instrument comprising a housing, a handle attached to the housing, an end effector, a shaft, and a disposable battery comprising a multi-color display unit. The handle comprises a motor and at least one control switch. The shaft comprises a controller located within the shaft, wherein the controller is configured to control at least one function of

10 the end effector.

Example 14 - The surgical instrument of Example 13, wherein the controller comprises a control circuit configured to control the display unit on the disposable battery.

Example 15 - The surgical instrument of Examples 13 or 14, wherein the end effector further comprises at least one sensor.

15 Example 16 - The surgical instrument of Examples 13, 14, or 15, wherein the display unit on the disposable battery is touch screen capable.

Example 17 - A sterilizable surgical instrument system comprising a handle assembly, a shaft attached to the distal end of the handle assembly, a disposable battery assembly, and an end effector attached to a distal end of the shaft. The handle assembly comprises a

20 motor and at least one control switch. The shaft comprises a controller located within the shaft. The disposable battery assembly comprises a disposable battery and a display unit.

Example 18 - The surgical instrument system of Example 17, wherein the controller comprises a control circuit configured to control the display unit on the disposable battery.

Example 19 - The surgical instrument system of Examples 17 or 18, wherein the end effector

25 further comprises at least one sensor.

Example 20 - The surgical instrument system of Examples 17, 18, or 19, wherein the display unit on the disposable battery housing is touch screen capable.

Example 21 - The surgical instrument system of Examples 17, 18, 19, or 20, wherein the display unit comprises a multi-color display configured to indicate at least one function of the

30 surgical instrument system.

Example 22 - A surgical instrument system comprising a handle assembly comprising a drive system including an electric motor, a battery comprising a first battery cell and a second battery cell, a first shaft assembly attachable to the handle assembly, and a second shaft assembly attachable to the handle assembly. The drive system utilizes a first power load from the battery to operate the first shaft assembly and the first power load is supplied by the first battery cell and not the second battery cell. The drive system comprises a

35 second power load to operate the second shaft assembly which is different than the second

power load and the second power load is supplied by the first battery cell and the second battery cell.

Example 23 - A surgical instrument system comprising a handle assembly and a battery.

The handle assembly comprises a housing and a drive system including an electric motor.

- 5 The battery is insertable into the housing in a first orientation and a second orientation. The battery is configured to supply a first maximum power to the drive system when the battery is in the first orientation, wherein the battery is configured to supply a second maximum power when the battery is in the second orientation, and wherein the first orientation is different than the second orientation.

- 10 Example 24- The surgical instrument system of Example 23, wherein the battery is inserted into the handle in the first orientation when a first shaft assembly is attached to the handle, and wherein the battery is inserted into the second orientation when a second shaft assembly is attached to the handle.

Example 25 - A surgical instrument system comprising a drive module comprising a drive

- 15 module housing and a shaft assembly attachable to the drive module housing. The surgical instrument system also comprises a drive system and a battery attachable to the drive module housing. The drive system comprises an electric motor positioned in the drive module housing, a drive shaft in the shaft assembly which is operably couplable with the electric motor when the shaft assembly is attached to the drive module, and a control circuit
- 20 including a microprocessor, wherein the microprocessor is positioned in the shaft assembly. The battery comprises a battery housing, at least one battery cell in the battery housing configured to supply power to the drive system when the battery is attached to the drive module housing, and a display in communication with control circuit when the battery is attached to the drive module housing.

- 25 Example 26 - The surgical instrument system of Example 25, wherein the display comprises electrophoretic media.

Example 27 - The surgical instrument system of Example 25, wherein the display comprises an active matrix backplane.

- 30 Example 28 - The surgical instrument system of Example 27, wherein the active matrix backplane comprises an amorphous silicon semiconductor.

Example 29 - The surgical instrument system of Example 27, wherein the active matrix backplane comprises a polythiophene semiconductor.

Example 30 - The surgical instrument system of Example 27, wherein the display comprises an electrochromic display.

- 35 Example 31- The surgical instrument system of Example 27, wherein the display comprises a liquid-crystal display.

Example 32 - The surgical instrument system of Example 27, wherein the display comprises a thin-film transistor liquid-crystal display.

Example 33 - A surgical instrument system comprising a drive module comprising a drive module housing and a battery attachable to the drive module housing. The battery

5 comprises a battery housing, at least one battery cell in the battery housing configured to supply power to the drive system when the battery is attached to the drive module housing, and a display in communication with a control circuit when the battery is attached to the drive module housing. The surgical instrument system also comprises a drive system, an electric motor positioned in the drive module housing and a control circuit including a
10 microprocessor, wherein the microprocessor is positioned in the battery housing.

Example 34 - The surgical instrument system of Example 33, wherein the display comprises electrophoretic media.

Example 35 - The surgical instrument system of Example 33, wherein the display comprises an active matrix backplane.

15 Example 36 - The surgical instrument system of Example 35, wherein the active matrix backplane comprises an amorphous silicon semiconductor.

Example 37 - The surgical instrument system of Example 35, wherein the active matrix backplane comprises a polythiophene semiconductor.

Example 38 - The surgical instrument system of Example 33, wherein the display comprises
20 an electrochromic display.

Example 39 - The surgical instrument system of Example 33, wherein the display comprises a liquid-crystal display.

Example 40 - The surgical instrument system of Example 33, wherein the display comprises a thin-film transistor liquid-crystal display.

25 Example 41 - A surgical instrument system, comprising a drive module comprising a drive module housing and a battery attachable to the drive module housing. The battery comprises a battery housing, at least one battery cell in the battery housing configured to supply power to the drive system when the battery is attached to the drive module housing, and a display in communication with a control circuit when the battery is attached to the drive
30 module housing. The surgical instrument system also comprises a drive system, an electric motor positioned in the drive module housing, and a control system including a microprocessor, wherein the microprocessor is not positioned in the drive module.

Example 42 - The surgical instrument system of Example 41, wherein the control system comprises at least one input on the drive module.

35 Example 43 - The surgical instrument system of Example 41, wherein the control system comprises at least one switch on the drive module.

Example 44 - A surgical instrument system comprising a drive module comprising a housing and an electric motor and a battery selectively attachable to the drive module. The battery comprises a housing comprising a connector configured to releasably connect the battery to the drive module, at least one battery cell, and an electronic display.

5 Example 45 - The surgical instrument system of Example 44, wherein the display comprises electrophoretic media.

Example 46 - The surgical instrument system of Example 44, wherein the display comprises an active matrix backplane.

10 Example 47 - The surgical instrument system of Example 46, wherein the active matrix backplane comprises an amorphous silicon semiconductor.

Example 48 - The surgical instrument system of Example 46, wherein the active matrix backplane comprises a polythiophene semiconductor.

Example 49 - The surgical instrument system of Example 44, wherein the display comprises an electrochromic display.

15 Example 50 - The surgical instrument system of Example 44, wherein the display comprises a liquid-crystal display.

Example 51 - The surgical instrument system of Example 44, wherein the display comprises a thin-film transistor liquid-crystal display.

20 Example 52 - A handle for use with a surgical instrument system, wherein the handle comprises a drive module and a sealed battery module. The a drive module comprises a housing and a sealed motor module removably positionable with the housing. The sealed motor module comprises a liquid-tight barrier, at least one electrical input extending through the liquid-tight barrier, and a rotatable output extending through the liquid-tight barrier. The sealed battery module comprises a housing comprising a connector configured to attach the
25 sealed battery module to the drive module, a liquid-tight battery barrier, and at least one electrical output extending through the liquid-tight battery barrier.

Example 53 - A surgical instrument system comprising a drive module comprising a drive system including an electric motor, a shaft attachable to the drive module, wherein the shaft comprises an end effector configured to treat the tissue of a patient. The surgical instrument
30 system also comprises a battery attachable to the drive module and at least one electronic display system on at least one of the shaft and the battery. The surgical instrument system also comprises a control circuit comprising a processor, wherein the control circuit is configured to control the drive system, and wherein the control circuit is configured to communicate with the at least one electronic display system, and a power switch configured
35 to place the battery in communication with the control circuit when the power switch is placed in an operational configuration, wherein the processor is configured to interrogate the

shaft and the battery to assess the number of electronic display systems in the surgical instrument system.

Example 54 - The surgical instrument system of Example 53, wherein the processor is configured to interrogate the shaft and the battery to assess the number of electronic display systems in the surgical instrument system when the power switch is moved into the operational configuration.

Example 55 - The surgical instrument system of Example 53, wherein the processor is configured to interrogate the shaft and the battery to assess the number of electronic display systems in the surgical instrument system when the battery is assembled to the surgical instrument system.

Example 56 - A surgical instrument system comprising a drive module comprising a drive system including an electric motor, a shaft attachable to the drive module, wherein the shaft comprises an end effector configured to treat the tissue of a patient, and a battery attachable to the drive module. The surgical instrument system also comprises at least one electronic display system on at least one of the drive module, the shaft, and the battery and a control circuit comprising a processor, wherein the control circuit is configured to control the drive system, wherein the control circuit is configured to communicate with the at least one electronic display system, and wherein the processor is configured to interrogate the shaft and the battery to assess the number of electronic display systems in the surgical instrument system.

Example 57 - The surgical instrument system of Example 56, wherein the processor is configured to interrogate the drive module, the shaft, and the battery to assess the number of electronic display systems in the surgical instrument system when the battery is assembled to the surgical instrument system.

Example 58 - A surgical instrument system comprising a drive module comprising a drive system including an electric motor, a shaft attachable to the drive module, wherein the shaft comprises an end effector configured to treat the tissue of a patient, and a battery attachable to the drive module. The surgical instrument system also comprises a control circuit comprising a processor, wherein the control circuit is configured to control the drive system during an operational sequence, and wherein the battery is configured to supply power to the control circuit during an initiation sequence, and a communications circuit configured to communicate with and receive data from an off-board control system during that initiation sequence, wherein the communications circuit is in communication with the control circuit, wherein the control circuit is configured to receive the data from the communications circuit, and wherein the control circuit is configured to modify the operational sequence using the data.

Example 59 - The surgical instrument system of Example 58, wherein the initiation sequence is initiated by the assembly of the battery to the drive module.

Example 60 - The surgical instrument system of Example 58, further comprising a switch configurable in an operational configuration, wherein the initiation sequence is initiated by placing the switch in the operational configuration.

Example 61 - The surgical instrument system of Example 58, wherein the communications circuit comprises a wireless signal transmitter and a wireless signal receiver.

Example 62 - The surgical instrument system of Example 58, wherein the operational sequence comprises an algorithm, and wherein the control circuit modifies the algorithm when modifying the operational sequence.

Example 63 - The surgical instrument system of Example 62, wherein the control circuit deactivates a function of the surgical instrument system when modifying the algorithm.

Example 64 - The surgical instrument system of Example 58, wherein the initiation sequence comprises an algorithm, and wherein the control circuit deactivates a function of the surgical instrument system when modifying the algorithm.

Example 65 - A surgical instrument system, comprising a surgical instrument configured to perform at least three functions of an end effector, a first motor, a second motor, a third motor, and a first handle comprising a first number of controls, wherein each control corresponds to one of the three functions of the end effector. The surgical instrument system also comprises a second handle comprising a second number of controls and a shaft assembly attachable to the first handle and the second handle, wherein the shaft assembly is attachable to the first handle in a first orientation to engage one of the motors, and wherein the shaft assembly is attachable to the second handle in a second orientation to engage a different one of the motors, and wherein the surgical instrument system is configured to perform a different end effector function in the first orientation and the second orientation, and wherein certain end effector functions are locked out based on which motor is engaged in each orientation.

Example 66 - The surgical instrument system of Example 65, wherein the first number of controls is different than the second number of controls.

Example 67 - The surgical instrument system of Example 65 or 66, wherein the first orientation is different than the second orientation.

Example 68 - The surgical instrument system of Examples 65, 66, or 67, wherein the first orientation prevents the surgical instrument from performing at least one function of the end effector.

Example 69 - The surgical instrument system of Examples 65, 66, 67, or 68, wherein the second orientation prevents the surgical instrument from performing at least one function of the end effector.

Example 70 - A surgical instrument system comprising a surgical instrument configured to perform at least three functions of an end effector and a motor operable in at least three states. The surgical instrument system also comprises a first handle comprising a first number of controls, wherein each control corresponds to a function of the end effector, a motor drive, and a first attachment portion, wherein the first attachment portion connects to the surgical instrument in a first orientation in order to enable a first set of end effector functions. The surgical instrument system also comprises a second handle comprising a second number of controls. The surgical instrument system also comprises a shaft assembly attachable to the first handle and the second handle, wherein the shaft assembly is attachable to the first handle in a first orientation, and wherein the shaft assembly is attachable to the second handle in a second orientation. The surgical instrument system also comprises an end effector attachable to the shaft assembly.

Example 71 - The surgical instrument system of Example 70, wherein the first number of controls is different than the second number of controls.

Example 72 - The surgical instrument system of Examples 70 or 71, wherein the first orientation is different than the second orientation.

Example 73 - The surgical instrument system of Examples 70, 71, or 72, wherein the first orientation prevents the surgical instrument from performing at least one function of the end effector.

Example 74 - The surgical instrument system of Examples 70, 71, 72, or 73, wherein the second orientation prevents the surgical instrument from performing at least one function of the end effector.

Example 75 - A surgical instrument system comprising a surgical instrument configured to perform at least three functions of an end effector, a first motor, a second motor, and a third motor. The surgical instrument system further comprises a first handle comprising a first number of controls, wherein each control corresponds to an end effector function, a second handle comprising a second number of controls, and a third handle comprising a third number of controls. The surgical instrument system also comprises a shaft assembly attachable to each of the handles, wherein the shaft assembly is attachable to each of the handles in a different orientation, and wherein the surgical instrument system is configured to perform a different end effector function in each different orientation, and wherein certain end effector functions are locked out based on which motor is engaged in each orientation.

Example 76 - A surgical instrument system, comprising a surgical instrument configured to perform at least three functions of an end effector. The surgical instrument system also comprises a first handle comprising a first number of controls, wherein each control corresponds to an end effector function, a second handle comprising a second number of controls, and a third handle comprising a third number of controls. The surgical instrument

system also comprises a shaft assembly attachable to each of the handles, wherein the shaft assembly is attachable to each of the handles in a different orientation, and wherein the surgical instrument system is configured to perform a different end effector function in each different orientation, and wherein certain end effector functions are locked out based on which handle is attached to the end effector.

Example 77 - A surgical instrument system comprising a first shaft assembly configured to perform a first function, a second function, and a third function and a second shaft assembly configured to perform the first function and the second function, but not the third function.

The surgical instrument system also comprises a handle, wherein the first shaft assembly and the second shaft assembly are selectively and separately attachable to the handle, wherein the handle comprises a first electric motor configured to drive the first function, a second electric motor configured to drive the second function, a third electric motor configured to drive the third function when the first shaft assembly is attached to the handle, and a lockout configured to prevent the third electric motor from being operated when the second shaft assembly is attached to the handle.

Example 78 - The surgical instrument system of Example 77, wherein the first shaft assembly is attachable to the handle in a first orientation and the second shaft assembly is attachable to the handle in a second orientation, and wherein the first orientation is different than the second orientation.

Example 79 - A surgical instrument system comprising a first shaft assembly configured to perform a first function, a second function, and a third function, a second shaft assembly configured to perform the first function and the second function, and a handle, wherein the first shaft assembly and the second shaft assembly are selectively, and separately, attachable to the handle. The handle comprises a first control configured to control the first function, a second control configured to control the second function, and a third control configured to control the third function when the first shaft assembly is attached to the handle, and locking means for locking out the third control when the second shaft assembly is attached to the handle.

Example 80 - The surgical instrument system of Example 79, wherein the handle further comprises a microprocessor comprising input gates and output gates, wherein the first control, the second control, and the third control are in signal communication with the microprocessor via the input gates, and wherein the locking means comprises deactivating the input gate associated with the third control when the second shaft assembly is attached to the handle.

Example 81 - The surgical instrument system of Example 79, wherein the handle further comprises a microprocessor comprising input gates and output gates, wherein the shaft assembly is in signal communication with the microprocessor via the output gates, and

wherein the locking means comprises deactivating the output gate associated with the third function when the second shaft assembly is attached to the handle.

Example 82 - A surgical instrument system comprising a shaft assembly configured to perform a first function, a second function, and a third function. The surgical instrument system also comprises a first handle comprising a first control for controlling the first function, a second control for controlling the second function, and a third control for controlling the third function when the shaft assembly is operably coupled to the first handle. The surgical instrument system also comprises a second handle comprising a first control for controlling the first function, a second control for controlling the second function, and a lockout for preventing the shaft assembly from performing the third function when the shaft assembly is operably coupled to the second handle.

Example 83 - The surgical instrument system of Example 82, wherein the shaft assembly is attachable to the first handle in a first orientation and the handle in a second orientation, and wherein the first orientation is different than the second orientation.

Example 84 - The surgical instrument system of Examples 82 or 83, wherein the shaft assembly comprises a longitudinal axis, an end effector, and an articulation joint, wherein the end effector comprises a jaw movable between an open position and a closed position, wherein the first function comprises moving the jaw, wherein the second function comprises articulating the end effector about the articulation joint, and wherein the third function comprises rotating the shaft assembly about the longitudinal axis.

Example 85 - A surgical instrument system comprising a shaft assembly configured to perform a first function, a second function, and a third function. The surgical instrument system also comprises a first handle comprising a first motor for driving the first function, a second motor for driving the second function, and a third motor for driving the third function when the shaft assembly is operably coupled to the first handle. The surgical instrument system also comprises a second handle comprising a first motor for driving the first function, a second motor for driving the second function, and a lockout for preventing the shaft assembly from performing the third function when the shaft assembly is operably coupled to the second handle.

Example 86 - The surgical instrument system of Example 85, wherein the shaft assembly is attachable to the first handle in a first orientation and the second handle in a second orientation, and wherein the first orientation is different than the second orientation.

Example 87 - The surgical instrument system of Examples 85 or 86, wherein the shaft assembly comprises a longitudinal axis, an end effector, and an articulation joint, wherein the end effector comprises a jaw movable between an open position and a closed position, wherein the first function comprises moving the jaw, wherein the second function comprises

articulating the end effector about the articulation joint, and wherein the third function comprises rotating the shaft assembly about the longitudinal axis.

Example 88 - The surgical instrument system of Examples 85, 86, or 87, wherein the shaft assembly comprises a first drive system for performing the first function, a second drive system for performing the second function, and a third drive system for performing the third function, and wherein the lockout comprises a locking element configured to engage the third drive and prevent the third drive from driving the third function.

Example 89 - A surgical instrument system comprising a shaft assembly, a first handle, and a second handle. The shaft assembly is configured to perform a first function, a second function, and a third function and comprises a first drive configured to perform the first function, a second drive configured to perform the second function, a third drive configured to perform the third function, and a lockout, wherein the lockout is selectively switchable between an unlocked configuration and a locked configuration, wherein the lockout prevents the shaft assembly from performing the third function when the lockout is in the locked configuration, and wherein the lockout permits the shaft assembly to perform the third function when the lockout is in the unlocked configuration. The first handle comprises a first motor for driving the first function, a second motor for driving the second function, a third motor for driving the third function when the shaft assembly is operably coupled to the first handle, and a control system configured to place the lockout in the unlocked configuration. The second handle comprises a first motor for driving the first function, a second motor for driving the second function, and a control system configured to place the lockout in the locked configuration.

Example 90 - A surgical instrument system comprising a first handle comprising a first gripping portion and a first shaft lock, and a second handle comprising a second gripping portion and a second shaft lock. The surgical instrument system also comprises a shaft assembly selectively, and separately, attachable to the first handle and the second handle, wherein the first shaft lock holds the shaft assembly to the first handle in a first orientation when the shaft assembly is attached to the first handle, wherein the second shaft lock holds shaft assembly to the second handle in a second orientation when the shaft assembly is attached to the second handle, and wherein the first orientation is different than the second orientation.

Example 91 - The surgical instrument system of Example 90, wherein the shaft assembly comprises a housing and an array of lock apertures extending around the housing, and wherein the first shaft lock and the second shaft lock engage the lock apertures.

Example 92 - The surgical instrument system of Example 91, wherein the first shaft lock comprises an arcuate ridge including a first end and a second end, a first lock shoulder at the first end, wherein the first lock shoulder is positionable in a lock aperture, and a second

lock shoulder at the second end, wherein the second lock shoulder is positionable in a lock aperture.

Example 93 - The surgical instrument system of Examples 91 or 92, wherein the second shaft lock comprises an arcuate ridge including a first end and a second end, a first lock shoulder at the first end, wherein the first lock shoulder is positionable in a lock aperture, and a second lock shoulder at the second end, wherein the second lock shoulder is positionable in a lock aperture.

Example 94 - A surgical instrument system comprising a shaft assembly comprising three drive functions, a first handle, and a second handle. The shaft assembly is selectively attachable to the first handle, wherein the first handle comprises a drive system configured to drive all three drive functions of the shaft assembly when the shaft assembly is attached to the first handle. The shaft assembly is selectively attachable to the second handle, wherein the second handle comprises a drive system configured to drive less than all three functions of the shaft assembly when the shaft assembly is attached to the second handle.

Example 95 - The surgical instrument system of Example 94, wherein the shaft assembly comprises a first drive system configured to perform a first drive function of the three drive functions, a second drive system configured to perform a second drive function of the three drive functions, and a third drive system configured to perform a third drive function of the three drive functions.

Example 96 - The surgical instrument system of Example 95, wherein the second handle comprises a housing and a lock projection, and wherein the lock projection is configured to engage the second drive system to prevent the operation of the second drive system when the shaft assembly is assembled to the second handle.

Example 97 - The surgical instrument system of Example 96, wherein the second handle comprises another lock projection, and wherein the another lock projection is configured to engage the third drive system to prevent the operation of the third drive system when the shaft assembly is assembled to the second handle.

Example 98 - The surgical instrument system of Examples 96 or 97, wherein the lock projection extends from the housing.

Example 99 - The surgical instrument system of Examples 96, 97, or 98, wherein the lock projection is integrally formed with the housing.

Example 100 - The surgical instrument system of Examples 94, 95, 96, 97, 98, or 99, wherein the first handle comprises a pistol grip and the second handle comprises a scissors grip.

Example 101 - The surgical instrument system of Examples 94, 95, 96, 97, 98, or 99, wherein the first handle comprises a pistol grip and the second handle comprises a pencil grip.

Example 102 - The surgical instrument system of Examples 94, 95, 96, 97, 98, 99, 100, or 101, wherein the shaft assembly comprises a clip applier.

Example 103 - A surgical instrument system comprising a shaft assembly comprising three drive functions requiring power above a power threshold, a first handle, and a second

5 handle. The shaft assembly is selectively attachable to the first handle, wherein the first handle comprises a drive system configured to drive all three drive functions of the shaft assembly at or above the power threshold when the shaft assembly is attached to the first handle. The shaft assembly is selectively attachable to the second handle, wherein the second handle comprises a drive system configured to drive less than all three functions of
10 the shaft assembly at or above the power threshold when the shaft assembly is attached to the second handle, and wherein the second handle is configured to disable the drive functions receiving power below the power threshold.

Example 104 - A surgical instrument system comprising a handle assembly. The handle assembly comprises an actuation trigger comprising a curved proximal portion and a curved
15 cylinder surrounding the curved proximal portion of the actuation trigger, wherein the curved cylinder comprises at least one electroactive polymer. The surgical instrument system also comprises a motor, a shaft attached to the handle assembly, an end effector attached to a distal end of the shaft, an actuation rod configured to transmit an actuation force to the end effector, and a sensor system configured to detect the magnitude of the actuation force,
20 wherein the electroactive polymer is responsive to the actuation force, and wherein the electroactive polymer provides tactile feedback to a user of the surgical instrument system by applying forces to the actuation trigger.

Example 105 - The surgical instrument system of Example 104, wherein the forces applied to the actuation trigger by the electroactive polymer are proportional to the actuation force.

25 Example 106 - The surgical instrument system of Example 105, wherein the forces applied to the actuation trigger by the electroactive polymer are directly proportional to the actuation force.

Example 107 - The surgical instrument system of Example 106, wherein the forces applied
30 to the actuation trigger by the electroactive polymer are linearly proportional to the actuation force.

Example 108 - The surgical instrument system of Example 106, wherein the forces applied to the actuation trigger by the electroactive polymer are non-linearly proportional to the actuation force.

35 Example 109 - The surgical instrument system of Examples 104, 105, 106, 107, or 108, further comprising a power source and a control system in communication with the sensor system, the curved cylinder, and the power source, wherein the control system is configured

to apply a voltage potential to the curved cylinder in response to the actuation force detected by the sensor system.

Example 110 - The surgical instrument system of Example 109, wherein the voltage potential is proportional to the actuation force.

- 5 Example 111 - The surgical instrument system of Example 110, wherein the voltage potential is linearly proportional to the actuation force.

Example 112 - The surgical instrument system of Examples 109, 110, or 111, wherein the curved cylinder expands in proportion to the magnitude of the voltage potential applied to the curved cylinder.

- 10 Example 113 - The surgical instrument system of Examples 104, 105, 106, 107, 108, 109, 110, 111, or 112, wherein the handle comprises a cavity comprising a sidewall, wherein the curved cylinder is positioned in the cavity, and wherein the sidewall prevents the expansion of the curved cylinder when a voltage potential is applied to the curved cylinder such that a gripping force is applied to the curved proximal portion.

- 15 Example 114 - The surgical instrument of Examples 104, 105, 106, 107, 108, 109, 110, 111, 112, or 113, wherein the end effector comprises a crimping mechanism configured to apply a clip to the tissue of a patient, and wherein the crimping mechanism is driven by the actuation rod.

- Example 115 - The surgical instrument of Examples 104, 105, 106, 107, 108, 109, 110, 111, 20 112, or 113, wherein the end effector is configured to apply staples to the tissue of a patient, and wherein the staples are pushed out of a staple cartridge by the actuation rod.

Example 116 - The surgical instrument of Examples 104, 105, 106, 107, 108, 109, 110, 111, 112, or 113, wherein the end effector comprises a needle configured to apply a suture to the tissue of a patient, and wherein the needle is driven by the actuation rod.

- 25 Example 117 - The surgical instrument of Examples 104, 105, 106, 107, 108, 109, 110, 111, 112, or 113, wherein the end effector comprises jaws configured to grasp tissue, and wherein the actuation rod closes the jaws.

- Example 118 - The surgical instrument of Examples 104, 105, 106, 107, 108, 109, 110, 111, 112, or 113, wherein the end effector comprises jaws configured to dissect tissue, and 30 wherein the actuation rod opens the jaws.

Example 119 - The surgical instrument of Examples 104, 105, 106, 107, 108, 109, 110, 111, 112, or 113, wherein the end effector is configured to ablate tissue with electrical energy.

- Example 120 - The surgical instrument of Examples 104, 105, 106, 107, 108, 109, 110, 111, 112, or 113, wherein the end effector comprises at least one electrode and is configured to 35 apply RF energy to tissue.

Example 121 - The surgical instrument of Examples 104, 105, 106, 107, 108, 109, 110, 111, 112, or 113, wherein the handle comprises a transducer, and wherein the end effector is configured to apply vibrational energy to tissue.

Example 122 - The surgical instrument of Examples 104, 105, 106, 107, 108, 109, 110, 111, 112, or 113, wherein the end effector comprises a knife configured to cut tissue, and wherein the knife is pushed distally by the actuation rod.

Example 123 - A surgical instrument system comprising a handle assembly wherein the handle assembly comprises an actuation trigger and a cylinder surrounding a portion of the actuation trigger, wherein the cylinder comprises at least one electroactive polymer. The surgical instrument system also comprises a power source, a motor, an actuation member configured to transmit an actuation force, a sensor system configured to detect the magnitude of the actuation force, and a control system in communication with the sensor system and the cylinder, wherein the control system is configured to apply a voltage potential from the power source to the cylinder in response to the actuation force, and wherein the cylinder applies a gripping force to the actuation trigger indicative of the magnitude of the actuation force.

Example 124 - A surgical instrument system comprising a handle assembly wherein the handle assembly comprises an actuation trigger and an electroactive polymer actuator. The surgical instrument system also comprises a voltage source, an electric motor, an actuation member configured to transmit an actuation force, a sensor system configured to detect the magnitude of the actuation force, and a control system in communication with the sensor system and the electroactive polymer actuator, wherein the control system is configured to apply a voltage potential from the voltage source to the electroactive polymer actuator in response to the actuation force, and wherein the electroactive polymer actuator applies a gripping force to the actuation trigger which is proportional to the magnitude of the actuation force.

Example 125 - A surgical instrument system comprising a handle assembly wherein the handle assembly comprises an actuation trigger and an electroactive polymer actuator. The surgical instrument system also comprises a power source, an electric motor configured to draw an electrical current from the power source, an actuation member operably coupled to the electric motor which is configured to transmit an actuation force, a sensor system configured to detect the magnitude of the electrical current, and a control system in communication with the sensor system and the electroactive polymer actuator, wherein the control system is configured to apply a voltage potential to the electroactive polymer actuator in response to the electrical current, and wherein the electroactive polymer actuator applies a gripping force to the actuation trigger which is proportional to the magnitude of the electrical current.

Example 126 - A robotic surgical instrument system comprising a surgical robot and a console configured to control the surgical robot. The console comprises an actuation trigger and an electroactive polymer actuator. The robotic surgical instrument system comprises a power source, an electric motor configured to draw an electrical current from the power source, an actuation member operably coupled to the electric motor which is configured to transmit an actuation force, a sensor system configured to detect the magnitude of the electrical current, and a control system in communication with the sensor system and the electroactive polymer actuator, wherein the control system is configured to apply a voltage potential to the electroactive polymer actuator in response to the electrical current, and wherein the electroactive polymer actuator applies a gripping force to the actuation trigger which is proportional to the magnitude of the electrical current.

Example 127 - A robotic surgical instrument system comprising a surgical robot and a console configured to control the surgical robot. The console comprises an actuation trigger and an electroactive polymer actuator. The robotic surgical instrument system also comprises a voltage source, an electric motor, an actuation member configured to transmit an actuation force, a sensor system configured to detect the magnitude of the actuation force, and a control system in communication with the sensor system and the electroactive polymer actuator, wherein the control system is configured to apply a voltage potential from the voltage source to the electroactive polymer actuator in response to the actuation force, and wherein the electroactive polymer actuator applies a gripping force to the actuation trigger which is proportional to the magnitude of the actuation force.

Example 128 - A surgical instrument system comprising a handle assembly which comprises an actuation trigger and an electroactive polymer actuator. The surgical instrument system also comprises a voltage source, an electric motor, an actuation member configured to transmit an actuation force, a sensor system configured to detect the magnitude of the actuation force, and a control system in communication with the sensor system and the electroactive polymer actuator, wherein the control system is configured to apply a voltage potential from the voltage source to the electroactive polymer actuator in response to the actuation force, and wherein the electroactive polymer actuator applies a friction force to the actuation trigger which is proportional to the magnitude of the actuation force.

Example 129 - A surgical instrument system comprising a handle assembly which comprises an actuation trigger and an electroactive polymer actuator. The surgical instrument system also comprises a voltage source, an electric motor, an actuation member configured to transmit an actuation force, a sensor system configured to detect the magnitude of the actuation force, and a control system in communication with the sensor system and the electroactive polymer actuator, wherein the control system is configured to apply a voltage potential from the voltage source to the electroactive polymer actuator in response to the

actuation force, and wherein the electroactive polymer actuator applies a resistance force to the actuation trigger which is proportional to the magnitude of the actuation force.

Example 130 - A surgical instrument system comprising a handle assembly which comprises an actuation trigger and an electroactive polymer actuator. The surgical instrument system also comprises a power source, an electric motor configured to draw an electrical current from the power source, an actuation member operably coupled to the electric motor which is configured to transmit an actuation force, a sensor system configured to detect the magnitude of the electrical current, and a control system in communication with the sensor system and the electroactive polymer actuator, wherein the control system is configured to apply a voltage potential to the electroactive polymer actuator in response to the electrical current, and wherein the electroactive polymer actuator applies a resistance force to the actuation trigger which is proportional to the magnitude of the electrical current.

Example 131 - A surgical instrument system comprising a surgical instrument and a housing which comprises a handle assembly, at least one motor, and a drive shaft. The surgical instrument system also comprises a shaft assembly configured to be attached to a distal end of the housing, wherein the shaft assembly comprises a control circuit and a locking mechanism, wherein the locking mechanism prevents movement of the drive shaft if the shaft assembly is not attached to the surgical instrument in an orientation which enables operation of the surgical instrument, and wherein the locking mechanism further comprises sensing means for determining whether the locking mechanism is actively engaged and an end effector attachable to a distal end of the shaft assembly.

Example 132 - The surgical instrument system of Example 131, wherein the control circuit further comprises at least one safety feature.

Example 133 - The surgical instrument system of Examples 131 or 132, wherein the locking mechanism is configured to prevent the actuation of the surgical instrument.

Example 134 - The surgical instrument system of Examples 131, 132, or 133, wherein the locking mechanism is configured to prevent activation of the motor.

Example 135 - The surgical instrument system of Examples 131, 132, 133, or 134, wherein the locking mechanism prevents movement of the shaft assembly when the shaft assembly is not attached to the housing.

Example 136 - The surgical instrument system of Examples 131, 132, 133, 134, or 135, wherein the locking mechanism is configured to detect whether the end effector is in a usable state.

Example 137 - The surgical instrument system of Examples 131, 132, 133, 134, 135, or 136, wherein the sensing means is configured to enable haptic feedback of the motor in order to alert a user of a state of the surgical instrument.

Example 138 - A surgical instrument comprising a housing which comprises a handle assembly, at least one motor, and a drive shaft. The surgical instrument also comprises a shaft assembly configured to be attached to a distal end of the housing, wherein the shaft assembly comprises a control circuit, and a locking mechanism, wherein the locking mechanism prevents movement of the drive shaft if the shaft assembly is not attached to the surgical instrument in an orientation which enables operation of the surgical instrument. The surgical instrument also comprises an end effector attachable to a distal end of the shaft assembly.

Example 139 - The surgical instrument of Example 138, wherein the control circuit further comprises at least one safety feature.

Example 140 - The surgical instrument of Examples 138 or 139, wherein the locking mechanism is configured to prevent the actuation of the surgical instrument.

Example 141 - The surgical instrument of Examples 138, 139, or 140, wherein the locking mechanism is configured to prevent activation of the motor.

Example 142 - The surgical instrument of Examples 138, 139, 140, or 141, wherein the locking mechanism prevents movement of the shaft assembly when the shaft assembly is not attached to the housing.

Example 143 - The surgical instrument of Examples 138, 139, 140, 141, or 142, wherein the locking mechanism is configured to detect whether the end effector is in a usable state.

Example 144 - The surgical instrument of Examples 138, 139, 140, 141, 142, or 143, wherein the sensing means is configured to enable haptic feedback of the motor in order to alert a user of a state of the surgical instrument.

Example 145 - A surgical assembly comprising a surgical instrument and a housing which comprises a handle, at least one motor, and a drive shaft assembly. The surgical assembly also comprises a shaft assembly configured to be attached to a distal end of the housing, wherein the shaft assembly comprises a control circuit and a locking mechanism, wherein the locking mechanism prevents movement of the drive shaft if the shaft assembly is not attached to the surgical instrument in an orientation which enables operation of the surgical instrument and wherein the locking mechanism further comprises an electrical sensor for determining whether the locking mechanism is actively engaged within the surgical instrument. The surgical assembly also comprises an end effector attachable to a distal end of the shaft assembly.

Example 146 - The surgical assembly of Example 145, wherein the control circuit further comprises at least one safety feature.

Example 147 - The surgical assembly of Examples 145 or 146, wherein the locking mechanism is configured to prevent the actuation of the surgical instrument.

Example 148 - The surgical assembly of Examples 145, 146, or 147, wherein the locking mechanism is configured to prevent activation of the at least one motor.

Example 149 - The surgical assembly of Examples 145, 146, 147, or 148, wherein the locking mechanism prevents movement of the shaft assembly when the shaft assembly is not attached to the housing.

Example 150 - The surgical assembly of Examples 145, 146, 147, 148, or 149, wherein the locking mechanism is configured to detect whether the end effector is in a usable state.

Example 151 - The surgical assembly of Examples 145, 146, 147, 148, 149, or 150, wherein the electrical sensor is configured to enable haptic feedback of the motor in order to alert a user of a state of the surgical instrument.

Example 152 - A surgical instrument configured to apply clips to the tissue of a patient, comprising an end effector which comprises a replaceable clip cartridge comprising a plurality of clips removably stored therein, an actuator configured to deploy the clips, and a lockout configurable in a locked configuration and an unlocked configuration, wherein the lockout is in the locked configuration when the replaceable clip cartridge is not in the end effector, wherein the lockout prevents the actuator from being actuated when the lockout is in the locked configuration, wherein the lockout is in the unlocked configuration when the replaceable clip cartridge is positioned in the end effector, and wherein the lockout permits the actuator to deploy the clips when the lockout is in the unlocked configuration. The surgical instrument also comprises a handle, an electric motor configured to drive the actuator, a control circuit configured to control the electric motor, and a sensing system configured to determine when the lockout is in the locked configuration, wherein the sensing system is in communication with the control circuit, and wherein the control circuit prevents the actuation of the electric motor when the sensing system determines that the lockout is in the locked configuration.

Example 153 - A surgical instrument configured to apply clips to the tissue of a patient, comprising an end effector which comprises a replaceable clip cartridge comprising a plurality of clips removably stored therein, an actuator configured to deploy the clips, a lockout configurable in a locked configuration and an unlocked configuration, wherein the lockout is in the locked configuration when the replaceable clip cartridge is not in the end effector, wherein the lockout prevents the actuator from being actuated when the lockout is in the locked configuration, wherein the lockout is in the unlocked configuration when the replaceable clip cartridge is positioned in the end effector, and wherein the lockout permits the actuator to deploy the clips when the lockout is in the unlocked configuration. The surgical instrument also comprises a handle, an electric motor configured to drive the actuator, a control circuit configured to control the electric motor, and a sensing system configured to determine when the lockout is in the locked configuration, wherein the sensing

system is in communication with the control circuit, and wherein the control circuit provides haptic feedback to the user of the surgical instrument when the sensing system determines that the lockout is in the locked configuration.

Example 154 - A surgical instrument configured to apply clips to the tissue of a patient

5 comprising an end effector which comprises a replaceable clip cartridge comprising a plurality of clips removably stored therein, an actuator configured to deploy the clips, and a lockout configurable in a locked configuration and an unlocked configuration, wherein the lockout is in the locked configuration when the replaceable clip cartridge has been completely expended, wherein the lockout prevents the actuator from being actuated when
10 the lockout is in the locked configuration, wherein the lockout is in the unlocked configuration when the replaceable clip cartridge is positioned in the end effector and has not been completely expended, and wherein the lockout permits the actuator to deploy the clips when the lockout is in the unlocked configuration. The surgical instrument also comprises a handle, an electric motor configured to drive the actuator, a control circuit configured to
15 control the electric motor, and a sensing system configured to determine when the lockout is in the locked configuration, wherein the sensing system is in communication with the control circuit, and wherein the control circuit prevents the actuation of the electric motor when the sensing system determines that the lockout is in the locked configuration.

Example 155 - A surgical instrument system configured to apply clips to the tissue of a

20 patient comprising a shaft assembly which comprises a longitudinal axis, an end effector, an articulation joint rotatably connecting the end effector to the shaft, a rotation drive shaft configured to rotate the shaft about the longitudinal axis, a clip firing drive shaft configured to deploy the clips, and an articulation drive shaft configured to articulate the end effector relative to the shaft. The end effector comprises a clip cartridge comprising a plurality of
25 clips removably stored therein and an actuator configured to deploy the clips. The surgical instrument system also comprises a first handle which comprises a rotation drive system configured to drive the rotation drive shaft, a clip firing drive system configured to drive the clip firing drive shaft, and an articulation drive system configured to drive the articulation drive shaft. The surgical instrument system also comprises a second handle comprising a
30 rotation drive lockout configured to lock the rotation drive shaft, a clip firing drive system configured to drive the clip firing drive shaft, and an articulation drive lockout configured to lock the articulation drive shaft.

Example 156 - A surgical instrument configured to apply a suture to the tissue of a patient, comprising an end effector which comprises a replaceable suture cartridge comprising a

35 suture removably stored therein, an actuator configured to deploy the suture, and a lockout configurable in a locked configuration and an unlocked configuration, wherein the lockout is in the locked configuration when the replaceable suture cartridge is not in the end effector,

wherein the lockout prevents the actuator from being actuated when the lockout is in the locked configuration, wherein the lockout is in the unlocked configuration when the replaceable suture cartridge is positioned in the end effector, and wherein the lockout permits the actuator to deploy the suture when the lockout is in the unlocked configuration.

5 The surgical instrument also comprises a handle, an electric motor configured to drive the actuator, a control circuit configured to control the electric motor, and a sensing system configured to determine when the lockout is in the locked configuration, wherein the sensing system is in communication with the control circuit, and wherein the control circuit prevents the actuation of the electric motor when the sensing system determines that the lockout is in
10 the locked configuration.

Example 157 - A surgical instrument configured to apply a suture to the tissue of a patient comprising an end effector which comprises a replaceable suture cartridge comprising a suture removably stored therein, an actuator configured to deploy the suture, a lockout configurable in a locked configuration and an unlocked configuration, wherein the lockout is
15 in the locked configuration when the replaceable suture cartridge is not in the end effector, wherein the lockout prevents the actuator from being actuated when the lockout is in the locked configuration, wherein the lockout is in the unlocked configuration when the replaceable suture cartridge is positioned in the end effector, and wherein the lockout permits the actuator to deploy the suture when the lockout is in the unlocked configuration.

20 The surgical instrument also comprises a handle, an electric motor configured to drive the actuator, a control circuit configured to control the electric motor, and a sensing system configured to determine when the lockout is in the locked configuration, wherein the sensing system is in communication with the control circuit, and wherein the control circuit provides haptic feedback to the user of the surgical instrument when the sensing system determines
25 that the lockout is in the locked configuration.

Example 158 - A surgical instrument configured to apply a suture to the tissue of a patient comprising an end effector which comprises a replaceable suture cartridge comprising a suture removably stored therein, an actuator configured to deploy the suture, a lockout configurable in a locked configuration and an unlocked configuration, wherein the lockout is
30 in the locked configuration when the replaceable suture cartridge has been completely expended, wherein the lockout prevents the actuator from being actuated when the lockout is in the locked configuration, wherein the lockout is in the unlocked configuration when the replaceable suture cartridge is positioned in the end effector and has not been completely expended, and wherein the lockout permits the actuator to deploy the suture when the
35 lockout is in the unlocked configuration. The surgical instrument also comprises a handle, an electric motor configured to drive the actuator, a control circuit configured to control the electric motor, and a sensing system configured to determine when the lockout is in the

locked configuration, wherein the sensing system is in communication with the control circuit, and wherein the control circuit prevents the actuation of the electric motor when the sensing system determines that the lockout is in the locked configuration.

Example 159 - A surgical instrument system configured to treat the tissue of a patient,

5 comprising a shaft assembly which comprises a longitudinal axis, an end effector comprising a movable member and an actuator configured to deploy the plurality of surgical clips, an articulation joint rotatably connecting the end effector to the shaft, a rotation drive shaft configured to rotate the shaft about the longitudinal axis, a firing drive shaft configured to deploy the movable member, and an articulation drive shaft configured to articulate the end
10 effector relative to the shaft. The surgical instrument system also comprises a first handle comprising a rotation drive system configured to drive the rotation drive shaft, a firing drive system configured to drive the firing drive shaft, and an articulation drive system configured to drive the articulation drive shaft. The surgical instrument system also comprises a second handle comprising a rotation drive lockout configured to lock the rotation drive shaft and a
15 firing drive system configured to drive the firing drive shaft.

Example 160 - A surgical instrument system configured to treat the tissue of a patient

comprising a shaft assembly which comprises a longitudinal axis, an end effector comprising a movable member and an actuator configured to deploy a plurality of clips, an articulation joint rotatably connecting the end effector to the shaft, a rotation drive shaft configured to
20 rotate the shaft about the longitudinal axis, a firing drive shaft configured to deploy the movable member, and an articulation drive shaft configured to articulate the end effector relative to the shaft. The surgical instrument system also comprises a first handle comprising a rotation drive system configured to drive the rotation drive shaft, a firing drive system configured to drive the firing drive shaft, and an articulation drive system configured
25 to drive the articulation drive shaft. The surgical instrument system also comprises a second handle comprising an articulation drive lockout configured to lock the articulation drive shaft and a firing drive system configured to drive the firing drive shaft.

Example 161 - A surgical instrument system configured to treat the tissue of a patient

comprising a shaft assembly configured to perform a first function, a second function, and a
30 third function wherein the shaft assembly comprises a first drive shaft configured to perform the first function, a second drive shaft configured to perform the second function, and a third drive shaft configured to perform the third function. The surgical instrument system also comprises a first handle and a second handle. The first handle comprises a first drive system configured to drive the first drive shaft, a second drive system configured to drive the
35 second drive shaft, and a third drive system configured to drive the third drive shaft. The second handle comprises a first drive lockout configured to lock the first drive shaft and a second drive system configured to drive the second drive shaft.

Example 162 - The surgical instrument system of Example 161, wherein the second handle comprises a drive lockout configured to lock the third drive shaft.

Example 163 - A surgical instrument system configured to treat the tissue of a patient, comprising a shaft assembly which comprises a first drive system configured to perform a first function, a second drive system configured to perform a second function, a first lockout configured to selectively engage the first drive system and prevent the first drive system from performing the first function, and a second lockout configured to selectively engage the second drive system and prevent the second drive system from performing the second function. The surgical instrument system also comprises a first handle comprising a first operating system configured to operate the first drive system and a second operating system configured to operate the second drive system, wherein the first lockout and the second lockout are disengaged when the shaft assembly is assembled to the first handle. The surgical instrument system also comprises a second handle comprising a first operating system configured to operate the first drive system but not comprising a second operating system configured to operate the second drive system, wherein the first lockout is disengaged and the second lockout is engaged when the shaft assembly is assembled to the second handle.

Example 164 - The surgical instrument system of Example 163, wherein the first lockout and the second lockouts are in their engaged states when the shaft assembly is not assembled to either the first handle or the second handle.

Example 165 - A surgical instrument system, comprising a handle comprising a drive system including an electric motor and a shaft assembly attachable to the handle, wherein the shaft assembly comprises a drive shaft that is operably engaged with the drive system when the shaft assembly is attached to the handle, wherein the drive system is configured to drive the drive shaft when the shaft assembly is in a usable condition. The surgical instrument system also comprises a sensor system configured to evaluate the condition of the shaft assembly and a control system in communication with the drive system and the sensor system, wherein the control system is configured to prevent the operation of the electric motor if the shaft assembly is in an unusable condition.

Example 166 - The surgical instrument system of Example 165, further comprising a haptic feedback system in communication with the control system, wherein the control system is configured to actuate the haptic feedback system to provide haptic feedback to the user of the surgical instrument system when the sensor system detects that the shaft assembly is in an unusable condition.

Example 167 - The surgical instrument system of Examples 165 or 166, wherein the handle further comprises a second drive system, wherein the shaft assembly further comprises a second drive shaft operably engageable with the second drive system when the shaft

assembly is attached to the handle, and wherein the control system is configured to use the second drive system when the sensor system detects that the shaft assembly is in an unusable condition.

Example 168 - A surgical instrument system comprising a handle which comprises a

5 housing, a handle electrical connector, a drive system including an electric motor, and a power source. The surgical instrument system also comprises a shaft assembly operably attachable to the handle, wherein the shaft assembly comprises a connector attachable to the housing when the shaft assembly is attached to the handle, a drive shaft engageable with the drive system when the shaft assembly is attached to the handle, a shaft electrical
10 connector configured to be electrically coupled with the handle electrical connector when the shaft assembly is attached to the handle, and a shaft control system in communication with the shaft electrical connector, wherein the shaft control system is configured to receive power from the power source through the shaft electrical connector. The surgical instrument system also comprises a lockout in communication with the shaft control system, wherein
15 the lockout comprises a solenoid, a lock element movable between an unlocked position, a hold position, and a locked position, a catch configured to releasably hold the lock element in the unlocked position, wherein the solenoid is configured to release the catch and allow the lock element to be moved into the hold position when the shaft control system receives power from the power source, and a biasing member configured to move the lock element
20 into the hold position when the catch releases the lock element and while the shaft assembly is attached to the handle, wherein the biasing member is configured to move the lock element into the locked position once the shaft assembly is detached from the handle, and wherein the lock element prevents the shaft assembly from being re-attached to the handle once the lock element is in the locked position.

25 Example 169 - The surgical instrument system of Example 168, wherein the shaft assembly comprises an unreleasable catch configured to hold the lock element in the locked position.

Example 170 - A surgical instrument system comprising a handle and a shaft assembly operably attachable to the handle. The handle comprises a housing and a power source.

The shaft assembly comprises a connector attachable to the housing when the shaft

30 assembly is attached to the handle, a shaft control system configured to receive power from the power source when the shaft assembly is attached to the handle, and a lockout in communication with the shaft control system. The lockout comprises a lock element movable between an unlocked position, a hold position, and a locked position, a catch configured to releasably hold the lock element in the unlocked position, wherein the catch is
35 configured to allow the lock element to be moved into the hold position when the shaft control system receives power from the power source, and a biasing member configured to move the lock element into the hold position when the catch releases the lock element and

while the shaft assembly is attached to the handle, wherein the biasing member is configured to move the lock element into the locked position once the shaft assembly is detached from the handle, and wherein the lock element prevents the shaft assembly from being re-attached to the handle once the lock element is in the locked position.

- 5 Example 171 - The surgical instrument system of Example 170, wherein the shaft assembly comprises an unreleasable catch configured to hold the lock element in the locked position.

[0298] Although various devices have been described herein in connection with certain embodiments, modifications and variations to those embodiments may be implemented.

Particular features, structures, or characteristics may be combined in any suitable manner in one or more embodiments. Thus, the particular features, structures, or characteristics
10 illustrated or described in connection with one embodiment may be combined in whole or in part, with the features, structures or characteristics of one or more other embodiments without limitation. Also, where materials are disclosed for certain components, other materials may be used. Furthermore, according to various embodiments, a single

15 component may be replaced by multiple components, and multiple components may be replaced by a single component, to perform a given function or functions. The foregoing description and following claims are intended to cover all such modification and variations.

[0299] The devices disclosed herein can be designed to be disposed of after a single use, or they can be designed to be used multiple times. In either case, however, a device can be
20 reconditioned for reuse after at least one use. Reconditioning can include any combination of the steps including, but not limited to, the disassembly of the device, followed by cleaning or replacement of particular pieces of the device, and subsequent reassembly of the device. In particular, a reconditioning facility and/or surgical team can disassemble a device and, after cleaning and/or replacing particular parts of the device, the device can be reassembled
25 for subsequent use. Those skilled in the art will appreciate that reconditioning of a device can utilize a variety of techniques for disassembly, cleaning/replacement, and reassembly. Use of such techniques, and the resulting reconditioned device, are all within the scope of the present application.

[0300] The devices disclosed herein may be processed before surgery. First, a new or
30 used instrument may be obtained and, when necessary, cleaned. The instrument may then be sterilized. In one sterilization technique, the instrument is placed in a closed and sealed container, such as a plastic or TYVEK bag. The container and instrument may then be placed in a field of radiation that can penetrate the container, such as gamma radiation, x-rays, and/or high-energy electrons. The radiation may kill bacteria on the instrument and in
35 the container. The sterilized instrument may then be stored in the sterile container. The sealed container may keep the instrument sterile until it is opened in a medical facility. A

device may also be sterilized using any other technique known in the art, including but not limited to beta radiation, gamma radiation, ethylene oxide, plasma peroxide, and/or steam.

[0301] While this invention has been described as having exemplary designs, the present invention may be further modified within the spirit and scope of the disclosure. This

5 application is therefore intended to cover any variations, uses, or adaptations of the invention using its general principles.

[0302] Any patent, publication, or other disclosure material, in whole or in part, that is said to be incorporated by reference herein is incorporated herein only to the extent that the incorporated materials do not conflict with existing definitions, statements, or other

10 disclosure material set forth in this disclosure. As such, and to the extent necessary, the disclosure as explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other disclosure material set forth herein will only be incorporated to the extent that no conflict arises between
15 that incorporated material and the existing disclosure material.

WHAT IS CLAIMED IS:

1. A surgical instrument system, comprising:
a handle, comprising:
a housing;
a motor disposed within said handle;
at least one control switch; and
a motor-control processor in communication with said at least one control switch to control said motor, wherein said processor is not positioned in said handle;
a shaft; and
a disposable battery housing configured to be attached to said housing, comprising:
a disposable battery; and
a display unit.
2. The surgical instrument system of Claim 1, further comprising a controller.
3. The surgical instrument system of Claim 2, wherein said controller is located within said shaft.
4. The surgical instrument system of Claim 3, wherein said controller comprises a control circuit configured to control said display unit on said disposable battery housing.
5. The surgical instrument system of Claim 1, wherein said display unit on said disposable battery housing is touch screen capable.
6. The surgical instrument system of Claim 1, wherein said display unit comprises a multi-color display configured to indicate at least one function of the surgical instrument system to a user.
7. A surgical instrument, comprising:
a handle, comprising:
a housing;
a motor located in said handle; and
at least one control switch;
a shaft;
a disposable power module, comprising:
a disposable battery; and

a display unit; and

a motor-control processor in communication with said at least one control switch to control said motor, wherein said processor is positioned in at least one of said shaft and said disposable power module.

8. The surgical instrument of Claim 7, further comprising a controller.
9. The surgical instrument of Claim 8, wherein said controller is located within said shaft.
10. The surgical instrument of Claim 9, wherein said controller comprises a control circuit configured to control said display unit on said disposable power module.
11. The surgical instrument of Claim 7, wherein said display unit on said disposable power module is touch screen capable.
12. The surgical instrument of Claim 7, wherein said display unit comprises a multi-color display configured to indicate at least one function of said surgical instrument.
13. A surgical instrument, comprising:
 - a housing;
 - a handle attached to said housing, wherein said handle comprises:
 - a motor; and
 - at least one control switch;
 - an end effector;
 - a shaft, comprising:
 - a controller located within said shaft, wherein the controller is configured to control at least one function of said end effector; and
 - a disposable battery comprising a multi-color display unit.
14. The surgical instrument of Claim 13, wherein said controller comprises a control circuit configured to control said display unit on said disposable battery.
15. The surgical instrument of Claim 13, wherein said end effector further comprises at least one sensor.

16. The surgical instrument of Claim 13, wherein said display unit on said disposable battery is touch screen capable.
17. A sterilizable surgical instrument system, comprising:
 - a handle assembly, comprising:
 - a motor; and
 - at least one control switch;
 - a shaft attached to a distal end of said handle assembly, wherein said shaft comprises a controller located within said shaft;
 - a disposable battery assembly, comprising:
 - a disposable battery; and
 - a display unit; and
 - an end effector attached to a distal end of said shaft.
18. The surgical instrument system of Claim 17, wherein said controller comprises a control circuit configured to control said display unit on said disposable battery.
19. The surgical instrument system of Claim 17, wherein said end effector further comprises at least one sensor.
20. The surgical instrument system of Claim 17, wherein said display unit on said disposable battery housing is touch screen capable.
21. The surgical instrument system of Claim 17, wherein said display unit comprises a multi-color display configured to indicate at least one function of said surgical instrument system.
22. A surgical instrument system, comprising:
 - a handle assembly comprising a drive system including an electric motor;
 - a battery comprising a first battery cell and a second battery cell;
 - a first shaft assembly attachable to said handle assembly, wherein said drive system utilizes a first power load from said battery to operate said first shaft assembly, and wherein said first power load is supplied by said first battery cell and not said second battery cell; and
 - a second shaft assembly attachable to said handle assembly, wherein said drive system comprises a second power load to operate said second shaft assembly which is

different than said second power load, and wherein said second power load is supplied by said first battery cell and said second battery cell.

23. A surgical instrument system, comprising:
a handle assembly, comprising:
a housing; and
a drive system including an electric motor; and
a battery insertable into said housing in a first orientation and a second orientation, wherein said battery is configured to supply a first maximum power to said drive system when said battery is in said first orientation, wherein said battery is configured to supply a second maximum power when said battery is in said second orientation, and wherein said first orientation is different than said second orientation.
24. The surgical instrument system of Claim 23, wherein said battery is inserted into said handle in said first orientation when a first shaft assembly is attached to said handle, and wherein said battery is inserted into said second orientation when a second shaft assembly is attached to said handle.
25. A surgical instrument system, comprising:
a drive module comprising a drive module housing;
a shaft assembly attachable to said drive module housing; and
a drive system, comprising:
an electric motor positioned in said drive module housing;
a drive shaft in said shaft assembly which is operably couplable with said electric motor when said shaft assembly is attached to said drive module; and
a control circuit including a microprocessor, wherein said microprocessor is positioned in said shaft assembly;
a battery attachable to said drive module housing, wherein said battery comprises:
a battery housing;
at least one battery cell in said battery housing configured to supply power to said drive system when said battery is attached to said drive module housing; and
a display in communication with control circuit when said battery is attached to said drive module housing.
26. The surgical instrument system of Claim 25, wherein said display comprises electrophoretic media.

27. The surgical instrument system of Claim 25, wherein said display comprises an active matrix backplane.
28. The surgical instrument system of Claim 27, wherein said active matrix backplane comprises an amorphous silicon semiconductor.
29. The surgical instrument system of Claim 27, wherein said active matrix backplane comprises a polythiophene semiconductor.
30. The surgical instrument sytem of Claim 27, wherein said display comprises an electrochromic display.
31. The surgical instrument system of Claim 27, wherein said display comprises a liquid-crystal display.
32. The surgical instrument system of Claim 27, wherein said display comprises a thin-film transistor liquid-crystal display.
33. A surgical instrument system, comprising:
a drive module comprising a drive module housing;
a battery attachable to said drive module housing, wherein said battery comprises:
a battery housing;
at least one battery cell in said battery housing configured to supply power to said drive system when said battery is attached to said drive module housing; and
a display in communication with a control circuit when said battery is attached to said drive module housing; and
a drive system;
an electric motor positioned in said drive module housing; and
a control circuit including a microprocessor, wherein said microprocessor is positioned in said battery housing.
34. The surgical instrument system of Claim 33, wherein said display comprises electrophoretic media.
35. The surgical instrument system of Claim 33, wherein said display comprises an active matrix backplane.

36. The surgical instrument system of Claim 35, wherein said active matrix backplane comprises an amorphous silicon semiconductor.
37. The surgical instrument system of Claim 35, wherein said active matrix backplane comprises a polythiophene semiconductor.
38. The surgical instrument system of Claim 33, wherein said display comprises an electrochromic display.
39. The surgical instrument system of Claim 33, wherein said display comprises a liquid-crystal display.
40. The surgical instrument system of Claim 33, wherein said display comprises a thin-film transistor liquid-crystal display.
41. A surgical instrument system, comprising:
a drive module comprising a drive module housing;
a battery attachable to said drive module housing, wherein said battery comprises:
a battery housing;
at least one battery cell in said battery housing configured to supply power to said drive system when said battery is attached to said drive module housing; and
a display in communication with a control circuit when said battery is attached to said drive module housing; and
a drive system;
an electric motor positioned in said drive module housing; and
a control system including a microprocessor, wherein said microprocessor is not positioned in said drive module.
42. The surgical instrument system of Claim 41, wherein said control system comprises at least one input on said drive module.
43. The surgical instrument system of Claim 41, wherein said control system comprises at least one switch on said drive module.
44. A surgical instrument system, comprising:
a drive module comprising a housing and an electric motor; and
a battery selectively attachable to said drive module, comprising:

a housing comprising a connector configured to releasably connect said battery to said drive module;
at least one battery cell; and
an electronic display.

45. The surgical instrument system of Claim 44, wherein said display comprises electrophoretic media.

46. The surgical instrument system of Claim 44, wherein said display comprises an active matrix backplane.

47. The surgical instrument system of Claim 46, wherein said active matrix backplane comprises an amorphous silicon semiconductor.

48. The surgical instrument system of Claim 46, wherein said active matrix backplane comprises a polythiophene semiconductor.

49. The surgical instrument system of Claim 44, wherein said display comprises an electrochromic display.

50. The surgical instrument system of Claim 44, wherein said display comprises a liquid-crystal display.

51. The surgical instrument system of Claim 44, wherein said display comprises a thin-film transistor liquid-crystal display.

52. A handle for use with a surgical instrument system, said handle comprising:
a drive module, comprising:
a housing;
a sealed motor module removably positionable with said housing, comprising:
a liquid-tight barrier;
at least one electrical input extending through said liquid-tight barrier;
and
a rotatable output extending through said liquid-tight barrier; and
a sealed battery module, comprising:
a housing comprising a connector configured to attach said sealed battery module to said drive module;

a liquid-tight battery barrier; and
at least one electrical output extending through said liquid-tight battery barrier.

53. A surgical instrument system, comprising:
a drive module comprising a drive system including an electric motor;
a shaft attachable to said drive module, wherein said shaft comprises an end effector configured to treat the tissue of a patient;
a battery attachable to said drive module;
at least one electronic display system on at least one of said shaft and said battery;
and
a control circuit comprising a processor, wherein said control circuit is configured to control said drive system, and wherein said control circuit is configured to communicate with said at least one electronic display system; and
a power switch configured to place said battery in communication with said control circuit when said power switch is placed in an operational configuration, wherein said processor is configured to interrogate said shaft and said battery to assess the number of electronic display systems in said surgical instrument system.

54. The surgical instrument system of Claim 53, wherein said processor is configured to interrogate said shaft and said battery to assess the number of electronic display systems in said surgical instrument system when said power switch is moved into said operational configuration.

55. The surgical instrument system of Claim 53, wherein said processor is configured to interrogate said shaft and said battery to assess the number of electronic display systems in said surgical instrument system when said battery is assembled to said surgical instrument system.

56. A surgical instrument system, comprising:
a drive module comprising a drive system including an electric motor;
a shaft attachable to said drive module, wherein said shaft comprises an end effector configured to treat the tissue of a patient;
a battery attachable to said drive module;
at least one electronic display system on at least one of said drive module, said shaft, and said battery; and
a control circuit comprising a processor, wherein said control circuit is configured to control said drive system, wherein said control circuit is configured to communicate with said

at least one electronic display system, and wherein said processor is configured to interrogate said shaft and said battery to assess the number of electronic display systems in said surgical instrument system.

57. The surgical instrument system of Claim 56, wherein said processor is configured to interrogate said drive module, said shaft, and said battery to assess the number of electronic display systems in said surgical instrument system when said battery is assembled to said surgical instrument system.

58. A surgical instrument system, comprising:
a drive module comprising a drive system including an electric motor;
a shaft attachable to said drive module, wherein said shaft comprises an end effector configured to treat the tissue of a patient;
a battery attachable to said drive module;
a control circuit comprising a processor, wherein said control circuit is configured to control said drive system during an operational sequence, and wherein said battery is configured to supply power to said control circuit during an initiation sequence; and
a communications circuit configured to communicate with and receive data from an off-board control system during said initiation sequence, wherein said communications circuit is in communication with said control circuit, wherein said control circuit is configured to receive said data from said communications circuit, and wherein said control circuit is configured to modify said operational sequence using said data.

59. The surgical instrument system of Claim 58, wherein said initiation sequence is initiated by the assembly of said battery to said drive module.

60. The surgical instrument system of Claim 58, further comprising a switch configurable in an operational configuration, wherein said initiation sequence is initiated by placing said switch in said operational configuration.

61. The surgical instrument system of Claim 58, wherein said communications circuit comprises a wireless signal transmitter and a wireless signal receiver.

62. The surgical instrument system of Claim 58, wherein said operational sequence comprises an algorithm, and wherein said control circuit modifies said algorithm when modifying said operational sequence.

63. The surgical instrument system of Claim 62, wherein said control circuit deactivates a function of said surgical instrument system when modifying said algorithm.

64. The surgical instrument system of Claim 58, wherein said initiation sequence comprises an algorithm, and wherein said control circuit deactivates a function of said surgical instrument system when modifying said algorithm.




FIG. 1





FIG. 2



3
G
E




FIG. 4

5/92





FIG. 5





7/92





FIG. 7


$$\frac{\infty}{\frac{1}{L}}$$






FIG. 9

10/92



0101

11/92






FIG. 12

13/92




FIG. 13




FIG. 14

15/92




FIG. 15




FIG. 16

17/92






FIG. 17


$$\frac{\infty}{1} \cdot \frac{1}{\infty}$$



১৭

20/92




FIG. 20




FIG. 21




FIG. 22




FIG. 22A

24/92




FIG. 23

25/92





FIG. 24



27/92




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38





FIG. 39






FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46





FIG. 47



48




Fig. 49




FIG. 50








FIG. 51

53/92



54/92



55/92




FIG. 54




FIG. 55

56/92




FIG. 56




FIG. 57

57/92





FIG. 58

58/92



55




FIG. 60




FIG. 61




FIG. 62




FIG. 63

63/92





FIG. 4






FIG. 66




FIG. 66A




FIG. 66B




FIG. 66C

67/92




FIG. 66D




FIG. 66E




FIG. 66F




FIG. 66G




FIG. 67




FIG. 68B




FIG. 68A




FIG. 68C




FIG. 68D

	RT/LE SHAFT ARTICULATION	DISTAL HEAD ROTATION	END-EFFECTOR ACTUATION #1 ACTUATION #2		SHAFT ROTATION
1 PENCIL HANDLE (8)	8mm MOTOR / +30°	MANUAL / >360°	LOCKED OUT	LOCKED OUT	LOCKED OUT
2 SCISSOR HANDLE (12)	12mm MOTOR 1 / +45°	MANUAL / >360°	MOTOR 2	LOCKED OUT	LOCKED OUT
3 PISTOL HANDLE (12)	12mm MOTOR1 / 5mm±45° 10mm±90°	12mm MOTOR 3 / >360°	MOTOR 2	MOTOR 2 WITH SHIFT	MANUAL / >360°

FIG. 69

75/92




FIG. 70




FIG. 71

77/92




FIG. 72




FIG. 73

FIG. 73A

RT/LE SHAFT ARTICULATION	DISTAL HEAD ROTATION	END-EFFECTOR		SHAFT ROTATION
		ACTUATION #1	ACTUATION #2	
12mm MOTOR 1/ +45°	MANUAL/ >360°	MOTOR 2	LOCKED OUT	LOCKED OUT

SCISSOR HANDLE 12

FIG. 73B

79/92




FIG. 74




FIG. 75

FIG. 75A

RT/LE SHAFT ARTICULATION	DISTAL HEAD ROTATION	END-EFFECTOR ACTUATION		SHAFT ROTATION
MOTOR1/5mm±45° 10mm±90°	MOTOR 3/ >360°	MOTOR 2	MOTOR 2 WITH SHIFT	MANUAL/ >360°

PISTOL HANDLE (12)

FIG. 75B




FIG. 76





FIG. 76A






FIG. 77A


$$OD\phi_T = ID\phi_{EAP}$$


FIG. 78B




FIG. 77B

$$OD\emptyset_T < ID\emptyset_{EAP}$$

Non-energized




FIG. 78A




FIG. 79




FIG. 80




FIG. 81




FIG. 82




FIG. 83




FIG. 85

FIG. 84

89/92




FIG. 85A Unfired, Attached/Detached




FIG. 85B Fired, Attached




FIG. 85C

90/92




FIG. 86

91/92





FIG. 87

92/92



INTERNATIONAL SEARCH REPORT

International application No
PCT/US2018/057238

A. CLASSIFICATION OF SUBJECT MATTER

INV. A61B17/29 A61B17/00
ADD. A61B17/122 A61B90/00 A61B17/128 A61B18/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EP0-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 2017/123841 A2 (ETHICON LLC [US]) 20 July 2017 (2017-07-20)	1-3
Y	abstract; figures 1-3, 17-19, 45 paragraphs [0152], [0192], [0194], [0206], [0234], [0486] -----	4-6
Y	EP 2 756 808 A1 (COVIDIEN LP [US]) 23 July 2014 (2014-07-23)	4,6
A	abstract; figure 3 paragraphs [0033], [0036] - [0037]; claims 1,2,13 -----	1-3,5
Y	US 2015/122870 A1 (ZEMLOK MICHAEL A [US] ET AL) 7 May 2015 (2015-05-07) abstract; figures 1,3,13-14,20 paragraphs [0081], [0191], [0192] ----- -/--	5



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

7 March 2019

Date of mailing of the international search report

15/03/2019

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Macaire, Stéphane

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2018/057238

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 2 509 523 A (MAMPETTA ANISH KUMAR [GB]; INNOVATIONS LTD M [GB]) 9 July 2014 (2014-07-09) abstract; figures 8a, 12a-12b page 6, paragraph 1-2 -----	1-3
A	US 2017/281173 A1 (SHELTON IV FREDERICK E [US] ET AL) 5 October 2017 (2017-10-05) abstract; figures 1, 30G, 53-56 paragraphs [0304], [0346], [0379] -----	1-3

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2018/057238

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☒ Claims Nos.: 7-64
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
see FURTHER INFORMATION sheet PCT/ISA/210
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of Item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fees, this Authority did not invite payment of additional fees.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- ☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- ☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

Continuation of Box II.2

Claims Nos.: 7-64

1. The application comprises 14 independent apparatus claims:

Independent apparatus claims 1, 7, 13, 17, 22, 23, 25, 33, 41, 44, 52, 53, 56 and 58.

There is no clear distinction between the independent claims because of overlapping scope. There are so many independent claims, and they are drafted in such a way that the claims as a whole are not in compliance with the provisions of clarity and conciseness of Article 6 PCT, as it is particularly burdensome for a skilled person to establish the subject-matter for which protection is sought (PCT Guidelines 9.30 and 9.34).

2. It is further noted that the claims do not include the reference signs in parentheses required for clarity by Article 6 PCT in combination with Rule 6 PCT.

3. The applicant did not reply to the invitation to provide informal clarification dated 28.01.2019.

Therefore the search has been based on the first independent claim and the corresponding dependent claims.

The applicant's attention is drawn to the fact that claims relating to inventions in respect of which no international search report has been established need not be the subject of an international preliminary examination (Rule 66.1(e) PCT). The applicant is advised that the EPO policy when acting as an International Preliminary Examining Authority is normally not to carry out a preliminary examination on matter which has not been searched. This is the case irrespective of whether or not the claims are amended following receipt of the search report or during any Chapter II procedure. If the application proceeds into the regional phase before the EPO, the applicant is reminded that a search may be carried out during examination before the EPO (see EPO Guidelines C-IV, 7.2), should the problems which led to the Article 17(2) declaration be overcome.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2018/057238

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 2017123841	A2	20-07-2017	BR 112018014410 A2	11-12-2018
			CN 108697461 A	23-10-2018
			EP 3402431 A2	21-11-2018
			JP 2019503230 A	07-02-2019
			US 2017202607 A1	20-07-2017
			WO 2017123841 A2	20-07-2017

EP 2756808	A1	23-07-2014	AU 2014200075 A1	31-07-2014
			CA 2839458 A1	16-07-2014
			CN 103919585 A	16-07-2014
			EP 2756808 A1	23-07-2014
			EP 3005955 A1	13-04-2016
			ES 2560843 T3	23-02-2016
			JP 6339805 B2	06-06-2018
			JP 2014136163 A	28-07-2014
			JP 2018126546 A	16-08-2018
			US 2014200561 A1	17-07-2014
			US 2017150983 A1	01-06-2017

US 2015122870	A1	07-05-2015	NONE	

GB 2509523	A	09-07-2014	NONE	

US 2017281173	A1	05-10-2017	EP 3225179 A1	04-10-2017
			EP 3225183 A1	04-10-2017
			EP 3225186 A1	04-10-2017
			EP 3225188 A2	04-10-2017
			EP 3225196 A2	04-10-2017
			EP 3228260 A2	11-10-2017
			US 2017281155 A1	05-10-2017
			US 2017281170 A1	05-10-2017
			US 2017281173 A1	05-10-2017
			US 2017281177 A1	05-10-2017
			US 2017281180 A1	05-10-2017
			US 2017281188 A1	05-10-2017
			WO 2017172586 A1	05-10-2017
			WO 2017172750 A1	05-10-2017
			WO 2017172915 A1	05-10-2017
			WO 2017172921 A1	05-10-2017
			WO 2017173015 A2	05-10-2017
			WO 2017173025 A2	05-10-2017
