



-
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

LED-BASED WHITE-LIGHT BACKLIGHTING FOR ELECTRONIC DISPLAYS

[0001] This invention relates in general to a backlight system for a liquid crystal (LCD) or other electronic display and, in particular, to controlling the color and lumen level of a red-green-blue (RGB) light-emitting diode (LED) backlight and the sensor(s) that control(s) such a backlight.

[0002] Backlighting with white light generated by RGB LEDs is known to those skilled in the art. However, the characteristics of the LEDs vary with temperature, current, and aging. These characteristics also vary from one LED in a batch to another. Thus there is need for a feedback control to maintain within set limits the color and lumen level of such a backlighting system. For the feedback control to work satisfactorily, sensors must be placed properly to provide the necessary optical feedback.

[0003] The present invention provides apparatus and method for backlighting an electronic display with LEDs to control luminosity, radiometric power, and tristimulus levels by means of feedback control through a microprocessor, thereby maintaining the white backlight at substantially constant levels, which can be chosen by an operator.

[0004] In one embodiment of the invention, apparatus for backlighting an electronic display with white light comprises: a plurality of light-emitting diodes (LEDs), each of the LEDs effective for emitting light of a single color; at least one light source comprised of at least three of the LEDs arranged in a combination that produces white light; a light guide effective for illuminating the display with the white light; and circuitry effective for maintaining the white light at a substantially constant level of color and luminosity by controlling the at least one light source. This embodiment of the invention utilizes a method for backlighting an electronic display with white light comprising the steps of: driving a plurality of LEDs, each of the LEDs emitting light of a single color; combining light emitted from at least three of the LEDs to form white light; illuminating the display with the white light; and controlling the color and brightness of the white light by means of feedback circuitry.

[0005] In another embodiment of the invention there is provided apparatus for backlighting an electronic display with white light comprising means for driving a

plurality of LEDs, each of the LEDs emitting light of a single color; means for combining light emitted from at least three of the LEDs to form white light; means for illuminating the display with the white light; means for controlling the color and brightness of the white light by feedback circuitry; and the means for controlling being subject to an operator's direction. The present invention addresses one or more of these concerns.

[0006] In the accompanying drawings, like reference numerals designate corresponding elements or parts throughout, wherein:

[0007] Fig. 1 illustrates the apparatus of the present invention for backlighting an LCD or other electronic display by means of RGB LEDs controlled by a microprocessor;

[0008] Fig. 2 illustrates the placement of photosensors in a light guide; and

[0009] Fig. 3 illustrates placement of photosensors in a light guide when only a single side light source is used.

[0010] Referring to Fig. 1, there is illustrated an apparatus for controlling white light for substantially uniform backlighting of an LCD 100 or similar display, utilizing a power supply 110, which obtains power from an alternating current source 115. Power supply 110 further comprises a plurality of LED drivers 120, 130, 140, one each for red, green, and blue drivers, respectively. Each of LED drivers 120, 130, 140 is connected to a plurality of LEDs of the same color, connected in suitable series and parallel combinations, that comprise each of a plurality of light sources 150, 160.

[0011] Light sources 150, 160 are each embedded in a heat sink 190, 200 to avoid overheating of LEDs and maximize uniformity of color. Light sources 150, 160 are in turn mounted on the edges of a light guide 170. Uniformity of color is maintained by forming a unit white cell on each of light sources 150, 160 in a suitable combination of LEDs, such as R-G-B, R-G-B-G, G-R-B, etc., that maximize uniformity of color. Optical arrangements couple the light from the LEDs of light sources 150, 160 to light guide 170.

[0012] LED drivers 120, 130, 140 supply current, suitably converted within power supply 110, to the LEDs in light sources 150, 160. A microprocessor 180, programmed with the functions necessary to control color and lumen level in light guide 170, provides signals that control the currents from LED drivers 120, 130, 140. A plurality of photo sensors 210 send feedback via a circuit 230 to permit

microprocessor 180 to vary the signals sent to LED drivers 120, 130, 140. These signals may take the form of amplitude modulation, PWM signals, or other suitable values. A controller 240 feeds to microprocessor 180 signals that determine color and brightness levels of an LCD or other electronic display (not shown) backlit by light guide 170.

[0013] Feedback control is required to maintain color and brightness in light guide 170. Without such control, variations in the characteristics of the individual LEDs in light sources 150, 160 will cause the color and brightness in light guide 170 to vary within unacceptable limits. The feedback control required depends on taking appropriate samples by sensing.

[0014] In a first embodiment of the present invention, temperatures of light sources 150, 160 are sensed within heat sinks 190, 200. Microprocessor 180 is programmed to compensate for temperature-related variations in color and brightness in light guide 170 caused by variations in the characteristics of the LEDs in light sources 150, 160. This compensation is effected by adjusting the currents sent by LED drivers 120, 130, 140 to the LEDs. This first embodiment has no mechanism to overcome aging effects in the individual LEDs.

[0015] In a second embodiment of the present invention, photo diodes 210 measure at least one of either the lumen level and the radiometric power level in light guide 170 by unfiltered photo diodes, photo diodes with Y filters, or other suitable means. Microprocessor 180 is programmed to compensate for variations in color and brightness in light guide 170, caused by variations in the characteristics of the LEDs in light sources 150, 160, by adjusting the currents from LED drivers 120, 130, 140 to the desired levels of lumen and/or radiometric power. This second embodiment cannot overcome variations in color caused by variations in temperature.

[0016] In a third embodiment, both the temperatures in heat sinks 190, 200 and at least one of either the lumen level or the radiometric power level in light guide 170 are sensed as described in the first and second embodiments and fed to microprocessor 180. By programming microprocessor 180 to adjust the currents from LED drivers 120, 130, 140 in response to both sets of feedback stimuli, this embodiment of the present invention compensates for both aging and temperature variations in the LEDs in light sources 150, 160.

[0017] In a fourth embodiment, photo diodes 210 are fitted with appropriate filters to sense the tristimulus values of the white light in light guide 170. These tristimulus values (or another measure of color), fed back to a suitably programmed microcomputer 180, adjust the currents of LED drivers 120, 130, 140 to match the tristimulus values for the light in light guide 170 to match reference values.

[0018] In a fifth embodiment, temperatures in heat sinks 190, 200 are measured to add temperature compensation to the adjusted tristimulus values referred to in the fourth embodiment.

[0019] In all of the above embodiments, the color and lumen level of the white light from light guide 170 can be manually set by an operator or automatically by the control circuitry.

[0020] To insure uniformity of color, the sensors must be placed appropriately to provide the necessary feedback components for uniform color control. Referring again to Figure 1, each of heat sinks 190, 200 has three temperature sensors 250. The placement of temperature sensors 250 on heat sinks 190, 200 depends on the latter's temperature profile. Feedback control is based on a weighted average of the outputs of temperature sensors 250.

[0021] A minimum of one pair of photo diodes 210 is required by the present invention, but their placement can vary. Referring again to Figure 1, a first embodiment places each of a pair of photo diodes 210 in the middle of each of two sides of light guide 170.

[0022] Referring to Figure 2, a second embodiment places photo diodes 210 on the underside of light guide 170, between its body and the reflector below. The light in light guide 170 is sensed by at least one set of photo diodes 210, and the average from all of them is used by microprocessor 180. Figure 2 shows three sets of photo sensors 260, 270, and 280. They are placed in a row substantially in the middle of a planar light guide 170, with photo sensors 270 in the middle of the row and photo sensors 260, 280 each placed approximately one-quarter of the distance from the side.

[0023] Referring to Figure 3, in this embodiment only a single source can illuminate light guide 170, i.e., light source 150 is embedded in heat sink 190 for single-sided illumination of light guide 170, and there is no light source 160 as in Figure 1. When light source 150 is alone, photo sensors 260, 270, 280 may be placed at the opposite edge of light guide 170 from light source 150. They are placed in a row with photo

sensors 270 in the middle of the row and photo sensors 260, 280 each placed approximately one-quarter of the distance from the side.

[0024] Many other positions and numbers of photo diodes 210 and temperature sensors 250 are possible within the present invention.

[0025] Having described preferred embodiments of the invention with reference to the accompanying drawings, it is to be understood that the invention is not limited to those precise embodiments, and that various changes and modifications may be effected therein by one skilled in the art without departing from the scope or spirit of the invention as defined in the appended claims. Other aspects and features of the present invention can be obtained from a study of the drawings, the disclosure, and the appending claims.

Claims

1. Apparatus for backlighting an electronic display with white light, which comprises:

5 a plurality of light-emitting diodes (LEDs)(120, 130, 140), each of said LEDs effective for emitting light of a single color;

at least one light source (150, 160) comprised of at least three of said LEDs arranged in a combination that produces white light (210);

10 a light guide (170) effective for illuminating said display with said white light;

circuitry (230) effective for maintaining said white light at a substantially constant level of color and luminosity by controlling said at least one light source; and said circuitry being controlled (180) either automatically or manually.

15 2. Apparatus as in claim 1, wherein said circuitry includes a microprocessor (180) effective for controlling current flowing to said LEDs.

20 3. Apparatus as in claim 2, wherein said circuitry includes at least one set of photo diodes (210) effective for measuring luminosity of said light guide (120) and sending a value thereof to said microprocessor (180).

25 4. Apparatus as in claim 2, wherein said circuitry includes at least one set of photo diodes (210) effective for measuring radiometric power level in said light guide (170) and sending a value thereof to said microprocessor (180).

5. Apparatus as in claim 2, wherein said circuitry includes at least one set of photo diodes (210) effective for measuring color values of said white light in said light guide and sending said values to said microprocessor (180).

30 6. Apparatus as in claim 2, wherein said plurality of LEDs are embedded in at least one heat sink (190, 200), said heat sink being fitted with at least one sensor effective for measuring a temperature of said LEDs and forwarding said temperature to said microprocessor (180).

7. Apparatus as in claim 6, wherein said sensor and at least one set of photo diodes (210) effective for measuring luminosity of said light guide (170) send outputs simultaneously to said microprocessor (180).

5

8. Apparatus as in claim 6, wherein said sensor and at least one set of photo diodes (210) effective for measuring radiometric power level in said light guide (170) send outputs simultaneously to said microprocessor (180).

10

9. Apparatus as in claim 6, wherein said sensor and at least one set of photo diodes (210) effective for measuring tristimulus values of said white light in said light guide (170) send outputs simultaneously to said microprocessor (180).

15

10. Apparatus as in claim 1, wherein said at least one set of photo diodes (210) contains three diodes placed an effective distance from each other in a row along an end of said light guide (170) opposite a single at least one light source, a middle member (270) of said set being placed substantially at the center of said end.

20

11. Apparatus as in claim 1, wherein said at least one set of photo diodes (210) contains three diodes (260, 270, 280) placed an effective distance from each other in a horizontal row substantially at the middle of said light guide (170), a middle member of said set (270) being placed substantially at the center of said light guide (170) and said at least one light source being a pair of light sources (260, 280) at respective ends of said light guide.

25

12. A method for backlighting an electronic display with white light, which comprises the steps of:

driving a plurality of LEDs (120, 130, 140), each of said LEDs emitting light of a single color;

30

combining light emitted from at least three of said LEDs to form white light;

illuminating (150, 160) said display with said white light; and

controlling (180) the color and brightness of said white light by means of feedback circuitry.

13. The method of claim 12, wherein said step of controlling includes a
5 further step of sensing the temperature (250) of said LEDs.

14. The method of claim 12, wherein said step of controlling includes a
further step of sensing the radiometric power level of said white light by means of at least
one set of photo diodes (210).
10

15. The method of claim 12, wherein said step of controlling includes a
further step of sensing the luminosity of said white light by means of at least one set of
photo diodes (210).

16. The method of claim 12, wherein said step of controlling includes a
further step of sensing the color values of said white light by means of at least one set of
photo diodes (210).
15

17. The method of claim 12, wherein said step of controlling includes a
further step of combining the sensed tristimulus values of said white light with the sensed
temperature (250) of said LEDs.
20

18. The method of claim 12, wherein said step of controlling includes a
step of combining the sensed luminosity (210) of said white light with the sensed
temperature (250) of said LEDs.
25

19. The method of claim 12, wherein said step of controlling includes a
further step of combining the sensed radiometric power level (210) of said white light with
the sensed temperature (250) of said LEDs.
30

20. Apparatus for backlighting an electronic display with white light,
which comprises:

means for driving a plurality of LEDs (120, 130, 140), each of said LEDs emitting light of a single color;


means for combining light emitted from at least three of said LEDs to form white light (210);

5 means for illuminating said display with said white light (150, 160);

means for controlling the color and brightness of said white light by feedback circuitry (230); and

said means for controlling being subject to an operator's direction (180).

10






FIG. 2




FIG. 3

INTERNATIONAL SEARCH REPORT

Intern Application No

PCT/IB 03/02549

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 G09G3/34 G09G3/36

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G09G H05B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X Y	US 2002/070914 A1 (BRUNING GERT W ET AL) 13 June 2002 (2002-06-13) column 6 paragraph '0009! - paragraph '0010! paragraph '0038! - paragraph '0039! paragraph '0047! figures 2-4	1,2, 12-20 3-9
Y	WO 02 47438 A (KONINKL PHILIPS ELECTRONICS NV) 13 June 2002 (2002-06-13) page 3, line 24 - line 27 page 4, line 8 - page 5, line 23 page 8, line 3 - line 5 figures 1,2 -/--	3-9



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

° Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

6 November 2003

Date of mailing of the international search report

17/11/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Farricella, L

INTERNATIONAL SEARCH REPORT

Interr il Application No

PCT/IB 03/02549

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 1 077 444 A (AGILENT TECHNOLOGIES INC) 21 February 2001 (2001-02-21)	12, 14-16, 20
Y	paragraph '0002! - paragraph '0003! paragraph '0019! - paragraph '0024! paragraph '0033! - paragraph '0035! paragraph '0050! - paragraph '0054! figures 1,3,4 -----	1-5
Y	DE 100 57 696 A (SIEMENS AG) 16 May 2002 (2002-05-16) paragraph '0017! - paragraph '0018! paragraph '0023! paragraph '0025! - paragraph '0026! figures 1-4 -----	1-5
A	US 6 255 786 B1 (YEN GEORGE) 3 July 2001 (2001-07-03) column 1, line 1 - line 59 column 4, line 4 - line 21 figures 1,2 -----	6

INTERNATIONAL SEARCH REPORT

 International Application No
 PCT/IB 03/02549

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 2002070914	A1	13-06-2002	CN 1422423 T EP 1350239 A1 WO 0248994 A1	04-06-2003 08-10-2003 20-06-2002
WO 0247438	A	13-06-2002	US 2002097000 A1 CN 1419797 T WO 0247438 A2 EP 1346609 A2 TW 535455 B	25-07-2002 21-05-2003 13-06-2002 24-09-2003 01-06-2003
EP 1077444	A	21-02-2001	US 6344641 B1 EP 1077444 A2 JP 2001092414 A	05-02-2002 21-02-2001 06-04-2001
DE 10057696	A	16-05-2002	DE 10057696 A1 WO 0242837 A1 US 2003197817 A1	16-05-2002 30-05-2002 23-10-2003
US 6255786	B1	03-07-2001	NONE	