

**(19) World Intellectual Property Organization
International Bureau**



**(43) International Publication Date
20 September 2007 (20.09.2007)**

PCT

(10) International Publication Number
WO 2007/105375 A1

(51) International Patent Classification:
G03G 15/08 (2006.01)

(81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(21) International Application Number: PCT/JP2007/050541

(22) International Filing Date: 10 January 2007 (10.01.2007)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2006-066011 10 March 2006 (10.03.2006) JP

(71) **Applicant (for all designated States except US): CANON KABUSHIKI KAISHA [JP/JP]; 30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo 146-8501 (JP).**

(72) Inventor; and

(75) **Inventor/Applicant (for US only): KAWAI, Tachio [JP/JP]; 1-10-5-1501, Ougicho, Odawara-shi, Kanagawa 250-0001 (JP).**

(74) **Agent: YAMADA, Ryuichi**; Toko International Patent Office, Hasegawa Bldg. 4F, 7-7, Toranomon 3-chome, Minato-ku, Tokyo 105-0001 (JP).


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A CLOSURE WITH INLET AND OUTLET PORTS, A VESSEL WITH INTEGRATED MIXING BALLS, AND A METHOD FOR SEPARATING MATERIAL FROM A SAMPLE



(57) Abstract: Image forming apparatus, wherein a process cartridge (7) and a developer supply cartridge (9) which is supplying developer to the process cartridge (7), are separably mountable to and dismountable from to a main assembly (100a) of the image forming apparatus. Each of the cartridges (7, 9) comprises an opening-closing mechanism to open and close shutters (35, 95, 65, 97) for opening and closing supply and receiving openings in order to avoid leakage of developer when one of the developer supply cartridge (9) or process cartridge (7) is mounted to or dismounted from the image forming apparatus. A mechanism is provided comprising a regulating member (68) on the process cartridge (7) which blocks the movement of the shutter (65, 97) in either a closed or open position. Said regulating member (68) interacts with an engaging members on the developer supply cartridge (9), thereby allowing to open and close the process cartridge shutter when the cartridges (7, 9) are mounted and dismounted, respectively.

DESCRIPTION

A CLOSURE WITH INLET AND OUTLET PORTS, A VESSEL WITH INTEGRATED MIXING BALLS, AND A METHOD FOR SEPARATING MATERIAL FROM A SAMPLE

5 ELECTROPHOTOGRAPHIC IMAGE FORMING APPARATUS

[TECHNICAL FIELD]

The present invention relates to a process cartridge, a developer supply cartridge and an 10 electrophotographic image forming apparatus usable with the same.

Here, the electrophotographic image forming apparatus (hereinafter called "image forming apparatus") is an apparatus forming an image on a 15 recording material through an electrophotographic image forming process. Examples of such an apparatus include an electrophotographic copying machine, an electrophotographic printer (LED printer, laser beam printer or the like), an electrophotographic printer 20 type facsimile machine, an electrophotographic printer type word processor and the like.

Here, the recording material is a material on which an image can be formed, and includes a recording sheet, an OHP sheet or the like.

25

[BACKGROUND ART]

In the field of the image forming apparatus, a

process cartridge type is known in which an electrophotographic photosensitive member and process means actable on the electrophotographic photosensitive member are unified into a cartridge 5 which is detachably mountable to the main assembly of the image forming apparatus. With such a process cartridge type, the maintenance of the apparatus can be carried out by the user without relying on a service person. For this reason, the operability is 10 improved.

A process cartridge which can be supplied with a developer from a developer supply cartridge is also known. Such a supply type process cartridge is advantageous in that process cartridge can be 15 downsized. This is because the developer accommodating portion thereof can be downsized.

In such a developer supply type, the developer supply cartridge is provided with a developer supply opening. Correspondingly, the process cartridge is 20 provided with a developer receiving opening. The developer is supplied from the developer supply cartridge to the process cartridge with the developer supply opening and the developer receiving opening being aligned with each other.

25 It is necessary to prevent the developer from leaking, when the user mounts the process cartridge into the main assembly of the apparatus or

when the user dismounts the process cartridge from the main assembly of the apparatus.

In addition, the developer leakage has also to be prevented, when the user mounts the developer

5 supply cartridge to the main assembly of the apparatus or when the user dismounts the developer supply cartridge from the main assembly of the apparatus.

From the foregoing, the developer supply opening and the developer receiving opening are

10 provided with opening and closing shutters, respectively.

As for the structure for opening and closing the developer supply opening, the following is known.

A force reception engaging portion for engagement with
15 the process cartridge is provided so that discharge opening shutter moves from a close position to an open position when the developer supply cartridge is mounted to the main assembly of the apparatus. In addition, a force is received from the process
20 cartridge to move the discharge opening shutter from the open position to the close position when the developer supply cartridge is removed from the main assembly of the apparatus. By doing so, the developer supply opening is opened and closed (US Patent. No. 25 7010250).

On the other hand, as for the system for opening and closing a developer receiving opening of

the process cartridge, the following is known. The main assembly of the apparatus is provided with an engaging portion which applies a force to the receiving port shutter to move it in interrelation with process cartridge mounting and demounting operation relative to the main assembly of the apparatus. In this manner, the developer receiving opening is opened and closed (US Patent. No. 7010250).

With such a structure, the developer supply opening can be opened and closed in either of the cases of mounting and demounting the developer supply cartridge relative to the main assembly of the image forming apparatus and mounting and demounting the process cartridge relative to the main assembly of the image forming apparatus.

Therefore, the developer supply opening can be opened and closed even when the developer supply cartridge or the process cartridge is mounted or demounted relative to the image forming apparatus, independently from each other.

It is realized in the developer supply type process cartridge that developer supply cartridge and the process cartridge can be mounted and mounted relative to the main assembly of the image forming apparatus independent from each other, without leakage of the developer.

For this reason, this technique is advantageous.

The present invention provides further development.

[DISCLOSURE OF THE INVENTION]

5 Accordingly, it is a principal object of the present invention to provide a developer supply cartridge, a process cartridge and an electrophotographic image forming apparatus wherein when the developer supply cartridge is removed from
10 the main assembly of the apparatus in a state that both of the process cartridge and the developer supply cartridge are set in the main assembly of the electrophotographic image forming apparatus, the leakage of the developer through a developer supply opening or through the developer receiving opening can
15 be prevented.

It is another object of the present invention to provide a developer supply cartridge, a process cartridge and an electrophotographic image forming apparatus wherein when the process cartridge is removed from the main assembly of the apparatus in a state that both of the process cartridge and the developer supply cartridge are set in the main assembly of the electrophotographic image forming apparatus, the leakage of the developer through a developer supply opening or through the developer receiving opening can be prevented.

It is a further object of the present invention to provide a developer supply cartridge, a process cartridge and an electrophotographic image forming apparatus wherein when the developer supply cartridge

5 enters the main assembly of the apparatus in a state that process cartridge is set in the main assembly of the apparatus, the developer can be supplied through the developer supply opening under the condition that developer receiving opening is capable of receiving

10 the developer.

It is a further object of the present invention to provide a developer supply cartridge, a process cartridge and an electrophotographic image forming apparatus wherein when the process cartridge enters

15 the main assembly of the apparatus in a state that developer supply cartridge is set in the main assembly of the apparatus, the developer can be supplied through the developer supply opening under the condition that developer receiving opening is capable

20 of receiving the developer.

It is a further object of the present invention to provide a developer supply cartridge, a process cartridge and an electrophotographic image forming apparatus wherein when the developer supply cartridge

25 is removed from the main assembly of the apparatus in a state that both of the process cartridge and the developer supply cartridge are set in the main

assembly of the apparatus, a supplying-side shutter can be moved from a developer-supply-permitting position to a developer-supply-preventing position under the condition that receiving-side shutter is

5 placed at a developer-reception-permitting position.

It is a further object of the present invention to provide a process cartridge, a developer supply cartridge and an electrophotographic image forming apparatus wherein when the process cartridge is

10 removed from the main assembly of the apparatus in a state that both of the process cartridge and the developer supply cartridge are set in the main assembly of the apparatus, a supplying-side shutter can be moved from a developer-supply-permitting

15 position to a developer-supply-preventing position under the condition that receiving-side shutter is placed at a developer-reception-permitting position.

It is a further object of the present invention to provide a developer supply cartridge, a process cartridge and an electrophotographic image forming apparatus wherein when the developer supply cartridge enters the main assembly of the apparatus in a state that process cartridge is set in the main assembly of the apparatus, a supplying-side shutter can be moved

20 from a developer-supply-preventing position to a developer-supply-permitting position under the condition that receiving-side shutter is placed at a

25

developer-reception-permitting position.

It is a further object of the present invention to provide a process cartridge, a developer supply cartridge and an electrophotographic image forming apparatus wherein when the process cartridge enters the main assembly of the apparatus in a state that developer supply cartridge is set in the main assembly of the apparatus, a supplying-side shutter can be moved from a developer-supply-preventing position to a developer-supply-permitting position under the condition that receiving-side shutter is placed at a developer-reception-permitting position.

It is a further object of the present invention to provide a process cartridge, a developer supply cartridge and an electrophotographic image forming apparatus wherein a receiving-side movable member for interrelatedly moving a receiving-side shutter can be used for moving a supplying-side movable member.

It is a further object of the present invention to provide a process cartridge, a developer supply cartridge and an electrophotographic image forming apparatus wherein when the process cartridge enters the main assembly of the apparatus, a supplying-side shutter can be moved from a developer-supply-preventing position to a developer-supply-permitting position after a receiving-side shutter placed at a developer-reception-preventing position is moved a

developer-reception-permitting position.

It is a further object of the present invention to provide a process cartridge, a developer supply cartridge and an electrophotographic image forming apparatus wherein a developer supply opening can be opened and closed by relative movement between the developer supply cartridge and the process cartridge.

It is a further object of the present invention to provide a process cartridge and an electrophotographic image forming apparatus wherein even if the process cartridge is entered into the main assembly of the apparatus in the state that developer supply cartridge is not set in the main assembly of the image forming apparatus, a developer receiving opening is not opened.

It is a further object of the present invention to provide a developer supply cartridge and an electrophotographic image forming apparatus wherein even if a developer supply cartridge is entered into the main assembly of the apparatus in the state that process cartridge is not set in the main assembly of the image forming apparatus, a developer supply opening is not opened.

According to an aspect of the present invention, there is provided a process cartridge detachably mountable to a main assembly of an electrophotographic image forming apparatus, wherein said process

cartridge is capable of receiving a supply of a developer from a developer supply cartridge, wherein the developer supply cartridge includes a supplying-side developer accommodating portion for accommodating

5 the developer, a supplying-side shutter portion movable between a developer-supply-permitting position for opening a developer supply opening for supplying the developer from the supplying-side developer accommodating portion into the process cartridge and a

10 developer-supply-preventing position for closing the developer supply opening, a supplying-side movable portion movable to interrelatedly move the supplying-side shutter portion between the developer-supply-permitting position and the developer-supply-

15 preventing position, and an engageable member, said process cartridge comprising an electrophotographic photosensitive drum; a developing roller for developing an electrostatic latent image formed on said electrophotographic photosensitive drum with the

20 developer; a receiving-side developer accommodating portion for accommodating the developer; a developer receiving opening for receiving the developer into said receiving-side developer accommodating portion; a receiving-side shutter portion movable between a

25 developer-reception-permitting position for opening said developer receiving opening and a developer-reception-preventing position for closing said

developer receiving opening; a regulating member; and a receiving-side movable portion movable to interrelatedly move said receiving-side shutter portion between the developer-reception-permitting 5 position and the developer-reception-preventing position, said receiving-side movable portion including a first receiving-side operating portion which takes an operating position when said receiving-side shutter portion is at the developer-reception- 10 preventing position and a second receiving-side operating portion which takes the operating position when said receiving-side shutter portion is at the developer-reception-permitting position, wherein when said process cartridge enters the main assembly of the 15 apparatus with said regulating member regulating movement to place said first receiving-side operating portion at the operating position in a state that said developer supply cartridge is set in the main assembly of the apparatus, said regulating member contacts the 20 engageable member to release said receiving-side movable portion, thus permitting movement of said receiving-side movable portion, then receiving-side movable portion moves said receiving-side shutter portion to the developer-reception-permitting position 25 in interrelation with said first receiving-side operating portion moved by contacting the engageable member, and then said receiving-side movable portion

moves the supplying-side shutter portion to the developer-supply-permitting position in interrelation with the supplying-side movable portion moved by engagement of said second receiving-side operating portion with the supplying-side movable portion while being regulated by said regulating member in a state that second receiving-side operating portion is placed at the operating position.

According to another aspect of the present invention, there is provided a developer supply cartridge for supplying a developer into a process cartridge, said developer supply cartridge being detachably mountable to a main assembly of an electrophotographic image forming apparatus, wherein said process cartridge includes an electrophotographic photosensitive drum; a developing roller for developing an electrostatic latent image formed on said electrophotographic photosensitive drum; a receiving-side shutter portion movable between a developer-reception-permitting position for opening a developer receiving opening for receiving the developer to be used by said developing roller for developing operation and a developer-reception-preventing position for closing said developer receiving opening; a receiving-side movable portion movable to interrelatedly move said receiving-side shutter portion between the developer-reception-

permitting position and the developer-reception-preventing position, said receiving-side movable portion including a receiving-side operating portion which takes an operating position when said receiving-5 side shutter portion is at said developer-reception-permitting position; a regulating member for regulating movement of said receiving-side movable portion when said receiving-side operating portion is at the operating position, said developer supply 10 cartridge comprising a supplying-side developer accommodating portion for accommodating the developer; a developer supply opening for supplying the developer from said supplying-side developer accommodating portion into said process cartridge through said 15 developer receiving opening; a supplying-side shutter portion movable between a developer-supply-permitting position for opening said developer supply opening and a developer-supply-preventing position for closing said developer supply opening; and a supplying-side 20 movable portion movable, when said developer supply cartridge enters said main assembly of the apparatus in a state that process cartridge is set in said main assembly of the apparatus, to interrelatedly move said supplying-side shutter portion from said developer- 25 supply-preventing position to the developer-supply-permitting position by engagement with said receiving-side operating portion of said receiving-side movable

portion, a movement of which is regulated by said regulating member in a state that receiving-side operating portion is positioned at the operating position.

5 According to a further aspect of the present invention, there is provided an electrophotographic image forming apparatus comprising the process cartridge and the developer supply cartridge detachably mountable to the main assembly of the 10 apparatus independently from each other.

These and other objects, features and advantages of the present invention will become more apparent upon a consideration of the following description of the preferred embodiments of the 15 present invention taken in conjunction with the accompanying drawings.

[BRIEF DESCRIPTION OF THE DRAWINGS]

Figure 1 is a sectional view of a main assembly 20 of an electrophotographic type color image forming apparatus according to first embodiment of the present invention.

Figure 2 is sectional views of a process cartridge and a developer supply cartridge mountable 25 to a color image forming apparatus according to the first embodiment of the present invention (a), and an enlarged sectional view of a guide portion of the main

assembly of the apparatus (b).

Figure 3 is a perspective view of a process cartridge according to the first embodiment of the present invention.

5 Figure 4 is a perspective view of a developer supply cartridge according to the first embodiment of the present invention.

Figure 5 is a perspective view of the process cartridge and the toner developer supply cartridge, 10 illustrating a mounting style thereof into the color image forming apparatus, according to the first embodiment of the present invention.

Figure 6 is an exploded perspective view of a shutter of a developer supply cartridge and the 15 elements therearound.

Figure 7 is sectional views of a supplying-side shutter wherein (a) illustrates a state that supply opening is open, (b) illustrates a state that supply opening is closed by a supplying-side shutter, (c) 20 illustrates a state that receiving opening is opened by a receiving-side shutter, (d) illustrates a state that receiving opening is closed by the receiving-side shutter.

Figure 8 is a front view of a supplying-side 25 movable member and a supplying-side shutter, illustrating connection therebetween.

Figure 9 is an exploded perspective view of a

shutter of the process cartridge and the elements therearound.

Figure 10 is a front view of a receiving-side movable member and a receiving-side shutter, 5 illustrating connection therebetween.

Figure 11 illustrates operations of the shutter portions when the developer supply cartridge is mounted to the main assembly of the apparatus in the state that process cartridge is set in the main 10 assembly.

Figure 12 illustrates operations of a shutter portion when the process cartridge is mounted to the main assembly of the apparatus in the state that developer supply cartridge is set in the main assembly 15 of the apparatus.

Figure 13a illustrates a positioning operation for the developer supply cartridge relative to the main assembly of the apparatus with respect to the longitudinal direction.

20 Figure 13b illustrates a positioning operation for the developer supply cartridge relative to the main assembly of the apparatus with respect to the longitudinal direction.

Figure 14 is an exploded perspective view of a 25 shutter of the developer supply cartridge and the elements therearound according to a second embodiment of the present invention.

Figure 15 is an exploded perspective view of a shutter of a process cartridge and the elements therearound, according to the second embodiment of the present invention.

5 Figure 16 illustrates operations the shutter portions when the process cartridge is mounted to the main assembly of the apparatus in the state that developer supply cartridge is set in the main assembly of the apparatus, according to the second embodiment 10 of the present invention.

Figure 17 is a front view of a toner seal winding-up portion of a developer supply cartridge according to the first embodiment of the present invention.

15 Figure 18 is a front view of a toner seal winding-up portion of a process cartridge according to the first embodiment of the present invention.

Figure 19 is a perspective view of a stopper actable on a supplying-side movable member of a 20 developer supply cartridge according to a third embodiment of the present invention.

Figure 20a illustrates operations of the stopper of the developer supply cartridge and the elements therearound, according to the third 25 embodiment over the present invention.

Figure 20b illustrates operations of the stopper of the developer supply cartridge and the

elements therearound, according to the third embodiment over the present invention.

Figure 20c illustrates operations of the stopper of the developer supply cartridge and the 5 elements therearound, according to the third embodiment over the present invention.

Figure 21 is a perspective view of an outer cover of the developer supply cartridge according to the third embodiment of the present invention.

10 Figure 22a illustrates operation of the outer cover of the developer supply cartridge and the elements therearound, according to the third embodiment of the present invention.

15 Figure 22b illustrates operation of the outer cover of the developer supply cartridge and the elements therearound, according to the third embodiment of the present invention.

20 Figure 22c illustrates operation of the outer cover of the developer supply cartridge and the elements therearound, according to the third embodiment of the present invention.

25 Figure 22d illustrates operation of the outer cover of the developer supply cartridge and the elements therearound, according to the third embodiment of the present invention.

Figure 22e illustrates operation of the outer cover of the developer supply cartridge and the

elements therearound, according to the third embodiment of the present invention.

Figure 23 is a perspective view of a shutter of the developer supply cartridge and the elements therearound, according to the first embodiment of the present invention.

Figure 24 is a perspective view of a shutter of the process cartridge and the elements therearound, according to the first embodiment of the present invention.

10 invention.

Figure 25 illustrates operations of toner seal winding-up portion of the process cartridge according to the first embodiment of the present invention.

Figure 26 illustrates operations of the toner seal winding-up portion of the developer supply cartridge according to the first embodiment of the present invention.

Figure 27 is an exploded perspective view of a shutter of a developer supply cartridge and the elements therearound.

Figure 28 is an exploded perspective view of a shutter of the process cartridge and the elements therearound.

25 [BEST MODE FOR CARRYING OUT THE INVENTION]

Referring to the accompanying drawings, the preferred embodiments of the present invention will be

described.

[First embodiment]

[General arrangement of image forming apparatus]

Referring to Figure 1, the general arrangement
5 of the image forming apparatus will be described.

Figure 1 is a longitudinal sectional view illustrating
the general arrangement of a full-color laser beam
printer 100 which is an exemplary image forming
apparatus.

10 The image forming apparatus 100 comprises four
process cartridges 7 (7a, 7b, 7c, 7d) arranged in a
horizontal direction and four developer supply
cartridges 9 (9a, 9b, 9c, 9d) provided correspondingly
thereto. The process cartridges 7 and the developer
15 supply cartridges 9 are detachably mountable to the
main assembly 100a of the apparatus of the image
forming apparatus 100 independently from each other.
Here, the main assembly 100a of the apparatus means
the entirety of the image forming apparatus 100
20 without the process cartridges 7 and the developer
supply cartridges 9. The process cartridge 7 contains
an electrophotographic photosensitive drum 1 (1a, 1b,
1c, 1d). The electrophotographic photosensitive drum
(photosensitive drum) 1 is rotated by driving means
25 (unshown) provided in the main assembly 100a of the
apparatus.

The process cartridge 7 includes a charging

roller (charging means) 2 (2a, 2b, 2c, 2d), developing means 4 (4a, 4b, 4c, 4d) and cleaning means 8 (8a, 8b, 8c, 8d) which are process means provided around the photosensitive drum 1. The main assembly 100a of the

5 apparatus comprises scanner units 3 (3a, 3b, 3c, 3d) and intermediary transfer members 5, respectively such that they are around the photosensitive drum 1 when the process cartridges are mounted to the main assembly. The developed image formed on the

10 photosensitive drum 1 is transferred onto an intermediary transfer member 5 by primary transferring means 14 (14a, 14b, 14c, 14d). The primary transferring means 14 is provided in the main assembly 100a of the apparatus.

15 The charging roller 2 is urged to the photosensitive drum 1 and functions to uniformly charge the surface of the photosensitive drum 1. The scanner unit 3 projects a laser beam onto the photosensitive drum 1 to form the electrostatic latent

20 image on the photosensitive drum 1. The developing means 4 (4a-4d (4a-4d) functions to develop the electrostatic latent image with a developer into a developed image. The developing means 4 develops the electrostatic latent image. The cleaning means 8 functions to remove the residual developer remaining

25 on the surface of the photosensitive drum 1 after the toner image is transferred.

The photosensitive drum 1, and the process means including the charging roller 2, the developing means 4 and the cleaning means 8 constitute a unit, that is, a process cartridge 7.

5 The operation of image formation will be described. First, the photosensitive drum 1 is rotated in timed relation with image formation. The scanner units 3 are operated sequentially for the respective process cartridges 7. The voltage is applied to the 10 charging roller 2 rotated by the photosensitive drum 1 while being in contact thereto by which the peripheral surface of the photosensitive drum 1 is charged electrically to a uniform potential. The scanner unit 3 produces a light beam modulated in accordance with 15 the image signal, and the peripheral surface of the photosensitive drum 1 is exposed to the image light. By doing so, an electrostatic latent image is formed on the peripheral surface of the photosensitive drum 1. The electrostatic latent image is developed with a 20 developer by the developing roller 17 (17a-17d) of the developing means 4. By this, a developed image is formed on the peripheral surface of the photosensitive drum 1 by the developing roller 17. Thus, the developing roller 17 develops the electrostatic latent 25 image using the developer.

Thereafter, the primary transferring means 14 is supplied with a bias voltage of a polarity opposite

to that of the developed image. By doing so, the developed image formed on the photosensitive drum 1 is transferred onto the intermediary transfer member 5 (primary transfer).

5 The developed images (four color developed images) formed on the photosensitive drum 1 are overlaid on the intermediary transfer member 5. Thereafter, secondary transferring means 6 is press-contacted to the intermediary transfer member 5. The 10 recording material S having been stopped at a predetermined position by the registration roller 10 is delivered to a nip formed between the intermediary transfer member 5 and the secondary transferring means 6.

15 The process cartridge 7a accommodates a yellow color developer. The process cartridge 7b accommodates a magenta color developer. The process cartridge 7c accommodates a cyan color developer. The process cartridge 7d accommodates a black color developer.

20 Therefore, a yellow color developed image is formed on the photosensitive drum 1a. Similarly, a magenta color developed image is formed on the photosensitive drum 1b, a cyan color developed image is formed on the photosensitive drum 1c, and a black color developed 25 image is formed the photosensitive drum 1d.

 The process cartridges 7a, 7b, 7c and 7d have the same structures although the colors of the

contained developers are different.

The secondary transferring means 6 is supplied with a bias voltage of the polarity opposite from that of the developer. Therefore, the developed images on 5 the intermediary transfer member 5 are transferred all together onto the surface of the fed recording material S.

Thereafter, the recording material S is fed to the fixing device 11 and is fixed by heat and pressure. 10 The recording material S is discharged onto the discharging tray 13 by discharging rollers 12. In this manner, the image forming operation is completed.

The developer is consumed by the developing operation. With the consumption of the developer, the 15 developer is supplied sequentially from the developer supply cartridge 9 (9a, 9b, 9c, the) which will be described hereinafter.

The structures of the developer supply cartridges 9a, 9b the 9c and 9d are the same although 20 the colors of the contained developer are different from each other.

Designated by reference characters 100b is a process cartridge mounting portion having a space into which the process cartridge 7 is mounted dismountably.

25 Designated by 100c is a supply cartridge mounting portion having a space into which the supply cartridge 9 is mounted dismountably.

The mounting portion 100b and 100c are provided in the main assembly 100a of the apparatus.

[Entering fashions of process cartridge 7 and developer supply cartridge 9]

5 Referring to Figure 2 to Figure 5, the description will be made as to fashions of insertion of the process cartridge 7 and the developer supply cartridge 9 into the main assembly 100a of the apparatus.

10 First, the operator opens a cartridge cover 110 provided in the main assembly 100a of the apparatus (Figure 5). Then, the operator advances the process cartridge 7 into the main assembly 100a of the apparatus along the longitudinal direction of the 15 photosensitive drum 1 (direction of arrow A in the Figure). In addition, the operator advances the developer supply cartridge 9 into the main assembly 100a of the apparatus along the longitudinal direction of the supplying-side developer accommodating portion 20 33 (direction of arrow A in the Figure). Thus, the cartridges 7 and 9 are inserted in the longitudinal direction. The process cartridge 7 and the developer supply cartridge 9 receive driving forces from the main assembly 100a of the apparatus at a rear side of 25 the main assembly 100a of the apparatus (leading side with respect to the entering direction).

The developer supply cartridge 9 is carried on

main assembly rails 101a, 101b provided in the main assembly 100a of the apparatus at portions-to-be-guided 42a, 42b of the developer supply cartridge 9 (Figure 2) when the developer supply cartridge 9 is 5 inserted.

The process cartridge 7 is carried on main assembly rails 102a, 102b provided in the main assembly 100a of the apparatus at portions-to-be-guided 43a, 43b (Figure 2) of the process cartridge 7. 10 [Structure of process cartridge]

Referring to Figures 2 and 3, the structure of the process cartridge 7 will be described.

As shown in Figure 2, the process cartridge 7 comprises a cleaning unit 22 and a developing unit 23 15 which are rotatably connected with each other.

The cleaning unit 22 comprises the cleaner container 15 which is a frame rotatably supporting the photosensitive drum 1 and comprises a charging roller 2. The cleaning unit 22 further comprises cleaning 20 means 8 in the form of cleaning blade 8e and so on. The cleaning blade 8e functions to remove the developer remaining on the photosensitive drum 1.

On the other hand, in a frame including the developing means 4, a receiving-side developer 25 accommodating portion 16 (developer accommodating portion) for accommodating the developer and a developing container 18 are connected with each other

by ultrasonic welding or the like. The developing unit 23 includes the developer accommodating portion 16 and the developer container 18. The developing container 18 rotatably supports the developing roller 17. A 5 fresh (unused) process cartridge 7 contains a predetermined amount of the developer in the developer accommodating portion 16. The developer is consumed for image formation, and the developer is supplied from the developer supply cartridge 9.

10 The developing container 18 includes the developing roller 17, a developing blade 19 for regulating a layer thickness of the developer deposited on the peripheral surface of the developing roller 17, and a developer supplying roller 20 in the 15 form of a sponge roller for supplying the developer onto the developing roller 17.

The developing unit 23 is rotatable relative to the cleaning unit 22.

20 The developer supply cartridge 9 (9a-9d) is mounted above the developing unit 23 (developer accommodating portion 16) in the main assembly 100a of the apparatus in the state that process cartridge 7 (7a-7d) is mounted to the main assembly 100a of the apparatus. The developer accommodating portion 16 is 25 provided in an upper portion with a developer receiving opening 16a for receiving the developer from the supply cartridge 9. Above the receiving opening

16a, there is provided a receiving-side shutter 65 for opening and closing the receiving opening 16a. The shutter 65 opens and closes the receiving opening 16a by rotation. Thus, the shutter 65 is movable between a 5 developer-reception-permitting position for opening the receiving opening 16a for receiving the developer and a developer-reception-preventing position for closing the receiving opening 16a. An upper portion of the shutter 65 is provided with a sealing member 67, 10 made of urethane foam, felt or the like, for connecting the process cartridge 7 and the developer supply cartridge 9 with each other. The receiving opening 16a functions to receive the developer into the developer accommodating portion 16 from the supply 15 cartridge 9. The process cartridge 7 is dismountably mounted to the mounting portion 100b, and the supply cartridge 9 is dismountably mounted to the mounting portion 100c thereabove. The process cartridge 7 and the supply cartridge 9 are detachably mountable 20 relative to the main assembly 100a of the apparatus independently from each other.

The sealing member 67 functions to prevent leakage of the developer through the connecting portion between the supply cartridge 9 and the process 25 cartridge 7 when the developer is supplied from the supply cartridge 9 into the process cartridge 7. The sealing member 67 is provided to assure the prevention

of the developer leakage, and is not inevitable.

[Structure of developer supply cartridge]

Referring to Figures 2 and a, the structure of the developer supply cartridge 9 will be described.

5 The supply cartridge 9 comprises a supplying-side developer accommodating portion 33 for accommodating the developer. In the state that process cartridge 7 and the supply cartridge 9 are mounted to or set in the main assembly 100a of the apparatus, the

10 lower portion of the developer accommodating portion 33 is provided with a developer supply opening 34 which may be aligned with the receiving opening 16a. Through the receiving opening 16a and the receiving opening 16a, the developer is supplied from the inside

15 of the developer accommodating portion 33 into the process cartridge 7. More particularly, the developer is supplied into the receiving-side developer accommodating portion 16 from the process cartridge 7. Above the supply opening 34, there is provided a screw

20 38 for feeding the developer. The screw 38 is rotated by receiving the training force from the main assembly 100a. By doing so, the developer is fed to the supply opening 34. Then, the developer is fed to the receiving opening 16a from the supply opening 34.

25 The developer accommodating portion 33 is provided therein with a developer feeding members 36 (36a, 36b) for feeding the developer to the screw 38.

The shaft portion 36a it supplied with a rotational driving force by which the developer fed sheet 36b coupled with the shaft portion 36a is rotated. In this manner, the fed sheet 36b feeds the developer to the 5 screw 38.

At the lower portion of the supply opening 34, there is provided a supplying-side shutter 35 for opening and closing the opening 34. The opening 34 is opened and closed by rotation of the shutter 35. In 10 other words, the shutter 35 is capable of take a developer-supply-permitting position where the shutter 35 opens the supply opening 34 for supplying the developer into the process cartridge 7 through the receiving opening from the developer accommodating portion 33. In addition, the shutter 35 can take a 15 developer-supply-preventing position where it closes the supply opening 34. The lower surface of the developer accommodating portion 33 is provided with a first engageable member 31b extending downward. The 20 first engageable member 31b is disposed at a trailing side of the supplying-side communication opening (T container communication opening) 44a as seen in an entering direction in which the developer supply cartridge 9 enters into the main assembly 100a of the 25 apparatus. At the leading side, a second engageable member 31a is provided similarly. Thus, at the upstream side of the supply opening 34, the first

engageable member 31b is provided, and at the downstream side thereof, the second engageable member 31a is provided, with respect to the entering direction in which the supply cartridge 9 enters the 5 main assembly 100a of the apparatus.

[Shutter mechanism of developer supply cartridge]

Referring to Figure 6 to Figure 8, Figures 17, 23 and 26, the structure of a shutter mechanism of the supply cartridge 9 according to this embodiment of the 10 present invention will be described.

Figure 6 is an exploded perspective view of the shutter 35 (supplying-side shutter portion) (rotatable member) of the supply cartridge 9. Figure 7 illustrates the supplying-side shutter 35 opening the supply opening 34 (a), and the supplying-side shutter 35 closing the supply opening 34 (b). Figure 7 also illustrates the receiving-side shutter 65 opening the receiving opening 16a (c), and the receiving-side shutter 65 closing the receiving opening 16a (d).
20 Figure 8 is a front view of the supplying-side movable member (supplying-side movable portion) 32 and the shutter 35 which are coupled with each other. Figure 26 illustrates a drive structure for the winding-up portion for winding up a toner seal of the supply cartridge 9. Figure 17 is a front view of the winding-up portion. Figure 23 is a perspective view of a shutter 35 and the parts in the neighborhood of the 25

shutter 35.

A lower surface 9e of the developer accommodating portion 33 is provided with a T housing 44 fixed thereto. The T housing 44 is provided at an upper part with a T housing opening 44d and is provided at a lower part with a T container communication opening 44a. The developer in the developer accommodating portion 33 is supplied into the process cartridge 7 (developer accommodating portion 16) through the opening 44d and the communication opening 44a. Between the opening 44d and the communication opening 44a, there is provided a supplying-side shutter inserting portion 44b. The inserting portion 44b functions to rotatably support the cylindrical portion 35a of the shutter 35.

Here, the lower surface means the surface or side facing downward when the supply cartridge 9 is mounted to the main assembly 100a of the apparatus.

The shutter 35 is provided with a connecting portion 35c projecting from a lateral edge of the cylindrical portion 35a (base portion) outwardly in the axial direction of the cylindrical portion. The shutter 35 is provided with communication openings 35b through the periphery of the cylindrical portion 35a at the diametrically opposing positions, respectively. More particularly, the communication openings 35b are disposed opposed to the opening 34 and to the

communication opening 44a with respect to a direction crossing with the axial direction. The cylindrical portion 35a is fitted into the shutter inserting portion 44b such that outer surface of the cylindrical portion 35a is contacted to the inner surface of the shutter inserting portion 44b. By doing so, the shutter 35 is rotatable relative to the developer accommodating portion 33.

At the open side of the shutter inserting portion 44b, there is provided a cap 39 for the inserting portion of the supplying-side shutter. The cap 39 is provided with arm portions 39b at the opposite end portions, respectively. Each of the arm portion 39b has a hole portion 39c which is engaged with a retaining portion 44c in the form of a claw provided on the T housing 44. By doing so, the cap 39 is fixed on the T housing 44. And, the shutter 35 is prevented from disengaging from the T housing 44.

The cap 39 has an opening 39a formed therein. Through the opening 39a, a connecting portion 35c of the shutter 35 is penetrated.

To the free end of the connecting portion 35c projected from the cap 39, a supplying-side movable member (supplying-side movable portion) 32 functioning to interrelatedly move the shutter 35 is fixed. The movable member 32 has an end projection 32a which is inserted into an end recess 35c1 formed in a free end

surface of the shutter 35. The projection 32a is press-fitted into the recess 35c1. By doing so, the movable member 32 is fixed on the shutter 35. The movable member 32 is integrally rotatable with the 5 shutter 35. In other word, the shutter 35 rotates in interrelation with rotation of the movable member 32.

The movable member 32 includes projections 32 (32b1, 32b2, 32b3, 32b4) and recesses 32c (32c1, 32c2, 32c3, 32c4) which are arranged alternately (Figure 8).

10 The description will be made as to an assembling method and an operation of the shutter (supplying-side shutter portion) and the elements therearound.

First, the shutter 35 is inserted into the 15 shutter inserting portion 44b of the T housing 44. The opening of the shutter inserting portion 44b is capped by the cap 39. Then, the hole portion 39c is engaged with the retaining portion 44c of the T housing 44. By doing so, the cap 39 is fixed to the T housing 44.

20 Thereafter, the end projection 32a of the movable member 32 is press-fitted into the end recess 35c1 of the supplying-side shutter 35. Then, the T housing 44 is mounted on the developer accommodating portion 33 by screws (unshown) or the like.

25 Figure 7, (a) is a sectional view of the shutter and the elements therearound in the state that developer supply cartridge 9 and the process cartridge

7 are mounted to or set in the image forming apparatus 100.

As shown in Figure 7, (a), when the process cartridge 7 and the developer supply cartridge 9 are mounted, the supply opening 34, the opening 44d and the communication opening 44a are opposed to the supplying-side shutter communication port 35b. Therefore, the developer supply from the supply cartridge 9 into the process cartridge 7 is enabled.

10 In this state, the screw 38 (Figure 2) provided above the opening 34 and the opening 44d is rotated. By this, the developer is fed to the opening 34. Then, the developer is let fall from the supply opening 34 to the receiving opening 16a.

15 Thus, in the state shown in Figure 7, (a), the shutter 35 is in the developer-supply-permitting position for opening the opening 34.

Figure 7, (b) is a sectional view of the shutter and the elements therearound in the state that 20 one of the developer supply cartridge 9 and the process cartridge 7 is taken out of the main assembly of the image forming apparatus 100a.

In the state shown in Figure 7, (b), the shutter 35 is in the developer-supply-preventing 25 position for closing the opening 34.

In this state, a portion of the cylindrical portion 35a of the shutter 35 other than the opening

35d (portion other than the communication opening 35b) is opposed to the supply opening 34, the opening 44d and the communication opening 44a.

When the supply cartridge 9 or the process cartridge 7 is removed from the main assembly 100a of the apparatus, the supplying-side movable member 32 receives a force from the receiving-side movable member (receiving-side movable portion) 62 of the process cartridge 7, which will be described hereinafter, to move, more particularly, to rotate in this embodiment. The shutter 35 rotates by 90° from the position permitting the developer supply (Figure 7, (a)) to a position preventing the developer supply in either one of the directions indicated by arrows B and C (Figure 7, (b)). By this, the opening 44d or the communication opening 44a of the supply cartridge 9 becomes not opposed to the communication opening 35b. By doing so, the opening 44d is closed so that supply of the developer into the process cartridge 7 is stopped.

In other words, the opening and closing operations of the shutter of the supply cartridge 9 are carried out by rotating the shutter 35 by 90°.

Between the developer accommodating portion 33 and the T housing 44, there is provided a T toner seal 120 (Figure 17). One longitudinal end 120a of the toner seal 120 is fixed to the supply opening 34 to

seal the supply opening 34. The other end 120b of the T toner seal 120 is fixed to a circular column portion 121a of a winding-up shaft 121. The winding-up shaft 121 is provided with a driving force receiving portion 121b which is rotatable integrally with the circular column portion 121a.

The driving force receiving portion 121b comprises a T driving force receiving coupling 152 for receiving a driving force from a main assembly 10 151 coupling provided in the main assembly 100a of the apparatus, when the supply cartridge 9 is mounted to the main assembly 100a of the apparatus. It receives the driving force from a gear portion 152a of the coupling 152 through a gear train including idler 15 gears 153, 154 Figure 26.

Here, in the case that supply cartridge 9 is a fresh one (not used), the supply opening 34 may be sealed by the toner seal 120. When the supply opening 34 is sealed by the toner seal 120, the winding-up 20 shaft 121 receives a driving force from the main assembly through the driving force receiving portion 121b to rotate in the direction of arrow D, in the state that supply cartridge 9 is set in the main assembly 100a of the apparatus (Figure 17).

25 By doing so, the winding-up shaft 121 winds the toner seal 120 up to open the supply opening 34. In the case that supply cartridge 9 is removed from the

main assembly 100a of the apparatus after the toner seal 120 is removed, the supply opening 34 is sealed by the shutter 35.

The discrimination whether or not the supply 5 cartridge 9 is a fresh one, is carried out by the main assembly 100a of the apparatus recognizing information stored in memory (unshown) provided in the supply cartridge 9.

In this embodiment, the developer supply 10 cartridge 9 is provided with the supplying-side shutter 35. For this reason, it is not always necessary to employ the toner seal, and the developer leakage through the supply opening 34 can still be prevented. However, with the above-described structure 15 having the toner seal, the leakage of the developer can be prevented assuredly during, for example, transportation of the developer supply cartridge.

In this embodiment, the supplying-side shutter 35 and the supplying-side movable member 32 are 20 unintegral or separate members. In an alternative structure, however, the cap 39 is not used, and as shown in Figure 27, the supplying-side shutter (supplying-side shutter portion) 95 is provided with disengagement prevention portion 95e of snap fit type, 25 for example. By doing so, the shutter 95 is engaged with the hole 96e of the T housing 96 so that disengagement can be prevented. Therefore, the shutter

95 and the supplying-side movable portion 95f may be one integral structure.

The supplying-side shutter 95 of the Figure 27 example corresponds to the above-described supplying-side shutter 35, and the T housing 96 corresponds to the T housing 44, and in addition, the supplying-side movable portion 95f corresponds to the supplying-side movable member 32. The communication opening 95b corresponds to the communication opening 35b, and non-opening portion 95d corresponds to the non-opening portion 35d. The T container communication opening 96a corresponds to the T container communication opening 44a, and the supplying-side shutter inserting portion 96b corresponds to the supplying-side shutter inserting portion 44b, and in addition, the T housing opening 96d corresponds to the T housing opening 44d.

The supply cartridge 9 further includes the following structures.

More particularly, it comprises a first engageable member 31b fixed at a position upstream of the supply opening 34 (supplying-side movable member 32) with respect to the advancing direction in which the supply cartridge 9 enters the main assembly 100a of the apparatus. In the case that supply cartridge 9 enters the main assembly 100a of the apparatus, the first engageable member 31b moves the regulating member 68 which will be described hereinafter, prior

to the shutter 35 opening the supply opening 34. By this, it releases the regulating operation of the regulating member 68. This enables movement of the receiving-side movable member 62. Subsequently, it is 5 brought into engagement with first receiving-side operating portions 62b1, 62b3 of the movable member 62 to rotate the movable member 62. This moves the receiving-side shutter 65 from the developer-reception-preventing position to the developer-reception-permitting position. 10

In addition, the developer supply cartridge 9 comprises a second engageable member 31a fixed at a position upstream of the supply opening 34 (supplying-side movable member 32) with respect to a dismounting 15 direction in which the developer supply cartridge 9 is removed from the main assembly of the apparatus 100. In the case that supply cartridge 9 is removed from the main assembly of the apparatus 100, the second engageable member 31a is brought into contact to the 20 regulating member 68 to move (rotate) the regulating member 68 after the shutter 35 closes the supply opening 34. By this, it releases the regulating operation of the regulating member 68. Thus, it permits the movement of the movable member 62. 25 Subsequently, it engages with a receiving-side operating portion provided at a position different from that of the receiving-side operating portion of

the receiving-side movable member 62. By this, the shutter 65 is moved from the developer-reception-permitting position to the developer-reception-preventing position.

5 In the state that supply cartridge 9 is mounted to the main assembly 100a of the apparatus, the supplying-side movable member 32 extends in a direction perpendicular to the bottom side (lower surface) 9e of the supply cartridge 9. The movable 10 member 32 is rotatable about a horizontal axis parallel with the lower surface 9e.

The supplying-side shutter 35 is in the form of a rotatable cylindrical which is rotatable about a horizontal axis parallel with the lower surface 9e of 15 the supply cartridge 9.

The cylindrical opening, extending along the longitudinal direction of the cylindrical shape, of the supplying-side shutter 35 opposes the developer supply opening 34. By doing so, the developer supply 20 opening 34 is opened. The portion of the cylindrical other than the cylindrical opening closes the supply opening 34 by opposing the receiving opening 16a.

The supplying-side movable member 32 comprises a supplying-side operating portion in the form of 25 projections (32b1, 32b2, 32b3, 32b4) which are engaged with projections 62b1, 62b3 (first receiving-side operating portion) and bifurcated projections 62b2,

62b4 (second receiving-side operating portion) to receive rotating forces. By doing so, the supplying-side shutter 35 is rotated.

[Shutter mechanism of process cartridge]

5 Referring to Figures 9, 10, 18, 24 and 25, the shutter mechanism of the process cartridge 7 of this embodiment will be described.

Figure 9 is an exploded perspective view of the shutter of the process cartridge 7 and the elements therearound. Figure 10 is a front view illustrating a state of connection between the receiving-side movable member 62 and the receiving-side shutter 65 (receiving-side shutter portion) (rotatable member). Figure 18 is a front view of the winding-up portion for winding the toner seal of the process cartridge. Figure 24 is a perspective view of the shutter of the process cartridge 7 and the elements therearound. Figure 25 illustrates a driving structure for the winding-up portion.

20 As shown in Figure 9, the shutter mechanism of the process cartridge 7 has the structures similar to those of the shutter mechanism of the supply cartridge 9. The developing-device housing 45 corresponds to the T housing 44. The developing-device housing opening 45d corresponds to the T housing opening 44d. The developing container communication opening 45a corresponds to the T container communication opening

44a. The development shutter inserting portion 45b corresponds to the supplying-side shutter inserting portion 44b. The receiving-side shutter 65 corresponds to the supplying-side shutter 35. The cylindrical portion 65a corresponds to the cylindrical portion 35a; the connecting portion 65c corresponds to the connecting portion 35c; the communication opening (opening) 65b corresponds to the communication opening 35b; and non-opening portion 65d corresponds to the 10 non-opening portion 35d. The cap 69 corresponds to the cap 39; the arm portion 69b corresponds to the arm portion 39b; the hole portion 69c corresponds to the hole portion 39c; the opening 69a corresponds to the opening 39a; and the end recess 65c1 corresponds to 15 the end recess 35c1. In view of these correspondences, the description of the corresponding portions of the process cartridge will be omitted for simplicity.

The description will be made as to the receiving-side movable member 62.

20 As shown in Figure 10, a movable member 62 fixed to a free end of the shutter 65 functions to move the shutter 65. In other word, the shutter 65 is interrelated with the movement (rotation) of the movable member 62. The movable member 62 is provided 25 with projections 62b (62b1, 62b2, 62b3, 62b4) and recesses 62c (62c1, 62c2, 62c3, 62c4) to apply a rotating force to the supply cartridge 9 with the

mounting and demounting operations of the process cartridge 7 relative to the main assembly 100a of the apparatus. The projection 62b is arranged along rotational moving direction of the movable member 62.

- 5 The projection 62b2 is provided at the center portion thereof with a recess 62d1 so that it constitutes a bifurcated projection. In addition, the projection 62b4 is provided at the center portion thereof with a recess 62d2 so that it constitutes a bifurcated
- 10 projection. The projections 62b2, 62b4 are engageable with the projections 32b (32b1, 32b2, 32b3, 32b4) of the movable member 32. The projections 62b1 - 62b4 constitute a receiving-side operating portion. More particularly, the projections 62b1, 62b3 constitute a
- 15 first receiving-side operating portion, and the projections 62b2, 62b4 constitute a second receiving-side operating portion. The recesses 62d1, 62d2 are provided to prevent the interference between the projection 32b and the projections 62b2, 62b4.
- 20 Referring to Figure 10, the parts of the projection 62b2 and 62b4 are enclosed by chain lines.

The developer accommodating portion 16 is further provided with a regulating member 68 for regulating rotation of the movable member 62. The 25 regulating member 68 is made slidabile in the vertical direction (direction of arrow E) by claw portions 71a, 72a of the slide rails 71, 72 provided in the

developer accommodating portion 16. The regulating member 68 is normally urged in a upward direction by a spring force (elastic force) of a compression spring 70 provided between the developer accommodating portion 16 and the regulating member 68. As shown in Figure 10, when the regulating member 68 is at the home position (regulation position), the regulation recess 68a is sequentially engageable with the projections 62b (62b1, 62b2, 62b3, 62b4) of the movable member 62. By doing so, the rotation of the movable member 62 is regulated. In other word, by the engagement between the projection 62b and the recess 68a, the rotation of the movable member 62 is regulated or prevented.

15 The topmost surface of the housing 45 is provided with a sealing member 67 having an opening 67a corresponding to the communication opening 45a.

20 The assembling method and operation of the shutter of the process cartridge 7 and the elements therearound will be described.

First, the shutter 65 is inserted into the shutter inserting portion 45b of the housing 45. The opening of the shutter inserting portion 45b is capped with the cap 69. Then, the hole portion 69c of the cap 25 69 is engaged with a retaining portion 45c of the housing 45. In this manner, the shutter 65 is fixed to the housing 45. Then, the end projection 62a of the

movable member 62 is press-fitted into the end recess 65c1 of the shutter 65. The regulating member 68 is engaged with the claw portions 71a, 72a of the slide rail 71, 72 on the outside of the developer

5 accommodating portion 16. Thereafter, the spring 70 is mounted between the regulating member 68 and the developer accommodating portion 16. Subsequently, the sealing member 67 is mounted to the communication opening 45a side of the housing 45. The developing-
10 device housing 45 is fixed to the developer accommodating portion 16 by screws (unshown) or the like.

The shutter 65 opens and closes similarly to the above-described shutter 35. With each 90° rotation
15 of the receiving-side shutter 65, the process cartridge 7 alternately becomes capable of developer reception from the developer supply cartridge 9 (developer-reception-permitting position, Figure 7, (c)) and becomes incapable of developer reception a
20 (developer-reception-preventing position, 7, (d)).

Thus, the receiving opening 16a is opened and closed by the rotation of the shutter 65 in interrelation with the 90° rotation of the receiving-side movable member 62.

25 Between the developer accommodating portion 16 and the developing-device housing 45, there is provided a D toner seal 130 (Figure 18). One

longitudinal end 130a of the D toner seal 130 is fixed to the developer accommodating portion 16 and seals the receiving opening 16a. The other end of the D toner seal 130 is fixed to the circular column portion 5 131a of the winding-up shaft 131. There is further provided a rotatable driving force receiving portion 131b which is rotatable integrally with the circular column portion 131a.

As shown in Figure 25, in the state that 10 process cartridge 7 is mounted in the main assembly 100a of the apparatus, the development driving force reception coupling 156 receives the driving force from the main assembly coupling 155, for the developing operation, provided in the main assembly of the 15 apparatus 100. The driving force receiving portion 131b receives the driving force through the gear train including idler gears 157, 158, 159 from the gear portion 156a of the coupling 156.

In this embodiment, when the process cartridge 20 7 is a fresh one (unused), the receiving opening 16a may be sealed by the above-described toner seal 130. In the case that receiving opening 16a is sealed by the toner seal 130, when the process cartridge 7 is set in the main assembly 100a of the apparatus, the 25 winding-up shaft 131 receives the driving force from the main assembly through the driving force receiving portion 131b.

Whether the process cartridge 7 is a fresh one or not is discriminated by the main assembly 100a of the apparatus detecting information stored in memory (unshown) provided in the process cartridge 7.

5 Then, the winding-up shaft 131 winds the toner seal 130 up to opening the receiving opening 16a. When the process cartridge 7 is removed from the main assembly 100a of the apparatus, the receiving opening 16a is sealed by the shutter 65.

10 The process cartridge is also provided with the receiving-side shutter 65 similarly to the developer supply cartridge. For this reason, the leakage of the developer from the developer receiving opening 16a can be prevented sufficiently even if the toner seal is 15 not employed. However, with the structure employing the above-described toner seal, the possible developer leakage during transportation of the process cartridge can be prevented assuredly.

15 In this embodiment, the receiving-side shutter 65 and the receiving-side movable member 62 are unintegral or separate members. However, in an alternative structure, as shown in Figure 28, the cap 69 is not used, but the receiving-side shutter (receiving-side shutter portion) 97 is provided with a 20 disengagement prevention portion 97e such as snap fit is provided, and the shutter 97 is engaged with a hole 98e of the developing-device housing 98 to prevent the 25

disengagement. By doing so, the shutter 97 and the receiving-side movable portion 97f may be made integral.

In Figure 28, the shutter 97 corresponds to the 5 above-described shutter 65; the movable member 97f corresponds to the movable member 62; and the developing-device housing 98 corresponds to the developing-device housing 45. The communication opening 97b corresponds to the communication opening 65b; and the non-opening portion 97d corresponds to the non-opening portion 65d. The developing container communication opening 98a corresponds to the developing container communication opening 45a; the development shutter inserting portion 98b corresponds 10 to the development shutter inserting portion 45b; and the developing-device housing opening 98d corresponds to the developing-device housing opening 45d. Therefore, the detailed description of these elements will be omitted for the sake of simplicity.

15 20 [Driving structure for the shutter portion]

Referring to Figures 11 and 12, the description will be made as to opening and closing operations of the shutter 35 and the shutter 65 during the mounting and demounting operations of the supply cartridge 9 25 and the process cartridge 7.

(In the case that developer supply cartridge is mounted)

Referring to Figure 11, the description will be made as to the case that supply cartridge 9 is mounted to the main assembly 100a of the apparatus in a state that process cartridge 7 is already set in the main assembly 100a of the apparatus. For the simplicity of illustration, the developer accommodating portion 33 and the developer accommodating portion 16 are omitted in Figure 11. The shutter 44, the communication opening 45b, the shutter 65, the communication opening 65b, the engaging portion 31a1 of the second engageable member 31a and the engaging portion 31b1 of the first engageable member 31b, are indicated by broken lines.

Before the supply cartridge 9 is mounted to the main assembly 100a of the apparatus, the opening 44d and communication opening 44a of the T housing are positioned such that they are not opposed to the communication opening 35b of the supplying-side shutter 35 (the state shown in (b) in Figure 7) (developer-reception-preventing position). Therefore, the supply of the developer into the process cartridge 7 is prevented (closed state).

When the process cartridge 7 is mounted to the main assembly 100a of the apparatus in the state that supply cartridge 9 is not mounted to the main assembly 100a of the apparatus, the movable member 62 receives no force from anywhere. Therefore, the shutter 65 does

not rotate. For this reason, the process cartridge 7 remains in the closed state in which the developer reception is prevented.

The regulation recess 68a of the regulating member 68 and the projections 62b (62b1 or 62b3) of the movable member 62 are in engagement with each other. Therefore, the movable member 62 is kept regulated (the rotation (movement) is prevented).

The operator inserts the supply cartridge 9 into the main assembly 100a of the apparatus while the portions-to-be-guided 42a, 42b set on the main assembly rails 101a, 101b (in the direction indicated by an arrow A in (k) of Figure 11).

When the supply cartridge 9 is advanced to the position shown in (j) of Figure 11, the engaging portion 31a1 of the second engageable member 31a is brought into contact to the inclined surface portion 68b1 of the guide surface 68b of the regulating member 68.

With further advancement of the supply cartridge 9, as shown in (i) of Figure 11, the inclined surface portion 68b1 is moved by the first engageable member 31a1. Therefore, the regulating member 68 having been urged to the upper regulation position by the elastic force of the urging spring 70, is moved downwardly against the elastic force toward the developer accommodating portion 16 in the

direction indicated by an arrow H in (i) of Figure 11 (movement-permitting position (rotation-permitting position)).

When the engaging portion 31a1 of the supply 5 cartridge 9 reaches the flat surface portion 68b2 of the guide surface 68b, the engagement between the regulation recess 68a of the regulating member 68 and a projection 62b (62b1 or 62b3 in Figure 10) is released. By this, the movable member 62 becomes 10 rotatable ((h) of Figure 11).

Thereafter, the engaging portion 31a1 slides on the flat surface portion 68b2 of the regulating member 68. And, the engaging portion 31a1 is engaged with the projection 62b (62b1 or 62b3) of the movable member 62 15 to rotate the movable member 62 in the couterclockwise direction ((g) of Figure 11). With the rotation of the movable member 62, the receiving-side shutter 65 fixed thereto is also rotated in the couterclockwise direction together with the movable member 62. By this, 20 the communication opening 65b of the shutter 65 is communicated with the developing-device housing opening 45d and the communication opening 45a. More particularly, the shutter 65 is now placed in the developer-reception-permitting position ((c) of Figure 25 7). The recess 62c (62c1 or 62c3 in Figure 10) is provided to receive the engaging portion 31a1 when the engaging portion 31a1 is engaged with the projection

62b (62b1 or 62b3).

When the supply cartridge 9 is advanced to the position where the engagement between the engaging portion 31a1 and the movable member 62 is released, 5 the shutter 65 is completely rotated through 90°. Then, the rotation of the shutter 65 stops. At this time, the communication opening 65b takes such a position as to oppose to the receiving opening 16a ((c) of Figure 7). Therefore, the opening state is reached in which 10 the developer reception from the supply cartridge 9 is enabled ((f) of Figure 11).

As shown in (e) - (d) of Figure 11, when the supply cartridge 9 is further advanced into the main assembly 100a of the apparatus, the inclined surface portion 68b3 is guided by the engaging portion 31a1. 15 Therefore, the regulating member 68 moves upwardly toward the regulation position (in the direction of an arrow G in (e) of Figure 11) relative to the developer accommodating portion 16 by the elastic force (spring 20 force) of the spring 70.

The engaging portion 31a1 of the supply cartridge 9 is disengaged from the inclined surface portion 68b3 of the guide surface 68b. The projection 62b (62b2 or 62b4 in Figure 10) is brought into 25 engagement with the regulation recess 68a of the regulating member 68. The movable member 62 restores the regulated position where the rotation is prevented

((c) of Figure 11).

The supply cartridge 9 is further advanced into the main assembly 100a of the apparatus. By this, the bifurcated projection 62b (62b2 or 62b4 in Figure 10) 5 of the movable member 62 is engaged with the projection 32b (32b1 or 32b3 of Figure 8) and the recess 32c (32c1 or 32c3 of Figure 8) of the movable member 32. At this time, the rotation of the movable member 62 is regulated or prevented by the regulating member 68. Therefore, the movable member 32 rotates in 10 the counterclockwise (direction of arrow I in (c) of Figure 11) by the force received from the movable member 62 with the entering movement of the supply cartridge 9. With the rotation of the movable member 15 32, the shutter 35 fixed thereto also rotates in the counterclockwise. The communication opening 35b of the supplying-side shutter 35 is brought into fluid communication (the developer can flow therethrough) with the housing opening 44d and the communication opening 44a ((c) - (b) of Figure 11). In other word, 20 the shutter 35 of the supply cartridge 9 is now in the developer-supply-permitting position.

The structure and operation of the process cartridge 7 and supply cartridge 9 are summarized as 25 follows. Also, the positioning structure relative to the main assembly 100a will be described.

The process cartridge 7 and the supply

cartridge 9 are detachably mountable to the main assembly 100a of the apparatus independently from each other.

The process cartridge 7 includes the

5 photosensitive drum 1 and the developing roller 17 for developing the electrostatic latent image formed on the photosensitive drum 1 with the developer. The process cartridge 7 includes the receiving-side shutter 65 movable between the developer-reception-

10 permitting position for opening the developer receiving opening 16a for receiving the developer and the developer-reception-preventing position for closing the receiving opening 16a. The process cartridge 7 includes the receiving-side movable member

15 62 which is movable in interrelation with the shutter 65 and which includes receiving-side operating portions 62b2 and 62b4 which are placed at the operating position when the shutter 65 is at the developer-reception-permitting position. The process

20 cartridge 7 includes the regulating member 68 for regulating the movement of the movable member 62 when the operating portion 62b2 or 62b4 is at the operating position ((e) of Figure 11). Here, the operating position is the position where the operating portion

25 62b2 or 62b4 is in engagement with the projection 32b of the supplying-side movable member 32, and the supplying-side movable member 32 is moved (rotated) by

the relative movement between the supplying-side movable member 32 and the receiving-side movable member 62. In this embodiment, the operating portion 62b2 or 62b4 is at the topmost position in the 5 operating position ((a) - (e)).

The supply cartridge 9 includes the supplying-side developer accommodating portion 33 for accommodating the developer. The supply cartridge 9 includes the T housing opening 44d for supplying the 10 developer from the developer accommodating portion 33 into the process cartridge 7 through the receiving opening 16a, and the supplying-side shutter 35 is movable between the toner-supply-permitting position where the T housing opening 44d and the communication opening 44a are in communicating relation with each 15 other and the developer-supply-preventing position for closing the T housing opening 44d and the communication opening 44a. The developer supply cartridge 9 includes the movable member 32 having the 20 projection 32b which is engageable with the operating portion 62b2 in the state of being regulated at the operating position. When the supply cartridge 9 advances into the main assembly 100a of the apparatus, the movable member 32 moves interrelatedly the shutter 25 35 from the toner-supply-preventing position to the toner-supply-permitting position by the operating portion 62b2 or 62b4 engages with the projection 32b

((d) - (a) of Figure 11).

When the supply cartridge 9 further advances into the main assembly 100a of the apparatus, the portion-to-be-positioned 40 of the supply cartridge 9 5 abuts the main assembly supporting shaft 103 provided in the main assembly 100a of the apparatus ((b) of Figure 13). The portion-to-be-positioned 40 is provided on the leading side end surface of the supply cartridge 9 with respect to the entering direction of 10 the supply cartridge 9 into the main assembly 100a of the apparatus. At this position, the 90°rotating operation of the shutter 35 is completed, so that mounting of the supply cartridge 9 to the main assembly 100a of the apparatus is completed. At this 15 time, the rotation of the supplying-side shutter 65 stops. And, the communication opening 65b is at such a position that it opposes the T housing opening 45d and the communication opening 45a ((c) of Figure 7) (developer-supply-permitting position). In the 20 developer supply opening 34 is now in the opening state, and the developer can be supplied into the process cartridge 7 ((a) of Figure 11).

When the cartridge 9 enters the main assembly 100a of the apparatus in a state that process 25 cartridge 7 is set in the main assembly 100a of the apparatus, the operations of the receiving-side movable member 62, the receiving-side shutter 65 and

the regulating member 68 are as follows.

The movable member 62 functions to interrelatedly move the shutter 65 between the developer-reception-permitting position and the

5 developer-reception-preventing position. The movable member 62 includes the receiving-side operating portion (second receiving-side operating portion) (bifurcated projections 62b2 and 62b4) which is at the operating position when the shutter 65 is placed at 10 the developer-reception-permitting position. The regulating member 68 regulates the movement (rotation) of the movable member 62 in the state that said receiving-side operating portion is at the operating position.

15 As described in the foregoing, the movable member 32 of the cartridge 9 has the following structures. When the cartridge 9 enters the main assembly 100a of the apparatus, the movable member 32 is moved (rotated) by engaging with the receiving-side 20 operating portion (projection 62b2, 62b4) of the movable member 62 regulated or confined by the regulating member 68 placed at the operating position. The movable member 32 interrelatedly moves the shutter 35 from the developer-supply-preventing position to 25 the developer-supply-permitting position. By doing so, the shutter 35 opens the supply opening 34.

Here, in this embodiment, the receiving-side

operating portion which is placed at operating position when the shutter 65 is placed at the developer-reception-permitting position. The movable member 32 is moved by the engagement with the 5 receiving-side operating portion (projection 62b2, 62b4) to move the shutter 35 from the developer-supply-preventing position to the developer-supply-permitting position. Therefore, when the supply cartridge 9 enters the main assembly 100a of the 10 apparatus, the supply opening 34 opens only when the shutter 65 is placed at the developer-reception-permitting position, that is, only when the receiving opening 16a is open. For this reason, it can be avoided that supply opening 34 opens despite the 15 receiving opening 16a is closed. Thus, the leakage of the developer from the supply opening 34 can be prevented.

According to this embodiment, when the supply cartridge 9 enters the main assembly 100a of the 20 apparatus, the supply opening 34 never opens unless the process cartridge 7 is mounted to the main assembly 100a of the apparatus.

As described in the foregoing, the supply cartridge 9 is advanced into the main assembly 100a of 25 the apparatus while being carried on the main assembly rails (main assembly side guide) 101a, 101b at the portions-to-be-guided 42a, 42b. It is desirable that

force required for the insertion is small while the positioning of the supply cartridge 9 is assured. From this standpoint, there is provided a clearance which is large at the clearance between the main assembly 5 supporting shaft 103 and the portion-to-be-positioned 40.

The portion-to-be-guided 42b which is closer to the movable member 32 as seen in the cross-sectional direction (left side with respect to the direction in 10 which the view of Figure 2 is seen) is guided. In order to accomplish this, the main assembly rail 101b functions to regulate a vertical deviation and a leftward deviation of the supply cartridge 9. The main assembly rail 101a regulates downward and rightward 15 deviations of the developer supply cartridge 9.

The supply cartridge 9 and the main assembly rail 101 will be described in detail. As shown in (b) of Figure 2, the portion-to-be-guided 42b includes a side portion-to-be-regulated 42b3, an upper side 20 portion-to-be-regulated 42b1 and a lower portion-to-be-regulated 42b2. When the developer supply cartridge 9 advances into the main assembly 100a of the apparatus, the portion-to-be-regulated 42b3, the portion-to-be-regulated 42b1 and the portion-to-be-regulated 42b2 are regulated by the main assembly rail 101b provided the main assembly 100a of the apparatus. The portion-to-be-regulated 42b1 is prevented from

upward movement by an upper surface regulating portion 101b1 of the main assembly rail 101b. The lower portion-to-be-regulated 42b2 is regulated in the downward movement by the lower surface regulating portion 101b2 of the main assembly rail 101b.

Similarly, the side portion-to-be-regulated 42b3 is regulated in the lateral movement by the side surface regulating portion 101b3 of the main assembly rail 101b. When the movable member 32 moves while being in engagement with the movable member 62, the portion-to-be-regulated 42b1 is prevented from upward movement by the regulating portion 101b1. Therefore, the movable member 32 can be moved with assured engagement with the movable member 62. For this reason, the opening and closing operations of the supplying-side shutter 35 and the receiving-side shutter 65 are assured.

Here, the portion-to-be-guided 42b is set so as to be guided by the main assembly rail 101b at least during the operations of the supplying-side shutter 35, the receiving-side shutter 65 and the regulating member 68, shown in (k) - (a) of Figure 11.

Therefore, as shown in (k) - (a), during the operations of the shutter members (35, 65) and the regulating member 68, the portion-to-be-guided 42b of the developer supply cartridge 9 is guided by the main assembly rail 101b with respect to the direction of the view of Figure 2 (cross-sectional direction). Thus,

the relative positional relation between the developer supply cartridge 9 and the process cartridge 7 can be maintained with respect to the cross-sectional direction.

5 (In the case that developer supply cartridge is removed)

When the supply cartridge 9 is dismounted from the main assembly 100a of the apparatus in the state that process cartridge 7 and the developer supply 10 cartridge 9 are set in the main assembly 100a of the apparatus, the operations are the opposite from those described above. More particularly, the operations are in the order of (a) - (b) - (c) - (d) - (e) - (f) - (g) - (h) - (i) - (j) - (k). Through these steps, the 15 supplying-side movable member 32, the supplying-side shutter 35, the regulating member 68, the receiving-side movable member 62, and the receiving-side shutter 65 operate.

The supply cartridge 9 includes the developer 20 accommodating portion 33 for accommodating the developer. The supply cartridge 9 includes the supplying-side shutter 35 movable between the developer-supply-permitting position for opening the developer supply opening 34 for supplying the developer from the developer accommodating portion 33 25 into the process cartridge 7 through the developer receiving opening 16a and the developer-supply-

2 preventing position for closing the developer supply opening 34. The developer supply cartridge 9 includes the supplying-side movable member 32 (supplying-side movable portion) having the projection 32b engageable
5 with the operating portion 62b2 or 62b4 which is regulated or confined to be at the operating position. The movable member 32 is moved (rotated) by the engagement of the operating portion 62b2 with the projection 32b with the movement of the supply
10 cartridge 9 to remove from the main assembly 100a of the apparatus, to interrelatedly move the supplying-side shutter 35 from the developer-supply-permitting position to the developer-supply-preventing position ((a) - (e) in Figure 11).

15 Therefore, after the supply cartridge 9 is removed, the shutter 65 of the process cartridge 7 remaining set in the main assembly 100a of the apparatus is interrelatedly closed by the dismounting operation of the supply cartridge 9 from the main
20 assembly 100a of the apparatus.

For this reason, even if the process cartridge 7 is removed in the state that supply cartridge 9 is not mounted to the main assembly 100a of the apparatus, the shutter 65 of the receiving opening 16a of the
25 process cartridge 7 keeps closed. Thus, even if only the supply cartridge 9 is removed from the main assembly 100a of the apparatus in the state that both

of the process cartridge 7 and the supply cartridge 9 are set in the main assembly 100a of the apparatus, the opening 16a of the shutter 65 is kept closed assuredly.

5 When the supply cartridge 9 is removed from the main assembly 100a of the apparatus in the state that process cartridge 7 is set in the main assembly 100a of the apparatus, the operations of the movable member 62, the shutter 65 and the regulating member 68 will 10 be described.

First, the movable member 62 is movable to interrelatedly move the receiving-side shutter 65 between the developer-reception-permitting position and the developer-reception-preventing position. The 15 movable member 62 includes the receiving-side operating portion (second receiving-side operating portion) (projections 62b2 and 62b4) which is at the operating position when the shutter 65 is placed at the developer-reception-permitting position. The 20 regulating member 68 regulates the movement of the movable member 62 when the operating portion (projection 62b2 or 62b4) is at the operating position.

As described hereinbefore, when the supply cartridge 9 is removed from the main assembly 100a of 25 the apparatus, the movable member 32 of the supply cartridge 9 is moved by the engagement with the receiving-side operating portion (projection 62b2 or

62b4) of the movable member 62 which is regulated or confined at the operating position by the regulating member 68. And, the movable member 32 interrelatedly moves the shutter 35 from the developer-supply-
5 permitting position to the developer-supply-preventing position.

In this manner, according to this embodiment of the present invention, when the supply cartridge 9 is removed from the main assembly 100a of the apparatus,
10 the movable member 32 is moved (rotated) by the engagement with the receiving-side operating portion (second receiving-side operating portion) (projection 62b2 or 62b4) of the movable member 62 which is regulated or confined at the operating position by the regulating member 68. Therefore, according to this embodiment, when the supply cartridge 9 is removed from the main assembly 100a of the apparatus, the receiving opening 16a is closed after the supply opening 34 is closed. Thus, when the supply cartridge
15 9 is removed from the main assembly 100a of the apparatus, it would not happen that supply opening 34 is closed after the receiving opening 16a is closed. Therefore, the possible leakage of the developer through the supply opening 34 can be prevented. In the
20 case that supply cartridge 9 is mounted to the main assembly 100a of the apparatus or is dismounted from the main assembly 100a of the apparatus in the state
25

that process cartridge 7 is set in the main assembly 100a of the apparatus, the operations of the movable member 62, the shutter 65 and the regulating member 68 are as follows.

5 First, the movable member 62 includes the first receiving-side operating portion 62b1 or 62b3 which is at the operating position when the shutter 65 takes the developer-reception-preventing position, the second receiving-side operating portion 62b2 or 62b4 which is at the operating position when the receiving-side shutter 65 takes the developer-reception-permitting position.

10 The regulating member 68 regulates the rotation of the movable member 62 when the first operating portion 62b1 or 62b3 or second operating portion 62b2 or 62b4 is placed at the operating position.

15 In the case that supply cartridge 9 is mounted to the main assembly 100a of the apparatus or is dismounted from the main assembly 100a of the apparatus in the state that process cartridge 7 is set in the main assembly 100a of the apparatus, the operations of the engageable member (second engageable member) 31a, the supplying-side movable member 32 and the supplying-side shutter 35 are as follows:

20 First, when the supply cartridge 9 enters the main assembly 100a of the apparatus, the engageable member (second engageable member) 31a is brought into

contact to the regulating member 68 which regulates the rotation of the movable member 62 by the first operating portion 62b1 or 62b3 placed at the operating position prior to the supply shutter 35 opening the 5 supply opening 34. The engageable member 31a moves the regulating member 68 downwardly against the elastic force of the spring 70. By this, it releases the regulating operation of the regulating member 68. Thus, the engageable member 31a permits movement of the 10 movable member 62. Subsequently, the engageable member 32a is engaged with the first operating portion 62b1 or 62b3 to rotate the movable member 62, in interrelation with which the shutter 65 is moved from the developer-reception-preventing position to the 15 developer-reception-permitting position. That is, the receiving opening 16a is opened.

In addition, when the supply cartridge 9 is removed from the main assembly 100a of the apparatus, the engageable member 31a is brought into contact to 20 the regulating member 68 which regulates (prevents) the rotation of the movable member 62 by the second receiving-side operating portion 62b2 or 62b4 placed at the operating position and moves the regulating member 68 downwardly against the elastic force, after 25 the supplying-side shutter 35 closes the supply opening 34. By this, it releases the regulating operation of the regulating member 68. Thus, the

engageable member 31a permits movement of the movable member 62.

Then, the engageable member 32a rotates the shutter 35 from the developer-reception-permitting 5 position to the developer-reception-preventing position in interrelation with rotation of the movable member 62 caused by engaging with the second operating portion 62b2 or 62b4. That is, the receiving opening 16a disclosed.

10 Here, the engageable member (second engageable member) 31a is disposed fixedly at a position downstream of the supply opening 34 (supplying-side movable member 32) with respect to the direction in which the supply cartridge 9 enters the main assembly 15 100a of the apparatus.

When the supply cartridge 9 enters the main assembly 100a of the apparatus, the movable member 32 rotates by engagement with the movable member 62 which is regulated by the regulating member 68 confining the 20 second operating portion 62b2 or 62b4 at the operating position, after the receiving-side shutter 65 opens the receiving opening 16a. The supplying-side movable member 32 moves the supplying-side shutter 35 from the developer-supply-preventing position to the developer- 25 supply-permitting position in interrelation with the rotation thereof. That is, the supply opening 34 is opened.

When the supply cartridge 9 is removed from the main assembly 100a of the apparatus, and movable member 32 rotates by the engagement with the movable member 62 which is regulated by the regulating member 68 confining the second receiving-side operating portion 62b2 or 62b4 at the operating position, prior to the receiving-side shutter 65 closing the receiving opening 16a. The movable member 32 moves the supplying-side shutter 35 from the developer-supply-permitting position to the developer-supply-preventing position in interrelation with the rotation thereof. That is, the supply opening 34 is closed.

According to this embodiment, when the supply cartridge 9 is mounted to or dismounted from the main assembly 100a of the apparatus in the state that process cartridge 7 is set in the main assembly 100a of the apparatus, the leakage of the developer through the supply opening 34 is prevented. The advantageous effects of the foregoing embodiments can be provided.

(In the case that process cartridge is mounted to main assembly of the apparatus)

The description will be made as to the case that process cartridge 7 is mounted to the main assembly 100a of the apparatus in the state that supply cartridge 9 is set in the main assembly 100a of the apparatus.

Before the process cartridge 7 is mounted to

the main assembly 100a of the apparatus, the housing opening 45d of the process cartridge 7 and the communication opening 45a are not opposed to the communication opening 65b ((d) of Figure 7). That is, 5 the shutter 35 takes the developer-supply-preventing position. Therefore, the receiving opening 16a is closed by the shutter 35, in which state the developer cannot be received from the supply cartridge 9. The regulation recess 68a of the regulating member 68 is 10 in engagement with the projection 62b (62b1 or 62b3) of the movable member 62. Therefore, the rotation (movement) of the movable member 62 is regulated or prevented.

Even when the supply cartridge 9 is mounted to 15 the main assembly 100a of the apparatus in the state that process cartridge 7 is out of the main assembly 100a of the apparatus, the movable member 32 does not receive any force. Therefore, the shutter 65 does not rotate. The supply opening 34 is closed, and in the 20 state, the developer supply to the process cartridge 7 is not possible. That is, the shutter 35 is kept at the developer-supply-preventing position.

First, as described hereinbefore, the portions-to-be-guided 43a 43b are placed on the main assembly 25 rails 102a, 102b, and the process cartridge 7 is advanced into the main assembly 100a of the apparatus in the direction indicated by an arrow A in (k) of

Figure 12).

When the process cartridge 7 is advanced to the position shown by (j) in Figure 12, the engaging portion 31b1 of the first engageable member 31b of the 5 supply cartridge 9 is contacted to the inclined surface portion 68b3 of the guide surface 68b of the regulating member 68.

With further advancement of the process cartridge 7, the inclined surface portion 68b3 is 10 guided by the engaging portion 31b1 as shown in (i) of Figure 12. Therefore, the regulating member 68 having been urged to the upper regulation position by the elastic force of the spring 70 is moved downwardly 15 against the elastic force (spring force) toward the permitting position provided at a lower part where the developer accommodating portion 16 is provided (in the direction indicated by an arrow H in (i) of Figure 12).

When the engaging portion 31b1 of the supply cartridge 9 reaches the flat surface portion 68b2 of 20 the guide surface 68b, the engagement between the regulation recess 68a of the regulating member 68 and the projection 62b (62b1 or 62b3 in Figure 10) is released. By this, the movable member 62 becomes rotatable ((h) of Figure 12).

25 Thereafter, the engaging portion 31b1 slides on the flat surface portion 68b2 of the regulating member 68 to engage with the projection 62b (62b1 or 62b3) of

the movable member 62, by which the movable member 62 is rotated in the clockwise direction ((g) of Figure 12). With the rotation of the movable member 62, the shutter 65 fixed thereto also rotates in the clockwise direction. And, the communication opening 65b of the shutter 65 is opposed to and communicated with the housing opening 45d and the communication opening 45a. The recess 62c (62c1 or 62c3 in Figure 10) is provided to receive the engaging portion 31a1 when the engaging portion 31a1 is engaged with the projection 62b (62b1 or 62b3).

When the process cartridge 7 is advanced to such a position that engagement between the engaging portion 31b1 and the movable member 62 is released, the shutter 65 has been rotated by 90°. Then, the rotation of the shutter 65 stops. At this time, the communication opening 65b is opposed to the housing opening 45d and the communication opening 45a (developer-supply-permitting position). Here, the shutter 65 of the process cartridge 7 opens so that process cartridge 7 is capable of receiving the developer from the supply cartridge 9 ((f) of Figure 12).

As shown in (e) - (d) of Figure 12, when the process cartridge 7 is further advanced into the main assembly 100a of the apparatus, the inclined surface portion 68b1 is guided by the engaging portion 31b1.

Therefore, the regulating member 68 is moved to the upper regulation position (in the direction indicated by an arrow in (e) of Figure 12) by the elastic force (spring force) of the spring 70.

5 When the engaging portion 31b1 of the supply cartridge 9 departs from the inclined surface portion 68b1 of the guide surface 68b, the projection 62b (62b2 or 62b4) in Figure 10 is engaged with the regulation recess 68a of the regulating member 68. The 10 movable member 62 restores the regulated position where the rotation is prevented ((d) of Figure 12).

The process cartridge 7 is further advanced into the main assembly 100a of the apparatus. Then, the projection 62b (62b2 or 62b4 Figure 10 in) of the 15 movable member 62 is engaged with the projection 32b (32b1 or 32b3 in Figure 8) and the recess 32c (32c2 or 32c4 in Figure 8) of the movable member 32. At this time, the rotation of the movable member 62 is regulated or prevented by the regulating member 68. 20 Therefore, the movable member 32 receives the force from the movable member 62 to rotate in the clockwise direction (arrow J in (c) of Figure 12). With the rotation of the movable member 32, the shutter 35 fixed thereto also rotates in the clockwise direction. 25 Then, the communication opening 35b of the shutter 35 is opposed to the T housing opening 44d and the communication opening 44a ((c) - (b)).

And, the portion-to-be-positioned of the process cartridge 7 is abutted to the main assembly supporting shaft (unshown) provided in the main assembly 100a of the apparatus. By doing so, the 90° 5 rotation the shutter 35 is completed. Thus, the mounting operation of the process cartridge 7 to the main assembly 100a of the apparatus is completed. At this time, the rotation of the shutter 35 stops. The communication opening 35b is now positioned to oppose 10 the housing T opening 44d and the communication opening 44a ((a) of Figure 7). The supply opening 34 is also opened, and therefore, the developer supply to the process cartridge 7 is permitted ((a) of Figure 12).

15 Here, the process cartridge 7 includes the receiving-side movable member 62 which will be described below.

The movable member 62 includes the first receiving-side operating portion (projection) 62b3, 20 62b1 which are placed at the operating position when the receiving-side shutter 65 is placed at the developer-supply-preventing position, and the second receiving-side operating portion (projection) 62b2, 62b4 which are placed at the operating position when 25 the receiving-side shutter 65 is placed at the developer-supply-permitting position. The movable member 62 moves the shutter 65 interrelatedly. The

movement of the movable member 62 is regulated by the regulating member 68 with the first operating portion 62b3, 62b1 placed at the first operating position. The movable member 62 moves downwardly by the regulating member 68 contacting the first engageable member 31b, when the process cartridge 7 enters the main assembly 100a of the apparatus. By doing so, the movable member 62 is released from the regulating member 68 to become movable (rotatable). Then, movable member 62 moves interrelatedly the receiving-side shutter 65 to the developer-supply-permitting position by the movement thereof caused by the first operating portion 62b3, 62b1 contacting the first engageable member 31b. The movement of the movable member 62 is regulated or confined by the regulating member 68 with the second operating portion 62b2, 62b4 placed at the operating position. The movable member 62 moves the receiving-side shutter 65 to the developer-supply-permitting position in interrelation with the movement (rotation) of the supplying-side movable member 32 caused by engagement of the second operating portion 62b2 62b4 with the supplying-side movable member 32.

In the case that process cartridge 7 is mounted to the main assembly 100a of the apparatus in the state that supply cartridge 9 is set in the main assembly 100a of the apparatus, the operations of the first engageable member 31b and the movable member 32

of the supply cartridge 9 all as follows.

First, when the process cartridge 7 enters the main assembly 100a of the apparatus, the first engageable member 31b is brought into contact to the 5 regulating member 68 which regulates or confines the movement of the movable member 62 in the state that shutter 65 is at the developer-supply-preventing position. And, the regulating member 68 is moved downwardly. By doing so, the movable member 62 10 releases the regulating action of the regulating member 68. By this, the movable member 62 becomes movable (rotatable). Subsequently, the first engageable member 31b moves the receiving-side shutter 65 to the permitting position in interrelation with 15 the movement (rotation) of the movable member 62 caused by contacting to the first engageable member 31b.

The movable member 32 is engaged with the operating portion 62b2, 62b4 of the movable member 62 20 regulated or confined at the operating position. When the process cartridge 7 advances into the main assembly 100a of the apparatus, the movable member 32 moves the shutter 35 from the developer-supply-preventing position to the developer-supply-permitting 25 position.

In the case that process cartridge 7 enters the main assembly 100a of the apparatus in the state that

supply cartridge 9 is set in the main assembly 100a of the apparatus, the operations of the receiving-side movable member 62 and the regulating member 68 are as follows.

5 First, the movable member 62 includes the first receiving-side operating portion 62b1 or 62b3 placed at the operating position with the shutter 65 placed at the developer-reception-preventing position, and the second receiving-side operating portion 62b2 or 10 62b4 placed at the operating position with the shutter 65 placed at the developer-reception-permitting position.

The regulating member 68 regulates or prevents the movement (the rotation) of the movable member 62 15 when the first receiving-side operating portion 62b1 or 62b3 is placed at the operating position, or when the second receiving-side operating portion 62b2 or 62b4 is placed at the operating position.

When the process cartridge 7 enters the main 20 assembly 100a of the apparatus, the regulating member 68 is contacted to the engageable member (first engageable member) 31b to release the movable member 62 from the regulating member 68, so that movable member 62 becomes movable (rotatable). The shutter 65 25 is moved to the developer-reception-permitting position in interrelation with the movement (rotation) of the first operating portion 62b1 or 62b3 caused by

the contact by the engageable member 31b. Subsequently, the movement of the movable member 62 is again regulated by the regulating member 68 when the second operating portion 62b2 or 62b4 is placed at the 5 operating position. And, the second operating portion 62b2 or 62b4 is engaged with the movable member 32 to move (rotate) it, and the supplying-side shutter 35 is moved to the developer-supply-permitting position in interrelation with the movement (rotation) of the 10 movable member 32. That is, the supply opening 34 is opened.

In the case that process cartridge 7 enters the main assembly 100a of the apparatus in the state that supply cartridge 9 is set in the main assembly 100a of 15 the apparatus, the operations of the engageable member (first engageable member) 31b, the supplying-side movable member 32 and the supplying-side shutter 35 are as follows.

When the process cartridge 7 enters the main 20 assembly 100a of the apparatus, the engageable member (first engageable member) 31b is contacted to the regulating member 68 which regulates the movement of the movable member 62 with the first operating portion 62b1 or 62b3 placed at the operating position. Thus, 25 the movable member 62 is released from the regulating member 68. Thus, it permits the movement of the movable member 62. The engageable member 31b is

contacted to the first operating portion 62b1 or 62b3 to move the movable member 32, in interrelation with which the shutter 65 is moved to the developer-reception-permitting position. In this manner, the 5 receiving opening 16a is opened.

When the process cartridge 7 enters the main assembly 100a of the apparatus, the supplying-side movable member 32 is moved (rotated) by engagement with the second receiving-side operating portion 62b2 or 62b4 of the movable member 62 which is regulated or confined by the regulating member 68 placed at the 10 operating position, after the engageable member 31b moves the shutter 65 to the developer-reception-permitting position. The movable member 32 moves 15 (rotates) interrelatedly the shutter 35 from the developer-supply-preventing position to the developer-supply-permitting position. By doing so, the supply opening 34 is opened.

In this manner, in this embodiment of the 20 present invention, when the process cartridge 7 enters the main assembly 100a of the apparatus, the first operating portion 62b1 62b3 is contacted to the engageable member 31b to move (rotate), in interrelation with which the shutter 65 is moved to 25 the developer-reception-permitting position.

Subsequently, the second operating portion 62b2 or 62b4 is brought into engagement with the movable

member 32. In accordance with the advancement of the process cartridge 7, the movable member 32 moves (rotates), in interrelation with which the shutter 35 is moved to the developer-supply-permitting position.

5 That is, the supply opening 34 is opened.

Therefore, according to this embodiment, when the process cartridge 7 enters the main assembly 100a of the apparatus, the supply opening 34 is opened only after the receiving opening 16a is opened. Therefore, 10 the supply opening 34 never opens in the state that receiving opening 16a is closed. Thus, according to this embodiment, when the process cartridge 7 enters the main assembly 100a of the apparatus, the leakage of the developer through the supply opening 34 can be 15 avoided.

In addition, according to this embodiment, when the process cartridge 7 enters the main assembly 100a of the apparatus, the receiving opening 16a is not opened unless the supply cartridge 9 is mounted to the 20 main assembly 100a of the apparatus. In this manner, the receiving opening 16a will never be opened in the state that supply cartridge 9 is not mounted to the main assembly 100a of the apparatus.

(In the case that process cartridge is removed from 25 main assembly of apparatus)

When the process cartridge 7 is removed from the main assembly 100a of the apparatus in the state

that process cartridge 7 and the developer supply cartridge 9 are set in the main assembly 100a of the apparatus, the operations are opposite. That is, referring to Figure 12, the order of operations is (a) 5 - (b) - (c) - (d) - (e) - (f) - (g) - (h) - (i) - (j) - (k). The movable member 32, the supplying-side shutter 35, the regulating member 68, the movable member 62 and the receiving-side shutter 65 are operated in this order.

10 As described in the foregoing, the process cartridge 7 detachably mountable to the main assembly 100a of the apparatus includes the receiving-side shutter 65. The shutter 65 is movable between the developer-reception-permitting position for opening 15 the receiving opening 16a for receiving the developer to be used by the developing roller 17 for development and the developer-reception-preventing position for closing the developer receiving opening 16a.

Furthermore, the shutter 65 is provided with 20 the receiving-side movable member 62 which is rotatable in interrelation with the shutter 65 so that shutter 65 is movable between the developer-reception-permitting position and the developer-reception-preventing position. The movable member 62 includes 25 the receiving-side operating portion 62b2 or 62b4 which is placed at the operating position when the shutter 65 is placed at the developer-reception-

permitting position. The movable member 62 further includes the regulating member 68 for regulating the movement of the movable member 62 when it is placed at the operating position.

5 The developer supply cartridge 9 which is detachably mountable to the main assembly of the apparatus to supply the developer to the process cartridge 7 includes the developer accommodating portion 16 for accommodating the developer. The
10 developer supply cartridge 9 further includes the supplying-side shutter 35. The shutter 35 is movable between the developer-supply-permitting position for opening the supply opening 34 for supplying the developer into the process cartridge through the
15 receiving opening 16a from the developer accommodating portion 16 and the developer-supply-preventing position for closing the supply opening 34.
Furthermore, it includes the engageable member (first engageable member) 31b. The first engageable member
20 31b is contacted to the regulating member 68 which regulates or confines the movement (rotation) of the movable member 62 with the shutter 65 placed at the developer-reception-preventing position, when the process cartridge 7 enters the main assembly of the
25 apparatus 100. By releasing the movable member 62 from the regulating member 68, the movement of the movable member 62 is enabled. Subsequently, the first

engageable member 31b is contacted to the movable member 62 to move the movable member 62, in interrelation with which the shutter 65 is moved to the description developer-reception-permitting

5 position. Furthermore, the developer supply cartridge includes the supplying-side movable member 32. When the process cartridge 7 enters the main assembly of the apparatus 100, the movable member 32 is moved (rotated) by engagement with the operating portion 62b2 or 62b4 of the movable member 62 which is regulated or confined by the regulating member 68 having the operating portion 62b4 or 62b2 placed at the operating position. The movable member 32 moves interrelatedly the supplying-side shutter 35 from the 10 developer-supply-preventing position to the developer-supply-permitting position.

15

The receiving-side movable member 62 is constructed as follows.

The movable member 62 includes the operating portion (projection) 62b2, 62b4 which is placed at the operating position when the shutter 65 is placed at the developer-reception-permitting position. The movable member 62 moves the shutter 65 interrelatedly.

20 The movable member 62 is regulated or prevented from movement by the regulating member 68 placed at the operating position, where the operating portion 62b2 is engaged with the projection 32b. By this, when the

process cartridge 7 is removed from the main assembly 100a of the apparatus, the movable member 62 is moved to move the shutter 35 to the developer-supply-preventing position. Subsequently, the movable member 5 62 becomes movable (rotatable) by the regulating member 68 contacting to the first engageable member 31b. The movable member 62 is moved by the operating portion (projection) 62b2, 62b4 contacting to the first engageable member 31b and is moved thereby, in 10 interrelation with which the shutter 65 is moved to the developer-reception-preventing position.

Therefore, after the process cartridge 7 is removed from the main assembly 100a of the apparatus, the supplying-side shutter 35 of the supply cartridge 15 9 which remains in the main assembly 100a of the apparatus is closed automatically by the dismounting operation of the process cartridge 7 from the main assembly 100a of the apparatus.

In the case that process cartridge 7 is removed 20 from the main assembly 100a of the apparatus in the state that supply cartridge 9 is set in the main assembly 100a of the apparatus, the operations of the receiving-side movable member 62, the receiving-side shutter 65 and the regulating member 68 are as follows.

25 First, the receiving-side movable member 62 includes the receiving-side operating portion 62b2, 62b4 which is placed at the operating position with

the shutter 65 placed at the developer-reception-permitting position. The movable member 62 functions to interrelatedly move the shutter 65 between the developer-reception-permitting position and the developer-reception-preventing position. When the process cartridge 7 is removed from the main assembly 100a of the apparatus, the receiving-side operating portion 62b2, 62b4 of the movable member 62 which is regulated or confined by the regulating member 68 5 placed at the operating position, is engaged with the supplying-side movable member 32 thereby to move (rotate) the movable member 32. The movable member 32 moves interrelatedly the supplying-side shutter 35 to the developer-supply-preventing position. That is, the supply opening 34 is closed. Subsequently, the movable member 62 is released from the regulating member 68 by the regulating member 68 contacting to the engageable member (first engageable member) 35b. The movable member 62 becomes movable thereby. Then, movable 10 member 62 is moved by the contact of the receiving-side operating portion 62b2, 62b4 to the engageable member (first engageable member) 35b, in the relation with which the shutter 65 is moved to the developer-reception-preventing position. That is, the receiving 15 opening 16a is closed. In the case that process cartridge 7 is removed from the main assembly 100a of the apparatus in the state that supply cartridge 9 is 20 25

set in the main assembly 100a of the apparatus, the operations of the supplying-side movable member 32 and the supplying-side shutter 35 are as follows.

First, when the process cartridge 7 is removed
5 from the main assembly 100a of the apparatus, the movable member 32 is moved (rotated) by the engagement with the operating portion 62b2, 62b4 of the movable member 62 which is regulated or confined by the regulating member 68 with the shutter 65 placed at the
10 developer-reception-permitting position. The movable member 32 moves (rotates) interrelatedly the shutter 35 from the developer-supply-permitting position to the developer-supply-preventing position. That is, the supply opening 34 is closed.

15 Here, according to this embodiment of the present invention, when the process cartridge 7 is removed from the main assembly 100a of the apparatus, the receiving-side operating portion 62b2, 62b4 is engaged with the movable member 32 thereby to move
20 (rotate) the movable member 32. The movable member 32 moves interrelatedly the shutter 35 to the developer-supply-preventing position. Subsequently, the movable member 62 is moved by the operating portion 62b2, 62b4 contact to the engageable member (first engageable member) 31b, in interrelation with which the shutter 65 is moved to the developer-reception-preventing
25 position. That is, the receiving opening 16a is closed.

Therefore, according to this embodiment, when process cartridge 7 is removed from the main assembly 100a of the apparatus, the receiving opening 16a is closed only after the supply opening 34 is closed.

5 Accordingly, with this embodiment of the present invention, the receiving opening 16a is never closed in the state that supply opening 34 is open.

Thus, according to this embodiment, the leakage of the developer can be prevented, when the process 10 cartridge 7 is removed from the main assembly 100a of the apparatus.

The description will be made as to the case that supply cartridge 9 is mounted to or dismounted from the main assembly 100a of the apparatus in the 15 state that process cartridge 7 is set in the main assembly of the apparatus and as to the case that process cartridge 7 is mounted to or dismounted from the main assembly 100a of the apparatus in the state that supply cartridge 9 is set in the main assembly of 20 the apparatus.

The operations of the receiving-side movable member 62, the receiving-side shutter 65 and the regulating member 68 of the process cartridge 7 are the same as with the case in that supply cartridge 9 25 is mounted to or dismounted from the main assembly 100a of the apparatus in the state that process cartridge 7 is set in the main assembly 100a of the

apparatus.

First, the first engageable member (engageable member) 31b, the second engageable member (engageable member) 32b and the supplying-side movable member 32
5 are as follows.

First, the first engageable member (engageable member) 31b will be described.

When the process cartridge enters the main assembly of the apparatus, the first engageable member
10 31b is contacted to the regulating member 68 which regulates or confines the rotation of the movable member 62 with the first receiving-side operating portion 62b1 or 62b3 placed at the operating position, prior to the shutter 35 opening the supply opening 34.
15 The first engageable member 31b moves the regulating member 68 downwardly against the elastic force of the spring 70. By doing so, the movable member 62 is released from the regulating member 68. By this, the movable member 62 becomes movable. Subsequently, the
20 first engageable member 31b is engaged with the first operating portion 62b1 or 62b3 thereby to rotate the movable member 62, in interrelation with which the shutter 65 is moved from the developer-reception-preventing position to the developer-reception-permitting position. That is, the receiving opening
25 16a is opened.

When the process cartridge 7 is removed from

the main assembly 100a of the apparatus, the first engageable member 31b is brought into contact to the regulating member 68 which regulates or confines the rotation of the movable member 62 with the second

5 receiving-side operating portion 62b2 or 62b4 placed at the operating position. The first engageable member 31b moves the regulating member 68 downwardly against the elastic force of the spring 70 to release the movable member 62 from the regulating member 68. Thus,

10 it permits the movement of the movable member 62. The first engageable member 31b is engaged with the second receiving-side operating portion 62b2 or 62b4 thereby to rotate the movable member 62, in interrelation with which the shutter 65 is rotated from the developer-

15 reception-permitting position to the developer-reception-preventing position. That is, the receiving opening 16a is closed.

Here, the first engageable member 31b is fixed at a position upstream of the supply opening 16a

20 (supplying-side movable member 32) the entering direction in which the supply cartridge 9 enters the main assembly 100a of the apparatus.

The description will be made as to the second engageable member 31a.

25 When the supply cartridge 9 enters the main assembly 100a of the apparatus, the second engageable member 31a is brought into contact to the regulating

member 68 which regulates or confines the rotation of the movable member 62 with the first receiving-side operating portion 62b1 or 62b3 placed at the operating position, prior to the shutter 35 opening the supply opening 34. The second engageable member 31a moves the regulating member 68 downwardly against the elastic force to release the movable member 62 from the regulating member 68. By doing so the second engageable member 31b makes the receiving-side movable member 62 movable. Then, the second engageable member 31b is engaged with the first operating portion 62b1 or 62b3 to rotate the movable member 62, in interrelation with which the shutter 65 is moved from the developer-reception-preventing position to the developer-reception-permitting position, namely, the receiving opening 16a is opened.

When the supply cartridge 9 is removed from the main assembly 100a of the apparatus, the second engageable member 31a is brought into contact to the regulating member 68 which regulates or confines the rotation of the movable member 62 with the second operating portion 62b2 or 62b4 placed at the operating position, after the shutter 35 closes the supply opening 34. The second engageable member 31a moves the movable member 62 downwardly against the elastic force of the spring 70. By this, it releases the regulating operation of the regulating member 68. Thus, it

permits the movement of the movable member 62.

Subsequently, the second engageable member 31a is engaged with the second operating portion 62b2 or 62b4 to rotate the movable member 62, in interrelation with 5 which the shutter 65 is rotated from the developer-reception-permitting position to the developer-reception-preventing position. That is, the receiving opening 16a is closed.

Here, the second engageable member 31a is fixed 10 at the position downstream of the supply opening 34 (supplying-side movable member 32) with respect to the entering direction in which the supply cartridge enters the main assembly of the apparatus.

The description will be made as to the 15 supplying-side movable member 32.

First, when the process cartridge 7 enters the main assembly 100a of the apparatus, the movable member 32 is rotated by engagement with the movable member 62 which is regulated by the regulating member 20 68, more particularly which is prevented from rotating by the second operating portion 62b2 or 62b4 confined at the operating position, after the first engageable member 31b causes the shutter 65 to open the receiving opening 16a. The movable member 32 moves 25 interrelatedly the shutter 35 from the developer-supply-preventing position to the developer-supply-permitting position. That is, the supply opening 34 is

opened.

In addition, the movable member 32 is rotated by engagement with the movable member 62 which is regulated by the regulating member 68, more particularly, which is prevented from rotating by the second operating portion 62b2 or 62b4 confined at the operating position, prior to the first engageable member 31b causes the shutter 65 to close the receiving opening 16a, when the process cartridge 7 is removed from the main assembly 100a of the apparatus.

The movable member 32 moves interrelatedly the shutter 35 from the developer-supply-permitting position to the developer-supply-preventing position. That is, the supply opening 34 is closed.

In addition, when the supply cartridge 9 enters the main assembly 100a of the apparatus, the movable member 32 is rotated by engagement with the movable member 62 which is regulated by the regulating member 68, more particularly, which is prevented from rotating by the second operating portion 62b2 or 62b4 confined at the operating position, after the second engageable member 31a causes the shutter 65 to open the receiving opening 16a. The movable member 32 moves interrelatedly the shutter 35 from the developer-supply-preventing position to the developer-supply-permitting position. That is, the supply opening 34 is opened.

In addition, when the supply cartridge 9 is removed from the main assembly 100a of the apparatus, the movable member 32 is rotated by engagement with the movable member 62 which is regulated the 5 regulating member 68, more particularly, which is prevented from rotating by the second operating portion 62b2 or 62b4 confined at the operating position. The movable member 32 moves interrelatedly the shutter 35 from the developer-supply-permitting 10 position to the developer-supply-preventing position. That is, the supply opening 34 is closed.

The description will be made as to the case that supply cartridge 9 enters the main assembly 100a of the apparatus in the state that process cartridge 7 is set in the main assembly of the apparatus and as to the case that process cartridge 7 enters the main 15 assembly 100a of the apparatus in the state that supply cartridge 9 is set in the main assembly of the apparatus.

20 The description will be made as to the structures and operations of the receiving-side movable member 62 and the regulating member 68 of the process cartridge 7.

The movable member 62 is rotated in 25 interrelation with the shutter 65 such that shutter 65 is movable between the developer-reception-permitting position and the developer-reception-preventing

position. The movable member 62 includes the first receiving-side operating portion 62b1 or 62b3 which is placed at the operating position when the shutter 65 takes the developer-reception-preventing position, and 5 the second receiving-side operating portion 62b2 or 62b4 which is placed at the operating position when the shutter 65 takes the developer-reception-permitting position.

The regulating member 68 regulates the rotation 10 of the movable member 62 when the first operating portion 62b1 or 62b3 or second operating portion 62b2 or 62b4 is placed at the operating position.

The description will be made as to the structures and operations of the first engageable 15 member 31b, the second engageable member 31a and the supplying-side movable member 32 of the supply cartridge 9.

When the process cartridge 7 enters the main assembly 100a of the apparatus, the first engageable 20 member 31b is brought into contact to the regulating member 68 which regulates the movable member 32, more particularly, which prevents the movable member 32 from rotating by the first operating portion 62b1 or 62b3 confined at the operating position, prior to the 25 shutter 35 opening the supply opening 34. The first engageable member 31b moves the regulating member 68 downwardly against the elastic force of the spring 70.

By this, it releases the regulating operation of the regulating member 68. Thus, it permits the movement of the movable member 62. Subsequently, the first engageable member 31b is engaged with the first

5 operating portion 62b1 or 62b3 to rotate the movable member 32, in interrelation with which the shutter 65 is rotated from the developer-reception-preventing position to the developer-reception-permitting position. That is, the receiving opening 16a is opened.

10 When the supply cartridge 9 enters the main assembly 100a of the apparatus, the second engageable member 31a is brought into contact to the regulating member 68 which regulates the movable member 62, more particularly, which prevents the movable member 62 from rotating by the first operating portion 62b1 or 62b3 confined at the operating position, prior to the shutter 35 opening the supply opening 34. The second engageable member 31a moves the regulating member 68 downwardly against the elastic force. By this, it

15 releases the regulating operation of the regulating member 68. Thus, it permits the movement of the movable member 62. The second engageable member 31a is engaged with the first operating portion 62b1 or 62b3 to rotate the movable member 62, in interrelation with

20 which the shutter 65 is rotated from the developer-reception-preventing position to the developer-reception-permitting position. That is, the receiving

25

opening 16a is opened.

When the process cartridge 7 enters the main assembly 100a of the apparatus, the supplying-side movable portion 32 is rotated by engagement with the 5 movable member 62 which is confined by the regulating member 68, more particularly, which is prevented from rotating by the second operating portion 62b2 or 62b4 confined at the operating position, after the first engageable member 31b causes the shutter 65 to open 10 the receiving opening 16a. The supplying-side movable portion 32 rotates interrelatedly the shutter 35 from the developer-supply-preventing position to the developer-supply-permitting position. That is, the supply opening 34 is opened.

15 Therefore, according to this embodiment of the present invention, the same advantageous effects as with the foregoing embodiments are provided.

The description will be made as to the structures and operations in the case that supply 20 cartridge 9 is removed from the main assembly 100a of the apparatus, or the process cartridge 7 is removed therefrom in a state that process cartridge 7 and the supply cartridge 9 are set in the main assembly 100a of the apparatus.

25 The structures of the receiving-side movable member 62 and the regulating member 68 of the process cartridge 7 are the same as those of the foregoing

embodiments.

The description will be made as to the structures and operations of the first engageable member 31b, the second engageable member 31a and the 5 supplying-side movable member 32 of the supply cartridge 9.

When the process cartridge 7 is removed from the main assembly 100a of the apparatus, the first engageable member 31b is brought into contact to the 10 regulating member 68 which regulates the movable member 62, more particularly, which is prevented from rotating by the second operating portion 62b2 or 62b4 confined at the operating position, after the shutter 35 closes the supply opening 34. The first engageable 15 member 31b moves the regulating member 68 downwardly against the elastic force. By doing so, the first engageable member 31b releases the movable member 62 from the regulating member 68. Thus, it permits the movement of the movable member 62. Subsequently, the 20 first engageable member 31b is engaged with the second operating portion 62b2 or 62b4 to rotate the movable member 62, in interrelation with which the shutter 65 is rotated from the developer-reception-permitting position to the developer-reception-preventing 25 position. That is, the receiving opening 16a is closed.

When the supply cartridge 9 is removed from the main assembly 100a of the apparatus, the second

engageable member 31a is brought into contact to the regulating member 68 which regulates the movable member 62, more particularly, which prevents the movable member 62 from rotating by the second

5 operating portion 62b2 or 62b4 confined at the operating position, after the shutter 35 closes the supply opening 34. The second engageable member 31a moves the regulating member 68 downwardly against the elastic force. By this, it releases the regulating 10 operation of the regulating member 68. Thus, it permits the movement of the movable member 62.

Subsequently, the second engageable member 31a is engaged with the second operating portion 62b2 or 62b4 to rotate the movable member 62, in interrelation with 15 which the shutter 65 is rotated from the developer-reception-permitting position to the developer-reception-preventing position. That is, the receiving opening 16a is closed.

According to this embodiment, the same 20 advantageous effects as with the foregoing embodiments are provided.

Here, the receiving-side movable member 62 is disposed on the upper surface of the process cartridge when the process cartridge 7 is mounted to the main 25 assembly 100a of the apparatus. The movable member 62 is rotatable such that peripheral moving direction thereof is along the mounting and dismounting

direction relative to the main assembly 100a of the apparatus of the process cartridge 7 and along the length of the process cartridge 7. That is, the movable member 62 is rotatable about a horizontal axis 5 extending in a direction crossing with a longitudinal direction of the process cartridge 7.

The shutter 65 is disposed on the upper surface of the process cartridge 7 when the process cartridge 7 is mounted to the main assembly 100a of the apparatus. The rotatable shutter 65 is cylindrical in shape. The shutter 65 is rotatable such that peripheral moving direction thereof is along the mounting and dismounting direction relative to the main assembly 100a of the apparatus of the process 10 cartridge 7 and along the length of the process cartridge 7. In other words, the shutter 65 is in the form of a cylinder rotatable about a horizontal axis 15 extending in a direction crossing with the longitudinal direction of the process cartridge 7. The shutter 65 is provided with an opening (communication opening 65b) in the peripheral surface thereof to permit flow of the developer in the radial direction of the cylindrical shape. When the opening is opposed or aligned with the receiving opening 16a, it opens 20 the receiving opening 16a. The shutter 65 closes the receiving opening 16a by a portion thereof other than 25 the opening is opposed to the developer receiving

opening.

Here, the upper surface is a surface facing upward when the process cartridge 7 is mounted to the main assembly 100a of the apparatus. It does not 5 necessarily mean a topmost service of the cartridge.

In this embodiment, the receiving-side shutter 65 is cylindrical, but this is not limiting. For example, the shutter 65 may be any rotatable member, more particularly, it may be in the form of a circular 10 column, for example. However, the cylindrical shape is preferable from the standpoint of easiness a manufacturing. The shutter is not limited to the rotatable structure, but may be of a slidable structure, which will be described hereinafter.

15 The first receiving-side operating portion 62b1 or 62b3 is provided with a projection provided on the peripheral surface of the receiving-side movable member 62. The projection is engaged with the engageable member (first engageable member 31b, second 20 engageable member 31a) to receive the rotating force.

By doing so, the receiving-side shutter 65 is rotated. The second receiving-side operating portion 62b2 or 62b4 is provided with a projection provided on the peripheral surface of the movable member 62. The 25 projection is engaged with the projection of the supplying-side operating portion 32b1, 32b2, 32b3, 32b4d of the movable member 32. By doing so, the

supplying-side shutter 35 is rotated.

According to this embodiment of the present invention, the transmission of the force is assured because it is accomplished by abutment between the 5 projections.

The movable member 32 is disposed on the lower surface of the supply cartridge 9 when the supply cartridge 9 is mounted to the main assembly 100a of the apparatus. The movable member 32 is rotatable such 10 that peripheral moving direction thereof is along the mounting and dismounting direction relative to the main assembly 100a of the apparatus of the supply cartridge 9 and along the length of the supply cartridge 9. That is, the movable member 32 is 15 rotatable about a horizontal axis extending in a direction crossing with a longitudinal direction of the supply cartridge 9.

The shutter 35 is disposed on the lower surface of the supply cartridge 9 when the supply cartridge 9 20 is mounted to the main assembly 100a of the apparatus. The rotatable shutter 65 is cylindrical in shape. The shutter 35 is rotatable such that peripheral moving direction thereof is along the mounting and dismounting direction relative to the main assembly 100a of the apparatus of the supply cartridge 9 and 25 along the length of the supply cartridge 9. In other words, the shutter 35 is in the form of a cylinder

rotatable about a horizontal axis extending in a direction crossing with the longitudinal direction of the supply cartridge 9. The shutter 35 is provided with an opening (communication opening 35b) in the 5 peripheral surface thereof to permit flow of the developer in the radial direction of the cylindrical shape, the opening being opposed or aligned with the receiving opening 16a to open the receiving opening 16a. When the opening (communication opening 35b) is 10 opposed to the supply opening 34, the supply opening 34 is opened, and when a portion other than the opening (communication opening 35b) is opposed to the supply opening 34, the supply opening 34 is closed.

Here, the lower surface means the surface or 15 side facing downward when the supply cartridge 9 is mounted to the main assembly 100a of the apparatus. It does not necessarily mean the bottommost surface.

In this embodiment, the shutter 35 is cylindrical in shape, but this is not limiting to the 20 present invention. It may be any rotatable member, a rotatable circular column, for example. However, the cylindrical shape is preferable from the standpoint of easiness a manufacturing. The shutter 35 is not limited to a rotatable one, but may be a slidable 25 shutter, which will be described hereinafter.

Furthermore, the movable member 32 is provided with the supplying-side operating portions 32b1, 32b2,

32b3 and 32b4. The projection of the supplying-side operating portion 32b1, 32b2, 32b3, 32b4 is engaged with the projection of the receiving-side operating portion 62b2, 62b4 to receive a rotating force. By 5 doing so, the shutter 35 is rotated.

According to this embodiment of the present invention, the transmission of the force is assured because it is accomplished by abutment between the projections.

10 As described hereinbefore, in this embodiment, the shutters 35 and 65 are rotatable cylindrical members (rotatable member). This is advantageous over a translational movement shutter in that area to which the developer is deposited is small.

15 The above-described operating position will be described in detail.

The operating position is the position at which the receiving-side operating portion (second receiving-side operating portion) 62b2, 62b4 of the 20 receiving-side movable member 62, when the process cartridge 7 is mounted to the main assembly 100a of the apparatus, is opposed to or engaged with the supplying-side movable member 32 of the supply cartridge 9 mounted to the main assembly 100a of the 25 apparatus. In this embodiment, the operating position is at the topmost position of the track of the rotation of the receiving-side movable member 62. At

this operating position, the receiving-side operating portion 62b2, 62b4 receives the force from the engageable member 31a or 31b to rotate the receiving-side movable member 62. Or, at this operating position, 5 the receiving-side operating portion 62b2, 62b4 applies the force to the supplying-side movable member 32 to rotate the supplying-side movable member 32.

In this manner, even if the developer supply cartridge 9 is mounted to the main assembly 100a of 10 the apparatus in the state that process cartridge 7 is not mounted to the main assembly 100a of the apparatus, the closed state of the developer supply opening 34 is maintained. In addition, even when the process cartridge 7 is removed from the main assembly 100a of 15 the apparatus in the state that both of the process cartridge 7 and the developer supply cartridge 9 are mounted to the main assembly 100a of the apparatus.

In the foregoing examples, the cartridges are properly operated irrespective of the order of 20 mounting the supply cartridge 9 and the process cartridge 7 or the order of dismounting the supply cartridge 9 and the process cartridge 7. The supplying-side movable member 32 and the receiving-side movable member 62 are rotatable such that 25 peripheral moving direction is along the mounting direction. In other words, movable member 62 is rotatable about a horizontal axis extending in a

direction crossing with the longitudinal direction of the process cartridge 7 in the state that process cartridge 7 is mounted to the main assembly 100a of the apparatus. Similarly, movable member 32 is 5 rotatable about a horizontal axis extending in a direction crossing with the longitudinal direction of the supply cartridge 9 in the state that supply cartridge 9 is mounted to the main assembly 100a of the apparatus.

10 Here, "horizontal" does not necessarily mean "perpendicular to the vertical direction (the direction of gravity)". More particularly, in this example, the "horizontal" covers the inclination from the right horizontal direction within the range of \pm 15 15° . The range is satisfactory as long as the movable member 32 and the movable member 62 are engaged with each other such that force can be transmitted. In other words, the range is satisfactory if the shutters 35 and 65 can be rotated.

20 By this, as compared with the conventional structure in which the supply opening and the sealing portion are mounted to a flat member rotatable about a vertical axis, the area of the developer supply opening and the area of the shutter are smaller with 25 respect to the cross-sectional direction. For this reason, the process cartridge 7 and the developer supply cartridge 9 can be downsized, and the foot

print of the image forming apparatus 100 can be reduced in the case that four process cartridges 7 and four developer supply cartridges 9 are arranged.

In addition, the supply opening 34 of the

5 supply cartridge 9 is opened, only after the receiving opening 16a of the process cartridge 7 is opened, irrespective of the order of mounting operations of the process cartridge 7 and the supply cartridge 9 into the main assembly 100a of the apparatus.

10 Therefore, the top level of the developer accommodated in the process cartridge 7 (developer accommodating portion 16) can be raised to the neighborhood of the receiving opening. This enables downsizing of the process cartridge 7 with respect to the direction of

15 height. Even when the process cartridge 7 is mounted to the main assembly 100a of the apparatus in the state that supply cartridge 9 is not set in the main assembly 100a of the apparatus, the receiving opening 16a is never be opened. Therefore, the developer is

20 prevented from blowing out through the opening 16a even upon the impact when the process cartridge 7 is mounted to the main assembly 100a of the apparatus. For this reason, the developer can be accommodated up to the neighborhood of the top level 7e.

25 In addition, the supply opening 34 is opened only after the receiving opening 16a is opened irrespective of the order of mounting of the process

cartridge 7 and supply cartridge 9 into the main assembly 100a of the apparatus. Therefore, the developer is prevented from scattering when the process cartridge 7 or the developer supply cartridge 5 9 is mounted to the main assembly 100a of the apparatus.

The developer receiving opening 16a is closed only after the supply opening 34 is closed, irrespective of the order of dismounting operations of 10 the process cartridge 7 and the supply cartridge 9 from the main assembly 100a of the apparatus. Therefore, the developer is prevented from scattering when the process cartridge 7 and/or the supply cartridge 9 is removed from the main assembly 100a of 15 the apparatus.

As described hereinbefore, the receiving opening 16a of the process cartridge 7 is not opened when the supply cartridge 9 is not set in the main assembly 100a of the apparatus. Therefore, even when 20 the process cartridge 7 is left in the main assembly 100a of the apparatus in the state that supply cartridge 9 is not set in the main assembly 100a of the apparatus, it is unlikely that foreign matter enters the process cartridge 7.

25 The supplying-side shutter 35 and the receiving-side shutter 65 can be opened in response to the mounting operation of the process cartridge 7 or

the supply cartridge 9 irrespective of the order of mounting operations of the process cartridge 7 and the supply cartridge 9 into the main assembly 100a of the apparatus.

5 Furthermore, the supplying-side shutter 35 and receiving-side shutter 65 receiving-side shutter 65 can be closed in response to the dismounting operation of the process cartridge 7 and the supply cartridge 9, irrespective of the order of removing operations of 10 the process cartridge 7 and the supply cartridge 9 into the main assembly 100a of the apparatus.

Accordingly, the opening and closing states of the supplying-side shutter 35 and the receiving-side shutter 65 can be switched therebetween in response to 15 the mounting operations of the process cartridge 7 and the supply cartridge 9, irrespective of the order of mounting operations of the process cartridge 7 and the supply cartridge 9 into the main assembly 100a of the apparatus.

20 Thus, the operator can properly mount or dismount the process cartridge 7 and the supply cartridge 9 relative to the main assembly 100a of the apparatus irrespective of the order of the mounting and demounting operations of them. Thus, the mounting 25 and demounting operativity is improved.

In addition, only when the receiving-side shutter 65 opens the receiving opening 16a, the

projection 62b of the cartridge side movable member 62 and the projection 32b and recess 32c of the supplying-side movable member 32 are engageable with each other.

5 For this reason, the movable members 32 and 62 function as detection portions for detecting the opening state of the shutter of the process cartridge 7. This eliminates the necessity of provision of detecting mechanisms for this purpose. Furthermore, 10 even if the operator erroneously mounts process cartridge 7 process cartridge 7 into the main assembly of the apparatus 100 in the state that shutter 65 of the process cartridge 7 is open, and then the operator mounts the supply cartridge 9 into the main assembly 15 of the apparatus 100, the movable members 32 and 62 are not engaged with each other.

In that occasion, the mounting of the supply cartridge 9 results in incomplete mounting. The incompleteness can notify the operator of the 20 erroneous mounting of the process cartridge 7.

[Second embodiment]

Referring to Figure 14 - Figure 16, the shutter mechanism according to a second embodiment of the present invention will be described. In the second 25 embodiment, the shutter portion is slidable in horizontal directions rather than rotatable. The basic structures of the developer supply cartridge and the

process cartridge and the like are the same as those of the first embodiments, and therefore, the detailed description thereof is omitted for simplicity. The shutter mechanism of the developer supply cartridge 5 and process cartridge process cartridge will be described. The same reference numerals as in Embodiment 1 are assigned to the elements having the corresponding functions in this embodiment, and the detailed description thereof is omitted for simplicity.

10 Figure 14 is an exploded perspective view of a shutter of a supply cartridge 9 and the elements therearound. Figure 15 is a perspective view of the shutter of the process cartridge 7 and the elements therearound. Figure 16 illustrates operations of the 15 shutter of the supply cartridge 9 and shows the elements therearound.

The shutter of the supply cartridge 9 in this embodiment will be described.

As shown in Figure 14, on the lower surface, 20 when the process cartridge 7 and the supply cartridge 9 are set in the main assembly 100a of the apparatus, of the developer accommodating portion 33 of the supply cartridge 9, the T housing 46 is fixed. The T housing 46 is provided with a T housing opening 25 46a corresponding to the receiving opening 16a of the process cartridge 7. At the opposite ends of the T housing opening 46a, there are provided groove

portions 46b 46c and stopper portions 46d. Below the T housing opening 46a, a supplying-side shutter 82 is provided.

The supplying-side shutter 82 comprises a

5 shutter portion (supplying-side shutter portion) 82a for opening and closing the T housing opening 46a and a supplying-side movable portion 82b for providing the opening and closing force by engagement with the process cartridge 7. The shutter portion 82a is

10 provided with a supplying-side shutter communication port 82c, a portion-to-be-engaged 82d, 82e and a claw portion 82f. On the other hand, the supplying-side movable portion 82b is provided with a guide groove 82b1 including inclined surfaces and a flat surface

15 portion.

The assembling method of the shutter of the supply cartridge 9 will be described.

First, portions-to-be-engaged 82d, 82e of the supplying-side shutter 82 are engaged with groove

20 portions 46b, 46c of the T housing 46. They are engaged such that claw portion 82f of the supplying-side shutter 82 rides over the stopper portion 46d. By this, the shutter 82 is held slidably in horizontal directions by the portions-to-be-engaged 82d portion-

25 to-be-engaged 82d, 82e and the groove portions 46b, 46c. The claw portion 82f and the stopper portion 46d engaged with each other functions to prevent the

shutter 82 from disengaging from the supply cartridge 9. With the sliding movement of the shutter 82, the supplying-side shutter communication port 85 and the T housing opening 46a become opposed to or aligned with 5 each other where the developer can be supplied from the supply cartridge 9.

The structures of the shutter of the process cartridge 7 in this embodiment will be described.

As shown in Figure 15, the receiving-side 10 movable member (receiving-side movable portion) 90 used in this embodiment is provided with operating portions 90a and 90b in the form of projections. As shown in Figure 15, the operating portion 90a, 90b, when the receiving-side shutter (receiving-side 15 shutter portion) 65 is in the open state for permitting reception of the developer by the developer receiving opening 80a of the developing-device housing 80, is placed at the position opposing the supply cartridge 9 (developer-supply-permitting position). 20 The other structures in the neighborhood of the shutter are the same as with the first embodiment, and therefore, the detailed description thereof will be omitted.

Referring to Figure 16, the description will be 25 made as to the case that process cartridge 7 is mounted to the main assembly 100a of the apparatus in the state that supply cartridge 9 is set in the main

assembly 100a of the apparatus.

During the mounting process of the process cartridge 7, the operations are the same as with the first embodiment up to a certain stage. More

5 particularly, the movable member 90 moves to open the receiving opening 80a, and then the movable member 90 is regulated to be prevented from rotation, by the regulating member 68, and up to this stage, the operations are the same as with the first embodiment.

10 Therefore, the description will be omitted. As described above, when the receiving opening 80a is in the open state for permitting developer reception, the operating portion 90a or 90b provided on the movable member 90 is disposed opposed to the supply cartridge 15 9 (developer-supply-preventing position) (Figure 16).

In this case, the T housing opening 46a of the developer supply cartridge 9 is not disposed opposed to the communication opening 82c, that is, it is in the closed state for preventing the supply of 20 developer. The process cartridge 7 is further advanced into the main assembly 100a of the apparatus. Then, the operating portion 90a or the operating portion 90b moves in the direction of an arrow K ((a) of Figure 16). And, the operating portion 90a or operating 25 portion 90b is engaged with the guide groove 82b1.

When the process cartridge 7 is further advanced into the main assembly 100a of the apparatus,

the operating portion 90a or the operating portion 90b is set in the guided by the inclined surface portion 82b3 and the flat surface portion 82b2 provided in the guide groove 82b1. Therefore, the supplying-side shutter 82 held slidably by the groove portion 46b and the groove portion 46c is moved in the direction of arrow L ((b) of Figure 16). That is, the shutter 82 moves horizontally.

The process cartridge 7 reaches the position ((b) of Figure 16) of completed mounting. Then, the operating portion 90a or the operating portion 90b is held by the flat surface portion 82b2 of the guide groove 82b1, and the communication opening 82c of the supplying-side shutter 82 and the T housing opening 46a become opposed to each other.

When the process cartridge 7 is dismounted from the main assembly 100a of the apparatus in the state that process cartridge 7 and the supply cartridge 9 are mounted, the supplying-side shutter 82, the regulating member 68, the movable member 90 and the receiving-side shutter 65 are operated in the reverse order.

Therefore, when the process cartridge 7 is set in the main assembly 100a of the apparatus, the housing opening 46a of the supply cartridge 9 mounted in the main assembly 100a of the apparatus and the communication opening 82c are not opposed to each

other. Therefore, the housing opening 46a is closed so that supply of the developer into the process cartridge 7 is not possible.

The operations are the same as those described 5 above when the supply cartridge 9 is mounted to the main assembly 100a of the apparatus in the state that process cartridge 7 is set in the main assembly 100a of the apparatus and when the supply cartridge 9 is dismounted from the main assembly of the apparatus 100 10 in the state that supply cartridge 9 and the process cartridge 7 are set in the main assembly of the apparatus 100.

According to this embodiment, similarly to the first embodiment, the space saving, the suppression of 15 toner scattering or the like is accomplished.

In this embodiment, the supplying-side shutter 82 is such that shutter portion 82a and the movable portion 82b are integral with each other. However, in this embodiment, the supplying-side shutter 82 may be 20 constituted by a supplying-side shutter for opening and closing the housing opening and a supplying-side movable member for receiving a force from the operating portion of the process cartridge.

In this embodiment, the shutter 82 slides in 25 the horizontal direction. By doing so, the supply opening 34 can be opened and closed.

[Third embodiment]

Referring to Figure 19 - Figure 22, the description will be made as to a shutter mechanism usable with the supply cartridge 9 and the process cartridge 7 which the present invention is applicable to, according to third embodiment of the present invention. In the third embodiment, an outer cover is employed.

Figure 19 is a perspective view of a stopper actable on the supplying-side movable member of the supply cartridge 9. Figure 20 illustrates operations of the stopper of the supply cartridge 9 and the elements therearound. Figure 21 is a perspective view of the outer cover of the supply cartridge 9. Figure 22 illustrates operations of the outer cover of the developer supply cartridge 9 and the elements therearound.

The structures of the shutter and the structures of the shutter of the supply cartridge 9 are the same as those of the process cartridge 7, and therefore, the description thereof is omitted.

[Structures of stopper of supplying-side movable member of supply cartridge]

Referring to Figure 19, movement regulating (stopper) of the movable member 32 of the supply cartridge 9 will be described.

The developer accommodating portion 33 is provided with a T regulation releasing member 141 and

T regulating member 140 for regulating the movement of the movable member 32.

The regulating member 140 is held for sliding movement in the vertical direction (direction of arrow 5 M) by claw portions 142a, 143a and slide rails 142, 143 provided on the developer accommodating portion 33.

The releasing member 141 is supported rotatably by the hole portion 141a of the releasing member 141 being engaged the shaft portion 144 and the 10 disengagement preventing member 147 provided on the developer accommodating portion 33. The releasing member 141 is provided with an engaging hole 141b engaged with the engagement shaft 140a of the regulating member 140. At a position across the hole 15 portion 141a (rotational center of the releasing member 141) from the engaging hole 141b, there is provided a force receiving shaft portion 141c for receiving a driving force from the main assembly of the apparatus 100. By the driving force, the releasing 20 member 141 is rotated.

By the elastic force of a coil spring 145 provided between the developer accommodating portion 33 and the releasing member 141, the releasing member 141 is urged in the clockwise direction (direction of arrow N of Figure 19). The urging force normally urges the regulating member 140 engaged with the releasing member 141 downwardly.

At the home position state (regulation position), the regulation recess 140b provided on the regulating member 140 and the projection 32b (32b1, 32b3) of the movable member 32 are engaged to each other. By this, the movement of the movable member 32 is regulated or is prevented.

5 [Operations of stopper of supplying-side movable member]

Referring to Figure 20, the operation of the 10 regulating member 140 when the supply cartridge 9 enters the main assembly of the apparatus 100 will be described.

As described hereinbefore, when the supply cartridge 9 is not set in the main assembly of the 15 apparatus 100, the recess 140b is in engagement with the projection 32b (32b1, 32b3) of the movable member 32. Therefore, the movement of the movable member 32 is regulated or prevented.

Therefore, even if the operator inadvertently 20 touches the movable member 32, or even if vibration is imparted to the supply cartridge 9 during transportation stage thereof, the movable member 32 does not move.

The supply cartridge 9 is carried on main 25 assembly rails 101a provided in the main assembly 100a of the apparatus and is advanced into the main assembly 100a of the apparatus (the supply cartridge 9

moves in the direction of arrow A ((a) of Figure 20).

When the supply cartridge 9 is inserted to the position shown in (b) of Figure 20, the force reception shaft portion 141c of the releasing member 141 is brought into contact to the inclined surface portion 146a of the guide 146 of the main assembly rail 101a.

And, with the advancement of the supply cartridge 9, the shaft portion 141c is guided by the inclined surface portion 146a. By doing so, the releasing member 141 is moved in the counterclockwise direction (in the direction of arrow P in (b) of Figure 20) against the elastic force (spring force). The releasing member 141 is urged in the clockwise direction by the elastic force of the coil spring 145. By this, the regulating member 140 positioned at the lower regulation position is moved to the upper permitting position (the direction of arrow Q of (b) in Figure 20) in the developer accommodating portion 33.

When the supply cartridge 9 is further advanced such that shaft portion 141c reaches the flat surface portion 146b of the guide surface 146, the engagement between the recess 140b and the projection 32b (32b1 or 32b3 in Figure 6) is released. By this, the movable member 32 becomes rotatable ((c) of Figure 20).

By moving the movable member 32 in this state,

the communication opening 44a is opened. Thus, the supply of the developer into the process cartridge 7 from the supply cartridge 9 is permitted.

In this manner, the release action for the

5 prevention of movement of movable member 32 by the regulating member 140 is controlled to occur prior to the movement of the movable member 32 opening the communication opening 44a, by the proper arrangement of the guide surface 146 (146a, 146b) of the main

10 assembly rail 101 in the longitudinal direction.

Therefore, the regulating member can regulate or prevent movement of the movable member 32, without preventing the opening and closing operation of the shutter portion 82a during the operation.

15 [Structure of T outer cover of supply cartridge]

As shown in Figure 21, the lower surface of the housing 44 of the supply cartridge 9 is covered by a T outer cover 148. The cover 148 includes a cover portion 148a covering the communication opening 44a of the housing 44 and a shaft hole 148b engaged by the shaft portion 149 of the developer accommodating portion 33. The cover 148 includes surfaces 148c1, 148c2 to be urged for retracting the cover 148 from the communication opening 44a by being contacted by

20 the sealing member 67 or the developing-device housing 45 of the process cartridge 7. The cover 148 is

25 disposed at a position covering the communication

opening 44a when it does not receive a force from the coil spring 150 disposed substantially coaxially with the shaft portion 149.

[Driving structure for T outer cover portion]

5 Referring to Figure 22, the description will be made as to the retracting operation of the cover 148 when only one of the supply cartridge 9 and the process cartridge 7 is set in the main assembly 100a of the apparatus, and the other cartridge is mounted
10 to the main assembly 100a of the apparatus.

First, the case that supply cartridge 9 is mounted to the main assembly 100a of the apparatus in the state that process cartridge 7 is set in the main assembly 100a of the apparatus will be dealt with.

15 The supply cartridge 9 is carried on the main assembly rails 101a and 101b provided in the main assembly of the apparatus 100 and is inserted in the direction indicated by an arrow A in Figure 22a.

When the supply cartridge 9 is inserted to the
20 position shown in Figure 22b, the surface 148c1 to be urged of the cover 148 is brought into contact to the sealing member 67 of the process cartridge 7 as indicated by chain lines in Figure 22b.

With the advancement of the supply cartridge 9,
25 the surface 148c1 is urged by the sealing member 67. By doing so, the cover 148 disposed at the position covering the communication opening 44a by the coil

spring 150 is rotated in the clockwise direction (R direction in the Figure) against the spring force.

Furthermore, before the completion of mounting operation of the supply cartridge 9 to the main

5 assembly of the apparatus 100, the cover 148 becomes retracted from the communication opening 44a.

Therefore, the supply of the developer from the supply cartridge 9 is permitted (Figure 22c).

When the supply cartridge 9 is removed from the
10 main assembly 100a of the apparatus in the state that process cartridge 7 and the supply cartridge 9 are set in the main assembly 100a of the apparatus, the order of the operations of the cover 148 are reverse (Figure 22c to Figure 22a).

15 When the supply cartridge 9 is removed, the cover 148 restores to the position covering the communication opening 44a by the urging force of the coil spring 150.

The description will be made as to the case
20 that process cartridge 7 is removed from the main assembly 100a of the apparatus in the state that process cartridge 7 and the supply cartridge 9 are set in the main assembly 100a of the apparatus.

The process cartridge 7 moves in the direction
25 of an arrow S (Figure 22d). During the period in which the surface 148c1 to be urged is urged by the sealing member 67 in the process of dismounting the process

cartridge 7, the cover 148 is kept retracted from the communication opening 34a (Figure 22d).

Thereafter, when the process cartridge 7 is further pulled out to such a position that sealing 5 member 67 becomes out of contact with the surface 148c1 to be urged, the cover 148 restores to the position covering the communication opening 34a by the urging force of the coil spring 150.

Therefore, when the supply cartridge 9 is 10 completely dismounted, the cover 148 restores the position covering the communication opening 44a by the urging force of the coil spring 150 (Figure 22e).

Thus, irrespective of whichever cartridge 7 or 9 is first removed, the T outer cover 148 covers the 15 communication opening 34a, 44a in the process of the removing operation of the cartridge.

In the case that process cartridge 9 is mounted to the main assembly of the apparatus 100 in the state that supply cartridge 9 is set in the main assembly of 20 the apparatus 100, the sealing member 67 urges the surface 148c2 to be urged. By this, similarly to the above-described case, the cover 148 disposed at the position covering the communication opening 44a by the coil spring 150 is moved against the elastic force 25 (spring force). And, the cover 148 is retracted from the communication opening 44a.

With such a structure, the portion supplying

the developer is normally covered by the cover 148 except for the operation state. Therefore, when the supply cartridge 9 is mounted to or dismounted from relative to the main assembly 100a of the apparatus,

5 the developer supplying portion disposed on lower surface portion of the supply cartridge 9 which is not easily seen by the operator is prevented from being inadvertently touched by the operator.

The operations when the cartridge 9 is mounted

10 to the main assembly 100a of the apparatus in the state that process cartridge 7 is set in the main assembly 100a of the apparatus or when the supply cartridge 9 is removed from the main assembly 100a of the apparatus in the state that cartridge 9 and the

15 process cartridge 7 are set in the main assembly 100a of the apparatus, are the same as those described above, and therefore, the detailed description of such cases are omitted.

In this embodiment, similarly to the first

20 embodiments, the space saving, the suppression of developer scattering or the like can be accomplished.

In the foregoing descriptions, the color electrophotographic image forming apparatus employing four supply cartridges and four process cartridge are

25 used correspondingly has been taken as an example. However, the present invention is not limited to such an example. For example, the present invention is

applicable to a developer supply cartridge and a process cartridge used with a monochromatic electrophotographic image forming apparatus. The present invention is also applicable to such an 5 electrophotographic image forming apparatus.

In addition, as described above, in present invention, the receiving-side shutter and the receiving-side movable member may be separate members, and the supplying-side shutter and the supplying-side 10 movable member may be separate members.

In such a case, the assembling is easy.

On the contrary, in the case of the integral structures, the number of parts can be reduced. One skilled in the art can properly select the structures 15 depending on the cases.

In the foregoing description, the operating portion has a projection. However, the present invention is not limited to such a structure. For example, the operating portion may be provided with a 20 friction member to intentionally enhance the sliding resistance. When the operating portion has the projection, the driving force can be transmitted assuredly.

As described in the foregoing, according to the 25 present invention, when the developer is supplied into the process cartridge from the developer supply cartridge, the leakage of the developer can be

effectively prevented.

According to present invention, the receiving-side movable member movable in interrelation with the receiving-side shutter can be used for moving the 5 supplying-side movable member.

According to the embodiment wherein the developer supply cartridge is entered into the main assembly of the apparatus in the state that process cartridge is set in the main assembly of the apparatus, 10 the developer can be supplied through the supply opening only when the receiving opening can receive the developer.

According to the embodiment wherein the developer supply cartridge is removed from the main assembly of the apparatus in the state that process cartridge is set in the main assembly of the apparatus, 15 the receiving opening is prevented from receiving the developer with the supply opening is prevented from supplying the developer.

According to the embodiment wherein the process cartridge is mounted to the main assembly of the apparatus in the state that developer supply cartridge is set in the main assembly of the apparatus, the developer can be supplied through the supply opening 20 only when the receiving opening can receive the developer. 25

According to the embodiment wherein the process

cartridge is removed from the main assembly of the apparatus in the state that developer supply cartridge is set in the main assembly of the apparatus, the receiving opening can prevent reception of the 5 developer with the supply opening is prevented from supplying the developer.

According to the embodiments of the present invention, the supply opening is prevented from opening even if the developer supply cartridge is 10 entered into the main assembly of the apparatus in the state that process cartridge is not set in the main assembly of the apparatus.

According to the embodiments of the present invention, the receiving opening is prevented from opening even if the process cartridge is entered into the main assembly of the apparatus in the state that developer supply cartridge is not set in the main assembly of the apparatus.

20 [INDUSTRIAL APPLICABILITY]

As described hereinabove, according to the present invention, it is possible to provide a developer supply cartridge, a process cartridge and an electrophotographic image forming apparatus wherein 25 when the developer supply cartridge is removed from the main assembly of the apparatus in a state that both of the process cartridge and the developer supply

cartridge are set in the main assembly of the electrophotographic image forming apparatus, the leakage of the developer through a developer supply opening or through the developer receiving opening can 5 be prevented.

While the invention has been described with reference to the structures disclosed herein, it is not confined to the details set forth and this application is intended to cover such modifications or 10 changes as may come within the purpose of the improvements or the scope of the following claims.

CLAIMS

1. A process cartridge detachably mountable to a main assembly of an electrophotographic image forming apparatus, wherein said process cartridge is capable of receiving a supply of a developer from a developer supply cartridge, wherein the developer supply cartridge includes a supplying-side developer accommodating portion for accommodating the developer,
5 a supplying-side shutter portion movable between a developer-supply-permitting position for opening a developer supply opening for supplying the developer from the supplying-side developer accommodating portion into the process cartridge and a developer-supply-preventing position for closing the developer supply opening, a supplying-side movable portion movable to interrelatedly move the supplying-side shutter portion between the developer-supply-permitting position and the developer-supply-preventing position, and an engageable member, said
10 process cartridge comprising:
an electrophotographic photosensitive drum;
a developing roller for developing an electrostatic latent image formed on said
15 electrophotographic photosensitive drum with the developer;
20 a receiving-side developer accommodating
25

portion for accommodating the developer;

a developer receiving opening for receiving the developer into said receiving-side developer accommodating portion;

5 a receiving-side shutter portion movable between a developer-reception-permitting position for opening said developer receiving opening and a developer-reception-preventing position for closing said developer receiving opening;

10 a regulating member; and

a receiving-side movable portion movable to interrelatedly move said receiving-side shutter portion between the developer-reception-permitting position and the developer-reception-preventing position, said receiving-side movable portion including a first receiving-side operating portion which takes an operating position when said receiving-side shutter portion is at the developer-reception-preventing position and a second receiving-side 15 operating portion which takes the operating position when said receiving-side shutter portion is at the developer-reception-permitting position, wherein when said process cartridge enters the main assembly of the apparatus with said regulating member regulating 20 movement to place said first receiving-side operating portion at the operating position in a state that said developer supply cartridge is set in the main assembly 25

of the apparatus, said regulating member contacts the engageable member to release said receiving-side movable portion, thus permitting movement of said receiving-side movable portion, then receiving-side

5 movable portion moves said receiving-side shutter portion to the developer-reception-permitting position in interrelation with said first receiving-side operating portion moved by contacting the engageable member, and then said receiving-side movable portion

10 moves the supplying-side shutter portion to the developer-supply-permitting position in interrelation with the supplying-side movable portion moved by engagement of said second receiving-side operating portion with the supplying-side movable portion while

15 being regulated by said regulating member in a state that second receiving-side operating portion is placed at the operating position.

2. A process cartridge detachably mountable to a

20 main assembly of an electrophotographic image forming apparatus, wherein said process cartridge is capable of receiving a supply of a developer from a developer supply cartridge, wherein the developer supply cartridge includes a supplying-side developer

25 accommodating portion for accommodating the developer, a supplying-side shutter portion movable between a developer-supply-permitting position for opening a

developer supply opening for supplying the developer from the supplying-side developer accommodating portion into the process cartridge and a developer-supply-preventing position for closing the developer supply opening, a supplying-side movable portion movable to interrelatedly move the supplying-side shutter portion between the developer-supply-permitting position and the developer-supply-preventing position, and an engageable member, said process cartridge comprising:

an electrophotographic photosensitive drum;

a developing roller for developing an electrostatic latent image formed on said electrophotographic photosensitive drum with the developer;

a receiving-side developer accommodating portion for accommodating the developer;

a developer receiving opening for receiving the developer into said receiving-side developer accommodating portion;

a receiving-side shutter portion movable between a developer-reception-permitting position for opening said developer receiving opening and a developer-reception-preventing position for closing said developer receiving opening;

a regulating member; and

a receiving-side movable portion movable to

interrelatedly move said receiving-side shutter portion between the developer-reception-permitting position and the developer-reception-preventing position, said receiving-side movable portion 5 including a receiving-side operating portion which takes the operating position when said receiving-side shutter portion is at the developer-reception-permitting position, wherein when said process cartridge is removed from the main assembly of the 10 apparatus in a state that supply cartridge is set in the main assembly of the apparatus, said receiving-side operating portion moves said supplying-side movable portion by engagement, with said supplying-side movable portion, of said receiving-side operating 15 portion of said receiving-side movable portion which is regulated by said regulating member in a state that receiving-side movable portion is placed at the operating position to interrelatedly move said supplying-side shutter portion to the developer-supply-preventing position, then said regulating 20 member contacts the engageable member to release said receiving-side movable portion, thus permitting movement of said receiving-side movable portion, and receiving-side movable portion moves said receiving- 25 side shutter portion to the developer-reception-preventing position in interrelation with said receiving-side operating portion moved by contacting

the engageable member.

3. A process cartridge according to Claim 1 or 2,
wherein said receiving-side movable portion is
5 disposed on an upper surface of said process cartridge
in a state that process cartridge is mounted to the
main assembly of the apparatus and is rotatable about
a horizontal axis crossing with a longitudinal
direction of said process cartridge.

10

4. A process cartridge according to any one of
Claims 1 - 3, wherein said receiving-side shutter
portion is disposed on an upper surface of said
process cartridge in a state that process cartridge is
15 mounted to the main assembly of the apparatus and
includes a rotatable member rotatable about a
horizontal axis crossing with a longitudinal direction
of said process cartridge, said rotatable member being
provided with an opening which opens in a radial
20 direction of rotation of said rotatable member,
wherein said developer receiving opening is opened by
said opening of said rotatable member opposing to said
developer receiving opening, and said developer
receiving opening is closed by a portion of said
25 rotatable member other than said opening opposing to
said developer receiving opening.

5. A process cartridge according to Claim 1,
wherein said receiving-side movable portion is
rotatable, wherein said first receiving-side operating
portion includes a projection having a portion
5 extending along a rotational movement direction of
said receiving-side movable portion, and said
projection receives a force by engagement with said
engageable member to rotate said receiving-side
shutter portion, wherein said second receiving-side
10 operating portion includes a projection having a
portion extending along the rotational moving
direction of said receiving-side movable portion, said
projection of said second receiving-side operating
portion is engageable with a projection of a
15 supplying-side operating portion of said supplying-
side movable portion to apply a rotating force, thus
rotating said supplying-side shutter portion.

6. A process cartridge according to Claim 2,
20 wherein said receiving-side movable portion is
rotatable, wherein said receiving-side operating
portion includes a projection having a portion
extending along a rotational moving direction of said
receiving-side movable portion, and a supplying-side
25 operating portion of said supplying-side movable
portion includes a projection having a portion
extending along a rotational moving direction of said

supplying-side movable portion, wherein said supplying-side shutter portion is rotated by said projection of said receiving-side movable portion engaging said projection of said supplying-side 5 movable portion and applying a rotating force.

7. A developer supply cartridge for supplying a developer into a process cartridge, said developer supply cartridge being detachably mountable to a main 10 assembly of an electrophotographic image forming apparatus, wherein said process cartridge includes an electrophotographic photosensitive drum; a developing roller for developing an electrostatic latent image formed on said electrophotographic photosensitive drum; a receiving-side shutter portion movable between a developer-reception-permitting position for opening a developer receiving opening for receiving the developer to be used by said developing roller for developing operation and a developer-reception- 15 preventing position for closing said developer receiving opening; a receiving-side movable portion movable to interrelatedly move said receiving-side shutter portion between the developer-reception-permitting position and the developer-reception- preventing position, said receiving-side movable 20 portion including a receiving-side operating portion which takes an operating position when said receiving- 25

side shutter portion is at said developer-reception-permitting position; a regulating member for regulating movement of said receiving-side movable portion when said receiving-side operating portion is 5 at the operating position, said developer supply cartridge comprising:

 a supplying-side developer accommodating portion for accommodating the developer;

 a developer supply opening for supplying the 10 developer from said supplying-side developer accommodating portion into said process cartridge through said developer receiving opening;

 a supplying-side shutter portion movable between a developer-supply-permitting position for 15 opening said developer supply opening and a developer-supply-preventing position for closing said developer supply opening; and

 a supplying-side movable portion movable, when 20 said developer supply cartridge enters said main assembly of the apparatus in a state that process cartridge is set in said main assembly of the apparatus, to interrelatedly move said supplying-side shutter portion from said developer-supply-preventing position to the developer-supply-permitting position 25 by engagement with said receiving-side operating portion of said receiving-side movable portion, a movement of which is regulated by said regulating

member in a state that receiving-side operating portion is positioned at the operating position.

8. A developer supply cartridge for supplying a developer into a process cartridge, said developer supply cartridge being detachably mountable to a main assembly of an electrophotographic image forming apparatus, wherein said process cartridge includes an electrophotographic photosensitive drum; a developing roller for developing an electrostatic latent image formed on said electrophotographic photosensitive drum; a receiving-side shutter portion movable between a developer-reception-permitting position for opening a developer receiving opening for receiving the developer to be used by said developing roller for developing operation and a developer-reception-preventing position for closing said developer receiving opening; a receiving-side movable portion movable to interrelatedly move said receiving-side shutter portion between the developer-reception-permitting position and the developer-reception-preventing position, said receiving-side movable portion including a receiving-side operating portion which takes an operating position when said receiving-side shutter portion is at said developer-reception-permitting position; a regulating member for regulating movement of said receiving-side movable

portion when said receiving-side operating portion is at the operating position, said developer supply cartridge comprising:

- a supplying-side developer accommodating portion for accommodating the developer;
- 5 a developer supply opening for supplying the developer from said supplying-side developer accommodating portion into said process cartridge through said developer receiving opening;
- 10 a supplying-side shutter portion movable between a developer-supply-permitting position for opening said developer supply opening and a developer-supply-preventing position for closing said developer supply opening; and
- 15 a supplying-side movable portion movable, when said developer supply cartridge enters said main assembly of the apparatus in a state that process cartridge is set in said main assembly of the apparatus, to interrelatedly move said supplying-side shutter portion from the developer-supply-permitting position to the developer-supply-preventing position by engagement with said receiving-side operating portion of said receiving-side movable portion, a movement of which is regulated by said regulating member in a state that receiving-side operating portion is positioned at the operating position.
- 20
- 25

9. A developer supply cartridge for supplying a developer into a process cartridge, said developer supply cartridge being detachably mountable to a main assembly of an electrophotographic image forming apparatus, wherein said process cartridge includes an electrophotographic photosensitive drum; a developing roller for developing an electrostatic latent image formed on said electrophotographic photosensitive drum; a receiving-side shutter portion movable between a developer-reception-permitting position for opening a developer receiving opening for receiving the developer to be used by said developing roller for developing operation and a developer-reception-preventing position for closing said developer receiving opening; a receiving-side movable portion movable to interrelatedly move said receiving-side shutter portion between the developer-reception-permitting position and the developer-reception-preventing position, said receiving-side movable portion including a first receiving-side operating portion which takes an operating position when said receiving-side shutter portion is at said developer-reception-preventing position, and a second receiving-side operating portion which takes the operating position when said receiving-side shutter portion is at said developer-reception-permitting position, a regulating member for regulating movement of said

receiving-side movable portion when said first or second receiving-side operating portion is at the operating position, said developer supply cartridge comprising:

- 5 a supplying-side developer accommodating portion for accommodating the developer;
 a developer supply opening for supplying the developer from said supplying-side developer accommodating portion into said process cartridge
- 10 through said developer receiving opening;
 a supplying-side shutter portion movable between a developer-supply-permitting position for opening said developer supply opening and a developer-supply-preventing position for closing said developer supply opening; and
 an engageable member for moving said receiving-side shutter portion to said developer-reception-permitting position by contacting, when said process cartridge enters the main assembly of the apparatus in
- 15 a state that said developer supply cartridge is set in the main assembly of the apparatus, to said regulating member which regulates movement of the receiving-side movable portion with said first receiving-side operating portion placed at the operating position to
- 20 release said receiving-side movable portion from said regulating member thus permitting movement of said receiving-side movable portion and then contacting to
- 25

5 said first receiving-side operating portion to move
said receiving-side movable portion and to
interrelatedly to move said receiving-side shutter
portion to said developer-reception-permitting
position; and

10 a supplying-side movable portion movable to
interrelatedly move said supplying-side shutter
portion from said developer-supply-preventing position
to said developer-supply-permitting position by
engagement with said second receiving-side operating
portion of said receiving-side movable portion which
is regulated at said operating position by said
regulating member, after said engageable member moves
said receiving-side shutter portion to said developer-
15 reception-permitting position.

10. A developer supply cartridge for supplying a
developer into a process cartridge, said developer
supply cartridge being detachably mountable to a main
20 assembly of an electrophotographic image forming
apparatus, wherein said process cartridge includes an
electrophotographic photosensitive drum; a developing
roller for developing an electrostatic latent image
formed on said electrophotographic photosensitive
25 drum; a receiving-side shutter portion movable between
a developer-reception-permitting position for opening
a developer receiving opening for receiving the

developer to be used by said developing roller for developing operation and a developer-reception-preventing position for closing said developer receiving opening; a receiving-side movable portion

5 movable to interrelatedly move said receiving-side shutter portion between the developer-reception-permitting position and the developer-reception-preventing position, said receiving-side movable portion including a receiving-side operating portion

10 which takes an operating position when said receiving-side shutter portion is at said developer-reception-permitting position; a regulating member for regulating movement of said receiving-side movable portion when said receiving-side operating portion is

15 at the operating position, said developer supply cartridge comprising:

a supplying-side developer accommodating portion for accommodating the developer;

a developer supply opening for supplying the

20 developer from said supplying-side developer accommodating portion into said process cartridge through said developer receiving opening;

a supplying-side shutter portion movable between a developer-supply-permitting position for

25 opening said developer supply opening and a developer-supply-preventing position for closing said developer supply opening; and

a supplying-side movable portion movable to interrelatedly move said supplying-side shutter portion from said developer-supply-permitting position to said developer-supply-preventing position by 5 engaging, when said process cartridge is removed from the main assembly of the apparatus in a state that said developer supply cartridge is set in the main assembly of the apparatus, with said receiving-side operating portion of said receiving-side movable portion which is regulated by said regulating member with said receiving-side shutter portion placed at 10 said developer-reception-permitting position.

11. A developer supply cartridge for supplying a developer into a process cartridge, said developer supply cartridge being detachably mountable to a main assembly of an electrophotographic image forming apparatus, wherein said process cartridge includes an electrophotographic photosensitive drum; a developing 20 roller for developing an electrostatic latent image formed on said electrophotographic photosensitive drum; a receiving-side shutter portion movable between a developer-reception-permitting position for opening a developer receiving opening for receiving the 25 developer to be used by said developing roller for developing operation and a developer-reception-preventing position for closing said developer

receiving opening; a receiving-side movable portion rotatable to interrelatedly move said receiving-side shutter portion between the developer-reception-permitting position and the developer-reception-

5 preventing position, said receiving-side movable portion including a first receiving-side operating portion which takes an operating position when said receiving-side shutter portion is at said developer-reception-preventing position, and a second receiving-
10 side operating portion which takes the operating position when said receiving-side shutter portion is at said developer-reception-permitting position, a regulating member for regulating rotation of said receiving-side movable portion when said first or
15 second receiving-side operating portion is at the operating position, said developer supply cartridge comprising:

a supplying-side developer accommodating portion for accommodating the developer;

20 a developer supply opening for supplying the developer from said supplying-side developer accommodating portion into said process cartridge through said developer receiving opening;

a supplying-side shutter portion movable
25 between a developer-supply-permitting position for opening said developer supply opening and a developer-supply-preventing position for closing said developer

supply opening;

an engageable member fixed at a position downstream of said developer supply opening with respect to an entering direction in which said 5 developer supply cartridge enters said main assembly of the apparatus, wherein when said developer supply cartridge enters the main assembly of the apparatus in a state that process cartridge is set in the main assembly of the apparatus, said engageable member 10 releases, prior to said supplying-side shutter portion opening said developer supply opening, said receiving-side movable portion from said regulating member by contacting said regulating member which regulates rotation of said receiving-side movable portion with 15 said first receiving-side operating portion placed at said operating position to move said regulating member downwardly against an elastic force, thus permitting movement of said receiving-side movable portion, then said engageable member engages with said first 20 receiving-side operating portion to rotate said receiving-side movable portion and to interrelatedly move said receiving-side shutter portion from said developer-reception-preventing position to said developer-reception-permitting position, wherein when 25 said developer supply cartridge is removed from the main assembly of the apparatus in the state that process cartridge is set in the main assembly of the

apparatus, said engageable member releases, after said supplying-side shutter portion closes said developer supply opening, said receiving-side movable portion from said regulating member by contacting said

5 regulating member which regulates rotation of said receiving-side movable portion with said second receiving-side operating portion placed at said operating position to move said regulating member downwardly against the elastic force, thus permitting

10 movement of said receiving-side movable portion, then said engageable member engages with said second receiving-side operating portion to rotate said receiving-side movable portion and to interrelatedly move said receiving-side shutter portion from said

15 developer-reception-permitting position to said developer-reception-preventing position; and

a supplying-side movable portion for moving said supplying-side shutter portion from said developer-supply-preventing position to said

20 developer-supply-permitting position and from said developer-supply-permitting position to said developer-supply-preventing position, wherein when said developer supply cartridge enters the main assembly of the apparatus in a state that process

25 cartridge is set in the main assembly of the apparatus, said supplying-side movable portion is rotated, after said receiving-side shutter portion opens said

developer receiving opening, by engagement with said receiving-side movable portion which is regulated by said regulating member with said second receiving-side operating portion placed at said operating position,

5 and in interrelation with rotation of said supplying-side movable portion, said supplying-side shutter portion is moved from said developer-supply-preventing position to said developer-supply-permitting position, and wherein said developer supply cartridge is removed

10 from the main assembly of the apparatus in the state that process cartridge is set in the main assembly of the apparatus, said supplying-side movable portion is rotated, prior to said receiving-side shutter portion closes said developer receiving opening, by engagement

15 with said receiving-side movable portion which is regulated by said regulating member with said second receiving-side operating portion placed at said operating position, and in interrelation with rotation of said supplying-side movable portion, said

20 supplying-side shutter portion is moved from said developer-supply-permitting position to said developer-supply-preventing position.

12. A developer supply cartridge for supplying a

25 developer into a process cartridge, said developer supply cartridge being detachably mountable to a main assembly of an electrophotographic image forming

apparatus, wherein said process cartridge includes an electrophotographic photosensitive drum; a developing roller for developing an electrostatic latent image formed on said electrophotographic photosensitive

5 drum; a receiving-side shutter portion movable between a developer-reception-permitting position for opening a developer receiving opening for receiving the developer to be used by said developing roller for developing operation and a developer-reception-

10 preventing position for closing said developer receiving opening; a receiving-side movable portion rotatable to interrelatedly move said receiving-side shutter portion between the developer-reception-permitting position and the developer-reception-

15 preventing position, said receiving-side movable portion including a first receiving-side operating portion which takes an operating position when said receiving-side shutter portion is at said developer-reception-preventing position, and a second receiving-

20 side operating portion which takes the operating position when said receiving-side shutter portion is at said developer-reception-permitting position, a regulating member for regulating rotation of said receiving-side movable portion when said first or

25 second receiving-side operating portion is at the operating position, said developer supply cartridge comprising:

a supplying-side developer accommodating portion for accommodating the developer;

a developer supply opening for supplying the developer from said supplying-side developer

5 accommodating portion into said process cartridge through said developer receiving opening;

a supplying-side shutter portion movable between a developer-supply-permitting position for opening said developer supply opening and a developer-

10 supply-preventing position for closing said developer supply opening;

a first engageable member fixed at a position upstream of said developer supply opening with respect to an entering direction in which said developer

15 supply cartridge enters said main assembly of the apparatus, wherein when said process cartridge enters the main assembly of the apparatus in a state that said developer supply cartridge is set in the main assembly of the apparatus, said first engageable member releases, prior to said supplying-side shutter portion opening said developer supply opening, said

20 receiving-side movable portion from said regulating member by contacting said regulating member which regulates rotation of said receiving-side movable portion with said first receiving-side operating

25 portion placed at said operating position to move said regulating member downwardly against an elastic force,

thus permitting movement of said receiving-side movable portion, then said first engageable member engages with said first receiving-side operating portion to rotate said receiving-side movable portion and to interrelatedly rotate said receiving-side shutter portion from said developer-reception-preventing position to said developer-reception-permitting position;

a second engageable member fixed at a position downstream of said developer supply opening with respect to the entering direction, wherein when said developer supply cartridge enters the main assembly of the apparatus in a state that process cartridge is set in the main assembly of the apparatus, said second engageable member releases, prior to said supplying-side shutter portion opening said developer supply opening, said receiving-side movable portion from said regulating member by contacting said regulating member which regulates rotation of said receiving-side movable portion with said first receiving-side operating portion placed at said operating position to move said regulating member downwardly against an elastic force, thus permitting movement of said receiving-side movable portion, then said second engageable member engages with said first receiving-side operating portion to rotate said receiving-side movable portion and to interrelatedly rotate said

receiving-side shutter portion from said developer-reception-preventing position to said developer-reception-permitting position; and

5 a supplying-side movable portion for rotating
5 said supplying-side shutter portion from said
developer-supply-preventing position to said
developer-supply-permitting position, wherein when
said process cartridge enters the main assembly of the
apparatus in a state that said developer supply
10 cartridge is set in the main assembly of the apparatus,
said supplying-side movable portion is rotated, after
said first engageable member causes said receiving-
side shutter portion to open said developer receiving
opening, by engagement with said receiving-side
15 movable portion which is regulated by said regulating
member with said second receiving-side operating
portion placed at said operating position, and in
interrelation with rotation of said supplying-side
movable portion, said supplying-side shutter portion
20 is rotated from said developer-supply-preventing
position to said developer-supply-permitting position,
and wherein when said developer supply cartridge
enters the main assembly of the apparatus in a state
that process cartridge is set in the main assembly of
25 the apparatus, said supplying-side movable portion is
rotated, after said second engageable member causes
said receiving-side shutter portion to open said

developer receiving opening, by engagement with said receiving-side movable portion which is regulated by said regulating member with said second receiving-side operating portion placed at said operating position,

5 and in interrelation with rotation of said supplying-side movable portion, said supplying-side shutter portion is rotated from said developer-supply-preventing position to said developer-supply-permitting position.

10

13. A developer supply cartridge for supplying a developer into a process cartridge, said developer supply cartridge being detachably mountable to a main assembly of an electrophotographic image forming apparatus, wherein said process cartridge includes an electrophotographic photosensitive drum; a developing roller for developing an electrostatic latent image formed on said electrophotographic photosensitive drum; a receiving-side shutter portion movable between a developer-reception-permitting position for opening a developer receiving opening for receiving the developer to be used by said developing roller for developing operation and a developer-reception-preventing position for closing said developer receiving opening; a receiving-side movable portion rotatable to interrelatedly move said receiving-side shutter portion between the developer-reception-

15

20

25

permitting position and the developer-reception-preventing position, said receiving-side movable portion including a first receiving-side operating portion which takes an operating position when said 5 receiving-side shutter portion is at said developer-reception-preventing position, and a second receiving-side operating portion which takes the operating position when said receiving-side shutter portion is at said developer-reception-permitting position, a 10 regulating member for regulating rotation of said receiving-side movable portion when said first or second receiving-side operating portion is at the operating position, said developer supply cartridge comprising:

15 a supplying-side developer accommodating portion for accommodating the developer;

a developer supply opening for supplying the developer from said supplying-side developer accommodating portion into said process cartridge 20 through said developer receiving opening;

a supplying-side shutter portion movable between a developer-supply-permitting position for opening said developer supply opening and a developer-supply-preventing position for closing said developer 25 supply opening;

a first engageable member fixed at a position upstream of said developer supply opening with respect

to an entering direction in which said developer supply cartridge enters said main assembly of the apparatus, wherein when said process cartridge is removed from the main assembly of the apparatus in a

5 state that said developer supply cartridge is set in the main assembly of the apparatus, said first engageable member releases, after said supplying-side shutter portion closes said developer supply opening, said receiving-side movable portion from said

10 regulating member by contacting said regulating member which regulates rotation of said receiving-side movable portion with said second receiving-side operating portion placed at said operating position to move said regulating member downwardly against an

15 elastic force, thus permitting movement of said receiving-side movable portion, then said first engageable member engages with said second receiving-side operating portion to rotate said receiving-side movable portion and to interrelatedly rotate said

20 receiving-side shutter portion from said developer-reception-permitting position to said developer-reception-preventing position;

25 a second engageable member fixed at a position downstream of said developer supply opening with respect to the entering direction, wherein when said developer supply cartridge is removed from the main assembly of the apparatus in a state that process

cartridge is set in the main assembly of the apparatus, said second engageable member releases, after said supplying-side shutter portion closes said developer supply opening, said receiving-side movable portion

5 from said regulating member by contacting said regulating member which regulates rotation of said receiving-side movable portion with said second receiving-side operating portion placed at said operating position to move said regulating member

10 downwardly against an elastic force, thus permitting movement of said receiving-side movable portion, then said second engageable member engages with said second receiving-side operating portion to rotate said receiving-side movable portion and to interrelatedly

15 rotate said receiving-side shutter portion from said developer-reception-permitting position to said developer-reception-preventing position; and

a supplying-side movable portion for rotating said supplying-side shutter portion from said

20 developer-supply-permitting position to said developer-supply-preventing position, wherein when said process cartridge is removed from the main assembly of the apparatus in a state that said developer supply cartridge is set in the main assembly

25 of the apparatus, said supplying-side movable portion is rotated, prior to said first engageable member causing said receiving-side shutter portion to close

said developer receiving opening, by engagement with said receiving-side movable portion which is regulated by said regulating member with said second receiving-side operating portion placed at said operating

5 position, and in interrelation with rotation of said supplying-side movable portion, said supplying-side shutter portion is moved from said developer-supply-permitting position to said developer-supply-preventing position, and wherein when said developer

10 supply cartridge is removed from the main assembly of the apparatus in a state that process cartridge is set in the main assembly of the apparatus, said supplying-side movable portion is rotated, prior to said second engageable member causing said receiving-side shutter

15 portion to close said developer receiving opening, by engagement with said receiving-side movable portion which is regulated by said regulating member with said second receiving-side operating portion placed at said operating position, and in interrelation with rotation

20 of said supplying-side movable portion, said supplying-side shutter portion is moves from said developer-supply-permitting position to said developer-supply-preventing position.

25 14. A developer supply cartridge according to Claim 7, further comprising a engageable member fixed at a position downstream of said supplying-side

movable portion with respect to an entering direction in which said developer supply cartridge enters the main assembly of the apparatus, wherein when said developer supply cartridge enters the main assembly of 5 the apparatus, said engageable member releases, prior to said supplying-side shutter portion opening said developer supply opening, said receiving-side movable portion from said regulating member by contacting said regulating member which regulates rotation of said 10 receiving-side movable portion with said receiving-side shutter portion placed at said developer-reception-preventing position to move said regulating member, thus permitting movement of said receiving-side movable portion, then said engageable member 15 engages with a first receiving-side operating portion to rotate said receiving-side movable portion, thus moving said receiving-side shutter portion from said developer-reception-preventing position to said developer-reception-permitting position.

20

15. A developer supply cartridge according to Claim 8, further comprising an engageable member fixed at a position upstream of said supplying-side movable portion with respect to a removing direction in which 25 said developer supply cartridge is removed from the main assembly of the apparatus, wherein when said developer supply cartridge is removed from the main

assembly of the apparatus, said engageable member releases, after said supplying-side shutter portion closes said developer supply opening, said receiving-side movable portion from said regulating member by

5 contacting said regulating member which regulates rotation of said receiving-side movable portion with said receiving-side shutter portion placed at said developer-reception-permitting position to move said regulating member, thus permitting movement of said

10 receiving-side movable portion, then said engageable member engages with a receiving-side operating portion to rotate said receiving-side movable portion, thus moving said receiving-side shutter portion from said developer-reception-permitting position to said

15 developer-reception-preventing position.

16. A developer supply cartridge according to any one of Claims 7 - 15, wherein said supplying-side movable portion is disposed on a lower surface of said developer supply cartridge in a state that said developer supply cartridge is mounted to the main assembly of the apparatus, and is rotatable about a horizontal axis crossing with a longitudinal direction of said developer supply cartridge.

25

17. A developer supply cartridge according to any one of Claims 7 - 15, wherein said supplying-side

shutter portion is disposed on a lower surface of said developer supply cartridge in a state that said developer supply cartridge is set in the main assembly of the apparatus and includes a rotatable member

5 rotatable about a horizontal axis crossing with a longitudinal direction of said developer supply cartridge, said rotatable member being provided with an opening which opens in a radial direction of rotation of said rotatable member, wherein said

10 developer receiving opening is opened by said opening of said rotatable member opposing to said developer receiving opening, and said developer receiving opening is closed by a portion of said rotatable member other than said opening opposing to said

15 developer receiving opening.

18. A developer supply cartridge according to any one of Claims 7, 8, 10 or 15, wherein said supplying-side movable portion is rotatable, and said supplying-side operating portion includes a projection having a portion extending along a rotational movement direction of said supplying-side movable portion, wherein said receiving-side movable portion is rotatable, and said receiving-side operating portion includes a projection having a portion extending along the rotational moving direction of said receiving-side movable portion, said projection of said supplying-

20

25

side movable portion is engageable with a projection of a receiving-side movable portion to receive a rotating force, thus rotating said supplying-side shutter portion.

5

19. A developer supply cartridge according to any one of Claims 7 - 18, further comprising a portion to be guided having a side surface to be regulated, an upper surface to be regulated, and a lower surface to be regulated, wherein when said developer supply cartridge enters the main assembly of the apparatus, said side surface to be regulated, said upper surface to be regulated and said lower surface to be regulated are regulated by a main assembly guide provided in the main assembly of the apparatus, and wherein in a state that said developer supplying-side movable portion is moving in engagement with said receiving-side movable portion, an upward movement of said upper surface to be regulated is regulated by the main assembly guide.

20

20. A developer supply cartridge according to Claim 9, wherein said engageable member is fixed at a position downstream of said supplying-side movable portion with respect to an entering direction in which said developer supply cartridge enters the main assembly of the apparatus.

21. A developer supply cartridge according to
Claim 10, further comprising an engageable member
fixed at a position downstream of said supplying-side
movable portion with respect to an entering direction
5 in which said developer supply cartridge enters the
main assembly of the apparatus, wherein when said
process cartridge is removed from the main assembly of
the apparatus, said engageable member releases, after
said supplying-side shutter portion closes said
10 developer supply opening, said receiving-side movable
portion from said regulating member by contacting said
regulating member which regulates movements of said
receiving-side movable portion with said receiving-
side shutter portion placed at said developer-
15 reception-permitting position to move said regulating
member, thus permitting movement of said receiving-
side movable portion, then said engageable member
engages with said receiving-side operating portion of
said receiving-side operating portion to rotate said
20 receiving-side movable portion to move said receiving-
side shutter portion from said developer-reception-
permitting position to said developer-reception-
preventing position.

25 22. An electrophotographic image forming apparatus
to which a process cartridge and a developer supply
cartridge for supplying a developer into the process

cartridge are detachably mountable, independently from each other, to a main assembly of the apparatus, said apparatus comprising:

- (i) a developer supply cartridge detachably mountable to the main assembly of the apparatus, said developer supply cartridge including,
 - a supplying-side developer accommodating portion for accommodating the developer,
 - a developer supply opening for supplying the developer from said supplying-side developer accommodating portion into said process cartridge,
 - a supplying-side shutter portion movable between a developer-supply-permitting position for opening said developer supply opening and a developer-supply-preventing position for closing said developer supply opening,
 - a supplying-side movable portion movable to interrelatedly move said supplying-side shutter portion between said developer-supply-permitting position and said developer-supply-preventing position, and
 - an engageable member; and
- (ii) a process cartridge detachably mountable to the main assembly of the apparatus, said process cartridge including,
 - an electrophotographic photosensitive drum,
 - a developing roller for developing an

electrostatic latent image formed on said electrophotographic photosensitive drum,

 a receiving-side developer accommodating portion for accommodating the developer,

5 a developer receiving opening for receiving the developer,

 a receiving-side shutter portion movable between a developer-reception-permitting position for opening said developer receiving opening and a

10 developer-reception-preventing position for closing said developer receiving opening, and

 a regulating member,

 a receiving-side movable portion movable to interrelatedly move said receiving-side shutter portion between the developer-reception-permitting position and the developer-reception-preventing position, said receiving-side movable portion including a first receiving-side operating portion which takes an operating position when said receiving-

15 side shutter portion is at the developer-reception-preventing position and a second receiving-side operating portion which takes the operating position when said receiving-side shutter portion is at the developer-reception-permitting position, wherein when

20 said process cartridge enters the main assembly of the apparatus with said regulating member regulating movement to place said first receiving-side operating

25

portion at the operating position in a state that said developer supply cartridge is set in the main assembly of the apparatus, said regulating member contacts the engageable member to release said receiving-side

5 movable portion, thus permitting movement of said receiving-side movable portion, then receiving-side movable portion moves said receiving-side shutter portion to the developer-reception-permitting position in interrelation with said first receiving-side

10 operating portion moved by contacting the engageable member, and then said receiving-side movable portion moves the supplying-side shutter portion to the developer-supply-permitting position in interrelation with the supplying-side movable portion moved by

15 engagement of said second receiving-side operating portion with the supplying-side movable portion while being regulated by said regulating member in a state that second receiving-side operating portion is placed at the operating position.

20

23. An electrophotographic image forming apparatus to which a process cartridge and a developer supply cartridge for supplying a developer into the process cartridge are detachably mountable, independently from

25 each other, to a main assembly of the apparatus, said apparatus comprising:

(i) a developer supply cartridge detachably

mountable to the main assembly of the apparatus, said developer supply cartridge including,

 a supplying-side developer accommodating portion for accommodating the developer,

5 a developer supply opening for supplying the developer from said supplying-side developer accommodating portion into said process cartridge,

 a supplying-side shutter portion movable between a developer-supply-permitting position for opening said developer supply opening and a developer-supply-preventing position for closing said developer supply opening,

10 a supplying-side movable portion movable to interrelatedly move the supplying-side shutter portion between the developer-supply-permitting position and the developer-supply-preventing position, and

 an engageable member; and

15 (ii) a process cartridge detachably mountable to the main assembly of the apparatus, said process cartridge including,

 an electrophotographic photosensitive drum,

 a receiving-side developer accommodating portion for accommodating the developer,

20 a developer receiving opening for receiving the developer,

 a receiving-side shutter portion movable between a developer-reception-permitting position for

opening said developer receiving opening and a developer-reception-preventing position for closing said developer receiving opening,

5 a regulating member, and

10 a receiving-side movable portion movable to interrelatedly move said receiving-side shutter portion between the developer-reception-permitting position and the developer-reception-preventing position, said receiving-side movable portion including a receiving-side operating portion which takes the operating position when said receiving-side shutter portion is at the developer-reception-permitting position, wherein when said process cartridge is removed from the main assembly of the

15 apparatus in a state that said developer supply cartridge is set in the main assembly of the apparatus, said receiving-side operating portion moves said supplying-side movable portion by engagement, with said supplying-side movable portion, of said receiving-side operating portion of said receiving-

20 side movable portion which is regulated by said regulating member in a state that receiving-side movable portion is placed at the operating position to interrelatedly move said supplying-side shutter portion to the developer-supply-preventing position,

25 then said regulating member contacts the engageable member to release said receiving-side movable portion,

thus permitting movement of said receiving-side movable portion, and receiving-side movable portion moves said receiving-side shutter portion to the developer-reception-preventing position in

5 interrelation with said receiving-side operating portion moved by contacting the engageable member.

24. An electrophotographic image forming apparatus to which a process cartridge and a developer supply

10 cartridge for supplying a developer into the process cartridge are detachably mountable, independently from each other, to a main assembly of the apparatus, said apparatus comprising:

(i) a process cartridge detachably mountable to

15 the main assembly of the apparatus, said process cartridge including,

an electrophotographic photosensitive drum,
a developing roller for developing an electrostatic latent image formed on said

20 electrophotographic photosensitive drum with the developer,

a receiving-side developer accommodating portion for accommodating the developer,
a developer receiving opening for receiving the

25 developer into said receiving-side developer accommodating portion,

a receiving-side shutter portion movable

between a developer-reception-permitting position for opening said developer receiving opening and a developer-reception-preventing position for closing said developer receiving opening,

5 a receiving-side movable portion movable to interrelatedly move said receiving-side shutter portion between the developer-reception-permitting position and the developer-reception-preventing position, said receiving-side movable portion

10 including a receiving-side operating portion which takes an operating position when said receiving-side shutter portion is at said developer-reception-permitting position, and

15 a regulating member for regulating movement of said receiving-side movable portion when said receiving-side operating portion is at the operating position,

(ii) a developer supply cartridge detachably mountable to the main assembly of the apparatus, said 20 developer supply cartridge including,

a supplying-side developer accommodating portion for accommodating the developer,

a developer supply opening for supplying the developer from said supplying-side developer 25 accommodating portion into said process cartridge through said developer receiving opening,

a supplying-side shutter portion movable

between a developer-supply-permitting position for opening said developer supply opening and a developer-supply-preventing position for closing said developer supply opening, and

- 5 a supplying-side movable portion movable, when said developer supply cartridge enters said main assembly of the apparatus in a state that process cartridge is set in said main assembly of the apparatus, to interrelatedly move said supplying-side
- 10 shutter portion from the developer-supply-preventing position to the developer-supply-permitting position by engagement with said receiving-side operating portion of said receiving-side movable portion, a movement of which is regulated by said regulating
- 15 member in a state that receiving-side operating portion is positioned at the operating position.

25. An electrophotographic image forming apparatus to which a process cartridge and a developer supply cartridge for supplying a developer into the process cartridge are detachably mountable, independently from each other, to a main assembly of the apparatus, said apparatus comprising:

- (i) a process cartridge detachably mountable to the main assembly of the apparatus, said process cartridge including,

an electrophotographic photosensitive drum,

a developing roller for developing an electrostatic latent image formed on said electrophotographic photosensitive drum with the developer,

5 a receiving-side developer accommodating portion for accommodating the developer,

a developer receiving opening for receiving the developer into said receiving-side developer accommodating portion,

10 a receiving-side shutter portion movable between a developer-reception-permitting position for opening said developer receiving opening and a developer-reception-preventing position for closing said developer receiving opening,

15 a receiving-side movable portion movable to interrelatedly move said receiving-side shutter portion between the developer-reception-permitting position and the developer-reception-preventing position, said receiving-side movable portion

20 including a receiving-side operating portion which takes an operating position when said receiving-side shutter portion is at said developer-reception-permitting position, and

25 a regulating member for regulating movement of said receiving-side movable portion when said receiving-side operating portion is at the operating position; and

(ii) a developer supply cartridge detachably mountable to the main assembly of the apparatus, said developer supply cartridge including, a supplying-side developer accommodating portion for 5 accommodating the developer, a developer supply opening for supplying the developer from said supplying-side developer accommodating portion into said process cartridge through said developer receiving opening,

10 a supplying-side shutter portion movable between a developer-supply-permitting position for opening said developer supply opening and a developer-supply-preventing position for closing said developer supply opening, and

15 a supplying-side movable portion movable, when said developer supply cartridge enters said main assembly of the apparatus in a state that process cartridge is set in said main assembly of the apparatus, to interrelatedly move said supplying-side shutter portion from the developer-supply-permitting position to the developer-supply-preventing position by engagement with said receiving-side operating portion of said receiving-side movable portion, a movement of which is regulated by said regulating 20 member in a state that receiving-side operating portion is positioned at the operating position.

25

26. An electrophotographic image forming apparatus to which a process cartridge and a developer supply cartridge for supplying a developer into the process cartridge are detachably mountable, independently from 5 each other, to a main assembly of the apparatus, said apparatus comprising:

(i) a process cartridge detachably mountable to the main assembly of the apparatus, said process cartridge including,

10 an electrophotographic photosensitive drum,
a developing roller for developing an electrostatic latent image formed on said electrophotographic photosensitive drum,
a receiving-side developer accommodating portion for accommodating the developer,
15 a developer receiving opening for receiving the developer into said receiving-side developer accommodating portion,
a receiving-side shutter portion movable between a developer-reception-permitting position for opening said developer receiving opening and a developer-reception-preventing position for closing said developer receiving opening,
20 a receiving-side movable portion rotatable to interrelatedly move said receiving-side shutter portion between the developer-reception-permitting position and the developer-reception-preventing

position, said receiving-side movable portion including a first receiving-side operating portion which takes an operating position when said receiving-side shutter portion is at said developer-reception-5 preventing position, and a second receiving-side operating portion which takes the operating position when said receiving-side shutter portion is at said developer-reception-permitting position, and a regulating member for regulating rotation of 10 said receiving-side movable portion when said first or second receiving-side operating portion is at the operating position; and

(ii) a developer supply cartridge detachably mountable to the main assembly of the apparatus, said 15 developer supply cartridge including,

a supplying-side developer accommodating portion for accommodating the developer,

a developer supply opening for supplying the developer from said supplying-side developer 20 accommodating portion into said process cartridge through said developer receiving opening,

a supplying-side shutter portion movable between a developer-supply-permitting position for opening said developer supply opening and a developer-25 supply-preventing position for closing said developer supply opening,

an engageable member fixed at a position

downstream of said developer supply opening with respect to an entering direction in which said developer supply cartridge enters said main assembly of the apparatus, wherein when said developer supply

5 cartridge enters the main assembly of the apparatus in a state that process cartridge is set in the main assembly of the apparatus, said engageable member releases, prior to said supplying-side shutter portion opening said developer supply opening, said receiving-

10 side movable portion from said regulating member by contacting said regulating member which regulates rotation of said receiving-side movable portion with said first receiving-side operating portion placed at said operating position to move said regulating member

15 downwardly against an elastic force, thus permitting movement of said receiving-side movable portion, then said engageable member engages with said first receiving-side operating portion to rotate said receiving-side movable portion and to interrelatedly

20 move said receiving-side shutter portion from said developer-reception-preventing position to said developer-reception-permitting position, wherein when said developer supply cartridge is removed from the main assembly of the apparatus in the state that

25 process cartridge is set in the main assembly of the apparatus, said engageable member releases, after said supplying-side shutter portion closes said developer

supply opening, said receiving-side movable portion from said regulating member by contacting said regulating member which regulates rotation of said receiving-side movable portion with said second 5 receiving-side operating portion placed at said operating position to move said regulating member downwardly against the elastic force, thus permitting movement of said receiving-side movable portion, then said engageable member engages with said second 10 receiving-side operating portion to rotate said receiving-side movable portion and to interrelatedly move said receiving-side shutter portion from said developer-reception-permitting position to said developer-reception-preventing position, and 15 a supplying-side movable portion for moving said supplying-side shutter portion from said developer-supply-preventing position to said developer-supply-permitting position and from said developer-supply-permitting position to said 20 developer-supply-preventing position, wherein when said developer supply cartridge enters the main assembly of the apparatus in a state that process cartridge is set in the main assembly of the apparatus, said supplying-side movable portion is rotated, after 25 said receiving-side shutter portion opens said developer receiving opening, by engagement with said receiving-side movable portion which is regulated by

said regulating member with said second receiving-side operating portion placed at said operating position, and in interrelation with rotation of said supplying-side movable portion, said supplying-side shutter portion is moved from said developer-supply-preventing position to said developer-supply-permitting position, and wherein said developer supply cartridge is removed from the main assembly of the apparatus in the state that process cartridge is set in the main assembly of the apparatus, said supplying-side movable portion is rotated, prior to said receiving-side shutter portion closes said developer receiving opening, by engagement with said receiving-side movable portion which is regulated by said regulating member with said second receiving-side operating portion placed at said operating position, and in interrelation with rotation of said supplying-side movable portion, said supplying-side shutter portion is moved from said developer-supply-permitting position to said developer-supply-preventing position.

27. An electrophotographic image forming apparatus to which a process cartridge and a developer supply cartridge for supplying a developer into the process cartridge are detachably mountable, independently from each other, to a main assembly of the apparatus, said apparatus comprising:

(i) a process cartridge detachably mountable to the main assembly of the apparatus, said process cartridge including,

an electrophotographic photosensitive drum,

5 a developing roller for developing an electrostatic latent image formed on said electrophotographic photosensitive drum,

a receiving-side developer accommodating portion for accommodating the developer,

10 a developer receiving opening for receiving the developer into said receiving-side developer accommodating portion,

a receiving-side shutter portion movable between a developer-reception-permitting position for

15 opening said developer receiving opening and a developer-reception-preventing position for closing said developer receiving opening,

a receiving-side movable portion rotatable to interrelatedly move said receiving-side shutter

20 portion between the developer-reception-permitting position and the developer-reception-preventing position, said receiving-side movable portion including a first receiving-side operating portion which takes an operating position when said receiving-

25 side shutter portion is at said developer-reception-preventing position, and a second receiving-side operating portion which takes the operating position

when said receiving-side shutter portion is at said developer-reception-permitting position, and

a regulating member for regulating rotation of said receiving-side movable portion when said first or

5 second receiving-side operating portion is at the operating position; and

(ii) a developer supply cartridge detachably mountable to the main assembly of the apparatus, said developer supply cartridge including, a

10 supplying-side developer accommodating portion for accommodating the developer,

a developer supply opening for supplying the developer from said supplying-side developer accommodating portion into said process cartridge

15 through said developer receiving opening,

a supplying-side shutter portion movable between a developer-supply-permitting position for opening said developer supply opening and a developer-supply-preventing position for closing said developer

20 supply opening,

a first engageable member fixed at a position upstream of said developer supply opening with respect to an entering direction in which said developer supply cartridge enters said main assembly of the

25 apparatus, wherein when said process cartridge enters the main assembly of the apparatus in a state that said developer supply cartridge is set in the main

assembly of the apparatus, said first engageable member releases, prior to said supplying-side shutter portion opening said developer supply opening, said receiving-side movable portion from said regulating member by contacting said regulating member which regulates rotation of said receiving-side movable portion with said first receiving-side operating portion placed at said operating position to move said regulating member downwardly against an elastic force, thus permitting movement of said receiving-side movable portion, then said first engageable member engages with said first receiving-side operating portion to rotate said receiving-side movable portion and to interrelatedly rotate said receiving-side shutter portion from said developer-reception-preventing position to said developer-reception-permitting position,

a second engageable member fixed at a position downstream of said developer supply opening with respect to the entering direction, wherein when said developer supply cartridge enters the main assembly of the apparatus in a state that process cartridge is set in the main assembly of the apparatus, said second engageable member releases, prior to said supplying-side shutter portion opening said developer supply opening, said receiving-side movable portion from said regulating member by contacting said regulating member

which regulates rotation of said receiving-side movable portion with said first receiving-side operating portion placed at said operating position to move said regulating member downwardly against an

5 elastic force, thus permitting movement of said receiving-side movable portion, then said second engageable member engages with said first receiving-side operating portion to rotate said receiving-side movable portion and to interrelatedly rotate said

10 receiving-side shutter portion from said developer-reception-preventing position to said developer-reception-permitting position, and

a supplying-side movable portion for rotating said supplying-side shutter portion from said

15 developer-supply-preventing position to said developer-supply-permitting position, wherein when said process cartridge enters the main assembly of the apparatus in a state that said developer supply cartridge is set in the main assembly of the apparatus,

20 said supplying-side movable portion is rotated, after said first engageable member causes said receiving-side shutter portion to open said developer receiving opening, by engagement with said receiving-side movable portion which is regulated by said regulating

25 member with said second receiving-side operating portion placed at said operating position, and in interrelation with rotation of said supplying-side

movable portion, said supplying-side shutter portion is rotated from said developer-supply-preventing position to said developer-supply-permitting position, and wherein when said developer supply cartridge

5 enters the main assembly of the apparatus in a state that process cartridge is set in the main assembly of the apparatus, said supplying-side movable portion is rotated, after said second engageable member causes said receiving-side shutter portion to open said

10 developer receiving opening, by engagement with said receiving-side movable portion which is regulated by said regulating member with said second receiving-side operating portion placed at said operating position, and in interrelation with rotation of said supplying-

15 side movable portion, said supplying-side shutter portion is rotated from said developer-supply-preventing position to said developer-supply-permitting position.

20 28. An electrophotographic image forming apparatus to which a process cartridge and a developer supply cartridge for supplying a developer into the process cartridge are detachably mountable, independently from each other, to a main assembly of the apparatus, said apparatus comprising:

25 (i) a process cartridge detachably mountable to the main assembly of the apparatus, said process

cartridge including,

an electrophotographic photosensitive drum,

a developing roller for developing an electrostatic latent image formed on said

5 electrophotographic photosensitive drum,

a receiving-side developer accommodating portion for accommodating the developer,

a developer receiving opening for receiving the developer into said receiving-side developer

10 accommodating portion,

a receiving-side shutter portion movable between a developer-reception-permitting position for opening said developer receiving opening and a developer-reception-preventing position for closing

15 said developer receiving opening,

a receiving-side movable portion rotatable to interrelatedly move said receiving-side shutter portion between the developer-reception-permitting position and the developer-reception-preventing

20 position, said receiving-side movable portion including a first receiving-side operating portion which takes an operating position when said receiving-side shutter portion is at said developer-reception-preventing position, and a second receiving-side

25 operating portion which takes the operating position when said receiving-side shutter portion is at said developer-reception-permitting position, and

a regulating member for regulating rotation of said receiving-side movable portion when said first or second receiving-side operating portion is at the operating position; and

5 (ii) a developer supply cartridge detachably mountable to the main assembly of the apparatus, said developer supply cartridge including,

a supplying-side developer accommodating portion for accommodating the developer,

10 a developer supply opening for supplying the developer from said supplying-side developer accommodating portion into said process cartridge through said developer receiving opening,

a supplying-side shutter portion movable 15 between a developer-supply-permitting position for opening said developer supply opening and a developer-supply-preventing position for closing said developer supply opening,

a first engageable member fixed at a position 20 upstream of said developer supply opening with respect to an entering direction in which said developer supply cartridge enters said main assembly of the apparatus, wherein when said process cartridge is removed from the main assembly of the apparatus in a 25 state that said developer supply cartridge is set in the main assembly of the apparatus, said first engageable member releases, after said supplying-side

shutter portion closes said developer supply opening, said receiving-side movable portion from said regulating member by contacting said regulating member which regulates rotation of said receiving-side

5 movable portion with said second receiving-side operating portion placed at said operating position to move said regulating member downwardly against an elastic force, thus permitting movement of said receiving-side movable portion, then said first

10 engageable member engages with said second receiving-side operating portion to rotate said receiving-side movable portion and to interrelatedly rotate said receiving-side shutter portion from said developer-reception-permitting position to said developer-reception-preventing position,

15 a second engageable member fixed at a position downstream of said developer supply opening with respect to the entering direction, wherein when said developer supply cartridge is removed from the main

20 assembly of the apparatus in a state that process cartridge is set in the main assembly of the apparatus, said second engageable member releases, after said supplying-side shutter portion closes said developer supply opening, said receiving-side movable portion

25 from said regulating member by contacting said regulating member which regulates rotation of said receiving-side movable portion with said second

receiving-side operating portion placed at said operating position to move said regulating member downwardly against an elastic force, thus permitting movement of said receiving-side movable portion, then

5 said second engageable member engages with said second receiving-side operating portion to rotate said receiving-side movable portion and to interrelatedly rotate said receiving-side shutter portion from said developer-reception-permitting position to said developer-reception-preventing position, and

10 developing-side movable portion for rotating said supplying-side shutter portion from said developer-supply-permitting position to said developer-supply-preventing position, wherein when

15 said process cartridge is removed from the main assembly of the apparatus in a state that said developer supply cartridge is set in the main assembly of the apparatus, said supplying-side movable portion is rotated, prior to said first engageable member

20 causing said receiving-side shutter portion to close said developer receiving opening, by engagement with said receiving-side movable portion which is regulated by said regulating member with said second receiving-side operating portion placed at said operating

25 position, and in interrelation with rotation of said supplying-side movable portion, said supplying-side shutter portion is moved from said developer-supply-

permitting position to said developer-supply-preventing position, and wherein when said developer supply cartridge is removed from the main assembly of the apparatus in a state that process cartridge is set 5 in the main assembly of the apparatus, said supplying-side movable portion is rotated, prior to said second engageable member causing said receiving-side shutter portion to close said developer receiving opening, by engagement with said receiving-side movable portion 10 which is regulated by said regulating member with said second receiving-side operating portion placed at said operating position, and in interrelation with rotation of said supplying-side movable portion, said supplying-side shutter portion is moves from said 15 developer-supply-permitting position to said developer-supply-preventing position.

29. An apparatus according to any one of Claims 22 - 28, wherein said receiving-side movable portion is 20 disposed on an upper surface of said process cartridge in a state that process cartridge is mounted to the main assembly of the apparatus, and is rotatable about a horizontal axis crossing with a longitudinal direction of said process cartridge.

25

30. An apparatus according to any one of Claims 22 - 29, wherein said receiving-side shutter portion is

disposed on an upper surface of said process cartridge in a state that process cartridge is mounted to the main assembly of the apparatus and includes a rotatable member rotatable about a horizontal axis 5 crossing with a longitudinal direction of said process cartridge, said rotatable member being provided with an opening which opens in a radial direction of rotation of said rotatable member, wherein said developer receiving opening is opened by said opening 10 of said rotatable member opposing to said developer receiving opening, and said developer receiving opening is closed by a portion of said rotatable member other than said opening opposing to said developer receiving opening.

15

31. An apparatus according to according to Claim 22, wherein said receiving-side movable portion is rotatable, wherein said first receiving-side operating portion includes a projection having a portion 20 extending along a rotational movement direction of said receiving-side movable portion, and said projection receives a force by engagement with said engageable member to rotate said receiving-side shutter portion, wherein said second receiving-side 25 operating portion includes a projection having a portion extending along the rotational moving direction of said receiving-side movable portion, said

projection of said second receiving-side operating portion is engageable with a projection of a supplying-side operating portion of said supplying-side movable portion to apply a rotating force, thus

5 rotating said supplying-side shutter portion.

32. An apparatus according to according to Claim 22, wherein said receiving-side movable portion is rotatable, wherein said receiving-side operating portion includes a projection having a portion extending along a rotational moving direction of said receiving-side movable portion, and a supplying-side operating portion of said supplying-side movable portion includes a projection having a portion extending along a rotational moving direction of said supplying-side movable portion, wherein said supplying-side shutter portion is rotated by said projection of said receiving-side movable portion engaging said projection of said supplying-side movable portion and applying a rotating force.

10

15

20

33. An apparatus according to according to any one of Claims 22 - 25, further comprising a engageable member fixed at a position downstream of said supplying-side movable portion with respect to an entering direction in which said developer supply cartridge enters the main assembly of the apparatus,

25

wherein when said developer supply cartridge enters the main assembly of the apparatus, said engageable member releases, prior to said supplying-side shutter portion opening said developer supply opening, said 5 receiving-side movable portion from said regulating member by contacting said regulating member which regulates rotation of said receiving-side movable portion with said receiving-side shutter portion placed at said developer-reception-preventing position 10 to move said regulating member, thus permitting movement of said receiving-side movable portion, then said engageable member engages with a first receiving-side operating portion to rotate said receiving-side movable portion, thus moving said receiving-side 15 shutter portion from said developer-reception-preventing position to said developer-reception-permitting position.

34. An apparatus according to according to any one 20 of Claims 23 - 25, further comprising an engageable member fixed at a position upstream of said supplying-side movable portion with respect to a removing direction in which said developer supply cartridge is removed from the main assembly of the apparatus, 25 wherein when said developer supply cartridge is removed from the main assembly of the apparatus, said engageable member releases, after said supplying-side

shutter portion closes said developer supply opening, said receiving-side movable portion from said regulating member by contacting said regulating member which regulates rotation of said receiving-side 5 movable portion with said receiving-side shutter portion placed at said developer-reception-permitting position to move said regulating member, thus permitting movement of said receiving-side movable portion, then said engageable member engages with a 10 receiving-side operating portion to rotate said receiving-side movable portion, thus moving said receiving-side shutter portion from said developer-reception-permitting position to said developer-reception-preventing position.

15

35. An apparatus according to according to any one of Claims 22 - 34, wherein said supplying-side movable portion is disposed on a lower surface of said developer supply cartridge in a state that said 20 developer supply cartridge is mounted to the main assembly of the apparatus, and is rotatable about a horizontal axis crossing with a longitudinal direction of said developer supply cartridge.

25

36. An apparatus according to according to any one of Claims 22 - 35, wherein said supplying-side shutter portion is disposed on a lower surface of said

developer supply cartridge in a state that said developer supply cartridge is set in the main assembly of the apparatus and includes a rotatable member rotatable about a horizontal axis crossing with a 5 longitudinal direction of said developer supply cartridge, said rotatable member being provided with an opening which opens in a radial direction of rotation of said rotatable member, wherein said developer receiving opening is opened by said opening 10 of said rotatable member opposing to said developer receiving opening, and said developer receiving opening is closed by a portion of said rotatable member other than said opening opposing to said developer receiving opening.

15

37. An apparatus according to according to any one of Claims 23 - 25, wherein said supplying-side movable portion is rotatable, and said supplying-side operating portion includes a projection having a 20 portion extending along a rotational movement direction of said supplying-side movable portion, wherein said receiving-side movable portion is rotatable, and said receiving-side operating portion includes a projection having a portion extending along 25 the rotational moving direction of said receiving-side movable portion, said projection of said supplying-side movable portion is engageable with a projection

of a receiving-side movable portion to receive a rotating force, thus rotating said supplying-side shutter portion.

5 38. An apparatus according to according to any one of Claims 22 - 37, further comprising a portion to be guided having a side surface to be regulated, an upper surface to be regulated, and a lower surface to be regulated, wherein when said developer supply

10 cartridge enters the main assembly of the apparatus, said side surface to be regulated, said upper surface to be regulated and said lower surface to be regulated are regulated by a main assembly guide provided in the main assembly of the apparatus, and wherein in a state

15 that said developer supplying-side movable portion is moving in engagement with said receiving-side movable portion, an upward movement of said upper surface to be regulated is regulated by the main assembly guide.

20 39. An apparatus according to according to Claim 22 or 23, wherein said engageable member is fixed at a position downstream of said supplying-side movable portion with respect to an entering direction in which said developer supply cartridge enters the main

25 assembly of the apparatus.

40. An apparatus according to according to Claim

24 or 25, further comprising an engageable member fixed at a position downstream of said supplying-side movable portion with respect to an entering direction in which said developer supply cartridge enters the 5 main assembly of the apparatus, wherein when said process cartridge is removed from the main assembly of the apparatus, said engageable member releases, after said supplying-side shutter portion closes said developer supply opening, said receiving-side movable 10 portion from said regulating member by contacting said regulating member which regulates movements of said receiving-side movable portion with said receiving-side shutter portion placed at said developer-reception-permitting position to move said regulating 15 member, thus permitting movement of said receiving-side movable portion, then said engageable member engages with said receiving-side operating portion of said receiving-side operating portion to rotate said receiving-side movable portion to move said receiving-side shutter portion from said developer-reception-permitting position to said developer-reception-preventing position.









FIG. 1


**FIG.2**


3/29


**FIG.3****FIG.4**


**FIG.5**

**FIG.6**

**FIG.7**

**FIG.8**

**FIG.9**

**FIG.10**




FIG. 11






FIG.12


12/29

(a)




(b)

**FIG.13**


**FIG.14**

14/29


**FIG.15**

15/29



(a)



(b)

**FIG. 16**

16/29

**FIG. 17****FIG. 18**

17/29








FIG.19

**FIG. 20(a)****FIG. 20(b)**



19/29

**FIG.20(c)**



20/29

**FIG.21**


21/29

**FIG.22(a)****FIG.22(b)**


22/29

**FIG.22(c)****FIG.22(d)**

23/29

**FIG.22(e)**

24/29

**FIG.23**

25/29







FIG.24

26/29


**FIG.25**

27/29

**FIG.26**

**FIG.27**

29/29

**FIG.28**

INTERNATIONAL SEARCH REPORT

International application No

PCT/JP2007/050541

A. CLASSIFICATION OF SUBJECT MATTER
INV. G03G15/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
G03G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 7 010 250 B1 (YAHAGI TAKASHI [JP]) 7 March 2006 (2006-03-07) cited in the application the whole document -----	1-40
A	US 2002/085857 A1 (KIM KYUNG-HWAN [KR] ET AL) 4 July 2002 (2002-07-04) paragraph [0031] - paragraph [0065]; figures 1,2,6-8 -----	1,2, 7-13, 22-28

 Further documents are listed in the continuation of Box C. See patent family annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

13 April 2007

26/04/2007

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Borowski, Michael

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/JP2007/050541

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
US 7010250	B1	07-03-2006	CN	1298126 A 06-06-2001
			CN	1512277 A 14-07-2004
			CN	1512278 A 14-07-2004
			CN	1512279 A 14-07-2004
			EP	1103865 A2 30-05-2001
			JP	2001222160 A 17-08-2001
			KR	20010061976 A 07-07-2001
US 2002085857	A1	04-07-2002	JP	3418618 B2 23-06-2003
			JP	2002214898 A 31-07-2002
			KR	20020058323 A 12-07-2002