



US009626619B2

(12) **United States Patent**
Kruest et al.

(10) **Patent No.:** **US 9,626,619 B2**
(45) **Date of Patent:** **Apr. 18, 2017**

(54) **SYSTEMS AND METHODS FOR SYNCHRONIZING A PLURALITY OF RFID INTERROGATORS IN A THEATRE OF OPERATION**

(71) Applicant: **NEOLOGY, INC.**, Poway, CA (US)

(72) Inventors: **James Robert Kruest**, San Diego, CA (US); **Gary Bann**, San Diego, CA (US)

(73) Assignee: **NEOLOGY, INC.**, Poway, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/007,079**

(22) Filed: **Jan. 26, 2016**

(65) **Prior Publication Data**

US 2016/0162776 A1 Jun. 9, 2016

Related U.S. Application Data

(63) Continuation of application No. 14/225,359, filed on Mar. 25, 2014, now Pat. No. 9,247,634, which is a (Continued)

(51) **Int. Cl.**

G06K 7/10 (2006.01)

G06K 19/077 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **G06K 19/07796** (2013.01); **G06K 7/0008** (2013.01); **G06K 7/10029** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC **G06K 19/07796**; **G06K 19/0723**; **G06K 19/07798**; **G06K 7/0008**; **G06K 7/10039**;

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,538,564 A 11/1970 Skoler et al.

4,660,127 A 4/1987 Gunter

(Continued)

FOREIGN PATENT DOCUMENTS

GB 2328839 A 3/1999

JP 2009250849 A 10/2009

MX 297024 6/2007

OTHER PUBLICATIONS

International Search Report and Written Opinion received in related International application No. PCTUS2007071823, mailed Feb. 14, 2008, 5 pages.

Primary Examiner — Brian Zimmerman


Assistant Examiner — Sara Samson

(74) *Attorney, Agent, or Firm* — Procopio, Cory, Hargreaves & Savitch LLP; Noel Gillespie

(57) **ABSTRACT**

RFID tags are used for many purpose including tracking. RFID interrogators are used to retrieve information from tags. In many applications, a plurality of RFID interrogators are required. Synchronization between interrogators in the same theatre of operation is critical to ensure that their broadcasts do not interfere with each other. In fixed RFID interrogator applications, RFID interrogators can be wired together allowing a channel to synchronize the transmissions of the RFID interrogators. Methods described herein can ensure that synchronization is maintained in the event of the failure of a synchronizing master. Furthermore, additional methods for synchronizing RFID interrogators in wireless applications are described allowing synchronization in the absence of wired connections between interrogators.

20 Claims, 11 Drawing Sheets



Related U.S. Application Data					
	continuation of application No. 11/766,749, filed on Jun. 21, 2007, now Pat. No. 8,680,973.	8,179,265 B2	5/2012	Elizondo et al.	
		8,427,279 B2 *	4/2013	Gravelle	G06K 7/0008 340/10.1
		8,451,095 B2	5/2013	Azevedo et al.	
		8,610,580 B2	12/2013	Elizondo et al.	
(60)	Provisional application No. 60/805,423, filed on Jun. 21, 2006.	2002/0048462 A1	4/2002	Weinberger et al.	
		2002/0063622 A1 *	5/2002	Armstrong	G06K 7/0008 340/10.31
(51)	Int. Cl.	2002/0109636 A1	8/2002	Johnson et al.	
	H04J 3/06 (2006.01)	2002/0123521 A1	9/2002	Lavin	
	G06K 7/00 (2006.01)	2002/0196126 A1	12/2002	Eisenberg et al.	
	G06K 19/07 (2006.01)	2004/0046663 A1	3/2004	Jesser	
	G06Q 10/08 (2012.01)	2004/0070953 A1	4/2004	Schulz et al.	
	H05K 1/02 (2006.01)	2004/0085192 A1	5/2004	Hartmann	
	H05K 1/14 (2006.01)	2004/0150521 A1	8/2004	Stilp	
	H05K 3/30 (2006.01)	2004/0212542 A1	10/2004	Rahim	
(52)	U.S. Cl.	2005/0077353 A1	4/2005	Oishi et al.	
	CPC	2005/0110641 A1	5/2005	Mendolia et al.	
	G06K 7/10039 (2013.01); G06K 19/0723 (2013.01); G06K 19/07798 (2013.01); G06Q 10/08 (2013.01); H04J 3/0641 (2013.01); H05K 1/0266 (2013.01); H05K 1/0268 (2013.01); H05K 1/142 (2013.01); H05K 3/30 (2013.01)	2005/0186902 A1	8/2005	Lieffort et al.	
		2005/0242953 A1	11/2005	Nakagawa et al.	
		2005/0248455 A1	11/2005	Pope et al.	
		2006/0001585 A1	1/2006	Saito et al.	
		2006/0006986 A1 *	1/2006	Gravelle	G06K 7/0008 340/10.3
		2006/0012465 A1	1/2006	Lee	
		2006/0022815 A1 *	2/2006	Fischer	G06K 7/0008 340/505
(58)	Field of Classification Search	2006/0052055 A1	3/2006	Rowse et al.	
	CPC	2006/0055539 A1	3/2006	Lawrence et al.	
	G06Q 10/08 ; H04J 3/0641 ; H05K 1/0266 ; H05K 1/0268 ; H05K 1/142 ; H05K 3/30	2006/0076401 A1 *	4/2006	Frerking	G06K 7/0008 235/380
	See application file for complete search history.	2006/0081333 A1	4/2006	Hohberger et al.	
(56)	References Cited	2006/0092040 A1 *	5/2006	Fishkin	G06K 7/10079 340/10.1
	U.S. PATENT DOCUMENTS	2006/0132313 A1	6/2006	Moskowitz	
		2006/0145864 A1	7/2006	Jacobson et al.	
		2006/0158311 A1	7/2006	Hall et al.	
		2006/0158313 A1 *	7/2006	Satou	G06K 7/0008 340/10.2
	4,935,907 A 6/1990 Friedman	2006/0176152 A1	8/2006	Wagner et al.	
	5,117,746 A 6/1992 Sharp	2006/0223340 A1	10/2006	Yoneda	
	5,640,151 A * 6/1997 Reis	2006/0279406 A1 *	12/2006	Stewart	G06K 7/10356 340/10.1
	5,689,238 A 11/1997 Cannon et al.	2007/0000989 A1	1/2007	Kadaba	
	5,751,220 A 5/1998 Ghaffari et al.	2007/0046467 A1 *	3/2007	Chakraborty	G06K 7/0008 340/572.1
	5,942,977 A 8/1999 Palmer et al.	2007/0057057 A1 *	3/2007	Andresky	G06K 7/0008 235/451
	6,034,603 A * 3/2000 Steeves	2007/0096911 A1	5/2007	Gualtieri	
		2007/0126554 A1 *	6/2007	Choi	G06K 7/0008 340/10.1
	6,060,992 A 5/2000 Huang et al.	2007/0137163 A1 *	6/2007	Hess	D07B 1/02 57/210
	6,118,379 A 9/2000 Kodukula et al.	2007/0171071 A1	7/2007	Chiu et al.	
	6,259,353 B1 7/2001 Berger et al.	2007/0173970 A1	7/2007	Shachar	
	6,330,971 B1 12/2001 Mabry et al.	2007/0279233 A1	12/2007	Ryckman	
	6,424,260 B2 7/2002 Maloney	2008/0024273 A1	1/2008	Kruest et al.	
	6,563,425 B2 5/2003 Nicholson et al.	2008/0055094 A1	3/2008	Barber et al.	
	6,643,801 B1 11/2003 Jammu et al.	2008/0129485 A1 *	6/2008	Tuttle	G06K 7/0008 340/539.11
	6,720,930 B2 4/2004 Johnson et al.	2008/0297312 A1 *	12/2008	Moshfeghi	H04L 47/10 340/10.1
	6,724,308 B2 4/2004 Nicholson	2008/0315992 A1	12/2008	Forster	
	6,750,771 B1 6/2004 Brand	2009/0079568 A1	3/2009	Forster et al.	
	6,812,838 B1 11/2004 Maloney	2010/0141392 A1 *	6/2010	Jo	G06K 7/0008 340/10.2
	6,983,033 B1 1/2006 Jenkins	2010/0148931 A1 *	6/2010	Pappu	G06K 7/0008 340/10.2
	6,989,796 B2 1/2006 Rahim	2011/0050426 A1	3/2011	Choong	
	7,075,435 B2 7/2006 Jesser	2011/0133899 A1	6/2011	Shachar	
	7,129,840 B2 10/2006 Hull et al.	2011/0163849 A1	7/2011	Kruest et al.	
	7,176,799 B1 2/2007 Golicz et al.				
	7,183,922 B2 2/2007 Mendolia et al.				
	7,295,120 B2 11/2007 Waldner et al.				
	7,336,174 B1 2/2008 Maloney				
	7,342,499 B2 3/2008 Chiu et al.				
	7,391,325 B2 6/2008 Cobianu et al.				
	7,432,816 B1 10/2008 Ku et al.				
	7,701,351 B2 4/2010 Kawai et al.				
	7,884,725 B2 2/2011 Kruest et al.				
	7,893,833 B2 2/2011 Shachar				
	7,969,282 B2 * 6/2011 Powell				G06K 7/10356 340/10.2
	8,072,326 B2 12/2011 Cotton				
	8,098,134 B2 1/2012 Azevedo et al.				

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

**SYSTEMS AND METHODS FOR
SYNCHRONIZING A PLURALITY OF RFID
INTERROGATORS IN A THEATRE OF
OPERATION**

RELATED APPLICATIONS INFORMATION

This present application is a continuation of U.S. patent application Ser. No. 14/225,359, filed on Mar. 25, 2014, entitled "Systems And Methods For Synchronizing A Plurality Of RFID Interrogators In A Theatre Of Operation" which claims the benefit of priority as a Continuation under 35 U.S.C. §120 of U.S. patent application Ser. No. 11/766,749, filed Jun. 21, 2007, entitled "Systems And Methods For Synchronizing A Plurality Of RFID Interrogators In A Theatre Of Operation," which in turn claims the benefit of priority under 35 U.S.C. 119(e) to Provisional Patent Application Ser. No. 60/805,423, entitled "RFID Smart Cabinet And A Multidocument Read/Write Station," filed Jun. 21, 2006, all of which are incorporated herein by reference as if set forth in full.

BACKGROUND

1. Field of the Invention

The field of the invention relates generally to Radio Frequency Identification (RFID) systems and more particularly to systems and methods for synchronizing a plurality of RFID interrogators in a theatre of operation.

2. Background of the Invention

FIG. 1 illustrates a basic RFID system **100**. A basic RFID system **100** comprises three components: an antenna or coil **104**, an interrogator **102** with decoder **112**, and a transponder, or RF tag **106** which is often electronically programmed with unique information. Antenna **104** emits radio signals **110** to activate and read and write data to tag **106**. Antenna **104** is the conduit between tag **106** and interrogator **102**, which controls data acquisition and communication. Antennas **104** are available in a variety of shapes and size, for example, in certain embodiments they can be built into a door frame to receive tag data from persons or things passing through the door. In other embodiments, antennas **104** can, for example, be mounted on an interstate toll booth to monitor traffic passing by on a freeway. Further, depending on the embodiments, the electromagnetic field, i.e., radio signal **110**, produced by an antenna **104** can be constantly present when, e.g., multiple tags **106** are expected continually. If constant interrogation is not required, then radio signal **110** can, for example, be activated by a sensor device.

Often antenna **104** is packaged with interrogator **102**. A conventional interrogator **102** can emit radio signals **110** in ranges of anywhere from one inch to 100 feet or more, depending upon the power output and the radio frequency used. When an RFID tag **106** passes through an electromagnetic zone associated with radio signal **106**, it detects radio signal **106**, which can comprise an activation signal. In some embodiments, interrogators can comprise multiple antenna, though typically only one transmits at a time.

RFID tags **106** come in a wide variety of shapes and sizes. Animal tracking tags, for example, inserted beneath the skin of an animal, can be as small as a pencil lead in diameter and one-half inch in length. Tags **106** can be screw-shaped for insertion, e.g., in order to identify trees or wooden items, or credit-card shaped for use in access applications. Anti-theft hard plastic tags that include RFID tags **106** can be attached to merchandise in stores. Heavy-duty RFID tags can be used to track intermodal containers, heavy machinery, trucks,

and/or railroad cars for maintenance and/or tracking purposes. A multitude of other uses and applications also exists, and many more will come into being in the future.

RFID tags **106** are categorized as either active or passive. Active RFID tags **106** are powered by an internal battery at and are typically read/write, i.e., tag data can be rewritten and/or modified. An active tag's memory size varies according to application requirements. For example, some systems operate with up to 1 MB of memory. In a typical read/write RFID work-in-process system, a tag **106** might give a machine a set of instructions, and the machine would then report its performance to tag **106**. This encoded data would then become part of the tagged part's history. The battery-supplied power of an active tag **106** generally gives it a longer read and write range. The trade off is greater size, greater cost, and a limited operational life.

Passive RFID tags **106** operate without a separate external power source and obtain operating power generated from radio signal **110**. Passive tags **106** are consequently much lighter than active tags **106**, less expensive, and offer a virtually unlimited operational lifetime. The trade off is that they have shorter read ranges than active tags **106** and require a higher-powered interrogator **102**. Read-only tags are typically passive and are programmed with a unique set of data, usually 32 to 128 bits, that cannot be modified. Read-only tags **106** often operate as a license plate into a database, in the same way as linear barcodes reference a database containing modifiable product-specific information. Not all passive tags **106** are read-only tags.

RFID systems are also distinguishable by their frequency ranges. Low-frequency, e.g., 30 KHz to 500 KHz, systems have short reading ranges and lower system costs. They are commonly used in security access, asset tracking, and animal identification applications. High-frequency, e.g., 850 MHz to 950 MHz and 2.4 GHz to 2.5 GHz, systems offer long read ranges, e.g., greater than 90 feet, high reading speeds, and are used for such applications as railroad car tracking and automated toll collection, however, the higher performance of high-frequency RFID systems **100** incurs higher system costs.

The significant advantage of all types of RFID systems **100** is the noncontact, non-line-of-sight nature of the technology. Tags **106** can be read through a variety of substances such as snow, fog, ice, paint, crusted grime, and other visually and environmentally challenging conditions, where barcodes or other optically read technologies cannot typically be used. RFID tags **106** can also be read in challenging circumstances at high speeds, often responding in less than 100 milliseconds. RFID has become indispensable for a wide range of automated data collection and identification applications that would not be possible otherwise.

A conventional RFID interrogator **102** comprises an RF transceiver **106** and a decoder **112**. Decoder **112** can, for example, be a micro controller or other processing circuit configured to carryout the required functions. Often, decoder **112** is interfaced with memory **114**. Firmware instructions used by decoder **112** to control the operation of interrogator **102** can be stored in memory **114**, along with RFID instructions that can be communicated to RFID tag **106** and can be used to control acquisition of information from RFID tags **106**. Memory **114** can, depending on the embodiment, comprise one or more memory circuits.

FIG. 2 shows an example transmission operation of an RFID interrogator. Graph **200** shows a transmission of the RFID interrogator when no data is transmitted. At the start of each frame **202**, interrogator **102** can be configured to transmit frame synchronization pulses **204**, which can have

a much shorter width than the period associated with frame 202. RFID interrogator 102 can transmit data to RFID tag 106 by modifying the frame synchronization pulses, for instance by doubling the pulses to represent a binary “zero” and tripling the synchronization pulses to represent a binary “one.” Graph 220 shows an example of such a transmission method by an RFID interrogator. Double pulses 222 and 230, which comprise two pulses sent within a short period compared to the frame period; represent the transmission of a “zero.” Triple pulse 226, which comprise three pulses sent within a short period compared to the frame period, represent the transmission of a “one.” Remaining single pulses 224 and 228 do not represent data and synchronize the associated frames.

Another method of modifying frame synchronization pulses used by RFID interrogators is to use wider pulses to represent a “zero” and still wider pulses to represent a “one.” Graph 240 shows an example of such a transmission method. The “wider” pulses 242 and 250, which are still short compared to the frame period, represent the transmission of a “zero.” The “widest” pulse 246, which is still short compared to the frame period but wider than pulses 242 and 250, represent the transmission of a “one.” The remaining “normal” width pulses 244 and 248 do not represent data and synchronize the associated frames 202.

Graphs 220 and 240 illustrate just two possible examples of communication protocols that can be used to facilitate transmission of data in system 100.

In response to interrogation signals from the interrogator 102, RFID tags 106 can be configured to respond in the second half of frames 202. Furthermore, in many embodiments of an RFID interrogation systems 100 both tags 106 and interrogator 102 operate in the same frequency range. The synchronization pulses, whether “normal” or modified to carry data can serve two additional purposes. First, the pulses can be used to define the boundaries of frames 202 so the tags 106 can respond at the appropriate time. Second, the pulses supply power for passive RFID tags 106.

FIG. 3 depicts an interrogation theatre 300 comprising a plurality of interrogators, of which interrogators 310 and 340 are shown for illustrative purposes. In addition, theatre 300 comprises a plurality of tags, of which tags 320, 322, and 344 are shown for illustrative purposes. Tags 320, 322, and 344 can for example, be similar to, or the same as, tag 106 described above. If allowed to operate independently, these readers can severely interfere with each other. To illustrate, in FIG. 3, RFID tags 320 and 322 are near interrogator 310, while RFID tag 344 is near interrogator 340. Temporally, interrogator 310 has just transmitted its request through its antenna 312 and is now awaiting a response signal from any nearby RFID tags. Because RFID tags 320 and 322 are near to interrogator 310, they respond with RF signals 330 and 332, respectively; however, at approximately the same time, interrogator 340 wishes to interrogate RFID tags nearby such as RFID tag 344, by transmitting signal 346 through antenna 342. Since the responses 330 and 332 are on the same frequency as the interrogation signal 346, and interrogation signal 346 can be of greater power than signals 330 and 332, interrogator 310 may only detect the signal from interrogator 340 rather than from RFID tags 320 and 322.

FIG. 4 depicts the timing of the example given above. Graph 400 depicts interrogator 310 attempting to interrogate nearby RFID tags using the communications protocol illustrated by graph 220. RFID tag 320 responds and its RF output signal 330 is graphed over time in graph 410; however, with an unsynchronized RFID interrogator 340

also attempting to interrogate nearby RFID tags as depicted in graph 420, associated signal 346 can interfere with signal 330. As a result, antenna 312 sees the signal depicted in graph 430, where rather than seeing pulses 412 and 414 of signal 330 (graph 410), interrogator 310 is likely to see something like pulses 432 and 436 dominated by the influence of signal 346 (graph 420) of interrogator 340. As a result, interrogator 310 may interpret pulses 434 and 438 of interrogator 340 as coming from RFID tag 320, or interrogator 310 may just fail to code any signal or may receive corrupted information.

SUMMARY

An RFID system comprises a plurality of synchronized RFID interrogators. Synchronization between interrogators in the same theatre of operation can be critical to ensure that their broadcasts do not interfere with each other. In fixed RFID interrogator applications, RFID interrogators can be wired together to allow synchronization of transmissions of the RFID interrogators.

In one aspect, synchronization is maintained in the event of the failure of a synchronizing master.

In another aspect, synchronizing RFID interrogators in the absence of wired connections between interrogators is provided.

These and other features, aspects, and embodiments of the invention are described below in the section entitled “Detailed Description.”

BRIEF DESCRIPTION OF THE DRAWINGS

Features, aspects, and embodiments of the inventions are described in conjunction with the attached drawings, in which:

FIG. 1 is a diagram illustrating an exemplary RFID system 100;

FIG. 2 is a diagram illustrating example transmission protocols that can be used in the system of FIG. 1;

FIG. 3 is a diagram illustrating an exemplary interrogation theatre comprising a plurality of interrogators;

FIG. 4 is a diagram illustrating example signals and timing for the theatre of FIG. 3;

FIG. 5 is a diagram illustrating an example baggage tracking system that includes a plurality of interrogators synchronized in accordance with one embodiment;

FIG. 6 is a diagram illustrating example signals and timing for the system of FIG. 5;

FIG. 7 is a diagram illustrating a temporal overview of a self-promotion process for synchronized interrogators in accordance with one embodiment;

FIG. 8 is a flowchart illustrating an example method for interrogator promotion in accordance with one embodiment;

FIG. 9 is a flowchart illustrating an example method for adjusting frame synchronization pulses, when interference is detected in accordance with one embodiment;

FIG. 10 is a diagram illustrating an example embodiment of RFID tag response encoding in accordance with one embodiment; and

FIG. 11 is a diagram illustrating an example detecting interference in accordance with one embodiment.

DETAILED DESCRIPTION

In one embodiment, synchronization signal 512 supplied by synchronization master 510 can be used by interrogators 520, 530, and 540 to ensure that the corresponding interro-

gator signals **524**, **534**, and **544** do not interfere with reception of signals transmitted by RFID tags **550-564**. For example, if graphs **620**, **630**, and **640** correspond to signals **544**, **534**, and **524**, respectively, then it can be seen that synchronization signal **512** (graph **610**) can cause each interrogator to begin transmission at the start of a common frame period. In other words, interrogators **520**, **530**, and **540** can be configured such that each interrogator upon receipt of a pulse in signal **512**. This can ensure that each interrogator is finished transmitting before the start of the second half of frame **604**, devoted by dashed line **606** during which responses from RFID tags **550-564** we received. Thus, interference signals **524**, **534**, and **544** with those transmitted from RFID tags **550-564** can be avoided.

As mentioned above, the start **602** of frames **604**, depending on the requirements of a particular implementation, begin some fixed period (Δd) after the rising edge of the pulses comprising signal **512** as illustrated on graph **610**. The delay (Δd) can, for example, be long enough to account for various delays associated with the circuitry comprising interrogators **520**, **530**, and **540**.

In order to avoid the problem illustrated in FIGS. **3** and **4**, for example, interrogators in a theatre of operation **300** can be synchronized as described herein. FIGS. **5** and **6** illustrate an embodiment of a system **500** with multiple interrogators in a single theatre of operation. In one embodiment, for example, such a system can be employed in a baggage tracking system, e.g., at an airport.

FIG. **5** depicts a baggage tracking system **500** where a plurality of interrogators **520**, **530** and **540** are synchronized in accordance with the systems and methods described herein. In airport baggage tracking system **500**, the objective is to track the time and identity of each bag that passes by various checkpoints. To facilitate this objective, an RFID interrogator is placed at each checkpoint. Each bag is equipped with a baggage tag comprising an RFID tag. Upon the check-in, each bag is placed on some sort of conveyance mechanism, such as a conveyor belt. RFID tags **550**, **552**, **554**, **556**, **558**, **560**, **562** and **564** represent the RFID tags embedded in the baggage tags affixed on each bag. Each bag traverses the checkpoint monitored by interrogator **540**, then the checkpoint monitored by interrogator **530**, followed by the checkpoint monitored by interrogator **520**.

Interrogators **520**, **530**, and **540** are coupled together and to a synchronization master **510**, which is responsible for synchronizing the interrogators. In this embodiment, the coupling is accomplished through wiring **514**. As depicted in FIG. **5**, synchronization master **510** can be a simple pulse generator; however, in other embodiments one of interrogators **520**, **530**, and **540** can serve as a synchronization master. The master transmits, e.g., master **510** can be configured to transmit a pulse train **512** to each of interrogators **520**, **530** and **540**. Interrogators **520**, **530**, and **540** can be configured, upon receiving the synchronization pulse, to transmit through antennas, **522**, **532**, and **542**, respectively, a radio signal **524**, **534**, and **544**, respectively, to interrogate passing RFID tags **550-564**. Signals **524**, **534**, and **544** can be synchronization pulses or can carry information, e.g., using the exemplary communication protocols illustrated in FIG. **2**.

FIG. **6** illustrates an example of the signals and synchronization pulses transmitted by interrogators **520**, **530**, and **540**. Graph **610** depicts synchronization pulse train **512**. Graph **620**, **630**, and **640** depict the signal outputs of interrogators **520**, **530**, and **540**, respectively. In some implementations, the start **602** of the RF frames **604** do not correspond precisely with the leading edges of the pulses in

graph **610**, because there can be some propagation delay in the circuitry associated with interrogators **520**, **530**, and **540**. A certain amount of inconsistency in the delay can be tolerated, because responses to interrogation signals are expected in the second half of the frame. As explained in detail below, each interrogator can transmit different signals without interfering with other interrogator's ability to receive RFID tag responses because regardless of the type of signal, all transmissions by all interrogators are concluded by the start of the second half of the frame **604** as illustrated by dashed lines **606**.

Thus, RFID interrogators **520**, **530**, and **540** can be coupled to a synchronization master **510** configured to synchronize transmissions from the interrogators; however, in the event of a failure associated with synchronization master **510**, system **500** can lose its ability to synchronize the signals of interrogators **520**, **530**, and **540**. In one embodiment, this is avoided by enabling one of the remaining interrogators to become the synchronization master. Accordingly, when employing such a cooperative strategy, an interrogator can be in one of two states a synchronization master or a synchronization slave. Thus, one or more of the interrogators in a system configured to implement such a cooperative strategy must be able to both send and receive a synchronization signal.

FIG. **7** is a diagram illustrating a temporal view of signals generated in a system employing such a cooperative strategy. In this example, each interrogator in the system is capable of both sending and receiving an interrogator signal. The system begins with an interrogator, or alternatively a signal generator, as a synchronization master configured to generate a synchronization signal as described above and illustrated in graph **710**. In this particular embodiment, there are three slave interrogators whose radio frame synchronization signals are depicted in graphs **720**, **730** and **740** and whose synchronization signals are depicted in graphs **725**, **735**, and **745**. At **750**, the synchronization master suffers a failure and ceases to generate the synchronization signal.

If just one of the interrogators in the system is capable of taking over as master, which is possible depending on the embodiment, then that interrogator will be promoted to master upon detecting the failure of the original synchronization master.

Such configurations can be sufficient to avoid synchronization failures; however, a potential drawback to such configurations is that there is no mechanism to ensure synchronization should one promoted interrogator subsequently fail, fails to generate of synchronization signal, or fails to be promoted. Thus, it can be preferable, depending on the implementation, for a plurality of interrogators to be capable of promotion to master. In such embodiments, there must be some mechanism for determining which interrogator will become the next master.

In one embodiment, the interrogators do not recognize an outage until a predetermined period of time has expired at **752**. From there each interrogator selects a random period of time to wait before it attempts to become the new synchronization master. Here, the first interrogator selects the interval between **752** and **754**. The second interrogator selects the interval between **752** and **756**, which happens to be a longer interval. The third interrogator happens to randomly pick the interval between **752** and **754**, the same as the first interrogator. These wait intervals should be large compared to the frame period. In another embodiment, each interrogator at some point in its normal process can select a random time out period before registering a failure of the master. To use the same example, the period would be that between **750** and

754 for the first interrogator, between 750 and 756 for the second interrogator, and between 750 and 754 for the third interrogator.

Each interrogator can be configured to send a pulse after the associated wait period to the other interrogators indicating its attempt to become the master. The other interrogators, upon receiving the pulse, can be configured to remain slaves. The new synchronization master can then send its synchronization signal to the other interrogators. A conflict can arise in the unlikely event that two or more interrogators pulse at the same time, which would be the case in the example above. In other embodiments, various schemes can be used to avoid such conflicts, or contentions. For example, in some embodiments, collision avoidance schemes can be used. Factors such as skew in the docks of each interrogator can eventually lead to a dispersion of the pulses generated. At this point, one of the interrogators will be seen as pulsing first relative to the others. This interrogator will then become the master and the others demoted to being slave interrogators. For example, at time 758, the pulse, generated by the third interrogator begins to trail those of the first interrogator. The third interrogator can be configured to detect that it is no longer the master, and cease to generate synchronization pulses at time 760.

FIG. 8 illustrates a flowchart illustrating an example method for interrogator promotion in accordance with the systems and methods. Wait states 810 and 850 represent the general waiting states for an interrogator in the slave state and in the master states, respectively. For example, most interrogators start in wait state 810. They can transition out of wait state 810 to step 812 if either a synchronization pulse is received from another interrogator or a predetermined period of time has elapsed since a synchronization pulse from a master was expected. This predetermined period is typically much larger than the frame period. If a synchronization pulse is detected, the interrogator remains a slave and can perform its regular duties by sending either a frame synchronization pulse or data to an RFID tag at step 820, and if appropriate, it can listen for RFID tag responses at step 822. Upon completion of the frame, the interrogator returns to wait state 810. On the other hand, if a synchronization pulse from a master has not been detected, at step 814, a timeout interval is selected, e.g., randomly generated as described above, the timeout interval can be with a predetermined range, which is typically many times the frame period. The interrogator then waits at step 816 for either this timeout period to expire or for a synchronization pulse from another interrogator.

If a synchronization pulse is received at step 818, the interrogator remains a slave and can continue to perform its regular duties starting at step 820; however, if the timeout expires then the interrogator attempts to become a master at step 854 by transmitting a synchronization pulse to all the other interrogators. It then can continue to perform its regular duties by sending either a frame synchronization pulse or data to an RFID tag at step 856 and then if appropriate, it can listen for RFID tag responses at step 858. Upon completion of its regular duties, the interrogator returns to wait state 850. In wait state 850, the interrogator waits for either the start of the next frame, which is one frame period after it sent the last synchronization pulse to the other interrogators, or for a synchronization pulse from another interrogator.

In step 852, if the interrogator detects a start of frame, it transmits a synchronization pulse to the other interrogators in step 854 and the process repeats as before. But if the interrogator detects another synchronization from another

interrogator, it ceases to be, a master, becomes a slave, and resumes slave duties at step 820. This can occur, for example, where the original master whose failure initiated the promotion from slave to master of steps 814-854 comes back online. This can also occur if during the promotion from slave to master one or more other interrogators waited the same random interval and were simultaneously promoted to master and over time, the internal clocks of the interrogators are skewed resulting in slight deviations in the pulse interval.

Though extremely unlikely, there may be a situation where three or more interrogators claim to be masters. Thus, in certain embodiments, each interrogator can be configured to determine under such circumstances that one of the other interrogators is the rightful master, which will cause each interrogator to switch to a slave state. At this point, no synchronization pulses are sent by any interrogator and the process for each interrogator follows the diagram in FIG. 8 by traversing steps 812, 814, 816 and 818. At which point, a new master is selected. Alternatively, skewing that results from differences in the tolerances and errors associated with the circuitry of each interrogator can be relied on to eventually result in one interrogator being promoted over the others as described above. Obviously, the more interrogators involved the longer such a process will take. Therefore, some alternatives as described above that reduces the delay involved can be preferable for selecting among three or more contending master interrogators.

It should be noted that in another embodiment, a random predetermined timeout greater than the predetermined "master timeout" and less than the sum of the "master timeout" and the "random timeout" range could be used in wait state 810, thereby combining steps 812, 814, 816, and 818 into a single branch point where the detection of a synchronization pulse transitions the interrogator to step 820 and the expiration of this new predetermined timeout promotes the interrogator to a master state by transitioning to step 854. Such a hybrid timeout period can be used, for example, when an interrogator changes master-slave state, when a new frame is detected, when the tenth new frame is detected, etc.

Though the above embodiments address the synchronization issues relating to the operation of multiple interrogators in a single theatre of operation, there are many applications where the wired approach described in the preceding examples is not feasible, e.g., where the RFID interrogators are mobile such as those mounted on a forklift in a warehouse tracking application, or those used as hand-held scanners in a shipment tracking application. Accordingly, one or more wireless communication links can be used to achieve synchronization. Any such wireless approach should provide an inefficient use of power and spectrum associated with the wireless communication channel or link. For instance, ideally a master interrogator should be as centrally located as possible; however, in mobile applications, the interrogators can move around in the theatre of operation. This can lead to inefficient use of power and spectrum since a master interrogator needs to generate sufficient power to be detected by even the most remote interrogator in the theatre of operation. But since it is an objective to mitigate interference between nearby interrogators, synchronization need only be enforced when interrogators are close enough to cause interference. Thus, in certain embodiments, interrogator synchronization is only employed when interference from other interrogators is detected.

FIG. 9 is a flowchart illustrating an example method for adjusting frame synchronization pulses, when interference is

detected, in accordance with the systems and methods described herein. In step **910**, the interrogator waits for the start of frame. In step **912**, the interrogator transmits its frame synchronization or data to nearby RFID tags at the start of the frame. The interrogator then waits, in step **914**, for the second half of the frame. At step **916**, the interrogator can attempt to detect any interference from other interrogators, while listening for RFID tag transmissions. If interference is detected at **918**, the interrogator delays, at step **920**, its start of next frame time to coincide with the start of frame it detected from another interrogator at **918**. If no interference is detected, the interrogator processes any RFID tag transmissions it may have received at step **922**. The process then repeats.

Basically, if two interrogators come close enough to interfere, the interrogator which is first to detect interference adjusts its frame synchronization timing to match the other interrogator. Because, they are out of sync, one interrogator will have to be first in detecting interference. The environment can become much more complicated if more than two interrogators are out of frame synchronization, but realistically that is unlikely, since the frame periods are typically on the order of microseconds and physical movements take a much longer time, so by the time a third interrogator is out of sync with the first two, those two should have synchronized.

There are many methods of distinguishing interrogation interference with RFID tag transmissions. Most of these methods involve incorporating certain patterns in the transmission protocol.

FIG. **10** illustrates a specific embodiment of such an encoding. Graph **1010** shows an interrogator's frame synchronization pulses. An RFID tag can transmit a "one" by sending a pulse in response in the second half of a first frame and no pulse in a second frame as depicted in graph **1030** and a "zero" by sending a no pulse in a first frame and a pulse in the second half of a second frame as depicted in graph **1040**. In the event of no pulse as in graph **1020**, there is no response from an RFID tag. In the event of a pulse in the second half frame of both a first and second frame, as in graph **1050**, interference from another RFID interrogator can be deduced. More complex patterns in RFID tags transmissions can be implemented, but often these complexities lead to many more false readings.

FIG. **11** is a flowchart illustrating an example method for synchronization that can alleviate some of the confusion associated with detecting interference. In the example of FIG. **11**, interrogators only attempt synchronization when not expecting RFID tag transmissions. In a practical system, RFID interrogators spend much of their time sending frame synchronization pulses, but not expecting a return transmission. In step **1110**, the interrogator waits for its internal clock to indicate a start of frame. In step **1112**, the interrogator decides if it has a pending transaction with an RFID tag, if so, at step **1114**, it decides whether it is waiting on a random count due to the detection of interference from a previous iteration. If so or if there is no pending transaction, the interrogator transmits a frame synchronization pulse at step **1116**. Otherwise, if there is a pending transaction and the interrogator is not waiting a random count or that count has expired hence no longer waiting, it transmits its data at step **1118**. The interrogator then waits for the second half of the frame at **1120**. At step **1122**, the interrogator can attempt to detect any interference from other interrogators, while listening for RFID to transmissions.

If interference is detected at **1122**, the interrogator behaves differently depending on whether it is expecting

data from an RFID tag. If it is not expecting data at step **1124**, the interrogator delays, at step **1126**, its start of next frame time to coincide with the start of frame it detected from the interfering interrogator at **1122**. If it is expecting data, the interrogator selects a random number of frames to wait in step **1128**. If no interference is detected, the interrogator processes any RFID tag transmissions it may have received at step **1130**. The process then repeats. In the event multiple interrogators are attempting to interrogate at the same time, the random count gives an interval when none of the interrogators are expecting data to synchronize their respective frame synchronization pulses.

While certain embodiments of the inventions have been described above, it will be understood that the embodiments described are by way of example only. Accordingly, the inventions should not be limited based on the described embodiments. Rather, the scope of the inventions described herein should only be limited in light of the claims that follow when taken in conjunction with the above description and accompanying drawings.

The invention claimed is:

1. A radio frequency identification (RFID) interrogation system, comprising:

multiple RFID interrogators, wherein each of the multiple RFID interrogators is configured to transmit a plurality of synchronization pulses to surrounding RFID tags, and wherein the multiple RFID interrogators includes a first RFID interrogator, the first RFID interrogator is configured to:

transmit a synchronization to nearby RFID tags;

while listening for RFID tag transmissions in response to the synchronization pulse, detect any interference from another RFID interrogator among the multiple RFID interrogators; and

if an interference is detected from another RFID interrogator among the multiple RFID interrogators, determine if data is expected from a nearby RFID tag, and if no data is expected, synchronize a transmission of the next synchronization pulse with the next synchronization pulse of the another RFID interrogator;

if interference is not detected from another RFID interrogator, wait for the expected data from the nearby RFID tag.

2. The RFID interrogation system of claim **1**, the first RFID interrogator detects interference from another RFID interrogator when;

a pulse is detected in the second half of a first frame and a pulse is detected in a second half of a second frame; and

the first frame occurs immediately before the second frame.

3. The RFID interrogation system of claim **1**, wherein if no interference is detected, the first RFID interrogator is configured to process any RFID tag transmission received during a second half of a frame.

4. The RFID interrogation system of claim **1**, wherein while synchronizing the transmission of the next synchronization pulse, the first RFID interrogator is configured to delay the transmission of the next synchronization pulse so that the start of the next synchronization pulse of the first RFID interrogator coincides with the start of the next synchronization pulse of the another RFID interrogator.

5. The RFID interrogation system of claim **1**, wherein while waiting for the expected data from the nearby RFID tag, the first RFID interrogator is configured to wait a random number of synchronization pulse periods.

11

6. The RFID interrogation system of claim 1, wherein the first and the another RFID interrogators are wirelessly coupled to each other.

7. The RFID interrogation system of claim 1, wherein the another RFID interrogator moves into a wireless detection range of the first RFID interrogator.

8. The RFID interrogation system of claim 1, wherein at least one of the first RFID interrogator and the another RFID interrogator is a mobile RFID interrogator.

9. The RFID interrogation system of claim 1, wherein the first RFID interrogator is a mobile RFID interrogator mounted on a forklift for warehouse tracking.

10. The RFID interrogation system of claim 1, wherein the first RFID interrogator is configured in form of a hand-held scanner for shipment tracking.

11. A method for operating a first radio frequency identification (RFID) interrogator among multiple RFID interrogators while avoiding interferences with other RFID interrogators among the multiple RFID interrogators, comprising:

transmitting a synchronization pulse by the first RFID interrogator to surrounding RFID tags;

while listening for RFID tag transmissions in response to the synchronization pulse, detecting any interference from another RFID interrogator among the multiple RFID interrogators;

if an interference is detected from another RFID interrogator among the multiple RFID interrogators, determining if data is expected from a nearby RFID tag, and if no data is expected, synchronizing a transmission of the next synchronization pulse of the first RFID interrogator with the next synchronization pulse of the another RFID interrogator;

if interference is not detected from another RFID interrogator, waiting for the expected data from the nearby RFID tag.

12

12. The method of claim 11, wherein detecting interference from another RFID interrogator includes: detecting a pulse in the second half of a first frame, detected a pulse in the second half of a second frame; and the first frame occurs immediately before the second frame.

13. The method of claim 11, wherein if no interference is detected, the method further comprises processing any RFID tag transmission received during a second half of a frame.

14. The method of claim 11, wherein synchronizing the transmission of the next synchronization pulse of the first RFID interrogator with the next synchronization pulse of the another RFID interrogator includes delaying the transmission of the next synchronization pulse of the first RFID interrogator so that the start of the next synchronization pulse of the first RFID interrogator coincides with the start of the next synchronization pulse of the another RFID interrogator.

15. The method of claim 11, wherein waiting for the expected data from the nearby RFID tag includes waiting for a random number of synchronization pulse periods.

16. The method of claim 11, wherein the first and the another RFID interrogators are wirelessly coupled to each other.

17. The method of claim 11, wherein the another RFID interrogator moves into a wireless detection range of the first RFID interrogator.

18. The method of claim 11, wherein at least one of the first RFID interrogator and the another RFID interrogator is a mobile RFID interrogator.

19. The method of claim 11, wherein the first RFID interrogator is a mobile RFID interrogator mounted on a forklift for warehouse tracking.

20. The method of claim 11, wherein the first RFID interrogator is used as a hand-held scanner for shipment tracking.

* * * * *